



US00RE45099E

(19) **United States**
(12) **Reissued Patent**
Schetky et al.

(10) **Patent Number:** **US RE45,099 E**
(45) **Date of Reissued Patent:** ***Sep. 2, 2014**

(54) **EXPANDABLE TUBING AND METHOD**

(56)

References Cited

(75) Inventors: **L. McDonald Schetky**, Camden, ME (US); **Craig D. Johnson**, Montgomery, TX (US); **Matthew R. Hackworth**, Pearland, TX (US); **Patrick W. Bixenman**, Houston, TX (US); **Peter Besselink**, Enschede (NL)

U.S. PATENT DOCUMENTS

| | | |
|-------------|--------|---------|
| 261,252 A | 7/1882 | Olmsted |
| 380,419 A | 4/1888 | Bignall |
| 997,191 A | 7/1911 | Hogarth |
| 1,135,809 A | 4/1915 | Jones |
| 1,229,437 A | 6/1917 | Foster |
| 1,233,888 A | 7/1917 | Leonard |
| 1,276,213 A | 8/1918 | Hare |
| 1,301,285 A | 4/1919 | Leonard |

(73) Assignee: **Halliburton Energy Services, Inc.**, Houston, TX (US)

(Continued)

(*) Notice: This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **12/872,220**

| | | |
|----|------------|--------|
| AU | 784777 | 8/2002 |
| AU | 2006202182 | 6/2006 |

(22) Filed: **Aug. 31, 2010**

(Continued)

Related U.S. Patent Documents

OTHER PUBLICATIONS

Reissue of:

(64) Patent No.: **7,185,709**
Issued: **Mar. 6, 2007**
Appl. No.: **10/806,509**
Filed: **Mar. 23, 2004**

Gravel Pack Systems: Mini-Beta Gravel Pack System, Baker Oil Tools, pp. 12-13, (Undated).

(Continued)

U.S. Applications:

(63) Continuation of application No. 09/973,442, filed on Oct. 9, 2001, now Pat. No. 6,799,637.
(60) Provisional application No. 60/242,276, filed on Oct. 20, 2000, provisional application No. 60/263,941, filed on Jan. 24, 2001.

Primary Examiner — William P Neuder

(74) *Attorney, Agent, or Firm* — McDermott Will & Emery LLP; John W. Wustenberg

(51) **Int. Cl.**
E21B 43/10 (2006.01)


(52) **U.S. Cl.**
USPC **166/380**; 166/207

(58) **Field of Classification Search**
USPC 166/380, 382, 207, 227
See application file for complete search history.

(57) **ABSTRACT**

An apparatus suitable for use in a wellbore comprises an expandable bistable device. An exemplary device has a plurality of bistable cells formed into a tubular shape. Each bistable cell comprises at least two elongated members that are connected to each other at their ends. The device is stable in a first configuration and a second configuration.

22 Claims, 17 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | |
|-------------|---------|---------------------|-------------|---------|--------------------|
| 1,314,600 A | 9/1919 | McCakey | 4,783,995 A | 11/1988 | Michel |
| 1,647,907 A | 11/1927 | Doty | 4,809,792 A | 3/1989 | Lynch |
| 1,945,079 A | 1/1934 | Riemenschneider | 4,832,121 A | 5/1989 | Anderson |
| 1,981,525 A | 11/1934 | Price | 4,866,062 A | 9/1989 | Toth |
| 2,016,683 A | 10/1935 | Moore | 4,874,327 A | 10/1989 | Ip |
| 2,050,128 A | 8/1936 | Schlumberger | 4,886,062 A | 12/1989 | Wiktor |
| 2,171,840 A | 9/1939 | Armentrout | 4,945,991 A | 8/1990 | Jones |
| 2,217,708 A | 10/1940 | Scaramucci | 4,950,258 A | 8/1990 | Kawai |
| 2,220,205 A | 11/1940 | Buckley | 4,969,890 A | 11/1990 | Sugita |
| 2,371,385 A | 3/1945 | Eckel | 4,976,142 A | 12/1990 | Perales |
| 2,530,966 A | 11/1950 | Huber | 4,990,155 A | 2/1991 | Wilkoff |
| 2,677,466 A | 5/1954 | Lowe | 4,994,071 A | 2/1991 | MacGregor |
| 2,696,169 A | 12/1954 | Lassiter | 5,102,417 A | 4/1992 | Palmaz |
| 2,760,581 A | 8/1956 | Johnston | 5,104,404 A | 4/1992 | Wolff |
| 2,769,655 A | 11/1956 | Holmes | 5,107,927 A | 4/1992 | Whiteley |
| 2,812,025 A | 11/1957 | Teague et al. | 5,119,373 A | 6/1992 | Fredricsson |
| 2,835,328 A | 5/1958 | Thompson | 5,141,360 A | 8/1992 | Zeman |
| 2,990,017 A | 6/1961 | Powers | 5,147,370 A | 9/1992 | McNamara |
| 3,069,125 A | 12/1962 | Hewitt | 5,156,220 A | 10/1992 | Forehand |
| 3,179,168 A | 4/1965 | Vincent | 5,163,321 A | 11/1992 | Perales |
| 3,203,451 A | 8/1965 | Vincent | 5,174,379 A | 12/1992 | Whiteley |
| 3,253,842 A | 5/1966 | Rabe | 5,186,255 A | 2/1993 | Corey |
| 3,297,092 A | 1/1967 | Jennings | 5,192,307 A | 3/1993 | Wall |
| 3,353,599 A | 11/1967 | Swift | 5,195,984 A | 3/1993 | Schatz |
| 3,358,492 A | 12/1967 | Richter | 5,197,978 A | 3/1993 | Hess |
| 3,389,752 A | 6/1968 | Lebourg | 5,211,241 A | 5/1993 | Mashaw, Jr. et al. |
| 3,414,055 A | 12/1968 | Vogt | 5,226,913 A | 7/1993 | Pinchuk |
| 3,415,321 A | 12/1968 | Venghiattis | 5,234,448 A | 8/1993 | Wholey |
| 3,419,080 A | 12/1968 | Lebourg | 5,243,190 A | 9/1993 | Bandy |
| 3,463,247 A | 8/1969 | Klein | 5,282,823 A | 2/1994 | Schwartz |
| 3,482,629 A | 12/1969 | Suman | 5,318,121 A | 6/1994 | Brockman |
| 3,489,220 A | 1/1970 | Kinley | 5,329,998 A | 7/1994 | King |
| 3,507,340 A | 4/1970 | Voetter | 5,337,823 A | 8/1994 | Nobileau |
| 3,508,587 A | 4/1970 | Mauch | 5,348,095 A | 9/1994 | Worrall et al. |
| 3,556,219 A | 1/1971 | Meldau | 5,354,308 A | 10/1994 | Simon |
| 3,561,529 A | 2/1971 | Owen | 5,355,948 A | 10/1994 | Sparlin |
| 3,604,732 A | 9/1971 | Malone | 5,355,949 A | 10/1994 | Sparlin |
| 3,657,744 A | 4/1972 | Ersek | 5,355,953 A | 10/1994 | Shy |
| 3,672,705 A | 6/1972 | Rush | 5,366,012 A | 11/1994 | Lohbeck |
| 3,692,114 A | 9/1972 | Murphey, Jr. et al. | 5,377,104 A | 12/1994 | Sorrells |
| 3,785,193 A | 1/1974 | Kinley | 5,377,823 A | 1/1995 | Steen et al. |
| 3,816,894 A | 6/1974 | Howard | 5,383,892 A | 1/1995 | Cardon |
| 3,864,970 A | 2/1975 | Bell | 5,383,926 A | 1/1995 | Lock |
| 3,898,717 A | 8/1975 | Schwartz | 5,396,957 A | 3/1995 | Surjaatmadja |
| 3,913,676 A | 10/1975 | Barbee, Jr. et al. | 5,397,355 A | 3/1995 | Marin |
| 3,926,409 A | 12/1975 | Abney | 5,403,341 A | 4/1995 | Solar |
| 3,963,076 A | 6/1976 | Winslow | 5,411,507 A | 5/1995 | Heckele |
| 4,064,938 A | 12/1977 | Fast | 5,419,760 A | 5/1995 | Narciso, Jr. |
| 4,065,953 A | 1/1978 | Frentzen | 5,449,373 A | 9/1995 | Pinchasik |
| 4,185,856 A | 1/1980 | McCaskill | 5,449,382 A | 9/1995 | Dayton |
| 4,253,522 A | 3/1981 | Setterberg, Jr. | 5,450,898 A | 9/1995 | Sparlin |
| 4,295,527 A | 10/1981 | Russe | 5,456,319 A | 10/1995 | Schmidt |
| 4,309,891 A | 1/1982 | Pogonowski | 5,492,175 A | 2/1996 | El-Rabaa et al. |
| 4,337,969 A | 7/1982 | Escaron | 5,496,365 A | 3/1996 | Sgro |
| 4,375,164 A | 3/1983 | Dodge | 5,500,013 A | 3/1996 | Buscemi |
| 4,401,158 A | 8/1983 | Spencer | 5,515,915 A | 5/1996 | Jones |
| 4,495,997 A | 1/1985 | Scott | 5,545,208 A | 8/1996 | Wolff |
| 4,541,486 A | 9/1985 | Wetzel | 5,545,210 A | 8/1996 | Hess |
| 4,553,595 A | 11/1985 | Huang | 5,554,183 A | 9/1996 | Nazari |
| 4,558,219 A | 12/1985 | LeBlanc | 5,556,413 A | 9/1996 | Lam |
| 4,558,742 A | 12/1985 | Huang | 5,562,690 A | 10/1996 | Green |
| 4,566,538 A | 1/1986 | Peterson | 5,562,697 A | 10/1996 | Christiansen |
| 4,578,608 A | 3/1986 | Mech | 5,576,485 A | 11/1996 | Serata |
| 4,580,568 A | 4/1986 | Gianturco | 5,601,593 A | 2/1997 | Freitag |
| 4,600,037 A | 7/1986 | Hatten | 5,618,299 A | 4/1997 | Khosravi |
| 4,606,408 A | 8/1986 | Zunkel | 5,628,787 A | 5/1997 | Mayer |
| 4,626,129 A | 12/1986 | Kothmann | 5,641,023 A | 6/1997 | Ross |
| 4,655,771 A | 4/1987 | Wallsten | 5,643,314 A | 7/1997 | Carpenter |
| 4,657,079 A | 4/1987 | Nagaoka | 5,663,805 A | 9/1997 | Asai |
| 4,665,906 A | 5/1987 | Jervis | 5,667,011 A | 9/1997 | Gill et al. |
| 4,665,918 A | 5/1987 | Garza | 5,670,161 A | 9/1997 | Healy |
| 4,706,659 A | 11/1987 | Matthews | 5,670,161 A | 12/1997 | Fischell |
| 4,733,665 A | 3/1988 | Palmaz | 5,695,516 A | 12/1997 | Fischell |
| 4,739,762 A | 4/1988 | Palmaz | 5,697,971 A | 12/1997 | Berry |
| 4,740,207 A | 4/1988 | Kreamer | 5,702,419 A | 12/1997 | Berry |
| | | | 5,723,781 A | 3/1998 | Pruett |
| | | | 5,725,570 A | 3/1998 | Heath |
| | | | 5,725,572 A | 3/1998 | Lam |
| | | | 5,733,303 A | 3/1998 | Israel |
| | | | 5,755,774 A | 5/1998 | Pinchuk |

(56)

References Cited

U.S. PATENT DOCUMENTS

7,048,052 B2 5/2006 Hackworth
 7,055,609 B2 6/2006 Hayes
 7,086,476 B2 8/2006 Johnson
 7,100,690 B2 9/2006 Mullen
 7,104,324 B2 9/2006 Wetzel
 7,108,062 B2 9/2006 Castano-Mears et al.
 7,131,494 B2 11/2006 Bixenman
 7,134,501 B2 11/2006 Johnson
 7,140,446 B2 11/2006 Metcalfe
 7,156,180 B2 1/2007 Schetky
 7,168,485 B2 1/2007 Johnson
 7,168,486 B2 1/2007 Hackworth
 7,182,134 B2 2/2007 Wetzel
 7,185,709 B2 3/2007 Schetky
 7,191,842 B2 3/2007 Hackworth
 7,222,676 B2 5/2007 Patel
 7,235,097 B2 6/2007 Calisse
 7,291,166 B2 11/2007 Cheng
 7,300,458 B2 11/2007 Henkes
 7,398,831 B2 7/2008 Schetky
 7,476,245 B2 1/2009 Abbate
 7,681,640 B2 3/2010 Bixenman
 7,758,628 B2 7/2010 Besselink
 2001/0027339 A1 10/2001 Boatman
 2001/0044652 A1 11/2001 Moore
 2002/0035394 A1* 3/2002 Fierens et al. 623/1.13
 2002/0092649 A1* 7/2002 Bixenman et al. 166/278
 2002/0107562 A1 8/2002 Hart
 2002/0125009 A1 9/2002 Wetzel
 2003/0074052 A1* 4/2003 Besselink 623/1.15
 2003/0079885 A1 5/2003 Schetky
 2003/0079886 A1 5/2003 Schetky
 2003/0199969 A1 10/2003 Steinke
 2004/0034402 A1 2/2004 Bales
 2004/0065445 A1 4/2004 Abercrombie Simpson et al.
 2004/0088043 A1 5/2004 Klein
 2004/0089454 A1 5/2004 Hackworth
 2004/0133270 A1 7/2004 Grandt
 2004/0182581 A1* 9/2004 Schetky et al. 166/380
 2004/0193247 A1 9/2004 Besselink
 2005/0039927 A1 2/2005 Wetzel
 2005/0055080 A1 3/2005 Istephanous
 2005/0163821 A1 7/2005 Sung
 2005/0182479 A1 8/2005 Bonsignore
 2006/0037745 A1 2/2006 Hart
 2006/0217795 A1 9/2006 Besselink
 2006/0241739 A1 10/2006 Besselink
 2007/0084608 A1 4/2007 Bixenman
 2007/0102153 A1 5/2007 Bixenman
 2008/0097571 A1 4/2008 Denison
 2009/0187243 A1 7/2009 Johnson

FOREIGN PATENT DOCUMENTS

AU 2006202182 A1 6/2006
 BE 1014914AS 6/2004
 CA 2602435 7/1998
 CA 2359450 4/2002
 CA 2359450 A1 4/2002
 CA 2513263 4/2002
 CA 2513263 A1 4/2002
 CA 2367810 7/2002
 CA 2367810 A1 7/2002
 CA 2544701 7/2002
 CA 2544701 A1 7/2002
 DE 8812719 11/1989
 DE 19728337 1/1999
 DE 10201631 11/2002
 DE 10201631 A1 11/2002
 EP 0274846 A1 7/1988
 EP 0326426 8/1989
 EP 0326462 A2 8/1989
 EP 0335341 A1 10/1989
 EP 0364787 4/1990

EP 0421729 4/1991
 EP 0540290 A2 5/1993
 EP 0587197 3/1994
 EP 0636345 2/1995
 EP 0664107 7/1995
 EP 0674095 9/1995
 EP 0679372 11/1995
 EP 0688545 12/1995
 EP 0734698 10/1996
 EP 0744164 11/1996
 EP 0779409 A1 6/1997
 EP 0897698 2/1999
 EP 1031329 A2 8/2000
 EP 1042997 10/2000
 EP 1152120 A2 11/2001
 EP 1223305 7/2002
 EP 1223305 A3 11/2002
 EP 1255022 A1 11/2002
 FR 2617721 A1 1/1989
 FR 2642812 8/1990
 GB 2081173 2/1982
 GB 2169515 7/1986
 GB 2175824 A 12/1986
 GB 2287093 A 9/1995
 GB 2317630 4/1998
 GB 2347448 9/2000
 GB 2355740 5/2001
 GB 2362462 A 11/2001
 GB 2366817 3/2002
 GB 2368082 * 4/2002
 GB 2369382 A 4/2002
 GB 2369382 5/2002
 GB 2370301 6/2002
 GB 2370574 7/2002
 GB 2371063 A 7/2002
 GB 2371064 7/2002
 GB 2371066 7/2002
 GB 2371574 7/2002
 GB 2379690 3/2003
 GB 2379691 3/2003
 GB 2379692 3/2003
 GB 2379693 3/2003
 GB 2379694 3/2003
 GB 2379694 A 3/2003
 GB 2382831 6/2003
 GB 2382831 A 6/2003
 GB 2386625 9/2003
 GB 2386625 A 9/2003
 GB 2392461 3/2004
 GB 2392461 A 3/2004
 GB 2395214 5/2004
 GB 2395214 A 5/2004
 GB 2403491 1/2005
 GB 2404683 2/2005
 GB 2404683 A 2/2005
 GB 2408531 6/2005
 GB 2408531 A 6/2005
 GB 2409694 7/2005
 GB 2409694 A 7/2005
 GB 2410273 7/2005
 GB 2410273 A 7/2005
 JP A9312743 12/1997
 JP 2002121654 4/2002
 JP 3958602 11/2002
 JP 2002332791 11/2002
 NL 1019192 4/2002
 NL 1019753 7/2002
 NL 1021076 7/2002
 NL 1022037 2/2003
 NO 20020223 A 7/2002
 NO 20034598 A 4/2004
 RU 2225497 7/2003
 RU 2225497 C2 7/2003
 RU 2263198 5/2005
 SG 104956 7/2004
 SU 1105620 7/1984
 WO 8602124 4/1986
 WO 9206734 A1 4/1992
 WO 9219310 A1 11/1992

(56)

References Cited

FOREIGN PATENT DOCUMENTS

| | | | |
|----|----------------|----|---------|
| WO | 9322986 | | 11/1993 |
| WO | 9403127 | A1 | 2/1994 |
| WO | 9509584 | | 4/1995 |
| WO | 9531945 | | 11/1995 |
| WO | 9532757 | | 12/1995 |
| WO | 9603942 | | 2/1996 |
| WO | 9609013 | | 3/1996 |
| WO | 9618359 | | 6/1996 |
| WO | 9629028 | | 9/1996 |
| WO | 9637680 | | 11/1996 |
| WO | 9641589 | | 12/1996 |
| WO | 9704721 | | 2/1997 |
| WO | 9800626 | | 1/1998 |
| WO | 9820810 | | 5/1998 |
| WO | 9820810 | A1 | 5/1998 |
| WO | 9822690 | | 5/1998 |
| WO | 9826152 | | 6/1998 |
| WO | WO 98/32412 | | 7/1998 |
| WO | 9849423 | | 11/1998 |
| WO | 9849423 | A | 11/1998 |
| WO | 9850673 | | 11/1998 |
| WO | 9850680 | | 11/1998 |
| WO | 9857030 | | 12/1998 |
| WO | 9902818 | | 1/1999 |
| WO | 9915108 | A2 | 4/1999 |
| WO | 9923354 | | 5/1999 |
| WO | 9945235 | | 9/1999 |
| WO | 0036386 | A1 | 6/2000 |
| WO | 0061908 | | 10/2000 |
| WO | 0129368 | | 4/2001 |
| WO | 0129368 | A1 | 4/2001 |
| WO | 0142620 | | 6/2001 |
| WO | 0146551 | | 6/2001 |
| WO | 200142620 | | 6/2001 |
| WO | 0165063 | | 9/2001 |
| WO | 0165067 | | 9/2001 |
| WO | 0173264 | | 10/2001 |
| WO | 0188332 | A1 | 11/2001 |
| WO | 0192680 | | 12/2001 |
| WO | 0206593 | | 1/2002 |
| WO | 0206625 | | 1/2002 |
| WO | 0225057 | | 3/2002 |
| WO | 308384 | | 2/2004 |
| WO | 2004014255 | A1 | 2/2004 |
| WO | WO 2004/014255 | | 2/2004 |
| WO | 2007076051 | | 7/2007 |
| WO | 2007076051 | A3 | 7/2007 |
| WO | 2007126729 | | 11/2007 |
| WO | 2007126729 | A3 | 11/2007 |

OTHER PUBLICATIONS

Sides, Win, Hydraulic Intelligent Completions, Baker Hughes, Advanced Technology Conference, Sep. 30-Oct. 1, 1999, slides 1-28 (6446729).

STDZ and Multizone Completion Systems, Halliburton Company, 1995.

Hamid, Syed, Lester, G. Scott and Adkins, Darrel W.; A Fiber-Optic Inspection System for Prepacked Screens: Society of Petroleum Engineers Inc.: pp. 1-12. Apr. 1999.

U.S. Pre-Grant Pub 2003/0056947, Cameron, Mar. 2003. Hamid, Syed, Lester, G. Scott and Adkins, Darrell W.; A Fiber-Optic Inspection System for Prepacked Screens; Society of Petroleum Engineers Inc.; pp. 1-9, 1999.

Hackworth et al., Development and First Application of Bistable Expandable Sand Screen, Oct. 5-8, 2003, SPE 84265, whole document.

European Search Report dated Mar. 15, 2006 re EP 05 02 2622 (PARGN.002VR1 EP) in 4 pages.

European Search Report dated Jul. 21, 2008 re EP 05 02 2622 (PARGN.002VR1EP) in 4 pages.

Office Action for U.S. Appl. No. 12/872,178 dated Jul. 28, 2011.

Office Action for U.S. Appl. No. 12/872,154 dated Feb. 25, 2011.

Office Action for U.S. Appl. No. 12/872,178 dated Mar. 1, 2011.

Office Action for U.S. Appl. No. 12/872,203 dated Mar. 3, 2011.

Office Action for U.S. Appl. No. 12/872,203 dated Jul. 20, 2011.

Office Action for U.S. Appl. No. 12/872,154 dated Jul. 20, 2011.

Besselink, Peter, Biflex Stents; SMST-99; Proceedings of the First European Conference on Shape Memory and Superelastic Technologies, Antwerp Zoo, Belgium, 1999; pp. 142-150.

Docket Sheet for *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. H-04-1959 (S.D. Tex.) (PACER Jun. 2, 2005) (5 pages).

Docket Sheet for *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.) (PACER Aug. 11, 2005) (13 pages).

Communication from United States District Court Transferring Case, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. H-04-1959 (S.D. Tex.), dated Sep. 7, 2004 (1 page).

Plaintiffs' Original Complaint, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. H-04-1959, (S.D. Tex.), filed May 14, 2004 (20 pages).

Defendants' Motions (1) to Dismiss the Complaint for Insufficiency of Process and Lack of Personal Jurisdiction, (2) to Dismiss Counts I-III of the Complaint for Failure to State a Claim and (3) in the Alternative, to Transfer This Action to the Federal District Court for the Northern District of California, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. H-04-1959, (S.D. Tex.), filed Jul. 7, 2004 (49 pages).

Plaintiffs' First Amended Complaint, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Aug. 19, 2004 (20 pages).

Answer of Defendants and Counterclaims of Kentucky Oil Technology N.V. Against Memry Corporation and Schlumberger Technology Corporation, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.) filed Nov. 2, 2004 (20 pages).

Plaintiff and Counterdefendant Memry Corporation's Answer to Kentucky Oil Technology N.V.'s Counterclaims and Demand for Jury Trial, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843 (N.D. Cal.), filed Dec. 3, 2004 (10 pages).

Schlumberger Technology Corporation's Notice of Motion and Motion to Dismiss Kentucky Oil Technology's Third, Fourth, Fifth, and Sixth Counterclaims; and Memorandum of Points and Authorities, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Jan. 24, 2005 (32 pages).

[Proposed] Order Granting Schlumberger Technology Corporation's Motion to Dismiss Kentucky Oil Technology's Third, Fourth, Fifth, and Sixth Counterclaims. *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Jan. 24, 2005 (3 pages).

First Amended Counterclaims of Kentucky Oil Technology N.V. Against Memry Corporation and Schlumberger Technology Corporation, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Feb. 9, 2005 (16 pages).

Schlumberger Technology Corporation's Notice of Motion and Motion to Dismiss Kentucky Oil Technology's First Amended Third, Fourth, Fifth, and Sixth Counterclaims; and Memorandum of Points and Authorities, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Feb. 24, 2005 (32 pages).

Request for Judicial Notice in Support of Schlumberger Technology Corporation's Motion to Dismiss Kentucky Oil Technology's First Amended Third, Fourth, Fifth, and Sixth Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Feb. 24, 2005 (3 pages).

[Proposed] Order Granting Schlumberger Technology Corporation's Motion to Dismiss Kentucky Oil Technology's First Amended Third, Fourth, Fifth, and Sixth Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Feb. 24, 2005 (3 pages).

Plaintiff and Counterdefendant Memry Corporation's Notice of Motion and Motion to Dismiss Kentucky Oil Technology's Third, Fourth, Fifth, and Sixth Counterclaims; and Memorandum of Points and Authorities, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Feb. 25, 2005 (29 pages).

(56)

References Cited

OTHER PUBLICATIONS

Request for Judicial Notice in Support of Memry Corporation's Motion to Dismiss Kentucky Oil Technology's Third, Fourth, Fifth, and Sixth Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Feb. 25, 2005 (3 pages).

[Proposed] Order Granting Memry Corporation's Motion to Dismiss Kentucky Oil Technology's Third Fourth, Fifth, and Sixth Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Feb. 25, 2005 (3 pages).

Opposition of Kentucky Oil to Motions of Memry Corporation and Schlumberger Technology Corporation to Dismiss First Amended Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V. Case No. C-04-03843, (N.D. Cal.), filed Mar. 11, 2005 (29 pages).

Kentucky Oil's Opposition to Counterdefendants' Requests for Judicial Notice in Support of Their Motions to Dismiss Kentucky Oil Technology's First Amended Third, Fourth, Fifth, and Sixth Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 11, 2005 (3 pages).

Plaintiff and Counterdefendant Memry Corporation's Reply in Support of Motion to Dismiss Kentucky Oil Technology's Third, Fourth, Fifth, and Sixth Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 18, 2005 (9 pages).

Plaintiff and Counterdefendant Memry Corporation's Reply in Support of Request for Judicial Notice, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 18, 2005 (4 pages).

Reply of Schlumberger Technology Corporation to Kentucky Oil Technology's Opposition to First Amended, Third, Fourth, Fifth, and Sixth Counterclaims. *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 18, 2005 (17 pages).

Schlumberger's Reponse to Kentucky Oil's Opposition to Counterdefendants' Requests for Judicial Notice, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 18, 2005 (3 pages).

Schlumberger's Notice of Motion and Motion to Strike Exhibits 1, 2, and 4 to the Declaration of Nicola A. Pisano, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 18, 2005 (3 pages).

Kentucky Oil's Opposition to STC's Motion to Strike Exhibits 1, 3 and 4 to the Declaration of Nicola A. Pisano, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 25, 2005 (3 pages).

Kentucky Oil's Notice of Motion and Motion to Strike Declaration of Benjamin Holl and Portions of Counterdefendants' Reply Briefs, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Mar. 25, 2005 (4 pages).

[Proposed] Order Granting Kentucky Oil's Motion to Strike Declaration of Benjamin Holl and Portions of Counterdefendants' Reply Briefs, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), entered Mar. 25, 2005 (2 pages).

Order Granting in Part and Denying in Part Counterdefendants' Motion to Dismiss, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), entered Apr. 8, 2005 (26 pages).

Plaintiff and Counterdefendant Memry Corporation's Reply to Kentucky Oil Technology N.V.'s Counterclaims and Demand for Jury Trial, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Apr. 18, 2005 (8 pages).

Second Amended Counterclaims of Kentucky Oil Technology N.V. Against Memry Corporation and Schlumberger Technology Corporation, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed May 6, 2005 (20 pages).

Plaintiff Memry Corporation's Reply to Kentucky Oil Technology N.V.'s Second Amended Counterclaims and Demand for Jury Trial, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Jun. 3, 2005 (9 pages).

Schlumberger Technology Corporation's Notice of Motion and Motion to Dismiss the Fourth, Fifth, Sixth, Seventh, and Eighth Counterclaims in Kentucky Oil Technology's Second Amended Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Jun. 3, 2005 (18 pages).

Opposition of Kentucky Oil Technology to Schlumberger Technology Corporation's Motion to Dismiss Kentucky Oil's Second Amended Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Jun. 17, 2005 (16 pages).

Schlumberger Technology Corporation's Reply Brief in Support of its Motion to Dismiss the Fourth, Fifth, Sixth, Seventh, and Eighth Counterclaims in Kentucky Oil Technology's Second Amended Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Jun. 24, 2005 (11 pages).

Order Granting in Part and Denying in Part STC's Motion to Dismiss, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), entered Jul. 14, 2005 (8 pages).

Schlumberger Technology Corporation's Answer to Kentucky Oil Technology's Second Amended Counterclaims, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Jul. 28, 2005 (8 pages).

Notice of Motion and Motion by Kentucky Oil To Compel Production of Documents by Schlumberger Technology Corporation Pursuant to Fed. R. Civ. Rule 37; Memorandum of Points and Authorities in Support Thereof; Declaration of Michael Bierman, *Memry Corporation v. Kentucky Oil Technology*, N.V. Case No. C-04-03843, (N.D. Cal.), filed Jul 28, 1005 (32 pages).

Schlumberger Technology Corporation's Opposition to Kentucky Oil Technology's Motion to Compel, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Aug. 4, 2005 (21 pages).

Declaration of David B. Moyer in Support of Schlumberger Technology Corporation's Opposition to Kentucky Oil Technology's Motion to Compel, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Aug. 4, 2005 (52 pages).

Kentucky Oil's Reply in Support of Motion to Compel, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Aug. 10, 2005 (18 pages).

Declaration of Nicola A. Pisano in Support of Kentucky Oil's Motion to Compel, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), filed Aug. 10, 2005 (69 pages).

Order Granting Kentucky Oil's Motion to Compel Production of Documents, *Memry Corporation v. Kentucky Oil Technology*, N.V., Case No. C-04-03843, (N.D. Cal.), entered Aug. 17, 2005 (8 pages).

US 6,706,063, 03/2004, Besselink (withdrawn)

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 4A




FIG. 4B




FIG. 4C

FIG. 4D




FIG. 5A

FIG. 5B




FIG. 6A

FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D





FIG. 9A




FIG. 9B







FIG. 10A

FIG. 10B




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 15





FIG. 15A






FIG. 17A




FIG. 17B




FIG. 18

EXPANDABLE TUBING AND METHOD

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS REFERENCE TO RELATED APPLICATIONS

The following is a continuation based on and claims the priority of patent application Ser. No. 09/973,442, filed Oct. 9, 2001, now U.S. Pat. No. 6,799,637 which was based on and claimed the priority of provisional application No. 60/242,276, filed Oct. 20, 2000 and provisional application No. 60/263,941, filed Jan. 24, 2001.

FIELD OF THE INVENTION

This invention relates to equipment that can be used in the drilling and completion of wellbores in an underground formation and in the production of fluids from such wells.

BACKGROUND OF THE INVENTION

Fluids such as oil, natural gas and water are obtained from a subterranean geologic formation (a "reservoir") by drilling a well that penetrates the fluid-bearing formation. Once the well has been drilled to a certain depth the borehole wall must be supported to prevent collapse. Conventional well drilling methods involve the installation of a casing string and cementing between the casing and the borehole to provide support for the borehole structure. After cementing a casing string in place, the drilling to greater depths can commence. After each subsequent casing string is installed, the next drill bit must pass through the inner diameter of the casing. In this manner each change in casing requires a reduction in the borehole diameter. This repeated reduction in the borehole diameter creates a need for very large initial borehole diameters to permit a reasonable pipe diameter at the depth where the wellbore penetrates the producing formation. The need for larger boreholes and multiple casing strings results in more time, material and expense being used than if a uniform size borehole could be drilled from the surface to the producing formation.

Various methods have been developed to stabilize or complete uncased boreholes. U.S. Pat. No. 5,348,095 to Worrall et al. discloses a method involving the radial expansion of a casing string to a configuration with a larger diameter. Very large forces are needed to impart the radial deformation desired in this method. In an effort to decrease the forces needed to expand the casing string, methods that involve expanding a liner that has longitudinal slots cut into it have been proposed (U.S. Pat. Nos. 5,366,012 and 5,667,011). These methods involve the radial deformation of the slotted liner into a configuration with an increased diameter by running an expansion mandrel through the slotted liner. These methods still require significant amounts of force to be applied throughout the entire length of the slotted liner.

A problem sometimes encountered while drilling a well is the loss of drilling fluids into subterranean zones. The loss of drilling fluids usually leads to increased expenses but can result in a borehole collapse and a costly "fishing" job to recover the drill string or other tools that were in the well.

Various additives are commonly used within the drilling fluids to help seal off loss circulation zones, such as cottonseed hulls or synthetic fibers.

Once a well is put in production an influx of sand from the producing formation can lead to undesired fill within the wellbore and can damage valves and other production related equipment. Many methods have been attempted for sand control.

The present invention is directed to overcoming, or at least reducing the effects of one or more of the problems set forth above, and can be useful in other applications as well.

SUMMARY OF THE INVENTION

According to the present invention, a technique is provided for use of an expandable bistable device in a borehole. The bistable device is stable in a first contracted configuration and a second expanded configuration. An exemplary device is generally tubular, having a larger diameter in the expanded configuration than in the contracted configuration. The technique also may utilize a conveyance mechanism able to transport the bistable device to a location in a subterranean borehole. Furthermore, the bistable device can be constructed in various configurations for a variety of applications.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will hereafter be described with reference to the accompanying drawings, wherein like reference numerals denote like elements, and:

FIGS. 1A and 1B are illustrations of the forces imposed to make a bistable structure;

FIG. 2A and 2B show force-deflection curves of two bistable structures;

FIGS. 3A-3F illustrate expanded and collapsed states of three bistable cells with various thickness ratios;

FIGS. 4A and 4B illustrate a bistable expandable tubular in its expanded and collapsed states;

FIGS. 4C and 4D illustrate a bistable expandable tubular in collapsed and expanded states within a wellbore;

FIGS. 5A and 5B illustrate an expandable packer type of deployment device;

FIGS. 6A and 6B illustrate a mechanical packer type of deployment device;

FIGS. 7A-7D illustrate an expandable swage type of deployment device;

FIGS. 8A-8D illustrate a piston type of deployment device;

FIGS. 9A and 9B illustrate a plug type of deployment device;

FIGS. 10A and 10B illustrate a ball type of deployment device;

FIG. 11 is a schematic of a wellbore utilizing an expandable bistable tubular;

FIG. 12 illustrates a motor driven radial roller deployment device; and

FIG. 13 illustrates a hydraulically driven radial roller deployment device.

FIG. 14 illustrates a bistable expandable tubular having a wrapping;

FIG. 14A is a view similar to FIG. 14 in which the wrapping comprises a screen;

FIG. 14B is a view similar to FIG. 14 showing another alternate embodiment;

FIG. 14C is a view similar to FIG. 14 showing another alternate embodiment;

FIG. 14D is a view similar to FIG. 14 showing another alternate embodiment;

3

FIG. 14E is a view similar to FIG. 14 showing another alternate embodiment;

FIG. 15 is a perspective view of an alternative embodiment of the present invention.

FIG. 15A is a cross-sectional view of an alternative embodiment of the present invention.

FIG. 16 is a partial perspective view of an alternative embodiment of the present invention.

FIGS. 17A-B are a partial perspective view and a partial cross-sectional end view respectively of an alternative embodiment of the present invention.

FIG. 18 is a partial cross-sectional end view of an alternative embodiment of the present invention.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and are herein described in detail. It should be understood, however, that the description herein of specific embodiments is not intended to limit the invention to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Bistable devices used in the present invention can take advantage of a principle illustrated in FIGS. 1A and 1B. FIG. 1A shows a rod 10 fixed at each end to rigid supports 12. If the rod 10 is subjected to an axial force it begins to deform as shown in FIG. 1B. As the axial force is increased rod 10 ultimately reaches its Euler buckling limit and deflects to one of the two stable positions shown as 14 and 15. If the buckled rod is now clamped in the buckled position, a force at right angles to the long axis can cause the rod to move to either of the stable positions but to no other position. When the rod is subjected to a lateral force it must move through an angle β before deflecting to its new stable position.

Bistable systems are characterized by a force deflection curve such as those shown in FIGS. 2A and 2B. The externally applied force 16 causes the rod 10 of FIG. 1B to move in the direction X and reaches a maximum 18 at the onset of shifting from one stable configuration to the other. Further deflection requires less force because the system now has a negative spring rate and when the force becomes zero the deflection to the second stable position is spontaneous.

The force deflection curve for this example is symmetrical and is illustrated in FIG. 2A. By introducing either a precurvature to the rod or an asymmetric cross section the force deflection curve can be made asymmetric as shown in FIG. 2B. In this system the force 19 required to cause the rod to assume one stable position is greater than the force 20 required to cause the reverse deflection. The force 20 must be greater than zero for the system to have bistable characteristics.

Bistable structures, sometimes referred to as toggle devices, have been used in industry for such devices as flexible discs, over center clamps, hold-down devices and quick release systems for tension cables (such as in sailboat rigging backstays).

Instead of using the rigid supports as shown in FIGS. 1A and 1B, a cell can be constructed where the restraint is provided by curved struts connected at each end as shown in FIGS. 3A-3F. If both struts 21 and 22 have the same thickness as shown in FIGS. 3A and 3B, the force deflection curve is linear and the cell lengthens when compressed from its open position FIG. 3B to its closed position FIG. 3A. If the cell

4

struts have different thicknesses, as shown in FIGS. 3C-3F, the cell has the force deflection characteristics shown in FIG. 2B, and does not change in length when it moves between its two stable positions. An expandable bistable tubular can thus be designed so that as the radial dimension expands, the axial length remains constant. In one example, if the thickness ratio is over approximately 2:1; the heavier strut resists longitudinal changes. By changing the ratio of thick-to-thin strut dimensions, the opening and closing forces can be changed. For example, FIGS. 3C and 3D illustrated a thickness ratio of approximately 3:1, and FIGS. 3E and 3F illustrate a thickness ratio of approximately 6:1.

An expandable bore bistable tubular, such as casing, a tube, a patch, or pipe, can be constructed with a series of circumferential bistable connected cells 23 as shown in FIGS. 4A and 4B, where each thin strut 21 is connected to a thick strut 22. The longitudinal flexibility of such a tubular can be modified by changing the length of the cells and by connecting each row of cells with a compliant link. Further, the force deflection characteristics and the longitudinal flexibility can also be altered by the design of the cell shape. FIG. 4A illustrates an expandable bistable tubular 24 in its expanded configuration while FIG. 4B illustrates the expandable bistable tubular 24 in its contracted or collapsed configuration. Within this application the term "collapsed" is used to identify the configuration of the bistable element or device in the stable state with the smallest diameter, it is not meant to imply that the element or device is damaged in any way. In the collapsed state, bistable tubular 24 is readily introduced into a wellbore 29, as illustrated in FIG. 4C. Upon placement of the bistable tubular 24 at a desired wellbore location, it is expanded, as illustrated in FIG. 4D.

The geometry of the bistable cells is such that the tubular cross-section can be expanded in the radial direction to increase the overall diameter of the tubular. As the tubular expands radially, the bistable cells deform elastically until a specific geometry is reached. At this point the bistable cells move, e.g. snap, to a final expanded geometry. With some materials and/or bistable cell designs, enough energy can be released in the elastic deformation of the cell (as each bistable cell snaps past the specific geometry) that the expanding cells are able to initiate the expansion of adjoining bistable cells past the critical bistable cell geometry. Depending on the deflection curves, a portion or even an entire length of bistable expandable tubular can be expanded from a single point.

In like manner if radial compressive forces are exerted on an expanded bistable tubular, it contracts radially and the bistable cells deform elastically until a critical geometry is reached. At this point the bistable cells snap to a final collapsed structure. In this way the expansion of the bistable tubular is reversible and repeatable. Therefore the bistable tubular can be a reusable tool that is selectively changed between the expanded state as shown in FIG. 4A and the collapsed state as shown in FIG. 4B.

In the collapsed state, as in FIG. 4B, the bistable expandable tubular is easily inserted into the wellbore and placed into position. A deployment device is then used to change the configuration from the collapsed state to the expanded state.

In the expanded state, as in FIG. 4A, design control of the elastic material properties of each bistable cell can be such that a constant radial force can be applied by the tubular wall to the constraining wellbore surface. The material properties and the geometric shape of the bistable cells can be designed to give certain desired results.

One example of designing for certain desired results is an expandable bistable tubular string with more than one diameter throughout the length of the string. This can be useful in

boreholes with varying diameters, whether designed that way or as a result of unplanned occurrences such as formation washouts or keyseats within the borehole. This also can be beneficial when it is desired to have a portion of the bistable expandable device located inside a cased section of the well while another portion is located in an uncased section of the well. FIG. 11 illustrates one example of this condition. A wellbore 40 is drilled from the surface 42 and comprises a cased section 44 and an openhole section 46. An expandable bistable device 48 having segments 50, 52 with various diameters is placed in the well. The segment with a larger diameter 50 is used to stabilize the openhole section 46 of the well, while the segment having a reduced diameter 52 is located inside the cased section 44 of the well.

Bistable collars or connectors 24A (see FIG. 4C) can be designed to allow sections of the bistable expandable tubular to be joined together into a string of useful lengths using the same principle as illustrated in FIG. 4A and 4B. This bistable connector 24A also incorporates a bistable cell design that allows it to expand radially using the same mechanism as for the bistable expandable tubular component. Exemplary bistable connectors have a diameter slightly larger than the expandable tubular sections that are being joined. The bistable connector is then placed over the ends of the two sections and mechanically attached to the expandable tubular sections. Mechanical fasteners such as screws, rivets or bands can be used to connect the connector to the tubular sections. The bistable connector typically is designed to have an expansion rate that is compatible with the expandable tubular sections, so that it continues to connect the two sections after the expansion of the two segments and the connector.

Alternatively, the bistable connector can have a diameter smaller than the two expandable tubular sections joined. Then, the connector is inserted inside of the ends of the tubulars and mechanically fastened as discussed above. Another embodiment would involve the machining of the ends of the tubular sections on either their inner or outer surfaces to form an annular recess in which the connector is located. A connector designed to fit into the recess is placed in the recess. The connector would then be mechanically attached to the ends as described above. In this way the connector forms a relatively flush-type connection with the tubular sections.

A conveyance device 31 transports the bistable expandable tubular lengths and bistable connectors into the wellbore and to the correct position. (See FIGS. 4C and 4D). The conveyance device may utilize one or more mechanisms such as wireline cable, coiled tubing, coiled tubing with wireline conductor, drill pipe, tubing or casing.

A deployment device 33 can be incorporated into the bottom hole assembly to expand the bistable expandable tubular and connectors. (See FIGS. 4C and 4D). Deployment devices can be of numerous types such as an inflatable packer element, a mechanical packer element, an expandable swage, a piston apparatus, a mechanical actuator, an electrical solenoid, a plug type apparatus, e.g. a conically shaped device pulled or pushed through the tubing, a ball type apparatus or a rotary type expander as further discussed below.

An inflatable packer element is shown in FIGS. 5A and 5B and is a device with an inflatable bladder, element, or bellows incorporated into the bistable expandable tubular system bottom hole assembly. In the illustration of FIG. 5A, the inflatable packer element 25 is located inside the entire length, or a portion, of the initial collapsed state bistable tubular 24 and any bistable expandable connectors (not shown). Once the bistable expandable tubular system is at the correct deployment depth, the inflatable packer element 25 is expanded

radially by pumping fluid into the device as shown in FIG. 5B. The inflation fluid can be pumped from the surface through tubing or drill pipe, a mechanical pump, or via a downhole electrical pump which is powered via wireline cable. As the inflatable packer element 25 expands, it forces the bistable expandable tubular 24 to also expand radially. At a certain expansion diameter, the inflatable packer element causes the bistable cells in the tubular to reach a critical geometry where the bistable "snap" effect is initiated, and the bistable expandable tubular system expands to its final diameter. Finally the inflatable packer element 25 is deflated and removed from the deployed bistable expandable tubular 24.

A mechanical packer element is shown in FIGS. 6A and 6B and is a device with a deformable plastic element 26 that expands radially when compressed in the axial direction. The force to compress the element can be provided through a compression mechanism 27, such as a screw mechanism, cans, or a hydraulic piston. The mechanical packer element deploys the bistable expandable tubulars and connectors in the same way as the inflatable packer element. The deformable plastic element 26 applies an outward radial force to the inner circumference of the bistable expandable tubulars and connectors, allowing them in turn to expand from a contracted position (see FIG. 6A) to a final deployment diameter (see FIG. 6B).

An expandable swage is shown in FIGS. 7A-7D and comprises a series of fingers 28 that are arranged radially around a conical mandrel 30. FIGS. 7A and 7C show side and top views respectively. When the mandrel 30 is pushed or pulled through the fingers 28 they expand radially outwards, as illustrated in FIGS. 7B and 7D. An expandable swage is used in the same manner as a mechanical packer element to deploy a bistable expandable tubular and connector.

A piston type apparatus is shown in FIGS. 8A-8D and comprises a series of pistons 32 facing radially outwardly and used as a mechanism to expand the bistable expandable tubulars and connectors. When energized, the pistons 32 apply a radially directed force to deploy the bistable expandable tubular assembly as per the inflatable packer element. FIGS. 8A and 8C illustrate the pistons retracted while FIGS. 8B and 8D show the pistons extended. The piston type apparatus can be actuated hydraulically, mechanically or electrically.

A plug type actuator is illustrated in FIGS. 9A and 9B and comprises a plug 34 that is pushed or pulled through the bistable expandable tubulars 24 or connectors as shown in FIG. 9A. The plug is sized to expand the bistable cells past their critical point where they will snap to a final expanded diameter as shown in FIG. 9B.

A ball type actuator is shown in FIGS. 10A and 10B and operates when an oversized ball 36 is pumped through the middle of the bistable expandable tubulars 24 and connectors. To prevent fluid losses through the cell slots, an expandable elastomer based liner 38 is run inside the bistable expandable tubular system. The liner 38 acts as a seal and allows the ball 36 to be hydraulically pumped through the bistable tubular 24 and connectors. The effect of pumping the ball 36 through the bistable expandable tubulars 24 and connectors is to expand the cell geometry beyond the critical bistable point, allowing full expansion to take place as shown in FIG. 10B. Once the bistable expandable tubulars and connectors are expanded, the elastomer sleeve 38 and ball 36 are withdrawn.

Radial roller type actuators also can be used to expand the bistable tubular sections. FIG. 12 illustrates a motor driven expandable radial roller tool. The tool comprises one or more sets of arms 58 that are expanded to a set diameter by means of a mechanism and pivot. On the end of each set of arms is a roller 60. Centralizers 62 can be attached to the tool to locate

it correctly inside the wellbore and the bistable tubular **24**. A motor **64** provides the force to rotate the whole assembly, thus turning the roller(s) circumferentially inside the wellbore. The axis of the roller(s) is such as to allow the roller(s) to rotate freely when brought into contact with the inner surface of the tubular. Each roller can be conically-shaped in section to increase the contact area of roller surface to the inner wall of the tubular. The rollers are initially retracted and the tool is run inside the collapsed bistable tubular. The tool is then rotated by the motor **64**, and rollers **60** are moved outwardly to contact the inner surface of the bistable tubular. Once in contact with the tubular, the rollers are pivoted outwardly a greater distance to apply an outwardly radial force to the bistable tubular. The outward movement of the rollers can be accomplished via centrifugal force or an appropriate actuator mechanism coupled between the motor **64** and the rollers **60**.

The final pivot position is adjusted to a point where the bistable tubular can be expanded to the final diameter. The tool is then longitudinally moved through the collapsed bistable tubular, while the motor continues to rotate the pivot arms and rollers. The rollers follow a shallow helical path **66** inside the bistable tubular, expanding the bistable cells in their path. Once the bistable tubular is deployed, the tool rotation is stopped and the roller retracted. The tool is then withdrawn from the bistable tubular by a conveyance device **68** that also can be used to insert the tool.

FIG. **13** illustrates a hydraulically driven radial roller deployment device. The tool comprises one or more rollers **60** that are brought into contact with the inner surface of the bistable tubular by means of a hydraulic piston **70**. The outward radial force applied by the rollers can be increased to a point where the bistable tubular expands to its final diameter. Centralizers **62** can be attached to the tool to locate it correctly inside the wellbore and bistable tubular **24**. The rollers **60** are initially retracted and the tool is run into the collapsed bistable tubular **24**. The rollers **60** are then deployed and push against the inside wall of the bistable tubular **24** to expand a portion of the tubular to its final diameter. The entire tool is then pushed or pulled longitudinally through the bistable tubular **24** expanding the entire length of bistable cells **23**. Once the bistable tubular **24** is deployed in its expanded state, the rollers **60** are retracted and the tool is withdrawn from the wellbore by the conveyance device **68** used to insert it. By altering the axis of the rollers **60**, the tool can be rotated via a motor as it travels longitudinally through the bistable tubular **24**.

Power to operate the deployment device can be drawn from one or a combination of sources such as: electrical power supplied either from the surface or stored in a battery arrangement along with the deployment device, hydraulic power provided by surface or downhole pumps, turbines or a fluid accumulator, and mechanical power supplied through an appropriate linkage actuated by movement applied at the surface or stored downhole such as in a spring mechanism.

The bistable expandable tubular system is designed so the internal diameter of the deployed tubular is expanded to maintain a maximum cross-sectional area along the expandable tubular. This feature enables mono-bore wells to be constructed and facilitates elimination of problems associated with traditional wellbore casing systems where the casing outside diameter must be stepped down many times, restricting access, in long wellbores.

The bistable expandable tubular system can be applied in numerous applications such as an expandable open hole liner (see FIG. **14**) where the bistable expandable tubular **24** is used to support an open hole formation by exerting an external radial force on the wellbore surface. As bistable tubular **24** is

radially expanded in the direction of arrows **71**, the tubular moves into contact with the surface forming wellbore **29**. These radial forces help stabilize the formations and allow the drilling of wells with fewer conventional casing strings. The open hole liner also can comprise a material, e.g. a wrapping **72**, that reduces the rate of fluid loss from the wellbore into the formations. The wrapping **72** can be made from a variety of materials including expandable metallic and/or elastomeric materials. By reducing fluid loss into the formations, the expense of drilling fluids can be reduced and the risk of losing circulation and/or borehole collapse can be minimized.

Liners also can be used within wellbore tubulars for purposes such as corrosion protection. One example of a corrosive environment is the environment that results when carbon dioxide is used to enhance oil recovery from a producing formation. Carbon dioxide (CO_2) readily reacts with any water (H_2O) that is present to form carbonic acid (H_2CO_3). Other acids can also be generated, especially if sulfur compounds are present. Tubulars used to inject the carbon dioxide as well as those used in producing wells are subject to greatly elevated corrosion rates. The present invention can be used for placing protective liners, a bistable tubular **24**, within an existing tubular (e.g., tubular **73** illustrated with dashed lines in FIG. **14**) to minimize the corrosive effects and to extend the useful life of the wellbore tubulars.

Another application involves use of the bistable tubular **24** illustrated in FIG. **14** as an expandable perforated liner. The open bistable cells in the bistable expandable tubular allow unrestricted flow from the formation while providing a structure to stabilize the borehole.

Still another application of the bistable tubular **24** is as an expandable sand screen where the bistable cells are sized to act as a sand control screen or an expandable screen element **74** can be affixed to the bistable expandable tubular as illustrated in FIG. **14A** in its collapsed state. The expandable screen element **74** can be formed as a wrapping around bistable tubular **24**. It has been found that the imposition of hoop stress forces onto the wall of a borehole will in itself help stabilize the formation and reduce or eliminate the influx of sand from the producing zones, even if no additional screen element is used.

Another application of the bistable tubular **24** is as a reinforced expandable liner where the bistable expandable tubular cell structure is reinforced with a cement or resin **75**, as illustrated in FIG. **14B**. The cement or resin **75** provides increased structural support or hydraulic isolation from the formation.

The bistable expandable tubular **24** also can be used as an expandable connection system to join traditional lengths of casing **76a** or **76b** of different diameters as illustrated in FIG. **14C**. the tubular **24** also can be used as a structural repair joint to provide increased strength for existing sections of casing.

Another application includes using the bistable expandable tubular **24** as an anchor within the wellbore from which other tools or casings can be attached, or as a "fishing" tool in which the bistable characteristics are utilized to retrieve items lost or stuck in a wellbore. The bistable expandable tubular **24** in its collapsed configuration is inserted into a lost item **77** and then expanded as indicated by arrows **78** in FIG. **14D**. In the expanded configuration the bistable tubular exerts radial forces that assist in retrieving the lost item. The bistable tubular also can be run into the well in its expanded configuration, placed over and collapsed in the direction of arrows **79** around lost item **77** in an attempt to attach and retrieve it as illustrated in FIG. **14E**. Once lost item **77** is gripped by bistable tubular **24**, it can be retrieved through wellbore **29**.

The above described bistable expandable tubulars can be made in a variety of manners such as: cutting appropriately shaped paths through the wall of a tubular pipe thereby creating an expandable bistable device in its collapsed state; cutting patterns into a tubular pipe thereby creating an expandable bistable device in its expanded state and then compressing the device into its collapsed state; cutting appropriate paths through a sheet of material, rolling the material into a tubular shape and joining the ends to form an expandable bistable device in its collapsed state; or cutting patterns into a sheet of material, rolling the material into a tubular shape, joining the adjoining ends to form an expandable bistable device in its expanded state and then compressing the device into its collapsed state.

The materials of construction for the bistable expandable tubulars can include those typically used within the oil and gas industry such as carbon steel. They can also be made of specialty alloys (such as a monel, inconel, hastelloy or tungsten-based alloys) if the application requires.

The configurations shown for the bistable tubular are illustrative of the operation of a basic bistable cell. Other configurations may be suitable, but the concept presented is also valid for these other geometries.

FIG. 15 illustrates an expandable tubing 80 formed of bi-stable cells 82. The tubing 80 defines a thinned portion 84 (best seen in FIG. 15) which may be in the form of a slot, as shown, a flattening, or other thinning of a portion of the tubing 80. The thinned portion 84 extends generally longitudinally and may be linear, helical, or follow some other circuitous path. In one embodiment, the thinned portion extends from one end of the tubing to the other to provide a communication line path 84 for the tubing 80. In such an embodiment, a communication line 86 may pass through the communication line path 84 along the tubing 80. In this way, the communication line 86 stays within the general outside diameter of the tubing 80 or extends only slightly outside this diameter. Although the tubing is shown with one thinned portion 84, it may include a plurality that are spaced about the circumference of the tubing 80. The thinned portion 84 may be used to house a conduit (not shown) through which communication lines 86 pass or which is used for the transport of fluids or other materials, such as mixtures of fluids and solids.

As used herein, the term "communication line" refers to any type of communication line such as electric, hydraulic, fiber optic, combinations of these, and the like.

FIG. 15A illustrates an exemplary thinned portion 84 designed to receive a device 88. As with the cable placement, device 88 is at least partially housed in the thinned portion of the tubing 80 so that the extent to which it extends beyond the outer diameter of the tubing 80 is lessened. Examples of certain alternative embodiments of devices 88 are electrical devices, measuring devices, meters, gauges, sensors. More specific examples comprise valves, sampling devices, a device used in intelligent or smart well completion, temperature sensors, pressure sensors, flow-control devices, flow rate measurement devices, oil/water/gas ratio measurement devices, scale detectors, equipment sensors (e.g., vibration sensors), sand detection sensors, water detection sensors, data recorders, viscosity sensors, density sensors, bubble point sensors, composition sensors, resistivity array devices and sensors, acoustic devices and sensors, other telemetry devices, near infrared sensors, gamma ray detectors. H₂S detectors, CO₂ detectors, downhole memory units, downhole controllers. Examples of measurements that the devices might make are flow rate, pressure, temperature, differential pressure, density, relative amounts of liquid, gas, and solids, water cut, oil-water ratio, and other measurements.

As shown in the figure, the device 88 may be exposed to fluid inside and outside of tubing 80 via openings formed by the cells 82. Thus, the thinned portion 84 may bridge openings as well as linkages 21, 22 of the cells 82. Also note that the communication line 86 and associated communication line path 84 may extend a portion of the length of the tubing 80 in certain alternative designs. For example, if a device 88 is placed intermediate the ends of the tubing 80, the communication line passageway 84 may only need to extend from an end of the tubing to the position of the device 80.

FIG. 16 illustrates an expandable tubing 80 formed of bi-stable cells 82 having thin struts 21 and thick struts 22. At least one of the thick struts (labeled as 90) is relatively wider than other struts of the tubing 80. The wider strut 90 may be used for various purposes such as routing of communication lines, including cables, or devices, such as sensor arrays.

FIGS. 17A and 17B illustrate tubing 80 having a strut 90 that is relatively wider than the other thick struts 22. A passageway 92 formed in the strut 90 facilitates placement of a communication line in the well and through the tubing 80 and may be used for other purposes. FIG. 17B is a cross sectional view showing the passageway 92. Passageway 92 is an alternative embodiment of a communication line path 84. A passageway 94 may be configured to generally follow the curvature of a strut, e.g. one of the thick struts 22, as further illustrated in FIGS. 17A and 17B.

FIG. 18 illustrates a thinned portion 84 having a dovetail design with a relatively narrower opening. The communication line 86 is formed so that it fits through the relatively narrow opening into the wider, lower portion, e.g. by inserting one side edge and then the other. Communication line 86 is held in place due to the dovetail design as is apparent from the figures. The width of the communication line 86 is greater than the width of the opening. Note that the communication line 86 may comprise a bundle of lines which may be of the same or different forms (e.g., a hydraulic, an electric, and a fiber optic line bundled together). Also, connectors for connecting adjacent tubings may incorporate a connection for the communication lines.

Note that the communication line passageway 84 may be used in conjunction with other types of expandable tubings, such as those of the expandable slotted liner type disclosed in U.S. Pat. No. 5,366,012, issued Nov. 22, 1994 to Lohbeck, the folded tubing types of U.S. Pat. No. 3,489,220, issued Jan. 13, 1970 to Kinley, U.S. Pat. No. 5,337,823, issued Aug. 16, 1994 to Nobileau, U.S. Pat. No. 3,203,451, issued Aug. 31, 1965 to Vincent.

The particular embodiments disclosed herein are illustrative only, as the invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the invention. Accordingly, the protection sought herein is as set forth in the claims below.

What is claimed is:

1. An apparatus for use in a wellbore, comprising: a wellbore tubular having a bistable device configured for deployment proximate a wellbore wall, the expandable bistable device having a plurality of bistable cells arranged in a generally tubular shape, the plurality of bistable cells being stable in a first configuration and in a second configuration, wherein the force required to move the plurality of bistable cells between the first

11

configuration and the second configuration is greater in one direction than the other.

2. The apparatus as recited in claim 1, wherein each bistable cell comprises at least two elongated members connected to each other.

3. The apparatus as recited in claim 2, wherein the first configuration is a first generally tubular configuration and the second configuration is a second generally tubular configuration having a larger diameter than the first generally tubular configuration.

4. The apparatus as recited in claim 3, further comprising a conveyance device able to transport the bistable device to a desired location in the wellbore.

5. The apparatus as recited in claim 4, further comprising a deployment device able to initiate expansion of the bistable device from its first generally tubular configuration to its second generally tubular configuration.

6. The apparatus as recited in claim 4, wherein each cell comprises a first member and a second member, the first member and the second member each comprising a midpoint and two ends, and further wherein the first member is more flexible than the second member.

7. The apparatus as recited in claim 6, wherein the first and second members are mechanically connected such that the second member hinders deformation of the first member.

8. The apparatus as recited in claim 7, wherein the first member has two stable positions, the first stable position being where the first member mid-point is adjacent to the second member mid-point, the second stable position being where the first member mid-point is displaced from the second member mid-point to form a gap between the first member mid-point and the second member mid-point.

9. The apparatus as recited in claim 6, wherein the second member has a greater thickness than the first member.

10. The apparatus as recited in claim 6, wherein the thickness ratio of the second member to the first member is greater than approximately 3:1.

11. The apparatus as recited in claim 6, wherein the thickness ratio of the second member to the first member is greater than approximately 6:1.

12. The apparatus as recited in claim 4, wherein the bistable device further comprises a wrapping attached to [the] *an* outer surface of the bistable device.

13. The apparatus as recited in claim 12, wherein the wrapping comprises an expandable screen.

14. The apparatus as recited in claim 4, wherein the bistable device further comprises a deformable material attached to [the] *an* outer surface of the bistable device.

15. The apparatus as recited in claim 14, wherein the deformable material comprises an elastomer.

16. The apparatus as recited in claim 15, wherein the elastomer is selected to be resistant to crude oils, brines, and acids encountered in oil and gas wells.

17. The apparatus as recited in claim 4, wherein the bistable device in [its] *the* second generally tubular configuration comprises a plurality of diameters.

[18. A method of facilitating use of a wellbore, comprising: isolating a portion of a wellbore with an expandable bistable device having a generally tubular shape formed by a plurality of bistable cells that permit the expandable bistable device to be selectively actuated between a contracted state and an expanded state.]

[19. A method of sealing a portion of a wellbore tubular, comprising: locating a bistable device comprising a plurality of bistable cells within a wellbore tubular adjacent to a zone

12

to be sealed; and expanding the bistable device against the wellbore tubular by moving the bistable device through a nonstable region towards an expanded stable state.]

[20. An apparatus for use in a wellbore, comprising:

5 a wellbore conduit having a bistable wall comprising a plurality of bistable cells, the bistable wall enabling transition of the wellbore conduit from a radially contracted stable state, in which the wellbore conduit is readily insertable into a wellbore, and a radially expanded state, in which the bistable wall is proximate the wall of the wellbore.]

[21. The apparatus as recited in claim 20, further comprising a conveyance device able to transport the wellbore conduit to a location in a borehole.]

[22. The apparatus as recited in claim 21, wherein the apparatus further comprises a deployment device that initiates the expansion or collapse of the bistable device.]

[23. A wellbore tubular, comprising:

20 a radially expandable bistable tubing comprising a plurality of bistable cells; and
a device mounted to the tubing, the device being configured to sense a wellbore parameter.]

[24. A method of routing a communication line in a well, comprising:

25 deploying an expandable tubing formed of bistable cells into a well;
connecting a communication line along at least a portion of the expandable tubing; and
30 expanding the expandable tubing in the well.]

25 [25. [The method as recited in claim 24] *A method of routing a communication line in a well, comprising:*

deploying an expandable tubing formed of bistable cells into a well;

connecting a communication line along at least a portion of the expandable tubing; and

expanding the expandable tubing in the well, wherein routing comprises routing a cable along an exterior of the expandable tubing.

40 [26. The method as recited in claim 24, further comprising attaching the communication line to the expandable tubing as the expandable tubing is deployed in the well.]

45 [27. The method as recited in claim 24, further comprising forming a communication line passageway in the expandable tubing to receive the communication line.]

[28. [The method as recited in claim 27, wherein forming comprises forming the communication line] *A method of routing a communication line in a well, comprising:*

deploying an expandable tubing formed of bistable cells into a well;

connecting a communication line along at least a portion of the expandable tubing;

expanding the expandable tubing in the well; and

forming a communication line passageway in the expandable tubing to receive the communication line along a thick strut formed between a plurality of bistable cells.

60 [29. The method as recited in claim [24] 28, further comprising providing a device attached to the expandable tubing.

[30. The method as recited in claim 29, wherein providing comprises attaching a sensor.

[31. The method as recited in claim 29, wherein providing comprises attaching an instrument.