



US00RE45212E

(19) **United States**  
(12) **Reissued Patent**  
**Wentink**

(10) **Patent Number:** **US RE45,212 E**  
(45) **Date of Reissued Patent:** **Oct. 28, 2014**

(54) **EVENT-BASED MULTICHANNEL DIRECT LINK**

(56) **References Cited**

(75) Inventor: **Menzo Wentink**, Utrecht (NL)

(73) Assignee: **Intellectual Ventures I LLC**,  
Wilmington, DE (US)

(21) Appl. No.: **13/351,588**

(22) Filed: **Jan. 17, 2012**  
(Under 37 CFR 1.47)

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **7,251,235**  
Issued: **Jul. 31, 2007**  
Appl. No.: **10/880,370**  
Filed: **Jun. 30, 2004**

U.S. Applications:

(63) Continuation of application No. 12/460,974, filed on Jul. 27, 2009, now Pat. No. Re. 43,127, which is an application for the reissue of Pat. No. 7,251,235, which is a continuation-in-part of application No. 10/353,391, filed on Jan. 29, 2003, now Pat. No. 6,791,962.

(60) Provisional application No. 60/388,569, filed on Jun. 12, 2002, provisional application No. 60/515,701, filed on Oct. 31, 2003.

(51) **Int. Cl.**  
**H04W 4/00** (2009.01)

(52) **U.S. Cl.**  
USPC ..... **370/338**; 370/401; 370/465

(58) **Field of Classification Search**  
USPC ..... 370/328–339  
See application file for complete search history.

U.S. PATENT DOCUMENTS

5,371,734 A	12/1994	Fischer
5,463,659 A	10/1995	Nealon et al.
5,465,398 A	11/1995	Flammer
5,487,069 A	1/1996	O'Sullivan et al.
5,537,414 A	7/1996	Takiyasu et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE	102 28 342	9/2003
DE	10228342 A1	9/2003

(Continued)

OTHER PUBLICATIONS

802.11 Wireless Networks: The Definitive Guide. O'Reilly & Associates, 2002. pp. 1-14.


(Continued)

*Primary Examiner* — Frank Duong

(57) **ABSTRACT**

Disclosed herein are exemplary techniques for the communication of information in a wireless system by using multiple wireless channels. A direct link between two or more wireless devices may be established by performing a direct link setup between two or more wireless devices using an access point, where the direct link setup is conducted over a base channel and the direct link is established on a parallel channel. The two or more wireless devices may switch to the parallel channel and use the established direct link to communicate information directly without the access point as an intermediary. In anticipation of a predetermined event, such as the transmission of a delivery traffic indication map (DTIM) beacon frame by the access point, the two or more wireless devices may switch back to the base channel so that uplink, downlink and/or peer-to-peer information may be transmitted and/or received.

**20 Claims, 5 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,636,220 A 6/1997 Vook et al.  
 5,752,201 A 5/1998 Kivari  
 5,768,531 A 6/1998 Lin  
 5,812,968 A 9/1998 Hassan et al.  
 5,822,682 A 10/1998 Schroderus et al.  
 5,862,142 A 1/1999 Takiyasu et al.  
 5,991,287 A 11/1999 Diepstraten et al.  
 5,995,849 A 11/1999 Williams et al.  
 5,999,127 A 12/1999 Dezelan  
 6,047,178 A 4/2000 Frlan  
 6,052,557 A 4/2000 Kinnunen et al.  
 6,084,865 A 7/2000 Dent  
 6,119,014 A 9/2000 Alperovich et al.  
 6,192,230 B1 2/2001 Van Bokhorst et al.  
 6,208,627 B1 3/2001 Menon et al.  
 6,222,842 B1 4/2001 Sasyan et al.  
 6,292,672 B1 9/2001 Chavez, Jr.  
 6,301,609 B1 10/2001 Aravamudan et al.  
 6,339,713 B1 1/2002 Hansson et al.  
 6,343,083 B1 1/2002 Mendelson et al.  
 6,347,095 B1 2/2002 Tang et al.  
 6,360,277 B1 3/2002 Ruckley et al.  
 6,415,146 B1 7/2002 Capece  
 6,424,820 B1 7/2002 Burdick et al.  
 6,430,604 B1 8/2002 Ogle et al.  
 6,463,290 B1 10/2002 Stilp et al.  
 6,470,058 B1 10/2002 Michalski et al.  
 6,484,027 B1 11/2002 Mauney et al.  
 6,487,180 B1 11/2002 Borgstahl et al.  
 6,496,694 B1 12/2002 Menon et al.  
 6,507,739 B1 1/2003 Gross et al.  
 6,525,690 B2 2/2003 Rudow et al.  
 6,529,748 B1 3/2003 Bruner  
 6,539,232 B2 3/2003 Hendrey et al.  
 6,542,748 B2 4/2003 Hendrey et al.  
 6,542,749 B2 4/2003 Tanaka et al.  
 6,542,750 B2 4/2003 Hendrey et al.  
 6,574,266 B1 6/2003 Haartsen  
 6,580,704 B1 6/2003 Wellig et al.  
 6,594,666 B1 7/2003 Biswas et al.  
 6,618,005 B2 9/2003 Hannah et al.  
 6,625,456 B1 9/2003 Busso et al.  
 6,631,271 B1 10/2003 Logan  
 6,665,520 B2 12/2003 Romans  
 6,744,743 B2 6/2004 Walton et al.  
 6,759,956 B2 7/2004 Menard et al.  
 6,763,240 B1 7/2004 Chambers et al.  
 6,778,515 B2 8/2004 Bolgiano et al.  
 6,785,251 B2 8/2004 Bolgiano et al.  
 6,788,688 B2 9/2004 Trebes, Jr.  
 6,791,962 B2 9/2004 Wentink  
 6,795,701 B1 9/2004 Hui et al.  
 6,799,056 B2 9/2004 Curley et al.  
 6,810,246 B1 10/2004 Kalofonos et al.  
 6,826,162 B2 11/2004 Haines et al.  
 6,842,460 B1 1/2005 Olkkonen et al.  
 6,904,055 B2 6/2005 Pichna et al.  
 6,925,286 B1 8/2005 Kraiem et al.  
 6,968,179 B1 11/2005 De Vries  
 6,978,151 B2 12/2005 Choi et al.  
 6,985,461 B2 1/2006 Singh  
 7,068,615 B2 6/2006 Niesen  
 7,095,722 B1 8/2006 Walke et al.  
 7,133,909 B2 11/2006 Bahl  
 7,212,827 B1 5/2007 Veschl  
 7,233,792 B2 6/2007 Chang  
 7,245,592 B2 7/2007 Soomro et al.  
 7,251,235 B2 7/2007 Wentink  
 7,260,392 B2 8/2007 Kitchin  
 7,277,692 B1 10/2007 Jones et al.  
 7,308,202 B2 12/2007 Roes et al.  
 7,359,727 B2 4/2008 Tsien et al.  
 7,421,466 B2 9/2008 Haines  
 7,450,550 B2 11/2008 Jin  
 7,508,799 B2 3/2009 Sumner et al.

7,545,771 B2 6/2009 Wentink et al.  
 2001/0031626 A1 10/2001 Lindskog et al.  
 2002/0025839 A1 2/2002 Usui  
 2002/0087724 A1 7/2002 Datta et al.  
 2002/0159544 A1 10/2002 Karaoguz  
 2002/0168040 A1 11/2002 Coffey  
 2002/0168993 A1 11/2002 Choi et al.  
 2002/0172186 A1 11/2002 Larsson  
 2002/0191573 A1 12/2002 Whitehill et al.  
 2003/0010524 A1 1/2003 Connor  
 2003/0036354 A1 2/2003 Lee et al.  
 2003/0063589 A1 4/2003 Haines et al.  
 2003/0096576 A1 5/2003 Salonidis et al.  
 2003/0126213 A1 7/2003 Betzler  
 2003/0140084 A1 7/2003 'Angelo  
 2003/0142641 A1 7/2003 Sumner et al.  
 2003/0185241 A1 10/2003 Lu et al.  
 2003/0198196 A1 10/2003 Bahl et al.  
 2003/0210658 A1 11/2003 Hernandez et al.  
 2003/0220765 A1 11/2003 Overy et al.  
 2003/0232598 A1 12/2003 Aljadeff et al.  
 2004/0044723 A1 3/2004 Bell et al.  
 2004/0048609 A1 3/2004 Kosaka  
 2004/0056901 A1 3/2004 March et al.  
 2004/0077920 A1 4/2004 Snyder  
 2004/0078598 A1 4/2004 Barber et al.  
 2004/0095907 A1 5/2004 Agee et al.  
 2004/0125775 A1 7/2004 Rios  
 2004/0125776 A1 7/2004 Haugli et al.  
 2004/0127214 A1 7/2004 Reddy et al.  
 2004/0147249 A1 7/2004 Wentink  
 2004/0184456 A1 9/2004 Binding et al.  
 2004/0192413 A1 9/2004 Frank  
 2004/0203698 A1 10/2004 Comp  
 2004/0236850 A1 11/2004 Krumm et al.  
 2004/0242154 A1 12/2004 Takeda et al.  
 2004/0246934 A1 12/2004 Kim  
 2005/0030976 A1 2/2005 Wentink  
 2005/0122927 A1 6/2005 Wentink  
 2005/0135305 A1 6/2005 Wentink  
 2005/0157674 A1 7/2005 Wentink  
 2005/0265305 A1 12/2005 Furukawa et al.  
 2006/0148406 A1 7/2006 Strater et al.  
 2007/0077894 A1 4/2007 Zhang et al.  
 2008/0095126 A1 4/2008 Mahany et al.

## FOREIGN PATENT DOCUMENTS

EP 1 168 676 1/2002  
 WO WO-02/49387 6/2002  
 WO WO-2004/077920 9/2004  
 WO WO-2005/046134 5/2005  
 WO WO-2005/067535 7/2005

## OTHER PUBLICATIONS

A. Soomro and S. Choi Philips Research USA, Proposal to Add Link Margin Field in Ieee 802.11h Submission, Sep. 2001, Slides 9-14.  
 Diepstraten et al., 802.11 Tutorial, IEEE, pp. 1-22, Mar. 1996.  
 ANSI/IEEE Std. 802.11, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specification, pp. 1-513, 1999.  
 Communication from the European Patent Office for EP Application 04794757.7, dated Jul. 28, 2009.  
 Donovan, Jeremy, "Location awareness beyond E911," EE Times, Jun. 9, 2003, 1 page.  
 ESTRI TR 101 683 V1.1.1, Broadband Radio Access Networks; HIPERLAN Type 2; System Overview, pp. 1-19, 2000.  
 Final Office Action for U.S. Appl. No. 10/977,469, mailed Aug. 8, 2008.  
 Final Office Action on U.S. Appl. No. 10/880,366, mailed Sep. 11, 2009.  
 Final Office Action on U.S. Appl. No. 10/880,370, mailed Nov. 3, 2006.  
 Final Office Action on U.S. Appl. No. 10/977,470, mailed Jul. 17, 2008.

(56)

**References Cited**

## OTHER PUBLICATIONS

Final Office Action on U.S. Appl. No. 10/977,490, mailed Mar. 5, 2012.

Final Office action on U.S. Appl. No. 12/460,974, mailed Jan. 27, 2011.

Ho et al., MediaPlex-An IEEE 802.11 Enhanced Protocol for QoS-Driven Wireless LANS, IEEE pp. 1-25, Nov. 3, 2000.

IEEE Standard 802.11h Amendment 5: Spectrum and transmit power management extensions in the 5 GHz band in Europe, published Oct. 14, 2003, IEEE, 75 pages.

IEEE STD 802.11e/D3.0, Part 11: Wireless Access Control (MAC) and Physical Layer (PHY) Specifications: Medium Access Control (MAC) Enhancements for Quality of Service (QoS), IEEE, 140 pages, 2002.

International Preliminary Report on patentability for PCT/US2004/033487, issued May 1, 2006.

International Preliminary Report on patentability for PCT/US2005/001303, issued Nov. 29, 2006.

International Search Report for PCT/US2004/033487, mailed Feb. 2, 2005.

Kammerman et al, WaveLan-II: A High-Performance Wireless LAN for the Unlicensed Band, Bell Labs Technical Journal, pp. 118-133, 1997.

Kandala et al., "Suggested Changes to Normative Text of WARP," IEEE, pp. 1-11, Jun. 2002.

Kitchen, Duncan, "Wireless Address Resolution Protocol," IEEE 802.11-02/016r0, Jan. 14, 2002, pp. 1-13.

Ni et al., QoS Issues and Enhancements for IEEE 802.11 Wireless LAN, INRIA, pp. 1-34, Nov. 2002.

Non-Final Office Action for U.S. Appl. No. 10/880,366, mailed Jan. 12, 2010.

Non-Final Office Action for U.S. Appl. No. 10/977,470, mailed Feb. 26, 2009.

Non-Final Office Action for U.S. Appl. No. 10/977,470, mailed Jan. 14, 2008.

Non-Final Office Action on U.S. Appl. No. 10/880,366, mailed Feb. 20, 2009.

Non-final Office Action on U.S. Appl. No. 10/880,367, mailed Jan. 21, 2011.

Non-final Office Action on U.S. Appl. No. 10/880,367, mailed Aug. 3, 2010.

Non-Final Office Action on U.S. Appl. No. 10/880,367, mailed Sep. 14, 2009.

Non-Final Office Action on U.S. Appl. No. 10/880,370, mailed Apr. 6, 2006.

Non-Final Office Action on U.S. Appl. No. 10/977,469, mailed Jan. 9, 2008.

Non-Final Office Action on U.S. Appl. No. 10/977,490, mailed Sep. 14, 2011.

Non-Final Office Action on U.S. Appl. No. 13/271,394, mailed Mar. 12, 2012.

Notice of Allowance for U.S. Appl. No. 10/880,370, mailed Jun. 12, 2007.

Notice of Allowance for U.S. Appl. No. 10/977,469, mailed Feb. 10, 2009.

Notice of Allowance on U.S. Appl. No. 10/880,366, mailed Nov. 26, 2010.

Notice of Allowance on U.S. Appl. No. 10/880,366, mailed May 28, 2010.

Notice of Allowance on U.S. Appl. No. 10/880,367, mailed Jul. 21, 2011.

Notice of Allowance on U.S. Appl. No. 12/460,974, mailed Sep. 21, 2011.

Notice of Allowance on U.S. Appl. No. 10/977,470, mailed Jan. 6, 2011.

Non-Final Office Action on U.S. Appl. No. 12/460,974, mailed Mar. 24, 2010.

Palm, Plam: Providing Fluid Connectivity in a Wireless World, 2002, 10 pages.

PanGoNetworks, PanGo "Overview", Intelligent Wireless, Copyright 2003, 1 page.

PanGoNetworks, PanGo "Proximity Platform," Intelligent Wireless, Copyright 2003, 2 pages.

PanGoNetworks, PanGo Mobile Applications Suite, Intelligent Wireless, Copyright 2003, 2 pages.

PanGoNetworks, PanGo Technology, How it Works, Intelligent Wireless, Copyright 2003, 1 page.

Wentink, "Direct Stream Request Protocol (DSRP)," IEEE, pp. 1-16, Jul. 2002.

Notice of Allowance on U.S. Appl. No. 13/271,394, mailed Jan. 22, 2013.

Final Office Action on U.S. Appl. No. 13/271,394, mailed Nov. 5, 2012.

Notice of Allowance on U.S. Appl. No. 11/035,065, mailed Oct. 1, 2013.

Non-Final Office Action on U.S. Appl. No. 10/977,490, mailed Mar. 5, 2014.

Notice of Allowance on U.S. Appl. 11/035,065, mailed Mar. 20, 2014.

Kitchen, Wireless Address Resolution Protocol, IEEE, pp. 1-13, Jan. 2000.\*

IEEE Std 801.11e/D3.0, Draft Supplemental to Standard for Telecommunications and Information Exchange Between Systems—LAN/MAN Specification, pp. 1-40, May 2002.\*

European Search Report and Written Opinion for Application No. PCT/US2004/033487 dated Feb. 2, 2005, 14 pages.

\* cited by examiner




Fig. 1





Fig. 2



**Fig. 3**




Fig. 4




Fig. 5

## EVENT-BASED MULTICHANNEL DIRECT LINK

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

### CROSS-REFERENCE TO RELATED APPLICATIONS

[This application is a continuation-in-part of U.S. patent application Ser. No. 10/353,391 filed Jan. 29, 2003, now U.S. Pat. No. 6,791,962, issued Sep. 14, 2004, which also claims benefit of U.S. Provisional Application No. 60/388,569, filed Jun. 12, 2002, entitled "Direct Link Protocol In Wireless Local Area" and also claims benefit of U.S. patent application Ser. No. 60/515,701 filed Oct. 31, 2003 and entitled "Location Awareness in Wireless Networks," the disclosures of which are herein incorporated by reference in their entireties.]

*Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 7,251,235. The reissue applications are application Ser. Nos. 12/460,974 (the parent of present application), and 13/351,588 (the present application).*

*This application is a continuation reissue of U.S. Ser. No. 12/460,974, filed Jul. 27, 2009, now U.S. Pat. No. Re. 43,127, granted Jan. 24, 2012, which is a reissue application of 10/880,370 filed Jun. 30, 2004, issued as U.S. Pat. No. 7,251,235, which claims benefit of U.S. Provisional Application Ser. No. 60/515,701 filed Oct. 31, 2003, entitled "Location Awareness in Wireless Networks," and is a continuation-in-part of U.S. patent application Ser. No. 10/353,391 filed Jan. 29, 2003, now U.S. Pat. No. 6,791,962, issued Sep. 14, 2004, which claims benefit of U.S. Provisional Application No. 60/388,569, filed Jun. 12, 2002, entitled "Direct Link Protocol In Wireless Local Area," the disclosures of which are herein incorporated by reference in their entireties.*

The present invention is also related to U.S. patent application Ser. No. 10/880,367 filed concurrently herewith and entitled "Direct Link Relay In a Wireless Network," U.S. patent application Ser. No. 10/880,367 filed concurrently herewith and entitled "Link Margin Notification Using Return Frame," U.S. patent application Ser. No. 10/880,325 filed concurrently herewith and entitled "Time-Scheduled Multichannel Direct Link," all claiming benefit of U.S. Provisional Application No. 60/515,701 filed Oct. 31, 2003, the entireties of which are incorporated by reference herein.

### FIELD OF THE INVENTION

The present invention relates generally to wireless communications between wireless devices and more particularly to utilizing multiple wireless channels to communicate information.

### BACKGROUND OF THE INVENTION

Various wireless standards, such as the Institute of Electrical and Electronics Engineers (IEEE) standards 802.11 a/b/c/e/g/i (referred to collectively as IEEE 802.11), provide for wireless connectivity between wireless devices, such as, for example, between a wireless station and an access point connected to an infrastructure network. In conventional wireless standards, the communication of information between peer wireless devices typically is routed through the access point.

To illustrate, to communicate information between a first wireless device and a second wireless device, the first wireless device wirelessly transmits one or more frames of information to the access point, where the frames designate the second wireless device as their destination. The access point then modifies the headers of the frames and transmits them for reception by the second wireless device.

The process of using the access point as an intermediary has a number of drawbacks. For one, the communication of information is delayed by routing it through the access point. Moreover, the wireless channel used by the wireless devices and access point to communicate information (also referred to as the "base" channel) may be crowded with traffic from other wireless devices similarly seeking to transmit information via the access point. As a result, access contention mechanisms often are implemented, which typically results in additional delay.

Accordingly, an improved technique for communicating information between wireless devices would be advantageous.

### SUMMARY OF THE INVENTION

The present invention mitigates or solves the above-identified limitations in known solutions, as well as other unspecified deficiencies in known solutions. A number of advantages associated with the present invention are readily evident to those skilled in the art, including economy of design and resources, transparent operation, cost savings, etc.

The present invention is directed to a method of communicating information directly between the first and second wireless devices in a wireless network including an access point logically connected to at least a first wireless device and a second wireless device.

A further aspect of this invention is a method, in a wireless network including an access point operably connected to at least a first wireless device and a second wireless device, of providing information between the access point and at least one of the first and second wireless devices via a first channel for at least a portion of a first period, providing a channel change request from the first wireless device to the second wireless device on the first channel, providing an affirmative response to the channel change request from the second wireless device to the first wireless device on the first channel, switching the second wireless device to a second channel subsequent to the receipt of the acknowledgement to the provision of the affirmative response to the channel change request, switching the first wireless device to the second channel subsequent to the transmission of the acknowledgement to the receipt of the affirmative response to the channel change request; and communicating information directly between the first and second wireless devices via the second channel for at least a portion of a second period.

A further aspect of this invention is a wireless device, in a wireless network having an access point, including a transceiver, and a direct link module operably connected to the transceiver and adapted to facilitate an establishment of a wireless direct link between the wireless device and another wireless device via a second channel, communicate information with the other wireless device via the wireless direct link for at least a portion of a first period, switch the transceiver from the first channel to a second channel in anticipation of a predetermined event; and communicate information with the access point via second channel for at least a portion of a second period.

A further aspect of this invention is a wireless system including an access point and at least a first wireless device

and a second wireless device. The first wireless device and a second wireless device are adapted to communicate information via a wireless direct link on a first channel during at least a portion of a first period, switch to a second channel in anticipation of a predetermined event; and communicate information with the access point on the second channel during at least a portion of a second period.

Still further features and advantages of the present invention are identified in the ensuing description, with reference to the drawings identified below.

### BRIEF DESCRIPTION OF THE DRAWINGS

The purpose and advantages of the present invention will be apparent to those of ordinary skill in the art from the following detailed description in conjunction with the appended drawings in which like reference characters are used to indicate like elements, and in which:

FIG. 1 is a schematic diagram illustrating an exemplary wireless system having multiple channels for communicating information between wireless devices is illustrated in accordance with at least one embodiment of the present invention.

FIG. 2 is a chart illustrating an exemplary event-based channel switch process for the wireless devices of FIG. 1 in accordance with at least one embodiment of the present invention.

FIG. 3 is a schematic diagram illustrating an exemplary wireless device in greater detail in accordance with at least one embodiment of the present invention.

FIG. 4 is a flow diagram illustrating an exemplary method for establishing a wireless direct link on a parallel channel in accordance with at least one embodiment of the present invention.

FIG. 5 is a flow diagram illustrating an exemplary event-based channel switch process in accordance with at least one embodiment of the present invention.

### DETAILED DESCRIPTION OF THE INVENTION

The following description is intended to convey a thorough understanding of the present invention by providing a number of specific embodiments and details involving the communication of information using multiple wireless channels. It is understood, however, that the present invention is not limited to these specific embodiments and details, which are exemplary only. It is further understood that one possessing ordinary skill in the art, in light of known systems and methods, would appreciate the use of the invention for its intended purposes and benefits in any number of alternative embodiments, depending upon specific design and other needs.

For ease of illustration, the various techniques of the present invention are discussed below in the context of IEEE 802.11-based wireless networking. However, those skilled in the art, using the teachings provided herein, may advantageously implement the disclosed techniques in other wireless networks. Accordingly, reference to techniques and components specific to IEEE 802.11, such as an 802.11-specific frame format or a series of transmissions specific to 802.11, applies also to the equivalent technique or component in other wireless network standards unless otherwise noted. Moreover, various actions standard to IEEE 802.11 and other wireless standards, such as, for example, the transmission of an ACK frame to acknowledge receipt of a frame, are omitted for ease of discussion.

Referring now to FIG. 1, an exemplary wireless system **100** employing one or more exemplary event-based channel switching techniques disclosed herein is illustrated in accordance with at least one embodiment of the present invention.

The system **100** incorporates a general wireless network topology described in IEEE 802.11 and other wireless standards wherein a plurality of wireless devices **102**, **104** are associated with at least one access point **106**. The wireless devices **102**, **104** include devices enabled to communicate wirelessly using one or more protocols. Such protocols may include, for example, the IEEE 802.11 protocols (802.11a/b/e/g/i), ANSI, Hyperlan, etc. Examples of wireless devices may include notebook (or "laptop") computers, handheld computers, desktop computers, workstations, servers, portable digital assistants (PDAs), cellular phones, audio/visual (A/V) consoles, gaming consoles, televisions or other displays, etc. To illustrate, the system **100** may include, for example, a multimedia system having one or more displays, audio/video components (e.g., a digital video disc (DVD) player or a compact disc (CD) player), sound systems, video game consoles, and the like, where each of these components may be wirelessly connected to a central console acting in the capacity of the access point **106**.

The access point **106** may be connected to an infrastructure network **108** or other network, such as, for example, the Internet, a local area network (LAN), a wide area network (WAN), and the like. Thus, wireless devices **102**, **104** may communicate with one or more networked devices on an infrastructure network via the access point **106**. Moreover, the wireless devices **102**, **104** may communicate with each other via conventional wireless links **112**, **114** with the access point **106** or, as discussed in greater detail below, via a wireless direct link **110** between the wireless devices **102**, **104** and optionally other wireless devices. Exemplary techniques for establishing and maintaining a wireless direct link are described below and in U.S. patent application Ser. No. 60/515,701, and U.S. patent application Ser. No. 60/388,569 the entirety of which is incorporated by reference herein.

In a conventional wireless network, information is communicated between wireless devices via an access point. A transmitting wireless device transmits the information to the access point on a base channel. The access point then processes the information, such as by changing the headers of one or more frames representing the information, and forwards the information to the receiving wireless device on the base channel. This use of the access point as the intermediary results in a delay in the overall transmission time for the information, as well as crowds the base channel because two transmissions take place, rather than one. Moreover, these transmissions may have been further delayed due to congestion on the base channel by other transmitting devices. Furthermore, the distances to the access point may be much larger than the distance between the communicating devices, which allows the communicating devices to use much higher data rates on direct communications.

Accordingly, the present invention provides techniques for enabling wireless devices to communicate information directly without use of the access point, while still permitting the transfer of information from the access point to the wireless devices, and vice versa. In at least one embodiment, conventional wireless links **112**, **114** between the access point **106** and the wireless devices **102**, **104**, respectively, may be used to initiate, establish and maintain a wireless direct link **110** between the wireless devices **102**, **104**. The wireless direct link **110** preferably is shifted to a parallel wireless channel (i.e., separate from the base channel) so that the transmission of information via the direct link **110** is not significantly impaired by traffic on the base channel, and vice versa.

## 5

Additionally, in at least one embodiment, the wireless devices **102, 104** may be configured to switch back to the base channel or other wireless channel to receive buffered downlink information or peer-to-peer information from the access point **106** or to transmit uplink information or peer-to-peer information to the access point **106**, for example. The switch between the parallel channel and the base channel may occur in anticipation of a predetermined event, such as the periodic transmission of a delivery traffic indication map (DTIM) beacon frame by the access point **106**, or the switch from the parallel channel to the base channel, or vice versa, may be initiated by either of the wireless devices **102, 104**.

Referring now to FIG. 2, a chart **200** depicting an exemplary event-based channel switching process is illustrated in accordance with at least one embodiment of the present invention. The ordinate **202** of the chart **200** represents time, whereas the abscissa **204** represents at least a portion of the frequency bandwidth in which the system **100** operates. In the illustrated example, base channel **206** represents the wireless channel used by the access point **106** to communicate with the wireless devices **102, 104**, and vice versa. Parallel channel **208** represents a channel used by wireless devices **102, 104**, to shift wireless direct link **110** to.

To illustrate, transmission period **210** may represent a direct link handshake period conducted on the base channel **206** to initiate and establish the direct link **110** on the parallel channel **208** for direct transmission of information between the wireless devices. An exemplary process for initiating and establishing a direct link **110** on a parallel channel is described in greater detail below with reference to FIG. 4. The direct link **110** may be established on parallel channel **208** for any of a variety of reasons, such as to reduce bandwidth congestion by using multiple channels to transmit information or to reduce latency in the transmission of information between the wireless devices **102, 104**. After establishing the direct link **110** on parallel channel **208**, the wireless devices **102, 104** switch to parallel channel **208** at or around time  $t_1$ . The subsequent transmission period **212** may represent a time period wherein information may be communicated between the wireless devices **102, 104** via the direct link **110** on parallel channel **208**. To inform the access point about the temporary absence from the base channel, the wireless devices **102** and **104** transmit a frame to the access point with the PM bit set, to indicate to the access point that they cannot be reached. In reality, the nodes are on the parallel channel and are most likely not in power save, but there is no difference from the viewpoint of the access point because the wireless nodes cannot be reached in either case. The access point will buffer traffic for these nodes in separate power save queues, for later delivery.

Although the wireless devices **102, 104** may directly communicate information via the direct link **110** on parallel channel **208**, the wireless devices **102, 104** may need to return to the base channel **206** or another channel on a periodic basis in order to receive information from the access point **106** or other wireless device and/or to provide uplink information to the access point **106** or peer wireless devices. To illustrate, the wireless devices **102, 104** may be unable to receive information from the access point **106** while their transceivers are tuned to the parallel channel **208** during transmission period **212**. Accordingly, the access point **106** may buffer information intended for the wireless devices **102, 104** during the transmission period **212**. As detailed in many wireless standards, access points typically periodically transmit information that indicates that the access point has buffered information for one or more wireless devices associated with the access point. For example, IEEE 802.11 provides for the

## 6

periodic transmission of a delivery traffic indication map (DTIM) beacon frame every DTIM period or at a target beacon transmission time (TBTT). The traffic indication map of the DTIM beacon frame indicates which wireless devices have information buffered at the access point.

Thus, in one embodiment, wireless devices **102, 104** switch back to the base channel **206** in anticipation of a predetermined event **220** (occurring, for example, at time  $t_2$ ), where the predetermined event **220** may include, for example: the transmission of buffered information, broadcast and/or multicast information by the access point **106** on the base channel **206**; the transmission of an indication of buffered information by the access point **106**, such as, for example, a DTIM beacon frame; and the like. In this instance, the wireless devices **102, 104** may use the indication of buffered information to determine whether they have information buffered at the access point **106** and then may request this information from the access point **106** using, for example, a Power Save (PS)-Poll frame. Thus, the transmission period **214** may represent the transmission of multicast, broadcast, and buffered unicast information from the access point **106** to the wireless devices **102, 104**, the transmission of uplink information from the wireless devices **102, 104** to the access point **106**, the transmission of peer-to-peer information between the wireless devices **102, 104** and other wireless devices, and the like.

At or about time  $t_3$ , the wireless devices **102, 104** may switch back to parallel channel **208** and continue communicating information directly via the direct link **110** during transmission period **216**. Alternatively, the wireless devices **102, 104** may initiate, establish and use a wireless direct link on a different channel. In either instance, the wireless devices **102, 104** may switch back to the base channel **206** in anticipation of another predetermined event **222**, e.g., the transmission of another DTIM map, at or around time  $t_4$ . Once switched to the base channel **206**, information between the access point **106**, the wireless devices **102, 104** and/or other wireless devices may be communicated as described above during transmission period **218**. The process of switching between channels to alternatively transmit information over a direct link on one channel and communicate with the access point **106** or other wireless device on another channel may continue for any number of cycles as appropriate. Note that the direct link can always be used, irrespective of whether the wireless devices **102** and **104** reside on the parallel channel or on the base channel.

Referring now to FIGS. 3-5, an exemplary configuration for wireless devices **102, 104** (illustrated as wireless device **302**), as well as exemplary methods **400** and **500** of its operation are illustrated in accordance with at least one embodiment of the present invention. Although certain actions are attributed to either wireless device **102** or wireless device **104** for ease of reference, those skilled in the art will appreciate that some or all of these actions may be performed by either wireless device **102** or wireless device **104**.

In the illustrated example of FIG. 3, the wireless device **302** (representative of either wireless device **102** or **104**) includes at least a transceiver **304** for transmitting and/or receiving signals representing information, one or more processors **306** and protocol stacks **308** for processing and otherwise preparing information for transmission via the transceiver **304**, as well as for processing information received via the transceiver **304**. The wireless device **302** further may include a multiple channel direct link (MCDL) module **310** for initiating, establishing, and maintaining a one or more wireless direct links on one or more channels, communicating information via the one or more wireless direct links, switching

between channels as appropriate, and other various actions described in detail herein. The MCDL module **310** may be implemented as software, hardware, firmware, or a combination thereof. To illustrate, the MCDL module **310** may be implemented as a software component of the protocol stack **308**, as a separate software program or module executed by the processor **306**, or as a software or hardware component implemented as part of the transceiver **304**.

Referring now to FIG. **4**, an exemplary method **400** for initiating and establishing a wireless direct link on a separate channel is illustrated in accordance with at least one embodiment of the present invention. To initiate a direct link on a channel other than the base channel used by the AP **106**, one of the wireless devices **102**, **104** (device **102** in this example) may transmit a setup request frame to the access point **106** on the base channel for forwarding to the wireless device **104** at step **402**, where the setup request frame represents an invitation or proposal to establish a direct link on another channel. To this end, the setup request frame may include a channel information element (CIE) (e.g., in the payload of the frame), where the CIE may include one or more indicators associated with a proposed channel, such as, for example, the center frequency and channel width of the proposed channel or a low frequency and a high frequency of the proposed channel. The proposed channel may be selected at random, or, in one embodiment, the wireless device **102** may scan one or more potential channels for traffic and select a channel having relatively little or no traffic as the proposed channel.

The setup request may be encapsulated inside a regular data frame, using LLC encapsulation. This method is described in more detail in U.S. patent application Ser. No. 60/515,701, which has been referenced before. Security credentials may also be included inside the setup frames. Due to the encapsulation in a regular data frame, any access point will forward the frame to the ultimate destination without processing the data portion, irrespective of whether the access point knows about this protocol or not. The LLC encapsulation effectively creates a transparent tunnel through the access point.

The access point **106** may process the setup request frame as necessary and forward the setup request frame to the wireless device **104** at step **404**. Access points will usually forward this data frame without additional processing of the payload. Upon receipt of the setup request frame, the wireless device **104** may consider the proposal to establish a direct link on the proposed channel. If acceptable, the wireless device **104** may transmit an affirmative setup response frame to the access point **106** on the base channel for forwarding to the wireless device **102** at step **406**. If the proposal to establish a direct link is acceptable but the proposed channel is not (because, for example, the wireless device **104** cannot operate at the proposed frequency), the wireless device **104** may transmit a conditional setup response frame to the access point **106** on the base channel for forwarding to the wireless device **102**. The conditional setup response frame may include a proposal for an alternate channel for consideration by the wireless device **102**.

If the proposal to establish a direct link is unacceptable (e.g., the wireless device **104** does not have a multiple channel direct link capability), the wireless device **104** may transmit a negative setup response frame to the wireless device **102** indicating that the wireless device **104** has declined to participate in a direct link with the wireless device **102**. In this instance, the wireless device **102** may attempt to set up a direct link **110** on the base channel or it may cease attempts to establish a direct link **110** with the wireless device **104**. In at least one embodiment, the setup response frame includes an

agreed/denied/conditional field that may be used to indicate whether the setup response is affirmative, negative or conditional. If the responding device does not support direct link, it may not recognize the multi channel capability (i.e. the CIE element), and it may respond with a response message that does not include a multi channel capability element (i.e. the CIE element). In this way, a direct link may still be set up, but possibly without the option of being shifted to another channel.

If the setup response frame is affirmative or conditional, the setup response frame may further include an indication that the wireless device **104** is entering a sleep mode or power-saving mode whereby the access point **106** is to buffer all information intended for the wireless device **104** until the access point **106** is polled for the buffered information. The power-saving mode indicator may include, for example, a power management (PM) bit set or cleared in the header of the setup response frame. Upon receipt of the setup response frame, the access point **106** preferably enacts the buffering mechanism if so directed by the power-saving mode indicator and forwards the setup response frame to the wireless device **102** at step **408**.

If the setup response frame is an affirmative response, the wireless device **102** may transmit a setup confirm frame to the access point **106** for forwarding at step **410**. If the response is conditional upon acceptance of the use of the channel proposed by the wireless device **104**, the wireless device **102** may determine whether this proposed channel is acceptable. If so, the wireless device **102** may transmit the setup confirm frame at step **410**. If the response is negative, the wireless device **102** preferably ceases any attempts to establish a direct link. As with the setup response frame, the setup confirmation frame may include an indication (e.g., a set PM bit) that the wireless device **102** is entering a sleep mode or power-saving mode and information intended for the wireless device **102** should be buffered at the access point **106**. Upon receipt of the setup confirm frame, the access point **106** may activate the buffering mechanism and forward the setup confirm frame to the wireless device **104** on the base channel at step **412**.

Upon transmitting the setup confirm frame at step **410**, in one embodiment, the wireless device **102** switches its transceiver **304** to the agreed-to channel and waits for the arrival of the wireless device **104** at step **414**. Likewise, the wireless device **104** switches its transceiver **304** to the proposed channel upon receipt of the setup confirm frame at step **416**. To announce its presence on the proposed channel, the wireless device **104** may transmit an announcement frame on the proposed channel directly to the wireless device **102** at step **418**. At this point, the direct link **110** may be considered to be established and the wireless devices **102**, **104** may initiate the communication of information on the parallel channel via the direct link **110** at step **420**.

In another embodiment, devices **102** and/or **104** do not set the PM bit on the direct link handshake frames, but separate frames with the PM bit set are transmitted instead. These frames may be Null frames or regular data frames. Shifting the direct link to another channel is postponed until after the transmission of these separate PM frames. Shifting the direct link may be accomplished by a permanent or temporary channel switch, which are discussed in detail below. The direct link handshake may still include a multi channel capability or a set of supported channels to which the direct link could be transferred.

There may be a delay between when the wireless device **102** switches to the parallel channel and when the wireless device **104** switches. In one embodiment, the wireless device **102** may use this waiting period to scan the parallel channel to

listen for traffic on the parallel channel. The arrival of wireless device **104** may be announced by the transmission of a first frame, which opens the direct link on the new channel. If the scan reveals that there is excessive traffic, the wireless device **102** may suspend or cancel the direct link by transmitting, for example, a slow resumption mode (SRM) frame or a fast resumption mode (FRM) frame, or the wireless device **104** may transmit a channel switch request to the wireless device **104** once the wireless device **104** has switched to the parallel channel, where the channel switch request represents a proposal to switch the direct link to another parallel channel. Permanent and temporary channel switch requests are discussed in detail below.

During the direct link setup phase described above, peer-to-peer traffic through the access point is preferably temporarily suspended to avoid any reordering of frames waiting at the access point **106**. As noted above, the wireless devices **102, 104** may use a power-saving mode indicator, such as, for example, the PM bit, to notify the access point **106** that the devices **102, 104** are entering a power-save mode and therefore directing the access point **106** to buffer downlink data until it is requested from the wireless devices via, for example, power mode-poll (PM-Poll) frames as described by IEEE 802.11.

Referring now to FIG. 5, an exemplary event-based channel switch process **500** is illustrated in accordance with at least one embodiment of the present invention. In the illustrated example, the method **500** initiates at steps **502A** and **502B** wherein the wireless devices **102, 104** switch from the parallel channel (established using method **400** of FIG. 4, for example) to the base channel of the access point **106** in anticipation of, or in preparation for, a predetermined event. In the illustrated example, the predetermined event includes the transmission of a DTIM beacon frame at steps **504A, 504B**. As described above, DTIM beacon frames typically are transmitted substantially periodically (i.e., every DTIM beacon interval) and include a bitmap that indicates which wireless devices have information buffered at the access point **106**. Thus, it generally is desirable for the wireless devices **102, 104** to switch to the base channel to receive the DTIM beacon frames so that the wireless devices **102, 104** may determine whether there is information waiting for them at the access point **106**. Accordingly, the wireless devices **102, 104** preferably switch to the base channel slightly before the DTIM beacon is scheduled to be transmitted to help ensure that the wireless devices **102, 104** are switched to the base channel in time to receive the DTIM beacon frame. Moreover, the wireless devices **102, 104** may remain on the base channel after receiving the DTIM beacon frame the transmission of broadcast and multicast information (steps **506A** and **506B**) typically follows the transmission of a DTIM beacon frame.

In at least one embodiment, the wireless devices **102, 104** are configured to switch back to the parallel channel at steps **508A** and **508B** after receiving the DTIM beacon frame and any multicast/broadcast information. If one or both of the wireless devices **102, 104** determine that they have buffered information at the access point **106** using the DTIM beacon frame, the wireless device (device **102** in this example) may transmit a permanent channel switch (PCS) request frame on the parallel channel with a request to switch back to the parallel channel to the other wireless device at step **510**. In this case, the PCS request frame represents a request to switch to a proposed channel and includes one or more indicators of the proposed channel, such as, for example, the center frequency and channel width or a low frequency and a high frequency for the proposed channel. If the proposed channel switch is acceptable to the receiving wireless device (device

**104** in this example), the receiving wireless device sends an affirmative PCS response frame on the parallel channel at step **512**. If the proposed channel switch is unacceptable (e.g., the receiving wireless device cannot operate at the proposed frequency), the receiving wireless device may transmit a conditional PCS response frame having an alternate proposed channel or a negative PCS response frame if no alternate channel is acceptable. If conditional, the wireless devices **102, 104** negotiate an channel acceptable to both wireless devices **102, 104** or if negative, the wireless devices **102, 104** may cease communicating on the parallel channel and return to the base channel.

In another embodiment, a parallel channel may have been agreed upon during the setup phase and the PCS request may not contain an explicit channel information element. The receipt of a PCS request simply indicates in that case that a switch to the other channel is requested, i.e. the parallel channel if transmitted on the base channel and the base channel if transmitted on the parallel channel.

In another embodiment, the wireless devices **102, 104** may stay on the base channel after the end of the broadcast and multicast transmissions, while returning to the parallel channel is signaled by an explicit PCS request.

The PCS request and response frames preferably are transmitted as quality-of-service (QoS) frames having a piggyback contention-free-acknowledgement (CF-Ack) as this type of frame typically requires only a single transmission operation (TXOP). Examples of suitable piggyback frames that may be implemented as PCS request and/or response frames are described in detail in U.S. patent application Ser. No. 10/880,367 filed concurrently herewith and entitled "Link Margin Notification Using Return Frame." Other frame formats, such as conventional data frames, may be used without departing from the spirit or the scope of the present invention.

Upon agreeing to a proposed switch to the base channel, the wireless devices **102, 104** make the channel switch at steps **514A, 514B**. One or both of the wireless devices **102, 104** then may request and receive buffered information from the access point **106**, provide uplink information to the access point **106**, and/or communicate information with peer wireless devices via the base channel. To illustrate, the wireless device **102** may use a reverse polling technique by transmitting a PS-Poll frame (e.g., a QoS+CF+Poll frame) to the access point **106** at step **516**, where the PS-Poll frame represents a request for buffered information and an indication (e.g., a clearing of the PM bit) that the wireless device **102** has exited the power-saving mode. In response to the PS-Poll frame, the access point **106** may transmit buffered downlink information to the wireless device **102** at step **518**. After the wireless device **102** has received the buffered downlink information (as indicated by the expiration of an uplink or downlink timeout), the wireless device **102** may transmit another frame, such as a null frame, to the access point **106** at step **520**, where the frame includes an indicator that the wireless device **102** is entering the power-saving mode so that the access point **106** may buffer any downlink information intended for the wireless device **102**. Uplink information and peer-to-peer information may be transmitted from the wireless devices **102, 104** in a similar manner.

To return to the parallel channel to resume communicating via the direct link **110**, one of the wireless devices (device **102** in this example) may transmit a PCS request frame on the base channel at step **522**, where the PCS request frame may include an indication of the proposed channel to which the wireless devices **102, 104** are to switch. Preferably, the wireless devices **102, 104** switch to the same parallel channel as

11

before. However, it may be appropriate to switch to another channel because, for example, the original parallel channel has become congested with traffic from other wireless devices or significant interference as appeared at one or more frequencies of the original parallel channel.

If the proposed channel is acceptable to the receiving wireless device (device **104** in this example) or if an alternate channel is to be proposed, the wireless device **104** may transmit an affirmative or conditional PCS response frame to the wireless device **102** on the base channel at step **524**. After agreeing to the channel switch, the wireless devices switch to the proposed parallel channel and recommence the communication of information between the wireless devices **102**, **104** via the direct link **110** on the parallel channel at step **528**.

In addition or as an alternate to using a PCS sequence to switch channels, the wireless devices **102**, **104** may utilize a temporary channel switch (TCS) sequence to temporarily move the direct link **110** to another channel. The TCS sequence typically includes a TCS request frame that may include a CIE and a timing synchronization function (TSF) to indicate the time at which the direct link **110** is scheduled to return to the current channel. The TCS sequence also may include a TCS response frame that includes an agreed/denied/conditional field similar to the field used for the PCS response frame. If the responding wireless device can not leave the current channel, for instance if it is not yet in a power-save mode with the access point **106**, it may set the denied field inside the TCS response frame. Otherwise, if the responding wireless device is ready to move to the proposed channel, it may set the agreed field inside the TCS response frame.

The TCS sequence also may be used to temporarily move the direct link **110** to the base channel for the exchange of information with the access point **106** (e.g., buffered information) or with peer devices. The direct link **110** preferably remains active during this time, so that information can be exchanged via the direct link **110** on the base channel as well. Devices **102** and **104** should not leave the power save state with the access point during this temporary stay on the base channel (for instance, by transmitting a frame to the access point with the PM bit reset), because it can not be ensured that they will be able to re-enter the power save state prior to the scheduled departure to the parallel channel with TCS.

Although the above techniques are described in the context of a direct link established between two devices, in some cases, multiple devices each may establish a direct link with a single device. The presence of multiple direct links raises the issue of selecting a common parallel channel for the multiple direct links. In one embodiment, the wireless device acting as the "hub" for the multiple peer devices may identify a suitable parallel channel that the multiple direct links may use by, for example, proposing a parallel channel currently in use, by scanning one or more other parallel channels, or by picking a channel at random. Another issue raised by multiple direct links includes channel switching. In one embodiment, if a device having multiple direct links wants to perform a channel switch, it preferably transmits a PCS request frame to each of the other direct link peer devices before switching to the proposed channel.

Yet another issue includes the implementation of power saving or the sleep mode. In one embodiment, this issue may be addressed by assuming that the traffic pattern has a star topology, so that there is a central node that communicates with the peripheral nodes, but the peripheral nodes do not communicate with each other. Under this assumption, the central node may be treated as a constantly awake node (CAN) that acts as a surrogate access point by buffering information for all of the peripheral nodes, while maintaining a client association with the real access point at the same time.

12

The peripheral nodes find can find the central node through its beacon transmissions and may associate with it instead of with the access point. The peripheral nodes then may use reverse polling to retrieve buffered information, as described above. This solution is suited for applications like gaming and multimedia, where a single central node maintains connections with several remote nodes, like game controllers or actuators, respectively.

Other embodiments, uses, and advantages of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. The specification and drawings should be considered exemplary only, and the scope of the invention is accordingly intended to be limited only by the following claims and equivalents thereof.

What is claimed is:

**[1.** In an 802.11x wireless network comprising an access point logically connected to at least a first wireless device and a second wireless device, a method of establishing a point-to-point connection directly between the first and second wireless devices comprising:

    sending a setup request frame from the first wireless device to the second wireless device on a first communication channel via the access point, the setup request frame including a proposed second communication channel;

    sending a setup response frame from the second wireless device to the first wireless device on the first communication channel via the access point; and

    communicating information directly between the first and second wireless devices on the second communication channel for a first time period.]

**[2.** The method as in claim **1**, further comprising: switching the first and second wireless devices from the second channel to the first channel in anticipation of a predetermined event; and

    communicating information between the access point and at least one of the first and second wireless devices via the first channel for at least a portion of a second time period.]

**[3.** The method as in claim **2**, further comprising: switching the first and second wireless devices from the second channel to the first channel prior to the second time period.]

**[4.** The method as in claim **2**, further comprising: switching the first and second wireless devices from the second channel to a third channel; and communicating, for a third time period, information directly between the first and second wireless devices the second channel.]

**[5.** The method as in claim **4**, wherein switching the wireless devices to the third channel comprises:

    providing a setup confirmation from the first wireless device to the second wireless device via the access point, the setup confirmation confirming the suitability of a wireless direct link on the third channel;

    switching the first wireless device to the third channel subsequent to the transmission of the setup confirmation; and

    switching the second wireless device to the third channel subsequent to the receipt of the setup confirmation.]

**[6.** The method as in claim **5**, wherein establishing the second wireless direct link on the third channel comprises:

    providing, on the second channel, a setup request from the first wireless device to the second wireless device via the access point, the setup request including one or more identifiers of the third channel; and

## 13

providing, on the second channel, an affirmative setup response from the second wireless device to the second wireless device via the access point in response to a receipt of the setup request at the second device; wherein the setup confirmation is provided in response to a receipt of the affirmative setup response at the first wireless device.]

[7. The method as in claim 6, wherein the one or more identifiers of the third channel includes a center frequency and a channel width.]

[8. The method as in claim 7, further comprising: scanning at least one channel to identify an unused channel, the unused channel being selected as the third channel.]

[9. The method as in claim 7, further comprising: randomly selecting one of a plurality of channels as the third channel.]

[10. The method as in claim 2, wherein the predetermined event includes a substantially periodic event.]

[11. The method as in claim 10, wherein the predetermined event includes a periodic transmission of an indication of information buffered at the access point, wherein at least a portion of the buffered information is intended for receipt by at least one of the first and second wireless devices.]

[12. The method as in claim 11, wherein the indication from the access point includes a delivery traffic indication map (TIM) beacon frame.]

[13. The method as in claim 10, wherein the predetermined event includes the delivery of broadcast and multicast data.]

[14. The method as in claim 1, wherein the second channel includes a base channel for communicating information between the access point to at least the first and second wireless devices.]

[15. In an 802.11x wireless network comprising an access point operably connected to at least a first wireless device and a second wireless device, a method of establishing a direct point-to-point connection between the two wireless devices comprising:

providing information between the access point and at least one of the first and second wireless devices via a first channel for at least a portion of a first period;

providing a channel change request from the first wireless device to the second wireless device on the first channel; providing an affirmative response to the channel change request from the second wireless device to the first wireless device on the first channel;

switching the second wireless device to a second channel subsequent to the receipt of the acknowledgement to the provision of the affirmative response to the channel change request;

switching the first wireless device to the second channel subsequent to the transmission of the acknowledgement to the receipt of the affirmative response to the channel change request; and

communicating information directly between the first and second wireless devices via the second channel for at least a portion of a second period,

wherein the 802.11x wireless network is configured to facilitate communications in an 802.11x protocol, and wherein the first channel is different than the second channel.]

[16. The method as in claim 15, wherein the channel change request includes an indication of a proposed center frequency and channel width for the second channel and wherein the affirmative response to the channel change request includes an affirmation of the proposed center frequency and channel width for the second channel.]

## 14

[17. The method as in claim 15, wherein the information communicated during at least a portion of the second period includes information buffered at the access point during the first period and having at least one of the first and second wireless devices as an intended recipient.]

[18. The method as in claim 15, wherein the first and second wireless devices switch from the first channel to the second channel in anticipation of a predetermined event.]

[19. The method as in claim 18, wherein the predetermined event includes a substantially periodic event.]

[20. The method as in claim 19, wherein the predetermined event includes a periodic transmission of an indication of information buffered at the access point, wherein at least a portion of the buffered information is intended for receipt by at least one of the first and second wireless devices.]

[21. The method as in claim 20, wherein the indication from the access point includes a delivery traffic indication map (TIM) frame.]

[22. In a wireless network having an access point, at least one wireless device comprising:

a transceiver; and

a direct link module operably connected to the transceiver and configured to:

facilitate an establishment of a wireless direct link between the wireless device and another wireless device on the network via a second frequency channel;

communicate information with the other wireless device via the wireless direct link on the second frequency channel for at least a portion of a first period;

switch the transceiver from the second frequency channel to a base channel in anticipation of a predetermined event; and

communicate information with the access point via the base channel for at least a portion of a second period, wherein the second frequency channel is different than the base channel.]

[23. The wireless device as in claim 22, wherein the direct link module is adapted to facilitate the establishment of the wireless direct link by:

providing a channel setup request to the other wireless device via the access point and the base channel;

receiving an affirmative response to the setup request from the other wireless device via the base channel;

providing a setup confirmation to the other wireless device via the base channel; and

tuning the transceiver to the second channel subsequent to the provision of the setup confirmation.]

[24. The wireless device as in claim 23, wherein the setup request includes an indication of a proposed center frequency and channel width for the second channel.]

[25. The wireless device as in claim 22, wherein the direct link module is adapted to facilitate the establishment of the wireless direct link by:

receiving a channel setup request from the other wireless device via the access point and the base channel;

providing an affirmative response to the setup request to the other wireless device via the base channel;

receiving a setup confirmation from the other wireless device via the base channel; and

tuning the transceiver to the second channel subsequent to the receipt of the setup confirmation.]

[26. The wireless device as in claim 25, wherein the setup request includes an indication of a proposed center frequency and channel width for the second channel.]

15

**[27.** The wireless device as in claim 26, wherein the direct link module is adapted to facilitate the establishment of the wireless direct link by:

providing a channel change request to the other wireless device via the access point;  
receiving an affirmative response to the channel request from the other wireless device via the access point;  
tuning the transceiver to the second channel subsequent to the receipt of the affirmative response.]

**[28.** The wireless device as in claim 22, wherein the direct link module is adapted to facilitate the establishment of the wireless direct link by:

receiving a channel change request from the other wireless device via the access point;  
providing an affirmative response to the channel request to the other wireless device via the access point; and  
tuning the transceiver to the second channel subsequent to the provision of the affirmative response.]

**[29.** The wireless device as in claim 22, wherein the predetermined event includes a substantially periodic event.]

**[30.** The wireless device as in claim 29, wherein the predetermined event includes a periodic transmission of an indication of information buffered at the access point during the first period, wherein at least a portion of the buffered information is intended for receipt by at least one of the first and second wireless devices.]

**[31.** The wireless device as in claim 30, wherein the indication from the access point includes a delivery traffic indication map (TIM) frame.]

**[32.** The wireless device as in claim 22, further comprising:  
at least one processor; and  
wherein the direct link module includes executable instructions adapted to manipulate the processor to:  
facilitate the establishment of the wireless direct link;  
communicate information with the other wireless device via the wireless direct link;  
switch the transceiver from the first channel to the base channel in anticipation of the predetermined event; and  
communicate information with the access point via the wireless direct link on the base channel.]

**[33.** A wireless system comprising:  
an access point; and  
at least a first wireless device and a second wireless device;  
wherein the first wireless device and the second wireless device are configured to:  
communicate information via a wireless direct link on a first channel during at least a portion of a first period;  
switch to a second channel in anticipation of a predetermined event; and  
communicate information with the access point on the second channel during at least a portion of a second period,  
wherein the first channel is different than the second channel.]

**[34.** The wireless system as in claim 33, wherein the predetermined event includes a substantially periodic event.]

**[35.** The wireless system as in claim 34, wherein the predetermined event includes a periodic transmission of an indication of information buffered at the access point during the first period, wherein at least a portion of the buffered information is intended for receipt by at least one of the first and second wireless devices.]

16

**[36.** The wireless system as in claim 35, wherein the indication from the access point includes a delivery traffic indication map (DTIM) frame.]

*37. A method comprising:*

*5 sending, from a first wireless device, a setup request frame to a second wireless device on a first communication channel via an access point, wherein the setup request frame comprises a proposed second communication channel;*

*10 receiving a setup response frame, at the first wireless device from the second wireless device, on the first communication channel via the access point, wherein the setup response frame comprises a proposed third communication channel;*

*15 sending, from the first wireless device, a setup confirm frame to the second wireless device on the first communication channel via the access point; and  
communicating information directly between the first wireless device and the second wireless device on the third communication channel.*

*38. The method of claim 37, further comprising returning to the first communication channel after a time period.*

*25 39. The method of claim 37, wherein the setup confirm frame comprises an indication to the access point that the first wireless device is entering a power-saving mode.*

*40. The method of claim 37, further comprising:  
returning to the first communication channel after a time period; and  
30 receiving, at the first wireless device, buffered data from the access point.*

*41. The method of claim 37, further comprising:  
scanning the third communication channel;  
determining an amount of traffic on the third communication channel; and  
35 suspending use of the third communication channel by the first wireless device and the second wireless device based upon the amount of traffic on the third communication channel.*

*42. The method of claim 41, further comprising transmitting a channel switch request based upon the amount of traffic on the third communication channel, wherein the channel switch request comprises a proposed fourth communication channel.*

*45 43. The method of claim 37, further comprising:  
periodically returning to the first communication channel for a period of time; and  
returning to the third communication channel after the period of time.*

*50 44. A wireless device comprising:  
one or more processors configured to:  
control sending, to another wireless device, a setup request frame on a first communication channel via an access point, wherein the setup request frame comprises a proposed second communication channel;  
55 control receiving a setup response frame from the other wireless device on the first communication channel via the access point, wherein the setup response frame comprises a proposed third communication channel;  
control sending a setup confirm frame to the other wireless device on the first communication channel via the access point; and  
control communicating information directly with the other wireless device on the third communication channel.*

*65 45. The wireless device of claim 44, wherein the one or more processors are further configured to control returning to the first communication channel after a time period.*

46. The wireless device of claim 44, wherein the setup confirm frame comprises an indication to the access point that the wireless device is entering a power-saving mode.

47. The wireless device of claim 44, wherein the one or more processors are further configured to:

control returning to the first communication channel after a time period; and

control receiving buffered data from the access point.

48. The wireless device of claim 44, wherein the one or more processors are further configured to:

control scanning the third communication channel; determine an amount of traffic on the third communication channel; and

suspend use of the third communication channel by the wireless device and the other wireless device based upon the amount of traffic on the third communication channel.

49. The wireless device of claim 48, wherein the one or more processors are further configured to control transmitting a channel switch request based upon the amount of traffic on the third communication channel, wherein the channel switch request comprises a proposed fourth communication channel.

50. The wireless device of claim 44, wherein the one or more processors are further configured to:

control periodically returning to the first communication channel for a period of time; and

control returning to the third communication channel after the period of time.

51. A non-transitory computer-readable medium having instructions stored thereon, the instructions comprising:

instructions to control sending, to another wireless device, a setup request frame on a first communication channel via an access point, wherein the setup request frame comprises a proposed second communication channel;

instructions to control receiving a setup response frame from the other wireless device on the first communication

channel via the access point, wherein the setup response frame comprises a proposed third communication channel;

instructions to control sending a setup confirm frame to the other wireless device on the first communication channel via the access point; and

instructions to control communicating information directly with the other wireless device on the third communication channel.

52. The non-transitory computer-readable medium of claim 51, further comprising instructions to control returning to the first communication channel after a time period.

53. The non-transitory computer-readable medium of claim 51, wherein the setup confirm frame comprises an indication to the access point that the wireless device is entering a power-saving mode.

54. The non-transitory computer-readable medium of claim 51, further comprising instructions to:

instructions to control returning to the first communication channel after a time period; and

instructions to control receiving buffered data from the access point.

55. The non-transitory computer-readable medium of claim 51, further comprising:

instructions to control scanning the third communication channel;

instructions to determine an amount of traffic on the third communication channel; and instructions to suspend use of the third communication channel by the wireless device and the other wireless device based upon the amount of traffic on the third communication channel.

56. The non-transitory computer-readable medium of claim 55, further comprising instructions to control transmitting a channel switch request based upon the amount of traffic on the third communication channel, wherein the channel switch request comprises a proposed fourth communication channel.

\* \* \* \* \*