

US00RE45304E

(19) **United States**
(12) **Reissued Patent**
Dole et al.

(10) **Patent Number:** **US RE45,304 E**
(45) **Date of Reissued Patent:** **Dec. 30, 2014**

(54) **PIPE COUPLING HAVING MOVABLE GRIPPING BODIES**

1,662,954 A * 3/1928 Broido et al. 285/332.3
1,791,810 A 2/1931 Furman
1,821,863 A 9/1931 Wilson
1,930,194 A 10/1933 Dillon 285/104
2,028,182 A 1/1936 Barnickol, Jr. 285/112

(75) Inventors: **Douglas R. Dole**, Whitehouse Station, NJ (US); **Michael V. Porter**, Easton, PA (US); **Torrey G. Sipos**, Catasauqua, PA (US)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Victaulic Company**, Easton, PA (US)

CA 2686708 C 11/2008
GB 2240600 A 8/1991
WO 2008144332 A1 11/2008

(21) Appl. No.: **13/415,086**

(22) Filed: **Mar. 8, 2012**

OTHER PUBLICATIONS

Related U.S. Patent Documents

Santella, Lena; Examiner's Report from corresponding Canadian patent application No. 2,686,708; May 17, 2011; pp. 1-4; Canadian Intellectual Property Office.

Reissue of:

(64) Patent No.: **7,950,701**
Issued: **May 31, 2011**
Appl. No.: **12/119,661**
Filed: **May 13, 2008**

(Continued)

U.S. Applications:

(60) Provisional application No. 60/938,003, filed on May 15, 2007.

Primary Examiner — Daniel P Stodola

Assistant Examiner — Fannie Kee

(74) *Attorney, Agent, or Firm* — Ballard Spahr LLP

(51) **Int. Cl.**
F16L 23/00 (2006.01)

(52) **U.S. Cl.**
USPC **285/367**; 285/253; 285/368; 285/411;
285/412; 285/420

(58) **Field of Classification Search**
USPC 285/252–253, 364–368, 411–413,
285/419–420

See application file for complete search history.

(57) **ABSTRACT**


A coupling for securing pipe elements together in end-to-end relation has segments joined end-to-end by adjustable connection members. The segments surround a central space which receives the pipe elements. One or more gripping bodies are captured between the segments. The gripping bodies are arranged opposite to each other. The segments have angularly oriented reaction surfaces on the connection members. The gripping bodies have angularly oriented contact surfaces which interface with the reaction surfaces. When the segments are drawn toward each other by the connection members, interaction between the reaction surfaces and the contact surfaces forces the gripping bodies radially inwardly. Inwardly facing arcuate surfaces on the segments and the gripping bodies engage and retain the pipe elements.

(56) **References Cited**

U.S. PATENT DOCUMENTS

591,796 A * 10/1897 De Wolf 285/253
711,946 A * 10/1902 Day 285/58
1,004,634 A * 10/1911 Dixon 285/114
1,532,596 A * 4/1925 Madsen 24/284

32 Claims, 14 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,165,920	A	7/1939	Burnip	
2,473,046	A	6/1949	Adams, Jr.	285/383
2,512,741	A *	6/1950	Goodall	248/309.4
3,003,793	A	10/1961	Pitt	285/112
3,078,108	A	2/1963	Smith	285/104
3,116,078	A	12/1963	Scherer	285/104
3,249,371	A *	5/1966	Peterman	285/253
3,329,446	A	7/1967	Katis et al.	285/112
3,351,352	A	11/1967	Blakeley et al.	
4,417,755	A	11/1983	Gittleman	285/373
4,438,954	A	3/1984	Hattori	285/104
4,611,835	A *	9/1986	Gittleman	285/125.1
4,611,839	A	9/1986	Rung et al.	
4,639,020	A	1/1987	Rung et al.	
4,729,582	A	3/1988	Zeidler	285/104
5,037,141	A	8/1991	Jardine	285/148.26
5,058,931	A	10/1991	Bowsher	285/112
5,121,946	A *	6/1992	Jardine	285/15
5,161,836	A *	11/1992	McKinnon	285/373
5,188,401	A	2/1993	Staniforth	
5,230,537	A	7/1993	Newman	
5,295,716	A	3/1994	Bridges	
5,605,357	A *	2/1997	Bird	285/15
5,722,701	A	3/1998	Choi	285/337
5,758,907	A	6/1998	Dole et al.	
5,769,467	A	6/1998	Bridges	
5,772,253	A *	6/1998	Hodge et al.	285/15
6,367,849	B1 *	4/2002	Tatsuta et al.	285/373
6,499,771	B1	12/2002	Snyder, Sr. et al.	
7,086,131	B2	8/2006	Gibb et al.	
7,107,662	B1	9/2006	Levario	
7,390,026	B2	6/2008	Noda	285/112
7,401,819	B2	7/2008	Gibb et al.	
7,712,796	B2	5/2010	Gibb et al.	
2005/0104369	A1	5/2005	Webb et al.	285/104
2005/0258641	A1	11/2005	Gibb	

OTHER PUBLICATIONS

Santella, Lena; Examiner's Report from corresponding Canadian patent application No. 2,686,708; Jul. 29, 2011; pp. 1-4; Canadian Intellectual Property Office.

No Author; Notice of Acceptance for corresponding Canadian patent application No. 2,686,708; Dec. 5, 2011; 1 page; Canadian Intellectual Property Office.

Dauvergne, Bertrand; Supplementary European Search Report and European Search Opinion from corresponding European patent application No. EP08755442; European Patent Office, Apr. 6, 2010; pp. 1-6.

Young, Lee W.; PCT Written Opinion of the International Searching Authority from corresponding International patent application No. PCT/US08/63587; Sep. 15, 2008; pp. 1-7.

Santella, Lena; Examiner's Report from related Canadian Patent Application No. 2,686,708; Canadian Intellectual Property Office; Apr. 11, 2011; pp. 1-17.

Kee, Fannie C; Non-Final Office Action from related U.S. Appl. No. 13/113,124; United States Patent and Trademark Office, Dec. 27, 2011; pp. 1-9.

Dunwoody, Aaron; Notice of Allowability from related U.S. Appl. No. 13/113,124; United States Patent and Trademark Office, Feb. 27, 2012; pp. 1-4.

Afzali, Sarang; Non-Final Office Action from related U.S. Appl. No. 13/011,199; United States Patent and Trademark Office, Feb. 8, 2012; pp. 1-10.


Double Bolt Clamp With Saddles Mar. 15, 2012, [online], [retrieved on Mar. 15, 2012] Retrieved from Dixon Valve & Coupling website using Internet <URL:http://www.dixonvalve.com/product/1360.html>.



Author Unknown; Translation of Chinese Search Report from corresponding Chinese patent application No. 201210269704.X; pp. 1-3; Jan. 22, 2014; State Intellectual Property Office of People's Republic China; Beijing, China.

Supplementray European Search Report for European Patent Application No. EP 08755442.4 Dated Mailed Apr. 6, 2010.

PCT/US08/63587—Sep. 15, 2008—Written Opinion.

* cited by examiner








FIG. 4




FIG. 4A







FIG. 4B











FIG. 8





Amended




FIG. 13





FIG. 14






FIG. 16




FIG. 17
Amended

1

PIPE COUPLING HAVING MOVABLE GRIPPING BODIES

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS-REFERENCE TO RELATED APPLICATION

This application is based on and claims priority to U.S. Provisional patent application No. 60/938,003, filed May 15, 2007.

FIELD OF THE INVENTION

This invention relates to couplings for joining pipe elements in end-to-end relationship.

BACKGROUND OF THE INVENTION

Mechanical couplings for joining pipe elements end-to-end find widespread use throughout a broad spectrum of industries such as the chemical industry, the petroleum industry and mining, as well as in municipal water service and fire suppression systems for buildings and other structures.

An example of a prior art coupling currently in use is provided in U.S. Pat. No. 7,086,131, which discloses a coupling having a pair of coupling segments joined end-to-end by fasteners received in lugs at each end of the segments. A sealing member is positioned between the segments. The coupling is pre-assembled at the factory. The segments are designed and sized to receive pipe elements in the field which are inserted directly between the coupling segments in the pre-assembled state, without the need to disassemble and reassemble the coupling. After insertion of the pipe elements, the fasteners are tightened to effect a fluid-tight, mechanically restrained joint between the pipe elements.

While it is advantageous to pre-assemble such couplings because it saves time and thereby cost during construction, power tools are often used to tighten the fasteners for convenience, as they are faster and less fatiguing. Power tools are of limited value, however, where no source of electrical power or compressed air is available, even those tools which are battery operated. Furthermore, power tools which cause electrical sparking may not be used in environments, such as mines, where explosive conditions may exist. It would be advantageous to provide a pipe coupling which can be pre-assembled (and thereby secure the cost advantages and convenience of such couplings) while being easily manually tightened by workmen installing the couplings. It is further advantageous to decrease the stiffness of the joint formed by the coupling for certain applications. This can be accomplished by employing couplings according to the invention.

SUMMARY OF THE INVENTION

The invention concerns a pipe coupling for securing end portions of a pair of pipe elements together end-to-end. In one embodiment, the coupling comprises a plurality of segments connectable end-to-end surrounding a central space for receiving the pipe elements. Each segment has a pair of arcuate surfaces positioned in spaced relation, the arcuate surfaces facing the central space and being engagable with the pipe elements. Connection members are positioned at opposite

2

ends of each of the segments for adjustably connecting the segments to one another. The connection members are adjustably tightenable for drawing the segments toward one another and into engagement with the pipe elements. Respective reaction surfaces are positioned on at least two of the connection members which face one another. The reaction surfaces face the central space. At least one gripping body is positioned between two of the segments. The gripping body has a pair of gripping surfaces positioned in spaced apart relation. The gripping surfaces face the central space for engagement with the pipe elements. A first pair of contact surfaces is positioned on the gripping body in facing relation with the reaction surfaces. Adjustable tightening of the connection members draws the coupling segments together. The contact surfaces interact with the reaction surfaces to move the gripping body into the central space for engagement of the gripping surfaces with the pipe elements.

The reaction surfaces are angularly oriented with respect to the projections. Orientation angles for the reaction surfaces from about 30° to about 60° are feasible, with 45° being preferred. The contact surfaces are also angularly oriented with respect to the projections. Orientation angles for the contact surfaces from about 30° to about 60° are feasible, with 45° being preferred.

In one embodiment of the coupling, the contact surfaces project radially outwardly away from the central space. In another embodiment, the gripping bodies have a second pair of contact surfaces. The first and second pairs of contact surfaces are positioned on opposite sides of the gripping body.

In another embodiment, the coupling comprises a plurality of segments connectable end-to-end surrounding a central space for receiving the pipe elements. Each segment has a pair of arcuate surfaces in spaced relation. The arcuate surfaces face the central space and are engagable with the pipe elements. Connection members are positioned at opposite ends of each of the segments for adjustably connecting the segments to one another. The connection members are adjustably tightenable for drawing the coupling segments toward one another and into engagement with the pipe elements. First and second reaction surfaces are positioned at opposite ends of each coupling segment in spaced relation. The reaction surfaces face the central space. First and second gripping bodies are positioned between the segments at opposite ends thereof. Each of the gripping bodies has a pair of gripping surfaces positioned in spaced relation to each other. The gripping surfaces face the central space and are engagable with the pipe elements. Each of the gripping bodies has a plurality of contact surfaces positioned in spaced relation. Each of the contact surfaces is engaged with one of the reaction surfaces of the segments. Each of the gripping bodies has end faces positioned opposite to one another. The segments have inwardly projecting shoulders positioned adjacent to the reaction surfaces. The shoulders are engagable with the end faces. Either the end faces or the shoulders or both are angularly oriented so as to cause rotation of the gripping bodies about an axis substantially perpendicular to the pipe elements when the coupling segments are drawn together. Adjustable tightening of the connection members draws the coupling segments together. The contact surfaces interact with the reaction surfaces to move the gripping bodies radially inwardly for engagement of the gripping surfaces with the pipe elements.

In one embodiment, the reaction surfaces extend in a tangential direction of the segments. In another embodiment, the gripping bodies comprise a channel adapted to receive a sealing member. The channel is skewed relatively to the gripping

3

surfaces so as to substantially align with the sealing member upon rotation of the gripping bodies.

Another embodiment of the pipe coupling according to the invention comprises a plurality of segments connectable end-to-end. The segments surround a central space. Each segment has first and second arcuate grooves in spaced relation facing the central space. Connection members are positioned at opposite ends of each of the segments for adjustably connecting the segments to one another. The connection members are adjustably tightenable for drawing the segments toward one another. First and second reaction surfaces are positioned at opposite ends of each coupling segment in spaced relation to one another. The reaction surfaces face the central space. First and second gripping bodies are positioned between the segments at opposite ends thereof. Each of the gripping bodies has first and second arcuate grooves positioned in spaced relation. The grooves face the central space. Each of the gripping bodies has a plurality of contact surfaces positioned in facing relation with the reaction surfaces. Each of the contact surfaces is engaged with one of the reaction surfaces on each of the segments. First and second retainers are received within the grooves of the couplings. Each of the retainers comprises an annular band having a plurality of teeth extending radially inwardly. Each annular band is split so as to permit radial motion of the teeth when the band is radially compressed. The first retainer is received within the first grooves in the coupling segments and the gripping bodies and the second retainer is received within the second grooves in the coupling segments and the gripping bodies. The teeth of the first retainer are angularly oriented toward the teeth of the second retainer, and the teeth of the second retainer are angularly oriented toward the teeth of the first retainer. Adjustable tightening of the connection members draws the coupling segments together. The contact surfaces interact with the reaction surfaces to move the gripping bodies radially inwardly for compressing the retainers into engagement with the pipe elements. Preferably, the reaction surfaces extend in a tangential direction of the segments.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded isometric view of an embodiment of a coupling according to the invention;

FIGS. 2 and 3 are cross-sectional views of the coupling shown in FIG. 1;

FIG. 4 is an isometric view of the coupling shown in FIG. 1;

FIGS. 4A and 4B are isometric views of alternate embodiments of a coupling according to the invention;

FIG. 5 is an exploded isometric view of another embodiment of a coupling according to the invention;

FIGS. 6 and 7 are elevational views of the coupling shown in FIG. 5;

FIG. 8 is an isometric view of the coupling shown in FIG. 5;

FIG. 9 is an isometric exploded view of another coupling embodiment according to the invention;

FIG. 10 is a front view of a component of the coupling shown in FIG. 9;

FIG. 11 is an isometric view of the coupling shown in FIG. 9;

FIG. 12 is a sectional view taken at line 12-12 of FIG. 11;

FIGS. 13 and 14 are sectional views of the coupling shown in FIG. 9;

FIG. 15 is an exploded view of another embodiment of the coupling according to the invention;

4

FIG. 16 is an exploded view of another embodiment of the coupling according to the invention; and

FIG. 17 is a sectional view of a portion of the coupling shown in FIG. 16.

DETAILED DESCRIPTION OF THE EMBODIMENTS

FIG. 1 shows an exploded isometric view of a coupling embodiment 10 according to the invention. Coupling 10 comprises a plurality of segments 12 and 14. Segments 12 and 14 are connectable end-to-end to surround a central space 16. Connection of the segments is effected by connection members 18 positioned at opposite ends of each of the segments 12 and 14. In this embodiment, the connection members comprise projections 20 which extend outwardly from the ends of the segments. Projections 20 have apertures 22 adapting them to receive fasteners, such as bolts 24 and nuts 26. The fasteners are adjustably tightenable and cooperate with the projections 20 for drawing the segments 12 and 14 toward the central space 16 upon tightening.

Each segment has a pair of arcuate surfaces 28. Surfaces 28 are positioned in spaced relation to one another and face the central space 16. The arcuate surfaces engage and retain pipe elements 30 (see FIG. 4) when the fasteners connecting projections 20 are tightened to draw the segments toward each other. The arcuate surfaces may engage circumferential grooves in the pipe elements, plain ended pipe elements, flared end pipe elements or pipe ends having a shoulder.

Each segment also has at least one, but preferably a plurality of, reaction surfaces 32 positioned on the connection members 18. In the embodiment shown in FIG. 1, two reaction surfaces 32 are positioned on each projection 20. The reaction surfaces are angularly oriented with respect to the projections, and may have an orientation angle 34 from about 30° to about 60° and are inclined so as to face the central space 16. Orientation angles of about 45° are preferred as explained below.

Coupling 10 also comprises one or more gripping bodies. In the example embodiment, two gripping bodies 36 and 38 are positioned between the segments 12 and 14 opposite to one another. Each gripping body has a pair of gripping surfaces 40. Similar to the arcuate surfaces 28, the gripping surfaces are positioned in spaced apart relation and face the central space 16. Each gripping body has a pair of contact surfaces 42 positioned in facing relation with the reaction surfaces 32 on the projections 20 of the segments 12 and 14. The contact surfaces are also angularly oriented with respect to the projections, and may have an orientation angle 44 from about 30° to about 60°. Orientation angles of about 45° are preferred as explained below. Preferably, the orientation angles 34 and 44 are complementary to one another, meaning that they have approximately the same angular orientation.

Upon assembly of the coupling 10, a seal 46 is captured within the central space 16 by the segments 12 and 14 and the gripping bodies [36]. Seal 46 ensures that the coupling 10 provides a fluid-tight joint between pipe ends. The seal 46 is sized so that, in an undeformed state, its outer circumference 48 supports the segments 12 and 14 and the gripping bodies 36 and 38 in spaced apart relation sufficient for pipe elements to be inserted into the central space 16 without disassembling the coupling.

Operation of the coupling is described with reference to FIGS. 2 and 3. FIG. 2 shows the coupling 10 as received from the factory in the pre-assembled state, installation ready. In this configuration, the fasteners are not yet tightened, thereby allowing the segments 12 and 14 and the gripping bodies 36

5

and 38 to be positioned radially outwardly away from the central space 16 to allow pipe elements (not shown for clarity) to be inserted into the central space. As noted above, the seal 46 is sized to hold the segments and gripping bodies radially outwardly to facilitate pipe insertion. Upon insertion, the pipe elements engage the seal 46 which provides fluid tightness to the joint. Next, the bolts 24 and nuts 26 are tightened, drawing the segments 12 and 14 toward one another and the central space 16. As the segments move, the arcuate surfaces 28 are brought into engagement with the outer surface of the pipe elements to retain them in the coupling. As shown in FIG. 3, motion of the segments 12 and 14 toward one another causes the gripping bodies 36 and 38 to move inwardly toward the central space 16, in a direction substantially perpendicular to the motion of the segments. This permits the gripping surfaces 40 on the gripping bodies 36 and 38 to also engage the outer surface of the pipe elements. Motion of the gripping bodies toward the central space 16 is effected by the interaction of the contact surfaces 42 on the gripping bodies with the reaction surfaces 32 on the projections 20. The angular orientation 44 and 34 of the contact surfaces and the reaction surfaces respectively, allows the forces between the surfaces to be resolved into a component directed toward the central space. This force, applied at the contact surfaces, causes the motion of the gripping bodies toward the central space. As noted above, orientation angles of about 45° are preferred for both the reaction surfaces and the contact surfaces. The 45° angles ensure that, during the motion of the segments 12 and 14 and the gripping bodies 36 and 38 toward the central space 16, the arcuate surfaces 28 and the gripping surfaces 40 are at all times equidistant from the pipe elements 30 and contact the pipe elements substantially simultaneously.

As shown in FIG. 2, there are multiple gaps 17 between the end faces 19 of the gripping bodies 36, 38, and shoulders 21 on segments 12 and 14. The gaps 17 allow for the relative motion between the gripping bodies and the segments. The gaps are about one half the size of gaps between segments in prior art couplings and consequently the gripping bodies and segments have less tendency to pinch the seal 46 as the gaps 17 close to virtually line on line contact as shown in FIG. 3. This results in more uniform compression of seal 46 and the elimination of extrusion paths for the seal when under pressure.

It is advantageous to position the reaction surfaces 32 on the projections 20 and have the contact surfaces 42 project substantially radially outwardly away from the central space 16 so that the interface between the contact surfaces and the reaction surfaces is near the fastener (bolt 24, nut 26) which joins the connection members 18 (in this example projections 20) to one another. Internal pressure within the coupling 10, acting on the seal 46, will force the segments 12 and 14 and the gripping bodies 36 and 38 away from the central space. Force applied to the gripping bodies within the coupling is transmitted to the segments at the interface between the contact surfaces 42 and the reaction surfaces 32. Due to their angular orientation, the contact surfaces will tend to act like a wedge and force the projections 20 apart. By placing the interface close to the fastener joining the projections, the separation of the projections will be less than if the interface were farther from the fastener. The advantageous positioning of the contact surface-reaction surface interface minimizes the separation of the segments and allows the coupling to withstand higher pressures without leaking. Furthermore, by placing the reaction forces between the segments and the gripping bodies near the fasteners the distortion of the segments by the gripping bodies is lessened and the coupling better maintains its round shape.

6

FIG. 4A illustrates another embodiment 11 of a coupling according to the invention. In this embodiment, the contact surfaces 42 on the gripping bodies 36 and 38 have a convex shape. This permits them to engage the reaction surfaces 32 tangentially when the segments 12 and 14 are drawn toward one another, resulting in reaction forces which cause motion of the gripping bodies toward the central space. The reaction surfaces 32 are angularly oriented. FIG. 4B shows another embodiment 13 wherein the reaction surfaces 32 have a convex shape and the contact surfaces 42 are angularly oriented. This again allows for tangential engagement between the reaction surfaces and the contact surfaces, resulting in reaction forces which cause motion of the gripping bodies toward the central space as the segments 12 and 14 are drawn toward each other.

FIG. 5 shows an isometric exploded view of another coupling embodiment 50 according to the invention. Coupling 50 has gripping bodies 36 and 38 with contact surfaces 52 positioned on opposite sides of the gripping bodies. Again, the contact surfaces are angularly oriented with respect to the connection members 18 and interface with reaction surfaces 54 positioned on the connection members 18. Orientation angles 56 for the contact surfaces from about 30° to about 60° are advantageous for this coupling design. It is preferred that the orientation angle of the reaction surfaces 54 be approximately the same as the contact surfaces as shown in FIG. 8.

Upon assembly of the coupling 50, a seal 46 is captured within the central space 16 by the segments 12 and 14 and the gripping bodies 36 and 38. Seal 46 ensures that the coupling 50 provides a fluid-tight joint between pipe ends. The seal is sized so that, in an undeformed state, its outer circumference 48 supports the segments 12 and 14 and the gripping bodies 36 and 38 in spaced apart relation sufficient for pipe elements to be inserted into the coupling without disassembling the coupling.

Operation of coupling 50 is similar to that of coupling 10 described above. As shown in FIG. 6, before tightening of fasteners 58 the segments 12 and 14 and the gripping bodies 36 and 38 are spaced outwardly away from the central space 16 so as to allow a pipe element to be inserted into the central space. Tightening of the fasteners as shown in FIG. 7 draws the segments 12 and 14 toward one another and the central space, allowing the arcuate surfaces 28 to engage the pipe elements' outer surface. Interaction between the contact surfaces 52 on the gripping bodies 36 and 38 and the reaction surfaces 54 on the segments 12 and 14 forces the gripping bodies to move inwardly toward the central space as the fasteners 58 are tightened. The inward motion of the gripping bodies allows their gripping surfaces 40 to engage the pipe elements 30 as shown in FIG. 8.

FIG. 9 shows an exploded view of another coupling embodiment 60 according to the invention. Coupling 60 comprises coupling segments 12 and 14. The segments are arranged in facing relation and are joined end-to-end by connection members 18 positioned at opposite ends of each segment. In this embodiment, as with those previously described, the connection members comprise outwardly extending projections 20 which receive fasteners 58 that are adjustably tightenable. Tightening of the fasteners draws the coupling segments 12 and 14 toward one another and the central space 16.

Each segment has inwardly facing arcuate surfaces 28 positioned in spaced relation to one another. The arcuate surfaces occupy positions between the ends of each segment. Reaction surfaces 32 are positioned in spaced relation at opposite ends of each coupling segment 12 and 14. The reaction surfaces face inwardly toward the central space 16 and

extend in a tangential direction around the segments. The reaction surfaces are angularly oriented as described below.

Gripping bodies **36** and **38** are positioned between the segments **12** and **14** at opposite ends of the coupling **60**. Each gripping body has inwardly facing gripping surfaces **40** arranged in spaced relation. Preferably, the gripping surfaces **40** align with respective arcuate surfaces **28** when the coupling is assembled as best shown in FIG. **11**. With reference again to FIG. **9**, each gripping body has contact surfaces **42** in spaced relation. Contact surfaces **42** face outwardly away from the central space **16** and engage respective reaction surfaces **32** on the segments **12** and **14**. The contact surfaces on the gripping bodies cooperate with the reaction surfaces on the segments such that, when the segments are drawn toward one another, for example, by the tightening of fasteners **58**, the gripping bodies are urged radially inwardly as explained further below.

A seal **46** is positioned between the coupling segments **12** and **14** and the gripping bodies **36** and **38**. Both the segments and gripping bodies have respective channels **62** and **64** positioned between the arcuate surfaces **28** and the gripping surfaces **40** which receive the seal. The inner circumference **66** of the seal **46** has inwardly facing sealing surfaces **68** and **70** which engage pipe elements joined by the coupling to form a fluid-tight seal. The seal **46** is sized so that, in an undeformed state, its outer [circumferences] *circumference* **72** supports the segments **12** and **14** and the gripping bodies **36** and **38** in spaced apart relation sufficient for pipe elements to be inserted into the central space **16** without disassembling the coupling. Preferably, the sealing member is a ring formed of an elastic, resilient material such as EPDM (*ethylene propylene diene monomer*) elastomer which deforms when the coupling segments are drawn toward one another by adjustably tightening the connection members **18**.

FIG. **11** shows the pipe coupling **60** in its pre-assembled state ready for use. To effect a fluid-tight joint connecting pipe elements in end-to-end relation, pipe elements **30** are inserted into the sealing member **46** as shown in FIG. **12**, so that the segments straddle facing end portions of the pipe elements. The pipe elements are inserted to an extent such that grooves **74** in the outer surfaces of the pipe elements align with the arcuate surfaces of the segments (not shown) and the gripping surfaces **40** of the gripping bodies **36** and **38**. Insertion of the pipe elements to the proper depth may be facilitated by a pipe stop **76** positioned on the sealing member between the sealing surfaces **68** and **70**. The pipe stop projects inwardly to engage the ends of the pipe elements and limit the insertion depth as desired.

FIG. **13** shows a cross-sectional view of the coupling **60** with pipe element **30** inserted. Attention is drawn to the reaction surfaces **32** on segments **12** and **14** engaging the contact surfaces **42** on gripping bodies **36** and **38**. The reaction surfaces are angularly oriented so that when the fasteners **58** are tightened, drawing the segments **12** and **14** toward one another as shown in FIG. **14**, the gripping bodies **36** and **38** are moved radially inwardly so that the gripping surfaces on the gripping bodies engage and grip the grooves **74** of the pipe elements **30** shown in FIG. **12**. The motion of the segments **12** and **14** toward one another also causes the arcuate surfaces **28** (not shown) on each segment to engage and grip the grooves as well. The pipe elements are, thus, secured in end-to-end relation. The sealing member is deformed radially inwardly to force the sealing surfaces **68** and **70** into further engagement with the outer surfaces of the pipe elements. This configuration produces a relatively rigid joint. A more flexible joint can alternately be provided if the motion of the arcuate surfaces is limited so that they do not engage and clamp the

floor of the groove. To this end, the travel of the gripping bodies is limited by the extent or length of the reaction surfaces and the contact surfaces. Limitation of motion of the arcuate surfaces on the segments toward the central space is preferably controlled by limiting the motion of the segments through contact of the connection members **18**.

As noted, the coupling embodiment **60** provides a substantially rigid joint for the pipe elements, i.e., the joint has significant stiffness about all three axes (bending, axial extension and torsion) to prevent significant angular deflection as well as axial movement (compression and extension) of the pipe elements relatively to one another. Torsional deflections are also inhibited. The rigidity of the joint is effected by the angularly oriented surfaces **78** and **80** positioned on each segment **12** and **14** adjacent to the connection members **18** as best shown in FIG. **9**. The surfaces **78** and **80** on each segment have opposite slopes and are in facing relation with the angularly oriented surfaces on the adjoining segment. When the segments **12** and **14** are drawn toward one another by tightening of fasteners **58**, the angularly oriented surfaces on each segment engage one another and force the segments to rotate in opposite directions about an axis **82**, perpendicular to the pipe elements joined by the coupling. The rotation of the segments causes the arcuate surfaces **28** to forcibly engage the sidewalls of the grooves in the pipe elements and stiffen the joint, as described in U.S. Pat. Nos. 4,611,839, 4,639,020 and 5,758,907 hereby incorporated by reference.

To further enhance the rigidity of the joint between pipe elements formed by coupling **60**, the gripping bodies **36** and **38** may be designed as shown in FIG. **9** such that their end faces **84** and **86** are angularly oriented relative to the gripping surfaces **40**. The angular orientation is best shown in FIG. **10** for gripping body **36** which takes on a rhomboidal profile as a result. The end faces **84** and **86** engage inwardly projecting shoulders **88** on each segment **12** and **14** as the segments are drawn toward one another when forming a joint. The angular orientation of the end faces causes the gripping bodies **36** and **38** to rotate in opposite directions about an axis **90** as they are brought into contact with the shoulders **88**. Axis **90** is substantially perpendicular to the pipe elements being joined by the coupling segments **12** and **14**. The rotation of the gripping bodies causes the gripping surfaces **40** thereon to rotate and forcibly engage the sidewalls of the grooves in the pipe elements similar to the arcuate surfaces on the segments. To avoid rotationally deforming the seal **46**, the channels **64** in each gripping body are skewed in the opposite direction of rotation so that, when the gripping elements rotate about axis **90**, the channels **64** will align with the sealing members so that essentially only radial compression results, i.e., there is no significant twisting of the sealing member about axis **90**.

It is further observed that the angular orientation of the end faces **84** and **86** causes rotation of the segments **12** and **14** about axis **82**, thereby rendering the sloped surfaces **78** and **80** optional, and useful to enhance the rotation of the segments if necessary.

Rotation of the gripping bodies **36** and **38** about axis **90** may also be achieved by angularly orienting the inwardly projecting shoulders **88** as shown in FIG. **15**, the orientation angle **92** of the shoulder forcing rotation of the gripping bodies as the segments **12** and **14** are drawn together, forcing engagement between the shoulders **88** and the end faces **84** and **86** of the gripping bodies. It is also possible to combine the features of FIGS. **9** and **15** and have both the end faces **84** and **86** angularly oriented as well as the shoulders **88**.

It is also feasible to provide angularly oriented surfaces on each segment which have opposite slopes. Such couplings will also provide a rigid joint, but the interaction of the sur-

faces causes the couplings to slide in opposite directions and thereby engage the sidewalls of the grooves. If it is desired to allow some degree of bending flexibility to the joint, the surfaces adjacent to the connection members are made with no slope, i.e., substantially flat.

FIG. 16 shows an exploded view of another coupling embodiment 94 according to the invention. Coupling 94 is used to couple plain end pipe elements together, i.e., pipes having no grooves, beads, enlargements or other features near the ends to facilitate engagement with the coupling. Many of the components of this embodiment are similar to coupling 60 and will not be described in detail. Note also that the sealing member 46 shown in FIG. 1 is not shown in FIG. 6 for clarity, although the same or a similar sealing member is also used with coupling 94.

To enable the coupling 94 to grip plain end pipe elements, two retainers 96 and 98 are used. Each retainer comprises an annular band 100 which has a plurality of flexible, resilient teeth 102. The teeth project radially inwardly for engagement with the pipe elements as described below. The teeth are also angularly oriented out of the plane of the band 100, with the teeth on retainer 96 being angled toward the teeth on retainer 98 and vice versa. The angular orientation of the teeth allows the pipe elements to be inserted into the coupling, but prevents the pipe elements from being withdrawn when the teeth forcibly engage the pipe elements as described below. Band 100 is split, as evidenced by the gap 104. This gap permits the band to be compressed radially to allow the teeth to engage the pipe elements.

The retainers are received within grooves 106 and 108 in segments 12 and 14 and grooves 110 and 112 in the gripping bodies 36 and 38. Preferably, when assembled, the grooves in the segments align with the grooves in the gripping bodies. As shown with reference to FIGS. 16 and 17, when the pipe elements 30 are inserted into the coupling 94 and the fasteners 58 are tightened, the segments 12 and 14 are drawn together and the gripping bodies 36 and 38 move inwardly in response to the interaction of the reaction surfaces 32 with the contact surfaces 42. The inward motion of the grooves 106, 108, 110 and 112 compresses the bands 100 of retainers 96 and 98 inwardly so that teeth 102 engage the surfaces of pipe elements 30. Because the teeth are angled they deflect inwardly and permit the pipe elements to be inserted into the coupling. But when force is applied which tends to remove the pipe elements from the coupling, the teeth prevent this motion due to the self-jamming characteristics of the angled teeth.

Retainers 96 and 98 preferably have a plurality of tabs 114 which project outwardly from the band 100. As shown in FIG. 16, the tabs engage the grooves 106 and 108 of the segments as well as grooves 110 and 112 of the gripping bodies and provide a degree of radial flexibility to the retainer. This added flexibility permits the segments to be joined in what is known as "pad-to-pad" relation wherein the connection members 18 on the segments abut one another when the fasteners 58 are tightened in spite of dimensional variations in the segments and pipes. It is advantageous that the segments join pad-to-pad as it provides a readily identifiable visual indication that the fasteners are fully tightened and thereby avoids the need for torquing the fasteners to a particular value as proof of completion of a fluid-tight joint. Avoiding the need for torque measurements simplifies installation of the coupling, as a torque wrench is not necessary.

Couplings according to the invention realize an advantage through the use of the moving gripping bodies which allows them to be installed from the pre-assembled state easily using hand tools. The movable gripping bodies reduce the torque

required to bring the segments together and grip the pipe elements to effect a fluid-tight joint.

What is claimed is:

5 **[1.** A pipe coupling for securing end portions of a pair of pipe elements together end-to-end, said coupling comprising: a plurality of segments connectable end-to-end surrounding a central space having a center for receiving said pipe elements, each said segment having a pair of arcuate surfaces positioned in spaced relation, said arcuate surfaces facing said central space and being engagable with said pipe elements;

10 connection members positioned at opposite ends of each of said segments for adjustably connecting said segments to one another, said connection members being adjustably tightenable for drawing said segments toward one another and into engagement with said pipe elements; respective reaction surfaces positioned on at least two of said connection members facing one another, said reaction surfaces facing said central space;

15 a gripping body positioned between at least two of said segments, said gripping body having a pair of gripping surfaces positioned in spaced apart relation and facing said center of said central space;

20 a first pair of contact surfaces positioned on said gripping body in facing relation with said reaction surfaces, and wherein adjustable tightening of said connection members draws said coupling segments together, said contact surfaces interacting with said reaction surfaces to move said gripping body into said central space for engagement of said gripping surfaces with said pipe elements.]

25 **2.** A pipe coupling according to claim 1, wherein said connection members comprise a pair of projections extending outwardly from the ends of said segments, said projections being adapted to receive fasteners for adjustably connecting said segments to one another, said fasteners being adjustably tightenable for drawing said arcuate surfaces of said segments into engagement with said pipe elements.

30 **3.** A pipe coupling according to claim 2, wherein said reaction surfaces are angularly oriented with respect to said projections.

35 **4.** A pipe coupling according to claim 3, wherein said reaction surfaces are oriented at an angle from about 30° to about 60°.

40 **5.** A pipe coupling according to claim 3, wherein said reaction surfaces are oriented at an angle of about 45°.

45 **6.** A pipe coupling according to claim 3, wherein said contact surfaces are angularly oriented with respect to said projections.

50 **7.** A pipe coupling according to claim 6, wherein said contact surfaces are oriented at an angle from about 30° to about 60°.

55 **8.** A pipe coupling according to claim 6, wherein said contact surfaces are oriented at an angle of about 45°.

9. A pipe coupling according to claim 1, wherein said contact surfaces project radially outwardly away from said central space.

10. A pipe coupling according to claim 1, further comprising a second pair of contact surfaces, said first and second pairs of contact surfaces being positioned on opposite sides of said gripping body.

60 **11.** A pipe coupling according to claim 1, further comprising a sealing member captured between said segments and positioned between said arcuate surfaces, said sealing member having inwardly facing sealing surfaces engagable with said pipe elements for forming a fluid-tight joint between said pipe elements.

11

12. A pipe coupling for securing end portions of a pair of pipe elements together end-to-end, said coupling comprising:
 a pair of segments connectable end-to-end surrounding a central space having a center for receiving said pipe elements, each said segment having a pair of arcuate surfaces positioned in spaced relation, said arcuate surfaces facing said central space and being engagable with said pipe elements;
 a connection member positioned at each end of each of said segments for adjustably connecting said segments to one another, said connection members being adjustably tightenable for drawing said segments toward one another and into engagement with said pipe elements;
 a respective reaction surface positioned on each of said connection members, said reaction surfaces facing said central space;
 a pair of gripping bodies positioned between said segments opposite to one another, said gripping bodies each having a pair of gripping surfaces positioned in spaced apart relation and facing said center of said central space;
 a first pair of contact surfaces positioned on each of said gripping bodies in facing relation with said reaction surfaces, and
 wherein adjustable tightening of said connection members draws said coupling segments together, said contact surfaces interacting with said reaction surfaces to move said gripping bodies into said central space for engagement of said gripping surfaces with said pipe elements.]

13. A pipe coupling according to claim 12, wherein said connection members comprise a pair of projections extending outwardly from the ends of said segments, said projections being adapted to receive fasteners for adjustably connecting said segments to one another, said fasteners being adjustably tightenable for drawing said arcuate surfaces of said segments into engagement with said pipe elements.

14. A pipe coupling according to claim 13, wherein said reaction surfaces are angularly oriented with respect to said projections.

15. A pipe coupling according to claim 14, wherein said reaction surfaces are oriented at an angle from about 30° to about 60°.

16. A pipe coupling according to claim 14, wherein said reaction surfaces are oriented at an angle of about 45°.

17. A pipe coupling according to claim 14, wherein said contact surfaces are angularly oriented with respect to said projections,

18. A pipe coupling according to claim 17, wherein said contact surfaces are oriented at an angle from about 30° to about 60°.

19. A pipe coupling according to claim 17, wherein said contact surfaces are oriented at an angle of about 45°.

20. A pipe coupling according to claim 12, wherein said contact surfaces project radially outwardly away from said central space.

21. A pipe coupling according to claim 12, further comprising a second pair of contact surfaces on each of said gripping bodies, said first and second pairs of contact surfaces being positioned on opposite sides of said gripping bodies.

22. A pipe coupling according to claim 12, further comprising a sealing member captured between said segments and positioned between said arcuate surfaces, said sealing member having inwardly facing sealing surfaces engagable with said pipe elements for forming a fluid-tight joint between said pipe elements.

23. In combination, a pair of pipe elements and a pipe coupling for securing said pair of pipe elements together end-to-end, each of said pipe elements having a circumferen-

12

tial groove positioned proximate to at least one end thereof for engagement with said coupling, said coupling comprising:

a plurality of segments connectable end-to-end surrounding a central space having a center for receiving said pipe elements, each said segment having a pair of arcuate surfaces positioned in spaced relation, each of said arcuate surfaces facing said central space and being engaged with a respective one of said grooves within each of said pipe elements;

connection members positioned at opposite ends of each of said segments for adjustably connecting said segments to one another, said connection members being adjustably tightenable for drawing said segments toward one another and bringing said arcuate surfaces into engagement with said grooves in each of said pipe elements;

respective reaction surfaces positioned on at least two of said connection members facing one another, said reaction surfaces facing said central space;

a gripping body positioned between at least two of said segments, said gripping body having a pair of gripping surfaces positioned in spaced apart relation and facing said center of said central space, each of said gripping surfaces being engaged with a respective one of said grooves within each of said pipe elements;

a first pair of contact surfaces positioned on said gripping body in facing relation with said reaction surfaces, and wherein adjustable tightening of said connection members draws said coupling segments together, said contact surfaces interacting with said reaction surfaces to move said gripping body into said central space for engagement of said gripping surfaces with said grooves of each of said pipe elements.

24. *The combination according to claim 23, wherein each of said segments further comprises a channel positioned between said arcuate surfaces and facing said central space.*

25. *The combination according to claim 24, wherein said gripping body further comprises a channel positioned between said gripping surfaces and facing said central space.*

26. *The combination according to claim 25, further comprising a seal positioned within said channels of said coupling segments and said gripping body.*

27. *In combination, a pair of pipe elements and a pipe coupling for securing said pair of pipe elements together end-to-end, each of said pipe elements having a circumferential groove positioned proximate to at least one end thereof for engagement with said coupling, said coupling comprising:*

a pair of segments connectable end-to-end surrounding a central space having a center for receiving said pipe elements, each said segment having a pair of arcuate surfaces positioned in spaced relation, said arcuate surfaces facing said central space and being engaged with a respective one of said grooves within each of said pipe elements;

a connection member positioned at each end of each of said segments for adjustably connecting said segments to one another, said connection members being adjustably tightenable for drawing said segments toward one another and bringing said arcuate surfaces into engagement with said grooves in each of said pipe elements;

a respective reaction surface positioned on each of said connection members, said reaction surfaces facing said central space;

a pair of gripping bodies positioned between said segments opposite to one another, said gripping bodies each having a pair of gripping surfaces positioned in spaced

13

apart relation and facing said center of said central space, each of said gripping surfaces being engaged with a respective one of said grooves within each of said pipe elements;

a first pair of contact surfaces positioned on each of said gripping bodies in facing relation with said reaction surfaces, and wherein adjustable tightening of said connection members draws said coupling segments together, said contact surfaces interacting with said reaction surfaces to move said gripping bodies into said central space for engagement of said gripping surfaces with said grooves of each of said pipe elements.

28. The combination according to claim 27, wherein each of said segments further comprises a channel positioned between said arcuate surfaces and facing said central space.

29. The combination according to claim 28, wherein each of said gripping bodies further comprises a channel positioned between said gripping surfaces and facing said central space.

30. The combination according to claim 29, further comprising a seal positioned within said channels of said coupling segments and said gripping bodies.

31. In combination, a pair of pipe elements and a pipe coupling for securing end portions of said pair of pipe elements together end-to-end, each of said pipe elements having a circumferential groove positioned proximate to at least one end thereof for engagement with said coupling, said coupling comprising:

a plurality of segments connectable end-to-end surrounding a central space for receiving said pipe elements, said central space having a center, each said segment having a pair of arcuate surfaces positioned in spaced relation, said arcuate surfaces facing said central space and being engaged with a respective one of said grooves within each of said pipe elements;

connection members respectively positioned at opposite ends on each one of said segments for adjustably connecting said segments to one another, said connection members being adjustably tightenable for drawing said segments toward one another and bringing said arcuate surfaces into engagement with said pipe elements;

at least one reaction surface positioned on at least one of said segments;

a gripping body positioned between at least two of said segments, said gripping body having a pair of gripping surfaces positioned in spaced apart relation and facing said center of said central space;

a first pair of contact surfaces positioned on said gripping body, at least one of said contact surfaces being in facing relation with said at least one reaction surface, and

14

wherein adjustable tightening of said connection members draws said coupling segments together, said at least one contact surface interacting with said at least one reaction surface to move said gripping body toward said central space and bringing said gripping surfaces into engagement with said pipe elements.

32. The combination according to claim 31, wherein said at least one reaction surface is positioned on one of said connection members.

33. In combination, a pair of pipe elements and a pipe coupling for securing end portions of said pair of pipe elements together end-to-end, each of said pipe elements having a circumferential groove positioned proximate to at least one end thereof for engagement with said coupling, said coupling comprising:

a pair of segments connectable end-to-end surrounding a central space for receiving said pipe elements, said central space having a center, each said segment having a pair of arcuate surfaces positioned in spaced relation, said arcuate surfaces facing said central space and being engaged with a respective one of said grooves within each of said pipe elements;

connection members respectively positioned at opposite ends on each one of said segments for adjustably connecting said segments to one another, said connection members being adjustably tightenable for drawing said segments toward one another and bringing said arcuate surfaces into engagement with said pipe elements;

at least one reaction surface positioned on at least one of said segments;

a gripping body positioned between said segments, said gripping body having a pair of gripping surfaces positioned in spaced apart relation and facing said center of said central space;

a first pair of contact surfaces positioned on said gripping body, at least one of said contact surfaces being in facing relation with said at least one reaction surface, and wherein adjustable tightening of said connection members draws said coupling segments together, said at least one contact surface interacting with said at least one reaction surface to move said gripping body toward said central space for engagement of said gripping surfaces with said pipe elements.

34. The combination according to claim 33, wherein said at least one reaction surface is positioned on one of said connection members.

* * * * *