

US00RE45398E

(19) **United States**
(12) **Reissued Patent**
Wallace

(10) **Patent Number:** **US RE45,398 E**
(45) **Date of Reissued Patent:** **Mar. 3, 2015**

(54) **SYSTEM FOR TRACKING AND ANALYZING WELDING ACTIVITY**

(71) Applicant: **Lincoln Global, Inc.**, City of Industry, CA (US)

(72) Inventor: **Matthew Wayne Wallace**, South Windsor, CT (US)

(73) Assignee: **Lincoln Global, Inc.**, City of Industry, CA (US)

(21) Appl. No.: **14/177,692**

(22) Filed: **Feb. 11, 2014**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,274,013**
Issued: **Sep. 25, 2012**
Appl. No.: **12/719,053**
Filed: **Mar. 8, 2010**

U.S. Applications:

(60) Provisional application No. 61/158,578, filed on Mar. 9, 2009.

(51) **Int. Cl.**
B23K 9/06 (2006.01)

(52) **U.S. Cl.**
USPC **219/137 R**; 219/124.34; 219/130.33;
219/136; 219/130.01

(58) **Field of Classification Search**
CPC **B23K 9/0953**
USPC **257/137 R**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,159,119 A 11/1915 Springer
D140,630 S 3/1945 Garibay

D142,377 S 9/1945 Dunn
D152,049 S 12/1948 Welch
2,681,969 A 6/1954 Burke
D174,208 S 3/1955 Abidgaard
2,728,838 A 12/1955 Barnes
D176,942 S 2/1956 Cross
2,894,086 A 7/1959 Rizer

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201083660 7/2008
CN 101419755 4/2009

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion from PCT/IB09/000605 dated Feb. 12, 2010.

(Continued)

Primary Examiner — David Vu


Assistant Examiner — Jonathan Han

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

A system and a method for tracking and analyzing welding activity. Dynamic spatial properties of a welding tool are sensed during a welding process producing a weld. The sensed dynamic spatial properties are tracked over time and the tracked dynamic spatial properties are captured as tracked data during the welding process. The tracked data is analyzed to determine performance characteristics of a welder performing the welding process and quality characteristics of a weld produced by the welding process. The performance characteristics and the quality characteristics may be subsequently reviewed.

195 Claims, 6 Drawing Sheets



AMENDED

(56)

References Cited

U.S. PATENT DOCUMENTS

3,035,155	A	5/1962	Hawk	D475,726	S	6/2003	Suga et al.	
3,356,823	A	12/1967	Waters	6,583,386	B1 *	6/2003	Ivkovich	219/130.01
3,555,239	A	1/1971	Kerth	6,621,049	B2	9/2003	Suzuki	
3,621,177	A	11/1971	Freeman McPherson et al.	6,624,388	B1	9/2003	Blankenship et al.	
3,654,421	A	4/1972	Streetman et al.	D482,171	S	11/2003	Vui et al.	
3,739,140	A	6/1973	Rotilio	6,647,288	B2	11/2003	Madill et al.	
3,866,011	A	2/1975	Cole et al.	6,649,858	B2	11/2003	Wakeman	
3,867,769	A	2/1975	Schow et al.	6,655,645	B1	12/2003	Lu et al.	
3,904,845	A	9/1975	Minkiewicz et al.	6,660,965	B2	12/2003	Simpson	
D243,459	S	2/1977	Bliss	6,697,701	B2	2/2004	Hillen et al.	
4,024,371	A	5/1977	Drake	6,697,770	B1	2/2004	Nagetgall	
4,041,615	A	8/1977	Whitehill	6,703,585	B2	3/2004	Suzuki	
D247,421	S	3/1978	Driscoll	6,710,299	B2	3/2004	Blankenship et al.	
4,124,944	A	11/1978	Blair	6,715,502	B1	4/2004	Rome et al.	
4,132,014	A	1/1979	Schow	D490,347	S	5/2004	Meyers	
4,237,365	A	12/1980	Lambros et al.	6,744,011	B1	6/2004	Hu et al.	
4,280,041	A	7/1981	Kiessling et al.	6,750,428	B2	6/2004	Okamoto et al.	
4,280,137	A	7/1981	Ashida et al.	6,772,802	B2	8/2004	Few	
4,314,125	A	2/1982	Nakamura	6,795,778	B2	9/2004	Dodge et al.	
4,410,787	A	10/1983	Kremers	6,798,974	B1	9/2004	Nakano et al.	
4,429,266	A	1/1984	Traadt	6,857,553	B1	2/2005	Hartman et al.	
4,452,589	A	6/1984	Denison	6,858,817	B2	2/2005	Blankenship et al.	
D275,292	S	8/1984	Bouman	D504,449	S	4/2005	Butchko	
D277,761	S	2/1985	Korovin et al.	6,920,371	B2	7/2005	Hillen et al.	
D280,329	S	8/1985	Bouman	6,940,037	B1 *	9/2005	Kovacevic et al.	219/121.64
4,611,111	A	9/1986	Baheti et al.	6,940,039	B2	9/2005	Blankenship et al.	
4,616,326	A	10/1986	Meier et al.	7,021,937	B2	4/2006	Simpson et al.	
4,677,277	A	6/1987	Cook et al.	7,132,617	B2	11/2006	Lee et al.	
4,680,014	A	7/1987	Paton et al.	7,170,032	B2	1/2007	Flood	
4,689,021	A	8/1987	Vasiliev et al.	7,194,447	B2	3/2007	Harvey et al.	
4,707,582	A	11/1987	Beyer	7,247,814	B2	7/2007	Ott	
4,716,273	A	12/1987	Paton et al.	D555,446	S	11/2007	Ibarrondo et al.	
D297,704	S	9/1988	Bulow	D561,973	S	2/2008	Kinsley et al.	
4,867,685	A	9/1989	Brush et al.	7,353,715	B2	4/2008	Myers	
4,877,940	A	10/1989	Bangs et al.	7,363,137	B2	4/2008	Brant et al.	
4,897,521	A	1/1990	Burr	7,375,304	B2	5/2008	Kainec et al.	
4,907,973	A	3/1990	Hon	7,414,595	B1	8/2008	Muffler	
4,931,018	A	6/1990	Herbst et al.	7,465,230	B2	12/2008	LeMay et al.	
5,192,845	A	3/1993	Kirmsse et al.	D587,975	S	3/2009	Aronson et al.	
5,206,472	A	4/1993	Myking et al.	7,516,022	B2	4/2009	Lee et al.	
5,320,538	A	6/1994	Baum	D602,057	S	10/2009	Osicki	
5,337,611	A	8/1994	Fleming et al.	D606,102	S	12/2009	Bender et al.	
5,360,156	A	11/1994	Ishizaka et al.	7,643,890	B1	1/2010	Hillen et al.	
5,360,960	A	11/1994	Shirk	7,687,741	B2	3/2010	Kainec et al.	
5,370,071	A	12/1994	Ackermann	D614,217	S	4/2010	Peters et al.	
D359,296	S	6/1995	Witherspoon	D615,573	S	5/2010	Peters et al.	
5,424,634	A	6/1995	Goldfarb et al.	D631,074	S	1/2011	Peters et al.	
5,464,957	A	11/1995	Kidwell et al.	7,874,921	B2	1/2011	Baszucki et al.	
D365,583	S	12/1995	Viken	7,991,587	B2	8/2011	Ihn	
5,670,071	A	9/1997	Ueyama et al.	8,069,017	B2	11/2011	Hallquist	
5,676,503	A	10/1997	Lang	8,265,886	B2	9/2012	Bisiauz et al.	
5,676,867	A	10/1997	Allen	8,274,013	B2	9/2012	Wallace	
5,708,253	A	1/1998	Bloch et al.	8,363,048	B2	1/2013	Gering	
D392,534	S	3/1998	Degen	8,365,603	B2	2/2013	Lesage et al.	
D396,238	S	7/1998	Schmitt	2001/0045808	A1	11/2001	Hietmann et al.	
5,823,785	A	10/1998	Matherne, Jr.	2002/0032553	A1	3/2002	Simpson et al.	
5,845,053	A	12/1998	Watanabe	2002/0046999	A1	4/2002	Veikkolainen	
6,008,470	A	12/1999	Zhang	2002/0085843	A1	7/2002	Mann	
6,049,059	A	4/2000	Kim	2003/0000931	A1	1/2003	Ueda	
6,051,805	A	4/2000	Vaidya et al.	2003/0111451	A1	6/2003	Blankenship et al.	
6,155,475	A	12/2000	Ekelof et al.	2003/0172032	A1	9/2003	Choquet	
6,155,928	A	12/2000	Burdick	2004/0035990	A1	2/2004	Ackeret	
6,236,017	B1	5/2001	Smartt et al.	2004/0050824	A1	3/2004	Samler	
6,242,711	B1	6/2001	Cooper	2004/0140301	A1	7/2004	Blankenship et al.	
6,271,500	B1	8/2001	Hirayam et al.	2004/0217096	A1 *	11/2004	Lipnevicius	219/125.11
6,330,938	B1	12/2001	Herve et al.	2005/0101767	A1	5/2005	Clapham et al.	
6,330,966	B1	12/2001	Eissfeller	2005/0103766	A1	5/2005	Iizuka et al.	
D456,428	S	4/2002	Aronson et al.	2005/0103767	A1	5/2005	Kainec et al.	
D456,828	S	5/2002	Aronson et al.	2005/0109735	A1	5/2005	Flood	
D461,383	S	8/2002	Blackburn	2005/0133488	A1	6/2005	Blankenship et al.	
6,441,342	B1	8/2002	Hsu	2005/0189336	A1	9/2005	Ku	
6,445,964	B1	9/2002	White et al.	2005/0199602	A1	9/2005	Kaddani et al.	
6,506,997	B2	1/2003	Matsuyama	2005/0230573	A1	10/2005	Ligertwood	
6,552,303	B1	4/2003	Blankenship et al.	2005/0252897	A1	11/2005	Hsu	
6,568,846	B1	5/2003	Cote et al.	2005/0275913	A1	12/2005	Vesely et al.	
				2005/0275914	A1	12/2005	Vesely et al.	
				2006/0014130	A1	1/2006	Weinstein	
				2006/0136183	A1	6/2006	Choquet	
				2006/0163227	A1	7/2006	Hillen et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0169682 A1 8/2006 Kainec et al.
 2006/0173619 A1 8/2006 Brant et al.
 2006/0207980 A1 9/2006 Jacovetty et al.
 2006/0213892 A1 9/2006 Ott
 2006/0258447 A1 11/2006 Baszucki et al.
 2007/0034611 A1 2/2007 Drius et al.
 2007/0038400 A1 2/2007 Lee et al.
 2007/0045488 A1 3/2007 Shin
 2007/0088536 A1 4/2007 Ishikawa
 2007/0198117 A1 8/2007 Wajihuddin
 2007/0211026 A1 9/2007 Ohta
 2007/0221797 A1 9/2007 Thompson et al.
 2007/0256503 A1 11/2007 Wong et al.
 2007/0277611 A1 12/2007 Portzgen et al.
 2007/0291035 A1 12/2007 Vesely et al.
 2008/0038702 A1 2/2008 Choquet
 2008/0061113 A9* 3/2008 Seki et al. 228/103
 2008/0078811 A1 4/2008 Hillen et al.
 2008/0078812 A1 4/2008 Peters et al.
 2008/0117203 A1 5/2008 Gering
 2008/0128398 A1 6/2008 Schneider
 2008/0135533 A1 6/2008 Ertmer et al.
 2008/0140815 A1 6/2008 Brant et al.
 2008/0149686 A1 6/2008 Daniel et al.
 2008/0203075 A1 8/2008 Feldhausen et al.
 2008/0233550 A1 9/2008 Solomon
 2008/0314887 A1 12/2008 Stoger
 2009/0015585 A1 1/2009 Klusza
 2009/0057286 A1 3/2009 Ihara
 2009/0152251 A1 6/2009 Dantinne et al.
 2009/0173726 A1 7/2009 Davidson et al.
 2009/0184098 A1 7/2009 Daniel et al.
 2009/0200281 A1 8/2009 Hampton
 2009/0200282 A1 8/2009 Hampton
 2009/0231423 A1 9/2009 Becker
 2009/0298024 A1 12/2009 Batzler et al.
 2010/0012637 A1 1/2010 Jaeger
 2010/0048273 A1 2/2010 Wallace et al.
 2010/0062405 A1 3/2010 Zboray et al.
 2010/0062406 A1 3/2010 Zboray et al.
 2010/0096373 A1 4/2010 Hillen et al.
 2010/0133247 A1* 6/2010 Mazumder et al. 219/121.83
 2010/0176107 A1 7/2010 Bong
 2010/0201803 A1 8/2010 Melikian
 2010/0224610 A1 9/2010 Wallace
 2010/0276396 A1 11/2010 Cooper et al.
 2010/0307249 A1 12/2010 Lesage et al.
 2011/0006047 A1 1/2011 Penrod et al.
 2011/0060568 A1 3/2011 Goldfine et al.
 2011/0091846 A1 4/2011 Kreindl et al.
 2011/0114615 A1 5/2011 Daniel et al.
 2011/0117527 A1 5/2011 Conrardy et al.
 2011/0183304 A1 7/2011 Wallace et al.
 2012/0189993 A1 7/2012 Kindig et al.

FOREIGN PATENT DOCUMENTS

CN 101419755 A1 4/2009
 CN 201229711 4/2009
 CN 101571887 11/2009
 CN 101587659 11/2009
 CN 101587659 A 11/2009
 DE 2833638 2/1980
 DE 3046634 1/1984
 DE 3244307 5/1984
 DE 3522581 1/1987
 DE 19615069 10/1997
 DE 19739720 10/1998
 DE 20009543 8/2001
 DE 102005047204 4/2007
 DE 102010038902 9/2012
 EP 108599 5/1984
 EP 127299 12/1984
 EP 145891 6/1985

EP 319623 6/1989
 EP 1527852 5/2005
 EP 1905533 4/2008
 ES 2274736 A1 5/2007
 ES 2274736 3/2008
 FR 2827066 1/2003
 FR 2926660 7/2009
 GB 1455972 11/1976
 GB 1511608 5/1978
 GB 2254172 9/1992
 GB 2454232 6/2009
 JP 2224877 9/1990
 JP 5329645 12/1993
 JP 7047471 2/1995
 JP 7232270 9/1995
 JP 8132274 5/1996
 JP 8150476 6/1996
 JP 8505091 6/1996
 JP 2000167666 6/2000
 JP 2001071140 3/2001
 JP 2003200372 7/2003
 JP 2003326362 11/2003
 JP 2006281270 10/2006
 JP 2007290025 11/2007
 JP 2009500178 1/2009
 JP 2009160636 7/2009
 KR 20090010693 1/2009
 KR 20090010693 A 1/2009
 RU 2008108601 11/2009
 SU 1038963 8/1983
 WO WO9845078 10/1998
 WO WO0143910 6/2001
 WO 2006034571 A1 4/2006
 WO WO2006034571 4/2006
 WO WO2007039278 4/2007
 WO WO2009060231 5/2009
 WO WO2009149740 12/2009
 WO WO2010000003 1/2010
 WO WO2010091493 8/2010
 WO WO2011067447 6/2011
 WO WO2012143327 10/2012
 WO WO2013014202 1/2013

OTHER PUBLICATIONS

International Search Report and Written Opinion from PCT/IB10/02913 dated Apr. 19, 2011.
 ASME Definitions, Consumables, Welding Positions, dated Mar. 19, 2001. See <http://www.gowelding.com/wp/asm4.htm>.
 Abbas, M., et al.; Code_Aster; Introduction to Code_Aster; User Manual; Booket U1.0-: Introduction to Code_Aster; Document: U1.02.00; Version 7.4; Jul. 22, 2005.
 Bjorn G. Agren; Sensor Integration for Robotic Arc Welding; 1995; vol. 5604C of Dissertations Abstracts International p. 1123; Dissertation Abs Online (Dialog® File 35): © 2012 ProQuest Info& Learning: <http://dialogweb.com/cgi/dwclient?req=1331233317524>; one (1) page; printed Mar. 8, 2012.
 Abid, et al., "Numerical simulation to study the effect of tack welds and root gap on welding deformations and residual stresses of a pipe-flange joint" by M. Abid and M. Siddique, Faculty of Mechanical Engineering, GIK Institute of Engineering Sciences and Technology, Topi, NWFP, Pakistan. Available on-line Aug. 25, 2005.
 "Penetration in Spot GTA Welds during Centrifugation," D.K. Aidun and S.A. Martin; Journal of Materials Engineering and Performance vol. 7(5) Oct. 1998—597.
 Arc+ simulator; http://www.123arc.com/en/depliant_ang.pdf; 2000, 2 pgs.
 ARS Electronica Linz GmbH, Fronius, 2 pages, May 18, 1997.
 Ascienetutor.com, A division of Advanced Science and Automation Corp., VWL (Virtual Welding Lab), 2 pages, 2007.
 16TH International Shop and Offshore Structures Congress: Aug. 20-25, 2006: Southhampton, UK, vol. 2 Specialist Committee V.3 Fabrication Technology Committee Mandate: T Borzecki, G. Bruce, Y.S. Han, M. Heinemann, A Imakita, L. Josefson, W. Nie, D. Olson, F. Roland, and Y. Takeda.

(56)

References Cited

OTHER PUBLICATIONS

- CS Wave, A Virtual learning tool for welding motion, 10 pages, Mar. 14, 2008.
- Choquet, Claude; "ARC+: Today's Virtual Reality Solution for Welders" Internet Page, Jan. 1, 2008.
- Code Aster (Software) EDF (France), Oct. 2001.
- Cooperative Research Program, Virtual Reality Welder Training, Summary Report SR 0512, 4 pages, Jul. 2005.
- Desroches, X.; Code-Aster, Note of use for acclulations of welding; Instruction manual U2.03 booklet: Thermomechanical; Document: U2.03.05; Oct. 1, 2003.
- Edison Welding Institute, E-Weld Predictor, 3 pages, 2008.
- Eduwelding+, Weld Into the Fugure; Online Welding Seminar—A virtual training environment; 123arc.com; 4 pages, 2005.
- Eduwelding+, Training Activities with arc+ simulator; Weld Into The Future, Online Welding Simulator—A virtual training environment; 123arc.com; 6 pages, May 2008.
- FH Joanneum, Fronius—virtual welding, 2 pages, May 12, 2008.
- The Fabricator, Virtual Welding, 4 pages, Mar. 2008.
- Fast, K. et al., "Virtual Training for Welding", Mixed and Augmented Reality, 2004, ISMAR 2004, Third IEEE and CM International Symposium on Arlington, VA, Nov. 2-5, 2004.
- Garcia-Ellende et al., "Defect Detection in Arc-Welding Processes by Means of the Line-to-Continuum Method and Feature Selection", www.mdpi.com/journal/sensors; Sensors 2009, 9, 7753-7770; doi: 10.3390/s91007753.
- Juan Vicenete Rosell Gonzales, "RV-Sold: simulator virtual para la formacion de soldadores"; Deformacion Metalica, Es. vol. 34, No. 301 Jan. 1, 2008.
- Hillis and Steele, Jr.; "Data Parallel Algorithms", Communications of the ACM, Dec. 1986, vol. 29, No. 12, p. 1170.
- "The influence of fluid flow phenomena on the laser beam welding process"; International Journal of Heat and Fluid Flow 23, dated 2002.
- The Lincoln Electric Company, CheckPoint Production Monitoring brochure; four pages; http://www.lincolnelectric.com/assets/en_US/products/literature/s232.pdf; Publication S2.32; issue date Feb. 2012.
- The Lincoln Electric Company, Production Monitoring brochure, 4 pages, May 2009.
- Eric Linholm, John Nickolls, Stuart Oberman, and John Montrym, "NVIDIA Testla: A Unifired Graphics and Computing Architecture", IEEE Computer Society, 2008.
- Mahrle, A., et al.; "the influence of fluid flow phenomena on the laser beam welding process" International Journal of Heat and Fluid Flow 23 (2002, No. 3, pp. 288-.
- Mavrikios D et al, A prototype virtual reality-based demonstrator for immersive and interactive simulation of welding processes, International Journal of Computer Integrated manufacturing, Taylor and Francis, Basingstoke, GB, vol. 19, No. 3, Apr. 1, 2006, pp. 294-300.
- Mechanisms and Mechanical Devices Source Book, Chironis, Neil Sclater; McGraw Hill; 2nd Addition, 1996.
- Miller Electric Mfg Co.; MIG Welding System features weld monitoring software; NewsRoom 2010 (Dialog® File 992); © 2011 Dialog. 2010; <http://www.dialogweb.com/cgi/dwclient?reg=1331233430487>; three (3) pages; printed Mar. 8, 2012.
- NSRP ASE, Low-Cost Virtual Reality Welder Training System, 1 Page, 2008.
- N. A. Tech., P/NA.3 Process Modeling and Optimization, 11 pages, Jun. 4, 2008.
- Virtual Reality Welder Trainer, Sessiion 5: Joining Technologies for Naval Applications: earliest date Jul. 14, 2006 (<http://weayback.archive.org>) by Nancy C. Porter, Edison Welding Institute; J. Allan Cote, General Dynamics Electric Boat; Timothy D. Gifford, VRSim, and Wim Lam, FCS Controls.
- Porter, et al., Virtual Reality Training, Paper No. 2005-P19, 14 pages, 2005.
- Production Monitoring 2 brochure, four pages, The Lincoln Electric Company, May 2009.
- Ratnam and Khalid: "Automatic classification of weld defects using simulated data and an MLP neural network." Insight vol. 49, No. 3; Mar. 2007.
- Russel and Norvig, "Artificial Intelligence: A Modern Approach", Prentice-Hall (Copyright 1995).
- "Design and Implementation of a Video Sensor for Closed Loop Control of Back Bead Weld Puddle Width," Robert Schoder, Massachusetts Institute of Technology, Dept. of Mechanical Engineering, May 27, 1983.
- Sim Welder, retrieved on Apr. 12, 2010 from: <http://www.simwelder.com>.
- SIMFOR / CESOL, "RV-SOLD" Welding Simulator, Technical and Functional Features, 20 pages, no date available.
- Training in a virtual environment gives welding students a leg up, retrieved on Apr. 12, 2010 from: <http://www.thefabricator.com/article/arcwelding/virtually-welding>.
- Wade, "Human uses of ultrasound: ancient and modern", Ultrasonics vol. 38, dated 2000.
- Wang et al., "Numerical Analysis of Metal Tranfser in Gas Metal Arc Welding," G. Wang, P.G. Huang, and Y.M. Zhang. Departements of Mechanical and Electrical Engineering. University of Kentucky, Dec. 10, 2001.
- Wang et al., Study on welder training by means of haptic guidance and virtual reality for arc welding, 2006 IEEE International Conference on Robotics and Biomimetics, ROBIO 2006 ISBN-10: 1424405718, p. 954-958.
- White et al., Virtual welder training, 2009 IEEE Virtual Reality Conference, p. 303, 2009.
- Edison Welding Institue, Inc. and Realweld Systems, Inc. -v- Lincoln Global, Inc.*; Complaint for Declaratory Judgement including Exhibits; Civil Action No. 2:12-cv-1040, 2012.
- Edison Welding Institue, Inc. and Realweld Systems, Inc. -v- Lincoln Global, Inc.*; Stipulated Extension of Time to Answer . . . Civil Action No. 2:12-cv-1040, 2013.
- Edison Welding Institue, Inc. and Realweld Systems, Inc. -v- Lincoln Global, Inc.*; Corporate Disclosure Statement; Civil Action No. 2:12-cv-1040, 2013.
- Edison Welding Institue, Inc. and Realweld Systems, Inc. -v- Lincoln Global, Inc.*; Notice of Appearance of Counsel; Civil Action No. 2:12-cv-1040, 2013.
- Edison Welding Institue, Inc. and Realweld Systems, Inc. -v- Lincoln Global, Inc.*; Unopposed Motion to Dismiss w/o Prejudice including Exhibits; Civil Action No. 2:12-cv-1040, 2013.
- Edison Welding Institue, Inc. and Realweld Systems, Inc. -v- Lincoln Global, Inc.*; Order Granting Motion; Civil Action No. 2:12-cv-1040, 2013.
- Edison Welding Institute, Inc.; Docket; Civil Action No. 2:12-cv-1040, 2012.
- Yizhong Wang, Younghua Chen, Zhongliang Nan, Yong Hu, Study on Welder Training by Means of Haptic Guidance and Virtual Reality for Arc Welding, 2006 IEEE International Conference on Robotics and Biomimetics, pp. 954-958, ROBIO 2006 ISBN-10:1424405718, Dec. 17-20, 2006, Kunming, China.
- Nancy C. Porter, J. Allan Cote, Timothy D. Gifford, Wim Lan, Virtual Reality Welder Training, Paper No. 2005-P19, 2005, pp. 1-14.
- Ascienetutor.Com, A Division of Advanced Science and Automation Corp., VWL (Virtual Welding Lab), 2007, 2 pages.
- Edison Welding Institute, E-Weld Predictor, 3 pages, 2008, Columbus, OH.
- Tim Heston, Virtually welding, The Fabricator, Mar. 2008, 4 pages, FMA Communications Inc., Rockford, IL, www.thefabricator.com.
- NSRP ASE, Low-Cost Virtual Reality Welder Training System, 2008, 1 page.
- Steven White, Mores Prachyabrued, Dhruva Baghi, Amit Aglawe, Dirk Reiners, Christoph Borst, Terry Chambers, Virtual Welder Trainer, IEEE Virtual Reality 2009, p. 303.
- Nancy Porter, J. Allan Cote, Timothy Gifford, Virtual Reality Welder Training, CRP Cooperative Research Program, Summary Report SR 0512, Jul. 2005, 4 pages.
- Weld Into the Future, Eduwelding+, Training Activities with arc+ simulator, 2005, 4 pages.

(56)

References Cited

OTHER PUBLICATIONS

Claude Choquet, ARC+: Today's Virtual Reality Solution for Welders, 123 Certification Inc., Montreal, Quebec, CA, May 2008, 6 pages.

Laurent Da Dalto, Dominique Steib, Daniel Mellet-d'Huart, Olivier Balet, CS WAVE A Virtual learning tool for the welding motion, <http://wave.c-s.fr>, Mar. 14, 2008, 10 pages.

CS WAVE, The Virtual Welding Trainer, 6 pages, 2007.

Fronius—virtual welding, www.fh-joanneum.at/ca/cn/yly/?lan=en, 2 pages, May 12, 2008.

Fronius, ARS Electronica, 2 pages, May 18, 1997.

P/NA.3 Process Modelling and Optimization, www.natech-inc.com/pna3/index.html, 11 pages, Jun. 4, 2008.

"RV-Sold" Welding Simulator Technical and Functional Features, SIMFOR, pp. 1-20, date unknown.

Juan Vicente Rosell, RV-Sold: Simulador virtual para la formacion de soldadores, Deformacion Metalica, Es. vol. 34, No. 301, 14 pages, Jan. 1, 2008.

Kenneth Fast, Timothy Gifford, Robert Yancy, Virtual Training for Welding, 3rd IEEE and ACM International symposium on Mixed and Augmented Reality (ISMAR 2004), 2 pages, 2004.

D. Mavrikios, V. Karabatsou, D. Fragos, G. Chryssolouris, A prototype virtual reality-Ocated demonstrator for immersive and interactive simulation of welding processes, International Journal of Computer Integrated Manufacturing, 294-301, 2006.

PCT/IB2009/00605 International Search Report.

PCT/IB2009/00605 Written Opinion.

U.S. Appl. No. 29/399,980, filed Jul. 10, 2009, issued May 11, 2010 as D615,573.

U.S. Appl. No. 29/339,979, filed Jul. 10, 2009, issued Apr. 20, 2010 as D614,217.

U.S. Appl. No. 29/339,978, filed Jul. 10, 2009.

U.S. Appl. No. 12/504,870, filed Jul. 17, 2009 claiming priority to U.S. Appl. No. 61/090,794.

U.S. Appl. No. 12/501,263, filed Jul. 10, 2009 claiming priority to U.S. Appl. No. 61/090,794.

U.S. Appl. No. 12/501,257, filed Jul. 10, 2009 claiming priority to U.S. Appl. No. 61/090,764.

* cited by examiner




FIG. 1
AMENDED




FIG. 2
AMENDED




Fig. 3




Fig. 4





Fig. 5

FIG. 6



SYSTEM FOR TRACKING AND ANALYZING WELDING ACTIVITY

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

This U.S. patent application claims priority to and the benefit of U.S. provisional patent application Ser. No. 61/158,578 which was filed on Mar. 9, 2009, and which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

Certain embodiments of the present invention pertain to systems for tracking and analyzing welding activity, and more particularly, to systems that capture weld data in real time (or near real time) for analysis and review. Additionally, the embodiments of the present invention provide a system for marking portions of a welded article by indicating possible discontinuities or flaws within the weld joint.

BACKGROUND

In many applications, ascertaining the quality of weld joints is critical to the use and operation of a machine or structure incorporating a welded article. In some instances, x-raying or other nondestructive testing is needed to identify potential flaws within one or more welded joints. However, non-destructive testing can be cumbersome to use, and typically lags the welding process until the inspector arrives to complete the testing. Additionally, it may not be effective for use with all weld joint configurations. Moreover, non-destructive testing does not provide any information about how the weld was completed. In welding applications where identifying waste is vital to producing cost effective parts, non-destructive testing provides no insight into problems like overfill.

Further limitations and disadvantages of conventional, traditional, and proposed approaches will become apparent to one of skill in the art, through comparison of such approaches with the subject matter of the present application as set forth in the remainder of the present application with reference to the drawings.

SUMMARY

The embodiments of the present invention pertain to a system for tracking and analyzing welding activity. The system may be used in conjunction with a welding power supply and includes a sensor array and logic processor-based technology that captures performance data (dynamic spatial properties) as the welder performs various welding activities. The system functions to evaluate the data via an analysis engine for determining weld quality in real time (or near real time). The system also functions to store and replay data for review at a time subsequent to the welding activity thereby allowing other users of the system to review the performance activity of the welding process.

These and other novel features of the subject matter of the present application, as well as details of illustrated embodiments thereof, will be more fully understood from the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a welder using an embodiment of a system for tracking and analyzing welding activity;

FIG. 2 is a schematic representation of an embodiment of the system of FIG. 1 for tracking and analyzing welding activity;

FIG. 3 is a schematic representation of an embodiment of the hardware and software of the system of FIGS. 1-2 for tracking and analyzing welding activity;

FIG. 4 is a flow diagram of an embodiment of the system of FIGS. 1-3 for tracking and analyzing welding activity;

FIG. 5 is a flowchart of an embodiment of a method for tracking and analyzing welding activity using the system of FIGS. 1-4; and

FIG. 6 illustrates an example embodiment of a graph, displayed on a display, showing tracked welding tool pitch angle versus time with respect to an upper pitch angle limit, a lower pitch angle limit, and an ideal pitch angle.

DETAILED DESCRIPTION

FIG. 1 is a perspective view of a welder 10 using an embodiment of a system 100 for tracking and analyzing welding activity while performing a welding process with a welding system 200. FIG. 2 is a schematic representation of an embodiment of the system 100 of FIG. 1 for tracking and analyzing welding activity. FIG. 3 is a schematic representation of an embodiment of the hardware 110, 130 and software 120 of the system 100 of FIGS. 1-2 for tracking and analyzing welding activity. FIG. 4 is a flow diagram of an embodiment of the system 100 of FIGS. 1-3 for tracking and analyzing welding activity. FIG. 5 is a flowchart of an embodiment of a method 500 for tracking and analyzing welding activity using the system 100 of FIGS. 1-4.

Referring again to the drawings wherein the showings are for purposes of illustrating embodiments of the invention only and not for purposes of limiting the same, FIG. 1 shows a system 100 for tracking and analyzing manual processes requiring the dexterity of a human end user 10. In particular, system 100 functions to capture performance data related to the use and handling of tools (e.g., welding tools). In one embodiment, the system 100 is used to track and analyze welding activity, which may be a manual welding process in any of its forms including but not limited to: arc welding, laser welding, brazing, soldering, oxyacetylene and gas welding, and the like. For illustrative purposes, the embodiments of the present invention will be described in the context of arc welding. However, persons of ordinary skill in the art will understand its application to other manual processes. In accordance with alternative embodiments of the present invention, the manual welder 10 may be replaced with a robotic welder. As such, the performance of the robotic welder and resultant weld quality may be determined in a similar manner.

In one embodiment, the system 100 tracks movement or motion (i.e., position and orientation over time) of a welding tool 230, which may be, for example, an electrode holder or a welding torch. Accordingly, the system 100 is used in conjunction with a welding system 200 including a welding power supply 210, a welding torch 230, and welding cables 240, along with other welding equipment and accessories. As a welder 10, i.e. end user 10, performs welding activity in accordance with a welding process, the system 100 functions to capture performance data from real world welding activity as sensed by sensors 160, 165 (see FIG. 2) which are discussed in more detail later herein.

In accordance with an embodiment of the present invention, the system **100** for tracking and analyzing welding activity includes the capability to automatically sense dynamic spatial properties (e.g., positions, orientations, and movements) of a welding tool **230** during a manual welding process producing a weld **16** (e.g., a weld joint). The system **100** further includes the capability to automatically track the sensed dynamic spatial properties of the welding tool **230** over time and automatically capture (e.g., electronically capture) the tracked dynamic spatial properties of the welding tool **230** during the manual welding process.

The system **100** also includes the capability to automatically analyze the tracked data to determine performance characteristics of a welder **10** performing the manual welding process and quality characteristics of a weld **16** produced by the welding process. The system **100** allows for the performance characteristics of the welder **10** and the quality characteristics of the weld to be reviewed. The performance characteristics of a welder **10** may include, for example, a weld joint trajectory, a travel speed of the welding tool **230**, welding tool pitch and roll angles, an electrode distance to a center weld joint, an electrode trajectory, and a weld time. The quality characteristics of a weld produced by the welding process may include, for example, discontinuities and flaws within certain regions of a weld produced by the welding process.

The system **100** further allows a user (e.g., a welder **10**) to locally interact with the system **100**. In accordance with another embodiment of the present invention, the system **100** allows a remotely located user to remotely interact with the system **100**. In either scenario, the system **100** may automatically authorize access to a user of the system **100**, assuming such authorization is warranted.

In accordance with an embodiment of the present invention, the system **100** for tracking and analyzing welding activity includes a processor based computing device **110** configured to track and analyze dynamic spatial properties (e.g., positions, orientations, and movements) of a welding tool **230** over time during a manual welding process producing a weld **16**. The system **100** further includes at least one sensor array **160**, **165** operatively interfacing to the processor based computing device **110** (wired or wirelessly) and configured to sense the dynamic spatial properties of a welding tool **230** during a manual welding process producing a weld **16**. The system **100** also includes at least one user interface operatively interfacing to the processor based computing device **110**. The user interface may include a graphical user interface **135** and/or a display device (e.g., a display **130** or a welding display helmet **180** where a display is integrated into a welding helmet as illustrated in FIG. 2). The system **100** may further include a network interface configured to interface the processor based computing device **110** to a communication network **300** (e.g., the internet).

In accordance with an embodiment of the present invention, a method **500** (see FIG. 5) for tracking and analyzing welding activity includes, in step **510**, setting up a manual welding process, and, in step **520**, sensing dynamic spatial properties (e.g., positions, orientations, and movements) of a welding tool **230** during a manual welding process producing a weld using at least one sensor (e.g., sensor arrays **160** and **165**). In step **530**, the method includes tracking the sensed dynamic spatial properties over time during the manual welding process using a real time tracking module **121** (see FIG. 4). The method also includes, in step **540**, capturing the tracked dynamic spatial properties as tracked data during the manual welding process using a computer based (e.g., electronic) memory device (e.g., a portion of the hardware **150**

and software **120** of the processor based computing device **110**). The method further includes, in step **550**, analyzing the tracked data to determine performance characteristics of a welder **10** performing the manual welding process and/or quality characteristics of a weld produced by the welding process using a computer based analysis engine **122**. In step **560**, at least one of the performance characteristics and the quality characteristics are reviewed using a display device (e.g., display device **130**). Alternatively, a visualization module or a testing module may be used in place of the display device **130**, as are well known in the art.

The method **500** may initially include selecting welding set up parameters for the welding process via a user interface **135** as part of step **510**. The method may also include outputting the performance characteristics of the welder **10** and/or the quality characteristics of a weld to a remote location and remotely viewing the performance characteristics and/or the quality characteristics via a communication network **300** (see FIG. 3).

The system **100** for tracking and analyzing welding activity comprises hardware and software components, in accordance with an embodiment of the present invention. In one embodiment, the system **100** incorporates electronic hardware. More specifically, system **100** may be constructed, at least in part, from electronic hardware **150** (see FIG. 4) of the processor based computing device **110** operable to execute programmed algorithms, also referred to herein as software **120** or a computer program product. The processor based computing device **110** may employ one or more logic processors capable of being programmed, an example of which may include one or more microprocessors. However, other types of programmable circuitry may be used without departing from the intended scope of coverage of the embodiments of the present invention. In one embodiment, the processor based computing device **110** is operatively disposed as a microcomputer in any of various configurations including but not limited to: a laptop computer, a desktop computer, a workstation, a server or the like. Alternatively, mini-computers or main frame computers may serve as the platform for implementing the system **100** for tracking and analyzing welding activity. Moreover, handheld or mobile processor based computing devices may be used to execute programmable code for tracking and analyzing performance data.

Other embodiments are contemplated wherein the system **100** is incorporated into the welding system **200**. More specifically, the components comprising the system **100** may be integrated into the welding power supply **210** and/or weld torch **230**. For example, the processor based computing device **110** may be received internal to the housing of the welding power supply **210** and may share a common power supply with other systems located therein. Additionally, sensors **160**, **165**, used to sense the weld torch **230** dynamic spatial properties, may be integrated into the weld torch handle.

The system **100** may communicate with and be used in conjunction with other similarly or dissimilarly constructed systems. Input to and output from the system **100**, termed I/O, may be facilitated by networking hardware and software including wireless as well as hard wired (directly connected) network interface devices. Communication to and from the system **100** may be accomplished remotely as through a network **300** (see FIG. 3), such as, for example, a wide area network (WAN) or the Internet, or through a local area network (LAN) via network hubs, repeaters, or by any means chosen with sound engineering judgment. In this manner,

5

information may be transmitted between systems as is useful for analyzing, and/or re-constructing and displaying performance and quality data.

In one embodiment, remote communications are used to provide virtual instruction by personnel, i.e. remote or offsite users, not located at the welding site. Reconstruction of the welding process is accomplished via networking. Data representing a particular weld may be sent to another similar or dissimilar system **100** capable of displaying the weld data (see FIG. **3**). It should be noted that the transmitted data is sufficiently detailed for allowing remote user(s) to analyze the welder's performance and the resultant weld quality. Data sent to a remote system **100** may be used to generate a virtual welding environment thereby recreating the welding process as viewed by offsite users as discussed later herein. Still, any way of communicating performance data to another entity remotely located from the welding site may be used without departing from the intended scope of coverage of the embodiments of the subject invention.

The processor based computing device **110** further includes support circuitry including electronic memory devices, along with other peripheral support circuitry that facilitate operation of the one or more logic processor(s), in accordance with an embodiment of the present invention. Additionally, the processor based computing device **110** may include data storage, examples of which include hard disk drives, optical storage devices and/or flash memory for the storage and retrieval of data. Still any type of support circuitry may be used with the one or more logic processors as chosen with sound engineering judgment. Accordingly, the processor based computing device **110** may be programmable and operable to execute coded instructions in a high or low level programming language. It should be noted that any form of programming or type of programming language may be used to code algorithms as executed by the system **100**.

With reference now to FIGS. **1-4**, the system **100** is accessible by the end user **10** via a display screen **130** operatively connected to the processor based computing device **110**. Software **120** installed onto the system **100** directs the end user's **10** interaction with the system **100** by displaying instructions and/or menu options on, for example, the display screen **130** via one or more graphical user interfaces (GUI) **135**. Interaction with the system **100** includes functions relating to, for example: part set up (weld joint set up), welding activity analysis, weld activity playback, real time tracking, as well as administrative activity for managing the captured data. Still other functions may be chosen as are appropriate for use with the embodiments of the present invention. System navigation screens, i.e. menu screens, may be included to assist the end user **10** in traversing through the system functions. It is noted that as the system **100** is used for training and analysis, security may be incorporated into the GUI(s) **135** that allow restricted access to various groups of end users **10**. Password security, biometrics, work card arrangement or other security measures may be used to ensure that system access is given only to authorized users as determined by an administrator or administrative user. It will be appreciated that the end user **10** may be the same or a different person than that of the administrative user.

In one embodiment, the system **100** functions to capture performance data of the end user **10** for manual activity as related to the use of tools or hand held devices. In the accompanying figures, welding, and more specifically, arc welding is illustrated as performed by the end user **10** on a weldment **15** (e.g., a weld coupon). The welding activity is recorded by the system **100** in real time or near-real time for tracking and analysis purposes mentioned above by a real time tracking

6

module **121** and an analysis module **122**, respectively (see FIG. **4**). By recorded it is meant that the system **10** captures data related to a particular welding process for determining the quality of the weld joint or weld joints. The types of performance data that may be captured include, but are not limited to, for example: weld joint configuration or weld joint trajectory, weld speed, welding torch pitch and roll angles, electrode distance to the center weld joint, wire feed speed, electrode trajectory, weld time, and time and date data. Other types of data may also be captured and/or entered into the system **100** including: weldment materials, electrode materials, user name, project ID number, and the like. Still, any type and quantity of information may be captured and/or entered into the system **100** as is suitable for tracking, analyzing and managing weld performance data. In this manner, detailed information about how the welding process for a particular weld joint was performed may be captured and reconstructed for review and analysis in an analysis record **124**.

The data captured and entered into the system **100** is used to determine the quality of the real world weld joint. Persons of ordinary skill in the art will understand that a weld joint may be analyzed by various processes including destructive and non-destructive methods, examples of which include sawing/cutting or x-raying of the weld joint respectively. In prior art methods such as these, trained or experienced weld personnel can determine the quality of a weld performed on a weld joint. Of course, destructive testing renders the weldment unusable and thus can only be used for a sampling or a subset of welded parts. While non-destructive testing, like x-raying, do not destroy the welded article, these methods can be cumbersome to use and the equipment expensive to purchase. Moreover, some weld joints cannot be appropriately x-rayed, i.e. completely or thoroughly x-rayed. By way of contrast, system **100** captures performance data during the welding process that can be used to determine the quality of the welded joint. More specifically, system **100** is used to identify potential discontinuities and flaws within specific regions of a weld joint. The captured data may be analyzed by an experienced welder or trained professional (e.g., a trainer **123**, see FIG. **4**), or in an alternative by the system **100** using the analysis module **122** for identifying areas within the weld joint that may be flawed. In one example, torch position and orientation along with travel speed and other critical parameters are analyzed as a whole to predict which areas along the weld joint, if any, are deficient. It will be understood that quality is achieved during the welding process when the operator **10** keeps the weld torch **230** within acceptable operational ranges. Accordingly, the performance data may be analyzed against known good parameters for achieving weld quality for a particular weld joint configuration.

FIG. **6** illustrates an example embodiment of a graph **600**, displayed on the display **130**, showing tracked welding tool pitch angle **640** versus time with respect to an upper pitch angle limit **610**, a lower pitch angle limit **620**, and an ideal pitch angle **630**. The upper and lower limits **610** and **620** define a range of acceptability between them. Different limits may be predefined for different types of users such as, for example, welding novices, welding experts, and persons at a trade show. The analysis engine **122** may provide a scoring capability, in accordance with an embodiment of the present invention, where a numeric score is provided based on how close to optimum (ideal) a user is for a particular tracked parameter, and depending on the determined level of discontinuities or defects determined to be present in the weld.

Performance data may be stored electronically in a database **140** (see FIG. **3**) and managed by a database manager in a manner suitable for indexing and retrieving selected sets or

subsets of data. In one embodiment, the data is retrieved and presented to an analyzing user (e.g., a trainer **123**) for determining the weld quality of a particular weld joint. The data may be presented in tabular form for analysis by the analyzing user. Pictures, graphs, and or other symbol data may also be presented as is helpful to the analyzing user in determining weld quality. In an alternative embodiment, the performance data may be presented to the analyzing user in a virtual reality setting, whereby the real world welding process is simulated using real world data as captured by the system **100**. An example of such a virtual reality setting is discussed in U.S. patent application Ser. No. 12/501,257 filed on Jul. 10, 2009. In this way, the weld joint and corresponding welding process may be reconstructed for review and analysis. Accordingly, the system **100** may be used to archive real data as it relates to a particular welded article. Still, it will be construed that any manner of representing captured data or reconstructing the welding process for the analyzing user may be used as is appropriate for determining weld quality.

In another embodiment, data captured and stored in the database **140** is analyzed by an analyzing module **122** (a.k.a., an analysis engine) of the system **100**. The analyzing module **122** may comprise a computer program product executed by the processor based computing device **110**. The computer program product may use artificial intelligence. In one particular embodiment, an expert system may be programmed with data derived from a knowledge expert and stored within an inference engine for independently analyzing and identifying flaws within the weld joint. By independently, it is meant that the analyzing module **122** functions independently from the analyzing user to determine weld quality. The expert system may be ruled-based and/or may incorporate fuzzy logic to analyze the weld joint. In this manner, areas along the weld joint may be identified as defective, or potentially defective, and marked for subsequent review by an analyzing user. Determining weld quality and/or problem areas within the weld joint may be accomplished by heuristic methods. As the system **100** analyzes welding processes of the various end users over repeated analyzing cycles, additional knowledge may be gained by the system **100** for determining weld quality.

A neural network or networks may be incorporated into the analysis engine **122** of the system **100** for analyzing data to determine weld quality, weld efficiency and/or weld flaws or problems. Neural networks may comprise software programming that simulates decision making capabilities. In one embodiment, the neural network(s) may process data captured by the system **100** making decisions based on weighted factors. It is noted that the neural network(s) may be trained to recognize problems that may arise from the weld torch position and movement, as well as other critical welding factors. Therefore, as data from the welding process is captured and stored, the system **100** may analyze the data for identifying the quality of the weld joint. Additionally, the system **100** may provide an output device **170** (see FIG. 4) that outputs indications of potential flaws in the weld such as, for example, porosity, weld overflow, and the like.

In capturing performance data, the system **100** incorporates a series of sensors, also referred to as sensor arrays **160**, **165** (see FIG. 2). The sensor arrays **160**, **165** include emitters and receivers positioned at various locations in proximity to the weldment **15**, and more specifically, in proximity to the weld joint **16** for determining the position and orientation of the weld torch **230** in real time (or near real time). In one embodiment, the sensor arrays **160**, **165** include acoustical sensor elements. It is noted that the acoustical sensor elements may use waves in the sub-sonic and/or ultra-sonic

range. Alternate embodiments are contemplated that use optical sensor elements, infrared sensor elements, laser sensor elements, magnetic sensor elements, or electromagnetic (radio frequency) sensor elements. In this manner, the sensor emitter elements emit waves of energy in any of various forms that are picked up by the sensor receiver elements. To compensate for noise introduced by the welding process, the system **100** may also include bandwidth suppressors, which may be implemented in the form of software and/or electronic circuitry. The bandwidth suppressors are used to condition the sensor signals to penetrate interference caused by the welding arc. Additionally, the system **100** may further incorporate inertial sensors, which may include one or more accelerometers. In this manner, data relating to position, orientation, velocity, and acceleration may be required to ascertain the movements (i.e., motion) of the weld torch **230**.

In one embodiment, part of the sensor arrays **160**, **165** are received by the weld torch **230**. That is to say that a portion of the sensors or sensor elements are affixed with respect to the body of the weld torch **230** (see sensor array **[160]** *165* of FIG. 2). In other embodiments, sensors and/or sensor elements may be affixed to a portion of the article being welded (see sensor array **[165]** *160* of FIG. 2). Still any manner of positioning and connecting the sensor elements may be chosen as is appropriate for tracking welding activity.

As an example of sensing and tracking a welding tool **230**, in accordance with an embodiment of the present invention, a magnetic sensing capability may be provided. For example, the receiver sensor array **165** may be a magnetic sensor that is mounted on the welding tool **230**, and the emitter sensor array **160** may take the form of a magnetic source. The magnetic source **160** may be mounted in a predefined fixed position and orientation with respect to the weldment **15**. The magnetic source **160** creates a magnetic field around itself, including the space encompassing the welding tool **230** during use and establishes a 3D spatial frame of reference. The magnetic sensor **165** is provided which is capable of sensing the magnetic field produced by the magnetic source. The magnetic sensor **165** is attached to the welding tool **230** and is operatively connected to the processor based computing device **110** via, for example, a cable, or wirelessly. The magnetic sensor **165** includes an array of three induction coils orthogonally aligned along three spatial directions. The induction coils of the magnetic sensor **165** each measure the strength of the magnetic field in each of the three directions and provide that information to the real time tracking module **121** of the processor based computing device **110**. As a result, the system **100** is able to know where the welding tool **230** is in space with respect to the 3D spatial frame of reference established by the magnetic field produced by the magnetic source **160**. In accordance with other embodiments of the present invention, two or more magnetic sensors may be mounted on or within the welding tool **230** to provide a more accurate representation of the position and orientation of the welding tool **230**, for example. Care is to be taken in establishing the magnetic 3D spatial frame of reference such that the weldment **15**, the tool **230**, and any other portions of the welding environment do not substantially distort the magnetic field created by the magnetic source **160**. As an alternative, such distortions may be corrected for or calibrated out as part of a welding environment set up procedure. Other non-magnetic technologies (e.g., acoustic, optical, electromagnetic, inertial, etc.) may be used, as previously discussed herein, to avoid such distortions, as are well known in the art.

With reference to all of the figures, operation of the system **100** will now be described in accordance with an embodiment of the present invention. The end user **10** activates the system

100 and enters his or her user name via the user interface 135. Once authorized access has been gained, the end user 10 traverses the menu system as prompted by the computer program product 120 via the GUI 135. The system 100 instructs the end user 10 to initiate set up of the welding article 15, which includes entering information about the weldment materials and/or welding process being used. Entering such information may include, for example, selecting a language, entering a user name, selecting a weld coupon type, selecting a welding process and associated axial spray, pulse, or short arc methods, selecting a gas type and flow rate, selecting a type of stick electrode, and selecting a type of flux cored wire.

In one embodiment, the end user enters the starting and ending points of the weld joint 16. This allows the system 100, via the real time tracking module 121, to determine when to start and stop recording the tracked information. Intermediate points are subsequently entered for interpolating the weld joint trajectory as calculated by the system 100. Additionally, sensor emitters and/or receivers 160, 165 are placed proximate to the weld joint at locations suitable for gathering data in a manner consistent with that described herein. After set up is completed, system tracking is initiated and the end user 10 is prompted to begin the welding procedure. As the end user 10 completes the weld, the system 100 gathers performance data including the speed, position and orientation of the weld torch 230 for analysis by the system 100 in determining welder performance characteristics and weld quality characteristics as previously described herein.

In summary, a system and a method for tracking and analyzing welding activity is disclosed. Dynamic spatial properties of a welding tool are sensed during a welding process producing a weld. The sensed dynamic spatial properties are tracked over time and the tracked dynamic spatial properties are captured as tracked data during the welding process. The tracked data is analyzed to determine performance characteristics of a welder performing the welding process and quality characteristics of a weld produced by the welding process. The performance characteristics and the quality characteristics may be subsequently reviewed.

While the claimed subject matter of the present application has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the claimed subject matter. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the claimed subject matter without departing from its scope. Therefore, it is intended that the claimed subject matter not be limited to the particular embodiment disclosed, but that the claimed subject matter will include all embodiments falling within the scope of the appended claims.

What is claimed is:

1. A system for tracking and analyzing welding activity, said system comprising:
 - means for automatically sensing [dynamic] spatial properties of a welding tool during a welding process producing a *real world* weld;
 - means for automatically tracking said sensed [dynamic] spatial properties [over time] during said welding process;
 - means for automatically capturing *in real time or near real time* said tracked dynamic spatial properties as tracked data during said welding process; and
 - means for automatically analyzing *in real time or near real time* said tracked data to determine [at least one of performance characteristics of a welder performing said

welding process and] a quality [characteristics] *characteristic* of [a] *said real world* weld produced by said welding process.

2. The system of claim 1, *wherein said analyzing further comprises determining a performance characteristic of a welder performing said welding process, and*

said system further [comprising] comprises means for reviewing said performance [characteristics] *characteristic* of [a] *said* welder performing said welding process.

3. The system of claim 1 further comprising means for reviewing said quality [characteristics] *characteristic* of [a] *said real world* weld produced by said welding process.

4. The system of claim 1 further comprising means for a user to locally interact with said system.

5. The system of claim 1 further comprising means for a user to remotely interact with said system.

6. The system of claim 1 further comprising means for automatically authorizing access to a user of said system.

7. The system of claim 1, *wherein said analyzing comprises determining a performance characteristic of a welder performing said welding process, and*

wherein said performance [characteristics of a welder include] characteristic includes at least one of a weld joint trajectory, a travel speed of said welding tool, welding tool pitch and roll angles, an electrode distance to a center weld joint, an electrode trajectory, and a weld time.

8. The system of claim 1 wherein said quality [characteristics of a weld produced by said welding process include] *characteristic includes* at least one of discontinuities and flaws within regions of [a] *said real world* weld produced by said welding process.

9. A system for tracking and analyzing welding activity, said system comprising:

at least one sensor array configured to sense [dynamic] spatial properties of a welding tool during a welding process producing a *real world* weld;

a processor based computing device operatively interfacing to said at least one sensor array and configured to track and analyze *in real time or near real time* said [dynamic] spatial properties of [a] *said* welding tool [over time] during [a] *said* welding process producing [a] *said real world* weld; and

at least one user interface operatively interfacing to said processor based computing device, *said at least one user interface displaying a quality characteristic of said real world weld produced by said welding process.*

10. The system of claim 9 wherein said at least one user interface includes a graphical user interface.

11. The system of claim 9 wherein said at least one user interface includes a display device.

12. The system of claim 9 further comprising a network interface configured to interface said processor based computing device to an external communication network.

13. The system of claim 9 wherein said at least one sensor array includes at least one of acoustical sensor elements, optical sensor elements, magnetic sensor elements, *inertial sensor elements*, and electromagnetic sensor elements.

14. A method for tracking and analyzing welding activity, said method comprising:

sensing [dynamic] spatial properties of a welding tool during a welding process producing a *real world* weld [using at least one sensor];

tracking said sensed [dynamic] spatial properties [over time] *in real time or near real time* during said welding process [using a real time tracking module];

11

capturing said tracked [dynamic] spatial properties as tracked data *in real time or near real time* during said welding process [using a computer based memory device]; and

analyzing said tracked data *in real time or near real time* to determine [at least one of performance characteristics of a welder performing said welding process and] a quality [characteristics] characteristic of [a] said real world weld produced by said welding process [using a computer based analysis engine].

15 15. The method of claim 14, wherein said analyzing further comprises determining a performance characteristic of a welder performing said welding process, and

wherein said method further [comprising] comprises outputting said performance [characteristics] characteristic of [a] said welder performing said welding process to at least one of a display device, a visualization module, and a testing module for review.

20 16. The method of claim 14 further comprising outputting said quality [characteristics] characteristic of [a] said real world weld produced by said welding process to at least one of a display device, a visualization module, and a testing module for review.

25 17. The method of claim 14 further comprising selecting welding set up parameters for said welding process via a user interface.

30 18. The method of claim [14] 15 further comprising remotely reviewing at least one of said performance [characteristics] characteristic of [a] said welder performing said welding process and said quality [characteristics] characteristic of [a] said real world weld produced by said welding process, via a communication network.

35 19. The method of claim 14, wherein said analyzing further comprises determining a performance characteristic of a welder performing said welding process, and

wherein said performance [characteristics of a welder include] characteristic includes at least one of a weld joint trajectory, a travel speed of said welding tool, welding tool pitch and roll angles, an electrode distance to a center weld joint, an electrode trajectory, and a weld time.

40 20. The method of claim 14 wherein said quality [characteristics of a weld produced by said welding process include] characteristic includes at least one of discontinuities and flaws within regions of [a] said real world weld produced by said welding process.

45 21. The system of claim 9, wherein said analysis of said spatial properties comprise determining at least one of a performance characteristic of a welder performing said welding process and a quality characteristic of said real world weld.

50 22. The system of claim 21, wherein said performance characteristic includes at least one of a weld joint trajectory, a travel speed of said welding tool, welding tool pitch and roll angles, an electrode distance to a center weld joint, an electrode trajectory, and a weld time.

55 23. The system of claim 21, wherein said quality characteristic includes at least one of a discontinuity and a flaw within a region of said weld produced by said welding process.

60 24. The system of claim 23, wherein said quality characteristic includes said flaw and said flaw comprises at least one of porosity and weld overfill.

65 25. The system of claim 24, wherein said spatial properties comprise at least one of a position, an orientation, and a movement of said welding tool.

12

26. The system of claim 9, wherein said welding tool comprises a portion of said at least one sensor array.

27. The system of claim 26, wherein said portion of said at least one sensor array includes at least one of acoustical sensor elements, magnetic sensor elements, inertial sensor elements, and electromagnetic sensor elements.

28. The system of claim 12, wherein said network interface is configured to transmit data representing said welding process to a remote system.

10 29. The system of claim 28, wherein said transmitted data comprises information related to a welder's performance.

30. The system of claim 9, wherein said processor based computing device is further configured to record in real time or near real time performance data corresponding to said welding process, and

wherein said performance data comprises at least one of a weld joint configuration or a weld joint trajectory, a weld speed, welding tool pitch and roll angles, an electrode distance to a center weld joint, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

31. The system of claim 30, wherein said processor based computing device is further configured to record at least one of weldment materials, electrode materials, user name, and project ID number.

32. The system of claim 31, wherein said analyzing further comprises comparing said performance data to known parameters to determine said quality characteristic of said real world weld.

33. The system of claim 9, wherein said analyzing comprises determining a score based on a comparison of at least one of said tracked spatial properties to an optimum value corresponding to said at least one of said tracked spatial properties.

34. The system of claim 33, wherein said optimum value is a range comprising an upper limit and a lower limit for said at least one of said tracked spatial properties.

35. The system of claim 34, wherein said tracked spatial properties comprise at least one of a weld joint trajectory, a weld speed, welding tool pitch angle, welding tool roll angle, an electrode distance to a center weld joint, a wire feed speed, and an electrode trajectory.

36. The system of claim 35, wherein said tracked spatial properties includes said welding tool pitch angle.

37. The system of claim 9, wherein said welding process is performed manually.

38. The system of claim 9, wherein said welding process is performed by a robotic welder.

39. The system of claim 11, wherein said display device is integrated into a welding helmet.

40. The system of claim 9, wherein said processor based computing device is configured to set up a virtual reality setting in which said welding process can be simulated using said spatial properties of said welding tool.

41. The system of claim 9, wherein said welding tool is one of an electrode holder and a welding torch.

42. The system of claim 9, wherein said analysis is performed by an expert system configured identify defective or potentially defective areas along a weld joint.

43. The system of claim 42, wherein said expert system comprises at least one of a rule-based system and a neural network.

44. The system of claim 43, wherein said expert system is said neural network and said analysis is based on weighted factors.

45. The system of claim 9, wherein said processor based computing device is further configured to capture information corresponding to said welding process in an analysis record for subsequent review.

46. The method of claim 14, wherein said sensing comprises measuring at least one of an acoustical signal, a magnetic signal, an optical signal, inertial signal, and an electromagnetic signal.

47. The method of claim 14, further comprising transmitting to a remote system data representing said welding process.

48. The method of claim 47, further comprising analyzing said welding process based on said transmitted data.

49. The method of claim 14, further comprising recording in real time or near real time performance data corresponding to said welding process,

wherein said performance data comprises at least one of a weld joint configuration or a weld joint trajectory, a weld speed, welding tool pitch and roll angles, an electrode distance to a center weld joint, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

50. The method of claim 49, wherein said recording further comprises recording data corresponding to at least one of weldment materials, electrode materials, user name, and project ID number.

51. The method of claim 49, wherein said analyzing comprises comparing said performance data to known parameters to determine said quality characteristic of said real world weld.

52. The method of claim 14, wherein said analyzing comprises determining a score based on a comparison of at least one of said tracked spatial properties to an optimum value.

53. The method of claim 52, wherein said optimum value is a range comprising an upper limit and a lower limit for said at least one of said tracked spatial properties.

54. The method of claim 53, wherein said tracked spatial properties comprise at least one of a weld joint trajectory, a weld speed, welding tool pitch angle, welding tool roll angle, an electrode distance to a center weld joint, a wire feed speed, and an electrode trajectory.

55. The system of claim 54, wherein said tracked spatial properties includes said welding tool pitch angle.

56. The method of claim 14, wherein said welding process is performed manually.

57. The method of claim 14, wherein said welding process is performed by a robotic welder.

58. The method of claim 14, further comprising storing information on said welding process an analysis record.

59. The method of claim 15, wherein said display device is integrated into a welding helmet.

60. The method of claim 16, wherein said display device is integrated into a welding helmet.

61. The method of claim 14, further comprising setting up a virtual reality setting in which said welding process can be simulated using said spatial properties of said welding tool.

62. The method of claim 14, wherein said welding tool is one of an electrode holder and a welding torch.

63. The method of claim 14, further comprising using an expert system to identify defective or potentially defective areas along said weld.

64. The method of claim 63, wherein said expert system uses at least one of a rule-based system and a neural network.

65. The method of claim 64, wherein said expert system uses said neural network and said identification is based on weighted factors.

66. The method of claim 14, further comprising capturing information corresponding to said welding process in an analysis record for subsequent review.

67. The method of claim 20, wherein said flaws comprise at least one of porosity and weld overfill.

68. The method of claim 67, wherein said spatial properties comprise at least one of a position, an orientation, and a movement of said welding tool.

69. A system for tracking and analyzing welding activity, said system comprising:

at least one sensor array configured to sense spatial properties of a welding tool during a welding process producing a real world weld; and

a processor based computing device operatively interfacing to said at least one sensor array and configured to track said spatial properties and record performance data corresponding to said welding process, said processor based computing device further configured to determine a quality characteristic of said real world weld.

70. The system of claim 69, wherein said analysis comprises comparing said performance data to known parameters to determine said quality characteristic of said weld.

71. The system of claim 70, wherein said quality characteristic includes at least one of a discontinuity and a flaw within a region of said weld.

72. The system of claim 71, wherein said recording is performed in real time or near real time.

73. The system of claim 72, wherein said spatial properties comprise at least one of a position, an orientation, and a movement of said welding tool, and

wherein said performance data comprises at least one of a weld joint configuration or a weld joint trajectory, a weld speed, welding tool pitch and roll angles, an electrode distance to a center weld joint, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

74. The system of claim 73, wherein said processor based computing device is further configured to record at least one of weldment materials, electrode materials, user name, and project ID number.

75. The system of claim 73, wherein said analyzing further comprises determining a score based on at least a comparison of at least one of said tracked spatial properties to an optimum value said at least one of said tracked spatial properties.

76. The system of claim 75, wherein said optimum value is a range comprising an upper limit and a lower limit for said at least one of said tracked spatial properties.

77. The system of claim 76, wherein said tracked spatial properties comprise at least one of a weld joint trajectory, a weld speed, welding tool pitch angle, welding tool roll angle, an electrode distance to a center weld joint, a wire feed speed, and an electrode trajectory.

78. The system of claim 77, wherein said tracked spatial properties includes said welding tool pitch angle.

79. The system of claim 71, wherein said quality characteristic includes said flaw and said flaw comprises at least one of porosity and weld overfill.

80. The system of claim 69, wherein said welding process is performed manually.

81. The system of claim 69, wherein said welding process is performed by a robotic welder.

82. The system of claim 69, further comprising a display device to display said quality characteristic.

83. The system of claim 82, wherein said display device is integrated into a welding helmet.

84. The system of claim 69, wherein said processor based computing device is configured to set up a virtual reality setting in which said welding process can be simulated using said spatial properties of said welding tool.

85. The system of claim 69, wherein said welding tool is one of an electrode holder and a welding torch.

86. The system of claim 69, wherein said analysis is performed by an expert system configured identify defective or potentially defective areas along said weld.

87. The system of claim 86, wherein said expert system is a neural network and said analysis is based on weighted factors.

88. The system of claim 69, wherein said processor based computing device is further configured to capture information corresponding to said welding process in an analysis record for subsequent review.

89. A system for tracking and analyzing welding activity, said system comprising:

a tracking module configured to track spatial positions of a welding tool during a welding process; and

a processor subsystem configured to ascertain at least one welding parameter during the welding process based on said tracked spatial positions and to determine a score based on a comparison of said at least one welding parameter to an optimum value.

90. The system of claim 89, wherein said at least one welding parameter includes a performance characteristic of a welder.

91. The system of claim 89, wherein said at least one welding parameter includes a quality characteristic of a weld.

92. The system of claim 89, wherein said at least one welding parameter includes a performance characteristic of a welder and a quality characteristic of a weld.

93. The system of claim 89, wherein said processor subsystem includes an expert system.

94. The system of claim 93, wherein said expert system comprises at least one of a rule-based system and a neural network.

95. The system of claim 89, wherein said optimum value is a range comprising an upper limit and a lower limit for said at least one welding parameter.

96. The system of claim 95, wherein said at least one welding parameter comprises at least one of a weld joint trajectory, a weld speed, welding tool pitch angle, welding tool roll angle, an electrode distance to a center weld joint, a wire feed speed, and an electrode trajectory.

97. The system of claim 96, wherein said tracked spatial properties includes said welding tool pitch angle.

98. The system of claim 97, wherein said welding process is performed manually.

99. The system of claim 89, wherein said welding process is performed by a robotic welder.

100. The system of claim 91, further comprising a display device to display said quality characteristic.

101. The system of claim 100, wherein said display is integrated into a welding helmet.

102. The system of claim 89, wherein said processor based computing device is configured to set up a virtual reality setting in which said welding process can be simulated using said spatial properties of said welding tool.

103. The system of claim 89, wherein said welding tool is one of an electrode holder and a welding torch.

104. A method for tracking and analyzing welding activity, said method comprising:

sensing spatial properties of a welding tool during a welding process producing a real world weld;

tracking said sensed spatial properties;
recording performance data corresponding to said welding process; and

analyzing said performance data in real-time or near real-time to determine a quality characteristic of said real world weld produced by said welding process.

105. The method of claim 104, wherein said analyzing comprises comparing said performance data to a known parameter to determine said quality characteristic of said real world weld.

106. The method of claim 105, wherein said welding process is performed by a robotic welder.

107. The method of claim 105, wherein said quality characteristic includes at least one of a discontinuity and a flaw within a region of said real world weld.

108. The method of claim 107, wherein said quality characteristic includes said flaw and said flaw comprises at least one of porosity and weld overfill.

109. The method of claim 107, wherein said recording is performed in real time or near real time.

110. The method of claim 109, wherein said spatial properties comprise at least one of a position, an orientation, and a movement of said welding tool, and

wherein said performance data comprises at least one of a weld joint configuration or a weld joint trajectory, a weld speed, welding tool pitch and roll angles, an electrode distance to a center weld joint, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

111. The method of claim 110, wherein further comprising recording at least one of weldment materials, electrode materials, user name, and project ID number.

112. The method of claim 104, wherein said analyzing further comprises determining a score based on at least a comparison of at least one of said tracked spatial properties to an optimum value.

113. The method of claim 112, wherein said optimum value is a range comprising an upper limit and a lower limit for said at least one of said tracked spatial properties.

114. The method of claim 113, wherein said tracked spatial properties comprise at least one of a weld joint trajectory, a weld speed, welding tool pitch angle, welding tool roll angle, an electrode distance to a center weld joint, a wire feed speed, and an electrode trajectory.

115. The system of claim 114, wherein said tracked spatial properties includes said welding tool pitch angle.

116. The method of claim 104, wherein said welding process is performed manually.

117. The method of claim 104, further comprising outputting said quality characteristic to a display device.

118. The method of claim 117, wherein said display device is integrated into a welding helmet.

119. The method of claim 104, further comprising setting up a virtual reality setting in which said welding process can be simulated using said spatial properties of said welding tool.

120. The method of claim 104, wherein said welding tool is one of an electrode holder and a welding torch.

121. The method of claim 104, further comprising using an expert system to identify defective or potentially defective areas along said weld.

122. The method of claim 121, wherein said expert system is a neural network and said identification is based on weighted factors.

123. The method of claim 104, further comprising capturing information corresponding to said welding process in an analysis record for subsequent review.

124. A method for tracking and analyzing welding activity, said system comprising:

tracking spatial positions of a welding tool during a welding process;

determining at least one welding parameter during the welding process based on said tracked spatial positions;

determining a score based on a comparison of said at least one welding parameter to an optimum value.

125. The method of claim 124, wherein said determining of said at least one welding parameter comprises analyzing a performance characteristic of a welder.

126. The method of claim 124, wherein said determining of said at least one welding parameter comprises analyzing a quality characteristic of a weld.

127. The method of claim 124, wherein said determining of said at least one welding parameter comprises analyzing a performance characteristic of a welder and a quality characteristic of a weld.

128. The method of claim 124, wherein said determining of said at least one welding parameter comprises using an expert system.

129. The method of claim 128, wherein said expert system uses at least one of a rule-based system and a neural network.

130. The method of claim 124, wherein said optimum value is a range comprising an upper limit and a lower limit for said at least one welding parameter.

131. The method of claim 130, wherein said at least one welding parameter comprises at least one of a weld joint trajectory, a weld speed, welding tool pitch angle, welding tool roll angle, an electrode distance to a center weld joint, a wire feed speed, and an electrode trajectory.

132. The method of claim 131, wherein said at least one welding parameter includes said welding tool pitch angle.

133. The method of claim 124, wherein said welding process is performed manually.

134. The method of claim 124, wherein said welding process is performed by a robotic welder.

135. The method of claim 124, further comprising setting up a virtual reality setting in which said welding process can be simulated using said spatial properties of said welding tool.

136. The system of claim 124, wherein said welding tool is one of an electrode holder and a welding torch.

137. A system for tracking welding activity, said system comprising:

an optical tracking system that tracks at least one of a position, a movement, and an orientation of a welding tool; and

a computer operatively interfacing to said optical tracking system, said computer determining at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool,

wherein said processor based computing device determines for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter.

138. The system of claim 137, wherein said score relates to a weld quality of a real world weld.

139. The system of claim 138, wherein said score relates to said weld quality of said real world weld, and

wherein said weld quality includes an indication of at least one of a discontinuity and a flaw within a region of said real world weld.

140. The system of claim 139, wherein said weld quality includes an indication of said flaw and said flaw comprises at least one of porosity and weld overfill.

141. The system of claim 139, wherein said determination of said score is performed in real time or near real time.

142. The system of claim 138, wherein an expert system identifies defective or potentially defective areas along said real world weld.

143. The system of claim 137, wherein said at least one parameter further includes at least one of a weld joint configuration or a weld joint trajectory, a weld speed, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

144. The system of claim 137, wherein said processor based computing device is further configured to record at least one of weldment materials, electrode materials, user name, and project ID number.

145. The system of claim 137, wherein said at least one predetermined limit includes an upper limit and a lower limit.

146. The system of claim 137, further comprising a display device to display said score.

147. The system of claim 146, wherein said display device is integrated into a welding helmet.

148. The system of claim 137, wherein said welding tool is one of an electrode holder and a welding torch.

149. A system for tracking welding activity, said system comprising:

an infrared tracking system that tracks at least one of a position, a movement, and an orientation of a welding tool based on an infrared element attached to said welding tool; and

a computer operatively interfacing to said infrared tracking system, said computer determining at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool,

wherein said computer determines for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter.

150. The system of claim 149, wherein said score relates to a weld quality of a real world weld.

151. The system of claim 150, wherein an expert system identifies defective or potentially defective areas along said real world weld.

152. The system of claim 150, wherein said score relates to said weld quality of said real world weld, and

wherein said weld quality includes an indication of at least one of a discontinuity and a flaw within a region of said real world weld.

153. The system of claim 152, wherein said weld quality includes an indication of said flaw and said flaw comprises at least one of porosity and weld overfill.

154. The system of claim 152, wherein said determination of said score is performed in real time or near real time.

155. The system of claim 149, wherein said at least one parameter further includes at least one of a weld joint configuration or a weld joint trajectory, a weld speed, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

156. The system of claim 149, wherein said processor based computing device is further configured to record at least one of weldment materials, electrode materials, user name, and project ID number.

157. The system of claim 149, wherein said at least one predetermined limit includes an upper limit and a lower limit.

158. The system of claim 149, further comprising a display device to display said score.

159. The system of claim 158, wherein said display device is integrated into a welding helmet.

160. The system of claim 149, wherein said welding tool is one of an electrode holder and a welding torch.

161. A method for tracking welding activity, said method comprising:

optically tracking at least one of a position, a movement, and an orientation of a welding tool;

determining at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool; and computing for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter.

162. The method of claim 161, wherein said score relates to a weld quality of a real world weld.

163. The method of claim 162, wherein an expert system identifies defective or potentially defective areas along said real world weld.

164. The method of claim 162, wherein said score relates to said weld quality of said real world weld, and

wherein said weld quality includes an indication of at least one of a discontinuity and a flaw within a region of said real world weld.

165. The method of claim 164, wherein said weld quality includes an indication of said flaw and said flaw comprises at least one of porosity and weld overflow.

166. The method of claim 164, wherein said determination of said score is performed in real time or near real time.

167. The method of claim 161, wherein said at least one parameter further includes at least one of a weld joint configuration or a weld joint trajectory, a weld speed, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

168. The method of claim 167, wherein said processor based computing device is further configured to record at least one of weldment materials, electrode materials, user name, and project ID number.

169. The method of claim 161, wherein said at least one predetermined limit includes an upper limit and a lower limit.

170. The method of claim 161, further comprising a display device to display said score.

171. The method of claim 170, wherein said display device is integrated into a welding helmet.

172. The method of claim 161, wherein said welding tool is one of an electrode holder and a welding torch.

173. A method for tracking welding activity, said method comprising:

tracking by infrared at least one of a position, a movement, and an orientation of a welding tool based on an infrared element attached to said welding tool;

determining at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool; and computing for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter.

174. The method of claim 173, wherein said score relates to a weld quality of a real world weld.

175. The method of claim 174, wherein said score relates to said weld quality of said real world weld, and

wherein said weld quality includes an indication of at least one of a discontinuity and a flaw within a region of said real world weld.

176. The method of claim 175, wherein said weld quality includes an indication of said flaw and said flaw comprises at least one of porosity and weld overflow.

177. The method of claim 175, wherein said determination of said score is performed in real time or near real time.

178. The method of claim 174, wherein an expert system identifies defective or potentially defective areas along said real world weld.

179. The method of claim 173, wherein said at least one parameter further includes at least one of a weld joint configuration or a weld joint trajectory, a weld speed, a wire feed speed, an electrode trajectory, a weld time, and time and date data.

180. The method of claim 179, wherein said processor based computing device is further configured to record at least one of weldment materials, electrode materials, user name, and project ID number.

181. The method of claim 173, wherein said at least one predetermined limit includes an upper limit and a lower limit.

182. The method of claim 173, further comprising a display device to display said score.

183. The method of claim 182, wherein said display device is integrated into a welding helmet.

184. The method of claim 173, wherein said welding tool is one of an electrode holder and a welding torch.

185. A system for tracking and analyzing welding activity, said system comprising:

at least one sensor array configured to sense spatial properties of a welding tool during a welding process producing a real world weld;

a processor based computing device operatively interfacing to said at least one sensor array and configured to track and analyze in real time or near real time said spatial properties of said welding tool during said welding process producing said real world weld; and

at least one display interfacing to said processor based computing device, said at least one display displaying a quality characteristic of said real world weld produced by said welding process.

186. A system for tracking welding activity, said system comprising:

an infrared tracking system that tracks at least one of a position, a movement, and an orientation of a welding tool based on an infrared emitter attached to said welding tool; and

a computer operatively interfacing to said infrared tracking system, said computer determining at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool, wherein said computer determines for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter.

187. A method for tracking welding activity, said method comprising:

tracking by infrared at least one of a position, a movement, and an orientation of a welding tool based on an infrared emission from said welding tool;

determining at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool, computing for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter.

188. A system for tracking welding activity, said system comprising:

an optical tracking system that tracks in real time or near real time at least one of a position, a movement, and an orientation of a welding tool; and

a computer operatively interfacing to said optical tracking system, said computer determining in real time or near

real time at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool, wherein said processor based computing device determines for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter, and wherein said score relates to a weld quality of a real world weld.

189. The system of claim 188, wherein said determination of said score is performed in real time or near real time.

190. A system for tracking welding activity, said system comprising:
 an infrared tracking system that tracks in real time or near real time at least one of a position, a movement, and an orientation of a welding tool based on an infrared element attached to said welding tool; and
 a computer operatively interfacing to said infrared tracking system, said computer determining in real time or near real time at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool,
 wherein said computer determines for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter, and
 wherein said score relates to a weld quality of a real world weld.

191. The system of claim 190, wherein said determination of said score is performed in real time or near real time.

192. A method for tracking welding activity, said method comprising:

optically tracking in real time or near real time at least one of a position, a movement, and an orientation of a welding tool;
 determining in real time or near real time at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool; and
 computing for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter, and
 wherein said score relates to a weld quality of a real world weld.

193. The method of claim 192, wherein said determination of said score is performed in real time or near real time.

194. A method for tracking welding activity, said method comprising:
 tracking by infrared in real time or near real time at least one of a position, a movement, and an orientation of a welding tool based on an infrared element attached to said welding tool;
 determining in real time or near real time at least one parameter that is at least one of a travel speed, a pitch angle, a roll angle, and an electrode distance to a center weld joint of said welding tool; and
 computing for each of said at least one parameter a score based on a comparison of said parameter to at least one predetermined limit for said parameter, and
 wherein said score relates to a weld quality of a real world weld.

195. The method of claim 194, wherein said determination of said score is performed in real time or near real time.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE45,398 E
APPLICATION NO. : 14/177692
DATED : March 3, 2015
INVENTOR(S) : Matthew Wayne Wallace

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims,

In column 9, line 63, delete “dynamic” and insert --[dynamic]--, therefor.

In column 11, line 51, delete “a” and insert --said--, therefor.

In column 12, line 46, delete “includes” and insert --include--, therefor.

In column 12, line 60, after “configured” insert --to--.

In column 13, line 7, before “inertial” insert --an--.

In column 13, line 43, delete “system” and insert --method--, therefor.

In column 13, line 44, delete “includes” and insert --include--, therefor.

In column 13, line 50, after “process” insert --in--.

In column 14, line 45, after “value” insert --corresponding to--.

In column 14, line 56, delete “includes” and insert --include--, therefor.

In column 15, line 8, after “configured” insert --to--.

In column 15, line 49, delete “includes” and insert --include--, therefor.

In column 15, lines 58-59, delete “based computing device” and insert --subsystem--, therefor.

In column 16, line 45, delete “system” and insert --method--, therefor.

Signed and Sealed this
Twenty-first Day of July, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office

In column 16, line 46, delete “includes” and insert --include--, therefor.

In column 17, line 42, delete “system” and insert --method--, therefor.

In column 17, line 54, delete “processor based computing device” and insert --computer--, therefor.

In column 18, lines 11-12, delete “processor based computing device” and insert --computer--,
therefor.

In column 18, lines 58-59, delete “processor based computing device” and insert --computer--,
therefor.

In column 19, lines 33-34, delete “processor based computing device is further configured to record”
and insert --computing further includes recording--, therefor.

In column 20, lines 9-10, delete “processor based computing device is further configured to record”
and insert --computing further includes recording--, therefor.

In column 21, line 4, delete “processor based computing device” and insert --computer--,
therefor.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE45,398 E
APPLICATION NO. : 14/177692
DATED : March 3, 2015
INVENTOR(S) : Matthew Wayne Wallace

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

In Column 17, Line 2, delete “system” and insert --method--, therefor.

Signed and Sealed this
Tenth Day of January, 2017



Michelle K. Lee
Director of the United States Patent and Trademark Office

(12) INTER PARTES REVIEW CERTIFICATE (1665th)

**United States Patent
Wallace**

**(10) Number: US RE45,398 K1
(45) Certificate Issued: Feb. 24, 2020**

**(54) SYSTEM FOR TRACKING AND
ANALYZING WELDING ACTIVITY**

(71) Applicant: Lincoln Global, Inc.

(72) Inventor: Matthew Wayne Wallace

(73) Assignee: Lincoln Global, Inc.

Trial Number:

IPR2016-00840 filed Apr. 18, 2016

Inter Partes Review Certificate for:

Patent No.: **RE45,398**
Issued: **Mar. 3, 2015**
Appl. No.: **14/177,692**
Filed: **Feb. 11, 2014**

The results of IPR2016-00840 are reflected in this inter partes review certificate under 35 U.S.C. 318(b).

INTER PARTES REVIEW CERTIFICATE
U.S. Patent RE45,398 K1
Trial No. IPR2016-00840
Certificate Issued Feb. 24, 2020

1

2

AS A RESULT OF THE INTER PARTES
REVIEW PROCEEDING, IT HAS BEEN
DETERMINED THAT:

Claims 9-31, 33-41, 45-50, 52-62, 66-69, 80-85, 88-92,
95-104, 112-120, 123-127, 130-141, 143-150, 152-162, 164-
177 and 179-195 are cancelled. ⁵

* * * * *