



US00RE45599E

(19) **United States**
(12) **Reissued Patent**
Moldoveanu

(10) **Patent Number:** **US RE45,599 E**
(45) **Date of Reissued Patent:** **Jul. 7, 2015**

(54) **METHOD TO ACQUIRE SIMULTANEOUSLY SEISMIC DATA WITH SOURCE ARRAYS DESIGNED FOR SPECIFIC TARGETS**

(75) Inventor: **Nicolae Moldoveanu**, Houston, TX (US)

(73) Assignee: **WESTERNGECO L.L.C.**, Houston, TX (US)

(21) Appl. No.: **14/047,163**

(22) Filed: **Oct. 7, 2013**

4,648,080 A	3/1987	Hargreaves	
4,721,180 A	1/1988	Haughland et al.	
4,739,858 A	4/1988	Dragoset, Jr.	
RE32,683 E *	5/1988	Ray	367/23
4,813,026 A	3/1989	Quaglino	
4,868,794 A	9/1989	Ziolkowski et al.	
4,956,822 A	9/1990	Barber et al.	
4,992,990 A	2/1991	Langeland et al.	
5,142,498 A	8/1992	Duren	
5,148,406 A	9/1992	Brink et al.	
5,281,773 A *	1/1994	Duren	181/111
5,717,655 A	2/1998	Beasley	
5,924,049 A	7/1999	Beasley et al.	
5,995,452 A *	11/1999	Bouyoucus	367/153

(Continued)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,948,825**
 Issued: **May 24, 2011**
 Appl. No.: **11/569,255**
 PCT Filed: **Jun. 17, 2004**
 PCT No.: **PCT/US2004/019184**
 § 371 (c)(1),
 (2), (4) Date: **Nov. 17, 2006**
 PCT Pub. No.: **WO2005/111657**
 PCT Pub. Date: **Nov. 24, 2005**

FOREIGN PATENT DOCUMENTS

AU	2004319619	11/2005
EP	0320073	5/1994

(Continued)

OTHER PUBLICATIONS

International Search Report of PCT Application No. PCT/US2004/019184 dated Dec. 23, 2004: pp. 1-3.

(Continued)

U.S. Applications:

(60) Provisional application No. 60/567,895, filed on May 4, 2004.

Primary Examiner — Mark Hellner

- (51) **Int. Cl.**
G01V 1/38 (2006.01)
- (52) **U.S. Cl.**
CPC **G01V 1/3861** (2013.01)
- (58) **Field of Classification Search**
USPC 367/14, 15, 144, 118; 181/118
See application file for complete search history.

(57) **ABSTRACT**


A method and apparatus for acquiring seismic data. In one embodiment, the method includes: moving a first air gun array in the water at a first depth and a second air gun array in the water at a second depth greater than the first depth, in which the total volume of the first air gun array is less than the total volume of the second air gun array, in which the first air gun array is separated from the second air gun array by a distance substantially equal to a shot point interval, firing seismic energy through the first and second air gun arrays through the water into the earth, and recording seismic signals reflected from strata in the earth beneath the water.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,744,021 A	7/1973	Todd
4,493,061 A	1/1985	Ray

13 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,044,038	A	3/2000	Allensworth	
6,446,008	B1	9/2002	Ozbek	
6,493,636	B1	12/2002	DeKok	
6,651,007	B2	11/2003	Ozbek	
6,671,223	B2	12/2003	Bittleston	
6,684,160	B1	1/2004	Ozbek et al.	
6,961,284	B2 *	11/2005	Moldoveanu	367/154
7,577,060	B2 *	8/2009	Toennessen et al.	367/16
7,800,977	B2	9/2010	Grion	
7,948,825	B2	5/2011	Moldoveanu	
7,961,549	B2	6/2011	Moldoveanu et al.	
8,559,264	B2	10/2013	Moldoveanu	
2002/0126565	A1	9/2002	Kawai et al.	
2003/0067842	A1	4/2003	Sukup et al.	
2008/0011540	A1 *	1/2008	Moldoveanu et al.	181/110

FOREIGN PATENT DOCUMENTS

GB	2141824	1/1985
GB	2141824 A	1/1985
WO	00/20895	4/2000
WO	01/16621	3/2001
WO	01/75481	10/2001
WO	2005111656	11/2005

OTHER PUBLICATIONS

Examination Report of British Application No. GB0623924.8 dated May 18, 2007: pp. 1-4.

Lunnon, "An evaluation of peak and bubble tuning in sub-basalt imaging: modeling and results," 65th Mtg. Europ. Assn. Geosci. Eng., Paper C01, 2003.

White, et al., "iSIMM pushes frontiers of marine seismic acquisition," First Break, vol. 20, Dec. 2002.

P. Austad, et al., "Marine Seismic Cable Steering and Computerized Control Systems," SEG Expanded Abstracts, 2000.

F. Avedik, et al., "Single bubble air-gun array for deep exploration," Geophysics vol. 58, Issue 3, 1993, pp. 366-382.

P. Christie, et al., "iSIMM looks beneath basalt for both industry and university research," 5th Conference & Exposition on Petroleum Geophysics in Hyderabad, India, 2004, pp. 186-193.

S. Grion, et al., "Over/under acquisition: breaking the resolution limits," 56th Mtg. European Association of Geoscientists Engineers, Jun. 2-5, 2003.

J. Martin, et al., "Acquisition of marine point receiver seismic data with a towed streamer," SEG 2000 Expanded Abstracts, pp. 1-4, 2000.

S. C. Singh, et al., "Broadband receiver response from dual-streamer data and applications in deep reflection seismology," Geophysics vol. 61, Issue 1, pp. 232-243, 1996.

L. Sonneland, et al., "2-D Deghosting Using Vertical Receiver Arrays," EAGE Extended Abstract, S11.6, 1986.

A. Ziolkowski, et al., "The signature of an air gun array," Computation from near-field measurements including interactions, Geophysics, vol. 47, No. 10, pp. 1413-1421, 1982.

A. Ziolkowski, et al., "The use of low frequencies for sub-basalt imaging," 71st Annual International Meeting for Society of Exploration Geophysics, pp. 74-77, 2001.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5




FIG. 6

**METHOD TO ACQUIRE SIMULTANEOUSLY
SEISMIC DATA WITH SOURCE ARRAYS
DESIGNED FOR SPECIFIC TARGETS**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

*CROSS-REFERENCES TO RELATED
APPLICATIONS*

This application is a reissue of U.S. patent application Ser. No. 11/569,255, now U.S. Pat. No. 7,948,825, which is the U.S. National Stage of International Application No. PCT/US2004/019184, filed Jun. 17, 2004, which claims the benefit of and priority to U.S. Provisional Patent Application No. 60/567,895, filed May 4, 2004.

BACKGROUND OF THE INVENTION

1. Field of the Invention

Embodiments of the present invention generally relate to marine seismic surveying, and more preferably, to methods for acquiring seismic data.

2. Description of the Related Art

Seismic exploration is widely used to locate and/or survey subterranean geological formations for hydrocarbon deposits. Since many commercially valuable hydrocarbon deposits are located beneath bodies of water, various types of marine seismic surveys have been developed. In a typical marine seismic survey, seismic streamers are towed behind a survey vessel. The seismic streamers may be several thousand meters long and contain a large number of sensors, such as hydrophones, geophones, and associated electronic equipment, which are distributed along the length of the each seismic streamer cable. The survey vessel also includes one or more seismic sources, such as air guns and the like.

As the seismic streamers are towed behind the survey vessel, acoustic signals, commonly referred to as "shots," produced by the one or more seismic sources are directed down through the water into strata beneath the water bottom, where they are reflected from the various subterranean geological formations. Reflected signals are received by the sensors, digitized, and then transmitted to the survey vessel. The digitized signals are referred to as "traces" and are recorded and at least partially processed by a signal processing unit deployed on the survey vessel. The ultimate aim of this process is to build up a representation of the subterranean geological formations beneath the streamers. Analysis of the representation may indicate probable locations of hydrocarbon deposits in the subterranean geological formations.

Many of the subterranean geological formations are better represented with low frequency seismic signals. Accordingly, a need exists in the art for one or more methods for acquiring seismic signals from subterranean geological formations that are better represented with low frequency seismic signals.

SUMMARY OF THE INVENTION

One or more embodiments of the invention are directed to a method for acquiring seismic data. In one embodiment, the method includes: moving a first air gun array in the water at a first depth and a second air gun array in the water at a second

depth greater than the first depth, in which the total volume of the first air gun array is less than the total volume of the second air gun array, in which the first air gun array is separated from the second air gun array by a distance substantially equal to a shot point interval; firing seismic energy by the first and second air gun arrays through the water into the earth; and recording seismic signals reflected from strata in the earth beneath the water.

In another embodiment, the method includes towing one or more seismic streamers in the water; towing a first air gun array and a second air gun array in the water at a first depth, in which the first and second air gun arrays are separated by a cross line distance that depends on a separation between the streamers; towing a third air gun array and a fourth air gun array in the water at a second depth greater than the first depth, in which the third and fourth air gun arrays are separated by the cross line distance that depends on the separation between the streamers; firing seismic energy, by the first, second, third and fourth air gun arrays, through the water into the earth; and recording seismic signals reflected from strata in the earth beneath the water.

In yet another embodiment, the method includes towing one or more seismic streamers in the water at one or more first depths defined by one or more first z coordinates and at a first x coordinate and a first y coordinate, in which each seismic streamer comprises a plurality of hydrophones disposed therealong; towing one or more air gun arrays in the water at one or more second depths defined by one or more second z coordinates and at substantially a second x coordinate and a second y coordinate; firing seismic energy, by the air gun arrays, through the water into the earth; and recording through the hydrophones seismic signals reflected from strata in the earth beneath the water.

One or more embodiments of the invention are also directed to a marine surveying arrangement. In one embodiment, the marine surveying arrangement includes a first air gun array tuned to a first bubble oscillation. The first air gun array has a first total volume. The marine surveying arrangement also includes a second air gun array tuned to a leading peak. The second air gun array has a second total volume that is greater than the first total volume. The second air gun array is horizontally separated from the first air gun array by a distance substantially equal to the speed at which the air gun arrays are moving multiplied by a delay time between the firing of the first air gun array and the firing of the second air gun array. The marine surveying arrangement further includes one or more seismic streamers having a plurality of hydrophones disposed therealong.

In another embodiment, the marine surveying arrangement includes one or more streamers having a separation therebetween, a first vessel deploying a first air gun array and a second air gun array separated by a cross line distance defined by the separation between the streamers. The first and second air gun arrays are tuned to a leading peak. Each one of the first and second air gun arrays has a first total volume. The marine surveying arrangement also includes a second vessel deploying a third air gun array and a fourth air gun array separated by the cross line distance. The third and fourth air gun arrays are tuned to a first bubble oscillation. Each one of the third and fourth air gun arrays has a second total volume greater than the first total volume.

BRIEF DESCRIPTION OF THE DRAWINGS

So that the manner in which the above recited features of the present invention can be understood in detail, a more particular description of the invention, briefly summarized

above, may be had by reference to embodiments, some of which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only typical embodiments of this invention and are therefore not to be considered limiting of its scope, for the invention may admit to other equally effective embodiments.

FIG. 1 illustrates a seismic survey vessel that may be used to acquire seismic data in accordance with one embodiment of the invention.

FIG. 2 illustrates a portion of the seismic streamer with an attached positioning device that may be used to acquire seismic data in accordance with one embodiment of the invention.

FIG. 3 illustrates a flow diagram of a method for enhancing the acquisition of low frequency seismic signals for sub-salt imaging in accordance with one embodiment of the invention.

FIG. 4A illustrates a cross sectional view of an air gun array configuration in accordance with one embodiment of the invention.

FIG. 4B illustrates a plan view of an air gun array configuration in accordance with another embodiment of the invention.

FIG. 4C illustrates a cross sectional view of an air gun array configuration in accordance with yet another embodiment of the invention.

FIG. 4D illustrates a cross sectional view of a seismic streamer configuration in accordance with one embodiment of the invention.

FIG. 5 illustrates up-going and down-going wave fields corresponding to at least one provided acoustic signal, or shot, in a marine seismic survey that may be used in connection with one embodiment of the invention.

FIG. 6 illustrates a flow diagram of a method for forming an over/under combination using one or more calibration filters that may be used in connection with one or more embodiments of the invention.

DETAILED DESCRIPTION

FIG. 1 illustrates a seismic survey vessel **10** that may be used to acquire seismic data in accordance with one embodiment of the invention. The seismic survey vessel **10** is shown towing an array of air guns **14**. The seismic survey vessel **10** is also shown towing an array of eight seismic streamers **12**. Each streamer **12** may be 6000 meters in length. The outermost streamers **12** in the array could be 700 meters apart, resulting in a horizontal separation of 100 meters between each streamer.

The air gun array **14** is comprised of air guns of varying sizes. The total volume of the air gun array **14** is 6000 cubic inches or greater. In one embodiment, the total volume of the air gun array **14** is in a range between 6780 to 10,170 cubic inches. In another embodiment, the total volume of the air gun array **14** is 8475 cubic inches. Air gun arrays with larger volumes generally allow greater penetration beneath the salt region. The air gun array **14** used in connection with various embodiments of the invention may include various types of air guns, such as Bolt LL guns, GI injector guns and the like. Although various embodiments of the invention are described with reference to air guns, other types of emitters, such as marine vibrator units, are also contemplated by the invention.

The air gun array **14** may also be tuned to the first bubble oscillation. Tuning the air gun array **14** to the first bubble oscillation includes staggering the firing of each air gun within the array so that the first bubble oscillations generated by the air guns coincide, thereby emitting a source signature having high amplitudes at low frequencies. The period of the

bubble emitted from each air gun depends on the volume of that air gun. For instance, air guns with small volumes emit bubbles with short periods. Accordingly, by appropriately staggering the firing of each air gun with a delay, the first bubble oscillations from all of the air guns within the air gun array **14** can be coordinated to occur at the same time. The air guns may be fired with delays that increase with decreasing air gun volume. The firings of the air guns may be staggered according to various techniques from commonly assigned U.S. Pat. No. 4,739,858, issued to Dragoset, Jr., which is incorporated herein by reference. In another embodiment, the air gun array **14** may be tuned to the leading peak. As such, the air guns are fired simultaneously to enhance the primary pulse and to minimize the bubble reverberation by destructive interference, thereby producing a seismic source signal having high amplitudes at high frequencies.

As a result of tuning the air gun array **14** to the first bubble oscillation, the source signature of the air gun array **14** may contain a mixed phase spectrum, which necessitates deterministic deconvolution to shape the source signature during processing. Deterministic deconvolution, however, may require the source signature of the air gun array **14** to be determined. The source signature of the air gun array **14** may be determined by first positioning a set of hydrophones adjacent the air guns but spaced therefrom by a distance such that none of the hydrophones penetrates the air bubbles produced by the air guns. Then, the emitted pressure wave in the near field of the air gun array at n independent points whose positions are known with respect to the air gun array is measured. The measurements are then processed by taking into account the interactions between the air guns to construct at least notionally an equivalent array of n non-interacting independent sources having n equivalent signatures which are superposable to provide the source signature of the air gun array **14**. The source signature of the air gun array **14** is then determined by superposing then equivalent signatures. In one embodiment, the source signature of the air gun array is the far field source signature of the air gun array. The above referenced process may be described in further detail in U.S. Pat. No. 4,868,794 issued to Ziolkowski et al., which is incorporated herein by reference. The source signature of the air gun array may then be used to design a designator operator on a shot by shot basis. In one embodiment, the air gun array diagnostics, such as, the firing time of each air gun, the depth of each air gun and the like, are recorded for each shot. The source signature of the air gun array **14** may then be computed using the air gun array diagnostics and a source signature computer modeling program, as commonly known by ordinary persons skilled in the art.

With regards to the streamers **12**, each streamer **12** includes a deflector **16** at a front portion and a tail buoy **20** at a rear portion. The deflector **16** is used to horizontally position the end of the streamer **12** nearest the seismic survey vessel **10** and the tail buoy **20** is used to create a drag at the end of the streamer **12** farthest from the seismic survey vessel **10**. The tension created on the seismic streamer **12** by the deflector **16** and the tail buoy **20** results in the roughly linear shape of the seismic streamer **12** shown in FIG. 1.

A plurality of streamer positioning devices **18**, known as birds, is positioned between the deflector **16** and the tail buoy **20**. Preferably, the positioning devices **18** are both vertically and horizontally steerable. These positioning devices **18** may, for instance, be located at regular intervals along the streamer **12**, such as every 200 to 400 meters. The vertically and horizontally positioning devices **18** can be used to constrain the shape of the seismic streamer **12** between the deflector **16** and the tail buoy **20** in both the vertical (depth) and horizontal

directions. A control system for the positioning devices **18** is distributed between a global control system **22** located on or near the seismic survey vessel **10** and a local control system **36** (shown in FIG. **2**) located within or near the positioning devices **18**. The global control system **22** is typically connected to the seismic survey vessel's navigation system and obtains estimates of system wide parameters, such as the vessel's towing direction and velocity and current direction and velocity, from the vessel's navigation system.

The global control system **22** monitors the actual positions of each of the positioning devices **18** and is programmed with the desired positions of or the desired minimum separations between the seismic streamers **12**. The horizontal positions of the positioning devices **18** can be derived, for instance, using the types of acoustic positioning systems described in commonly assigned U.S. Pat. No. 4,992,990, which is incorporated herein by reference. Alternatively, or additionally, a satellite-based global positioning system can be used to determine the positions of the equipment. The vertical positions of the positioning devices **18** are typically monitored using pressure sensors attached to the positioning devices **18**, as discussed below.

The global control system **22** preferably maintains a dynamic model of each of the seismic streamers **12** and utilizes the desired and actual positions of the positioning devices **18** to regularly calculate updated desired vertical and horizontal forces the positioning devices **18** should impart on the seismic streamers **12** and to move them from their actual positions to their desired positions. The global control system **22** preferably calculates the desired vertical and horizontal forces based on the behavior of each streamer **12** and also takes into account the behavior of the complete streamer array. Due to the relatively low sample rate and time delay associated with the horizontal position determination system, the global control system **22** runs position predictor software to estimate the actual locations of each of the positioning devices **18**. The global control system **22** also checks the data received from the vessel's navigation system. The global control system **22** will typically acquire the following parameters from the vessel's navigation system: vessel speed (m/s), vessel heading (degrees), current speed (m/s), current heading (degrees), and the location of each of the positioning devices **18** in the horizontal plane in a vessel fixed coordinate system. Current speed and heading can also be estimated based on the average forces acting on the streamers **12** by the positioning devices **18**. The global control system **22** will preferably send the following values to the local bird controller: demanded vertical force, demanded horizontal force, towing velocity, and crosscurrent velocity.

FIG. **2** illustrates a portion of the seismic streamer **12** with an attached positioning device **18**, which is capable of controlling the position of seismic streamer **12** in both the vertical and horizontal directions. The seismic streamer **12** further includes a communication line **24**, which may consist of a bundle of fiber optic data transmission cables and power transmission wires. The communication line **24** passes along the length of the seismic streamer **12** and is connected to the seismic sensors (not shown), hydrophones **26**, which are distributed along the length of the streamer **12**, and to the positioning device **18**. The positioning device **18** preferably has a pair of independently moveable wings **28**, which are connected to rotatable shafts **32**, which are rotatable by wing motors **34**. The positioning device **18** allows the orientation of the wings **28** with respect to the positioning device body **30** to be changed.

The wing motors **34** may consist of any type of device that is capable of changing the orientation of the wings **28**. The

wing motors **34** may either be electric motors or hydraulic actuators. The local control system **36** controls the movement of the wings **28** by calculating a desired change in the angle of the wings **28** and selectively driving the motors **34** to effectuate this change.

One of the benefits of the above referenced control system is that the desired change in the orientation of the wing **28** is calculated using an estimate of the velocity of the positioning device **18** rather than simply relying on a feedback-loop type of control system that operates in the same manner regardless of the vessel speed. Because the force produced by wing **28** is proportional to the velocity of the device squared, a much more precise calculation of the desired change in the wing orientation can be made by using an estimate of the device velocity. As mentioned above, the global control system **22** shares responsibilities with the local control system **36**. The global control system **22** is tasked with monitoring the positions of the streamers **12** and providing desired forces or desired position information to the local control system **36**. The local control system **36** within each positioning device **18** is tasked with adjusting the wing splay angle to rotate the positioning device **18** to the proper position and for adjusting the wing common angle to produce the magnitude of total desired force required. The positioning devices **18**, including the global control system **22** and the local control system **36** are described in more detail in commonly assigned GB/2,342,081, which is incorporated herein by reference. One or more embodiments of the invention also contemplate other designs for the positioning devices **18**, including those utilizing one full-moving wing with ailerons, three full-moving wings, four full-moving wings, and those described in commonly assigned U.S. Pat. No. 6,671,223, which is incorporated herein by reference.

With respect to the hydrophones **26**, in one embodiment, the hydrophones **26** may not be wired as to form groups that generate a single output. Rather, each hydrophone **26** is set to generate a separate output, which is subsequently filtered by an adaptive beamformer. The adaptive beamformer includes two or more spatially and/or temporally local multichannel adaptive filters with two or more channels. The adaptive beamformer is configured to discriminate its response in accordance with the spatial and/or temporal spectral content of the input signals. In this manner, filtered output signals can be generated and recorded for each hydrophone. The hydrophones **26** may be spaced at intervals of 3.125 meters to attenuate unwanted noise in the received seismic signals. The spacing between the hydrophones **26** may be based on a number of factors, such as available bandwidth for data transmission and recording or manufacturing costs. The spacing between the hydrophones **26** in combination with the adaptive beamformer are configured to reduce unwanted noise, particularly coherent noise, such as bulge wave noise, swell noise, and crossflow noise. The hydrophone configuration and the adaptive beamformer are described in more detail in commonly assigned U.S. Pat. No. 6,684,160, which is incorporated herein by reference.

FIG. **3** illustrates a flow diagram of a method **300** for enhancing the acquisition of low frequency seismic signals for sub-salt imaging in accordance with one embodiment of the invention. At step **310**, the air gun array **14** is towed at 10.2 meters or deeper. In one embodiment, the air gun array **14** may be towed between 10-25 meters deep. By placing the air gun array at such depths, the pass band of the source ghost response migrates to lower frequencies, thereby permitting the low frequency signal to be preserved. Accordingly, the depth of the air gun array **14** may be selected such that the pass

zone of the ghost response coincides with a frequency range of the energy generated by the air gun array 14.

At step 320, the seismic streamers 12 are towed at 10.2 meters or deeper. In one embodiment, the seismic streamers 12 may be towed between 10-25 meters deep. By placing the seismic streamers 12 at such depths, the pass band of the streamer ghost response migrates to lower frequencies, thereby permitting the low frequency signal to be preserved. Accordingly, the depth of the seismic streamers 12 may be selected such that the pass zone of the ghost response coincides with a frequency range of the energy generated by the air gun array 14.

At step 330, the seismic signals reflected from strata in the earth beneath the salt region are received by the hydrophones disposed on the seismic streamers 12. During acquisition, a low cut filter is often used to reduce swell noise contamination. However, the low cut filter also removes low frequency signals. In accordance with one embodiment of the invention, the seismic signals are recorded by the hydrophones without any low cut filters or with the low cut filter option turned off. In this manner, the amplitude of the low frequency signals may be enhanced.

In accordance with one or more embodiments of the invention, the seismic signals may be acquired using various air gun array and streamer configurations. FIG. 4A illustrates a cross sectional view of an air gun array configuration in accordance with one embodiment of the invention, which includes air gun arrays 402 and 404. Air gun array 402 is configured to enhance high frequency seismic signals, while air gun array 404 is configured to enhance low frequency seismic signals. Air gun array 402 is peak tuned, i.e., air gun array 402 is tuned to the leading peak, while air gun array 404 is bubble tuned, i.e., the air gun array 404 is tuned to the first bubble oscillation. In one embodiment, air gun array 402 may be bubble tuned, while air gun array 404 may be peak tuned. The total volume of air gun array 404 is greater than the total volume of air gun array 402. For example, air gun array 402 has a total volume of 5085 cubic inches, whereas air gun array 404 has a total volume of 6780 cubic inches.

Air gun array 404 is disposed at a greater depth than air gun array 402. For example, air gun array 402 is disposed at a depth between about 6 to 8 meters, while air gun array 404 is disposed at a depth between about 14 to 18 meters. The difference in depth between air gun array 402 and air gun array 404 may be selected such that $I/dt < f_{max}$, where f_{max} is the maximum frequency in the seismic data. The time dt is determined by the depth difference between the two emitter arrays and by the velocity of seismic energy in water, which is a known quantity.

In addition to being separated in the vertical direction (z direction), the two air gun arrays are displaced by a horizontal distance dx in the horizontal direction (x direction). The horizontal displacement between the two emitter arrays is substantially equal to the shot point interval of the marine seismic surveying arrangement. As an example, for a seismic surveying arrangement that generates a shot point interval of 37.5 m, the horizontal displacement of the air gun arrays is approximately 37.5 m.

The two air gun arrays, however, are not displaced in the y direction, which extends out of the paper and perpendicular to the direction of movement of the air gun arrays. The seismic survey vessel 10 is configured to tow air gun arrays 402 and 404 at a speed V .

In use, the air gun arrays 402 and 404 are moved through the water in the direction along which the arrays are displaced. The air gun arrays 402 and 404 are fired in a "flip flop" sequence at equal shot point intervals, e.g., 37.5 m. The air

guns on the array nearer the seismic survey vessel 10, i.e., air gun array 402, are fired initially. These air guns may be fired consecutively or simultaneously. After a time delay equal to the time required for the towing vessel to travel 37.5 m (i.e., dx/V), the air guns of the air gun array further from the seismic survey vessel 10, i.e., air gun array 404, are fired. The time delay dx/V between the firings of the two air gun arrays ensures that each air gun of one array is fired at the same x and y coordinates as the corresponding air gun of the other array, but at different depths. As such, two shot records are generated at points having the same x and y coordinates, but at different z coordinates (depths). In one embodiment, the air gun arrays 402 and 404 are fired simultaneously using a source encoding technique such that each wavefield is encoded with a signature to indicate the air gun array to which the encoded wavefield is associated. Various encoding techniques are discussed in more detail in commonly assigned U.S. Pat. No. 5,924,049, which is incorporated herein by reference.

FIG. 4B illustrates a plan view of an air gun array configuration in accordance with one embodiment of the invention, which includes air gun arrays 412, 422, 414 and 424. Air gun arrays 412 and 422 are towed by seismic survey vessel 420, while air gun arrays 414 and 424 are towed by seismic survey vessel 430. Seismic survey vessel 430 is shown as directly behind seismic survey vessel 420. Seismic survey vessel 430, however, may be positioned anywhere relative to seismic survey vessel 420. For instance, seismic survey vessel 430 may be placed beside seismic survey vessel 420. The two seismic survey vessels may be separated by a distance based on geophysical or survey design considerations, such as an offset range.

Air gun arrays 412 and 422 are configured to enhance high frequency seismic signals, while air gun arrays 414 and 424 are configured to enhance low frequency seismic signals. Air gun arrays 412 and 422 are peak tuned, while air gun arrays 414 and 424 are bubble tuned. In one embodiment, air gun arrays 412 and 422 may be bubble tuned, while air gun arrays 414 and 424 may be peak tuned. The total volume of air gun arrays 414 and 424 is greater than the total volume of air gun arrays 412 and 422. For example, each one of air gun arrays 412 and 422 has a total volume of 5085 cubic inches, whereas each one of air gun arrays 414 and 424 has a total volume of 6780 cubic inches.

Air gun arrays 414 and 424 are disposed at a greater depth than air gun arrays 412 and 422. For example, air gun arrays 412 and 422 may be disposed at a depth of about 6 to 8 meters, while air gun arrays 414 and 424 may be disposed at a depth of about 14 to 18 meters.

Air gun arrays 412 and 422 are separated by a cross line distance dy in the y direction. The cross line distance dy between air gun arrays 412 and 422 depends on the separation between the streamers 12. Preferably, the cross line distance dy is half of the steamer separation. Air gun arrays 412 and 422, however, are not displaced in the x direction. Likewise, air gun arrays 414 and 424 are separated by the same cross line distance dy that separates air gun arrays 412 and 422, and are not displaced in the x direction.

In use, air gun arrays 412, 422, 414 and 424 are fired simultaneously using a source encoding technique such that each wavefield is encoded with a signature to indicate the air gun array with which the encoded wavefield is associated. As mentioned above, various encoding techniques are discussed in more detail in commonly assigned U.S. Pat. No. 5,924,049, which is incorporated herein by reference.

FIG. 4C illustrates a cross sectional view of an air gun array configuration in accordance with one embodiment of the

invention, which includes air gun arrays **432**, **434** and **436**. Air gun arrays **432**, **434** and **436** are disposed in the water at three different depths. Air gun array **432** is disposed substantially vertically above air gun array **434**, while air gun array **434** is disposed substantially vertically above air gun array **436**. In this manner, air gun arrays **432**, **434** and **436** have the same x and y coordinates but different z coordinates. This arrangement may be referred to as an over/under combination of the air gun arrays. The term “over” is typically associated with the shallower air gun arrays and the term “under” is typically associated with the deeper air gun arrays. In use, air gun arrays **412**, **422**, **414** and **424** may be fired in a “flip flop” sequence, or simultaneously using a source encoding technique such that each wavefield is encoded with a signature to indicate the particular air gun array to which the encoded wavefield is associated. Various encoding techniques are discussed in more detail in commonly assigned U.S. Pat. No. 5,924,049, which is incorporated herein by reference.

FIG. 4D illustrates a cross sectional view of a seismic streamer configuration in accordance with one embodiment of the invention, which includes seismic streamers **452**, **454**, **456** and air gun array **460**. Seismic streamers **452**, **454**, **456** are disposed in the water at three different depths. Seismic streamer **452** is disposed substantially vertically above seismic streamer **454**, while seismic streamer **454** is disposed substantially vertically above seismic streamer **456**. In this manner, seismic streamers **452**, **454** and **456** have the same x and y coordinates but different z coordinates. This arrangement may be referred to as an over/under combination of the seismic streamers. The term “over” is typically associated with the shallower seismic streamers and the term “under” is typically associated with the deeper seismic streamers. Although only one air gun array is shown to operate in connection with seismic streamers **452**, **454** and **456**, one or more embodiments of the invention contemplate seismic streamers **452**, **454** and **456** to operate with various air gun array configurations, such as those described with reference to FIGS. 4A, 4B and 4C.

FIG. 5 illustrates up-going and down-going wave fields **500**, **505**, **510**, **515**, **520**, **525** corresponding to at least one provided acoustic signal, or shot, in a marine seismic survey. Although the up-going and down-going wave fields are discussed as if they are separate entities, persons of ordinary skill in the art should appreciate that the up-going and down-going wave fields **500**, **505**, **510**, **515**, **520**, **525** may represent portions of a single wave field produced by a single shot or portions of a plurality of wave fields produced by a plurality of shots.

An “over” seismic sensor **540** is deployed at a depth Z_o beneath a surface **530** of a body of water **535** and an “under” seismic sensor **550** is deployed at a depth Z_u beneath the surface **530**. The “over” seismic sensor **540** detects one or more physical quantities indicative of the up-going and down-going wave fields **510**, **515**. In one embodiment, the “over” seismic sensor **540** detects a pressure wave field $P(Z_o)$ at the location of the “over” seismic sensor **540**. The “under” seismic sensor **550** detects one or more physical quantities indicative of the up-going and down-going wave fields **520**, **525**. In one embodiment, the “under” seismic sensor **550** detects a pressure wave field $P(Z_u)$ at the location of the “under” seismic sensor **550**.

The up-going wave field **520** at the “under” seismic sensor **550**, represented by $U(Z_u)$, can be related to the pressure wave fields $P(Z_o)$ at the location of the “over” seismic sensor **540** and $P(Z_u)$ at the location of the “under” seismic sensor **550** by the expression:

$$U(Z_u) = \frac{W_D P(Z_o) - P(Z_o)}{W_D - W_U},$$

where W_D and W_U are wave field extrapolator operators for the down-going and up-going wave fields, respectively. Similarly, the down-going wave field **525** at the “under” seismic sensor **550**, represented by $D(Z_u)$, can be related to the pressure wave fields $P(Z_o)$ and $P(Z_u)$ by the expression:

$$D(Z_u) = \frac{P(Z_o) - W_U P(Z_u)}{W_D - W_U}.$$

In one embodiment, the wave field extrapolator operator W_U is given by the expression:

$$W_U = e^{-j2\pi f \sqrt{1-k^2 v^2 / f^2} (z_o - z_u)}$$

and the wave field extrapolator operator W_D is given by the expression:

$$W_D = e^{-j2\pi f \sqrt{1-k^2 v^2 / f^2} (z_u - z_o)},$$

where v is the water velocity, f is the wave frequency, and k is the wave number. Persons of ordinary skill in the art should appreciate that the expression for the wave field extrapolator operator W_U is only valid for non-evanescent waves, i.e. $1-k^2 v^2 / f^2 > 0$. Persons of ordinary skill in the art should also appreciate that similar expressions may be derived to relate the up-going and down-going wave fields **510**, **515** at the “over” seismic sensor **540** to the pressure wave fields $P(Z_o)$ and $P(Z_u)$.

The up-going wave field **500** just beneath the surface **530** is given by the expression:

$$U(0) = U(Z_u) e^{-j2\pi f \sqrt{1-k^2 v^2 / f^2} (z_u)},$$

and the down-going wave field **505** just beneath the surface **530** is given by the expression:

$$D(0) = D(Z_u) e^{-j2\pi f \sqrt{1-k^2 v^2 / f^2} (z_u)}.$$

The above expressions for the up-going and down-going wave fields **500**, **505** assume that the surface **530** is at $Z=0$.

If the surface **530** is assumed to be perfectly calm, a circumstance that is virtually never achieved in practice, then the up-going and the down-going wave fields **500**, **505** at the surface **530** are equal in absolute value and have opposite signs. In mathematical terms, the surface **530** is considered a free surface at which a pressure wave field vanishes, i.e. $P(Z=0)=0$, so that the up-going and down-going wave fields **500**, **505** are related by a flat sea boundary condition:

$$P(Z=0) = U(0) + D(0) = 0.$$

By imposing the flat sea boundary condition in the form $U(0) = -D(0)$, i.e. a surface reflectivity of -1 , for a data window below a direct arrival, the following expression may be derived:

$$P(Z_o) \left[e^{j2\pi f \sqrt{1-k^2 v^2 / f^2} Z_u} \left(1 - e^{-j2\pi f \sqrt{1-k^2 v^2 / f^2} Z_u} \right) \right] =$$

$$P(Z_u) \left[e^{j2\pi f \sqrt{1-k^2 v^2 / f^2} Z_o} \left(1 - e^{-j2\pi f \sqrt{1-k^2 v^2 / f^2} Z_o} \right) \right].$$

Persons of ordinary skill in the art should appreciate that the expressions in brackets are ghost operators, F_o and F_u , for the over and under seismic data, respectively, in the case of a perfectly calm surface **530**. Accordingly, the above expression states that the pressure at the “over” seismic receiver **540** multiplied by the ghost operator F_u of the “under” seismic receiver **550** is equal to the pressure at the “under” seismic receiver **550** multiplied by the ghost operator F_o of the “over” seismic receiver **540**. In mathematical terms, the above expression may be written in the simplified form: $P(Z_o)F_o = P(Z_u)F_u$.

However, as discussed above, the surface **530** is virtually never flat, as assumed above and in conventional practice. Moreover, the above expressions do not account for temporal and spatial variations in the water velocity, reflectivity of the surface **530**, streamer positioning errors, and other non-ideal conditions that are frequently encountered in real marine seismic surveys. To account, at least in part, for the effects of the aforementioned non-ideal conditions, one or more calibration filters are determined in a manner that will be discussed in detail below. The calibration filters are then used to form an over/under combination of marine seismic data acquired by the “over” seismic receiver **540** and the “under” seismic receiver **550**. For example, the over/under combination may be formed by modifying the surface boundary condition using the one or more calibration filters. The over/under combination formed with the modified boundary condition may result in a combined data set with reduced noise relative to a data set formed by an over/under combination using the flat sea boundary condition.

FIG. **6** illustrates a flow diagram of a method **600** for forming an over/under combination using one or more calibration filters in accordance with one or more embodiments of the invention. First and second data sets are selected (at **610**). In one embodiment, the first and second data sets are selected (at **610**) to be pre-stack over and under data sets acquired by at least one seismic sensor coupled to an “over” streamer and at least one seismic sensor coupled to an “under” streamer in an over/under streamer combination. However, the present invention is not limited to selecting (at **610**) all of the data in the pre-stack data set. In one alternative embodiment, portions of the pre-stacked data set acquired within a selected time window and/or a selected offset may be selected (at **610**). In another alternative embodiment, portions of the pre-stacked data set from a selected gather, such as a shot gather and/or a receiver gather, may be selected (at **610**).

The first and/or second data sets may be provided via transmission over a wired and/or wireless medium. For instance, the over and under data sets may be selected from the data as it is gathered, or shortly after it is collected, from a seismic survey. Alternatively, the first and/or second data sets may be recorded on and transmitted via recording tape, magnetic disks, compact disks, DVDs, and the like. Thus, the first and second data sets can, in some embodiments, be selected from data previously collected and archived on some magnetic or optical storage medium.

One or more calibration filters are determined (at **620**) using the selected over and under data sets. In one embodiment, the one or more calibration filters are determined (at **620**) by initially assuming, as discussed above, the pressure at

the “over” seismic receiver **440** multiplied by the ghost operator F_u of the “under” seismic receiver **450** is equal to the pressure at the “under” seismic receiver **450** multiplied by the ghost operator F_o of the “over” seismic receiver **440**, i.e. $P(Z_o)F_o = P(Z_u)F_u$. This technique is often referred to as across-ghosting technique.

However, as discussed above, this relationship generally is not precise for the acquired over/under seismic data. The one or more calibration filters, $a(f)$, may therefore be determined using the expression $a(f)P(Z_o)F_o = P(Z_u)F_u$. For example, the one or more calibration filters may be determined by evaluating the expression $a(f)P(Z_o)F_o = P(Z_u)F_u$ by a least-squares criterion. However, persons of ordinary skill in the art should appreciate that the present invention is not limited to applying the least-squares criterion to the expression $a(f)P(Z_o)F_o = P(Z_u)F_u$. Further, any desirable expression may be evaluated with any desirable technique used to determine the calibration filters. Persons of ordinary skill in the art should also appreciate that the one or more calibration filters may be determined such that the expression $a(f)P(Z_o)F_o = P(Z_u)F_u$ holds true in a statistical sense, even though it may not hold precisely for all the acquired seismic data used to determine the calibration filters.

The one or more calibration filters are then used to combine (at **630**) the first and second data sets to form a third data set, such as an over/under combined data set. The one or more calibration filters may be used to define a perturbed boundary condition using over and under data sets. The perturbed boundary condition is then incorporated into a selected over/under combination technique that is used to combine (at **630**) the over and under seismic data. Persons of ordinary skill in the art should appreciate that the present invention is not limited to any particular technique for combining (at **630**) the over and under seismic data using the one or more calibration filters. In various alternative embodiments, any desirable technique for combining (at **630**) the over and under seismic data using the one or more calibration filters may be used.

While the foregoing is directed to embodiments of the present invention, other and further embodiments of the invention may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

The invention claimed is:

1. A method for acquiring seismic data, comprising:
 - moving a first air gun array in the water at a first depth and a second air gun array in the water at a second depth greater than the first depth, wherein the total volume of the first air gun array is less than the total volume of the second air gun array, wherein the first air gun array is separated from the second air gun array by a distance substantially equal to a shot point interval;
 - firing seismic energy by the first and second air gun arrays through the water into the earth; and
 - recording a plurality of seismic signals reflected from strata in the earth beneath the water.

2. The method of claim **1**, wherein the first air gun array is tuned to a leading peak and the second air gun array is tuned to a first bubble oscillation.

3. The method of claim **1**, wherein the first air gun array is separated from the second air gun array by about 37.5 meters.

4. The method of claim **1**, wherein moving the first and second air gun arrays comprises moving the first and second air gun arrays at a speed V in an x direction, wherein the first air gun array is separated from the second air gun array by a distance dx in the x direction.

5. The method of claim **4**, wherein firing seismic energy through the first and second air gun arrays comprises:

13

firing seismic energy through the first air gun array; and firing seismic energy through the second air gun array at a time dx/V after the first air gun array is fired.

6. The method of claim 4, wherein the first air gun array is disposed closer to a seismic survey vessel than the second air gun array, wherein the first and second air gun arrays are moved by the seismic survey vessel.

7. The method of claim 1, wherein firing seismic energy through the first and second air gun arrays comprises firing the first and second air gun arrays sequentially.

8. The method of claim 1, wherein firing seismic energy through the first and second air gun arrays comprises firing the first and second air gun arrays simultaneously.

9. The method of claim 1, wherein the first air gun array is configured to enhance high frequency seismic energy.

10. The method of claim 1, wherein the second air gun array is configured to enhance low frequency seismic energy.

14

11. A marine surveying arrangement, comprising:
a first air gun array tuned to a first bubble oscillation, wherein the first air gun array has a first total volume;
a second air gun array tuned to a leading peak, wherein the second air gun array has a second total volume that is greater than the first total volume, wherein the second air gun array is horizontally separated from the first air gun array by a distance substantially equal to the speed at which the air gun arrays are moving multiplied by a delay time between the firing of the first air gun array and the firing of the second air gun array; and
one or more seismic streamers having a plurality of hydrophones disposed therealong.

12. The marine surveying arrangement of claim 11, wherein the first total volume is about 5085 cubic inches and the second total volume is about 6780 cubic inches.

13. The marine surveying arrangement of claim 11, wherein the distance is about 37.5 meters.

* * * * *