



US00RE45791E

(19) **United States**
(12) **Reissued Patent**
James et al.

(10) **Patent Number:** **US RE45,791 E**
(45) **Date of Reissued Patent:** ***Nov. 3, 2015**

(54) **MULTI-NEEDLE CHAIN STITCH QUILTING APPARATUS AND METHOD**

(58) **Field of Classification Search**
USPC 112/117, 163-167, 197, 199, 200,
112/285-298, 475.01-475.08;
700/136-138
See application file for complete search history.

(71) Applicant: **L&P Property Management Company, South Gate, CA (US)**

(72) Inventors: **Michael A. James, Davie, FL (US); Jeff Kaetterhenry, Algonquin, IL (US); James T. Frazer, North Olmstead, OH (US); Terrance L. Myers, Joplin, MO (US)**

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,649,065 A	8/1953	Casper	112/84
3,183,866 A	5/1965	Walbert et al.	
3,749,041 A	7/1973	Bowin	
3,935,827 A	2/1976	Winter	
4,006,696 A	2/1977	Robertson	
4,154,130 A	5/1979	Smith et al.	
4,352,333 A	10/1982	Yamazawa	

(Continued)

OTHER PUBLICATIONS

Search Report and Written Opinion from corresponding PCT/US06/35233, dated Jul. 25, 2008 (pages).

(Continued)

(73) Assignee: **L&P Property Management Company, South Gate, CA (US)**

(*) Notice: This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/830,220**

(22) Filed: **Mar. 14, 2013**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,061,288**
Issued: **Nov. 22, 2011**
Appl. No.: **12/371,738**
Filed: **Feb. 16, 2009**

Primary Examiner — Ismael Izaguirre

(74) *Attorney, Agent, or Firm* — Wood, Herron & Evans, LLP

U.S. Applications:

(63) Continuation of application No. 13/475,412, filed on May 18, 2012, now Pat. No. Re. 44,885, which is an application for the reissue of Pat. No. 8,061,288, which is a

(Continued)


(57) **ABSTRACT**

A multi-needle chain-stitch quilting machine and method of operation thereof are provided that imparts relative motion between the needles and the material that is controlled so as to pull needle thread tails from the needle side of the quilted material. The feature of controlling thread tails may be optional to provide selection of either a high speed mode of operation without thread tail control or a quality mode of operation with reduction or removal of needle thread tails from the face of the quilted material. Thread trimmers may be included at each needle location on the looper side of the material to cut both needle and looper threads.

(51) **Int. Cl.**
D05B 11/00 (2006.01)
D05B 19/14 (2006.01)
D05B 69/30 (2006.01)

(52) **U.S. Cl.**
CPC **D05B 19/14** (2013.01)

38 Claims, 57 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/744,561, filed on May 4, 2007, now Pat. No. 7,770,530, which is a continuation-in-part of application No. 11/744,389, filed on May 4, 2007, now Pat. No. 7,789,028, which is a continuation of application No. PCT/US2006/035233, filed on Sep. 8, 2006, and a continuation-in-part of application No. 11/040,499, filed on Jan. 21, 2005, now Pat. No. 7,143,705, which is a continuation-in-part of application No. 10/804,833, filed on Mar. 19, 2004, now Pat. No. 7,073,453, which is a continuation-in-part of application No. PCT/US03/07083, filed on Mar. 6, 2003.

- (60) Provisional application No. 60/763,172, filed on Jan. 27, 2006, provisional application No. 60/762,471, filed on Jan. 26, 2006, provisional application No. 60/715,423, filed on Sep. 9, 2005, provisional application No. 60/362,179, filed on Mar. 6, 2002, provisional application No. 60/446,417, filed on Feb. 11, 2003, provisional application No. 60/446,430, filed on Feb. 11, 2003, provisional application No. 60/446,419, filed on Feb. 11, 2003, provisional application No. 60/447,773, filed on Feb. 14, 2003, provisional application No. 60/446,426, filed on Feb. 11, 2003, provisional application No. 60/446,529, filed on Feb. 11, 2003.

(56) **References Cited**

U.S. PATENT DOCUMENTS


4,474,124	A	10/1984	Yamazawa	
4,501,208	A	2/1985	Landoni	112/118
4,569,297	A	2/1986	Dusch	
4,658,752	A	4/1987	Keilmann et al.	
4,669,403	A	6/1987	Bagnall	
4,776,291	A	10/1988	Tajima et al.	
4,838,187	A	6/1989	Tatum	

5,005,499	A	4/1991	Landoni	
5,103,747	A	4/1992	Resta et al.	
5,154,130	A	10/1992	Gribetz et al.	
5,269,238	A	12/1993	Landoni	
5,287,820	A	2/1994	Stutzacker	
5,289,791	A *	3/1994	Sanders et al.	112/475.01
5,509,365	A	4/1996	Cash	
5,603,270	A	2/1997	White et al.	
5,676,077	A	10/1997	Landoni	
5,782,193	A	7/1998	Schwarzberger et al.	112/470.13
5,784,990	A	7/1998	Shimizu et al.	
5,832,849	A	11/1998	Kaetterhenry et al.	
5,839,382	A	11/1998	Tice et al.	
5,873,315	A	2/1999	Codos	
5,913,276	A	6/1999	Kurono et al.	
5,927,221	A *	7/1999	Porter et al.	112/470.07
5,931,106	A	8/1999	Papajewski et al.	
5,967,068	A *	10/1999	Landoni	112/117
6,026,756	A	2/2000	Frazer et al.	
6,065,412	A	5/2000	Schwarzberger et al.	
6,178,903	B1	1/2001	Bondanza et al.	
6,223,666	B1	5/2001	Resta	112/117
6,237,517	B1	5/2001	Bondanza et al.	
6,273,013	B1 *	8/2001	Carey, Jr.	112/117
6,805,063	B2	10/2004	Enns et al.	
6,895,878	B2	5/2005	Stutzacker	112/117
7,073,453	B2	7/2006	Frazer et al.	112/117
7,143,705	B2	12/2006	Frazer et al.	112/117
7,770,530	B2 *	8/2010	James et al.	112/475.08
7,789,028	B2 *	9/2010	James et al.	112/117
8,061,288	B2 *	11/2011	James et al.	112/475.08
2004/0237864	A1	12/2004	Frazer et al.	
2005/0178307	A1	8/2005	Frazer et al.	
2007/0261620	A1 *	11/2007	James et al.	112/117
2011/0020356	A1	1/2011	Fang et al.	
2011/0203506	A1 *	8/2011	Price et al.	112/475.08

OTHER PUBLICATIONS

U.S. Patent and Trademark Office, Search Report and Written Opinion, from corresponding PCT/US06/35233, dated Jul. 25, 2008.

* cited by examiner






FIG. 1A




FIG. 1B




FIG. 2A





FIG. 2C






FIG. 4




FIG. 4C




FIG. 4F




FIG. 4G





FIG. 5Y






FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 5G




FIG. 5H




FIG. 5I




FIG. 5J




FIG. 5K




FIG. 5L




FIG. 5M






FIG. 5N






FIG. 5Q










FIG. 5R










FIG. 6




FIG. 6A




FIG. 6B





FIG. 6C






FIG. 6E




FIG. 6F





FIG. 6H






FIG. 6J




FIG. 6K




FIG. 6L




FIG. 6M




FIG. 7A




FIG. 7C





FIG. 7B




FIG. 7D




FIG. 7E




FIG. 7F




FIG. 7G




FIG. 7H




FIG. 7I




FIG. 7J




FIG. 7K




FIG. 7L




FIG. 7M




FIG. 7N




FIG. 7O




FIG. 7P




FIG. 8




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 8G




FIG. 8H




FIG. 8I




FIG. 8J




FIG. 8K




FIG. 8L




FIG. 9





FIG. 9B



PRIOR ART
FIG. 9A




FIG. 9C




FIG. 9D




FIG. 9E




FIG. 9F




FIG. 9G




FIG. 9H




FIG. 9I




FIG. 9J




FIG. 9K




FIG. 9L




FIG. 9M




FIG. 9N

MULTI-NEEDLE CHAIN STITCH QUILTING APPARATUS AND METHOD

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

This is a Continuation Reissue of application Ser. No. 13/475,412, filed May 18, 2012, now U.S. Pat. No. Re. 44,885, which is an application for a reissue of U.S. Pat. No. 8,061,288 (Ser. No. 12/371,738, filed Feb. 6, 2009), which is a Continuation of U.S. patent application Ser. No. 11/744,561 filed May 4, 2007 now U.S. Pat. No. 7,770,530; which is a Continuation-in-Part of U.S. patent application Ser. No. 11/744,389 filed May 4, 2007 now U.S. Pat. No. 7,789,028; which is a Continuation of PCT application US2006/035233 filed Sep. 8, 2006; which claims the benefit of U.S. Provisional Application Ser. Nos. 60/715,423 filed Sep. 9, 2005; 60/762,471 filed Jan. 26, 2006; and 60/763,172 filed Jan. 27, 2006; all hereby expressly incorporated herein by reference and to all of which priority is claimed. PCT application US2006/035233 is also a Continuation-in-Part of U.S. patent application Ser. No. 11/040,499 filed Jan. 21, 2005, now U.S. Pat. No. 7,143,705; which is a Continuation-In-Part of U.S. patent application Ser. No. 10/804,833 filed Mar. 19, 2004, now U.S. Pat. No. 7,073,453; which is a Continuation-In-Part of PCT Application No. PCT/US03/07083 filed Mar. 6, 2003; which claims the benefit of U.S. Provisional Patent Applications: Ser. No. 60/362,179 filed Mar. 6, 2002; Ser. No. 60/446,417 filed Feb. 11, 2003; Ser. No. 60/446,430 filed Feb. 11, 2003; Ser. No. 60/446,419 filed Feb. 11, 2003; Ser. No. 60/446,426 filed Feb. 11, 2003; Ser. No. 60/446,529 filed Feb. 11, 2003; and Ser. No. 60/447,773 filed Feb. 14, 2003; all of which applications are hereby expressly incorporated herein by reference and to all of which priority is claimed.

This application is also related to PCT Application PCT/US2005/008312 filed Mar. 11, 2005; which claims the benefit of U.S. application Ser. Nos. 10/804,833 and 11/040,499 and is hereby also expressly incorporated by reference herein. PCT Application No. PCT/US03/07083 also claims the benefit of U.S. Provisional Patent Application Ser. No. 60/362,179 filed Mar. 6, 2002, which is also hereby expressly incorporated by reference herein.

FIELD OF THE INVENTION

This invention relates to quilting, and particularly relates to quilting with high-speed multi-needle quilting machines on wide webs of multi-layered material. More particularly, the invention relates to multi-needle quilting of products such as mattress covers and other quilted products on wide webs of multi-layered material.

BACKGROUND OF THE INVENTION

Quilting is a sewing process by which layers of textile material and other fabric are joined to produce compressible panels that are both decorative and functional. Stitch patterns are used to decorate the panels with sewn designs while the stitches themselves join the various layers of material that make up the quilts. The manufacture of mattress covers involves the application of large scale quilting processes. The

large scale quilting processes usually use high-speed multi-needle quilting machines to form series of mattress cover panels along webs of the multiple-layered materials. These large scale quilting processes typically use chain-stitch sewing heads which produce resilient stitch chains that can be supplied by large spools of thread. Some such machines can be run at up to 1500 or more stitches per minute and drive one or more rows of needles each to simultaneously stitch patterns across webs that are ninety inches or more in width. Higher speeds, greater pattern flexibility and increased operating efficiency are constant goals for the quilting processes used in the bedding industry. Traditional multi-needle quilting machines, while fast and efficient, have been less useful in producing high-end-market mattress cover products and comforters, which are often made on the slower but more flexible single or dual needle quilting machines.

Conventional multi-needle quilting machines have three axes of motion. An X-axis can be considered as the longitudinal direction of motion of a web of the material as it moves through the quilting station. Frequently, such bi-directional motion is provided in which the web of material can move in either a forward or a reverse direction to facilitate sewing in any direction, such as is needed for the quilting of 360 degrees patterns on the material. Material accumulators usually accompany such bi-directional machines so that sections of a web can be reversed without changing the direction of the entire length of web material along the quilting line. A Y-axis of motion is also provided by moving the web from side to side, also for funning quilted patterns. Usually the quilting mechanism remains stationary in the quilting process and the motion of the material is controlled to affect the quilting of various patterns.

The X-axis and the Y-axis are parallel to the plane of the material being quilted, which traditionally is a horizontal plane. A third axis, a Z-axis, is perpendicular to the plane of the material and defines the nominal direction of motion of reciprocating needles that form the quilting stitches. The needles, typically on an upper sewing head above the plane of the material, cooperate with loopers on the opposite or lower side of the material, which reciprocate perpendicular to the Z-axis, typically in the X-axis direction. The upper portion of the sewing mechanism that includes the needle drive is, in a conventional multi-needle quilting machine, carried by a large stationary bridge. The lower portion of the sewing mechanism that includes the looper drives is attached to a cast iron table. There may be, for example, three rows of sewing elements attached to each respective upper and lower structure. All of the needles are commonly linked to and driven by a single main shaft.

Conventional multi-needle quilting machines use a single large presser foot plate that compresses the entire web section of material in the sewing area across the width of the web. On a typical machine that is used in the mattress industry, this presser foot plate might, during each stitch, compress an area of material that is over 800 square inches in size to a thickness of as little as 1/4 inch. When the needles are withdrawn from the material following each stitch formation, the presser foot plate must still compress the material to about 7/16 inch. Since the material must, while still under the presser foot plate, move relative to the stitching elements to form the pattern, patterns are typically distorted by the drag forces exerted on it parallel to the plane of the material. These conventional machines are large and heavy, and occupy a substantial area on the floor of a bedding manufacturing plant.

Further, multi-needle quilting machines lack flexibility. Most provide a line or an array of fixed needles that operate simultaneously to sew the same pattern and identical series of

stitches. Changing the pattern requires the physical setting, rearrangement or removal of needles and the threading of the altered arrangement of needles. Such reconfiguration takes operator time and substantial machine down-time.

Traditional chain stitch machines used for quilting reciprocate one or more needles through thick multi-layered material using a crank mechanism driven by a rotary shaft. The force of a drive motor, as well as inertia of the linkage, forces the needle through the material. The needle motion so produced is traditionally sinusoidal, that is, it is defined by a curve represented by the equation $y = \text{sine } x$. For purposes of this application, motion that does not satisfy that equation will be characterized as non-sinusoidal. Thus, the needle motion carries a needle tip from a raised position of, for example, one inch above the material, downward through material compressed to approximately $\frac{1}{4}$ inch, to a point about $\frac{1}{2}$ inch below the material where its motion reverses. The needle carries a needle thread through the material and presents a loop on the looper side of the material to be picked up by a looper thread. On the looper side of a material, a looper or hook is reciprocated about a shaft in a sinusoidal rotary motion. The looper is positioned relative to the needle such that its tip enters the needle thread loop presented by the needle to extend a loop of looper thread through the needle thread loop on the looper side of the material. The motion of the looper is synchronized with motion of the needle so that the needle thread loop is picked up by the looper thread when the needle is at the downward extent of its cycle. The needle then rises and withdraws from the material and leaves the needle thread extending around the looper and looper thread loop.

When the needle is withdrawn from the material, the material is shifted relative to the stitching elements and the needle again descends through the material at a distance equal to one stitch length from the previous point of needle penetration, forming one stitch. When again through the material, the needle inserts the next loop of needle thread through a loop formed in the looper thread that was previously poked by the looper through the previous needle thread loop. At this point in the cycle, the looper itself has already withdraw from the needle thread loop, in its sinusoidal reciprocating motion, leaving the looper thread loop extending around a stitch assisting element, known as a retainer in many machines, which holds the looper thread loop open for the next descent of a needle. In this process, needle thread loops are formed and passed through looper thread loops as looper thread loops are alternatively formed and passed through needle thread loops, thereby producing a chain of loops of alternating needle and looper thread along the looper side of the material, leaving a series of stitches formed only of the needle thread visible on the needle side of the material.

The traditional sinusoidal motion of the needle and looper in a chain stitch forming machine have, through years of experience, been adjusted to maintain reliable loop-taking by the thread so that stitches are not missed in the sewing process. In high speed quilting machines, the motion of the needle is such that the needle tip is present below the plane of the material, or a needle plate that supports the material, for approximately $\frac{1}{3}$ of the cycle of the needle, or 120 degrees of the needle cycle.

During the portion of the needle cycle when the needle extends through the material, no motion of the material relative to the needle is preferred. Inertia of machine components and material causes some of the between-stitch motion of material relative to the needle to occur with the needle through the material. This results in needle deflection, which can cause missed stitches as the looper misses a needle thread

loop or the needle misses a looper thread loop, or causes loss of pattern definition as material stretches and distorts. Further, limiting the time of needle penetration of the fabric defines the speed of the needle through the fabric, which determines the ability of the needle to penetrate thick multi-layered material. Increase of the needle speed then requires increasing the distance of needle travel, which causes excess needle thread slack below the fabric that must be pulled up to tighten the stitches during the formation of the stitches. Accordingly, the traditional needle motion has imposed limitations on chain stitch sewing and particularly on high speed quilting.

Further, looper heads on known multi-needle quilting machines provide the looper motion by moving cam followers over a cam surface, which requires lubrication and creates a wear component requiring maintenance.

Additionally, chain stitch forming elements used on multi-needle quilting machines typically each include a needle that reciprocates through the material from the facing side thereof and a looper or hook that oscillates in a path on the back side of the material through top-thread loops formed on the back side of the material by the penetrating needle. Chain stitching involves the forming of a cascading series or chain of alternating interlocking between a top thread and a bottom thread on the back side of the material by the interaction of the needle and looper on the backside of the material, which simultaneously forms a clean series of top-thread stitches on the top side of the material. The reliable forming of the series of stitches requires that the paths of the needle and looper of each stitching element set be accurately established, so that neither the needle nor the looper misses the take-up of the loop of the opposing thread. The missing of such a loop produces a missed stitch, which is a defect in the stitching pattern.

Initially, and periodically in the course of the use of a quilting machine, the relative positions of the needle and the looper must be adjusted. Typically, this involves the adjusting of the transverse adjustment of the position of the looper on its axis of oscillation. In multi-needle quilting machines, such an adjustment is made to bring the path of the looper in close proximity to the side of the needle just above the eye in the needle through which is passed the top thread. At this position, a loop of the needle thread is formed beside the needle through which the looper tip inserts a loop of the bottom thread. The formations of these loops and the interlocking chain of stitches is described in detail in U.S. Pat. No. 5,154,130, hereby expressly incorporated herein by reference.

Looper adjustment has been typically a manual process. The adjustment is made with the machine shut down by a technician using some sort of a hand tool to loosen, reposition, check and tighten the looper so that it passes close to or lightly against the needle when the needle is near the bottom-most point in the needle's path of travel on the bottom side of the material being quilted. The adjustment takes a certain amount of operator time. In a multi-needle quilting machine, the number of needles may be many, and the adjustment time may be large. It is not uncommon that the quilting line would be shut down for the major portion of an hour or more just for needle adjustment.

Furthermore, since the looper adjustment has been a manual process, difficulties of access to the adjusting elements, difficulties in determining the relative looper and needle positions, and difficulties in holding the adjusting elements in position while securing or locking the locking components of the assemblies has served as a source of adjustment error.

Chain stitch forming elements used on multi-needle quilting machines typically each include a needle that reciprocates through the material from the facing side thereof and a looper or hook that oscillates in a path on the back side of the material through top-thread loops formed on the back side of the material by the penetrating needle. Chain stitching involves the forming of a cascading series or chain of alternating interlocking between a top thread and a bottom thread on the back side of the material by the interaction of the needle and looper on the backside of the material, which simultaneously forms a clean series of top-thread stitches on the top side of the material. The top thread or needle thread penetrates the fabric from the top side or facing side of the fabric and forms loops on the bottom side or back side of the fabric. The bottom thread remains exclusively on the back side of the fabric where it forms a chain of alternating interlocking loops with the loops of the top thread.

High speed multi-needle quilting machines, such as those that are used in the manufacture of mattress covers, often sew patterns in disconnected series of pattern components. In such sewing, tack stitches are made and, at the end of the quilting of a pattern component, at least the top thread is cut. Then the fabric advances relative to the needles to the beginning of a new pattern component, where more tack stitches are made and sewing recommences. One such high speed multi-needle quilting machine is described in U.S. Pat. No. 5,154,130, referred to above. This patent particularly describes in detail one method of cutting thread in such multi-needle quilting machines. Accordingly, there is a need for more reliable and more efficient thread management in multi-needle quilting machines.

These characteristics and requirements of high-speed multi-needle quilting machines, and the deficiencies discussed above, impede the achievement of higher speeds and greater pattern flexibility in conventional quilting machines. Accordingly, there is a need to overcome these obstacles and to increase the operating efficiency of quilting processes, particularly for the high volume quilting used in the bedding industry.

Further, there is a constant need for easy ways to change materials supplied, usually in web form, to multi-needle quilting machines. With web supplies, this need includes the need for ways to splice the length of material to be fed from a new supply to the trailing edge of the web of material that has been fed to the machine. In many quilting machines, particularly in the machines set forth in the applications identified above where the web moves vertically upwardly through the quilting station, the material supply enters the machine from near the floor. This is particularly helpful in minimizing the resistance on the web that could cause distortion of the material when stretchable material is being quilted. Sometimes such stretchable materials are used as ticking in mattress covers, for example. When entering the machine from a position near the floor, it is often difficult to change materials and to splice a new supply of material to the web entering the machine. Accordingly, improvement in such material supplies is needed.

SUMMARY OF THE INVENTION

A primary objective of the present invention is to improve the efficiency and economy of quilt making, particularly in high-speed, large-scale quilting applications such as are found in the bedding industry. Particular objectives of the invention include increasing quilting speeds, reducing the size and cost of quilting equipment, and increasing the flexibility in quilt patterns produced over those of the prior art.

A further objective of the present invention is to provide flexibility in the arrangement of needles in a multi-needle quilting machine. An additional objective of the invention is to reduce machine down-time and operator time needed to change needle settings in multi-needle quilting machine operation.

A particular objective of the invention is to provide a quilting head that is adaptable to various configurations of a multi-needle quilting machine, and that can be used in a number of machines of various sizes, types and orientations, for example, in single or multi-needle machines, in machines having one or more rows of needles, machines having needles variously spaced, and machines having needles oriented vertically, horizontally or otherwise. Another particular objective of the invention is to provide sewing heads that can be operated differently in the same machine, such as to sew in different directions, to sew different patterns or to sew at different rates.

Another objective of the present invention is to improve reliability of sewing element adjustment in quilting machines. A more particular objective of the invention is to provide for looper adjustment that can be carried out quickly and positively by a quilting machine operator. A further objective of the invention is to provide a reliable indication of when the looper of a chain stitch sewing head of a quilting machine is in or out of proper adjustment.

A further objective of the present invention is to provide for the cutting of thread in a multi-needle quilting machine. A more particular objective of the invention is to provide for thread cutting in a multi-needle quilting machine that has separately operable or separately movable, replaceable or reconfigurable heads. Another objective of the invention is to provide for more reliable monitoring and/or control of thread tension in a quilting machine, particularly a multi-needle quilting machine. A more particular objective of the invention is the automatic maintenance and adjustment of thread tension in such quilting machines.

According to principles of the present invention, a multi-needle quilting machine is provided in which the needles reciprocate in other than a vertical direction as used by multi-needle quilting machines of the prior art. The quilting machine of the present invention provides several axes of motion that differ from those of conventional multi-needle quilting machines. In the illustrated embodiments of the invention, the substrate is supported in a vertical plane while the needles reciprocate in a horizontal direction. While support of the substrate in a vertical plane with needles oriented horizontally is preferred and has important advantages, other non-horizontal substrate orientations (i.e., having a significant vertical component to the plane orientation and referred to herein as generally vertical) and non-vertical needle orientations (i.e., having a significant horizontal component to the needle orientation and referred to herein as generally horizontal) are compatible with many of the features of the invention, while some features of the invention can provide advantages with any substrate or needle orientation.

One preferred embodiment of a quilting machine, according to certain principles of the present invention, provides two or more bridges that are capable of separate or independent control. Each bridge may be provided with a row of sewing needles. The needles may be driven together, each separately or independently, or in various combinations.

In accordance with the illustrated embodiment of the invention, seven axes of motion are provided. These include an X0-axis that is unidirectional, which provides for feed of the material in only one downstream direction. In another embodiment, bidirectional X-axis motion is provided. This

X-axis motion is brought about by the rotation of feed rolls that advance the material in web form through a quilting station.

Further in accordance with the illustrated embodiment, independently movable bridges that carry the needle and looper stitching mechanisms are provided with two axes of motion, X1,Y1 and X2,Y2, respectively. The Y-axis motion moves the respective bridge side-to-side, parallel to the web and transverse to its extent and direction of motion, while the X-axis motion moves the bridge up and down parallel to the web and parallel to its direction of motion. In the alternative embodiment, where bi-directional motion of the web is provided, the X-axis motion of the bridge is not necessarily provided. The X,Y motions of the bridges are brought about by separately controlled X and Y drives for each of the bridges. Preferably, the Y-axis motion of the bridges has a range of about 18 inches, 9 inches in each direction on each side of a center position, and the X-axis motion of the bridges has a range of 36 inches relative to the motion of the web, whether the web or the bridges move in the X direction.

According to certain principles of the present invention, a quilting machine is provided with one or more quilting heads that can operate with a needle in a horizontal or vertical orientation. According to other aspects of the invention, a self-contained sewing head is provided that can be operated alone or in combination with one or more other such sewing heads, either in synchronism in the same motion or independently to sew the same or a different pattern, in the same or in a different direction, or at the same or at a different speed or stitch rate.

One preferred embodiment of a quilting machine according to certain principles of the present invention, provides sewing heads that can be ganged together on a stationary platform or a movable bridge, and can be so arranged with one or more other sewing heads that are ganged together in a separate and independent group on another platform or bridge, to operate in combination with other heads or independently and separately controlled.

In the illustrated embodiment of the invention, the bridges are separately and independently supported and moved, and several separately and independently operable sewing heads are supported on each bridge. The bridges each are capable of being controlled and moved, separately and independently, both transversely and longitudinally relative to the plane of the material being quilted. The bridges are mounted on common leg supports that are spaced around the path of the material to be quilted, which extends vertically, with the bridges guided by a common linear-bearing slide system incorporated into each leg support. Each leg also carries a plurality of counterweights, one for each bridge. Each bridge is independently driven vertically and horizontally-transversely by different independently controllable servo motors. Motors for each bridge produce the bridge vertical and horizontal movements.

Further, according to certain aspects of the present invention, each bridge has an independently controllable drive for reciprocating the sewing elements, the needles and loopers. The drive is most practically a rotary input, as from a rotary shaft, that operates the reciprocating linkages of the elements. The independent operation of the drives on each of the bridges allows for independent sewing operation of the sewing heads or groups of sewing heads, or the idling of one or more heads while one or more others are sewing. The heads each have elements that respond to controls from a controller, preferably in response to digital signals delivered to all the heads on a common bus, with each controllable element pro-

vided with a decoding circuit that selects the signals from the bus that are intended for the respective element.

In an illustrated embodiment of the invention, each sewing head, including each needle head and each looper head, is linked to a common rotary drive through an independently controllable clutch that can be operated by a machine controller to turn the heads on or off, thereby providing pattern flexibility. Further, the heads may be configured in sewing element pairs, each needle head with a corresponding similarly modular looper head. While the heads of each pair can be individually turned on or off, they are typically turned on and off together, either simultaneously or at different phases in their cycles, as may be most desirable. Alternatively, only the needle heads may be provided with selective drive linkages, while the looper heads may be linked to the output of a needle drive motor so as to run continuously. This linkage may be direct and permanent, or may be adjustable, switchable or capable of being phased in relation to the needle drive, such as by providing a differential drive mechanism in the looper drive train. When direct drive is employed, the looper head drive is linked to an input drive shaft through a gear box, rather than a clutch. Each of the looper heads is further provided with an alignment disk on the looper drive shaft to allow precise phase setting of each looper head relative to the other looper heads or the needle drive when the looper head is installed in the machine. Further, each looper head housing is provided with adjustments in two dimensions in a plane perpendicular to the needle to facilitate alignment of the looper head with a corresponding needle head upon looper head installation.

Further in accordance with other principles of the invention, a plurality of presser feet are provided, each for one needle on each needle head. This allows for a reduction in the total amount of material that needs to be compressed, reducing the power and the forces needed to operate the quilter. Each of the needles, as well as the corresponding loopers, may be separately movable and controllable, or moved and controlled in combinations of fewer than all of those on a bridge, and can be selectively enabled and disabled. Enabling and disabling of the needles and loopers is provided and preferably achieved by computer controlled actuators, such as electric, pneumatic, magnetic or other types of actuators or motors or shiftable linkages.

The need for less overall pressure and force by the sewing elements and by the presser foot plates allows for lighter weight construction of the quilting machine and for a smaller machine having a smaller footprint in the bedding plant. Further, the use of individual presser feet avoids much of the pattern distortion caused by the presser arrangements of the past. These advantages are further enhanced by wider spacing between the needle plate on the looper side of the fabric and the raised presser feet on the needle side of the fabric. This spacing can be up to several inches.

According to further principles of the present invention, the needle in a chain stitch forming machine may be driven in motion that differs from a traditional sinusoidal motion. In an illustrated embodiment of the invention, a needle of a chain stitch forming head, or each needle of a plurality of chain stitch forming heads, is driven so as to remain in a raised position for a greater portion of its cycle and to penetrate the material during a smaller portion of its cycle than would be the case with a traditional sinusoidal needle motion. Also in accordance with this illustrated embodiment of the invention, the needle is driven so that it moves downwardly through the material at a faster speed than it moves as it withdraws from the material. In alternative embodiments of the invention, a sinusoidal motion is provided.

In one embodiment of asymmetric, non-sinusoidal needle motion, the needle descends through the material to a depth approximately the same as that presented by sinusoidal motion, but moves faster and thus arrives at its lowest point of travel in a smaller portion of its cycle than with traditional sinusoidal motion. Nonetheless, the needle rises from its lowest point of travel more slowly than it descends, being present below the material for at least as long or longer than with the traditional sinusoidal motion, to allow sufficient time for pickup of the needle thread loop by the looper. As a result, more material penetrating force is developed by the needle than with the prior art and less needle deflection and material distortion is produced than with the prior art, due primarily to the extension of the needle through the material for less time.

One embodiment of a quilting machine according to certain principles of the present invention, provides a mechanical linkage in which an articulated lever or drive causes the needle motion to depart from a sinusoidal curve. A cam and cam follower arrangement may also provide a curve that departs from a sinusoidal curve. Similar linkage may also drive a presser foot.

Mechanical and electrical embodiments of the invention can be adapted to produce needle motion according to the present invention. In one embodiment of the invention, the stitching elements, particularly the needle, of each needle pair is driven by a servo motor, preferably a linear servo motor, with the motion of the needle controlled to precisely follow a preferred curve. In one preferred embodiment of a non-sinusoidal motion, the curve carries the needle tip slightly upward beyond the traditional 0 degree top position in its cycle and maintains it above the traditional curve, descending more rapidly than is traditionally the case until the bottommost position of the needle tip, or the 180 degree position of the needle drive, is reached. Then the needle rises to its 0 degree position either along or slightly below the traditional position of the needle.

A quilting machine having a servo-controlled quilting head suitable for implementing this motion is described in U.S. patent application Ser. No. 09/686,041, hereby expressly incorporated by reference herein. With such an apparatus, the quilting head servo is controlled by a programmed controller to execute a sewing motion. With the present invention, the controller is programmed to operate the sewing head to drive the needle in a motion as described herein. In an alternative embodiment, the needle head of a quilting machine is provided with mechanical linkage that is configured to impart non-sinusoidal motion to the needle as described above. A mechanism for imparting this motion may be formed with asymmetrically weighted linkages and components that have a mass distribution that will offset the asymmetrical forces generated by the asymmetrical motion, minimizing the inducement of vibration from irregular acceleration resulting from the non-harmonic, non-sinusoidal motion that differs from the traditional harmonic sine function. In some embodiments, the sewing heads themselves are provided with housing structures which, when the heads are mounted on the bridges, serve to reinforce, strengthen and stiffen the bridges, to minimize vibration.

In addition, in accordance with the principles of the present invention, the looper heads convert an input rotary motion into two independent motions without requiring cam followers sliding over cams. Therefore, the looper heads are high speed, balanced mechanisms that have a minimum number of parts and do not require lubrication, thereby minimizing maintenance requirements. Similarly, the needle heads are constructed so as to require no lubrication.

According to other principles of the present invention, a looper adjustment feature is provided for adjusting the looper-needle relationship in a chain-stitch quilting machine, and particularly for use on a multi-needle quilting machine.

The adjustment feature includes a readily accessible looper holder having an adjustment element by which the tip of the looper can be moved toward and away from the needle. In one embodiment, a single bi-directionally adjustable screw or other element moves the looper tip in either direction. A separate locking element is also preferably provided. For adjusting the looper, the controller advances the stitching elements to a loop-take-time adjustment position where they stop and enter a safely lock mode, for adjustment of the loopers. Then, when adjustment is completed, the controller reverses the stitching elements so that no stitch is formed in the material.

According to another aspect of the invention, a needle-looper proximity sensor is provided that is coupled to an indicator, which signals, to an operator adjusting the looper, the position of the looper relative to the needle of a stitching element set. Preferably, a color coded light illuminates to indicate the position of the looper relative to the needle, with one indication when the setting is correct and one or more other indications when the setting is incorrect. The incorrect indication may include one color coded illumination when the looper is either too close or too far from the needle, with another indication when the looper is too far in the other direction.

In an illustrated embodiment of the invention, a looper holder is provided with an accessible adjustment mechanism by which an operator can adjust the transverse position of a looper relative to a needle in either direction with a single adjustment motion. The mechanism includes a looper holder in which a looper element is mounted to pivot so as to carry the tip of the looper transversely relative to the needle of the stitching mechanism. Adjustment of the looper tip position is changed by turning a single adjustment screw one way or the other to move the looper tip right or left relative to the needle. The looper is spring biased in its holder against the tip of the adjustment screw so that, as the screw is turned one way, the spring yields to the force of the screw and, as the screw is turned the other way, the spring rotates the looper toward the screw. The adjustment screw and spring hold the looper in its adjusted position and a lock screw, which is provided on the holder, can be tightened to hold the looper in its adjusted position.

According to other features of the invention, a sensor is provided to signal the position of the looper tip relative to the needle, which may be in the form of an electrical circuit that detects contact between the looper and needle. Indicator lights may be provided, for example, to tell the operator who is making a looper adjustment when the needle is in contact with the needle, so that the contact make/brake point can be accurately considered in the adjustment. The sensor may alternatively be some other looper and/or needle position monitoring device.

According to principles of the present invention, a multiple needle quilting machine is provided with individual thread cutting devices at each needle position. The thread cutting devices are preferably located on each of the looper heads of a multi-needle chain stitch quilting machine, and each of the devices are separately operable. In the preferred embodiment, each looper head of a multi-needle quilting machine is provided with a thread cutting device with a movable blade or blade set that cuts at least the top thread upon a command from a machine controller. The device also preferably cuts the bottom thread, and when doing so, also preferably holds the

bottom or looper thread until the stitching resumes, usually at a new location on the fabric being quilted. Where the quilting machine has separately actuatable or separately controllable sewing heads, or heads that can be individually mounted or removed, the looper component of each such head is provided with a separately controllable thread cutting device.

In order to reduce the likelihood of missed stitches, active or passive looper thread tail guides can be used to manipulate or otherwise guide the looper thread tail below the needle plate upon startup. In certain embodiments, a looper thread deflector is provided to guide the looper thread so the needle does not miss the looper thread triangle. In addition, particularly at startup of a pattern following the cutting of the looper thread, a split-start control method is provided as an alternative feature for avoiding missed stitches at startup. The split start feature is one use of the feature that allows the needle and looper drives to be decoupled and moved separately. With the split start feature, the initial motion of the needle and looper proceeding separately upon startup so as to render the pickup of the stitches predictable. This is achieved by insuring that the looper picks up the top-thread loop before the needle picks up the bottom thread loop triangle, which is a method that can be provided with alternatives to the split start, such as looper thread manipulation. This is assisted by a pair of needle guards at each looper drive location, one on the looper and one on the looper housing, both of which are adjustable. The dual needle guards limit needle deflection perpendicular to the plane of motion of the looper, which increases the reliability of stitch formation.

Alternative solutions are provided to wipe the cut top thread to the top of the material, including a thread wiper mechanism and a bridge movement wipe cycle that remove the cut top thread from the material after it has been cut before the start of a new pattern component. In addition, a thread tuck cycle is provided that places the cut top-thread tail on the back side of the material at the beginning of the stitching of a pattern curve. The tuck cycle also reduces the likelihood of missing stitches on start up. The wipe and tuck cycles may be combined as part of the tacking, thread cutting, jumping, tacking and startup sequence between patterns.

A tack-stitch sequence sewing method is also provided that minimizes needle deflection and further reduces the likelihood of missing stitches, which is particularly useful during the start up tack sequence. The sequence involves stitching a distance, for example approximately one inch, in the direction of the pattern, then returning along the same line to the original position before starting the normal sewing of the pattern along the sewing line. In this sequence, long stitches are used coupled with intermittent feed of the stitching elements relative to the material. This intermittent feed includes the alternate cycling of the needle through the material without feeding the material relative to the needle and then the pausing of the needle cycle with the needle withdrawn from the material while the material is moved relative to the needle. The stopping of the material or the needle is not necessarily absolute, but may rather be a smooth slowing of the needle or material motion while the other moves more rapidly. This sequence of stitches may be applied whenever stitching reverses direction in a pattern, particularly when the reversal causes the stitching to be applied back over previously formed stitches in the pattern. It is particularly useful during the start-up tack, and either may or may not also be applied for the ending tack. During sewing, continuous feed, rather than intermittent feed, is preferably employed. For the transition from an intermittent feed stitch sequence to the continuous feed stitching at the beginning of sewing of a pattern where

the threads have been previously cut, a series of intermittent-continuous transition stitches are used.

Further in accordance with principles of the invention, each thread of a quilting or other sewing machine is provided with a thread tension monitoring device. A thread tension control device for each such thread is made to automatically vary its adjustment so as to regulate the tension of the thread in response to the monitoring thereof. Preferably, a closed loop feedback control is provided for each of the threads of the machine. Each is operable to separately measure the tension of the thread and to correct the tension on a thread-by-thread basis.

The bridge drive system that is provided allows the bridges to be moved and controlled separately and moves the bridges precisely and quickly, maintaining their orientation without binding. This feature is used to perform novel sewing methods by which the bridges can be started and stopped separately in a synchronized manner to align patterns and avoid waste material between patterns. In addition, tack stitches can be sewn at different times by the needles of different bridges.

The separately controllable motions of the different bridges and the different degrees of motion provide a capability for producing a wider range of patterns and greater flexibility in selecting and producing patterns. Unique quilt patterns, such as patterns in which different patterns are produced by different needles or different needle combinations, can be produced. For example, the different bridges can be moved to sew different patterns at the same time.

A number of new patterns and pattern sewing techniques are provided by the features of the present invention. Some of these are provided, at least in part, as a result of the features of the equipment according to principles of the invention. And some of these are provided, at least in part, by methods and techniques according to other principles of the invention. Particular applications are set forth in connection with the discussion of the figures and the operation of the equipment in the detailed description below. For example, combination patterns can be formed of different pattern components that are sewn simultaneously or in a time-shared fashion by two different bridges that move independently. One continuous pattern can be sewn while discrete TACK-AND-JUMP patterns or a second different continuous pattern can be sewn along with the first pattern. An intermediate quilted product that includes one or more continuous patterns extending along more than one panel or portion of a panel on a continuous web provide speed and efficiency in quilting patterns that previously could be sewn on only single needle quilting machines or other slow machines, as well as new quilted patterns.

The mechanism has lower inertia than conventional quilting machines. Increased quilting speeds by $\frac{1}{3}$ are provided, for example, to 2000 stitches per minute.

The need for less overall pressure and force by the sewing elements and by the presser foot plates allows for lighter weight construction of the quilting machine and for a smaller machine having a smaller footprint in the bedding plant. Further, the use of individual presser feet avoids much of the pattern distortion caused by the presser arrangements of the past.

In addition, the elimination of the need to move the material to be quilted from side to side and the elimination of the need to squeeze the material under a large presser foot plate allows the machine to have a simple material path, which allows for a smaller machine size and is more adaptable to automated material handling.

In accordance with still other features of the present invention, a split start feature is provided that can be implemented

using a single drive servo for the needles and loopers. A phase shifting mechanism is provided to accomplish this with both needles and loopers being driven from the same motor. Further, in accordance with the invention, the phase of the loopers is advanced relative to that of the needles, then the loopers and needles are moved together maintaining the phase difference between them, then the loopers and needles are brought back into phase, by retracting the loopers for example or slowing or stopping the loopers relative to the needles while the needles catch up, from which point the cycle continues with the needles and loopers in phase.

In accordance with still further features of the present invention, a startup or end tack stitch apparatus and method are provided in which the tack stitch sequence can vary to accommodate different materials or products. The method and apparatus can provide for manual selection of the tack stitch sequence, for manual specification of the product or material type followed by machine response to the selection to set the appropriate tack stitch sequence, for automatic detection or analysis of the product or material type to determine the appropriate tack stitch sequence, or to selectable modes providing any or all of these features. In addition or as an alternative to the tack stitch sequence variation, other machine operating parameters such as thread pull-off, material movements and other functions may be varied in response to the differences in product or material. For example, where material is thicker or denser than ordinarily encountered, a slower, more aggressive or longer intermittent stitch tack sequence may be appropriate.

These and other objectives and advantages of the present invention will be more readily apparent from the following detailed description of the drawings of the preferred embodiment of the invention, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a quilting machine embodying principles of the present invention.

FIG. 1A is a cross-sectional top view of the quilting machine of FIG. 1 taken along the line 1A-1A of FIG. 1 illustrating particularly the lower bridge.

FIG. 1B is an enlarged top view illustrating a needle head and looper head assembly pair of bridges of FIG. 1A.

FIG. 2 is an isometric diagram illustrating one embodiment of a needle head and looper head assembly pair of the quilting machine of FIG. 1 viewed from the needle side.

FIG. 2A is an isometric diagram illustrating the needle head assembly of the needle and looper head pair of FIG. 2 viewed from the looper side.

FIG. 2C is an isometric diagram, similar to FIG. 2, illustrating an alternative needle and looper head pair.

FIG. 3 is an isometric diagram, partially cut away, illustrating the needle head clutch of the needle head assembly of FIGS. 2 and 2A.

FIG. 4 is an isometric diagram illustrating one embodiment of a looper head assembly of FIG. 2.

FIG. 4C is a top view, in the direction of the looper shaft, of a portion of the looper drive assembly of FIG. 4 with the looper in position for adjustment.

FIG. 4D is a disassembled perspective view of a looper holder and looper of the looper drive assembly of FIG. 4C.

FIG. 4E is a cross-sectional view of the looper, in the direction indicated by the line 4E-4E in FIG. 4C.

FIG. 4F is a diagram of one embodiment of a looper position indicator for the looper adjustment mechanism of FIGS. 4C-4E.

FIG. 4G is a diagram of one embodiment of a needle guard assembly.

FIG. 5 is a perspective diagram illustrating the use of one of a plurality of thread cutting devices as it is configured on each of a corresponding plurality of looper heads of a multi-needle quilting machine according to principles of the present invention.

FIG. 5A is a diagram illustrating the respective position of the needle and looper and the needle and looper threads at the end of a series of stitches, in relation to a thread cutting device.

FIGS. 5B and 5C are diagrams illustrating steps in the thread cutting operation.

FIG. 5D is a diagram of a thread tension measuring circuit according to certain aspects of the present invention.

FIGS. 5E-5J are diagrams illustrating thread handling features including thread tail wipe and tuck cycles according to certain embodiments of the invention.

FIGS. 5K-5X are diagrams illustrating stitching element motions of stitching sequences according to certain embodiments of the invention.

FIG. 5Y is a diagram illustrating a looper thread deflector according to an embodiment of the invention.

FIG. 6 is a diagrammatic isometric view illustrating one embodiment of a motion system of the machine of FIG. 1.

FIG. 6A is a diagrammatic cross-sectional representation a line 6A-6A of FIG. 6 depicting the motion system with a moving material web and the bridges stationary.

FIG. 6B is a diagrammatic cross-sectional representation similar to FIG. 6A depicting the motion system with a moving bridges and the material web stationary.

FIG. 6C is an enlarged perspective view illustrating the left portion of the machine of FIG. 1 in detail.

FIG. 6D is a cross-sectional view along line 6D-6D of FIG. 6C.

FIG. 6E is an enlarged sectional view of a portion of FIG. 6C.

FIG. 6F is a cross-sectional view along the line 6F-6F of FIG. 6E.

FIG. 6H is an isometric view of a portion of a bridge illustrating an alternative embodiment of a stitching element drive of the machine of FIG. 1 with the needle head and looper head assembly pair of FIG. 2C.

FIG. 6I is an enlarged perspective view of the bridge of FIG. 6H illustrating the needle head assembly side of the bridge.

FIG. 6J is a top view of a bridge with a differential drive according to certain embodiments of the invention.

FIG. 6K is a cross-sectional view through a portion of FIG. 6J showing needles and loopers in phase.

FIG. 6L is a cross-sectional view similar to FIG. 6K showing needles and loopers in phase out of phase for a split-start.

FIG. 6M is a disassembled perspective view showing a phase shifter differential drive component in detail.

FIG. 7A is a diagram illustrating the quilting of a standard continuous pattern.

FIG. 7B is a diagram illustrating the quilting of a 360 degree continuous pattern.

FIG. 7C is a diagram illustrating the quilting of a discontinuous pattern.

FIG. 7D is a diagram illustrating the quilting of different linked patterns.

FIG. 7E is a diagram illustrating the quilting of variable length, continuous 360 degree patterns.

FIG. 7F is a diagram illustrating the simultaneous quilting of continuous mirror image patterns.

15

FIG. 7G is a diagram illustrating the simultaneous quilting of different patterns.

FIG. 7H is a diagram illustrating a portion of a continuous quilted pattern.

FIG. 7I is a diagram illustrating a portion of a discontinuous, TACK-AND-JUMP quilted pattern.

FIG. 7J is a diagram illustrating a portion of a combination of the continuous and discontinuous quilted patterns of FIGS. 7H and 7I.

FIG. 7K is a diagram similar to FIG. 7H illustrating a portion of another continuous quilted pattern.

FIG. 7L is a diagram illustrating a portion of a combination of the continuous quilted patterns of FIGS. 7H and 7K.

FIG. 7M is a diagram showing a length of web spanning more than one quilted panel on which is quilted a combination pattern of which at least one is continuous.

FIGS. 7N-7P are diagrams showing selected embodiments of the web of FIG. 7M.

FIG. 8 is an isometric view of a facing material supply and splicing station configured for installation immediately upstream of the quilting machine of FIG. 1.

FIGS. 8A-8L are a sequence of diagrams illustrating the change and splicing of facing material with the station of FIG. 8.

FIG. 9 is a diagram illustrating a combination pattern made up of closely spaced diverse patterns quilted according to one embodiment of the present invention.

FIG. 9A is a diagram illustrating a combination pattern quilted on machines of the prior art.

FIGS. 9B-9N are diagrams illustrating steps in quilting processes for quilting the combination pattern of FIG. 9.

DETAILED DESCRIPTION OF THE DRAWINGS

FIGS. 1 and 1A illustrate a multi-needle quilting machine 10 according to one embodiment of the invention. The machine 10 is of a type used for quilting wide width webs of multi-layered material 12, such as the materials used in the bedding industry in the manufacture of mattress covers. The machine 10, as configured, may be provided with a smaller footprint and thus occupies less floor area compared with machines of the prior art, or in the alternative, can be provided with more features in the same floor space as machines of the prior art. The machine 10, for example, has a footprint that is about one-third of the floor area as the machine described in U.S. Pat. No. 5,154,130, which has been manufactured by the assignee of the present invention for this industry for a number of years.

The machine 10 is built on a frame 11 that has an upstream or entry end 13 and a downstream or exit end 14. The web 12, extending in a generally horizontal entry plane, enters the machine 10 beneath a catwalk 29 at the entry end 13 of the machine 10 at the bottom of the frame 11, where it passes either around a single entry idler roller 15 or between a pair of entry idler rollers at the bottom of the frame 11, where it turns upwardly and extends in a generally vertical quilting plane 16 through the center of the frame 11. At the top of the frame 11, the web 12 again passes between a pair of web drive rollers 18 and turns downstream in a generally horizontal exit plane 17. One or both of the pairs of rollers at the top and bottom of the frame may be linked to drive motors or brakes that may control the motion of the web 12 through the machine 10 and control the tension on the web 12, particularly in the quilting plane 16. Alternatively, one or more other sets of rollers, as described below, may be provided for one or more of these purposes. The machine 10 operates under the control of a programmable controller 19.

16

At the entry end 13 of the machine 10 are the rolls of material that make up the web of multi-layered material 12 that enters this entry region 13 in web form from beneath catwalk 29, which is provided for a machine operator to walk across the front of the machine 10. The top or facing layer 12a of the material 12, or, in the case of mattress cover quilting, the ticking layer, is fed beneath this catwalk from a supply station 400 located upstream of the catwalk 29. The supply station 400 is that illustrated in perspective in FIG. 8. The remaining layers of material, including the fill 12b and the backing layer 12c are fed from supplies (not shown) upstream of the facing layer supply station 400. The facing layer A is supplied to the machine 10 from a supply roll 401 supported at the supply station 400. As illustrated in FIG. 8, and in the side elevational view of FIG. 8A.

The supply station 401 includes a frame 402 that can be set in a fixed position against the upstream side of the catwalk 29 of the quilting machine 10. A supply roll cradle 403 is pivotally mounted to the frame 402 and carries, at its remote end, two pair of notched mounting blocks, including lower blocks 404 and upper blocks 405. The blocks 404 and 405 are configured to support the opposite ends of an axial rod, such as axial rod 406, which extends through the center of, and supports, the supply roll 401. When material is being fed from the supply roll 401, the roll 401 is supported on the blocks 404, as illustrated in FIG. 8A, with the facing layer of material 12a extending horizontally from the roll 401, under the catwalk 29, and to the machine 10.

When a material change is desired, a new roll of facing material 410 is set on the catwalk 29, which serves as a pre-staging area, as illustrated in FIG. 8B. The roll 410 may have an axial rod 411 extending through the hole in the center of the roll 410. The extensions of this rod 411 from the ends of the roll 410 can serve as handles for use by a pair of attendants for placing the roll 410 on the catwalk 29. From its position on the catwalk 29, the new roll 410 is staged for replacing the roll 401 by rolling it onto a tray 412 immediately adjacent the catwalk 29, as illustrated in FIG. 8C. From this position, the roll 410 is moved to the cradle 403 by lifting from the tray 412 the axial rod 411 by its ends and placing them in the upper blocks 405 of the cradle 403, as illustrated in FIG. 8D.

After the new roll 410 has been mounted on the cradle 403, a hydraulic or pneumatic cylinder 415 is activated to lift the cradle 403 above the frame 402 by pivoting the cradle 403 upward on the frame 402. This leaves the rolls 403 and in the positions illustrated in FIG. 8E, with the web of facing material 12a extending from the roll 401, below the catwalk 29, to the machine 10. At this point, another cylinder 416 is activated to lower a clamping arm 417, which clamps the material 12a against a clamping bar 418 on the frame 402, as illustrated in FIG. 8F. At this point, the material 12a is cut from the roll 401, which may be done manually with a knife or scissors, along a transverse line at location 420, providing just enough trailing material to allow the trailing edge 421 of the material 12a to drop into a splicing position in a splicer mechanism 425, as illustrated in FIG. 8G.

Once the trailing edge 421 is in the splicing mechanism 425, held between the clamping arm 417 and the clamping bar 418, and the material 12a has been cut from the roll 401, the roll 401 can be lifted by rod 406 and removed from the lower blocks 404 of the cradle 403 and placed in a tray 430 at the top of the frame 402, as illustrated in FIG. 8H. Then, the new roll 410 can be moved from upper blocks 405 of the cradle 403 to the lower blocks 404, where it will replace the previous roll 401 of facing material 12a, as illustrated in FIG. 8I. Then the leading edge 426 of material from the roll 410 is placed

adjacent the trailing edge **421** of the facing material **12a**, in the splicer **425**, where the materials from rolls **410** and **401** are spliced together by sewing a transverse row of single-lock chain stitches with the splicer **425**, to form a continuous web of facing material **12a**, as illustrated in FIG. **8J**. Then the clamping arm **417** can be pivoted up out of its clamping position by actuation of the cylinder **416**, leaving the new material from roll **410** extending from roll **410** spliced to the old material from roll **401** that extends into the quilting machine **10**, as illustrated in FIG. **8K**. Whereupon, the cylinder **415** can be activated to lower the carriage **403** to bring the roll **410** into the former position of the original roll **401**, at which the machine **10** can be run with facing material supplied from the new roll **410**, as illustrated in FIG. **8L**.

While the description above discusses a device used for splicing webs of material together when replacing one web of material with another, the device can be used for easily and efficiently splicing a short length of material to a web to feed one or a few panels of material into a quilter. This can be advantageous in providing custom printed panels to a quilter, for example, as described in U.S. Pat. Nos. 6,263,816 and 6,435,117, hereby expressly incorporated by reference herein.

Alternative embodiments can be devised using the principles and features set forth above. For example, the material **12a** can be guided through the splicer mechanism **425** and spliced to the leading edge of the material from roll **410** before the material **12a** is cut from the roll **401**.

On the frame **11** is mounted a motion system that includes a plurality of bridges, including a lower bridge **21** and an upper bridge **22**, that move vertically on the frame, but which may include more than the two bridges illustrated. Each of the bridges **21**, **22** has a front member **23** and a back member **24** (FIG. **1A**) that each extend horizontally generally parallel to, and on opposite sides of, the quilting plane **16**. Each front member **23** has mounted thereon a plurality of needle head assemblies **25**, each configured to reciprocate a needle in longitudinal horizontal paths perpendicular to the quilting plane **16**. Between adjacent needle head assemblies **25**, a rib or stiffener plate **89** is provided to structurally stiffen the bridge and to resist dynamic deformation from the sewing forces applied by the needle drives. Each of the needle head assemblies **25** can be separately activated and controlled by the machine controller **19**. A plurality of looper head assemblies **26**, one corresponding to each of the needle head assemblies **25**, are mounted on each of the back members **24** of each of the bridges **21**, **22**. The looper head assemblies **26** each are configured to oscillate a looper or hook in a plane generally perpendicular to the quilting plane **16** to intersect the longitudinal paths of the needles of the corresponding needle head assemblies **25**. The looper head assemblies **26** may also be separately activated and controlled by the machine controller **19**. Each needle head assembly **25** and its corresponding looper head assembly **26** make up a stitching element pair **90**, in which the stitching elements cooperate to form a single series of double lock chain stitches. In the embodiment shown in FIGS. **1** and **1A**, there are seven such stitching element pairs **90**, including seven needle head assemblies **25** on the front members **23** of each bridge **21,22**, and seven corresponding looper head assemblies **26** on the rear member **24** of each bridge **21,22**. Stitching element pairs **90** are illustrated in more detail in FIG. **1B**.

No single-piece needle plate is provided. Rather, a six-inch square needle plate **38** is provided parallel to the quilting plane **16** on the looper side of the plane **16** on each of the looper heads **26**. This needle plate **38** has a single needle hole

81 that moves with the looper head **26**. All of the needle plates **38** typically lie in the same plane.

Similarly, no common presser foot plate is provided. Instead, as described below, each needle head assembly **25** includes a respective one of a plurality of separate presser feet **158**. Such local presser feet are provided in lieu of a single presser foot plate of the prior art that extends over the entire area of the multiple row array of needles. A plurality of presser feet are provided on each front member **23** of each bridge **21**, **22**, each to compress material around a single needle. Preferably, each needle assembly **25** is provided with its own local presser foot **158** having only sufficient area around the needle to compress the material **12** for sewing stitches with the respective needle assembly.

Each of the needle assemblies **25** on the front members **23** of the bridges **21,22** is supplied with thread from a corresponding spool of needle thread **27** mounted across on the frame **11** on the upstream or needle side of the quilting plane **16**. Similarly, each of the looper assemblies **26** on the back members **24** of the bridges **21,22** is supplied with thread from a corresponding spool of looper thread **28** mounted across the frame **11**, on the downstream or looper side of the quilting plane **16**.

As illustrated in FIGS. **1-1B**, a common needle drive shaft **32** is provided across the front member **23** of each bridge **21,22** to independently drive each of the needle head assemblies **25**. Each shaft **32** is driven by a needle drive servo **67** on the needle side member **23** of each respective bridge **21**, **22** that is responsive to the controller **19**. A looper belt drive system **37** is provided on the back member **24** of each of the bridges **21**, **22** to drive each of the looper head assemblies. Each looper drive belt system **37** is driven by a looper drive servo **69** on the looper side member **24** of each respective bridge **21**, **22** that is also responsive to the controller **19**. Each of the needle head assemblies **25** may be selectively coupled to or decoupled from the motion of the needle drive shaft **32**. Similarly, each looper head assembly **26** may be selectively coupled to or decoupled from the motion of the looper belt drive system **37**. Each of the needle drive shafts **32** and looper belt drive systems **37** are driven in synchronism through either mechanical linkage or motors controlled by the controller **19**.

Referring to FIG. **2**, each needle head assembly **25** is comprised of a clutch **100** that selectively transmits power from the needle drive shaft **32** to a needle drive **102** and presser foot drive **104**. The needle drive **102** has a crank **106** that is mechanically coupled to a needle holder **108** by an articulated needle drive **110**, which includes three links **114**, **116** and **120**. The crank **106** has an arm or eccentric **112** rotatably connected to one end of the first link **114**. One end of the second link **116** is rotatably connected to a pin **117** extending from a base **118** that, in turn, is supported on the front member of one of the bridges **21**, **22**. One end of the third link **120** is rotatably connected to a pin **123** extending from a block **122** that is secured to a reciprocating shaft **124**, which is an extension of the needle holder **108**. Opposite ends of the respective links **114**, **116** and **120** are rotatably connected together by a pivot pin **121** that forms a joint in the articulated needle drive **110**.

The shaft **124** is mounted for reciprocating linear motion in fore and aft bearing blocks **126**, **128**, respectively. The drive block **122** has a bearing (not shown) that is mounted on a stationary linear guide rod **130** that, in turn, is supported and rigidly attached to the bearing blocks **126**, **128**. Thus, rotation of the crank **106** is operative via the articulated needle drive **110** to reciprocate a needle **132** secured in a distal end of the needle holder **108**.

Referring to FIG. 2A, the presser foot drive 104 has an articulated presser foot drive 144 that is similar to the articulated needle drive 110. A crank 140 is mechanically connected to a presser foot holder 142 via mechanical linkage 144, which includes three links, 146, 150 and 152. One end of a fourth link 146 is rotatably coupled to an arm or an eccentric 148 on the crank 140. One end of a fifth link 150 is rotatably connected to a pin 151 extending from the base 118, and one end of a sixth link 152 is rotatably connected to a pin 155 extending from a presser foot drive block 154. Opposite ends of the respective links 146, 150 and 152 are rotatably connected together by a pivot pin 153 that forms a joint in the presser foot articulated drive 144. The presser foot drive block 154 is secured to a presser foot reciprocating shaft 156 that, in turn, is slidably mounted within the bearing blocks 125, 126. A presser foot 158 is rigidly connected to the distal end of the presser foot reciprocating shaft 156. The drive block 154 has a bearing (not shown) that is mounted for sliding motion on the linear guide rod 130. Thus, rotation of the crank 140 is operative via the articulated presser foot drive 144 to reciprocate the presser foot 158 with respect to the needle plate 38.

The needle drive crank 106 and presser foot crank 140 are mounted on opposite ends of an input shaft (not shown) supported by bearing blocks 160. A pulley 162 is also mounted on and rotates with the cranks 106, 140. A timing belt 164 drives the cranks 106, 140 in response to rotation of an output pulley 166. The clutch 100 is operable to selectively engage and disengage the needle drive shaft 32 with the output pulley 166, thereby respectively initiating and terminating the operation of the needle head assembly 25.

Referring to FIG. 3, the output pulley 166 is fixed to an output shaft 168 that is rotatably mounted within a housing 170 of the clutch 100 by means of bearings 172. The needle drive shaft 32 is rotatably mounted within the output shaft 168 by bearings 174. The drive member 176 is secured to the needle drive shaft 32 and is rotatably mounted within the housing 170 by bearings 178. The drive member 176 has a first, radially extending, semicircular flange or projection 180 extending in a direction substantially parallel to the centerline 184 that provides a pair of diametrically aligned drive surfaces, one of which is shown at 182. The drive surfaces 182 are substantially parallel to a longitudinal centerline 184 of the needle drive shaft 32.

The clutch 100 further includes a sliding member 186 that is keyed to the output shaft 168. Thus, the sliding member 186 is able to move with respect to the output shaft 168 in a direction substantially parallel to the centerline 184. However, the sliding member 186 is locked or keyed from relative rotation with respect to the output shaft 168 and therefore, rotates therewith. The keyed relationship between the sliding member 186 and the output shaft 168 can be accomplished by use of a keyway and key or a spline that couples the sliding member 186 to the shaft 168. Alternatively, an internal bore of the sliding member 186 and the external surface of the output shaft 168 can have matching noncircular cross-sectional profiles, for example, a triangular profile, a square profile, or a profile of another polygon.

The sliding member 186 has a first, semicircular flange or projection 188 extending in a direction substantially parallel to the centerline 184 toward the annular flange 182. The flange 188 has a pair of diametrically aligned drivable surfaces, one of which is shown at 190, that can be placed in and out of opposition to the drive surfaces 182 of the flange 180. The sliding member 186 is translated with respect to the output shaft 168 by an actuator 192. The actuator 192 has an annular piston 194 that is mounted for sliding motion within an annular cavity 196 in the housing 100, thereby forming

fluid chambers 198, 200 adjacent opposite ends of the piston 194. Annular sealing rings 202 are used to provide a fluid seal between the piston 194 and the walls of the fluid chambers 198, 200. The sliding member 186 is rotationally mounted with respect to the piston 194 by bearings 204.

In operation, the needle drive shaft 32 is stopped at a desired angular orientation, and pressurized fluid, for example, pressurized air, is introduced into the fluid chamber 198. The piston 194 is moved from left to right as viewed in FIG. 3, thereby moving the drivable surfaces 190 of the sliding member 186 opposite the drive surfaces 182. With the clutch 100 so engaged, the needle drive shaft 32 is directly mechanically coupled to the sliding member 186 and the output shaft 168, the output pulley 166 follows exactly the rotation of the needle drive shaft 32. A subsequent rotation of the needle drive shaft 32 results in a simultaneous rotation of the output shaft 168.

Upon the needle drive shaft 32 again being stopped at the desired angular orientation, the pressurized fluid is released from the fluid chamber 198 and applied to the fluid chamber 200. The piston 194 is moved from right to left as viewed in FIG. 3, thereby moving the drivable surfaces 190 out of contact with the driving surface 182 and disengaging the clutch 100. Thus, the drive surfaces 182 rotate past the drivable lugs 188 and the needle drive shaft 32 rotates independent of the output shaft 168. However, in the disengaged state, it is desirable that the output shaft 168 maintain a fixed angular position while the clutch 100 is disengaged. Thus, the sliding member 186 has a second, semicircular annular lockable flange 206 extending to the left, as viewed in FIG. 3, in a direction substantially parallel to the centerline 184. The lockable flange has diametrically aligned lockable surfaces 205.

As shown in FIG. 4, the looper and retainer drive 212 provides a looper 216 with a reciprocating angular motion about a pivot axis 232 in a plane immediately adjacent the reciprocating needle 132. The looper and retainer drive 212 also moves a retainer 234 in a closed loop path in a plane that is substantially perpendicular to the plane of reciprocating angular motion of the looper 216 and the path of the needle 132.

The looper 216 is secured in a looper holder 214 that is mounted on a flange 220 extending from a first looper shaft 218a. An outer end of the looper shaft 218a is mounted in a bearing 236 that is supported by a looper drive housing 238. An inner end of the looper shaft 218a is connected to an oscillator housing 240. Thus, the looper 216 extends generally radially outward from the axis of rotation 232 of the looper shaft 218.

FIG. 4 shows the looper drive assembly 26 of a type of multi-needle quilting machine 10 in which the needles are oriented horizontally. The looper drive assembly 26 may include a selective coupling element 210, for example, clutch 210 that connects the input 209 of the drive assembly 226 to a drive train that is synchronized to the drive for a cooperating needle drive assembly. The looper drive assembly 26 includes a frame member 219 on which the drive assembly 226 and 210 are mounted in mutual alignment. The frame member 219 is mounted to the rear portion 24 of the respective bridge 21, 22 such that the looper head assembly 26 aligns with the corresponding needle head assembly 25. The output of the clutch 210 drives a looper drive mechanism 212, that has an output shaft 218 having a flange 220 thereon, on which is mounted a looper holder 214. In other types of multi-needle quilting machines, such a looper holder 214 may oscillate with other loopers about a common shaft that is rocked by a common drive linkage that is permanently coupled to the

drive train of a needle drive, as described in U.S. Pat. No. 5,154,130. The nature of the chain stitch forming machine and the number of needles is not material to the concepts of the present invention.

In general, a looper **216**, when mounted in a looper holder **214**, is made to oscillate on the shaft **218** along a path **800** that brings it into a cooperating stitch forming relationship with a needle **132**, as illustrated in FIG. 4C. The stitch forming relationships and motions of the needle and looper are more completely described in U.S. Pat. No. 5,154,130. During stitch formation, the tip **801** of the looper enters a loop **803** in a top thread **222** that is presented by the needle **132**. In order to pick up this loop **803**, the transverse position of the tip **801** of the looper **216** is maintained in adjustment so that it passes immediately beside the needle **132**. Adjustment of the looper **216** is made with the shaft **218** stopped in its cycle of oscillation with the looper tip **801** in transverse alignment with the needle **132**, as illustrated in FIG. 4C. In such adjustment, the tip **801** of the looper **216** is moved transversely, that is, perpendicular to the needle **132** and perpendicular to the path **800** of the looper **216**.

As depicted in FIGS. 4C and 4D, a preferred embodiment of the looper **216** is formed of a solid piece of stainless steel having a hook portion **804** and a base portion **805**. At the remote end of the hook portion **804** is the looper tip **801**. The base portion **805** is a block from which the hooked portion **804** extends from the top thereof. The base portion **805** has a mounting peg **806** extending from the bottom thereof by which the looper **216** is pivotally mounted in a hole **807** in the holder **214**.

The holder **214** is a forked block **809** formed of a solid piece of steel. The forked block **809** of the holder **214** has a slot **808** therein that is wider than the base portion **805** of the looper **216**. The looper **216** mounts in the holder **214** by insertion of the base **805** into the slot **808** and the peg **806** into the hole **807**. The looper **216** is loosely held in the holder **214** so that it pivots through a small angle **810** on the pin **806** with the body **805** moving in the slot **808** as illustrated in FIG. 4E. This allows the tip **801** of the looper **216** to move transversely a small distance, as is indicated by the arrow **811**, which, though arcuate, is comparable to a straight transverse line, with the angle of the hook **804** of the looper **214** being relatively insignificant.

The adjustment is made by an allen-head screw **812** threaded in the holder **214** so as to abut against the base **805** of the looper **214** at a point **813** offset from the pin **806**. A compression spring **814** bears against the looper body **805** at a point **815** opposite the screw **812** so that a tightening of the screw **812** causes a motion of the tip **801** of the looper **216** toward the needle **132** while a loosening of the screw **812** causes a movement of the tip **801** of the looper **216** away from the needle **132**. A locking screw **816** is provided to lock the looper **216** in its position of adjustment in the holder **214** and to loosen the looper **216** for adjustment. The locking screw **816** effectively clamps the pin **806** in the hole **807** to hold it against rotation.

In practice, the looper **214** position is preferably adjusted so that the tip **801** is either barely in contact with the needle **132** or minimally spaced from the needle **132**. In order to facilitate the attainment of such a position, an electrical indicator circuit **820** is provided, as diagrammatically illustrated in FIG. 4F. The circuit **820** includes the looper **216**, which is mounted in the holder **214**, which is, in turn, mounted through an electrical insulator **821** to the flange **220** on the shaft **218**, as shown in FIG. 4D. The holder **214** is electrically connected to an LED or some other visual indicator **822**, which is connected in series between the holder **214** and an electrical

power supply or electrical signal source **823**, which is connected to ground potential on the frame **11**. The needle **132** is also connected to ground potential. As such, when the looper **216** is in contact with the needle **132**, a circuit through the indicator **822** and power or signal source **833** is closed, activating the indicator **822**.

An operator can adjust the looper **216** by adjusting the screw **812** back and forth such that the make-break contact point between the needle **132** and the looper **216** is found. Then the operator can leave the looper in that position or back off the setting one way or the other, as desired, and then lock the looper **216** in position by tightening the screw **816**.

When looper adjustment is to be made, the machine **10** will be stopped with the needle in the 0 degree or top dead center position, whereupon the controller **19** advances the stitching elements to the loop-take-time position in the cycle (FIG. 4C), where the elements stop and the machine enters a safety lock mode in which an operator will make looper adjustments. After the needles and loopers are set, with input from the operator, the controller **19** of the machine **10** moves the looper and needle in a direction other than the direction to form a stitch. This is achieved by driving the needle and looper drive servos **67** and **69** in reverse to rotate the needle drive shafts **32** and looper drives **37** backward to move the looper and needle backwards in their cycles, thereby returning the needle to its 0 degree position. This prevents the forming of a stitch, which is desirable because looper adjustment is often best made between patterns. By preventing stitch formation, looper adjustment can be made anywhere along a stitch line, whether or not it is desired to continue sewing along a line or path. Further, the condition that holds the trimmed looper thread and wiped top thread, as explained in connection with FIGS. 5-5D below, in describing the trimmed thread condition, is preserved.

Single needle sewing machines have employed a variety of thread cutting devices. Such a device **850** is illustrated in FIG. 5. It includes a reciprocating linear actuator **851**, which may be pneumatic. A double barbed cutting knife **852** is mounted to slide on the actuator **851**, which withdraws linearly toward the actuator **851** when it is actuated. The actuator **851** is, in turn, mounted on a sliding block **858** (not shown in FIG. 5; shown in embodiment of FIG. 2C) which moves the actuator **851** and related assembly toward and away from the needle hole in the needle plate **38**, to a position it occupies when the cutting device is actuated and back to a rest position out of the way of the looper **216**. The knife **852** has a needle thread barb **854** and a looper thread barb **853**, each of which hooks the respective top and bottom threads when the actuator **851** is actuated. The barbs **853** and **854** both have cutting edges thereon to thereupon cut the respective threads. A stationary sheath member **855** is fixed to the actuator **851**, which has surfaces configured to cooperate with the sliding knife **852** to sever the threads. In doing so, the knife **852** is stopped in a retracted position which allows the tail of the needle thread to be released but keeps the bottom thread tail clamped between the knife **852** and a spring metal clamp **856** fixed to the bottom of the sheath member **855**. This clamping prevents unthreading of the looper, which can be close to the cutoff position, whereby the looper thread tail may be very short. FIGS. 5-5D illustrate the assembly in a machine having the needles oriented vertically. In the machine **10**, however, the needle **132** is oriented horizontally, perpendicular to the vertical material plane **16**, while the looper **216** is oriented to oscillate in a transverse-horizontal direction, parallel to the plane **16**, with the tip **801** of the looper **216** pointing toward the left side of the machine **10** (viewed from the front as in FIG. 1).

FIG. 5A shows the looper drive assembly 26 of a type of multi-needle quilting machine 10 in which the needles are oriented horizontally. At the end of the sewing of a chain of stitches that constitutes a discrete pattern or pattern component, the needle 132 and looper 216 typically stop in a position as illustrated in FIG. 5A in which the needle 132 is withdrawn from the material on the needle side of the fabric 12 being quilted. At this point in the stitching cycle, a needle thread 222 and a looper thread 224 are present on the looper side of the material 12 being quilted. The needle thread 222 extends from the material 12 down around the looper hook 804 of the looper 218 and returns to the fabric 12, while the looper thread 224 extends from a thread supply 856, through the looper hook 804 and out a hole in the tip 801 of the looper 216, and into the material 12.

On the looper side of the material 12, at each of a plurality of the looper heads 26, is positioned one of the cutting devices 850, each having an actuator 851 thereof equipped with a pneumatic control line 857 connected through appropriate interfaces (not shown) to an output of a quilting machine controller 19. The individual thread cutting device 850 per se is a thread cutting device used in the prior art in single needle sewing machines.

In accordance with the present invention, a plurality of the devices 850 are employed in a multi-needle quilting machine in the manner described herein. Referring to FIGS. 5 and 5A, on each looper assembly 26 of a multi-needle chain stitch quilting machine, a device 850 is positioned so that, when extended, the knife 852 of the device 850 extends between the looper 216 and the material 12, and is connected to operate under computer control of the controller 19 of the quilting machine. When at a point in the cycle at which the thread may be cut, as illustrated in FIG. 5A, the controller 19 actuates the actuator 851, which moves the knife 852 through the loop of the needle thread 222 such that it hooks the needle and looper threads, as illustrated in FIG. 5B. Then the knife 852 retracts to cut the needle thread 222 and the looper thread 224 extending from the material 12. Both cut ends of the needle thread 222 are released, as is the cut end of the looper thread 224 that extends to the material. However, the end of the looper thread 224 that extends to the looper 216 remains clamped, as illustrated in FIG. 5C. This clamping holds the looper thread end so that a loop is formed when sewing resumes, thereby preventing the loss of an unpredictable number of stitches before the chaining of the threads begins, which would cause defects in the stitched pattern.

As additional insurance in avoiding lost stitches at the beginning of sewing, the looper is oriented such that, should the end of the looper thread 224 fail to clamp, the end of the thread 224 will be oriented by gravity on the correct side of the needle so that the series of stitches will begin. In this way, the probability that the loops will take within the first few stitches that constitute the tack stitches sewn and the beginning of a pattern is high.

The above thread trimming feature is particularly useful for multi-needle quilting machines having selectively operable heads or heads that can be individually and separately installed, removed or rearranged on a sewing bridge. The individual cutting devices 850 are provided with each looper head assembly and are removable, installable and movable with each of the looper head assemblies. In addition, where the heads are selectively operable, the feature provides that each thread cutting device is separately controllable.

To supplement the thread trimming feature, a thread tail wiper 890 is provided on the needle head assembly 25. As further illustrated in FIG. 5C, the wiper 890 includes a wire hook wiping element 891 that is pivotally mounted on a

pneumatic actuator 892 adjacent the needle 132 to rotate the wiping element 891, after the needle thread 221 is cut, about a horizontal axis that is perpendicular to the needle 132. When actuated, the actuator 892 sweeps the wiping element 891 around the tip of the needle 132 on the inside of the presser foot bowl 158 to pull the tail of the needle thread 221 from the material 12 to the needle side of the material 12 and to the inside of the presser foot bowl 158. From this position, upon startup of sewing, the top thread will not be clamped under the presser foot, so the thread tail will typically be readily tucked to the back of the material 12 when the needle first descends at the start of a pattern.

FIG. 5D illustrates a thread tension control system 870 that can similarly be applied to individual threads of sewing machines, and which is particularly suitable for each of the individual threads of a multi-needle quilting machine as described above. A thread, for example, a looper thread 224, typically extends from a thread supply 856 and through a thread tensioning device 871, which applies friction to the thread and thereby tensions the thread moving downstream, for example, to a looper 216. The device 871 is adjustable to control the tension on the thread 224. The system 870 includes a thread tension monitor 872 through which the thread 224 extends between the tensioner 871 and the looper 216. The monitor 872 includes a pair of fixed thread guides 873, between which the thread is urged and deflected transversely by a sensor 874 on an actuating arm 875 supported on a transverse force transducer 876, which measures the transverse force exerted on the sensor 874 by the tensioned thread 224 to produce a thread tension measurement. Each of the threads 222 and 224 is provided with such a thread tension control.

A thread tension signal is output by the transducer 876 and communicated to the controller 19. The controller 19 determines whether the tension in the thread 224 is appropriate, or whether it is too loose or too tight. The thread tensioner 871 is provided with a motor or other actuator 877, which performs the tension adjustment. The actuator 877 is responsive to a signal from the controller 19. When the controller 19 determines from the tension measurement signal from the transducer 876 that the tension in thread 224 should be adjusted, the controller 19 sends a control signal to the actuator 877, in response to which the actuator 877 causes the tensioner 871 to adjust the tension of the thread 224.

In lieu of the use of a thread tail wiper 890, as illustrated in FIG. 5C, or other mechanism for pulling the cut top thread free after being cut and before resuming sewing at a new location, a machine control sequence may be executed that will achieve the results of the thread tail wiping function. FIG. 5E illustrates the state of the top thread 222 immediately after a tack stitch sequence is performed at the end of the sewing of a pattern component, before threads have been cut. The top thread 222 is shown extending from a top-thread supply 401, through a top-thread tensioner 402 to the eye of the needle, which is operated by an actuator 403 controlled by an output of the controller 19, to the needle 132. Between the tensioner 402 and the needle 132, the top thread 222 passes through a pull-off mechanism 404 that includes a pusher 405 driven by an actuator 406 that is also controlled by an output of the controller 19. In FIG. 5E, the pusher 405 is shown in solid lines in its retracted position. When the actuator 406 is actuated, the pusher 405 moves to its extended position 407, illustrated by a broken line, to pull the top thread to the position also illustrated by a broken line. A top-thread pull-off is executed by the controller 19 sending a signal to the actuator 403 of the top-thread tensioner 402 to release tension on the top thread 222 for a short interval of time during which the

25

thread pull-off mechanism **404** is pulsed. The pulsing of the thread pull-off mechanism **404** results from a signal from the controller **19** to the actuator **406** of the pull-off mechanism **404** which causes the pusher **405** to deflect the top thread **222** so as to pull off a length of slack top thread from the top-thread supply **401**. Alternatively, the needle **132** can be caused to move a short distance of roughly a few inches relative to the material **12** to pull the length of slack in the top thread to pull through the needle **132** to add a length of thread tail between the needle **132** and the material **12**. This relative movement can be brought about by advancing the web **12** or by moving bridges **21**, **22** or both.

After the top thread **222** has been pulled off as described above, the threads **222** and **224** are cut and the looper thread is clamped as described above in connection with FIG. **5C**. In this embodiment, the wiper mechanism **890**, however, need not be present. Instead, a wiping motion may be employed. At this point in the procedure, the top-thread tail extends from the needle **132** down through the material **12** to below the material to the position at which it was cut, as illustrated in FIG. **5F**, and thread tension has been reapplied to the top thread. Then, the needle **132** is advanced to a new starting position **410** relative to the material **12**, that is, either the bridges or the material or both can be moved, bringing the thread to the top of the material for the resumption of sewing as illustrated in FIG. **5G**.

Then, whether or not wiper **890** has been employed prior to this point, a top-thread tuck cycle is executed in which the sewing heads are operated through one stitch cycle, which pokes the top-thread tail through the material **12** to below the material **12**, where it is caught by the looper **216**, as illustrated in FIG. **5H**. Then, with the tension of the top thread **222** having been previously applied by actuation of the tensioner **402**, the needle **132** is moved in a thread wipe motion relative to the material **12**, away from and back to the starting position **410** where the thread penetrated the material **12** as illustrated in FIG. **5I**. For this motion, the controller **19** selects the direction by interpreting the pattern to be sewn. This motion is enough to pull the remaining top-thread tail to the bottom or looper side of the material **12** without pulling the tail again out of the material. The length of this motion may be different for different applications.

The motion path may be, for example, a line, an arc, a triangle a combination of a line and an arc or some other motion or combination that takes the needle about two inches more or less from the position **410**. A different path length may be used depending on the length of the thread tail that the machine is designed or programmed to cut. The path is preferably oriented so that any slack in the top thread produced at the needle **132** lies on a side of the pattern path that avoids the thread being caught in the sewing pattern or being struck by the needle **132**. With the machine **10**, this motion is preferably implemented by holding the material **12** stationary and moving the bridges **21**, **22** in the path parallel to the plane of the material **12**. At the end of the tuck cycle, the machine is in the position shown in FIG. **5J**.

The start of a pattern requires that the sewing elements, the needle **132** and the looper **216**, cooperate such that the needle thread **222** and looper thread **224** alternately pick up loops formed by the other thread to start the formation of stitches of the chain. When a stitch cycle is executed in the middle of a sewing sequence, that is, once the chain has begun, the needle **132** descends through the material **12** to pick up a loop **412**, sometimes referred to as the triangle, formed between the looper **216**, the top thread **222** and the looper thread **224**, the formation of which loop is facilitated by the action of the retainer or spreader **234**, as illustrated in FIG. **5K**. (See FIG.

26

5F of U.S. Pat. No. 5,154,130 for a more complete explanation. FIGS. **5A-5G** of that patent are sequential illustrations of a normal chain-stitch forming cycle.) However, with the threads not yet set in the material **12**, the looper thread **224** terminates below the needle plate **38** and below the retainer **234**. Specifically, the looper thread **224** is clamped between the cutting knife **852** and the spring clamp **856** (FIG. **5J**). Therefore, the triangle **412** does not yet exist in its normal form and the catching of this loop by the needle **132** is not necessarily completely predictable. As a result, there is an increased likelihood that the first stitch will be missed. More importantly, there is an unacceptable probability that each subsequent stitch will be missed until some indeterminate number of stitch cycles later when the first stitch is formed. This can result in a flawed product or wasted product and can require repair or a scrapping of the product.

It has been found that stitch-forming reliability when starting to sew a pattern is greatly improved by manipulating the threads so that the looper picks up the loop of the top thread before the needle picks up the loop of the bottom thread. This can be achieved by redirecting the tail of the looper thread. More reliably, this can also be achieved by altering the timing of the stitching elements relative to each other, that is, the timing of the needles relative to the timing of the loopers, so that the first loop taken is the loop of the top thread, which is taken by the advancing looper. This, in turn, can be carried out by so manipulating the threads or timing the stitching elements so that the needle misses the bottom thread loop on the first descent of the needle. One way that this can be caused to happen is by insuring that the needle passes on the "wrong" side of the bottom thread on the first descent of the needle. The bottom thread is on the "wrong" side of the needle when the looper thread tail extends from the tip of the looper back along the looper side of the needle.

Before the start of sewing, after the needle **132** is moved to a new position relative to the material **12**, the needle **132** is above the material **12** with the top thread **222** extending through the eye of the needle **132** from the thread spool to the thread tail. In a normal stitch cycle, the needle **132** would start above the material, as shown in FIG. **5L**, with the looper **216** advanced as shown. The tail of the looper thread **224** is below the needle plate **38** and below the retainer **234**. In conventional start up, the looper **216** would retract as the needle **132** descended, probably, but not necessarily, passing between the bottom thread **224** and the looper **216**, as illustrated in FIG. **5M**, taking the bottom thread loop, as illustrated in FIG. **5N**. This results in the looper thread **224** wrapping the needle thread **222** close to the looper **216** below the retainer **234**, as illustrated in FIG. **5O**, resulting in a distorted triangle that increases the likelihood that the needle **132** will miss the loop on its next descent.

Each sewing head, including each needle head and each looper head, may be linked to a common rotary drive through an independently controllable clutch that can be operated by a machine controller to turn the heads on or off, thereby providing pattern flexibility. The heads may be configured in sewing-element pairs, each needle head being modular with a corresponding similarly modular looper head. While the heads of each pair can be individually turned on or off, they are typically turned on and off together, either simultaneously or at different phases in their cycles, as may be most desirable. Alternatively, only the needle heads may be provided with selective drive linkages, while the looper heads may be linked to the output of a needle drive motor so as to run continuously, since they do not penetrate the material and do not form stitches when the needles are not operating. The looper linkage may be direct and permanent, or may be adjustable,

switchable or capable of being phased in relation to the needle drive. For example, the looper drive may be coupled to the needle drive by providing a differential drive mechanism in the looper drive train. When direct drive is employed, the looper head drive may be linked to an input drive shaft through a gear box, rather than a clutch. Each of the looper heads may be further provided with an alignment disk on the looper drive shaft to allow precise phase setting of each looper head relative to the other looper heads or the needle drive when the looper head is installed in the machine. Further, each looper head housing may be provided with adjustments in two dimensions in a plane perpendicular to the needle to facilitate alignment of the looper head with a corresponding needle head upon looper head installation.

In order to reduce the likelihood of missed stitches, particularly at startup of a pattern following the cutting of the looper thread, a split-start control method is provided for avoiding missed stitches at startup. A split start method is one use of the feature that allows the needle and looper drives to be decoupled and moved separately. With the split start feature, the initial motion of the needle and looper proceed separately upon startup so as to render the pickup of the stitches predictable. This is achieved by insuring that the looper picks up the top-thread loop before the needle picks up the bottom thread loop triangle.

With the split start method, with the mechanism stopped so that the needle near its top dead center position in its cycle and the needles and loopers locked and in phase, the elements are then unlocked so the looper can be moved independently of the needle, for example, to be advanced in its cycle, for example, by 180 degrees. Then the needle can be advanced 180 degrees relative to the looper position to bring the needle in phase with the looper, insuring that the needle will miss the looper thread triangle or loop in the looper thread at the beginning of the initial cycle. Then the elements can be relocked in phase. Upon further advancing of the elements, the looper will thereupon pick up the needle thread loop before a looper thread loop is picked up by the needle, producing a predictable start to the stitch sequence.

According to one embodiment of the invention, the needle and looper drives are decoupled when at the starting position of FIG. 5P, which is similar to that of FIG. 5L, and the needle is held in its top dead center position. The looper drive is then advanced one-half cycle, to move the looper 216 to the position illustrated in FIG. 5Q, thereby retracting the looper 216 out of the path of the needle 132. Then the looper drive is held in its half cycle position while the needle drive is activated to lower the needle 132 to its half cycle position, which leaves the needle 132 clear of the bottom thread 224, as illustrated in FIG. 5R. Then the needle and looper drives are again coupled together and advanced together in synchronization, whereupon the looper 216 begins to take up the needle loop in approximately the three-quarter position of the stitch cycle, as illustrated in FIG. 5S, and proceeds from there to the full cycle position as illustrated in FIG. 5T. Then the elements continue to move through the next cycle, where the formation of stitches can be seen, as illustrated in FIGS. 5U through 5X. Approximately by the position in FIG. 5X, the looper thread tail will have pulled itself from the clamping action of the thread trimmer.

The splitting of the needle and looper drive upon startup, as described, avoids the missing of stitches upon startup. The splitting of the needle and looper drive cycles has other uses, such as in facilitating thread trimming.

As an alternative to the use of the split start method described above, the likelihood of missed stitches at startup can be reduced by redirecting or guiding the thread tail of the

looper thread so as to prevent the bottom thread loop from being picked up by the needle before the top-thread loop is picked up by the looper. Such redirection may be achieved by a shifting or other positioning of the thread trimmer and clamp 850 (FIG. 5J) to move the tail of the looper thread 224 away from the needle side of the looper 216. The use of a thread-pusher mechanism or other looper thread redirecting technique can be used to cause the looper to pick up the top-thread loop before the needle picks up the bottom thread loop.

Another phenomenon that increases the probability for missed stitches on startup is the fact that the spreader or retainer 234 is not able to form the triangle with the looper thread 224 until the looper thread 224 is drawn toward the needle plate 34 and the material 12. The looper thread 234 being clamped by the thread trimmer 850 is held out of reach of the retainer 234. Before sewing starts, it is possible that considerable looper thread slack develops in the looper thread tail between the looper 216 and the clamp position at the thread trimmer 850. Such slack can form a large loop that swings to the opposite side of the looper from the needle, reducing the likelihood of a stitch being picked up in any given cycle, even after the first descent of the needle, thereby delaying unpredictably the start of a stitch chain. Such delay can result in an unacceptably long gap in the sewn pattern, requiring repair or scrapping of a panel. The likelihood of such problems resulting from this looper thread slack can be reduced by confining the looper thread. This confinement can be achieved by providing a looper thread deflector 430 below the needle plate 38, as illustrated in FIG. 5Y. Structure such as a thread deflector 430 can be placed to control the direction of the tail of looper thread 224 leaving the looper 216 upon start-up and to affect the spacing the looper thread tail and the looper in such a way that the needle 132 does not miss the looper thread loop after the looper has taken the needle thread loop. Such structure as the looper thread deflector 430 improve the reliability of stitch formation whether or not split start techniques are employed. In some cases, the improved reliability is enough to allow the split start feature to be omitted.

The looper thread deflector 430 illustrated in FIG. 5Y is in the shape of a wedge and is secured to the bottom of the needle plate 38. The wedge of the deflector 430 has a tapered surface 431 that is positioned close to the path of the tip of the looper 216 when the looper advances to its forward position near the zero degree or needle up position as illustrated in FIG. 5P. In this position, upon starting a pattern, the looper thread tail is clamped at the thread cut off 850 at the opposite side of the needle path. The surface 431 of the deflector 430 is positioned relative to the path of the looper to guide the looper thread tail away from the needle plate enough so that, once the looper has picked up the needle thread loop, the looper thread 224 is highly likely to be on the needle side of the looper 216 so that the descending needle 132 picks up a looper thread loop on its next descent. The looper thread deflector 430 contributes to reducing the missed stitches on startup when the split start method described above is not used or not available.

FIG. 5Y also illustrates a conventional needle guard 460, mounted to the base portion 805 of the looper 216, as better illustrated in FIG. 4D. This needle guard can be adjusted by pivoting it on the looper 216, where it can be locked in position by a set screw (not shown) in hole 461 in FIG. 4D. This needle guard 460 keeps the descending needle 132 from deflecting to the right of the advancing looper 216, keeping it to the left of the looper, as illustrated in FIGS. 5R and 5S, so that the looper 216 picks up the loop and does not skip the stitch.

An improved alternative embodiment is illustrated in FIG. 4G, in which a double needle guard assembly 470 is provided. The assembly 470 includes a first needle guard 471 and a second needle guard 472. The first needle guard 471 performs a function similar to that of needle guard 460, and is also pivotally adjustably mounted to the base 805 of the looper 216. The second needle guard 472 is a rod of circular cross-section, and is rotatably adjustably mounted in a hole in a mounting block 473 rigidly fixed to the looper side of the needle plate 38. In the embodiment of FIG. 4G, the thread deflector 430 is also mounted to the mounting block 473. The needle guard 472 keeps the descending needle 132 from deflecting further to the left of the advancing looper 216 so that the looper 216 does not pass to the right of the needle thread 222 and thereby miss the top thread loop and thus skip the stitch, but rather passes between the needle thread 222 and the needle 132 (FIG. 5S). The circular cross-section of the second needle guard 472 is centered on an axis 474 that is parallel to the plane of the looper motion and of the needle plate, that is, in horizontal, transverse orientation in the described machines. The needle guard 472 has an eccentric base 475 having an axis 476 that is spaced from, but parallel to, the axis 474 and that mounts in a hole in the block 473. As such, the needle guard 472 is rotatably adjustable in its mounting hole in block 473 so as to move it and its axis 474 toward or away from the needle 132, where it can be locked in position by tightening of an alien head screw 477 on the block 473.

The technique used in sewing tack-stitch sequences is also improved to reduce the likelihood of missed stitches, particularly during the start-up tack-stitch sequence. Preferably, a start-up tack stitch sequence is started by sewing a short distance of approximately one inch in the direction of the intended pattern, then sewing back over the initial stitches to the starting position before proceeding forward over the same line of stitches. At the beginning, a few long stitches are sewn, followed by normal length stitches. A typical normal stitch rate might be seven stitches per inch. To start the tack sequence, the thread would first be set at the origin of the pattern curve, which can be by using the wipe and tuck cycle described above. Then two triple-length stitches may be sewn, followed by a single normal length stitch in a direction away from the origin along the pattern curve line. Then seven normal-length stitches may be sewn back to the origin. Then the sewing direction can reverse again and sew over the initial stitches along the pattern curve.

In the normal sewing of a pattern, the feed of the bridges or the material or the combination thereof preferably results in a continuous feed motion of the stitching elements relative to the material. In the tack sequence, however, and particularly in those portions of the tack sequences where longer than normal stitches are used, the resultant feed is intermittent. The intermittent feed is preferably not abrupt, however, and is rather made by smooth transitions between rapid relative motion between the stitching elements and the material when the needle is clear of the material and relatively little or no such motion when the needle is engaged with the material. During the sewing of normal length stitches, whether before or after the sewing of the long stitches, the feed is preferably continuous and smooth.

Generally, high speed sewing in the quilting of patterns is performed with continuous stitching, with a needle motion that is sinusoidal as a function of time or at least of the distance stitched. During the so-called intermittent feed referred to above, the needle motion may be considered non-sinusoidal as a function of distance, with the reciprocation of the needle being faster than sinusoidal when the needle pen-

etrates the material and slower when the needle is withdrawn from the material. The needle speed transition may be smooth. This type of needle speed variation is useful whenever a reversal is employed in the sewing of a pattern. Cases involving the starting of sewing with needles moving from a stopped condition relative to the material are cases where such needle drive motion is beneficial. Tack sewing is a common example of both situations, and where such needle speed variation is desirable.

For example, needle speed may be started from a stop and run at a continuous cycle speed with motion that is sinusoidal as a function of time, but with feed of the material and needle relative to each other being faster when the needle is withdrawn from the material and slower when the needle is penetrating the material, presenting needle motion as a non-sinusoidal motion relative to the distance moved relative to the material. With such motion, a few larger than average stitches may be sewn, then the material feed between needle penetrations of the material can be gradually reduced to normal stitch spacing at which continuous stitching can continue. Then, in performing a tack, the needle direction relative to the material is reversed, and a similar sequence of a few longer than normal stitches, with the non-sinusoidal needle motion, are carried out followed by a transition to normal size stitches. A similar scheme can be employed whenever direction reversal occurs, not just at the beginning and ending of a pattern. This reduces malformed stitches, missed stitches and thread breakage. The movement of the needle relative to the material can be carried out (1) by moving the bridges relative to the frame of the machine while holding the material stationary, (2) by holding the bridges stationary relative to the machine while moving the material, or (3) by a combination of relative movements of both the bridges and material relative to the frame of the machine.

The movement referred to above can be carried out in such a way that takes into account the inertia of machine components and the material as well as material deformation and other effects of acceleration, deceleration, needle deflection and other factors to optimize or minimize these effects. For example, in normal sewing within the body of a pattern, the needles might reciprocate sinusoidally through the series of stitch cycles with the relative movement between the material and the needles, that is movement parallel to the plane of the material, being continuous, or at a constant speed. In this example, the needles might reciprocate at 1400 cycles per minute with the needle movement relative to the material being 200 inches per minute. Then, when a tack sequence is to be sewn, this parallel movement as well as the speed of the reciprocating needle motion can be proportionately slowed to, say, 100 inches per minute and 700 cycles per minute, respectively. Then, for a tack stitch, the reciprocating needle motion speed can be varied and moved non-sinusoidally by, for example, moving at a 2100 cycle per second rate for the portion of a cycle when the needle is penetrating the material and then slowing to a few hundred cycles per second or less between penetrations of the material to sew a normal length stitch or a longer-than-normal length stitch, as the controller may command, with minimal needle deflection and minimal material distortion. As such, the reciprocating needle motion is accelerated to a greater cycle speed when penetrating the material and decelerated to a slower cycle speed between stitch penetrations. Transition stitches can be sewn before or after the tack stitch to transition to or from a normal stitch. Such a sequence can be used for tack stitch sewing or whenever a direction reversal is sewn in a pattern.

The machine 10 has a motion system 20 that is diagrammatically illustrated in FIG. 6. Each of the bridges 21, 22 are

separately and independently movable vertically on the frame 11 through a bridge vertical motion mechanism 30 of the motion system 20. The bridge vertical motion mechanism 30 includes two elevator or lift assemblies 31, mounted on the frame 11, one on the right side and one on the left side of the frame 11 (see FIG. 1A). Each of the lift assemblies 31 includes two pairs of stationary vertical rails 40, one pair on each side of the frame 11, on each of which ride two vertically movable platforms 41, one for each of two of vertical bridge elevators, including a lower bridge elevator 33 and an upper bridge elevator 34. Each of the elevators 33, 34 includes two of the vertically movable platforms 41, one on each side of the frame 11, which is equipped with bearing blocks 42 that ride on the rails 40. The platforms 41 of each of the elevators 33, 34 are mounted on the rails 40 so as to support the opposite sides of the respective bridge to generally remain longitudinally level, that is, level front-to-back.

The upper bridge 22 is supported at its opposite left and right ends on respective right and left ones of the platforms 41 of the upper elevators 34, while the lower bridge 21 is supported at its opposite left and right ends on respective right and left platforms 41 of the lower elevators 33. While all of the elevator platforms 41 are mechanically capable of moving independently, the opposite platforms of each of the elevators 33,34 are controlled by the controller 19 to move up or down in unison. Further, the elevators 33,34 are each controlled by the controller 19 move the platforms 41 on the opposite sides each bridge 21,22 in synchronism to keep the bridges 21,22 transversely level, that is, from side-to-side.

Mounted on each side of the frame 11 and extending vertically, parallel to the vertical rails 40, is a linear servo motor stator 39. On each platform 41 of the lower and upper elevators 33, 34 is fixed the armature of a linear servo motor 35,36, respectively. The controller 19 controls the lower servos 35 to move the lower bridge 21 up and down on the stators 39 while maintaining the opposite ends of the bridge 21 level, and controls the upper servos 36 to move the upper bridge 22 up and down on the same stators 39, while maintaining the opposite ends of the bridge 22 level. The vertical motion mechanism 30 includes digital encoders or resolvers 50, one carried by each elevator, to precisely measure its position of the platform 41 on the rails 40 to feed back information to the controller 19 to assist in accurately positioning and leveling the bridges 21, 22. While linear motors such as the linear servos are preferable, alternative drives such as ball-screws and rotary servos, or other drive devices, may be employed. The encoders 50 are preferably absolute encoders that output actual position signals.

The motion system 20 includes a transverse-horizontal motion mechanism 85 for each of the bridges 21, 22. Each of the bridges 21, 22 has a pair of tongues 49 rigidly extending from its opposite ends on the right and left sides thereof, which support the bridges 21, 22 on the platforms 41 of the elevators 33, 34. The tongues 49 are moved transversely on the elevator platforms 41 in the operation of the transverse-horizontal bridge motion mechanism 85. The tongues 49 on each of the bridges 21,22 carry transversely extending guide structure 44 in the form of rails that ride in bearings 43 on the platforms 41 of the respective elevators 33,34 (FIG. 6A). Fixed to the tongue 49 on one side of each of the bridges 21, 22, extending parallel to the rails or guide structure 44, is a linear servo stator bar 60. Fixed to one of the platforms 41 of each respective bridge 21, 22 is an armature of a linear servo 45,46 positioned to cooperate with and transversely move the stator bar 60 in response to signals from the controller 19. The transverse-horizontal motion mechanism includes decoders 63 for each of the bridges 21, 22 that are provided adjacent the

armatures of servos 45,46 on the respective elevators 41 to feed back transverse bridge position information to the controller 19 to aid in precise control of the transverse bridge position. The bridges 21, 22 are independently controllable to move vertically, up and down, and transversely, left and right, and operated in a coordinated manner to stitch a quilted pattern on the material 12. In the embodiment illustrated, each bridge can move transversely 18 inches (+/-9 inches from its center position), and each bridge can move up or down 36 inches (+/-18 inches from its center position. The range of vertical motion of the lower and upper bridges 21, 22 can overlap.

The drive rollers 18 at the top of the frame 11, which are also part of the overall motion system 20, are driven by a feed servo motor 64 at the top of the frame 11, as illustrated in FIG. 6, on the right side (facing downstream) of the frame 11. When activated, the servo 64 drives the rollers 18 to feed the web of material 12 downstream, pulling it upward along the plane 16 through the quilting station and between the members 23 and 24 of both of the bridges 21 and 22. The rollers 18 further drive a timing belt 65 located in the frame 11 at the left side of the machine 10, as illustrated in FIG. 6A. The bridges 21, 22 may also each be provided with a pair of pinch rollers 66, in place of idler roller 15, that are journaled to the respective elevator platforms 41 on which the respective bridges 21,22 are supported. These rollers 66 grip the material 12 at the levels of the bridges 21, 22 to minimize the transverse shifting of the material at the level of the sewing heads 25, 26. The pinch rollers 66 are synchronized by the belt 65 so that the tangential motion of their surfaces at the nips of the pairs of roller 66 move with the material 12.

Omitting the roller 66 in favor of only the idler roller 15 has also been found to be an acceptable alternative. This alternative may be desirable to avoid material bunching during certain material and bridge motion sequences.

As illustrated in FIG. 6A, with the elevator platforms 41 supporting the bridges 21,22 stationary, activation of the motor 64 drives the rollers 18 to advance the web 12 downstream and upward between the pinch rollers 66 of the bridges 21,22. The rollers 18, in turn, turn a belt drive cog wheel 600 on the left side of the frame 11 which drives the belt 65. The rollers 66 on both of the bridges 21,22 are driven by the motion of the belt 65 so that they have the same tangential velocity, when the bridges 21,22 are vertically fixed, to roll with the material 12 as the material 12 is moved up by the motion of the rollers 18. On the other hand, when the feed rolls 18 and material 12 are stationary, the belt 65 remains stationary, as illustrated in FIG. 6B. With the belt 65 stationary, movement up or down of either bridge 21, 22 forces the rollers 66 to move relative to the web 12 and also relative to the belt 65. The movement of the rollers 66 relative to the belt 65 causes the rollers 66 to rotate at a rate that keeps the roller surfaces at the nip between them stationary at the web 12 so that the rollers 66 roll along the surface of the stationary web of material 12. Furthermore, combinations of motion of the web 12 and of a bridge 21,22 are accompanied with combined motion being imparted to the rollers 66 that effectively subtracts the upward motion of a bridge 21,22 from the upward motion of the web 12, so that the surfaces of the rollers 66 at the nips of the sets of rollers 66 always move with the material 12. This synchronized motion between the web 12 and the pinch rollers 66 of each of the bridges 21, 22 maintains longitudinal tension on the material 12 and clamps the material 12 at each of the bridges 21, 22, resisting transverse material distortion of the web 12.

The structure that enables the belt 65 to synchronize the motion of the pinch rollers 66 with the motions of the bridges

21,22 and the web 12 is illustrated also in FIGS. 6C and 6D as well as FIGS. 6A and 6B as explained above. The belt 65 extends around the cog drive roller 600, which is driven through a gear assembly 601 by the feed rollers 18 (FIG. 6D). The belt 65 further extends around four idler pulleys 602-605 rotatably mounted to the stationary frame 11. The belt 65 also extends around a driven pulley 606 and an idler pulley 607, both rotatably mounted to the elevator platform 41 for the lower bridge 21, and around idler pulley 608 and driven pulley 609, both rotatably mounted to the elevator platform 41 for the upper bridge 22, all on the left side of the frame 11. The driven pulley 606 is driven by the motion of the belt 65 and, in turn, through a gear mechanism 610 (FIG. 6D), drives the pinch rollers 66 of the lower bridge 21, while driven pulley 609, is also driven by the motion of belt 65 and, through gear mechanism 611, drives the pinch rollers 66 of the upper bridge 22. The gear mechanisms 610 and 611 have drive ratios related to that of drive gear mechanism 601 such that the tangential velocity of the rollers 66 and rollers 18 is zero relative to that of the web 12. It should be noted that the path of the belt 65 remains the same regardless of the positions of the bridges 21 and 22.

Additionally, inlet rollers 15 are shown at the bottom of FIG. 6D and in FIGS. 6E and 6F as a pair of rollers similar to rollers 18. If such rollers 15 are so provided and are to be driven, which might be desirable or undesirable, depending on the feed system for the web 12 upstream of the machine 10, such rollers 15 should be also driven by the belt 65, as through a gear mechanism 612 driven by the roller 605 that is driven by the belt 65. In such a case, the rollers 15 should be maintained at the same tangential velocity as the feed rollers 18 through properly matched gear ratios between mechanisms 601 and 612. It might, however, be preferred to allow the rollers 15 to rotate freely as idler rollers, and to provide only a single roller 15 above and on the upstream side of the material 12, around which the material 12 would extend. Each of the gear mechanisms 601, 610 and 611 may be substantially as illustrated and described for gear mechanism 612.

The vertical motion of the bridges 21, 22 is coordinated with the downstream motion of the web of material 12 by the controller 19. The motion is coordinated in such a way that the bridges 21, 22 can efficiently remain within their 36 inch vertical range of travel. Further, the two bridges 21, 22 can be moving so as to stitch different patterns or different portions of a pattern. As such, their separate motions are also coordinated so that both bridges 21, 22 remain in their respective ranges of travel, which may require that they operate at different stitch speeds. This may be achieved by the controller 19 controlling one bridge independently while the motion of the other bridge is dependent on or slaved to that of the other bridge, though other combinations of motion may be better suited to various patterns and circumstances.

The stitching of patterns by the sewing heads 25,26 on the bridges 21, 22 is carried out by a combination of vertical and transverse motions of the bridges 21, 22 and thus, the sewing heads 25, 26 that are on the bridges, relative to the material 12. The controller 19 coordinates these motions in most cases so as to maintain a constant stitch size, for example, seven stitches to the inch, which is typical. Such coordination often requires a varying of the speed of motion of the bridges or the web or both or a varying of the speed of sewing heads 25, 26.

The speed of the needle heads 25 is controlled by the controller 19 controlling the operation of two needle drive servos 67 that respectively drive the common needle drive shafts 32 on each of the bridges 21, 22. Similarly, the speed of the looper heads 26 is controlled by the controller 19 controlling the operation of two looper drive servos 69, one on each

bridge 21, 22, that drive the common looper belt drive systems 37 on each of the bridges 21,22. The sewing heads 25, 26 on different bridges 21, 22 can be driven at different rates by different operation of the two servos 67 and the two servos 69. The needle heads 25 and looper heads 26 on the same bridges 21, 22, however, are run at the same speed and in synchronism to cooperate in the formation of stitches, although these may be phased slightly with respect to each other for proper loop take-up, needle deflection compensation, or other purposes.

Further, the horizontal motion of the bridges is controlled in some circumstances such that they move in opposite directions, thereby tending to cancel the transverse distortion of the material 12 by the sewing operations being performed by either of the bridges 21, 22. For example, when the two bridges 21, 22 are sewing the same patterns, they can be controlled to circle in opposite directions. Different patterns can also be controlled such that transverse forces exerted on the web 12 cancel as much as practical.

Embodiments above are provided with separate drive servos for the needle head assemblies 25 and the looper head assemblies 26 for each bridge 21, 22. In particular, each bridge 21, 22 includes a needle drive servo 67, separately controllable by a signal from the controller 19, which drives a shaft 32, which, in turn, drives all of the needle head assemblies 25 on the respective bridge, with each needle head assembly 25 being selectively engageable through a clutch 100, also operated by signals from the controller 19. Also, each bridge 21, 22 further includes a looper drive servo 69, also separately controllable by a signal from the controller 19, which drives a belt 37, which, in turn, drives all of the looper head assemblies 26 on the respective bridge, with each looper head assembly 26 being selectively engageable through a similar clutch 210, also operated by signals from the controller 19. The separate drives 67 and 69 facilitate the split-start feature, described above, as well as needle deflection compensation, plus is useful for other control refinements.

A number of alternatives to the bridge design, the needle head assemblies, and the needle and looper drives and the control thereof are also illustrated in and described. In FIG. 6H, an end portion or tongue 49 of a bridge 21 or 22 is illustrated in which the needle drive motor 67 is linked to drive both the needle head assemblies 25 and looper head assemblies 26 of the same bridge. The servo 67 directly drives the output shaft 32, which is the needle drive input shaft for that bridge. The shaft 32, in turn, drives a cog belt 32a that drives a looper drive input shaft 37a, which takes the place of the looper drive belt 37 in previously described embodiments. With this embodiment, needles 132 and loopers 216 are driven together, and are not separately controlled or phased. Because the stitching elements are mechanically linked, power failures and other malfunctions are less likely to result in mechanical damage to the machine. Nonetheless, the ability to separately control needle and looper heads can be reinstated by retaining the looper drive servo 69 while linking its output to the shaft 37a through a differential drive 69a, which can be added between the belt drive 32a and the looper drive shaft 37a.

The looper drive shaft 37a is linked through a belt 37b to a segmented shaft 37c that is formed of an alternating series of torque tubes 37d and gear boxes 210a. The gear boxes 210a take the place of the looper drive clutches 210, but drive the looper and retainer drives 212 of the looper head assemblies 26 continuously rather than allowing each to be driven selectively as with the embodiments described above. Activation and deactivation of the needle alone determines whether the set of stitching elements participates in the sewing of the pattern. Since the loopers 216 do not penetrate the material

being sewn, they can be run continuously whether the corresponding needle drive assemblies **25** are being driven or not, although clutches **210** could be provided instead of gear boxes **210a**.

The looper head assemblies **26** of this embodiment, illustrated as assemblies **26a** in FIG. 2C, include a looper and retainer drive **212** essentially as described above. They also each include the needle plate **38**, illustrated as a rectangular plate **38a**, which is fixed relative to the looper drive housing **238**, which contains the needle hole **81**. Each gear box **210a** has an output shaft that is locked to the input shaft of the looper and retainer drive **212** by a collar **440** such that these shafts are adjustable only axially with respect to each other. Each gear box **210a** is supported by two hearings **441**, one on each side of the gear box **210a**, that surround the shaft **37c**, which is the input drive shaft of the gear boxes **210a**. The bearings **441** are each locked in a clamp member **442** that is bolted to the bridge. As such, the gear boxes **210a** are adjustable only axially relative to the shaft **37c**.

When a looper head assembly **26a** is installed on the rear portion **24** of a bridge **21,22**, four adjustments can be made. Two horizontal adjustments are available to adjust the assembly **26a** on the bridge. Before tightening the clamp members **442**, the gear box **210a** can be positioned transversely on the shaft **37c** to align the needle hole **81** transversely with needle **132**. Then the collar **440** can be loosened and the assembly **26a** moved toward or away from the needle drive assembly **25** to adjust the needle plate **38a** relative to the fabric plane **16**. Angular adjustment of the looper and retainer drive **212** is made by aligning a disc (not shown) on the input shaft of the drive **212** inside the housing **238** with an alignment hole **444** in the housing **238**. This is done by inserting a cylindrical pin (not shown) through the hole **444** and rotating the shaft of the drive **212** until the pin fits into the hole in the alignment disc. When the adjustments are made, the collar **440** is tightened. Vertical adjustment of the looper **216** is made by the looper adjustment described above in connection with FIG. 4E.

A needle head assembly **25** that produces a simple sinusoidal needle motion is illustrated, as the needle head assembly embodiment **25a** also in FIG. 2C. Each needle head assembly **25a** includes a clutch **100** that selectively transmits power from the needle drive shaft **32** to a needle drive **102a** and presser foot drive **104a**. The needle drive **102a**, the presser foot drive **104a** and the clutch **100** as well as the shaft **32**, are supported on a needle drive housing **418**. The needle drive **102a** includes the crank **106** that is driven through a drive belt **164** by the output pulley **166** of the clutch **100**. The crank **106** is mechanically coupled to the needle holder **108** by a direct needle drive link **110a**. The arm or eccentric **112** of crank **106** is rotatably connected to one end of the link **110a**. The other end of the link **110a** is rotatably connected to pin **123** extending from block **122** of the reciprocating shaft **124**, which is an extension of the needle holder **108**. The shaft **124** is mounted for reciprocating linear motion as in the assembly **25** described in connection with FIG. 2 above. The presser foot drive **104a** is generally similar to the presser foot drive **104** described in connection with FIG. 2A above. The components of the needle head assemblies **25a** are made of materials that allow the heads to be operated without requiring lubrication.

The housing **418** is a structural member having three mounting flanges **451**, **452** and **453** that support the assembly **25a** and its related components on the front portion **23** of the bridge **21,22**. The front portions **23** of the bridges **21, 22** of the embodiment **23a** illustrated in FIG. 6I, use the housings **418** of the head assemblies **25a** to stiffen the bridge portion, which is formed of an open trough **455**. The flanges **451** are bolted to

the vertical face of the trough **455**, while the flanges **452** and **453** are bolted to transversely extending channels along the base of the trough **455**, thereby adding stiffening structure that reinforces the trough **455** so as to resist the main stresses and dynamic loads encountered during sewing. The drive shaft **32**, which is formed of sections of torque tubes **32a** and solid shaft sections **32b** (FIG. 2C), is also in part supported by the housings **218** through the clutches **100** that are mounted to the housings **218**, thereby confining some of the drive forces to these housings **218**. This arrangement makes it practical to eliminate additional structural features such as the ribs **89** (FIG. 1).

In a typical configuration, the quilter **10** quilts a web **12** that may be fed downstream to a panel cutter and trimmer, or that may be rolled and transferred to an off-line cutting and trimming device. Motion of the web **12** and the bridges **21, 22** can also be coordinated with panel cutting operations performed by a panel cutting assembly **71** located at the top of the frame **11**. The panel cutter **71** has a cut-off head **72** that traverses the web **12** just downstream of the drive rollers **18**, and a pair of trimming or slitting heads **73** on opposite sides of the frame **11**, immediately downstream of the cut-off head **72**, to trim selvage from the sides of the web **12**.

The cut-off head **72** is mounted on a rail **74** to travel transversely across the frame **11** from a rest position at the left side of the frame **11**. The head is driven across the rail **74** by an AC motor **75** that is fixed to the frame **11** with an output linked to the head **72** by a cog belt **76**. The cut-off head **72** includes a pair of cutter wheels **77** that roll along opposite sides of the material **12** with the material **12** between them so as to transversely cut quilted panels from the leading edge of the web **12**. The wheels **77** are geared to the head **72** such that the speed of the cutting edges of the wheels **77** are proportional to the speed of the head **72** across the rail **74**.

The controller **19** synchronizes the operation of the cut-off head **72**, activating the motor **75** when the edge of a panel is correctly positioned at a cut-off position defined by the path of the travel of the cutting wheels **77**. The controller **19** stops the motion of the material **12** at this position as the cut-off action is carried out. During the cut-off operation, the controller **19** may stop the sewing performed by the sewing heads **25,26**, or may continue the sewing by moving the bridges **21,22** to impart any longitudinal motion of the sewing heads **25,26** relative to the material **12** when the material **12** is stopped for cutting.

The trimming or slitting by the slitting heads **73** takes place as the web of material **12** or panels cut therefrom are moved downstream from the cutting head **72**. The slitting heads **73** each have a set of opposed feed belts **78** thereon that are driven in coordination with a pair of slitting wheels **79**. The structure and operation of these slitting heads **73** are explained in detail in U.S. Pat. No. 6,736,078, filed Mar. 1, 2002, by Kaetterhenry et al. and entitled "Soft Goods Slitter and Feed System for Quilting", hereby expressly incorporated by reference herein.

The feed belts **78** and wheels **79** are geared to operate together and driven by the drive system of feed rollers **18** as the web **12** is advanced through the slitters **73**. The belts **78** are operated separate from the feed rolls **18** after a panel has been cut from the web by the cutting head **72** to clear the panels from the belts **78**. The slitting heads **73** are transversely adjustable on a transversely extending track **80** across the width of the frame **11** so as to accommodate webs **12** of differing widths, as explained in U.S. Pat. No. 6,736,078. The adjustment is made under the control of the controller **19** after a panel has been severed and cleared from the trimming belts **78**. The slitting heads **73** and the adjustment of their trans-

verse position on the frame **11** to coincide with the edges of the material **12** are carried out under the control of controller **19** in a manner set forth in U.S. Pat. No. 6,736,078 and as explained herein.

With the structure described above, the controller **19** moves the web in the forward direction, moves the upper bridge up, down, right and left, moves the lower bridge up, down, right and left, switches individual needle and looper drives selectively on and off, and controls the speed of the needle and looper drive pairs, all in various combinations and sequences of combinations, to provide an extended variety of patterns and highly efficient operation. For example, simple lines are sewn faster and in a variety of combinations. Continuous 180 degree patterns (those that can be sewn with side to side and forward motion only) and 360 degree patterns (those that require sewing in reverse) are sewn in greater varieties and with greater speed than with previous quilters. Discrete patterns that require completion of one pattern component, sewing of tack stitches, cutting the threads and jumping to the beginning of a new pattern component can be sewn in greater varieties and with greater efficiency. Different patterns can be linked. Different patterns can be sewn simultaneously. Patterns can be sewn with the material moving or stationary. Sewing can proceed in synchronization with panel cutting. Panels can be sewn at variable needle speeds and with different parts of the pattern sewn simultaneously at different speeds. Needle settings, spacings and positions can be changed automatically.

For example, simple straight lines can be sewn parallel to the length of the web **12** by fixing the bridges in selected positions and then only advancing the web **12** through the machine by operation of the drive rollers **18**. The sewing heads **25**, **26** are driven so as to form stitches at a rate synchronized to the speed of the web to maintain a desired stitch density.

Continuous straight lines can be sewn transverse the web **12** by fixing the web **12** and moving a bridge horizontally while similarly operating the sewing heads. Multiple sewing heads can be operated simultaneously on the moving bridge to sew the same transverse line in segments so that the motion of the bridge need only equal the horizontal spacing between the needles. As a result, the transverse lines are sewn faster.

Continuous patterns are those that are formed by repeating the same pattern shape repeatedly as the machine sews. Continuous patterns that can be produced by only unidirectional motion of the web relative to the sewing heads, coupled with transverse motion, can be referred to as standard continuous patterns. These are sometimes referred to as 180 degree patterns. They are sewn on the machine **10** by fixing the vertical positions of the bridges and advancing the feed rolls **18** to move the web **12**, moving the bridges **21**, **22** horizontally only. On the machine **10**, the web **12** does not move transversely relative to the frame **1**.

FIG. 7A is an example of a standard continuous pattern. With a traditional multi-needle sewing machine in which all of the needles sew the same patterns simultaneously, the illustrated pattern **900** can be sewn provided that there are two rows of needles spaced by the distance **D**. The distance **D** is a fixed parameter of the machine and cannot be varied from pattern to pattern. This is because the needle row spacing is fixed and all of the needles must move together. With the machine **10**, described above, the distance **D** can be any value, because alternate stitches can be sewn with needles on one bridge while the other stitches are sewn with needles on the other bridge. The two bridges can be moved in any relationship to each other. Furthermore, if the two bridges are spaced at a vertical distance of **2D**, with a needle of each bridge

starting at points **901** and **902**, for example, they can move in the opposite transverse directions as the web feeds upward, thereby sewing the alternate rows **903** and **904** as mirror images of the same pattern. In this way, the transverse forces exerted on the material by bridge motion will cancel, thereby minimizing material distortion.

Continuous patterns that require bidirectional web motion relative to the sewing heads are referred to herein as 360 degree patterns. These 360 degree patterns can be sewn in various ways. The web **12** can be held stationary with a pattern repeat length sewn entirely with bridge motion, then the web **12** can be advanced one repeat length, stopped, and the next repeat length can then also be sewn with only bridge motion. A more efficient and higher throughput method of sewing such 360 degree continuous patterns involves advancing the web **12** to impart the required vertical component of web versus head motion of the pattern, with the bridges sewing only by horizontal motion relative to the web **12** and the frame **11**. When a point in the pattern is reached where reverse vertical sewing direction is required, the web **12** is stopped by stopping feed rolls **18** and the bridge or bridges doing the sewing are moved upward. When the vertical direction must be reversed again, the bridge moves downward with the web remaining stationary until the bridge reaches the initial position from which its vertical motion started and the web's motion stopped. Then web motion takes over to impart the vertical component of the pattern until the pattern needs to be reversed again. This combination of bridge and web vertical motion prevents the bridge from walking out of range.

An example of a 360 degree continuous pattern **910** is illustrated in FIG. 7B. The sewing of this pattern starts, for example, at point **911** and vertical line **912** is sewn only with upward vertical web motion. Then, at point **913**, the web stops and the horizontal line **914** is sewn with transverse bridge motion only to point **915**, then with upward bridge motion only to sew line **916**, then transverse bridge motion only to sew line **917**, then with downward vertical bridge motion only to sew line **918**, then transverse bridge motion only to sew line **919**, then downward vertical bridge motion only to sew line **920**. Then line **921** is sewn with transverse bridge motion only, then line **922** is sewn with upward bridge motion only, then line **923** is sewn with transverse bridge motion only to point **924**. At this point and along the line **923**, the bridge is at the farthest distance below its initial position than at any point in the pattern. Then, the bridge moves downward to sew line **925** as far as point **926**, which is adjacent point **915** where the vertical bridge motion started, at which point **926**, the bridge is back to its initial vertical position, whereupon its vertical motion stops and the web moves upward to sew the line further to point **927**. Then transverse bridge motion only sews line **928** to point **929**, which is back to the beginning point of the pattern.

Discontinuous patterns that are formed of discrete pattern components, which are referred to by the trademark as TACK & JUMP patterns by applicant's assignee, are sewn in the same manner as the continuous patterns, with tack stitches made at the beginning and end of each pattern component, thread trimming after the completion of each pattern component and the advancing of the material relative to the needles to the beginning of the next pattern. 180 degree and 360 degree patterns are processed as are continuous patterns. An example of such a 360 degree pattern **930** is illustrated in FIG. 7C. One simple way to sew these patterns is to sew the patterns with bridge motion, tack the patterns and cut the threads, then jump to the next repeat with web motion only. However, adding web motion as in FIG. 7B to the pattern sewing portion can increase throughput.

Different patterns can be linked together according to the concept described in U.S. Pat. No. 6,026,756. FIG. 7D is an example of linked patterns that can be sewn on the machine **10** without vertical motion of a bridge, with the two bridges sharing the sewing of the clover-leaf patterns **941** by sewing the opposite sides as mirror images. Alternatively, one bridge can sew the patterns **941** as 360 degree discontinuous patterns while the other bridge sews the straight line patterns.

FIG. 7E illustrates a continuous 360 degree pattern **950** sewn with one bridge sewing alternative patterns **951** with the other bridge sewing a mirror image **952** of the same pattern. This pattern **950** is sewn using similar web and bridge vertical motion logic as pattern **910** of FIG. 7B. In determining the apportionment of vertical motion between the bridges and the web, the controller **19** analyzes the pattern before sewing begins. In such a determination, at the start of each pattern repeat, the transverse position at the end of the repeat must be the same as it was when the pattern started and the vertical web position must be the same or further downstream (up). The pattern **950** may be sewn with the lower bridge first sewing tack stitches at points **953** and sewing patterns **951**. The sewing will use bridge horizontal motion and only web vertical motion until points **954** are reached. Then, the web stops and the bridge sews vertically, down then up, to point **955**, at which the bridge is at the same longitudinal position on the web and the same vertical position as it was at point **954**. Then the web feed takes over for the sole vertical motion and the sequence is repeated for the second half of the pattern **956**.

When point **957** is reached, the second bridge begins patterns **952** with a tack stitch at point **953**, which it sews in the same manner as the first bridge sewed pattern **951**, except with the horizontal or transverse direction being reversed. The sewing continues with the bridges and web moving vertically the same and simultaneously for both patterns **951** and **952**, with transverse motion of one bridge being equal and opposite to the transverse motion of the other bridge. The sewing continues until the lower bridge reaches point **958**, where tack stitches are sewn and the threads are cut. After one more pattern repeat, the second bridge comes to the same point, and it sews tack stitches and its threads are cut.

Two different patterns can be sewn simultaneously by moving one bridge to form one pattern and the other bridge to form another pattern. The operation of both bridges and the sewing heads thereon are controlled in relation to a common virtual axis. This virtual axis can be increased in speed until one bridge reaches its maximum speed, with the other bridge being operated at a lower speed at a ratio determined by the pattern requirements. Pattern **960** of FIG. 7F illustrates this. With one bridge sewing the vertical lines of pattern **961** and the other bridge simultaneously sewing the zig-zag lines of pattern **962**, the stitching rates of the two bridges must be different. Since the stitched series for pattern **962** is longer than that for pattern **961**, pattern **962** is driven at a one-to-one ratio to a virtual axis or reference which is set at the maximum stitching speed. If the lines of pattern **962** are at a 45 degree angle, for example, the stitch rate for pattern **961** will be set at 0.707 times the rate of that of pattern **962**.

Patterns can be sewn by combinations of vertical and horizontal motion of the bridges while the material is being advanced, thereby making possible the optimizing of the process. FIG. 7G, for example, shows a pattern **970** made up of a straight line border pattern **971** in combination with diamond patterns **972** and circle patterns **973**. If the overall panel is larger than the 36 inch vertical bridge travel, for example if dimension L is 70 inches, stitching can proceed as follows: the diamonds and circles of the upper half **974** of the

panel are sewn first, with one bridge sewing the diamonds and the other sewing the circles, or some other combination, using 360 degree logic, with the web stationary. Then the border pattern **971** is sewn with the web moving 35 inches upward during the process, sewing vertical and horizontal lines as described above. Then the diamonds and circles of the bottom half **975** of the panel being sewn. Alternatively, the upper half of the panel can be sewn with the upper circle and diamond patterns being sewn by the top bridge and the lower circle and diamond (two rows) being sewn with the bottom bridge. Then after the border lines are sewn, the circle and diamond patterns of the lower panel half can be similarly apportioned between the bridges.

Where different patterns are to be sewn with different needle combinations from panel to panel, or where different portions of a panel are to be sewn with different needle combinations, the controller can switch the needles on or off. These features can be used to sew pattern combinations as described in U.S. Pat. No. 6,026,756, hereby expressly incorporated by reference herein. With the machine **10** described herein, a wider variety of patterns can be combined and efficiently sewn.

Embodiments of the present invention include new complex patterns. One class of complex patterns provided combines continuous patterns, as for example the zig-zag pattern **550** shown in FIG. 7H with a discontinuous pattern, such as, for example, the circle array pattern **552** shown in FIG. 7I. The pattern **552** can be a pattern known as a TACK AND JUMP pattern in which pattern components are sewn, then a tack stitch sequence is sewn and the top thread (at least) is cut, then a jump is implemented in which the stitching elements move to new starting points on the material where the quilting of new pattern components is begun. Such patterns **550** and **552** can be sewn to produce a combination pattern **554** as shown in FIG. 7J. In so sewing the pattern **554** on the machine **10**, the patterns **550** and **552** can be sewn simultaneously. The continuous pattern **550** can be sewn on a continuously advancing web with the heads of the lower bridge **21**, preferably in an alternating left and right transverse, while separate TACK AND JUMP circles of the pattern **552** are sewn with heads of the upper bridge **22** in coordination with the zig-zag pattern **550**. The bridge **21** can be kept in a fixed longitudinal position as the pattern **550** is sewn, with only the web moving, although the bridge **21** can be moved up and down on the machine frame as the continuous pattern **550** is sewn. The 360 degree circles of pattern **552** are sewn most conveniently sewn with both transverse and longitudinal movement of the bridge **22** to sew the circles on a moving web.

The continuous pattern **550** can be sewn with four heads of the lower bridge **21** running continuously as the web feeds downstream at a constant speed, while 360 degree circles of pattern **552** are being sewn with three heads of the upper bridge **22** sewing intermittently, tacking and cutting threads at the end of each circle pattern. Alternatively, the circles can be sewn using six heads of the upper bridge **22**, three simultaneously sewing one row of three circles alternating with three other heads sewing simultaneously an alternating row of circle patterns. Using six heads requires less transverse bridge motion and allows the circles to be more widely spaced.

Another continuous pattern **556**, illustrated in FIG. 7K, can be combined with the continuous pattern **550** of FIG. H to produce a combination pattern **557** as illustrated in FIG. 7L. The combination pattern **557** that is made up of the two continuous patterns **550** and **556** can be quilted by sewing the pattern **550** with one bridge, for example bridge **21**, and sewing the pattern **556** with the other bridge, bridge **22**. In so sewing, one or both bridges **21** and **22** can be kept in fixed

longitudinal positions while sewing the two continuous patterns **550** and **556** simultaneously on a continuously advancing web. Alternatively, one or both of the bridges **21**, **22** can be moving longitudinally during all or part of their sewing time while sewing. Transverse motion of the bridges **21**, **22** as well as the stitching speed of the heads on the two bridges can be varied relative to each other and in coordination with the longitudinal movement of the web or bridges, in a manner most efficient to acceptably produce the patterns **550** and **556** and the combination pattern **557**.

The combination patterns **554** and **557** can extend across a length of web **560** that is longer than one panel length, or that includes at least one quilted panel **561** and at least a portion **562** of another panel upstream of the panel **561** emerging from a quilting station, as illustrated in FIG. 7M. The web length **560** extends from the upper bridge **22** downstream to a panel cutoff or take-up roll. Such combination patterns can be sewn on a web at high speed and efficiently, providing a high product through-put. For example, as illustrated in FIG. 7N, pattern **554** extends without interruption along a length of a web of multi-layered material **560** from one panel length **555** to another, before the individual panel lengths **555** are eventually cut from the web to form individual mattress cover panels that are quilted with combination patterns **554**. The continuous pattern component **550** can be sewn continuously along the multi-panel lengths of the web without cutting the treads and without sewing tack stitch sequences, thus allowing high speed production. FIG. 7O illustrates pattern **557** along a length of a web of multi-layered material **560** extending substantially the lengths of each of a plurality of panel lengths **555**, but with the threads tacked between each of the panels. The pattern component **550** also can be sewn efficiently. FIG. 7P illustrates continuous pattern component **550** sewn along a multi-panel length web with the combined pattern changing from pattern **552** to pattern **556** between panels while the pattern **550** continues unchanged on a length of the web **560**. The intermediate quilted product webs **560** are most useful for the efficient production of quilted panels having combination patterns of which at least one is continuous.

With the quilting machine **10** described herein, other patterns can be sewn that have either not been possible or practical with machines of the prior art. For example, FIG. 9 shows a section **500** of the quilted web **12** on which two pattern sections **501** and **502** have been quilted. Both of these patterns are selected as continuous, unidirectional patterns for simplicity, but the principles discussed in connection with the sewing of these patterns can be combined with the principles discussed above in connection with many of the patterns of FIGS. 7A-7G to produce other, more complex patterns and combinations of patterns to provide advantages of additional features and sewing techniques. The patterns **501** and **502** on the web section **500** have some common characteristics as well as some distinctive properties. Both are continuous unidirectional patterns of types that have been each separately produced on fixed-needle, multi-needle quilting machines where the same pattern extends from one of a panel to the other. The pattern **501**, for example, is referred to as an "onion" pattern, which is formed of alternating, generally-sinusoidal curves **503** and **504**. These curves **503,504** may be considered as identical but 180 degrees out of phase, so that they converge and diverge to produce the illustrated onion pattern **501**. The pattern **502** is referred to as a "diamond" pattern, and is formed of alternating, zig-zag lines **505** and **506**. These lines or curves **505** and **506** may be also considered as identical but 180 degrees out of phase, so that they too converge and diverge to produce the illustrated diamond pat-

tern **502**. The two curves **503**, **504** of the pattern **501** are made up of pattern repeat cycles **507**, while the two curves **505**, **506** of the pattern **502** are made up of repeat cycles **508**. The two patterns **501** and **502** are separated by a small length **510** of the web **12**.

Each of the patterns **501** and **502** may be considered as being made up of (1) a starting length **511** and **512**, respectively, that is spanned by 180 degrees, or half, of a pattern repeat cycle, (2) an intermediate length **513** and **514**, respectively, that is spanned by one or more 360 degree, or full, pattern repeat cycles, and (3) an ending length **515** and **516**, respectively, that is also spanned by 180 degrees of a pattern repeat cycle. These lengths **511-516** are described for a web **12** that moves upward in FIG. 9 through the machine **10** and is quilted from top to bottom in the figure. Each curve of the patterns **501** and **502** begins with a tack stitch sequence **517** and ends with a tack stitch sequence **518**. The tacked beginnings and ends of these curves and the longitudinal proximity of the end tacks **518** of one pattern and the beginning tacks **517** of the next pattern are particularly advantageous features of this aspect of the present invention. The length **210** of web **12** between the patterns **501** and **502** may be less than the length of 180 degrees of the pattern, even substantially less, for example, 90 degrees, 15 degrees or zero degrees. This inter-pattern length **210** may be present on a panel where the panel is made of two of the same or different patterns, such as both of the patterns **501** and **502** as illustrated, or may be present at the boundary between two panels. Where the inter-pattern length **210** lies on the boundary between two patterns, the panels may be cut in this region, thereby minimizing or eliminating waste of the material of the web **12** between the panels. In FIG. 9, each of the patterns **501** and **502** is shown as two pattern cycles long, with each respectively made up of one half-cycle long starting length **511** or **512**, one full-cycle long intermediate length **513** or **514**, and one half-cycle long ending length **515** or **516**.

While each of the patterns **501** and **502** can be sewn on prior art multi-needle quilting machines such as described in U.S. Pat. No. 5,154,130, there are limitations, as can be appreciated by reference to FIG. 9A. This is in part because, with the conventional multi-needle quilting machines, multiple rows of needles are mounted on a common rigid sewing head structure on which the needles are fixed and the rows are constrained to a fixed distance apart, with all of the needles of all of the rows stitching simultaneously and maintaining the fixed relationship determined by their arrangement on the sewing head structure. The simultaneous stitches are formed by the needles of a first row, at positions **521**, spaced a transverse distance **522** from each other, and needles of a second row, at positions **523**, spaced a transverse distance **524** from each other, with the rows being spaced a longitudinal distance **525** apart. This needle arrangement defines the relative dimensions of the components, particularly in the longitudinal direction, of the onion designs of the pattern **501** in FIG. 9A. Similar dimensional limitations are the result of the needle positions **526** transversely spaced a distance **527** on the first bar and needle positions **528** spaced a distance **529** on the second bar. The transverse spacings **527** and **529** need not be, and in FIG. 9A are not, the same for pattern **502** as the spacings **522** and **524** for pattern **502** in FIG. 9A. The longitudinal spacing **525** of the rows is the same for patterns **501** and **502** due to structural limitations of the equipment. These distances **525**, **527** and **529** define the dimensions of the components of the diamond designs of the pattern **502** in FIG. 9A.

The transition from stitching the pattern **501**, which, as shown in FIG. 9A, uses four needles per bar for each of two

needle bars, to stitching the pattern **502**, which, as shown uses seven needles per bar for each of the two needle bars, requires a change of needle settings. With at least most machines of the prior art, needle setting change is typically a manual operation. Alternatively, pattern **502** could be replaced with a pattern limited to those that use the same four needles as pattern **501**, such as a pattern having four rather than seven rows of diamonds, so that no needle change would be required to change from pattern **501** to pattern **502**. Further, since all of the needles of a fixed needle machine start and stop sewing at the same time, regardless of which row on the sewing head they occupy, the start and stop positions of pattern curves **503** and **504**, which are sewn by needles on different rows and located at positions **521** and **523**, respectively, are necessarily longitudinally spaced a distance **525** apart, leaving a half-length portion of one of the only curves **503** or **504** occupying a length of the web equal to the distance **525** at both the beginning and end of each of the patterns **501** and **502**. This results in a production of a length **530** of scrap material or waste equal to two lengths **525** between adjacent patterns on the web **12**, which must be cut off and discarded. This, in turn, requires that the pattern extend to the cut upstream and downstream ends of the panel. This eliminates the ability of producing a panel having a pattern spaced from the ends of the panel with the curves of the pattern that are sewn by different needle bars starting and stopping at the same point. Further, transverse alignment of tack stitches sewn by needles of different needle bars has not been known. In addition, the combination of equipment and techniques of the prior art have not been provided for the quilting of panels having two patterns with curves that start and stop in alignment and that are closely spaced to each other on the same panel, as illustrated in FIG. **9**.

According to one embodiment of the invention, a pattern as illustrated in FIG. **9** is produced on a modified multiple-needle quilting machine. Such a pattern has the limitation that the repeat length **507** for pattern **501** is generally the same as the repeat length **508** for the pattern **502**. In this embodiment, a multi-needle quilting machine such as that of U.S. Pat. No. 5,154,130 is provided with automatically retractable or selectable needles, so that one bar of needles may be disabled while another bar of needles is sewing. In addition, such a multi-needle quilting machine has the ability to reverse the relative motion of the web **12** relative to the bars or bridges that carry the sewing heads. While the method is explained herein for a machine in which the sewing heads are longitudinally fixed relative to a machine frame through which the web **12** moves longitudinally forward and, at least for short distances backward, the explanation applies to machines in which the sewing heads are fixed in an array on a bridge with which they can move longitudinally together relative to the material. The method is illustrated by reference to FIGS. **9B-9I**.

Referring to FIG. **9B**, a web **12** is advanced in the direction of the arrow **531** through a quilting station having a needle bar array **532** that includes an upstream needle bar **533** and a downstream needle bar **534**. The needle bars **533** and **534** are at a fixed distance **525** apart. The needles of the upstream needle bar **533** begin sewing pattern curves **503** by sewing tack stitch sequences **517** at needle positions **523**. After the web **12** has advanced a distance **525**, as illustrated in FIG. **9C**, the needles of the downstream bar **534** are activated and begin sewing the pattern curves **504** by sewing tack stitch sequences **517** at needle positions **521** to begin sewing curves **504** at start positions that align at the same longitudinal position as the beginnings of curves **503**. Then the web **12** is advanced further as both bars **533** and **534** of needles stitch curves **503** and

504 simultaneously until the position of FIG. **9D** is reached, at which points tack stitch sequences **518** are sewn, the thread is cut and the needles at positions **523** on bar **533** are disabled. Sewing then continues with the needles at positions **521** on bar **534** until the web is at the position illustrated in FIG. **9E**. At this position of the web **12**, the needles of bar **534** sew tack stitch sequences **518**, then the threads are cut and the needles of bar **534** are disabled, whereupon the pattern **501** is completed.

At this point the machine is ready to sew pattern **502**, except that the web **12** has advanced past the upstream bar **533** and must be backed-up a distance **525** to the position shown in FIG. **9F** so that pattern **502** can be sewn in a sequence similar to that for sewing pattern **501** described above in connection with FIGS. **9B-9E**. For sewing pattern **502**, needles at positions **528** on bar **534** are activated to sew tack stitch sequences **517** to start curves **505** which they begin to sew as the web **12** advances a distance **525**. The pattern **502** can thus be started at a distance **510** from the end of pattern **501** without material waste. Then, when at the position shown in FIG. **9G**, needles at positions **526** on bar **534** are activated to sew tack stitch sequences **517** for the start of curves **506**. Then the web **12** is advanced further as both bars **533** and **534** of needles stitch curves **503** and **504** simultaneously until the position of FIG. **9H** is reached, at which points tack stitch sequences **518** are sewn, the thread is cut and the needles at positions **528** on bar **533** are disabled. Sewing then continues with the needles at positions **526** on bar **534** until the web is at the position illustrated in FIG. **9I**. At this position of the web **12**, the needles of bar **534** sew tack stitch sequences **518**, then the threads are cut and the needles of bar **534** are disabled, whereupon the pattern **502** is completed. If another pattern **501** or **502** is to be sewn close to the completed pattern **502**, again the web **12** will have to be reversed a distance **525** to the start of the next pattern.

Because the needle bars **533** and **534** move together, when making the tack stitch sequences **517** in FIGS. **9C** and **9G** and the tack stitch sequences **518** in FIGS. **9D** and **9H**, the needles of the other bar will be active, and, as a result, tack stitch sequences will be sewn midway in the curves being sewn with those other needles. This may be aesthetically undesirable. As an alternative, these needles could be deactivated without cutting the threads, which cause undesirable thread handling problems with possible slack in the thread sequence or missed stitches resulting. For these and other reasons, sewing pattern combinations having the properties of patterns **501** and **502** as illustrated in FIG. **9** is preferably performed with the quilter **10**, as described below in reference to FIGS. **9J-9N**.

The combination of patterns **501** and **502** shown in FIG. **9** can be sewn more simply and with greater flexibility with the quilting machine **10** described above. FIG. **9J** shows the bridges **21** and **22** of the machine **10** in arbitrary start positions in the middle of their travel ranges, sufficiently high on the frame to allow for some downward travel. The sewing may start with the needles of the lower bridge **21** stitching tack stitch sequences **517** at the beginnings of curves **503** of pattern **501**. Then the lower bridge **21** begins to sew the curves **503** while moving downwardly with the web **12** stationary while upper bridge **22** moves downwardly to the same starting position, to the positions shown in FIG. **9K**. This motion could be accompanied by, or replaced by, upward motion of the web **12**. When at the starting positions, the needles of upper bridge **22** then stitch tack stitch sequences **518** at the beginnings of curves **504**. Because the sewing heads on the bridges **21** and **22** can operate independently, the tack stitch sequences **518** can be sewn by upper bridge **22** while the lower bridge **21** continues uninterrupted to stitch normal

stitches of the curves **503**. Furthermore, the distance that the lower bridge **21** moves downwardly can be any distance within its travel range that allows enough clearance for the upper bridge **22** to be placed at the starting position. By moving downward a full pattern cycle **513**, for example, the curves **503** and **504** can be stitched with the bridges **21** and **22** moving transversely in the opposite directions, using the web-distortion reduction method described above.

Then, with the bridges **21** and **22** longitudinally stationary, the web **12** moves upward and the curves **503** and **504** are stitched to the end of the pattern, as illustrated in FIG. **9M**. On the way to this state, the web **12** passes through the position shown in FIG. **9L**, where the end of the curves **503** are reached, and tack stitch sequences **518** are stitched by the bridge **21**. This tack stitching sequence can be carried out with the web **12** moving continuously and the curves **504** being stitched without interruption by the bridge **22**, as additional transverse and longitudinal movements are being made by bridge **21**.

After pattern **501** is complete, as illustrated in FIG. **9M**, the web **12** is stopped and the bridges **21** and **22** move upward until the bridge is at the same starting position that is shown in FIG. **9J**. The needle heads are then activated or deactivated, as necessary, to prepare for the stitching of the new pattern. In this case, three intervening sewing heads are activated, one between each of the four heads that were activated for the stitching of pattern **501**, so that all seven heads can stitch pattern **502**. Then, the stitching of pattern **502** proceeds in the same general manner as did the stitching of pattern **501**.

Alternatively, with the machine **10**, the lower bridge **21** can proceed immediately after completing curves **503** of pattern **501** to begin stitching curves **505** of pattern **502**, even while upper bridge **22** is still stitching curves **504** of pattern **501**. This is illustrated in FIG. **9N**. When two bridges are sewing different patterns, the controller **19** of the machine **10** controls the bridge motion, the web motion and the sewing head drives in such a way as to maintain a programmed stitch density, for example seven stitches per inch being typical, for the curves being stitched by both bridges. Usually this can be done by holding one bridge longitudinally stationary as the web moves at a constant feed rate or the heads on the stationary bridge stitch at a constant stitching rate, while compensating movements are made by controlling the other bridge and the sewing heads on the other bridge.

While the description of FIGS. **9-9M** has been described in connection with continuous, unidirectional patterns, this has been done to more clearly illustrate certain features and principles. These features and principles can be used with other pattern features, such as those described in connection with FIGS. **7-7G**. Where such patterns might include bidirectional longitudinal motions, the principles of the methods of FIGS. **9-9M** may be the same net longitudinal forward or backward motions to such other patterns or pattern features.

Panel cutting can be synchronized with the quilting. When a point on the length of the web at which the panel is to be transversely cut from the web **12** reaches the cutoff knife head **72**, the web feed rolls **18** stop the web **12** and the cut is made. Sewing can continue uninterrupted by replacing the upward motion of the web with downward motion of a bridge. This is anticipated by the controller **19**, which will cause the web **12** to be advanced by the rollers **18** faster than the sewing is taking place to allow the bridge to move upward enough so it is enough above its lowermost position to allow it to sew downward for the duration of the cutting operation while the web is stopped.

The illustrated embodiments of multi-needle quilting machines set forth above provide several axes of motion that

differ from those of conventional multi-needle quilting machines. Some embodiments of these quilting machines have two or more bridges that are capable of separate or independent control, each bridge being provided with a row of sewing needles that may be driven together, each separately or independently, or in various combinations. Each bridge may have an independently controllable drive for reciprocating the sewing elements, the needles and loopers. The drive is most practically a rotary input, as from a rotary shaft, that operates the reciprocating elements. Independent operation of the drives on each of the bridges can allow for independent sewing operation of the sewing heads or groups of sewing heads, or the idling of one or more heads, while one or more others is sewing.

It has been shown that each sewing head, including each needle head and each looper head, can be linked to a common rotary drive through an independently controllable clutch that can be operated by a machine controller to turn the heads on or off, thereby providing pattern flexibility. The heads are typically configured in sewing element pairs, each needle head with a corresponding similarly modular looper head. While the heads of each pair can be individually turned on or off, they are typically turned on and off together, either simultaneously or at different phases in their cycles, as may be most desirable. Alternatively, only the needle heads may be provided with selective drive linkages, while the looper heads may be linked to the output of a drive motor so as to run continuously. This linkage may be direct and permanent, or may be adjustable, switchable or capable of being phased in relation to the needle drive, such as by providing a differential drive mechanism in the looper drive train. When direct drive is employed, the looper head drive may be linked to an input drive shaft through a gear box, rather than a clutch. Each of the looper heads may be further provided with an alignment disk on the looper drive shaft to allow precise phase setting of each looper head relative to the other looper heads or the needle drive when the looper head is installed in the machine. Further, each looper head housing may be provided with adjustments in two dimensions in a plane perpendicular to the needle to facilitate alignment of the looper head with a corresponding needle head upon looper head installation.

As described above, in order to reduce the likelihood of missed stitches, particularly at startup of a pattern following the cutting of the looper thread, a split-start control method is provided for avoiding missed stitches at startup. The split start feature is one use of a feature that allows the needle and looper drives to be decoupled and moved separately. With the split-start feature, the initial motion of the needle and looper proceed separately upon startup so as to render the pickup of the stitches predictable. This is achieved by insuring that the looper picks up, that is passes through, a top-thread loop before the needle picks up or passes through a bottom thread loop triangle.

With a split-start method, with the mechanism stopped with the needle in top-dead-center position in its cycle with the looper extended, and with the needles and loopers locked and in phase, the elements are unlocked and the looper can be advanced in its cycle. The advance can be, for example, 180 degrees to the looper's retracted position or by some lesser amount that is enough to insure that the looper thread triangle is not in the path of the needle. Fifteen degrees to twenty degrees, for example 17 degrees, can be sufficient. Then the needle can be advanced a like amount to bring it in phase with the looper, insuring that the needle will miss the looper thread triangle or loop in the looper thread on its first penetration of the material for a pattern. Then the elements are relocked. Upon further advancing of the elements, the looper will there-

upon pick up the needle thread loop before a looper thread loop is picked up by the needle.

In accordance with certain principles of the present invention, a split start may be executed using a single drive servo for the needles and loopers. A phase shifting mechanism is provided to accomplish this with both needles and loopers being driven from the same motor. Further, in accordance with other principles of the invention, the phase of the loopers may be advanced relative to that of the needles, then the loopers and needles may be moved together while maintaining the phase difference between them, then the loopers and needles may be brought back into phase by retracting the loopers, for example, or by slowing or stopping the loopers relative to the needles while the needles catch up, from which point the cycle can continue with the needles and loopers in phase.

Where, as illustrated, a multi-needle quilting machine 10 includes two moveable and independently operable bridges 21 and 22, each having thereon a plurality of separately controllable needle heads 25 and a corresponding plurality of looper heads 26, the speed of the needle heads 25 may be controlled by a controller controlling the operation of a needle drive servo 67 that drives a common needle drive shaft 32 on the bridge 21. Similarly, the speed of the looper heads 26 may be controlled by the controller controlling the operation of a looper drive servo 69 on the bridge 21, that drives the common looper belt drive systems 37 on one of the bridges. The sewing heads 25, 26 on different bridges 21, 22 can be driven at different rates by different operation of the two servos 67 and the two servos 69 on the respective bridges. The needle heads 25 and looper heads 26 on the same bridges 21, 22, however, are usually run at the same speed and in synchronism to cooperate in the formation of stitches, although these may be phased slightly with respect to each other for proper loop take-up, needle deflection compensation, or other purposes.

Certain embodiments are provided with separate drive servos for the needle head assemblies 25 and the looper head assemblies 26 for each respective bridge. In particular, each bridge includes a needle drive servo 67, separately controllable by a signal from the controller 19 which drives shaft 32, which, in turn, drives all of the needle head assemblies 25 on the respective bridge, with each needle head assembly 25 being selectively engageable through a clutch 100, also operated by signals from the controller 19. Also, each bridge further includes a looper drive servo 69, also separately controllable by a signal from the controller 19, which drives a belt 37, which, in turn, drives all of the looper head assemblies 26 on the respective bridge, with each looper head assembly 26 being selectively engageable through a similar clutch 210, also operated by signals from the controller 19. The separate drives 67 and 69 can be controlled separately to facilitate the split-start feature, as well as needle deflection compensation, or for other control refinements. With the split-start feature using the separate drives 67 and 69, at startup when starting a pattern after a thread cut, the loopers can be advanced with the needles held at top dead center, then the needles operated through a similar portion of a cycle, wherein the needle will miss the triangle or loop in the looper thread upon its descent. Then the needle and looper are resynchronized and driven together, whereupon the looper will pick up the needle thread in the next cycle.

According to one embodiment, the needle and looper drives can be decoupled when at the starting position of FIG. 5P, which is similar to that of FIG. 5L, and the needle can be held in its top dead center position. The looper drive is then advanced one-half cycle, to move the looper 216 to the posi-

tion illustrated in FIG. 5Q, thereby retracting the looper 216 out of the path of the needle 132. Then the looper drive is held in its half cycle position while the needle drive is activated to lower the needle 132 to its half cycle position, which leaves the needle 132 clear of the bottom thread 224, as illustrated in FIG. 5R. Then the needle and looper drives are again coupled together and advanced together in synchronization, whereupon the looper 216 begins to take up the needle loop in approximately the three-quarter position of the stitch cycle, as illustrated in FIG. 5S, and proceeds from there to the full cycle position as illustrated in FIG. 5T. Then the elements continue to move through the next cycle, where the formation of stitches can be seen, as illustrated in FIGS. 5U through 5X.

In FIG. 6H, an end portion or tongue 49 of a bridge 21 or 22 is illustrated in which the needle drive motor 67 is linked to drive both the needle head assemblies 25 and looper head assemblies 26 of the same bridge. The servo 67 directly drives the output shaft 32, which is the needle drive input shaft for that bridge. The shaft 32, in turn, drives a cog belt 32a that drives a looper drive input shaft 37a, which takes the place of the looper drive belt 37 in previously described embodiments. With this embodiment, needles 132 and loopers 216 are driven together, and are not separately controlled or phased. Because the stitching elements are mechanically linked, power failures and other malfunctions are less likely to result in mechanical damage to the machine. Nonetheless, the ability to separately control needle and looper heads can be reinstated by retaining the looper drive servo 69 while linking its output to the shaft 37a through a differential drive or phase shifter 69a, which can be added between the belt drive 32a and the looper drive shaft 37a.

In FIGS. 6J-6M, in which FIG. 6J is a top view of a bridge 21 with the differential drive 69a included, servo motor 67 directly drives the shaft 32 to operate the needle heads 25. The differential drive 69a includes a transfer drive belt 32a connected between the needle drive shaft 32 and the input shaft 37a of the looper drive belt assembly 37 which drives the looper heads 26. FIG. 6K, which is a cross-sectional view through the phase shifter 69a, shows the shifter 69a in its default condition in which the shafts 32 and 37a are synchronized to drive the needle heads 25 and looper heads 26 in phase. The phase shifter 69a is shown in detail in FIG. 6M.

A pair of idler pulleys 301 and 302 is mounted between a pair of idler plates 303 and 304 to spread the loop of the belt 32a, to locate less slack in the belt 32a on the higher tension side 305 of a drive pulley 37c on the looper drive shaft 37a than on the low tension side 306. A pneumatic linear actuator 310 is linked between the housing of the phase shifter 69a and the idler plates 303,304 to pivot the plates when actuated to the position shown in FIG. 6L, which moves the slack in the belt 32a to the high tension side 305 of the pulley 37c, which rotates the looper drive shaft 32a forward, advancing the phase of the looper heads 26 in relation to the needle heads 25. This is configured to advance the looper approximately 25 degrees in its cycle. At the start of a pattern after threads have been cut, with the needles in top dead center, the actuator 310 is actuated to advance the loopers 25 degrees, then the needle and looper are operated through 180 degrees while maintaining the phase shift, then the loopers are resynchronized with the needles by deactuating the actuator 310 and reversing the loopers 25 degrees, whereupon the needles will have descended without picking up the triangle or looper thread loop. Then the needles and loopers are advanced in synch, whereupon the loopers pick up the needle thread loops in the next half cycle.

A number of other motions will achieve the same result. For example, if the actuator 310 is a servo motor, the loopers

can be stopped at the advanced phase angle 180 degrees, for example, as the needles are advancing from 155 degrees to 180 degrees, thereby resynchronizing the needles and loopers without reversing the direction of the loopers 26. While a 25 degree phase shift is suitable for some designs of quilting machines, other shifts might be more appropriate for other machine designs. The splitting of the needle and looper drive upon startup, as described, avoids the missing of stitches upon startup. The splitting of the needle and looper drive cycles has other uses, such as in facilitating thread trimming. The use of the split-start feature can eliminate the need for the thread deflectors 430 shown in FIG. 5Y. The illustrated phase shifting actuator provides a simple and reliable device, which operates to switch the phase relationship of the loopers between an in-phase setting and a setting at which the loopers are a fixed portion of a cycle ahead of the needles. Use of a variable differential drive or separate servo motors for needles and loopers would provide increasing degrees of flexibility in phasing the loopers relative to the needles, and would allow moving both elements simultaneously at different speeds through their cycles.

The split-start feature may be combined in different ways with other features when starting to sew a pattern. The wipe cycle, described in connection with FIGS. 5H-5J is one of them. After jumping to the starting point of a new pattern or pattern element, the needle thread tails are lying on the face of the material, extending from the needles through the holes in the pressure foot plates along the fabric. The wipe cycle is a way to remove these tails by pulling them to the backside of the material. The machine can be made to operate in alternative modes that either employ or omit such a wipe cycle. Where product quality is preferred, the wipe cycle is used to totally remove the needle thread tails from the face of the product. This can increase the quilting time of from 2 to 20 percent, depending on the pattern and the configuration of the machine. Alternatively, a high speed, lower quality mode can be provided for customers or products that can tolerate some thread tails. To reduce quilting time, split start motions can be carried in part while the bridges or web are advancing between patterns.

With the wipe cycle used in combination with a split-start, a split start should be carried out after the wipe cycle. However, an execution of a split-start cycle before a wipe cycle can increase the reliability and predictability of the wipe cycle, but such a wipe cycle should still be followed by a further split-start cycle, since the effect of the first split-start cycle on the thread positions at the beginning the stitch sequence is undone by the wipe cycle. The result of the combination of split-start and wipe cycles is that two cycles of the stitching elements reliably form the first stitch of a sequence without a visible top-thread tail.

The first stitch is usually the first stitch of a beginning tack stitch sequence, which may be an intermittent stitch sequence as described above. Such intermittent tack stitches include strings of stitches usually beginning with one or more long stitches then transitioning through progressively shorter stitches into a series of continuous stitches sewn with a standard sinusoidal needle motion. The preferred tack stitch sequence may differ for different quilted products. The difference may be in the number of stitches in the tack sequence as well as in the combination of different stitches that make up a particular tack stitch sequence. For example, stiffer or thicker quilted products may call for a different tack stitch sequence than more flexible or thinner quilted products. The type of tack stitch to be applied to a particular product may be applied by the controller in response to information stored in the product database. Data in the product database may

directly specify the tack stitch needed or the controller may apply a lookup scheme or algorithm to derive or otherwise determine the tack stitch sequence for which the particular product calls.

The product database may also contain other product-based parameters. In addition to the tack stitch sequence, for example, the desired wipe cycle path or distance may differ from product to product, and the controller may base the wipe cycle to be executed on data read from or derived from the product record. The product records in the product database typically include the identification of the pattern to be quilted, the material combination that will make up the material web, and the size of the panels. To this information may be added, or from this information may be derived, the product-based features set forth above and below.

Another product-based parameter may include the positioning of the thread for thread trimming at the end of a pattern. For example, to make it easier to contact the threads with the thread cutter blade and to clamp the looper thread at the end of a pattern, a bridge movement may be executed that moves the bridges in a particular direction relative to the stitching elements. Such a movement may, for example, move the bridges up a predetermined distance. This movement would pull the stitch hole down relative to the needle plate and position the threads against a particular spot on the lower edge of the needle hole in the needle plate. These threads would extend directly from this spot to the looper, making their location predictable and making the proper contact of the threads with the cutting element reliable. The amount of bridge motion desired to accomplish this may depend on the product being quilted. For example, a bridge movement of a greater distance is required with thicker material than with thinner material to position the thread in the best position for cutting. Such distance can be read or derived from data in the product database.

Another product-based feature is one that modifies thread pull-off so as to prevent the needle thread from being pulled from the needle under certain conditions. With some materials, for example thin materials, the material does not provide enough friction on the thread tail to insure that needle thread is pulled from the needle thread supply spool upon startup. Therefore, for products formed of such material, extra bridge motion is added to the thread pull-off. This leaves additional needle thread slack at the needle, reducing the drag caused by the needle thread spool on the needle thread. The addition of this extra bridge movement is added based on data read from or derived from the product database.

The sewing of extra stitch lines to provide material stability is also a product-based feature that can be read from or derived from the product database. For example, a series of stitches, referred to herein as a "stabilization line", may be helpful on certain types of tack-and-jump products that might carry one of the sewing head pairs off one side of the material. Such a stabilization line would be sewn along an edge of the material for patterns in which the sewing heads might move off that edge. The stitch line would guard against head catching or snagging the edge of one or more material layers as the head moves back onto the material.

For example, the need to sew a stabilization line can arise where a web is registered to the left side of the machine (facing downstream from the front). In this case, the leftmost head of a bridge will move close to, but not off of, the left edge of the material as the bridge shifts transversely. The rightmost head can, however, move off the right edge of the material when the bridge shifts to the right. After doing so, when the bridge returns to the left, the heads that moved off the material can snag the material. The sewing of a stabilization line

51

longitudinally along the right edge of the web to join the loose layers of material together can avoid the snagging of the material. The line of stitches along the right edge of the web holds the layers together so the top layer or layers of material aren't free to be caught by the returning head.

This feature is only needed on certain types of patterns, namely tack and jump pattern arrays in which the heads move transversely off the edge of the web when the head is not sewing. The feature is product based, and involves sewing pattern logic that adds the longitudinal stabilization line to be sewn when the web is advancing downstream relative to the bridges, including when the bridges are descending on the frame and moving upstream relative to the web, and the pattern is one that takes the rightmost head or heads off the edge of the machine. The stabilization line sewing feature is normally turned off, but is automatically enabled from the product database for products needing the stabilization line.

When the stabilization line feature is on, whenever the bottom-most or upstream bridge is moving below or upstream of the leading end of the sewn stabilization line or the sewn pattern, which is usually when the web is moving up relative to the bridge in the illustrated embodiments, a head at the right end of the bridge is caused by the controller to sew the stabilization line along the right edge of the web. The line can be sewn between pattern components and from the end of the last pattern until the bridges and material are repositioned to the next pattern zero.

Those skilled in the art will appreciate that the application of the present invention herein is varied, that the invention is described in preferred embodiments, and that additions and modifications can be made without departing from the principles of the invention.

The following is claimed:

[1. A method of operating a quilting machine having at least one stitching element pair that each includes a needle and a looper, to control needle thread tails on the needle side of a chain stitch quilted material having a needle side and a looper side, the method comprising:

with a needle at a starting point on the material and in a retracted position spaced from the needle side of the material and a needle thread tail extending from each needle entirely on the needle side of the material, initiating a thread tail wipe cycle by operating a programmed controller to reciprocate the needle through a stitch cycle and back to the retracted position to poke the needle thread through the material to the looper side of the material at the starting point on the material; then

further operating the controller to advance a looper through a loop in the needle thread so that the needle thread extends from the needle and around the looper on the looper side of the material, then through the material with the needle thread tail remaining on the needle side of the material; then

with the tension applied to the needle thread, further operating the controller to impart relative movement between the needle and the material, in a path from and back toward the starting point, in a direction parallel to the material a distance sufficient to pull the needle thread until the needle thread tail is pulled to the looper side of the material; then

with the thread tail on the looper side of the material, operating the controller to drive the stitching element pair to sew a chain stitch sequence in the material.]

52

[2. The method of claim 1 further comprising:

operating the controller to drive the stitching element pair to sew a tack stitch sequence at the end of the chain stitch sequence and then to move the needle to the retracted position; then

operating the controller to activate a thread trimming mechanism on the looper side of the material to trim both the needle thread and a looper thread and producing a needle thread tail on the looper side of the material;

with the tension applied to the needle thread, further operating the controller to impart relative movement between the needle and the material in a direction parallel to the material to position the needle at a second starting point on the material and to pull the needle thread until the needle thread tail is pulled out of the material to the needle side of the material; then

with a needle at the second starting point on the material and in a retracted position spaced from the needle side of the material and a needle thread tail extending from each needle entirely on the needle side of the material, initiating a thread tail wipe cycle by operating a programmed controller to reciprocate the needle through a stitch cycle and back to the retracted position to poke the needle thread through the material to the looper side of the material at a starting point on the material; then

further operating the controller to advance a looper through a loop in the needle thread so that the needle thread extends from the needle and around the looper on the looper side of the material, then through the material with the needle thread tail remaining on the needle side of the material; then

with the tension applied to the needle thread, further operating the controller to impart relative movement between the needle and the material, in a path from and back toward the second starting point, in a direction parallel to the material a distance sufficient to pull the needle thread until the needle thread tail is pulled to the looper side of the material; then

with the thread tail on the looper side of the material, operating the controller to drive the stitching element pair to sew a second chain stitch sequence in the material.]

[3. The method of claim 2 wherein the quilting machine is a multi-needle quilting machine having a plurality of stitching element pairs each that include a needle and a looper, wherein:

the initiating of the thread tail wipe cycles is performed with each of a plurality of needles at respective starting points and in retracted positions spaced from the needle side of the material with each needle having a needle thread tail extending from the needle on the needle side of the material, by operating the programmed controller to reciprocate the needles simultaneously through a stitch cycle and back to the retracted position to poke the needle threads through the material to the looper side of the material at the respective starting points on the material;

the further operating of the controller to advance the looper includes operating the controller to advance each of a plurality of loopers through loops in respective needle threads so that the needle threads extend from the needles and around the loopers on the looper side of the material, then through the material with the needle thread tails remaining on the needle side of the material;

the further operating of the controller to impart relative movement includes further operating the controller, with tension applied to the needle threads, to impart

53

relative movement between each of the needles and the material, in paths from and back toward the respective starting points, in a direction parallel to the material a distance sufficient to pull the needle threads until the needle thread tails are pulled to the looper side of the material; and

the operating of the controller to drive the stitching element pair includes operating the controller, with the thread tails on the looper side of the material, to drive each of the stitching element pairs to sew a respective one of a plurality of chain stitch sequences in the material.]

[4. The method of claim 1 wherein the quilting machine is a multi-needle quilting machine having a plurality of stitching element pairs each that include a needle and a looper, wherein:

the initiating of the thread tail wipe cycles is performed with each of a plurality of needles at respective starting points and in retracted positions spaced from the needle side of the material with each needle having a needle thread tail extending from the needle on the needle side of the material, by operating the programmed controller to reciprocate the needles simultaneously through a stitch cycle and back to the retracted position to poke the needle threads through the material to the looper side of the material at the respective starting points on the material;

the further operating of the controller to advance the looper includes operating the controller to advance each of a plurality of loopers through loops in respective needle threads so that the needle threads extend from the needles and around the loopers on the looper side of the material, then through the material with the needle thread tails remaining on the needle side of the material;

the further operating of the controller to impart relative movement includes further operating the controller, with tension applied to the needle threads, to impart relative movement between each of the needles and the material, in paths from and back toward the respective starting points, in a direction parallel to the material a distance sufficient to pull the needle threads until the needle thread tails are pulled to the looper side of the material; and

the operating of the controller to drive the stitching element pair includes operating the controller, with the thread tails on the looper side of the material, to drive each of the stitching element pairs to sew a respective one of a plurality of chain stitch sequences in the material.]

[5. The method of claim 1 wherein:

the path is a line, an arc, a triangle or some other combination of lines and arcs.]

[6. The method of claim 1 wherein:

the movement is imparted by moving of the needles relative to the material and holding the material stationary relative to the machine.]

[7. The method of claim 1 further comprising:

following the stitching of the patterns, operating the plurality of stitching element pairs to sew tack stitch sequences; then

with the top threads extending from top-thread supply spools through top-thread tensioners through the needles and into the material, releasing tension on the top threads and pulling off slack in the top threads between the supplies and the needles; then

imparting relative movement between the needles and the material that is sufficient to pull the slack in the top threads through the each needle to add thread tails between the needles and the material; then

54

cutting the top threads on the looper side of the material to create top-thread tails extending from the needle through the material to the looper side of the material; then

imparting relative movement between the needles and the material that is sufficient to pull the top thread tails from the material to the needle side of the material and locating the needles at new starting locations relative to the material; then

with each of a plurality of needles at the new starting locations and in retracted positions spaced from the needle side of the material with the needle thread tails extending from the needles on the needle side of the material, reciprocating the needles through a stitch cycle and back to the retracted positions to poke the needle threads through the material to below the material around respective loopers with ends of the thread tails remaining on the needle side of the material; then

with the tension applied to the needle threads, imparting relative movement between the needles and the material by a distance sufficient to pull the needle threads until the needle thread tails are pulled to the looper side of the material but insufficient to pull the needle thread tails out of the material.]

[8. The method of claim 1 wherein the imparting of the relative movement between the needles and the material proceeds along a path that is dependent on and differs in accordance with different patterns or quilted material properties.]

[9. The method of claim 1 wherein the imparting of the relative movement between the needles and the material proceeds along a path that is dependent on and differs in accordance with different patterns or quilted material properties.]

[10. A method of operating a multi-needle quilting machine having a plurality of stitching element pairs each that include a needle and a looper, to control needle thread tails on the needle side of a chain stitch quilted material having a needle side and a looper side, the method comprising:

with each of a plurality of needles in retracted positions spaced from the needle side of the material to be quilted and with a needle thread tail extending from each needle on the needle side of the material, reciprocating the needles through a first stitch cycle and back to the retracted positions to poke the needle threads through the material to the looper side of the material where each needle thread has a loop that is entered by a looper of the respective stitching element pair while ends of the thread tails remain on the needle side of the material; then

with the tension applied to the needle threads, pulling the needle threads until the ends of the needle thread tails are pulled to the looper side of the material; then

with the needle thread tails to the needle side of the material, operating the plurality of stitching element pairs to sew a plurality of chain stitch sequences in the material.]

[11. The method of claim 10 further comprising:

providing an option, selectable by a user of a quilting machine, for enabling or disabling the method so as to either reduce or eliminate needle thread tails with the method enabled, or alternatively to provide higher speed machine operation with the method disabled.]

[12. The method of claim 10 further comprising:

cutting the top threads with a plurality of thread trimming devices, each including a thread trimming mechanism situated one at each looper so as to be operable, when actuated, to cut a looper thread and the needle thread.]

55

[13. A multi-needle quilting machine comprising:

a frame;

a plurality of chain stitching element pairs, each pair including a needle mounted to reciprocate through quilting material from the front side of a quilting material plane and a cooperating looper mounted to oscillate with respect to the needle on the back side of the quilting material plane to form chain stitches with a needle thread extending through the needle and a looper thread extending through the looper;

a motion system operative to move the material longitudinally relative to the frame and to impart relative transverse movement between the stitching element pairs and the material;

a plurality of thread trimming devices, each including a thread trimming mechanism situated one at each looper so as to be operable, when actuated, to cut a looper thread; and

a programmed controller operative to control the stitching element pairs, the motion system and the thread trimming devices.]

[14. The quilting machine of claim 13 wherein:

the controller is programmed to perform a thread tail wipe cycle by initiating the wipe cycle with each of a plurality of needles in retracted positions spaced from the needle side of the material and with a needle thread tail extending from each needle on the needle side of the material and operating the stitching element pairs to reciprocate the needles through a first stitch cycle and back to the retracted positions to poke the needle threads through the material to the looper side of the material where each needle thread has a loop that is entered by a looper of the respective stitching element pair while ends of the thread tails remain on the needle side of the material, then with tension applied to the needle threads, imparting relative movement of the needles parallel to the material to pull the needle threads until the ends of the needle thread tails are pulled to the looper side of the material, then with the needle thread tails to the needle side of the material, operating the plurality of stitching element pairs to sew a plurality of chain stitch sequences in the material.]

[15. The quilting machine of claim 13 wherein:

each thread trimming mechanism is situated at a looper so as to be operable, when actuated, to cut both the needle thread and the looper thread extending from the material.]

[16. The quilting machine of claim 15 further comprising:

a plurality of thread tail wipers on the front side of the material, one proximate the needle at each stitching element pair, that activates to pull the needle thread tail from the material to the front side thereof when the needle thread is cut.]

[17. The quilting machine of claim 13 wherein:

the trimming mechanisms are selectively operable, when actuated, to selectively cut individual looper threads.]

[18. The quilting machine of claim 13 wherein:

each thread trimming mechanism is operable, when actuated, to clamp the end of the cut looper thread extending from the looper.]

[19. The quilting machine of claim 13 wherein:

each thread trimming device includes linkage for moving the thread trimming mechanism thereof between a thread cutting position adjacent the looper and a rest position remote from the looper.]

56

[20. The quilting machine of claim 13 wherein:

each thread trimming mechanism is situated at a looper so as to be operable, when actuated, to cut both the needle thread and the looper thread extending from the material;

the trimming mechanisms are selectively operable, when actuated, to selectively cut individual looper threads;

each thread trimming mechanism is operable, when actuated, to clamp the end of the cut looper thread extending from the looper; and

each thread trimming device includes linkage for moving the thread trimming mechanism thereof between a thread cutting position adjacent the looper and a rest position remote from the looper.]

21. A quilting machine comprising:

a frame;

structure for supporting a length of a web of multi-layered material in a quilting plane;

a web drive for advancing a supported web in a longitudinal direction in the quilting plane;

a plurality of bridges, including a first bridge and a second bridge, spaced from one another in the longitudinal direction, each bridge being moveable relative to each other and relative to the supported material, longitudinally and transversely, adjacent and parallel to the quilting plane;

each bridge having a plurality of needles supported thereon on a needle side of the quilting plane and a plurality of loopers mounted thereon on a looper side of the quilting plane opposite the needle side, each needle being reciprocable in a direction perpendicular to the quilting plane through material supported in the quilting plane to sew stitches in the material;

a plurality of bridge longitudinal drives, one for each bridge, and operable to move the bridge bidirectionally in a longitudinal direction parallel to the plane;

a plurality of bridge transverse drives, one for each bridge, and operable to move the bridge bidirectionally in a transverse direction parallel to the plane;

a plurality of stitching element sets on each of the bridges, each including one of the needles and one of the loopers, and each operable to sew a series of stitches in material supported in the quilting plane; and

a programmed controller operable to selectively control the web drive, the bridge drives, and the stitching element sets, in accordance with pattern program data.

22. The quilting machine of claim 21 wherein:

each of the stitching element sets includes a needle drive that is capable of being selectively enabled or disabled in response to a control signal from the controller so that selective ones of the needles reciprocate to sew stitches in the material.

23. The quilting machine of claim 21 wherein:

each bridge has a plurality of presser feet thereon, one for each stitching element set, that is moveable on the bridge, toward and away from the plane, in synchronism with the reciprocating of one of the needles.

24. The quilting machine of claim 21 wherein:

the bridges are separately and independently moveable longitudinally and transversely relative to the frame and the material.

25. The quilting machine of claim 21 wherein:

the longitudinal direction is a vertical direction; and each bridge is supported on each end thereof on a pair of elevators, one on each side of the frame, to move the bridge vertically relative to the frame and parallel to the plane of the material.

57

26. The quilting machine of claim 25 wherein: each bridge is moveable transversely in a horizontal direction relative to the frame.
27. The quilting machine of claim 24 wherein: each of the elevators is servo driven and separately controlled by the controller to maintain the bridges level while being moved.
28. The quilting machine of claim 21 further comprising: a plurality of linear servos on the frame controllable to move the bridges longitudinally on the frame in response to signals from the controller.
29. The quilting machine of claim 21 further comprising: a plurality of linear servo armatures, at least two on each bridge, at least one on each end thereof; a plurality of linear servo stators, at least one at each side of the frame, each having one of the armatures of each bridge moveable longitudinally thereon.
30. The quilting machine of claim 21 further comprising: a plurality of linear servos, at least one on each bridge, controllable to move the bridges transversely relative to the frame in response to signals from the controller.
31. The quilting machine of claim 21 wherein: at least one of the stitching element sets is transversely moveable on the bridge.
32. The quilting machine of claim 21 wherein: at least one of the stitching element sets is transversely moveable on the bridge in response to a signal from the controller to change patterns.
33. The quilting machine of claim 21 wherein: at least one of the stitching element sets is transversely moveable on the bridge in response to a signal from the controller to vary the spacing between sets on the bridge during quilting.
34. The quilting machine of claim 21 wherein: the needles and loopers of the stitching element sets are moveable relative to each other and parallel to the quilting plane to compensate for needle deflection.
35. The quilting machine of claim 21 wherein: the loopers have a phase that is varied relative to that of the corresponding needle of the respective sets, to compensate for needle deflection.
36. The quilting machine of claim 21 wherein: each stitching element set has associated therewith at least one servo by which an element of the set is separately drivable.
37. The quilting machine of claim 21 wherein: each needle head and each looper head has associated therewith a servo by which it is separately drivable.
38. The quilting machine of claim 21 wherein: the web drive has a transversely extending pair of web drive rollers linked the web drive and journaled to the frame longitudinally downstream of the bridges; each of the bridges has a pair of transversely extending pinch rollers moveable therewith and linked to the web drive rollers so as to move therewith as the web moves relative thereto, that roll with the web as the bridges move longitudinally.
39. The quilting machine of claim 21 wherein: the web drive has a transversely extending pair of web drive rollers linked to the web drive and journaled to the frame longitudinally downstream of the bridges; each of the bridges has a pair of transversely extending pinch rollers moveable therewith and linked to the web drive rollers by at least one belt so as to rotate the pinch rollers at the same tangential speed as the web drive rollers minus the longitudinal speed of the respective bridge relative to the frame.

58

40. The quilting machine of claim 21 further comprising: a plurality of servo driven belts on the frame controllable to move the bridges longitudinally on the frame in response to signals from the controller.
41. A multi-needle quilting machine comprising: a frame for supporting a substrate web of material for quilting; a material drive selectively operable to move the substrate web longitudinally relative to the frame; one or more bridge assemblies selectively moveable longitudinally relative to the frame; a plurality of stitching elements on the one or more bridge assemblies, stitching element being operable to sew a series of stitches on the substrate web of material; a transverse drive selectively operable to impart transverse relative movement between the plurality of stitching elements and the substrate web of material; a controller operable to control the operation of the material drive, the movement of the one or more bridge assemblies, the operation of the stitching elements and the operation of the transverse drive to sew series of stitches on the substrate web of material while either: a) moving the web of material relative to the frame while the one or more bridge assemblies has zero longitudinal velocity relative to the frame, b) moving the one or more bridge assemblies longitudinally relative to the frame while the substrate web of material is stationary relative to the frame, or c) moving both the substrate web of material and the one or more bridge assemblies relative to the frame, wherein either A) the one or more bridge assemblies include 1) two or more rows of the stitching elements with each row being moveable longitudinally relative to another one of the rows of stitching elements 2) or at least two bridges each including one or more rows of stitching elements, each bridge being moveable longitudinally and transversely relative to the other ones of the bridges, or B) the material drive is operable to move at least a portion of the substrate web longitudinally and vertically, and the stitching elements include needles oriented horizontally perpendicular to said portion of the web.
42. A method of quilting comprising: supporting a multi-layered material in a plane in a quilting machine having a plurality of bridges extending horizontally in a transverse direction adjacent the plane and spaced from one another in a longitudinal direction perpendicular to the transverse direction, each with a plurality of needles on one side of the plane and a corresponding plurality of loopers on the opposite side of the frame, each corresponding pair of needles and loopers providing a cooperating chainstitch-forming element set, each of the bridges being moveable transversely and longitudinally relative to each other and relative to and parallel to the plane; moving one of the bridges relative to another of the bridges to carry a plurality of the needles and loopers in different transverse motions while sewing the stitches; and reciprocating a plurality of the needles through the plane while oscillating a corresponding plurality of the loopers on the opposite side of the material from the needles so as to sew a corresponding plurality of series of stitches on the material to quilt the material.
43. The method of claim 42 further comprising: moving at least one of the bridges carrying a plurality of the needles and loopers transversely while sewing the stitches.

59

44. The method of claim 42 further comprising:
moving at least two of the bridges each carrying a plurality
of the needles and loopers transversely while sewing the
stitches.
45. The method of claim 42 further comprising: 5
moving one of the bridges oppositely relative to another of
the bridges so as to cancel transverse distorting forces
on the material.
46. The method of claim 42 wherein the longitudinal direc- 10
tion is a vertical direction, the method further comprising:
moving at least one of the bridges carrying a plurality of
needles and loopers vertically relative to the material
while sewing the stitches.
47. The method of claim 46 wherein the longitudinal direc- 15
tion is a vertical direction, the method further comprising:
moving at least one of the bridges carrying a plurality of
needles and loopers vertically relative to the frame while
sewing the stitches.
48. The method of claim 46 wherein the longitudinal direc- 20
tion is a vertical direction, the method further comprising:
moving the material vertically relative to the frame while
sewing the stitches.
49. The method of claim 42 further comprising: 25
moving at least one of the bridges carrying a plurality of
needles and loopers longitudinally relative to the frame
and moving the material longitudinally relative to the
frame while sewing the stitches.
50. The method of claim 42 further comprising: 30
sewing stitches with the sewing elements on one bridge at
one stitch rate while sewing stitches with the sewing
elements of another bridge at a different stitch rate.
51. The method of claim 42 further comprising:
providing a plurality of bridges adjacent the material, each
having a plurality of needles and a corresponding plu-
rality of loopers thereon;

60

- performing with the needles and loopers on each of the
bridges the step of reciprocating the respective plurality
of needles through the plane while oscillating the cor-
responding respective plurality of loopers on the oppo-
site side of the material from the needles so as to sew a
corresponding plurality of series of stitches on the mate-
rial to quilt the material.
52. The method of claim 51 further comprising:
separately controlling the needles and loopers on different
bridges to quilt patterns differently on the material.
53. The method of claim 42 further comprising:
separately moving the bridges while performing with the
needles and loopers on each of the bridges the step of
reciprocating the respective plurality of needles through
the plane while oscillating the corresponding respective
plurality of loopers on the opposite side of the material
from the needles so as to sew a corresponding plurality
of series of stitches on the material to quilt the material.
54. The method of claim 53 further comprising:
separately moving the bridges transversely while sewing
the stitches.
55. The method of claim 53 further comprising:
separately moving the bridges longitudinally while sewing
the stitches.
56. The method of claim 42 further comprising:
selectively with a controller enabling different ones of the
needles while disabling others of the needles so as to
quilt patterns with only the selected ones of the needles.
57. The method of claim 42 further comprising:
compressing the material with a plurality of presser foot
plates while sewing with the plurality of needles.
58. The method of claim 42 further comprising:
compressing the material with a plurality of presser foot
plates, one for each one of the needles, while sewing with
the plurality of needles.

* * * * *