

US00RE45854E

(19) **United States**
(12) **Reissued Patent**
Gittinger et al.

(10) **Patent Number:** **US RE45,854 E**
(45) **Date of Reissued Patent:** **Jan. 19, 2016**

(54) **METHOD AND AN APPARATUS FOR CAPTURING THREE-DIMENSIONAL DATA OF AN AREA OF SPACE**

(71) Applicant: **FARO Technologies, Inc.**, Lake Mary, FL (US)

(72) Inventors: **Juergen Gittinger**, Ludwigsburg (DE); **Bernd-Dietmar Becker**, Ludwigsburg (DE); **Reinhard Becker**, Ludwigsburg (DE)

(73) Assignee: **FARO TECHNOLOGIES, INC.**, Lake Mary, FL (US)

(21) Appl. No.: **14/549,851**

(22) Filed: **Nov. 21, 2014**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,847,922**
Issued: **Dec. 7, 2010**
Appl. No.: **12/515,489**
PCT Filed: **Jun. 29, 2007**
PCT No.: **PCT/EP2007/005789**
§ 371 (c)(1),
(2) Date: **May 19, 2009**
PCT Pub. No.: **WO2008/003436**
PCT Pub. Date: **Jan. 10, 2008**

(30) **Foreign Application Priority Data**

Jul. 3, 2006 (DE) 10 2006 031 580

(51) **Int. Cl.**
G01C 3/08 (2006.01)
G01C 1/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G01C 15/06** (2013.01); **G01C 15/02** (2013.01)

(58) **Field of Classification Search**
CPC G01C 15/02; G01C 15/04; G01C 15/06
USPC 382/103, 105, 154; 356/4.01, 614; 358/453, 475, 480

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,898,484 A 4/1999 Harris
D423,534 S 4/2000 Raab et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2005200937 A1 9/2006
CN 2236119 y 9/1996

(Continued)

OTHER PUBLICATIONS

Bijhold, Jurrien, et al., "Forensic Imaging—A Review: 2001 to 2004", 14th International Forensic Science Symposium, Review Papers, Interpol—Lyon, Oct. 19-22, 2004, pp. 189-205.

(Continued)


Primary Examiner — Kenneth J Whittington

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

In a method for capturing three-dimensional data of an area of space, a plurality of measuring beams (L_s) are sent out to a plurality of measuring points. A detector (50) receives a plurality of reflected beams (L_r) which are reflected by the measuring points (34a). A plurality of distances to the measuring points (34a, 34b) are determined as a function of the reflected beams (L_r). According to one aspect of the invention, at least one object (30) which comprises a hidden channel (66) having a visible entry opening (72) is located in the area of space. A rod-shaped element (32) is inserted into the channel (66) in such a manner that a [free end] proximal portion (70) protrudes from the entry opening (72). A first distance to a first measuring point (34a) and a second distance to a second measuring point (34b) are determined. An orientation (74) of the hidden channel (66) is determined as a function of the first and the second distances.

14 Claims, 4 Drawing Sheets



(51)	Int. Cl.			7,599,106 B2	10/2009	Matsumoto et al.
	G01C 15/06	(2006.01)		7,600,061 B2	10/2009	Honda
	G01C 15/02	(2006.01)		7,602,873 B2	10/2009	Eidson
				7,604,207 B2	10/2009	Hasloecheer et al.
				7,610,175 B2	10/2009	Eidson
(56)	References Cited			7,614,157 B2	11/2009	Granger
	U.S. PATENT DOCUMENTS			7,624,510 B2	12/2009	Ferrari
				7,625,335 B2	12/2009	Deichmann et al.
				7,626,690 B2	12/2009	Kumagai et al.
				D607,350 S	1/2010	Cooduvalli et al.
	D441,632 S	5/2001	Raab et al.	7,656,751 B2	2/2010	Rischar et al.
	D472,824 S	4/2003	Raab et al.	7,659,995 B2	2/2010	Knighton et al.
	D479,544 S	9/2003	Raab et al.	D610,926 S	3/2010	Gerent et al.
	6,675,122 B1 *	1/2004	Markendorf et al. 702/150	7,693,325 B2	4/2010	Pulla et al.
	D490,831 S	6/2004	Raab et al.	7,697,748 B2	4/2010	Dimsdale et al.
	D491,210 S	6/2004	Raab et al.	7,701,592 B2	4/2010	Saint Clair et al.
	7,230,689 B2	6/2007	Lau	7,712,224 B2	5/2010	Hicks
	7,242,590 B1	7/2007	Yeap et al.	7,721,396 B2	5/2010	Fleischman
	7,246,030 B2	7/2007	Raab et al.	7,728,833 B2	6/2010	Verma et al.
	7,249,421 B2	7/2007	MacManus et al.	7,728,963 B2	6/2010	Kirschner
	7,256,899 B1	8/2007	Faul et al.	7,733,544 B2	6/2010	Becker et al.
	7,269,910 B2	9/2007	Raab et al.	7,735,234 B2	6/2010	Briggs et al.
	D551,943 S	10/2007	Hodjat et al.	7,743,524 B2	6/2010	Eaton et al.
	7,285,793 B2 *	10/2007	Husted 250/577	7,752,003 B2	7/2010	MacManus
	7,296,364 B2	11/2007	Seitz et al.	7,756,615 B2	7/2010	Barfoot et al.
	7,296,955 B2	11/2007	Dreier	7,765,707 B2	8/2010	Tomelleri
	7,296,979 B2	11/2007	Raab et al.	7,769,559 B2	8/2010	Reichert
	7,306,339 B2	12/2007	Kaufman et al.	7,774,949 B2	8/2010	Ferrari
	7,307,701 B2	12/2007	Hoffman, II	7,777,761 B2	8/2010	England et al.
	7,312,862 B2	12/2007	Zumbrunn et al.	7,779,548 B2	8/2010	Ferrari
	7,313,264 B2	12/2007	Crampton	7,779,553 B2	8/2010	Jordil et al.
	D559,657 S	1/2008	Wohlford et al.	7,784,194 B2	8/2010	Raab et al.
	7,319,512 B2	1/2008	Ohtomo et al.	7,787,670 B2	8/2010	Urushiya
	7,330,242 B2	2/2008	Reichert et al.	7,793,425 B2	9/2010	Bailey
	7,337,344 B2	2/2008	Barman et al.	7,798,453 B2	9/2010	Maningo et al.
	7,342,650 B2	3/2008	Kern et al.	7,800,758 B1	9/2010	Bridges et al.
	7,348,822 B2	3/2008	Baer	7,804,602 B2	9/2010	Raab
	7,352,446 B2	4/2008	Bridges et al.	7,805,851 B2	10/2010	Pettersson
	7,360,648 B1	4/2008	Blaschke	7,805,854 B2	10/2010	Eaton
	7,372,558 B2	5/2008	Kaufman et al.	7,809,518 B2	10/2010	Zhu et al.
	7,372,581 B2	5/2008	Raab et al.	7,834,985 B2	11/2010	Morcom
	7,383,638 B2	6/2008	Granger	7,847,922 B2	12/2010	Gittinger et al.
	7,388,654 B2	6/2008	Raab et al.	RE42,055 E	1/2011	Raab et al.
	7,389,870 B2	6/2008	Slappay	7,869,005 B2	1/2011	Ossig et al.
	7,395,606 B2	7/2008	Crampton	RE42,082 E	2/2011	Raab et al.
	7,400,384 B1	7/2008	Evans et al.	7,881,896 B2	2/2011	Atwell et al.
	7,403,268 B2	7/2008	England et al.	7,889,324 B2	2/2011	Yamamoto
	7,403,269 B2	7/2008	Yamashita et al.	7,891,248 B2	2/2011	Hough et al.
	7,430,068 B2	9/2008	Becker et al.	7,900,714 B2	3/2011	Milbourne et al.
	7,430,070 B2	9/2008	Soreide et al.	7,903,245 B2	3/2011	Miousset et al.
	7,441,341 B2	10/2008	Eaton	7,903,261 B2	3/2011	Saint Clair et al.
	7,443,555 B2	10/2008	Blug et al.	7,908,757 B2	3/2011	Ferrari
	7,447,931 B1	11/2008	Rischar et al.	7,933,055 B2	4/2011	Jensen et al.
	7,449,876 B2	11/2008	Pleasant et al.	7,935,928 B2	5/2011	Serger et al.
	7,454,265 B2	11/2008	Marsh	7,965,747 B2	6/2011	Kumano
	7,463,368 B2	12/2008	Morden et al.	7,982,866 B2	7/2011	Vogel
	7,477,359 B2	1/2009	England et al.	D643,319 S	8/2011	Ferrari et al.
	7,477,360 B2	1/2009	England et al.	7,990,397 B2	8/2011	Bukowski et al.
	7,480,037 B2	1/2009	Palmateer et al.	7,994,465 B1	8/2011	Bamji et al.
	7,508,496 B2	3/2009	Mettenleiter et al.	7,995,834 B1	8/2011	Knighton et al.
	7,508,971 B2	3/2009	Vaccaro et al.	8,001,697 B2	8/2011	Danielson et al.
	7,515,256 B2	4/2009	Ohtomo et al.	8,020,657 B2	9/2011	Allard et al.
	7,525,276 B2	4/2009	Eaton	8,022,812 B2	9/2011	Beniyama et al.
	7,527,205 B2	5/2009	Zhu et al.	8,028,432 B2	10/2011	Bailey et al.
	7,528,768 B2	5/2009	Wakayama et al.	8,036,775 B2	10/2011	Matsumoto et al.
	7,541,830 B2	6/2009	Fahrbach et al.	8,045,762 B2	10/2011	Otani et al.
	7,545,517 B2	6/2009	Rueb et al.	8,051,710 B2	11/2011	Van Dam et al.
	7,546,689 B2	6/2009	Ferrari et al.	8,052,857 B2	11/2011	Townsend
	7,551,771 B2	6/2009	England, III	8,064,046 B2	11/2011	Ossig et al.
	7,552,644 B2	6/2009	Haase et al.	8,065,861 B2	11/2011	Caputo
	7,557,824 B2	7/2009	Holliman	8,082,673 B2	12/2011	Desforges et al.
	7,561,598 B2	7/2009	Stratton et al.	8,099,877 B2	1/2012	Champ
	7,564,250 B2	7/2009	Hocker	8,117,668 B2	2/2012	Crampton et al.
	7,568,293 B2	8/2009	Ferrari	8,123,350 B2	2/2012	Cannell et al.
	7,578,069 B2	8/2009	Eaton	8,152,071 B2	4/2012	Doherty et al.
	D599,226 S	9/2009	Gerent et al.	D659,035 S	5/2012	Ferrari et al.
	7,589,595 B2	9/2009	Cutler	8,171,650 B2	5/2012	York et al.
	7,589,825 B2	9/2009	Orchard et al.	8,179,936 B2	5/2012	Bueche et al.
	7,591,077 B2	9/2009	Pettersson	D662,427 S	6/2012	Bailey et al.
	7,591,078 B2	9/2009	Crampton			

(56)

References Cited

U.S. PATENT DOCUMENTS

8,218,131	B2	7/2012	Otani et al.	
8,224,032	B2	7/2012	Fuchs et al.	
8,260,483	B2	9/2012	Barfoot et al.	
8,269,984	B2	9/2012	Hinderling et al.	
8,276,286	B2	10/2012	Bailey et al.	
8,284,407	B2	10/2012	Briggs et al.	
8,310,653	B2	11/2012	Ogawa et al.	
8,321,612	B2	11/2012	Hartwich et al.	
8,346,392	B2	1/2013	Walser et al.	
8,346,480	B2	1/2013	Trepagnier et al.	
8,352,212	B2	1/2013	Fetter et al.	
8,353,059	B2	1/2013	Crampton et al.	
D676,341	S	2/2013	Bailey et al.	
8,379,191	B2	2/2013	Braunecker et al.	
8,381,704	B2	2/2013	Debelak et al.	
8,384,914	B2	2/2013	Becker et al.	
D678,085	S	3/2013	Bailey et al.	
8,391,565	B2	3/2013	Purcell et al.	
8,402,669	B2	3/2013	Ferrari et al.	
8,422,035	B2	4/2013	Hinderling et al.	
8,497,901	B2	7/2013	Pettersson	
8,533,967	B2	9/2013	Bailey et al.	
8,537,374	B2	9/2013	Briggs et al.	
8,619,265	B2	12/2013	Steffey et al.	
8,645,022	B2	2/2014	Yoshimura et al.	
8,659,748	B2	2/2014	Dakin et al.	
8,659,752	B2	2/2014	Cramer et al.	
8,661,700	B2	3/2014	Briggs et al.	
8,677,643	B2	3/2014	Bridges et al.	
8,683,709	B2	4/2014	York	
8,699,007	B2	4/2014	Becker et al.	
8,705,012	B2	4/2014	Greiner et al.	
8,705,016	B2	4/2014	Schumann et al.	
8,718,837	B2	5/2014	Wang et al.	
8,784,425	B2	7/2014	Ritchey et al.	
8,797,552	B2	8/2014	Suzuki et al.	
8,830,485	B2	9/2014	Chow et al.	
2004/0119020	A1	6/2004	Bodkin	
2005/0188557	A1	9/2005	Raab et al.	
2006/0066836	A1 *	3/2006	Bridges et al.	356/5.13
2006/0182314	A1 *	8/2006	England et al.	382/106
2006/0244746	A1 *	11/2006	England et al.	345/419
2007/0171394	A1 *	7/2007	Steiner et al.	356/5.01
2008/0218728	A1 *	9/2008	Kirschner	356/4.01
2009/0322859	A1	12/2009	Shelton et al.	
2009/0323121	A1	12/2009	Valkenburg et al.	
2010/0095542	A1	4/2010	Ferrari	
2010/0321152	A1	12/2010	Argudyaev et al.	
2011/0001958	A1	1/2011	Bridges et al.	
2012/0069352	A1	3/2012	Ossig et al.	
2012/0113913	A1	5/2012	Tirola et al.	
2012/0140244	A1	6/2012	Gittinger et al.	
2012/0217357	A1	8/2012	Franke	
2012/0260512	A1	10/2012	Kretschmer et al.	
2012/0260611	A1	10/2012	Jones et al.	
2012/0262700	A1	10/2012	Schumann et al.	
2012/0287265	A1	11/2012	Schumann et al.	
2013/0010307	A1	1/2013	Greiner et al.	
2013/0025143	A1	1/2013	Bailey et al.	
2013/0025144	A1	1/2013	Briggs et al.	
2013/0027515	A1	1/2013	Vinther et al.	
2013/0062243	A1	3/2013	Chang et al.	
2013/0070250	A1	3/2013	Ditte et al.	
2013/0094024	A1	4/2013	Ruhland et al.	
2013/0097882	A1	4/2013	Bridges et al.	
2013/0125408	A1	5/2013	Atwell et al.	
2013/0162472	A1	6/2013	Najim et al.	
2013/0176453	A1	7/2013	Mate et al.	
2013/0201487	A1	8/2013	Ossig et al.	
2013/0205606	A1	8/2013	Briggs et al.	
2013/0212889	A9	8/2013	Bridges et al.	
2013/0222816	A1	8/2013	Briggs et al.	
2013/0300740	A1	11/2013	Snyder et al.	
2014/0002608	A1	1/2014	Atwell et al.	
2014/0049784	A1	2/2014	Woloschyn et al.	

2014/0063489	A1	3/2014	Steffey et al.
2014/0226190	A1	8/2014	Bridges et al.
2014/0240690	A1	8/2014	Newman et al.
2014/0362424	A1	12/2014	Bridges et al.

FOREIGN PATENT DOCUMENTS

CN	1307241	A	8/2001
CN	2508896	Y	9/2002
CN	2665668	Y	12/2004
CN	1630804	A	6/2005
CN	1630805	A	6/2005
CN	1688867	A	10/2005
CN	1735789		2/2006
CN	1812868	A	8/2006
CN	1818537	A	8/2006
CN	1838102	A	9/2006
CN	1839293	A	9/2006
CN	1853084	A	10/2006
CN	1926400	A	3/2007
CN	101024286	A	8/2007
CN	101156043	A	4/2008
CN	101163939	A	4/2008
CN	101371099	A	2/2009
CN	101416024		4/2009
CN	101484828		7/2009
CN	201266071	Y	7/2009
CN	101506684		8/2009
CN	101511529	A	8/2009
DE	2216765	A1	4/1972
DE	3227980	A1	5/1983
DE	3245060	A1	7/1983
DE	3340317	A1	8/1984
DE	4027990	C1	2/1992
DE	4222642	A1	1/1994
DE	4340756	A1	6/1994
DE	4303804	A1	8/1994
DE	4445464	A1	7/1995
DE	4410775	A1	10/1995
DE	4412044	A1	10/1995
DE	29622033		2/1997
DE	19543763	A1	5/1997
DE	19601875	A1	7/1997
DE	19607345	A1	8/1997
DE	19720049	A1	11/1998
DE	19811550	A1	9/1999
DE	19820307	A1	11/1999
DE	19850118	A1	5/2000
DE	19928958	A1	11/2000
DE	10114126	A1	10/2001
DE	10026357	A1	1/2002
DE	20208077	U1	5/2002
DE	10137241	A1	9/2002
DE	10155488	A1	5/2003
DE	10219054	A1	11/2003
DE	10232028		2/2004
DE	10336458	A1	2/2004
DE	10244643	A1	4/2004
DE	20320216	U1	4/2004
DE	10304188	A1	8/2004
DE	10326848	A1	1/2005
DE	202005000983	U1	3/2005
DE	10361870	A	7/2005
DE	102004015668	B3	9/2005
DE	102004015111	A1	10/2005
DE	102004028090	A1	12/2005
DE	103 61 870	B4	5/2006
DE	202006005643	U1	8/2006
DE	102004010083	B4	11/2006
DE	102005043931	A1	3/2007
DE	102005056265	A1	5/2007
DE	102006053611	A1	5/2007
DE	102005060967	A1	6/2007
DE	102006023902		11/2007
DE	102006024534	A1	11/2007
DE	102006035292	A1	1/2008
DE	202006020299	U1	5/2008
DE	102007037162	A1	2/2009
DE	102008014274	A1	8/2009

(56)

References Cited

FOREIGN PATENT DOCUMENTS

DE 102008039838 A1 3/2010
 DE 102005036929 B4 6/2010
 DE 102008062763 B3 7/2010
 DE 102009001894 A1 9/2010
 DE 102009035336 B3 11/2010
 DE 102009055988 3/2011
 DE 102010032726 B3 11/2011
 DE 102010032725 A1 1/2012
 DE 202011051975 U1 2/2013
 DE 102012107544 B3 5/2013
 DE 102012109481 A1 4/2014
 EP 0546784 A2 6/1993
 EP 0667549 A2 8/1995
 EP 0727642 A1 8/1996
 EP 0730210 A1 9/1996
 EP 0614517 3/1997
 EP 0838696 A1 4/1998
 EP 0949524 A1 10/1999
 EP 1160539 12/2001
 EP 1189124 A1 3/2002
 EP 0767357 B1 5/2002
 EP 1310764 A2 5/2003
 EP 1342989 A2 9/2003
 EP 1347267 A1 9/2003
 EP 1361414 A1 11/2003
 EP 1452279 9/2004
 EP 1468791 A1 10/2004
 EP 1056987 B1 4/2005
 EP 1528410 A1 5/2005
 EP 1669713 A1 6/2006
 EP 1734425 12/2006
 EP 1429109 B1 4/2007
 EP 1764579 12/2007
 EP 1878543 A2 1/2008
 EP 1967930 A2 9/2008
 EP 2003419 A1 12/2008
 EP 2023077 A1 2/2009
 EP 2042905 A1 4/2009
 EP 2060530 A1 5/2009
 EP 2068067 A1 6/2009
 EP 2068114 6/2009
 EP 2108917 A1 10/2009
 EP 2177868 A2 4/2010
 EP 2259013 A1 12/2010
 EP 2400261 A1 12/2011
 FR 2603228 A1 3/1988
 FR 2935043 A1 2/2010
 GB 894320 4/1962
 GB 1112941 5/1968
 GB 2222695 A 3/1990
 GB 2255648 A 11/1992
 GB 2336493 A 10/1999
 GB 2341203 A 3/2000
 GB 2388661 A 11/2003
 GB 2420241 A 5/2006
 GB 2447258 A 9/2008
 GB 2452033 A 2/2009
 JP 5581525 6/1955
 JP 575584 A 1/1982
 JP 58171291 A 1/1983
 JP 5827264 2/1983
 JP S58171291 A 10/1983
 JP 59133890 A 8/1984
 JP 61062885 A 3/1986
 JP S61157095 A 7/1986
 JP 63135814 A 6/1988
 JP 0357911 A 3/1991
 JP 04115108 A 4/1992
 JP 04225188 8/1992
 JP 04267214 A 9/1992
 JP 0572477 A 3/1993
 JP 06313710 A 11/1994
 JP 1994313710 A 11/1994
 JP 06331733 12/1994
 JP 06341838 12/1994

JP 074950 A 1/1995
 JP 07128051 A 5/1995
 JP 7210586 A 8/1995
 JP 07229963 A 8/1995
 JP 0815413 A 1/1996
 JP 0821714 A 1/1996
 JP 08129145 A 5/1996
 JP 08136849 A 5/1996
 JP 08262140 A 10/1996
 JP 0921868 1/1997
 JP 10213661 A 8/1998
 JP 1123993 A 1/1999
 JP 2001056275 A 8/1999
 JP 2000121724 A 4/2000
 JP 2000249546 A 9/2000
 JP 2000339468 A 12/2000
 JP 2001013001 A 1/2001
 JP 2001021303 A 1/2001
 JP 2011066211 A 3/2001
 JP 2001337278 A 12/2001
 JP 2003050128 A 2/2003
 JP 2003156330 A 5/2003
 JP 2003156562 A 5/2003
 JP 2003194526 A 7/2003
 JP 2003202215 A 7/2003
 JP 2003216255 A 7/2003
 JP 2003308205 A 10/2003
 JP 2004109106 A 4/2004
 JP 2004245832 A 9/2004
 JP 2004257927 A 9/2004
 JP 2004333398 A 11/2004
 JP 2004348575 A 12/2004
 JP 2005030937 A 2/2005
 JP 2005055226 A 3/2005
 JP 2005069700 A 3/2005
 JP 2005174887 A 6/2005
 JP 2005517908 6/2005
 JP 2005215917 A 8/2005
 JP 2005221336 A 8/2005
 JP 2005257510 A 9/2005
 JP 2006038683 A 2/2006
 JP 2006102176 A 4/2006
 JP 2006203404 A 8/2006
 JP 2006226948 A 8/2006
 JP 2006241833 A 9/2006
 JP 2006266821 A 10/2006
 JP 2006301991 A 11/2006
 JP 2007514943 A 6/2007
 JP 2007178943 A 7/2007
 JP 2008076303 A 4/2008
 JP 2008082707 A 4/2008
 JP 2008096123 A 4/2008
 JP 2008107286 A 5/2008
 JP 2008304220 A 12/2008
 JP 2009063339 A 3/2009
 JP 2009524057 6/2009
 JP 2009531674 A 9/2009
 JP 2009229255 A 10/2009
 JP 2009541758 A 11/2009
 JP 2010169405 A 8/2010
 JP 2013516928 A 5/2013
 JP 2013517508 A 5/2013
 JP 2013117417 A 6/2013
 JP 2013543970 A 12/2013
 WO 8801924 A1 3/1988
 WO 8905512 A1 6/1989
 WO 9208568 A1 5/1992
 WO 9711399 3/1997
 WO 9808050 A1 2/1998
 WO 9910706 A1 3/1999
 WO 0014474 3/2000
 WO 0020880 A2 4/2000
 WO 0026612 A1 5/2000
 WO 0033149 6/2000
 WO 0034733 6/2000
 WO 0063645 A1 10/2000
 WO 0063681 A2 10/2000
 WO 0177613 A1 10/2001
 WO 02084327 A2 10/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	02101323	A2	12/2002
WO	2004096502	A1	11/2004
WO	2005008271	A2	1/2005
WO	2005059473	A2	6/2005
WO	2005072917	A1	8/2005
WO	2005075875		8/2005
WO	2005100908	A1	10/2005
WO	2006000552	A1	1/2006
WO	2006014445	A1	2/2006
WO	2006051264	A1	5/2006
WO	2006053837	A1	5/2006
WO	2007002319	A1	1/2007
WO	2007012198	A1	2/2007
WO	2007028941		3/2007
WO	2007051972	A1	5/2007
WO	2007087198	A1	8/2007
WO	2007118478	A1	10/2007
WO	2007125081	A1	11/2007
WO	2007144906	A1	12/2007
WO	2008019856	A1	2/2008
WO	2008027588	A2	3/2008
WO	2008047171	A1	4/2008
WO	2008048424	A2	4/2008
WO	2008052348	A1	5/2008
WO	2008064276	A3	5/2008
WO	2008066896		6/2008
WO	2008068791	A1	6/2008
WO	2008075170	A1	6/2008
WO	2008121073	A1	10/2008
WO	2008157061	A1	12/2008
WO	2009001165	A1	12/2008
WO	2009016185	A1	2/2009
WO	2009053085	A1	4/2009
WO	2009083452	A1	7/2009
WO	2009095384	A2	8/2009
WO	2009123278	A1	10/2009
WO	2009127526	A1	10/2009
WO	2009130169	A1	10/2009
WO	2009149740	A1	12/2009
WO	2010040742	A1	4/2010
WO	2010092131	A1	8/2010
WO	2010108089	A2	9/2010
WO	2010108644	A1	9/2010
WO	2010148525	A1	12/2010
WO	2011000435	A1	1/2011
WO	2011000955	A1	1/2011
WO	2011021103	A1	2/2011
WO	2011029140	A1	3/2011
WO	2011057130	A2	5/2011
WO	2011060899	A1	5/2011
WO	2011002908	A1	6/2011
WO	2011090829	A2	7/2011
WO	2011090895	A1	7/2011
WO	2012037157	A2	3/2012
WO	2012038446	A1	3/2012
WO	2012061122	A1	5/2012
WO	2012013525	A2	8/2012
WO	2012103525	A2	8/2012
WO	2012112683	A2	8/2012
WO	2012125671	A1	9/2012
WO	2013112455	A1	8/2013
WO	2013188026	A1	12/2013
WO	2013190031	A1	12/2013
WO	2014128498	A2	8/2014

OTHER PUBLICATIONS

Decision Revoking the European Patent (Art. 101(3)(b) EPC) dated Aug. 14, 2013, filed in Opposition re Application No. 07 785 873.6/ Patent No. 2 062 069, Proprietor: Faro Technologies, Inc., filed by Leica Geosystem AG on Feb. 5, 2013, 12 pages.

Faro Laser Scanner LS, Recording Reality's Digital Fingerprint, The Measure of Success, Rev. Aug. 22, 2005.

Faro Laserscanner LS, Presentation Forensic Package, Policeschool of Hessen, Wiesbaden, Germany, Dec. 14, 2005; Faro Technologies, Copyright 2008.

Haag, et al., "Technical Overview and Application of 3D Laser Scanning for Shooting Reconstruction and Crime Scene Investigations", Presented at the American Academy of Forensic Sciences Scientific Meeting, Washington, D.C., Feb. 21, 2008.

Howard, et al., "Virtual Environments for Scene of Crime Reconstruction and Analysis", Advanced Interfaces Group, Department of Computer Science, University of Manchester, Manchester, UK, Feb. 28, 2000.

Ingensand, H., Dr., "Introduction to Geodetic Metrology", "Einführung in die Geodatische Messtechnik", Federal Institute of Technology Zurich, 2004, with English translation.

Langford, et al., "Practical Skills in Forensic Science", Pearson Education Limited, Essex, England, First Published 2005, Forensic Chemistry.

Leica Geosystems, FBI Crime Scene Case Study, Tony Grissim, Feb. 2006.

Leica Geosystems, TruStory Forensic Analysis by Albuquerque Police Department, 2006.

Leica TPS800 Performance Series—Equipment List, 2004.

Provision of a copy of the minutes in accordance with Rule 124(4) EPC dated Aug. 14, 2013, filed in Opposition re Application No. 07 785 873.6/Patent No. 2 062 069, Proprietor: Faro Technologies, Inc., filed by Leica Geosystem AG on Feb. 5, 2013.

Se, et al., "Instant Scene Modeler for Crime Scene Reconstruction", MDA, Space Missions, Ontario, Canada, Copyright 2005, IEEE.

The Scene, Journal of the Association for Crime Scene Reconstruction, Apr.-Jun. 2006, vol. 12, Issue 2.

Huebner, Siegfried F., "Sniper Shooting Techniques, Schartschutzen-Schiesstechnik", 1989, with English Translation.

Davidson, A. et al., "MonoSLAM: Real-Time Single Camera SLAM", IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 29, No. 6, Jun. 1, 2007, pp. 1052-1067, XP011179664.

Gebre, Biruk A., et al., "Remotely Operated and Autonomous Mapping System (ROAMS)", Technologies for Practical Robot Applications, TEPPRA 2009, IEEE International Conference on Nov. 9, 2009, pp. 173-178, XP031570394.

Harrison A. et al., "High Quality 3D Laser Ranging Under General Vehicle Motion", 2008 IEEE International Conference on Robotics and Automation, May 19-23, 2008, pp. 7-12, XP031340123.

May, S. et al., "Robust 3D-Mapping with Time-of-Flight Cameras", Intelligent Robots and Systems, IROS 2009, IEEE/RSJ International Conference on Oct. 10, 2009, pp. 1673-1678, XP031581042.

Ohno, K. et al., "Real-Time Robot Trajectory Estimation and 3D Map Construction Using 3D Camera", Intelligent Robots and Systems, 2006 IEEE/RSJ International Conference on Oct. 1, 2006, pp. 5279-5285, XP031006974.

Surmann, H. et al., "An Autonomous Mobile Robot with a 3D Laser Range Finder for 3D Exploration and Digitalization of Indoor Environments", Robotics and Autonomous Systems, Elsevier Science Publishers, vol. 45, No. 3-4, Dec. 31, 2003, pp. 181-198.

Yan, R., et al., "3D Point Cloud Map Construction Based on Line Segments with Two Mutually Perpendicular Laser Sensors", 2013 13th International Conference on Control, Automation and Systems (ICCAS 2013), IEEE, Oct. 20, 2013, pp. 1114-1116.

Ye, C. et al., "Characterization of a 2-D Laser Scanner for Mobile Robot Obstacle Negotiation" Proceedings / 2002 IEEE International Conference on Robotics and Automation, May 11-15, 2002, Washington, D.C., May 1, 2002, pp. 2512-2518, XP009169742.

YK Cho, et al. "Light-weight 3D LADAR System for Construction Robotic Operations" (pp. 237-244); 26th International Symposium on Automation and Robotics in Construction (ISARC 2009), Jun. 24, 2009.

Williams, J.A., et al., Evaluation of a Novel Multiple Point Set Registration Algorithm, Copyright 2000, [Retrieved on Jan. 18, 2010 at 04:10 from IEEE Xplore].

Hart, A., "Kinematic Coupling Interchangeability", Precision Engineering, vol. 28, No. 1, Jan. 1, 2004, pp. 1-15, XP55005507, ISSN: 0141-6359, DOI: 10.1016/S0141-6359(03)00071-0.

HYDROpro Navigation, Hydropgraphic Survey Software, Trimble, www.trimble.com, Copyright 1997-2003.

(56)

References Cited

OTHER PUBLICATIONS

Information on Electro-Optical Information Systems; EOIS 3D Mini-Moire C.M.M. Sensor for Non-Contact Measuring & Surface Mapping; Direct Dimensions, Jun. 1995.

iQsun Laserscanner Brochure, 2 pages, Apr. 2005.

It is Alive in the Lab, Autodesk University, Fun with the Immersion MicroScribe Laser Scanner, [online], [retrieved Nov. 29, 2011], http://labs.blogs.com/its_alive_in_the_lab/2007/11/fun-with-the-im.html; 3 pages.

J. Geng "Structured-Light 3D Surface Imaging: A Tutorial," *Advances in Optics and Photonics* 3; Mar. 31, 2011, pp. 128-160; IEEE Intelligent Transportation System Society; 2011 Optical Society of America.

Jasiobedzki, Piotr, "Laser Eye—A New 3D Sensor for Active Vision", *SPIE—Sensor Fusion VI*, vol. 2059, Sep. 7, 1993, pp. 316-321, XP00262856, Boston, U.S.A., Retrieved from the Internet: URL:<http://scitation.aip.org/getpdf/servlet/Ge>.

Jasperneite, et al., Enhancements to the Time Synchronization Standard IEEE-1588 for a System of Cascaded Bridges, IEEE, 2004.

JGeng "DLP-Based Structured Light 3D Imaging Technologies and Applications" (15 pages) *Emerging Digital Micromirror Device Based Systems and Application III*; edited by Michael R. Douglass, Patrick I. Oden, *Proc. of SPIE*, vol. 7932, 79320B; (2011) SPIE.

Umeda, K., et al., Registration of Range and Color Images Using Gradient Constraints and Ran Intensity Images, *Proceedings of the 17th International Conference on Pattern Recognition (ICPR'04)*, Copyright 2010 IEEE. [Retrieved online Jan. 28, 2010—IEEE.

Kreon Laser Scanners, Getting the Best in Cutting Edge 3D Digitizing Technology, B3-D MCAD Consulting/Sales [online], [retrieved Nov. 29, 2011], <http://www.b3-d.com/Kreon.html>.

Laser Reverse Engineering with Microscribe, [online], [retrieved Nov. 29, 2011], http://www.youtube.com/watch?v=8VRz_2aEJ4E&feature=Playlist&p=F63ABF74F30DC81B&playnext=1&playnext_from=PL&index=1.

Leica Geosystems: "Leica Rugby 55 Designed for Interior Built for Construction", Jan. 1, 2009, XP002660558, Retrieved from the Internet: URL:http://www.leica-geosystems.com/downloads123/zz/lasers/Rugby%2055/brochures/Leica_Rugby_55_brochure_en.pdf [re.

Leica Rugby 55 Designed for Interior Built for Construction Brochure, Leica Geosystems, Heerbrugg, Switzerland, www.leica-geosystems.com.

Merriam-Webster (m-w.com), "Interface". 2012. <http://www.merriam-webster.com/dictionary/interface>.

Merriam-Webster (m-w.com), "Parts". 2012. <http://www.merriam-webster.com/dictionary/parts>.

Merriam-Webster (m-w.com), "Traverse". 2012. <http://www.merriam-webster.com/dictionary/traverse>.

MG Lee; "Compact 3D LIDAR based on optically coupled horizontal and vertical Scanning mechanism for the autonomous navigation of robots" (13 pages) vol. 8037; downloaded from <http://proceedings.spiedigitallibrary.org/> on Jul. 2, 2013.

MicroScan 3D User Guide, RSI GmbH, 3D Systems & Software, Oberursel, Germany, email: info@rsi-gmbh.de, Copyright RSI Roland Seifert Imaging GmbH 2008.

Moog Components Group "Technical Brief; Fiber Optic Rotary Joints" Document No. 303 (6 pages) Mar. 2008; MOOG, Inc. 2008 Canada; Focal Technologies.

Moog Components Group; "Fiber Optic Rotary Joints; Product Guide" (4 pages) Dec. 2010; MOOG, Inc. 2010.

Non-Final Office Action, Issued Mar. 23, 2015.

P Ben-Tzvi, et al "Extraction of 3D Images Using Pitch-Actuated 2D Laser Range Finder for Robotic Vision" (6 pages) BNSDOCID <XP 31840390A_1_>, Oct. 15, 2010.

Trimble—Trimble SPS630, SPS730 and SPS930 Universal Total Stations, [on-line] http://www.trimble.com/sps630_730_930.shtml (1 of 4), [Retrieved Jan. 26, 2010 8:50:29AM].

Romer "Romer Absolute Arm Maximum Performance Portable Measurement" (Printed 2010); Hexagon Metrology, Inc., <http://us.Romer.com>; 2010.

Surman et al. "An autonomous mobile robot with a 3D laser range finder for 3D exploration and digitalization of indoor environments." *Robotics and Autonomous Systems* vol. 45 No. 3-4, Dec. 31, 2003, pp. 181-198. Amsterdam, Netherlands.

Willoughby, P., "Elastically Averaged Precisoion Alignment", In: "Doctoral Thesis", Jun. 1, 2005, Massachusetts Institute of Technology, XP55005620, abstract 1.1 Motivation, Chapter 3, Chapter 6.

Romer "Romer Absolute Arm Product Brochure" (2010); Hexagon Metrology; www.hexagonmetrology.com; Hexagon AB 2010.

Romer "Romer Measuring Arms Portable CMMs for R&D and shop floor" (Mar. 2009) Hexagon Metrology (16 pages).

Romer Measuring Arms; Portable CMMs for the shop floor; 20 pages; Hexagon Metrology, Inc. (2009) <http://us.Romer.com>.


RW Boyd "Radiometry and the Detection of Optical Radiation" (pp. 20-23) 1983 Jon Wiley & Sons, Inc.


Sauter, et al., Towards New Hybrid Networks for Industrial Automation, IEEE, 2009.




Spada, et al., IEEE 1588 Lowers Integration Costs in Continuous Flow Automated Production Lines, XP-002498255, ARC Insights, Insight # 2003-33MD&H, Aug. 20, 2003.

International Search Report for International Application No. PCT/EP2007/005789 mailed Oct. 30, 2007.

* cited by examiner










Fig.6

METHOD AND AN APPARATUS FOR CAPTURING THREE-DIMENSIONAL DATA OF AN AREA OF SPACE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS REFERENCE

This is a U.S. national stage of application No. PCT/EP2007/005789, filed on 29 Jun. 2007. Priority under 35 U.S.C. §119(a) and 35 U.S.C. §365(b) is claimed from German Application No. 10 2006 031 580.4, filed 3 Jul. 2006, the disclosure of which is also incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to a method for capturing three-dimensional data of an area of space, comprising the steps of:

- providing a laser scanner having a transmitter and a receiver,
- sending out a plurality of measuring beams by means of the transmitter to a plurality of measuring points in the area of space,
- receiving a plurality of reflected beams which are reflected by the measuring points, and
- determining a plurality of distances to the plurality of measuring points as a function of the reflected beams.

The invention also relates to an apparatus for capturing three dimensional data of an area of space, comprising a laser scanner having a transmitter and a receiver, the transmitter being configured for sending out a plurality of measuring beams to a plurality of measuring points in the area of space, the receiver being configured for receiving a plurality of reflected beams which are reflected by the measuring points and for determining a plurality of distances to the plurality of measuring points as a function of the reflected beams.

Such a method and such an apparatus are known, for example, from DE 103 61 870 B4.

This document discloses a laser scanner comprising a measuring head which holds a rotor rotatably supported. The rotor is rotated about a horizontal axis whilst sending out a plurality of laser beams. Due to the rotation of the rotor, the laser beams are sent out into a plurality of directions in space which cover an elevation angle of 270° or more. In addition, the measuring head is rotated about a vertical axis so that the laser beams sent out almost completely scan the surrounding area of space. In the measuring head, a receiver is arranged which receives the reflected beams reflected from object points in the area of space and which determines the distances to the object points by means of a difference in delay time between the beams sent out and the received beams. In addition, the receiver generates for each measuring point a gray scale value which depends on the intensity of the reflected measuring beam. Altogether, this known laser scanner can be used for recording a three-dimensional image of an area of space, the plurality of gray scale values producing an all-rotund image which is comparable to a black/white recording of the area of space. In addition, a distance information item is provided for each measuring point so that the area of space can be examined more accurately, surveyed and/or documented later by

means of the recorded data. A typical application for such a laser scanner is the surveying of factory halls in which, for example, a new production line is to be planned and set up. In another known application, such a laser scanner is moved through a tunnel tube (if necessary without rotation about the vertical axis) in order to check, e.g., the state of the tunnel and determine the clear width at every point in the tunnel.

In principle, such a laser scanner is suitable for capturing three-dimensional data of any area of space which is bounded by objects such as walls or natural obstacles. The relatively fast and extensive data acquisition including an “optical image” of the area of space in an all-round view also allows such a laser scanner to be advantageous for forensic applications, i.e. the coverage and documentation of crime scenes. However, forensic coverage of a crime scene requires further information which cannot be supplied by laser scanners hitherto known. This includes primarily information about the location and the course of bullet channels produced when a projectile penetrates into a wall or into another obstacle.

For the forensic coverage of bullet channels, rods marked with [colours] *colors* are used today which rods are inserted into a bullet channel in such a manner that a [proximal end] *proximal-portion* of the rods [protrudes] *protrude* from the entry opening of the bullet channel. These rods can be used for identifying the orientation of the bullet channel. Suitable rods are offered, for example, by the Lightning Powder Company, Inc., 13386 International Parkway, Jacksonville, Fla. 32218, USA.

Against this background, it is an object of the present invention to improve a method and an apparatus of the type initially mentioned in order to open up new applications. In particular, it is an object of the invention to facilitate the forensic data capture of an area of space.

SUMMARY OF THE INVENTION

According to one aspect of the present invention, this object is achieved by a method of the type initially mentioned in which the area of space comprises at least one object which contains a hidden channel having a visible entry opening, a rod-shaped element being inserted into the channel in such a manner that a [free end] *proximal portion freely* protrudes from the entry opening, a first distance to a first measuring point at the [free end] *proximal portion* and at least one second distance to a second measuring point at the [free end] *proximal portion* are determined, and an orientation of the hidden channel is determined as a function of the first and second distances.

According to another aspect of the invention, this object is achieved by an apparatus of the type initially mentioned in which the receiver is also configured for determining an orientation of a rod-shaped element having a [free end] *proximal portion* which protrudes from an entry opening of a hidden channel at an object in the area of space by the receiver determining a first distance to a first measuring point at the [free end] *proximal portion* and at least one second distance to a second measuring point at the [free end] *proximal portion*.

The present invention can be used for determining the orientation of a bullet channel or any other channel hidden in an object from the data which are acquired by means of the laser scanner. The capabilities of the known laser scanner are extended because the laser scanner, somehow, can “look into” the object by means of the rod-shaped element. As can be easily understood, the novel method and the novel apparatus are particularly well suited for the forensic data capture of crime scenes in which firearms were used. In addition, however, the novel method and the novel apparatus can also be

3

used for other purposes in which the orientation of a channel hidden in an object is to be documented and surveyed, for example for documenting drilled holes in building walls.

The novel method and the novel apparatus have the advantage that the orientation of the channel can be determined very rapidly and with high accuracy, the data for determining the orientation being acquired at the same time as the “remaining” area of space is measured three-dimensionally. It is particularly advantageous that the orientation of the channel can be marked in the “optical image” of the area of space which facilitates documentation and later analysis.

The above-mentioned object is thus completely achieved.

In a preferred embodiment of the invention, the rod shaped element has a rod-shaped distal [area] *portion* and a proximal [area] *portion*, the rod-shaped distal [area] *portion* being configured for insertion into the hidden channel and the proximal [area] *portion* having at least one enlarged body at which the first and second measuring [point] *points* are arranged. The first and second measuring point are preferably arranged at a relative distance from one another along the rod-shaped element, the relative distance preferably being approximately 10 cm or more. The distal [area] *portion* preferably has an outside diameter between about 0.2 cm and 1 cm. The outside diameter of the enlarged body is preferably between about 2 cm and 15 cm, furthermore preferably between about 5 cm and 10 cm.

Providing the rod-shaped element with a relatively thin distal [area] *portion* and a thickened proximal [area] *portion* facilitates precise and unambiguous determination of the orientation. The relatively thin distal [end] *portion* enables the rod-shaped element to be inserted into narrow bullet channels, drilled holes etc. On the other hand, the enlarged body at the proximal [area] *portion* facilitates unambiguous identification of the rod-shaped element and thus a more reliable and accurate determination of the orientation. This was not to be expected at the beginning because an increase in measuring accuracy is typically achieved by means of a “fine” measuring instrument. In the present embodiment, however, an enlarged body is used which exceeds the dimensions of the hidden channel by 10- to 20-times in preferred embodiments. However, it has been found that the enlarged body can be surveyed in its own dimensions due to the three-dimensional coverage of the area of space which then enables the orientation to be determined mathematically with increased accuracy.

In a further embodiment, the distal [area] *portion* defines a longitudinal axis and the at least one body has a center point which is essentially located on the longitudinal axis.

In this embodiment, the body is arranged approximately coaxially with respect to the distal [area] *portion* of the rod-shaped element. This facilitates the exact determination of the orientation. In addition, the rotational position of the rod-shaped element about its longitudinal axis is not important in this embodiment so that the rod-shaped element can be positioned in the channel in a simpler and quicker manner.

In a further embodiment, a plurality of body distances to a plurality of measuring points at the at least one body are determined and the center point is determined as a function of the plurality of body distances.

In this embodiment, the body itself is surveyed in order to determine its center point as precisely as possible. The more accurately it is possible to determine the center point of the body, the more accurately it is possible to determine the orientation of the hidden channel.

In a preferred refinement of this embodiment, the body has a defined geometric shape and an ideal image of this geometric shape is matched to a cloud of points which represents the plurality of body distances. For example, the matching can

4

take place in accordance with the method of least squares. This embodiment enables the orientation of the hidden channel to be determined accurately even when the surveying of the body is burdened with high measurement noise.

In a further embodiment, each reflected beam has a beam intensity and the orientation is also determined as a function of the beam intensities.

In this embodiment, it is not only the distance information but also the beam intensities which are used for determining the position and alignment of the at least one body. Since the accuracy with which the orientation can be determined depends on the accuracy with which the body is surveyed, this embodiment enables the measuring accuracy to be further improved.

In a further embodiment, the at least one body has an elongated shape, particularly a cylindrical shape.

In this embodiment, the body has a defined main direction which is advantageously coaxial with the orientation sought. Using such a body facilitates the determination of the orientation and increases the measuring accuracy. The longer the elongated shape, the more it is possible to detect measuring points which are further apart by means of the laser scanner. Measuring points which are far apart reduce measuring errors which can be produced due to tolerances and/or measurement noise.

In a further embodiment, the rod-shaped element comprises at least two bodies which are arranged at a relative distance from one another.

This embodiment, too, provides for measuring points which are far apart on the rod-shaped element and, in consequence, a reduction in measuring errors. This embodiment is particularly advantageous if the at least two bodies have the same shape because identical algorithms can then be used for determining the center [point] *points*. Compared with a single elongated body, this embodiment has the advantage that the [free] *freely protruding* proximal [end] *portion* is loaded by a lighter weight which reduces bending of the rod-shaped element.

In a further embodiment, the at least two bodies are spheres. As an alternative, the at least two bodies can be cubes or other geometric elements.

Spheres enable the center point to be determined in a relatively simple and precise manner which is largely independent of the direction of view or the angle of view of the laser scanner. Spheres are therefore generally preferred as bodies. By comparison, cubic bodies have the advantage that the rod shaped element cannot roll away which facilitates practical handling and transportation.

In a further embodiment, the hidden channel is a bullet channel and an assumed position of a gunman within the area of space is determined as a function of the orientation. The determination of the assumed position is advantageously automatic by looking for a position which approximately corresponds to the size of a gunman along the orientation.

This embodiment represents a particularly preferred application of the novel method and of the novel apparatus because it simplifies and accelerates the forensic data capture of a crime scene.

In a further embodiment, the rod-shaped element comprises a marking 80 (see FIG. 3, for example) in the distal [area] *portion* 68, which marking 80 has more reflective and less reflective sections.

Using this embodiment, the depth of the hidden channel can be documented in a very simple manner since the sections with different reflectivity lead to different beam intensities of the reflected beams. Such a marking 80 is therefore clearly

5

visible in the optical image and it can be identified in a relatively quick and simple manner in the recorded data.

It goes without saying that the features mentioned above and those yet to be explained in the following can be used not only in the combination specified in each case but also in other combinations or by themselves without departing from the scope of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Illustrative embodiments of the invention are shown in the drawing and will be explained in greater detail in the following description.

FIG. 1 shows a simplified representation of a preferred illustrative embodiment of the invention,

FIG. 2 shows a laser scanner which is used in the illustrative embodiment according to FIG. 1, in a partially cut side view,

FIGS. 3 to 5 show various illustrative embodiments of rod-shaped elements according to the present invention, and

FIG. 6 shows a simplified flowchart for explaining an illustrative embodiment of the method according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

In FIG. 1, a laser scanner according to an embodiment of the present invention is designated by the reference number 10 overall. The laser scanner 10 has a measuring head 12 which is arranged on a tripod 14 in this case. The measuring head 12 can be rotated on the tripod 14 about a vertical axis 16 which is indicated by an arrow 18.

The measuring head 12 has an approximately U-shaped housing. Between the two housing legs, a rotor 20 is arranged which can be rotated about a horizontal axis 22 as is indicated by the arrow 24. The rotor 20 has an exit window from which a measuring beam Ls can emerge. The measuring beam Ls extends along a beam axis 26 to a measuring point 28 on an object 30. The measuring beam is reflected from the measuring point 28 and passes back to the measuring head 12 as reflected beam Lr where the reflected beam Lr encounters the rotor 20 and is detected by a detector, not shown here. From the time difference between sending out of the measuring beam Ls and the reception of the reflected beam Lr, the distance d between the laser scanner 10 and the measuring point 28 can be determined. The measuring beam Ls is advantageously modulated for determining the delay time.

According to a preferred embodiment of the invention, the measuring point 28 is located here in the area of an entry or exit opening of a channel (not shown here) which is hidden in the object 30. To determine the orientation of the channel, the novel apparatus comprises a rod-shaped element 32 which is inserted with a rod-shaped distal [end] portion 68 (best seen with reference to FIG. 2) into the opening of the channel. At [the free] a freely protruding proximal [end] portion 70 (best seen with reference to FIG. 2) of the rod-shaped element 32, a body in the form of a sphere 34 is arranged here.

Reference number 36 designates a person who stands at a position in the area of space 38 from which a shot has presumably been fired, the projectile of which has created the hidden channel in the object 30. This position can be determined from the orientation of the hidden channel by means of the novel method and the novel apparatus.

FIG. 2 shows the laser scanner 10 and the rod-shaped element 32 in further detail. Identical reference symbols designate the same elements as before.

The measuring head 12 has a base 40 on which two support walls 42, 44 are arranged vertically. The support wall 42,

6

together with a housing part 46, forms an internal space in which a light transmitter 48 and a detector 50 are arranged. The light transmitter 48 is here a laser diode, the detector 50 comprises a plurality of light-sensitive elements in a matrix-type arrangement.

Reference number 52 designates an evaluation and control unit which contains a PC-based computing unit in a preferred embodiment. The evaluation and control unit 52 drives the light transmitter 48 in such a manner that it generates a modulated measuring beam Ls. In addition, the evaluation and control unit 52 reads out the detector 50 for determining the distance d and the light intensity of the reflected light beam Lr.

The rotor 20 here carries a mirror 54 which is arranged opposite the transmitter 48 and the detector 50 and which is inclined by 45° with respect to the latter. The rotor 20 is connected to a drive 56 which produces a rotation of the mirror 54 about the horizontal axis 22. Due to this rotation, the measuring beam Ls is deflected along a vertical circular area in the area of space 38.

As already mentioned with respect to FIG. 1, the laser scanner 10 of the present embodiment has a further drive 58 which provides for a rotation of the measuring head 12 about the vertical axis 16. This allows the "vertical fan" spanned by means of the measuring beam Ls to be rotated within the area of space 38 so that the measuring beam Ls can illuminate virtually all object points in the environment of the laser scanner 10. In order to be able to correlate the distance and intensity information with the individual measuring points 28, the drives 56, 58 are provided with encoders 60, 62 by means of which the respective alignment of the measuring beam Ls is determined.

Reference number 66 designates a hidden channel in the object 30, for example a wall. According to an illustrative embodiment of the invention, the distal [end] portion 68 of the rod-shaped element 32 is pushed into the channel 66. The proximal [end] portion 70 of the rod-shaped element 32 protrudes from the entry or exit opening 72 of the channel 66. At the proximal [end] portion 70, two spheres 34a, 34b are arranged here as will still be described in greater detail by means of FIG. 3 in the text which follows.

The rod-shaped element 32 defines a longitudinal axis 74 which corresponds to the orientation of the hidden channel 66. This orientation can be determined in an automated manner by means of the two spheres 34a, 34b by determining the position of the two spheres 34a, 34b by means of the laser scanner 10. The positions of the spheres can be used for determining a vector which represents the orientation 74.

FIG. 3 shows a preferred embodiment of the rod-shaped element 32. The element 32 has a distal [end] portion 68 which is configured for being inserted into the hidden channel. At the proximal [end] portion 70, two spheres 34a, 34b are arranged at a defined distance dss. The outside diameter dr of the rod is here about 0.5 mm. By comparison, the outside diameter ds of the spheres 34a, 34b is of an order of magnitude of about 5 to 10 cm. However, the spheres 34a, 34b can also be smaller or larger, spheres having a larger diameter being more easily identified in the measurement data of the laser scanner 10. On the other hand, spheres having a smaller diameter facilitate the handling of the element 32 and provide for a lesser weight at the [free] freely protruding proximal [end] portion.

In one illustrative embodiment, the spheres 34a, 34b are of polystyrene and are pushed onto the rod of the [rod] rod-shaped element 32. The spheres 34a, 34b can be movable on the rod or can be fixed in their respective position, for example by bonding.

Each sphere 34a, 34b has a center point 76a, 76b of the sphere which is determined in preferred illustrative embodiments of the novel method. As shown in FIG. 3, the center points 76a, 76b of the spheres are here located on the longitudinal axis 74, i.e. the rod of the rod-shaped element 32 passes centrally through the center points 76a, 76b of the spheres.

FIG. 4 shows a further illustrative embodiment of a rod-shaped element 82 which, in principle, corresponds to the element 32 from FIG. 3. However, the element 82 has cubic bodies 84a, 84b instead of the spheres 34a, 34b.

FIG. 5 shows a further illustrative embodiment of a rod-shaped element 86 which has only a single cylindrical body 88 in contrast to the two previous illustrative embodiments.

In the text which follows, a preferred illustrative embodiment of the novel method is described by means of FIG. 6. After all components have been set up and taken into operation, the mirror 54 is positioned according to step 94. According to step 96, the measuring beam Ls is sent out. According to step 98, the reflected beam Lr is received. According to step 100, the evaluation and control unit 52 is then used for determining the distance to the measuring point 28 from the delay time difference. In addition, a gray scale value is determined from the intensity of the reflected beam Lr according to step 102. According to step 104, this is repeated for all positions of the mirror 54 which can be adjusted by means of the two drives 56, 58, in order to obtain a 3D recording of the area of space 38.

Once all measurement data have been recorded, the body or bodies on the rod-shaped element 32, such as, for example, the spheres 34a, 34b, is/are identified according to step 106. Following this, the coordinates of the center points 76a, 76b are determined according to step 108. In preferred embodiments, this is done by fitting ideal spheres into the "clouds of points" which were recorded by means of the laser scanner 10. For example, the fitting-in can take place in accordance with the method of least squares. Following this, the center point coordinates of the spheres fitted in are calculated.

From the center point coordinates calculated, the orientation 74 is determined according to step 110. Following this, the assumed position of the gunman who has fired a projectile which has formed the (bullet) channel 66 is determined according to step 112. For this purpose, a position or position range is sought along the orientation 74 at which a "typical height" above ground intersects the orientation 74. The typical height is within the range of between about 1 m and 1.80 m. As an alternative or additionally, the assumed position of the gunman can be determined by inserting an image of a person along the orientation 74 into the image of the area of space which was recorded by means of the laser scanner 10 (from the intensities of the reflected beams). In further illustrative embodiments, a person 36 can be recorded during the scanning of the area of space 38 so that the coordinates of the person 36 can be compared with the orientation 74.

The invention claimed is:

1. A method for capturing three-dimensional data of an area of space, comprising:
 - providing a laser scanner comprising a transmitter and a receiver,
 - sending out a plurality of measuring beams (Ls) by means of the transmitter to a plurality of measuring points in the area of space,
 - receiving a plurality of reflected beams (Lr) which are reflected by the measuring points, [and]
 - determining a plurality of distances to the plurality of measuring points as a function of the reflected beams (Lr),

determining for each measuring point of the plurality of measuring points a gray scale value that depends on an intensity of respective ones of the plurality of reflected beams (Lr), and

recording a cloud of points, representative of the plurality of measuring points in the area of space, determined as a function of the plurality of distances and respective gray scale values,

wherein the area of space comprises at least one object which contains a hidden channel having a visible entry opening, a rod-shaped element being inserted into the channel in such a manner that a [free end] proximal portion of the rod-shaped element protrudes from the entry opening, [a first distance] the rod-shaped element comprising a defined geometric shape having a first three-dimensional coordinate and at least one second three-dimensional coordinate in the area of space, an ideal image of the geometric shape being matched to the cloud of points that represents measuring points of the geometric shape, the first three-dimensional coordinate to a first measuring point at the [free end] proximal portion and [at least one second distance] the at least one second three-dimensional coordinate to a second measuring point at the [free end] proximal portion being determined using the ideal image that is matched to the cloud of points that represent measuring points of the geometric shape, and an orientation of the hidden channel being determined as a function of a vector between the first and second [distance] three-dimensional coordinates.

2. The method according to claim 1, wherein the rod-shaped element has a rod-shaped distal [area and a proximal area] portion, the rod-shaped distal [area] portion being configured for insertion into the hidden channel and the proximal [area] portion having at least one enlarged body at which the first and second measuring points are arranged.

3. The method according to claim 2, wherein the distal [area] portion defines a longitudinal axis, and that the at least one body has a center point which is essentially located on the longitudinal axis.

4. The method according to claim 3, wherein a plurality of body distances to a plurality of measuring points at the at least one body are determined, and that the center point is determined as a function of the plurality of body distances.

5. The method according to claim 1, wherein each reflected beam (Lr) has a beam intensity, and the orientation is also determined as a function of the beam intensities.

6. The method according to claim [1] 2, wherein the at least one body has an elongated shape, particularly a cylindrical shape.

7. The method according to claim 1, wherein the rod-shaped element comprises at least two bodies arranged at a relative distance (dss) from one another.

8. The method according to claim 7, wherein the at least two bodies are spheres.

9. The method according to claim 7, wherein the at least two bodies are cubes.

10. The method according to claim 1, wherein the hidden channel is a bullet channel, and an assumed position of a gunman within the area of space is determined as a function of the orientation.

11. The method according to claim [1] 2, wherein the rod-shaped element comprises a marking in the distal [area] portion, which marking has more reflective and less reflective sections.

12. The method according to claim 1, wherein the rod-shaped element further comprises a rod-shaped distal [area

9

and a proximal area] *portion*, the rod-shaped distal [area] *portion* being configured for insertion into the hidden channel and the proximal [area] *portion* comprising at least one enlarged body providing at least two measuring points which are different from one another.

13. An apparatus structured to capture three-dimensional data of an area of space, comprising:

a laser scanner having a transmitter and a receiver, the transmitter being configured for sending out a plurality of measuring beams (Ls) to a plurality of measuring points in the area of space, and the receiver being configured to receive a plurality of reflected beams (Lr) which are reflected by the measuring points [and], to determine a plurality of distances to the plurality of measuring points as a function of the reflected beams (Lr), *to determine for each measuring point of the plurality of measuring points a gray scale value that depends on an intensity of respective ones of the plurality of reflected beams (Lr), and to record a cloud of points, representative of the plurality of measuring points in the area of space, determined as a function of the plurality of distances and respective gray scale values, and*

a rod-shaped element comprising a defined geometric shape,

wherein the receiver is [also arranged] *configured* for determining an orientation of a hidden channel at an object in

10

the area of space, wherein [a] *the* rod-shaped element has a [free end] *proximal portion* which protrudes from an entry opening of the hidden channel,

wherein the receiver is configured for: matching an ideal image of the geometric shape to the cloud of points that represent measuring points of the geometric shape, the geometric shape having a first three-dimensional coordinate and at least one second three-dimensional coordinate in the area of space; determining [a first distance] the first three-dimensional coordinate to a first measuring point at the [free end] proximal portion and [at least one second distance] the at least one second three-dimensional coordinate to a second measuring point at the [free end] proximal portion using the ideal image that is matched to the cloud of points that represent measuring points of the geometric shape; and, determining the orientation of the hidden channel as a function of a vector between the first and second three-dimensional coordinates.

14. The apparatus according to claim 13, wherein the rod-shaped element further comprises a rod-shaped distal [area] and a proximal area] *portion*, the rod-shaped distal [area] *portion* being configured for insertion into the hidden channel and the proximal [area] *portion* comprising at least one enlarged body providing at least two measuring points which are different from one another.

* * * * *