

US00RE45884E

(19) **United States**
(12) **Reissued Patent**
Wies et al.

(10) **Patent Number:** **US RE45,884 E**
(45) **Date of Reissued Patent:** **Feb. 9, 2016**

(54) **CHAT INTERFACE WITH HAPTIC FEEDBACK FUNCTIONALITY**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Evan F. Wies**, Old Greenwich, CT (US);
Dean C. Chang, Gaithersburg, MD (US);
Michael P. Ruf, Parkland, FL (US)

EP 0 349 086 1/1990
EP 0 326 439 B1 8/1993

(Continued)

(73) Assignee: **Immersion Corporation**, San Jose, CA (US)

OTHER PUBLICATIONS

Adelstein, "Design and Implementation of a Force Reflecting Manipulandum for Manual Control research," DSC-vol. 42, Advances in Robotics, Edited by H. Kazerooni, pp. 1-12, 1992.

(21) Appl. No.: **13/028,882**

(Continued)

(22) Filed: **Feb. 16, 2011**

Primary Examiner — Mariela Reyes

Assistant Examiner — Thong Vu

Related U.S. Patent Documents

(74) *Attorney, Agent, or Firm* — Miles & Stockbridge P.C.

Reissue of:

(64) Patent No.: **7,493,365**
Issued: **Feb. 17, 2009**
Appl. No.: **11/545,739**
Filed: **Oct. 10, 2006**

(57) **ABSTRACT**

A chat interface allowing a user to exchange haptic chat messages with other users in a chat session over a computer network. A chat interface can be displayed by a local computer and receives input data from a user of the local computer, such as text characters or speech input. The input data provides an outgoing chat message that can include sent force information. The outgoing chat message is sent to a remote computer that is connected to the local host computer via a computer network. The remote computer can display a chat interface and output a haptic sensation to a user of the remote computer based at least in part on the force information in the outgoing chat message. An incoming message from the remote computer can also be received at the chat interface, which may also include received force information. The incoming chat message is displayed on a display device to the user of the local computer. A haptic sensation can be output to the user of the local computer using a haptic device coupled to the local computer, where the haptic sensation is based at least in part on the received force information received from the remote computer.

U.S. Applications:

(63) Continuation of application No. 09/608,129, filed on Jun. 30, 2000, now Pat. No. 7,159,008.

(51) **Int. Cl.**
G06F 15/16 (2006.01)
G06F 3/01 (2006.01)

(52) **U.S. Cl.**
CPC **G06F 3/016** (2013.01)

(58) **Field of Classification Search**
CPC G06F 15/16; G06Q 10/10; H04L 51/00
USPC 709/204; 705/9
See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

3,157,853 A 11/1964 Hirsch
3,220,121 A 11/1965 Cutler

(Continued)

53 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,497,668 A 2/1970 Hirsch
 3,517,446 A 6/1970 Corlyon et al.
 3,902,687 A 9/1975 Hightower
 3,903,614 A 9/1975 Diamond et al.
 4,160,508 A 7/1979 Salsbury
 4,236,325 A 12/1980 Hall et al.
 4,513,235 A 4/1985 Acklam et al.
 4,581,491 A 4/1986 Boothroyd
 4,599,070 A 7/1986 Hladky et al.
 4,708,656 A 11/1987 De Vries et al.
 4,713,007 A 12/1987 Alban
 4,891,764 A 1/1990 McIntosh
 4,930,770 A 6/1990 Baker
 4,934,694 A 6/1990 McIntosh
 4,938,483 A 7/1990 Yavetz
 5,019,761 A 5/1991 Kraft
 5,022,407 A 6/1991 Horch et al.
 5,035,242 A 7/1991 Franklin
 5,038,089 A 8/1991 Szakaly
 5,078,152 A 1/1992 Bond
 5,186,695 A 2/1993 Mangseth et al.
 5,208,745 A 5/1993 Quentin et al.
 5,212,473 A 5/1993 Louis
 5,240,417 A 8/1993 Smithson et al.
 5,271,290 A 12/1993 Fischer
 5,275,174 A 1/1994 Cook
 5,299,810 A 4/1994 Pierce
 5,309,140 A 5/1994 Everett
 5,334,027 A 8/1994 Wherlock
 5,466,213 A 11/1995 Hogan
 5,547,382 A 8/1996 Yamasaki
 5,555,894 A 9/1996 Doyama et al.
 5,629,594 A 5/1997 Jacobus et al.
 5,690,582 A 11/1997 Ulrich et al.
 5,695,400 A 12/1997 Fennell, Jr. et al.
 5,719,561 A 2/1998 Gonzales
 5,721,763 A 2/1998 Joseph et al.
 5,734,373 A 3/1998 Rosenberg et al.
 5,764,916 A 6/1998 Busey et al.
 5,766,016 A 6/1998 Sinclair
 5,785,630 A 7/1998 Bobick et al.
 5,818,836 A 10/1998 DuVal
 5,844,392 A 12/1998 Peurach et al.
 5,880,731 A 3/1999 Liles et al.
 5,884,029 A 3/1999 Brush, II et al.
 5,889,670 A 3/1999 Schuler et al.
 5,907,677 A 5/1999 Glenn et al.
 5,933,599 A 8/1999 Nolan
 5,943,648 A 8/1999 Tel
 5,956,484 A 9/1999 Rosenberg et al.
 5,963,217 A 10/1999 Grayson et al.
 5,973,678 A 10/1999 Stewart et al.
 5,978,467 A 11/1999 Walker et al.
 5,983,190 A 11/1999 Trower et al.
 5,987,503 A 11/1999 Murakami
 6,028,593 A 2/2000 Rosenberg et al.
 6,046,726 A 4/2000 Keyson
 6,047,356 A 4/2000 Anderson et al.
 6,076,100 A 6/2000 Cottrille et al.
 6,101,530 A 8/2000 Rosenberg et al.
 6,108,704 A 8/2000 Hutton et al.
 6,111,577 A 8/2000 Zilles et al.
 6,154,773 A 11/2000 Roberts et al.
 6,161,126 A 12/2000 Weis et al.
 6,166,732 A 12/2000 Mitchell et al.
 6,169,540 B1 1/2001 Rosenberg et al.
 6,175,954 B1 1/2001 Nelson et al.
 6,219,034 B1 4/2001 Elbing et al.
 6,219,045 B1 4/2001 Leahy et al.
 6,249,806 B1 6/2001 Kohda et al.
 6,252,579 B1 6/2001 Rosenberg et al.
 6,256,663 B1 7/2001 Davis
 6,281,651 B1 8/2001 Haanpaa et al.
 6,292,174 B1 9/2001 Mallett et al.
 6,329,994 B1 12/2001 Gever et al.

6,339,754 B1 1/2002 Flanagan et al.
 6,342,880 B2 1/2002 Rosenberg et al.
 6,347,307 B1 2/2002 Sandhu et al.
 6,349,301 B1 2/2002 Mitchell et al.
 6,393,461 B1 5/2002 Okada et al.
 6,396,509 B1 5/2002 Cheng
 6,421,048 B1 7/2002 Shih et al.
 6,422,941 B1 7/2002 Thorner et al.
 6,425,764 B1 7/2002 Lamson
 6,429,846 B2 8/2002 Rosenberg et al.
 6,442,590 B1 8/2002 Inala et al.
 6,459,892 B2 10/2002 Burgan et al.
 6,496,200 B1 * 12/2002 Snibbe et al. 715/701
 6,519,771 B1 2/2003 Zenith
 6,523,022 B1 2/2003 Hobbs
 6,539,218 B2 3/2003 Higuchi et al.
 6,546,390 B1 4/2003 Pollack et al.
 6,559,845 B1 5/2003 Harvill et al.
 6,563,487 B2 5/2003 Martin et al.
 6,563,503 B1 5/2003 Comair et al.
 6,630,944 B1 10/2003 Kakuta et al.
 6,658,010 B1 * 12/2003 Enns et al. 370/401
 6,677,858 B1 1/2004 Faris et al.
 6,678,720 B1 1/2004 Matsumoto et al.
 6,693,626 B1 2/2004 Rosenberg
 6,711,264 B1 3/2004 Matsumoto et al.
 6,742,116 B1 5/2004 Matsui et al.
 6,755,743 B1 6/2004 Yamashita et al.
 6,760,751 B1 7/2004 Hachiya et al.
 6,763,371 B1 * 7/2004 Jandel 709/204
 6,859,819 B1 2/2005 Rosenberg et al.
 6,965,868 B1 * 11/2005 Bednarek 705/9
 7,084,867 B1 * 8/2006 Ho et al. 345/419
 7,149,208 B2 12/2006 Mattaway et al.
 7,222,228 B1 * 5/2007 Stephens et al. 713/1
 2001/0044725 A1 11/2001 Matsuda et al.
 2003/0067908 A1 4/2003 Mattaway
 2004/0125120 A1 7/2004 Weiner

FOREIGN PATENT DOCUMENTS

EP 0 655 301 B1 6/1998
 EP 0 997 177 A2 5/2000
 GB 2 235 310 2/1991
 GB 2 235 310 A 2/1991
 GB 2 325 766 12/1998
 GB 2 325 766 A 12/1998
 JP H2-185278 7/1990
 JP H4-8381 1/1992
 JP H5-192449 8/1993
 JP H7-24147 1/1995
 JP 09-138767 5/1997
 JP 10-200882 7/1998
 WO WO 91/02313 2/1991
 WO WO 94/25923 11/1994
 WO WO 91/02313 2/1999
 WO WO 99/40504 8/1999
 WO WO 00/10099 2/2000

OTHER PUBLICATIONS

Adelstein, "A Virtual Environment System For The Study Of Human Arm Tremor," Ph.D. Dissertation, Dept. of Mechanical Engineering, MIT, Jun. 1989.
 Aukstakalnis et al., "Silicon Mirage: The Art and Science of Virtual Reality," ISBN 0-938151-82-7, pp. 129-180, 1992.
 Baigrie, "Electric Control Loading—A Low Cost, High Performance Alternative," Proceedings, pp. 247-254, Nov. 6-8, 1990.
 Bejczy et al., "A Laboratory Breadboard System For Dual-Arm Teleoperation," SOAR '89 Workshop, JSC, Houston, TX, Jul. 25-27, 1989.
 Bejczy et al., "Kinesthetic Coupling Between Operator and Remote Manipulator," International Computer Technology Conference, The American Society of Mechanical Engineers, San Francisco, CA, Aug. 12-15, 1980.
 Bejczy, "Generalization of Bilateral Force-Reflecting Control of Manipulators," Proceedings Of Fourth CISM-IFTOMM, Sep. 8-12, 1981.

(56)

References Cited

OTHER PUBLICATIONS

- Bejczy, "Sensors, Controls, and Man-Machine Interface for Advanced Teleoperation," *Science*, vol. 208, No. 4450, pp. 1327-1335, 1980.
- Bejczy, et al., "Universal Computer Control System (UCCS) For Space Telerobots," CH2413-3/87/0000/0318501.00 1987 IEEE, 1987.
- Brooks et al., "Hand Controllers for Teleoperation—A State-of-the-Art Technology Survey and Evaluation," JPL Publication 85-11; NASA-CR-175890; N85-28559, pp. 1-84, Mar. 1, 1985.
- Burdea et al., "Distributed Virtual Force Feedback, Lecture Notes for Workshop on Force Display in Virtual Environments and its Application to Robotic Teleoperation," 1993 IEEE International Conference on Robotics and Automation, pp. 25-44, May 2, 1993.
- Caldwell et al., "Enhanced Tactile Feedback (Tele-Taction) Using a Multi-Functional Sensory System " 1050-4729/93, pp. 955-960, 1993.
- Colgate, J. Edward, et al., "Implementation of Stiff Virtual Walls in Force-Reflecting Interfaces," Department of Mechanical Engineering, Northwestern University, Evanston, IL, Sep. 1993.
- "Cyberman Technical Specification," Logitech Cyberman Swift Supplement, Apr. 5, 1994.
- Eberhardt et al., "Including Dynamic Haptic Perception by The Hand: System Description and Some Results," DSC-vol. 55-1, Dynamic Systems and Control: vol. 1, ASME 1994.
- Eberhardt et al., "OMAR—A Haptic display for speech perception by deaf and deaf-blind individuals," IEEE Virtual Reality Annual International Symposium, Seattle, WA, Sep. 18-22, 1993.
- Gobel et al., "Tactile Feedback Applied to Computer Mice," International Journal of Human-Computer Interaction, vol. 7, No. 1, pp. 1-24, 1995.
- Gotow et al., "Controlled Impedance Test Apparatus for Studying Human Interpretation of Kinesthetic Feedback," WA11-11:00, pp. 332-337, 1989.
- Howe, "A Force-Reflecting Teleoperated Hand System for the Study of Tactile Sensing in Precision Manipulation," Proceedings of the 1992 IEEE International Conference on Robotics and Automation, Nice, France, May 1992.
- IBM Technical Disclosure Bulletin, "Mouse Ball-Actuating Device With Force and Tactile Feedback," vol. 32, No. 9B, Feb. 1990.
- Hinckley, K., "Haptic Issues for Virtual Manipulation," Dissertation for PHD at the University of Virginia, pp. 1-200, Dec. 1996.
- Iwata, "Pen-based Haptic Virtual Environment," 0-7803-1363-1/93 IEEE, pp. 287-292, 1993.
- Jacobsen et al., "High Performance, Dextrous Telerobotic Manipulator With Force Reflection," Intervention/ROV '91 Conference & Exposition, Hollywood, Florida, May 21-23, 1991.
- Jones et al., "A perceptual analysis of stiffness," ISSN 0014-4819 Springer International (Springer-Verlag); Experimental Brain Research, vol. 79, No. 1, pp. 150-156, 1990.
- Kaczmarek et al., "Tactile Displays," Virtual Environment Technologies, May 1995.
- Kontarinis et al., "Display of High-Frequency Tactile Information to Teleoperators," Telemanipulator Technology and Space Telerobotics, Won S. Kim, Editor, Proc. SPIE vol. 2057, pp. 40-50, Sep. 7-9, 1993.
- Marcus, "Touch Feedback in Surgery," Proceedings of Virtual Reality and Medicine The Cutting Edge, Sep. 8-11, 1994.
- McAffee, "Teleoperator Subsystem/Telerobot Demonstrator: Force Reflecting Hand Controller Equipment Manual," JPL D-5172, pp. 1-50, A1-A36, B1-B5, C1-C36, Jan. 1988.
- Minsky, "Computational Haptics: The Sandpaper System for Synthesizing Texture for a Force-Feedback Display," Ph.D. Dissertation, MIT, Jun. 1995.
- Ouhyoung et al., "The Development of a Low-Cost Force Feedback Joystick and Its Use in the Virtual Reality Environment," Proceedings of the Third Pacific Conference on Computer Graphics and Applications, Pacific Graphics '95, Seoul, Korea, Aug. 21-24, 1995.
- Ouh-Young, "Force Display in Molecular Docking," Order No. 9034744, p. 1-369, 1990.
- Ouh-Young, "A Low-Cost Force Feedback Joystick and Its Use in PC Video Games," IEEE Transactions on Consumer Electronics, vol. 41, No. 3, Aug. 1995.
- Patrick et al., "Design and Testing of A Non-reactive, Fingertip, Tactile Display for Interaction with Remote Environments," Cooperative Intelligent Robotics in Space, Rui J. deFigueiredo et al., Editor, Proc. SPIE vol. 1387, pp. 215-222, 1990.
- Pimentel et al., "Virtual Reality: through the new looking glass," 2nd Edition; McGraw-Hill, ISBN 0-07-050167-X, pp. 41-202, 1994.
- Rabinowitz et al., "Multidimensional tactile displays: Identification of vibratory intensity, frequency, and contactor area," Journal of The Acoustical Society of America, vol. 82, No. 4, Oct. 1987.
- Russo, "Controlling Dissipative Magnetic Particle Brakes in Force Reflective Devices," DSC-vol. 42, Advances in Robotics, pp. 63-70, ASME 1992.
- Russo, "The Design and Implementation of a Three Degree of Freedom Force Output Joystick," MIT Libraries Archives Aug. 14, 1990, pp. 1-131, May 1990.
- Scannell, "Taking a Joystick Ride," Computer Currents, Boston Edition, vol. 9, No. 11, Nov. 1994.
- Shimoga, "Finger Force and Touch Feedback Issues in Dexterous Telemanipulation," Proceedings of Fourth Annual Conference on Intelligent Robotic Systems for Space Exploration, Rensselaer Polytechnic Institute, Sep. 30-Oct. 1, 1992.
- Snow et al., "Model-X Force-Reflecting-Hand-Controller," NT Control No. MPO-17851; JPL Case No. 5348, pp. 1-4, Jun. 15, 1989.
- Stanley et al., "Computer Simulation of Interacting Dynamic Mechanical Systems Using Distributed Memory Parallel Processors," DSC-vol. 42, Advances in Robotics, pp. 55-61, ASME 1992.
- Tadros, "Control System Design for a Three Degree of Freedom Virtual Environment Simulator Using Motor/Brake Pair Actuators", MIT Archive © Massachusetts Institute of Technology, pp. 1-88, Feb. 1990.
- Terry et al., "Tactile Feedback In A Computer Mouse," Proceedings of Fourteenth Annual Northeast Bioengineering Conference, University of New Hampshire, Mar. 10-11, 1988.
- Yamakita et al., "Tele-Virtual reality of Dynamic Mechanical Model," Proceedings of the 1992 IEEE/RSJ International Conference on Intelligent Robots and Systems, Raleigh, NC, Jul. 7-10, 1992.
- 1998 IEEE International Conference on robotics and Automation, web page at www.wings.buffalo.edu/academic/department/eng/mae/ieee/icra98/ABST.html, as available via the Internet.
- Curry, "Supporting Collaborative Interaction in Tele-Immersion," 1998, web page at www.sv.vt.edu/future/cave/pub/curryMs/CurryMS.html, as available via the Internet.
- Hansen, "Enhancing Documents with Embedded Programs: How Ness Extends Insets in the Andrew Toolkit," Computer Languages, 1990, IEEE.
- Hayward et al., "Parameter Sensitivity Analysis for Design and Control of Force Transmission Systems," 1995, web page at www.cim.mcgill.ca/~haptic/pub/MC.trans.ps.gz, as available via the Internet.
- Jones et al., "NSF Workshop on Human-Centered Systems: Breakout Group 2—Communication and Collaboration," web page at www.ifp.uiuc.edu/nsfhcs/bog_reports/bog2.html, as available via the Internet and printed Mar. 1, 2005.
- MacLean, "Designing with Haptic Feedback," 2000, web page at www.cs.ubc.ca/nest/lci/papers/2000/maclean-icra00-DesignWithHaptic-reprint.pdf, as available via the Internet.
- Mania et al., "A Classification for User Embodiment in Collaborative Virtual Environments (extended version)," web page at www.cs.bris.ac.uk/~mania/paper1.htm, as available via the Internet.
- Mine, "Virtual Environment Interaction Techniques," 1995, web page at ftp.cs.unc.edu/pub/technical-reports/95-018.ps.Z, as available via the Internet.
- Mine, "ISAAC: A Virtual Environment Tool for the Interactive," 1995, web page at ftp.cs.unc.edu/pub/technical-reports/95-020.ps.Z, as available via the internet.
- Picinbono et al., "Extrapolation: A Solution for Force Feedback?" Virtual Reality and Prototyping, 1999, web page at www-sop.inria.fr/epidaure/AISIM/CompteRendu/aisim3/picinobo.pdf, as available via the Internet.

(56)

References Cited

OTHER PUBLICATIONS

Ruspini et al., "The Haptic Display of Complex Graphical Environments," 1997, Computer Graphics Proceedings, Annual Conference Series, www.robotics.stanford.edu/people/krasi/Siggraph97.ps.Z, as available via the Internet.

Thompson, II et al., "maneuverable Nurbs Models within a Haptic Virtual Environment," web page available at www.cs.utah.edu/gdc/publications/papers/thompson97b.ps.Z, as available via the Internet.
Wloka, "Interacting with Virtual Reality," 1995, web page at wilma.cs.brown.edu/research/graphics/research/pub/papers/coimbra.ps, as available via the Internet.

ATIP98.059, Virtual Reality (VR) Development at SERI (Korea), 1998, web page at www.atip.org/public/atip.reports.98.059r.html, as available via the Internet.

McLaughlin et al., "The USC Interactive Art Museum: Removing the Barriers between Museums and their Constituencies," web page at <http://ascusc.org/jcmc/paperforica.html>, as available via the Internet.

Bouguila, et al., "Effect of Coupling Haptics and Stereopsis on Depth," web page at www.dcs.gla.ac.uk/~stephen/workshops/haptic/papers/bougilia-paper.pdf, as available via the Internet.

Pao et al., "Synergistic Visual/Haptic Computer Interfaces," 1998, Hanoi, Vietnam, web page at schof.colorado.edu/~pao/anonftp/vietnam.ps, as available via the Internet.

eRENA, Deliverable 7b.1, Pushing Mixed Reality Boundaries, 1999, web page at www.nada.kth.se/arena/pdf/D7b_1.pdf, as available via the Internet.

Real Time Graphics, Green Bar-Full Page EPS, Aug. 1998, web page at www.cgsd.com/rtqAug98.pdf as available via the Internet.

United States Patent and Trademark Office, Office Action, U.S. Appl. No. 11/545,739, mailed Oct. 22, 2007.

United States Patent and Trademark Office, Office Action, U.S. Appl. No. 11/545,739, mailed Mar. 5, 2008.

United States Patent and Trademark Office, Office Action, U.S. Appl. No. 09/608,129, mailed Sep. 24, 2003.

United States Patent and Trademark Office, Office Action, U.S. Appl. No. 09/608,129, mailed Mar. 19, 2004.

United States Patent and Trademark Office, Office Action, U.S. Appl. No. 09/608,129, mailed Aug. 10, 2004.

United States Patent and Trademark Office, Office Action, U.S. Appl. No. 09/608,129, mailed Mar. 15, 2005.

United States Patent and Trademark Office, Office Action, U.S. Appl. No. 09/608,129, mailed Nov. 28, 2005.

NPA International Inc., Office Action, Application No. 200810083652, dated Dec. 15, 2009.

NPA International Inc., Office Action, Application No. 200810083652, dated Aug. 19, 2010.

European Patent Office, Communication Pursuant to 94(3) EPC, Application No. 01995050, dated May 25, 2009.

European Patent Office, European Supplemental Search Report, Application No. 01995050, dated Mar. 18, 2009.

State Intellectual Office of the Peoples Republic of China, Notification of the First Office Action, Application No. 01810866, dated Apr. 2, 2004.

Japanese Patent Office, Notification of Reasons for Refusal, Application No. 2010-260419, dispatched Oct. 27, 2011.

Japanese Patent Office, Notification of Reasons for Refusal, Application No. 2010-260419, dispatched Aug. 30, 2012.

Patent Cooperation Treaty, International Search Report, International Application No. PCT/US01/41099, mailed Jan. 2, 2002.

Patent Cooperation Treaty, International Preliminary Examination Report, International Application No. PCT/US01/41099, dated May 18, 2002.

IEEE International Conference on Robotics and Automation, May 16-20, 1998, Lueven, Belgium, 41 pages.

Wloka, M, Interacting with Virtual Reality, Science and Technology Center for Computer Graphics and Scientific Visualization, Brown University Site, Department of Computer Science, Brown University, 1995, 14 pages.

Yamakita, M. et al., Tele-Virtual Reality of Dynamic Mechanical Model, Proceedings of the 1992 IEEE/RSJ International Conference on Intelligent Robots and Systems, Raleigh, NC Jul. 7-10, 1992.

* cited by examiner




FIG. 1




FIG. 2




FIG.3b




FIG. 3c




FIG.3d




FIG. 4

CHAT INTERFACE WITH HAPTIC FEEDBACK FUNCTIONALITY

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCES TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 09/608,126 entitled "Chat Interface with Haptic Feedback Functionality" filed Jun. 30, 2000, now U.S. Pat. No. 7,159,008 the entirety of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

The present invention relates generally to interface devices for allowing humans to interface with computer systems, and more particularly to computer interface devices that provide input from the user to computer systems and implement force feedback to the user.

Using an interface device, a user can interact with an environment displayed by a computer system to perform functions and tasks on the computer, such as playing a game, experiencing a simulation or virtual reality environment, using a computer aided design system, operating a graphical user interface (GUI), or otherwise influencing events or images depicted on the screen. Common human-computer interface devices used for such interaction include a joystick, mouse, trackball, stylus, tablet, pressure-sensitive ball, or the like, that is connected to the computer system controlling the displayed environment. Typically, the computer updates the environment in response to the user's manipulation of a user-manipulatable physical object such as a joystick handle or mouse, and provides visual and audio feedback to the user utilizing the display screen and audio speakers. The computer senses the user's manipulation of the user object through sensors provided on the interface device that send locative signals to the computer.

In some interface devices, haptic feedback is also provided to the user, also known as "force feedback." These types of interface devices can provide physical sensations which are felt by the user manipulating a user manipulable object of the interface device. For example, the Wingman Force joystick or the Wingman Force Feedback Mouse from Logitech Inc. may be connected to a computer and provides forces to a user of the controller. One or more motors or other actuators are used in the device and are connected to the controlling computer system. The computer system controls forces on the joystick in conjunction and coordinated with displayed events and interactions by sending control signals or commands to the actuators. The computer system can thus convey physical force sensations to the user in conjunction with other supplied feedback as the user is grasping or contacting the joystick or other object of the interface device. For example, when the user moves the manipulatable object and causes a displayed cursor to interact with a different displayed graphical object, the computer can issue a command that causes the actuator to output a force on the user object, conveying a feel sensation to the user.

Force feedback can be used to communicate ideas and messages as well as effects. Forces can in many instances provide additional information to a recipient of the message that may not be apparent in a text or voice message. For example, a text message sent to another user over the Internet may not include information indicating how strong the user feels about the topic expressed or other message subtext. Users can try to express this subtext using well-known icons or symbols known as "emoticons," which are iconic representations of emotions or messages, such as the "smiley" to indicate a humorous message, expressed as a colon and right parenthesis mark, :), which resembles a face smiling when viewed from the side. Variations of the smiley emoticon can express a variety of other emotions. However, such emoticons and symbols are limited in the complexity of the messages they convey and the range of different messages possible. Haptic feedback, in contrast, can offer much more complex and direct ways to express such subtext to other users in a more compelling fashion.

SUMMARY OF THE INVENTION

The present invention is directed to an interface allowing a user to exchange haptic chat messages with other users over a computer network. The user is able to provide messages that cause haptic sensations to one or more remote users which have a haptic interface device, allowing more diverse and compelling messages to be sent in a chat environment.

More particularly, one method of the present invention provides a chat interface displayed by a local computer, the chat interface capable of providing haptic messages to other users across a network. The chat interface is displayed on a display device of the local computer, and input data from a user of the local computer is received at the chat interface, the input data providing an outgoing chat message which can include sent force information. The outgoing chat message to be sent to a remote computer that is connected to the local host computer via a computer network, and the remote computer can display a chat interface and output a haptic sensation to a user of the remote computer based at least in part on the force information. An incoming message from the remote computer is received at the chat interface, which may also include received force information. The incoming chat message is displayed on a display device to the user of the local computer. A haptic sensation can be output to the user of the local computer using a haptic device coupled to the local computer, where the haptic sensation is based at least in part on the received force information received from the remote computer.

The local computer and remote computer can each be coupled to a server machine via the network, such as an IRC server, or can be coupled to each other via a peer-to-peer connection. The chat interface preferably includes multiple available haptic effects, each selectable by the user to be sent as the force information in the chat message. The chat interface also may allow the user to create a custom haptic sensation to be referenced by the force information sent to the remote computer. The force information is also preferably associated with sound information, such that the remote computer outputs a sound effect in coordination with the output of the haptic sensation. In one embodiment, the received force (or other) information can be processed by a background application running on the local computer simultaneously with the chat interface, the background application controlling the output of the haptic sensation to the user.

The sent force information may include a network address, which is then used by the chat interface on the remote com-

puter as a network location at which to retrieve additional force information required to output a force sensation to the haptic device at the remote computer. For example, the network address can be an address of a web server storing a library of standard and customized haptic sensations which can be output by the haptic device. In addition, custom force information can be uploaded from a client machine to a server at the network address, where the uploaded custom force information can be downloaded by a different client computer to output a haptic sensation based on the custom force information. The force information in the chat message can alternatively include data characterizing the desired haptic sensation. Preferably, the chat interface allows the user of the local computer to type a text command including text characters to be sent as a force command or cause force information to be sent to the remote computer. The text force command is preferably displayed in a chat interface of the remote computer and includes at least one delimiter character for indicating the nature of the text force command or can be a predetermined character(s), such as those used for emoticons. Chat messages can also be in audio or other formats, and one embodiment allows audio waveforms in chat messages to be analyzed to base haptic sensations on waveform content.

The present invention advantageously provides features in a chat interface on a computer to allow enhancements to chat messages using haptic sensations. The user can select a desired haptic sensation or even customize a haptic sensation to provide with a message to one or more other users in a chat session. The haptic sensations allow a wide variety of emotions and other content and subtext of messages to be conveyed, allowing a user more freedom to express a desired message across a computer network.

These and other advantages of the present invention will become apparent to those skilled in the art upon a reading of the following specification of the invention and a study of the several figures of the drawing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a haptic system suitable for use as a client computer in the present invention;

FIG. 2 is a block diagram illustrating a network configuration suitable for use with the present invention;

FIG. 3a is a screen display of one embodiment of a chat interface of the present invention allowing haptic messages to be sent and received;

FIG. 3b is a screen display of the chat interface of FIG. 3a in which a haptic effect is selected to be sent as a haptic message;

FIG. 3c is a screen display of an input screen of the chat interface of FIG. 3a to allow the user to specify information about a custom haptic effect;

FIG. 3d is a screen display of a selection screen of the chat interface of FIG. 3a to allow a user to retrieve and test a haptic effect from a list stored on a different server; and

FIG. 4 is a screen display of another embodiment of the chat interface of FIG. 3b including buttons used to send haptic messages.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIG. 1 is a block diagram illustrating a force feedback interface system 10 for use with the present invention controlled by a host computer system. Interface system 10 includes a host computer system 12 and an interface device 14.

Host computer system 12 is preferably a personal computer, such as an IBM-compatible or Macintosh personal computer, or a workstation, such as a SUN or Silicon Graphics workstation. Alternatively, host computer system 12 can be one of a variety of home video game systems, such as systems available from Nintendo, Sega, or Sony, a television "set top box" or a "network computer", etc. Host computer system 12 preferably implements a host application program with which a user 22 is interacting via peripherals and interface device 14. For example, the host application program can be a video game, medical simulation, scientific analysis program, operating system, graphical user interface, or other application program that utilizes force feedback. Typically, the host application provides images to be displayed on a display output device, as described below, and/or other feedback, such as auditory signals.

Host computer system 12 preferably includes a host microprocessor 16, random access memory (RAM) 17, read-only memory (ROM) 19, input/output (I/O) electronics 21, a clock 18, a display screen 20, and an audio output device 21. Display screen 20 can be used to display images generated by host computer system 12 or other computer systems, and can be a standard display screen, CRT, flat-panel display, 3-D goggles, or any other visual interface. Audio output device 21, such as speakers, is preferably coupled to host microprocessor 16 via amplifiers, filters, and other circuitry well known to those skilled in the art (e.g. in a sound card) and provides sound output to user 22 from the host computer 18. Other types of peripherals can also be coupled to host processor 16, such as storage devices (hard disk drive, CD ROM/DVD-ROM drive, floppy disk drive, etc.), printers, and other input and output devices. Data for implementing the interfaces of the present invention can be stored on computer readable media such as memory (RAM or ROM), a hard disk, a CD-ROM or DVD-ROM, etc.

An interface device 14 is coupled to host computer system 12 by a bi-directional bus 24. The bi-directional bus sends signals in either direction between host computer system 12 and the interface device. An interface port of host computer system 12, such as an RS232 or Universal Serial Bus (USB) serial interface port, parallel port, game port, etc., connects bus 24 to host computer system 12.

Interface device 14 includes a local microprocessor 26, local memory 27, sensors 28, actuators 30, a user object 34, optional sensor interface 36, an optional actuator interface 38, and other optional input devices 39. Local microprocessor 26 is coupled to bus 24 and is considered local to interface device 14 and is dedicated to force feedback and sensor I/O of interface device 14. Microprocessor 26 can be provided with software instructions to wait for commands or requests from computer host 12, decode the command or request, and handle/control input and output signals according to the command or request. In addition, processor 26 preferably operates independently of host computer 16 by reading sensor signals and calculating appropriate forces from those sensor signals, time signals, and stored or relayed instructions selected in accordance with a host command. Suitable microprocessors for use as local microprocessor 26 include the MC68HC711E9 by Motorola, the PIC16C74 by Microchip, and the 82930AX by Intel Corp., for example. Microprocessor 26 can include one microprocessor chip, or multiple processors and/or co-processor chips, and/or digital signal processor (DSP) capability.

Microprocessor 26 can receive signals from sensors 28 and provide signals to actuators 30 of the interface device 14 in accordance with instructions provided by host computer 12 over bus 24. For example, in a preferred local control embodi-

5

ment, host computer system **12** provides high level supervisory commands to microprocessor **26** over bus **24**, and microprocessor **26** manages low level force control loops to sensors and actuators in accordance with the high level commands and independently of the host computer **18**. The force feedback system thus provides a host control loop of information and a local control loop of information in a distributed control system. This operation is described in greater detail in U.S. Pat. No. 5,739,811 and patent application Ser. Nos. 08/877,114 and 08/050,665 (which is a continuation of U.S. Pat. No. 5,734,373), all incorporated by reference herein. Microprocessor **26** can also receive commands from any other input devices **39** included on interface apparatus **14**, such as buttons, and provides appropriate signals to host computer **12** to indicate that the input information has been received and any information included in the input information. Local memory **27**, such as RAM and/or ROM, is preferably coupled to microprocessor **26** in interface device **14** to store instructions for microprocessor **26** and store temporary and other data. In addition, a local clock **29** can be coupled to the microprocessor **26** to provide timing data.

Sensors **28** sense the position, motion, and/or other characteristics of a user object **34** of the interface device **14** along one or more degrees of freedom and provide signals to microprocessor **26** including information representative of those characteristics. Rotary or linear optical encoders, potentiometers, optical sensors, velocity sensors, acceleration sensors, strain gauge, or other types of sensors can be used. Sensors **28** provide an electrical signal to an optional sensor interface **36**, which can be used to convert sensor signals to signals that can be interpreted by the microprocessor **26** and/or host computer system **12**.

Actuators **30** transmit forces to user object **34** of the interface device **14** in one or more directions along one or more degrees of freedom, and/or may apply forces to the housing of the device **14**, in response to signals received from microprocessor **26**. Actuators **30** can include two types: active actuators and passive actuators. Active actuators include linear current control motors, stepper motors, pneumatic/hydraulic active actuators, a torquer (motor with limited angular range), a voice coil actuators, and other types of actuators that transmit a force to move an object. Passive actuators can also be used for actuators **30**, such as magnetic particle brakes, friction brakes, or pneumatic/hydraulic passive actuators. Actuator interface **38** can be optionally connected between actuators **30** and microprocessor **26** to convert signals from microprocessor **26** into signals appropriate to drive actuators **30**.

Other input devices **39** can optionally be included in interface device **14** and send input signals to microprocessor **26** or to host processor **16**. Such input devices can include buttons, dials, switches, levers, or other mechanisms. For example, in embodiments where user object **34** is a joystick, other input devices can include one or more buttons provided, for example, on the joystick handle or base. Power supply **40** can optionally be coupled to actuator interface **38** and/or actuators **30** to provide electrical power. A safety switch **41** is optionally included in interface device **14** to provide a mechanism to deactivate actuators **30** for safety reasons.

User manipulable object **34** ("user object") is a physical object, device or article that may be grasped or otherwise contacted or controlled by a user and which is coupled to interface device **14**. By "grasp", it is meant that users may physically contact the object in some fashion, such as by hand, with their fingertips, or even orally in the case of handicapped persons. The user **22** can manipulate or move the object to interface with the host application program the user

6

is viewing on display screen **20**. Object **34** can be a joystick, mouse, trackball, keyboard, stylus (e.g. at the end of a linkage), steering wheel, sphere, medical instrument (laparoscope, catheter, etc.), pool cue (e.g. moving the cue through actuated rollers), hand grip, knob, button, or other article.

The haptic feedback interface device **14** can take a variety of forms, including a mouse, joystick, gamepad, steering wheel, chair pads which the user sits on, fishing rod, pool cue, etc. A variety of these types of devices are available commercially. For example, suitable mice for use with the present invention include kinesthetic force and vibrotactile mice, such as those described in copending U.S. application Ser. Nos. 08/965,720, 09/125,711, 09/456,887, and 60/182,868, all incorporated herein by reference. The user object **34** and/or interface device **14** can also be a keyboard having haptic feedback functionality; some embodiments of such a keyboard are described in copending application no. 09/450,361, filed on May 12, 2000, and entitled, "Haptic Feedback Using a Keyboard Device," which is incorporated herein by reference. One preferred embodiment of a system for use with the present invention is a haptic keyboard and a haptic mouse, where the user may type messages on the haptic keyboard in the chat interface of the present invention, and may use the haptic mouse to move a cursor to select functions within the chat interface. Both devices can output the haptic feedback communicated in the present invention. Thus, when using both devices, the user can experience the haptic feedback at all times, whether the user has one hand on the keyboard and one hand on the mouse, both hands on the keyboard or one hand on the mouse, or no hands on the keyboard and one hand on the mouse.

Haptic Feedback Chat Interface

FIG. 2 is a block diagram illustrating a computer networking structure **60** suitable for use with the present invention. A chat server machine **70** can be provided which can implement a chat communication program and/or protocol, such as IRC, as is well known to those of skill in the art. The server can be available over the Internet and/or World Wide Web, for example, or on a LAN, WAN, or other network (including a wireless network, device network, telephone network, etc.). Client machines **72a** and **72b** can connect to and communicate with the server over the network. Each client machine **72** is coupled to a haptic device **74** that outputs haptic sensations to the user as detailed above and which is physically contacted and operated by the user of the client machine. The client machines **72a**, **72b** and **73** can connect to the server, and through the server the client machines can establish a connection with each other. In a chat, the user of each client machine sends data to one or more of the other client machines, where it is read and sensed by the other user. The chat server **70** can be used merely as a way for two client machines to find each other and connect, so that communication between client machines is thereafter only between themselves; or, the chat server **70** can continue to receive and route data between the clients. In other embodiments, client machines can directly connect to each other in a peer-to-peer connection, without the use of a separate server machine, over various types of networks, connections, and channels. The term "network," as used herein, is intended to refer to all such communication connections.

In the described implementation, clients **72a** and **72b** each include a chat client functional portion **76** and a haptic control functional portion **78**. The chat client **76** interacts with the chat server **70** according to standard protocols to provide chat communications to the user of the client machine from other

client machines. For example, server **70** can be an IRC (Internet Relay Chat) server which communicates with clients using well-known IRC protocols. Other types chat protocols that can be used include pure HTML-based chat protocols, Java-based chat protocols, or protocols based in other standards. Some clients connected to server **70** and participating in chat sessions, such as client **73**, may only be implementing the chat client portion **76** and thus ignore the haptic implementation of haptic messages.

The haptic control portion **78** interacts with the chat client portion **76** to provide control over haptic sensations of the present invention that are associated with chat messages. For example, received messages which are interpreted as haptic messages or commands can be detected by the haptic control portion **76** and haptic sensations can be commanded from portion **78** to the haptic device **74**. Furthermore, in some embodiments, the haptic control portion **78** can communicate with one or more other servers, such as web server **80**. For example, force effect data, sound data, or other data can be retrieved by the haptic control portion **78** to implement particular haptic sensations. This operation is described in greater detail below.

FIG. **3a** is a diagram of display screen **20** of host computer **12** showing a displayed interface **100** illustrating one example of a chat interface for a network chat application program of the present invention. A network chat program allows two or more people at different computers or terminals to communicate with each other over a computer network, as is well known to those skilled in the art. In some embodiments, a single person can interact with a "simulated person" or entity in a chat-like communication, such as with a AI game character or player implemented by a program running on a server, which can also make use of the present invention. In different embodiments, messages in different formats can be sent, such as in text, sound, images, or a combination of these. The chat interface of the present invention also allows haptic sensations to be sent from one user to one or more other users across the network based on the message desired to be sent. Some methods for providing haptic feedback over a network are described in U.S. Pat. No. 6,028,593 and U.S. patent application Ser. No. 09/153,781, both incorporated herein by reference. The network can be a local area network (LAN), wide area network (WAN), the Internet, or other network.

Display screen **20** is shown displaying a chat interface **100** of the present invention. The interface **100** can implement and connect to a server running a standard chat program and protocol, such as Internet Relay Chat (IRC), using methods well known to those skilled in the art. IRC simply provides text characters from one client to the chat server **70**, which routes the text characters to the other clients participating in the chat session. In some embodiments, the chat protocol used can be a proprietary one that only functions with particular programs.

In the described embodiment, a chat client program handles all the standard chat interfacing, while a haptic functionality program interfaces with the chat program to handle the output of haptic sensations. For example, the chat interface **100** can be displayed within a web browser program, such as Microsoft Internet Explorer or Netscape Navigator, as a web page. For example, in one implementation, the Internet Explorer web browser can make use of the MS Chat ActiveX Control available from Microsoft Corp., which can perform all the functions necessary to communicate with an IRC server and the necessary network protocols; this can be the chat client portion **76** as shown in FIG. **2**. The ActiveX Control can generate events, such as when message data is received, to allow other programs to act upon those events.

The haptic control portion **78** can be running alongside the chat ActiveX Control and can receive the events from the control. When an event occurs, the haptic control portion can check the input for specific haptic commands or messages and generate commands to cause haptic sensations for the user if appropriate.

Alternatively, the chat interface **100** can be implemented as a separate application program, as a functional part of another program or operating system, a Java applet or other program implemented over the World Wide Web or Internet, or other implementation. Similar embodiments used for force feedback in web pages sent over the World Wide Web are described in copending application Ser. No. 09/244,622, incorporated herein by reference. For example, in one embodiment the haptic chat interface can be a portion of an "instant messaging" program such as ICQ or AOL Instant Messenger, available from America Online, Inc., which allows users to chat using text, send files to each other, connect to each other using a game program, etc. In a different embodiment, a background application, which is always running on the client computer, checks all input being sent and/or received and determines if any of the input qualifies as a haptic message, e.g. if any input has the brackets surround text characters as described below. Thus, a standard chat interface program can be used for providing chat functionality, with the background application enabling the haptic sensations for haptic messages. If such a background application is used, particular application programs, such as chat programs and instant messaging programs, can be designated by the user to be monitored by the background application, so that the background application ignores input and output of other programs not relevant to haptic messaging. A background application used for force feedback functionality in a graphical user interface, which can also be applied to the chat interface of the present invention, is described in copending U.S. patent application Ser. No. 08/970,953, incorporated herein by reference.

In still other embodiments, the interface **100** can portray a 2-D or 3-D graphical environment through which the user can navigate and manipulate. For example, in a virtual or game environment implemented over the Internet or other network (e.g., using VRML protocols), a message can be sent to another 3-D character or avatar, and a haptic component to the message can be provided for the recipient.

Interface **100** includes information fields **102**, chat window **104**, a user list window **106**, and effects window **108**. Information fields **102** allow the user to specify connection and naming options. A server name field **112** allows the user to specify a particular server to which to connect. For example, the described implementation allows the user to connect to IRC servers. Alternatively, this can be a client name to connect directly to another client machine, if such functionality is provided in the chat interface. Nickname field **114** allows the user to specify a name that is used within a chat. Room name field **116** allows the user to specify a "chat room" or particular area on the specified server in which the chat is held which allows only the users designated to be in that chat room to communicate with each other in the chat session. The "leave" button **118**, when selected by the user (e.g. with keyboard or mouse cursor), causes the user to leave any chat session in which the user is currently participating. Attributes **120** allow the user to designate whether the user will feel the haptic sensations associated with an effect from window **108** when such an effect is received from another user, and/or hear the sound effect associated with that haptic message when it is received (or, in some embodiments, when the haptic or sound effect is sent by the user, to allow the user to haptically and

auditorily experience a message in the way that the recipient of the message will experience it). Icon attributes **122** allow the user to designate whether the user will feel the haptic sensations and/or the sound effects associated with “icons” (emoticons) received from a different user, i.e. messages having haptic and auditory content when used in the present invention, each message represented by a single command or icon. For example, a smiley icon (“:”) can, when received, cause a predefined force sensation and sound to be output to the user if attributes **122** are selected. The user can therefore select whether he or she wants to experience the haptic and/or auditory content of iconic messages received in the chat interface **100**.

Chat window **104** displays the text messages typed in (or otherwise input) by the user as well as messages sent from other users that are currently connected to the user’s computer in a chat session. The user can type in a text message in the text entry field **126**, can send the message to all the users in the chat session by selecting button **128**, or can “whisper” the message only to users selected in window **106** by selecting the button **130**. In other implementations, each of the users in the chat session may display messages in a separate window or other area of the interface **100** dedicated to that user. User list window **106** displays all the users currently in the chat room or session in which the user is participating or observing (e.g., in a chat room which the user wishes to observe without sending messages of his or her own). The users participating in the chat room are able to type messages to the other users in the chat room, where those messages are displayed in the chat window **104**. In some embodiments, a user is able to select one or more names of users displayed in window **106** to call up information about those users and/or send messages directly to those users. In the preferred embodiment, the user can select one or more names and send tactile messages to the selected users.

Effects list **108** provides a number of force effects that can be sent as haptic messages to a particular users selected in the user list window **106** (or to all users if no users in list **106** are selected). Each of the effects listed in list **108** also has one or more sounds associated with it which are played by the recipient’s client machine when the haptic message is sent. Effects list **108** preferably includes all the haptic messages which the user can send, including any custom or newly-downloaded messages. The messages are only sent to the selected user(s), so that other unselected users are not sent the messages. Each name in list **108** represents a particular haptic sensation that has been associated with that name or label in list **108**. To send a haptic message, the user can select one of the effects in list **108** with a displayed cursor or by using some other selection method (keyboard, etc.). This preferably calls up a menu to allow the user to perform different functions with the selected effect, as detailed below with respect to FIG. **3b**. The list **108** preferably can be scrolled or otherwise navigated if it includes too many entries to be displayed all at one time.

FIG. **3b** shows the displayed interface **100** of FIG. **3a**, where the user has selected one of the effects in list **108** to display an options menu **140**. For example, the user can use a mouse or other pointing device to move the cursor on the desired effect and push a particular mouse button to bring up the menu **140**. Menu **140** includes a number of options, including a send command **142**, a whisper command **144**, a play command **146**, a compose new effect command **148**, and an import effect command **150**. The user may select any of these commands.

The interface **100** of FIG. **3b** shows the send command **142** selected. This command will cause the selected effect in list **108** to be sent to the all users participating in the chat, i.e.

users in the chat room. For example, the “laugh” effect shown selected in FIG. **3b** is sent to all participants in the chat session. In the described embodiment, this is implemented by sending text characters that are designated or delimited as a haptic command by other text characters. For example, characters that are surround by brackets <and> can be interpreted as haptic commands by the haptic control portion of the interface **100**. Thus, the command <laugh> is sent to the other clients when the “laugh” effect is sent using the menu **140**. Preferably, the command label generally signifies in natural language the haptic sensation with which it is associated; e.g., the command “slap” signifies a high magnitude jolt, while the command “wink” may signify a lower magnitude sensation.

The haptic control portion of the recipient user’s client detects the received command and outputs a force sensation with the same name to the haptic device. Thus, for example, when the effect “pat” is selected (or the command <pat> is entered), an associated haptic message is sent to other chat user(s). The recipient user(s) then feel the haptic message via a haptic feedback interface device that the recipient user is using. The haptic message is delivered to the recipient user as a haptic sensation output by the recipient user’s haptic interface device, e.g. a pulse, vibration, jolt, etc. or combination of multiple haptic sensations. Each of the effects in list **108** preferably has a name or label that is appropriate to the haptic sensation associated with that name. For example, the “pat” effect preferably provides a haptic message implementing a small, smooth jolt to the grip or user object of the recipient user’s haptic device, like a pat of a hand. The “giggle” effect can provide a low-frequency vibration, the “slap” effect can provide a sharp, high magnitude jolt, the “smile” effect can provide a slow side-to-side motion, etc.

Also, a predefined sound effect is also preferably associated with the sent message to more effectively convey the message, although such sound need not be played in alternate embodiments. The sound effect is synchronized with features of the haptic sensation of the haptic message. For example, the message “slap” can provide a single haptic jolt and sound effect, while the message “slap-slap” can provide two successive jolts, each jolt synchronized with appropriate slapping sound effects. A sound file (which can be in a standardized format such as .wav) can be associated with the haptic command on the recipient client machine, and this sound file is played concurrently with the output of the force sensation. In other embodiments, other types of media data can be output synchronized with the haptic effect instead of or in addition to the sound effect. For example, animated or static graphics or images can be displayed on a display screen in coordination with the output of the haptic effect and with the sound effect. These other types of data can be stored in files and accessed similar to the sound files described above.

A chat user can also preferably send a haptic message by typing a text command in the chat window directly with a keyboard (or inputting the command with another input device) rather than selecting an effect from the list **108**. For example, the user could simply type “<slapslap>” to cause the appropriate haptic message to be sent. Furthermore, predefined “emoticons” can be defined to be associated with haptic and sound effects and can be sent as haptic commands. For example, a smiley emoticon, “:”)”, when typed into entry field **126** and sent to another user, can cause the same haptic sensation as a “smile” effect selected from effects list **108**, or can cause a unique associated haptic sensation to be output to the recipient. Other examples of emoticons include “: (” (frown), “:;)” (wink), and “: o” (surprise). In some embodiments, to be used as haptic messages, such emoticons are placed between brackets to indicate that they are haptic com-

mands. Other embodiments can automatically interpret such emoticons as commands, without brackets or other command characters or delimiters. Emoticons can preferably be pre-defined by a user in a separate list, where each emoticon can be associated with haptic effects and sound effects similarly to the custom effects described below.

In the described embodiment, the command sent to the recipient clients as a haptic message is also displayed in the recipients' chat window **104** (and the sender's window **104**, if desired) as the text characters in the message. Thus, a "smile" haptic message **124** is displayed in FIG. **3b** which caused a haptic sensation and associated sound to be output on the recipient's client machine. The displayed message **124** indicates visually to the user that a haptic message has been sent.

In some embodiments, the user can send a normal text message as well as a haptic effect and sound effect, all simultaneously. For example, the user can type in a message in field **126** and can select an option (not shown) in menu **140** such as "send with text message", which will cause the selected haptic effect (and associated sound effect) to be simultaneously sent with the text message in field **126** to recipient users. Thus, the term "haptic message" as referenced herein can include a haptic effect as well as a sound effect, a text message, and/or other content.

The whisper command **144** in menu **140**, when selected, causes the selected haptic effect(s) from list **108** to be sent only to those users selected in window **106**, but is otherwise similar to the send command **142**. The play command **146** allows the selected haptic effect(s), and their associated sounds, to be output on the user's own client machine so that the user can check how the haptic message will be experienced by recipient users.

The actual haptic message contents that are sent to the recipient client machine(s) can vary in different embodiments. In the described embodiment, the available haptic messages from list **108** are identical for all users in the chat, who are all using the same interface **100**. Thus, the only information that needs to be sent to other users in a haptic message is the high level command indicating the type of haptic sensation is being sent as a message, such as the text label of the effect surround by brackets explained above, or some other type of command. This allows the chat interface of the recipient client machine to receive the command as standard text characters or other standardized data, and allows the haptic control portion of the recipient client machine to know which haptic sensation should be output. It should be noted that in some embodiments, a haptic message can be sent without the sending client knowing that it is a haptic message. For example, as explained above, an emoticon without any other special characters can be sent by a non-force feedback standard client in a chat session as a text message, and the emoticon can be considered a haptic message by the receiving client so that a haptic sensation associated with the emoticon is output upon reception. Such an implementation can be considered a "generic" haptic effect that is implemented only at the receiving client.

In other embodiments, more sophisticated haptic messages can be sent or indicated. For example, the haptic message can include force information content and/or additional commands that are sent to the recipient user's client machine and instruct the haptic device of the recipient user to output a haptic sensation. This can allow for customized haptic sensations to be output that are not previously defined within the interface **100**. The force information can be provided in several different ways. For example, the force information can be sent as a high level command that indicates a standardized type of haptic sensation to output, where it is assumed that the

recipient users all have a standardized library of haptic sensations available on their computer systems which the high level command can reference. In some embodiments, additional information can be sent, such as one or more command parameters that characterize the commanded haptic sensation, e.g., time duration of the sensation, frequency, magnitude, direction, button parameters, rise time and decay time, simulated mass or position, etc. In yet other embodiments, data describing and defining the actual haptic sensation can be sent over, such as a series of force magnitudes and directions. Or, a network address (or other location) can be sent at which the haptic sensation data can be downloaded or retrieved. Many of these methods can allow completely customized haptic sensations to be sent which recipient users do not already have. For example, the first time a customized haptic message is sent, all the data required to implement the haptic sensation is also sent. Any description data need not be sent thereafter when that haptic message is sent successive later times, since the haptic description data is already resident and saved on the recipient computer system. Such sending of description data is obviously more suitable for communication over faster, broadband networks and connections due to the larger amount of data sent.

Custom haptic effects and sound effects can also be composed by users. For example, if the user selects the Compose New Effect command **148** from menu **140**, the user preferably accesses a user interface to allow effect creation. One example of such a user interface is shown in FIG. **3c**. A dialog box **160** is displayed when the user has selected command **148**. The user can enter information into fields of the dialog box to define a custom haptic effect and sound effect. For example, a name or label for the haptic message can be specified in field **162**, a network address or local address for the location of the haptic effect associated with the label (where the data can be organized in a file having a standardized format, such as an ".IFR" file) can be specified in a field **164**, the name of the haptic effect file at the address of field **164** can be specified in field **166**, and the network or local address of sound data, such as a sound file, can be specified in field **168**. Once the user has entered this data to create a new haptic message, the name of field **162** is displayed in the list **108** of the chat interface **100** and can be selected similarly to the other listed effects.

In some embodiments, libraries of standardized as well as customized haptic effects and sound effects can be stored on network servers available on a network having wide distribution, such as the Internet, which recipient users can access to download the needed data to experience received haptic messages. In the described embodiment, web server **80** (shown in FIG. **2**) can be accessed by the haptic control portion of the chat program of the present invention (e.g. by using a URL address and CGI script) to download needed haptic effects and/or data, as well as sound data. For example, a sending user can create a custom haptic effect on his or her client machine using the interface of FIG. **3c**. At the time of effect creation, or when the creating user enters a chat room, or if/when that user so chooses, the custom haptic effect is uploaded to the web server **80** to be stored and made available to other clients accessing the network. Other users on different client machines, when entering the chat room or after the time when the custom effect has been uploaded, can automatically download the custom haptic effect from the web server **80**, or can download the custom effect when the user of that machine so chooses. For example, upon entering a chat session, the chat interface on each client machine can check which haptic effects are needed for the chat session; this can be accomplished by maintaining a continuously-updated

“chat room list” of effects on the web server, which includes all effects which could be sent from any of the client machines in the chat room. A particular chat interface can check that list upon entry into the chat session, and then download the effects in the list not currently stored on that client machine. 5 Alternatively, when a haptic message referencing the custom effect is sent to a client machine, the recipient client machine can download the data for that effect at the time of reception of the haptic message.

The chat interface **100** (or other separate program or web page) can include features to allow users to connect to a server that lists customized haptic sensations available from multiple other users that have chosen to make their sensations available, and which allows users to connect to various other user client machines or servers to download selected haptic sensation files and data. For example, if the user selects the Import Effect command **150** of the menu **148**, the user can preferably import any of several available effects. An example of an interface to allow such selection is shown in FIG. 3d. Window **170** shows a library list stored on a web server (or other server) that includes a number of categories and subcategories **172** of effects available on the server. In each category or subcategory **172**, a number of effects **174** can be listed which are stored on the server. Effects which are not currently stored on the client machine displaying the interface **100** can be designated or marked as such. The user can select an effect **174** and then select the retrieve button **176** to download the selected effect to the local client machine. The user can also select the play button **178** to play a selected, retrieved effect **174**, allowing the user to experience how the effect feels. If the user selects the import button **180**, a selected effect is added to and displayed in the list **108** of effects (and downloaded if necessary) and can be sent by the user as a haptic message, as well as played when the user receives a haptic message including that haptic effect. Any sound effects associated with the retrieved haptic effect are also preferably downloaded.

The effects can be categorized on the server according to a number of different criteria. For example, groups of haptic messages can be displayed and organized according to types of messages, emotion of the message, strength of the message, etc. For example, a “sad messages” category can include all those haptic messages conveying such an emotional state, and a “romance” category can include haptic messages conveying an appropriate close, personal message.

In other embodiments, the chat interface can be part of a voice communication program allowing voice communication or telephony over the computer network **60**. Voice communication features can be found in existing utility programs or in API’s such as DirectX. For example, when saying something to a recipient user, a sending user can select a message effect similar to an effect in list **108** to provide a haptic sensation to the recipient user in conjunction with the spoken message, or independent of any speech. Haptic messages can also be selected to be sent to a recipient user based on spoken message occurrences or content; for example, a haptic message can be sent each time a word is spoken. If voice recognition is implemented on the client machine (e.g., using standard available voice recognition software), a haptic message can be based on a software interpretation of the actual spoken message content. Thus, if the user says, “I hate you” to another user, a “slap” or “punch” message can automatically be sent with or right after the voice message to provide the appropriate haptic sensation.

A haptic message can be “generic,” i.e. the haptic output can be generated on the receiving machine based on user preferences, where the user can associate desired haptic sen-

sations with particular commands that are received in an appropriate interface. Alternatively, a haptic message can be “authored”, where the sending user defines how the haptic sensation is to be felt within the message, by pointing to standardized haptic sensations or providing the data necessary to implement the authored haptic sensation. Such generic and authored implementations are similar to generic and authored force effects sent over networks as described in copending U.S. application Ser. No. 09/244,622.

In another embodiment, haptic sensations can be based on audio speech that is input and transmitted as chat messages to be output by the other client machines in the chat session. In one such embodiment, a process can be running on the receiving client computer which analyzes incoming audio speech data and commands haptic sensations based on the speech data. For example, in a simple embodiment, a wave pattern representing the speech data can be converted to haptic sensations based on the shape of the waveform, where each (or a selected) peak in the waveform can cause the output of a pulse or jolt on the haptic device, and repeating peaks in the waveform can cause a vibration. Other features of waveforms can be designated for other haptic effects, e.g., jumps in amplitude by a predetermined amount can cause a jolt or pulse, or the jolt’s magnitude can be proportional to the jump in amplitude of the waveform.

In a more complex embodiment, the speech waveforms of the received message can be analyzed for predetermined, particular characteristics which may indicate the emotional content of the audio chat message, and a haptic sensation appropriate to the emotional content can then be output to the user. For example, a laugh of the sending user might provide distinguishing characteristics in the sent waveform, such as a high frequency, high amplitude oscillation. If such a laugh is detected, a haptic sensation such as an oscillation or wiggling of the mouse (or other user manipulandum) can be output. A shout from the sending user might appear in the waveform as a quick transition from low amplitude to high amplitude, and the associated haptic sensation can be a quick, high frequency vibration or pulse. A sigh from the sending user may cause a long, low frequency, low volume, consistent pitch or amplitude in the waveform, which can be associated with gentle, circular motions of the manipulandum or low frequency vibrations on the haptic device. Other emotions or inherent messages can be similarly analyzed in received waveforms and appropriate haptic sensations output based on the analysis.

FIG. 4 illustrates a slightly different embodiment **100'** of a chat interface, similar to the chat interface **100** shown in FIG. 3a. Interface **100'** is different from interface **100** in that several haptic message buttons are provided instead of the list **108** of effects. Whisper haptic message buttons **210** are used to send haptic and auditory messages to particular users selected in the user list window **106**. The messages are only sent to users selected in the window **106**. Each button **210** represents a particular haptic sensation that has been associated with the name of the button, similar to an effect listed in list **108** described above. To send a haptic message, the user merely selects one of the buttons **210** with a displayed cursor or by using some other selection method (keyboard, voice, etc.). Thus, when the button “pat” is selected, an associated haptic message is sent to the selected user(s). The selected user(s) then feel the haptic message via a haptic feedback interface device that the selected user is using. General haptic sensation message buttons **212** are similar to whisper buttons **210**, except that the haptic message designated by the button label is sent to all users in the chat session instead of selected users.

While this invention has been described in terms of several preferred embodiments, it is contemplated that alterations, permutations and equivalents thereof will become apparent to those skilled in the art upon a reading of the specification and study of the drawings. For example, many different application programs can use the messaging functions of the present invention, including game programs, virtual reality programs and environments, teleconferencing applications for business meetings, telephone-type voice communications over computer networks or other communication channels, etc. Furthermore, certain terminology has been used for the purposes of descriptive clarity, and not to limit the present invention. It is therefore intended that the following appended claims include all such alterations, permutations, and equivalents as fall within the true spirit and scope of the present invention.

The invention claimed is:

1. A method, comprising:
[receiving a connection from a remote client device;]
receiving a selection of at least one haptic effect from [the remote client] *a first device*;
transmitting the at least one haptic effect to the [remote client] *first device*;
receiving a message from a second device; and
transmitting the message to the [remote client] *first device*, the message including a parameter configured to cause the remote [client] *first device* to output the at least one haptic effect.
2. The method of claim 1, wherein the [remote client] *first device* comprises a wireless device *and an actuator*.
3. The method of claim 1, wherein the at least one haptic effect comprises a haptic effect and a sound.
4. The method of claim 1, further comprising storing the at least one haptic effect on the [local client] *second device*.
5. The method of claim 1, wherein the message comprises text information.
6. A system, comprising:
a first device in communication with a network [and comprising an actuator], the first device configured to:
receive a selection from a second device of at least one haptic effect;
transmit the at least one haptic effect from the first device to the second device based at least in part on the selection[.];
receive a message from a third device[.]; and
transmit the message to the second device, the message including a parameter configured to cause the second device to output the at least one haptic effect.
7. The system of claim 6, wherein the [remote client] *second device* comprises a wireless device.
8. The system of claim 6, wherein the at least one haptic effect comprises a haptic effect and a sound.
9. The system of claim 6, wherein the [remote client] *second device* is further configured to store the copy of the at least one haptic effect.
10. The system of claim 6, wherein the message comprises text information.
11. A *non-transitory* computer-readable medium comprising program code, the program code comprising:
[program code for connecting to a first device from a local client device;]
program code for selecting, *at a local device*, at least one haptic effect [from the] *stored on a first device*;
program code for receiving, *at the local device*, the at least one haptic effect from the first device;
program code for receiving, *at the local device*, a message from a remote device; and

program code for outputting the at least one haptic effect to the local [client] device based at least in part on the message.

12. The *non-transitory* computer-readable medium of claim 11, wherein the at least one haptic effect comprises a haptic effect and a sound.

13. The *non-transitory* computer-readable medium of claim 11, further comprising program code for storing the at least one haptic effect on the local [client] device.

14. The *non-transitory* computer-readable medium of claim 11, wherein the local client device comprises a wireless device.

15. The *non-transitory* computer-readable medium of claim 11, wherein the at least one haptic effect comprises a haptic effect and a sound.

16. The *non-transitory* computer-readable medium of claim 11, wherein the message comprises text information.

17. A *non-transitory* computer-readable medium comprising:

program code for receiving a text message from a remote device, the text message comprising data;

program code for identifying a haptic effect based on the data;

program code for displaying the text message; and

program code for outputting the haptic effect.

18. The *non-transitory* computer-readable medium of claim 17 wherein the data comprises force information, and wherein the program code for identifying the haptic effect comprises program code for generating a haptic effect based on the force information.

19. The *non-transitory* computer-readable medium of claim 17, wherein the data comprises an emoticon.

20. The *non-transitory* computer-readable medium of claim 21, wherein the data comprises an emoticon.

21. A device comprising:

an input device;

a network interface;

a processor in communication with the network interface and the input device, the processor configured to:

receive a text message from a remote device, the text message comprising data;

identify a haptic effect based on the data;

display the text message; and

output the haptic effect.

22. The device of claim 21 wherein the data comprises force information, and wherein the processor is configured to identify the haptic effect based on the force information.

23. A *non-transitory* computer-readable medium comprising program code, the program code comprising:

program code for receiving an input from a user, the input comprising a text message, the text message comprising force information; and

program code for transmitting the text message to a remote wireless device, the force information configured to cause the remote wireless device to output a haptic effect.

24. The *non-transitory* computer-readable medium of claim 23, wherein the program code for transmitting the text message comprises program code for transmitting the text message over a wireless network.

25. The *non-transitory* computer-readable medium of claim 23, wherein the program code for transmitting the text message comprises program code for transmitting the text message over a telephone network.

26. A device comprising:

an input device;

a network interface;

a processor in communication with the network interface and the input device, the processor configured to:

receive a text message from a remote device, the text message comprising data;

identify a haptic effect based on the data;

display the text message; and

output the haptic effect.

a processor in communication with the network interface and the input device, the processor configured to: receive an input from a user, the input comprising a text message, the text message comprising data; and transmit the text message to a remote device, the data configured to cause the remote device to output a haptic effect.

27. The device of claim 26, wherein the device further comprises a microphone and wherein the processor is further configured to:

receive a spoken message from the microphone, determine force information associated with the spoken message; and transmit the spoken message and the force information to the remote device using the network interface.

28. The device of claim 26, wherein the network interface is a wireless network interface.

29. The device of claim 26, wherein the processor is further configured to associate force information with the text message, and transmit the force information.

30. The device of claim 29, the processor further configured to determine the force information based on a selection of a haptic effect by a user.

31. The device of claim 29, the processor further configured to determine the haptic effect based on voice recognition of the spoken message.

32. A non-transitory computer-readable medium comprising program code, the program code comprising:

program code for receiving an input from a user, the input comprising speech; program code for determining force information associated with the speech; and program code for transmitting the speech and the force information to a remote device, the force information configured to cause the remote device to output a haptic effect.

33. The non-transitory computer-readable medium of claim 32, wherein determining the force information is based on a selection of a haptic effect by a user.

34. The non-transitory computer-readable medium of claim 32, wherein determining the force information is based on voice recognition of the speech.

35. A non-transitory computer-readable medium comprising:

program code for receiving a message from a user device, the message comprising data; program code for identifying a haptic effect based on the data; program code for displaying the message; and program code for outputting the haptic effect.

36. The non-transitory computer-readable medium of claim 35, wherein the data comprises haptic information, and wherein the program code for identifying the haptic effect comprises program code for generating the haptic effect based on the haptic information.

37. The non-transitory computer-readable medium of claim 35, wherein the data comprises at least one or more of an emoticon, an animated graphic, an animated image, a static graphic, a static image, or media data.

38. The non-transitory computer-readable medium of claim 37, wherein the program code for program code for identifying the haptic effect comprises program code for generating a haptic effect based on the haptic information in coordination with the display of the at least one or more of the emoticon, the animated graphic, the animated image, the static graphic, the static image, or media data.

39. A device comprising: an recipient device including a display; a network interface;

a processor in communication with the network interface and the recipient device, the processor configured to: receive a message from a sender device, the message comprising data; identify a haptic effect based on the data; display the message; and output the haptic effect.

40. The device of claim 39 wherein the recipient device further comprises a haptic attribute designation option for the recipient device.

41. The device of claim 39 wherein the data comprises haptic information, and wherein the processor is configured to identify the haptic effect based on the haptic information.

42. The device of claim 39, wherein the data comprises at least one or more of an emoticon, an animated graphic, an animated image, a static graphic, a static image, or media data.

43. The device of claim 42, wherein the data comprises haptic information, and wherein the processor is configured to coordinate the output the haptic effect based on the haptic information with the display on the recipient device of the at least one or more of the emoticon, the animated graphic, the animated image, the static graphic, the static image, or media data.

44. A non-transitory computer-readable medium comprising program code, the program code comprising:

program code for receiving an input from a user, the input comprising a message, the message comprising haptic information; and program code for transmitting the message to a recipient wireless device, the haptic information configured to cause the recipient wireless device to output a haptic effect.

45. The non-transitory computer-readable medium of claim 44, wherein the program code for transmitting the message comprises program code for transmitting the message over a wireless network.

46. The non-transitory computer-readable medium of claim 44, wherein the program code for transmitting the message comprises program code for transmitting the message over a telephone network.

47. A device comprising: an input device;

a network interface; a processor in communication with the network interface and the input device, the processor configured to: receive an input from a user, the input comprising a message, the message comprising data; and transmit the message to a recipient device, the data configured to cause the recipient device to output a haptic effect.

48. A non-transitory computer-readable medium comprising:

program code for receiving a message from a remote device, the message comprising at least one or more of an emoticon, an animated graphic, an animated image, a static graphic, a static image, or media data; program code for identifying a haptic effect based on the at least one or more of the emoticon, the animated graphic, the animated image, the static graphic, the static image, or media data;

program code for displaying the message; and program code for outputting the haptic effect coordinated with the displaying of the at least one or more of the

19

emoticon, the animated graphic, the animated image, the static graphic, the static image, or media data.

49. *A device comprising:*

an input device;

a network interface;

a processor in communication with the network interface and the input device, the processor configured to:

receive a message from a sender device, the message comprising at least one or more of an emoticon, an animated graphic, an animated image, a static graphic, a static image, or media data;

identify a haptic effect based on the at least one or more of the emoticon, the animated graphic, the animated image, the static graphic, the static image, or media data;

display the message; and

output the haptic effect.

50. *A non-transitory computer-readable medium comprising program code, the program code comprising:*

program code for receiving an input from a user, the input comprising a message, the message comprising haptic information and at least one or more of an emoticon, an animated graphic, an animated image, a static graphic, a static image, or media data; and

program code for transmitting the message to a recipient wireless device, the haptic information configured to cause the recipient wireless device to output a haptic

20

effect coordinated with the display of the at least one or more of the emoticon, the animated graphic, the animated image, the static graphic, the static image, or media data.

5 51. *The non-transitory computer-readable medium of claim 50, wherein the program code for transmitting the message comprises program code for transmitting the message over a wireless network.*

10 52. *The non-transitory computer-readable medium of claim 50, wherein the program code for transmitting the message comprises program code for transmitting the message over a telephone network.*

53. *A device comprising:*

an input device;

a network interface;

a processor in communication with the network interface and the input device, the processor configured to:

receive an input from a user, the input comprising a message, the message comprising at least one or more of an emoticon, an animated graphic, an animated image, a static graphic, a static image, or media data; and

transmit the message to a recipient wireless device, the data configured to cause the recipient wireless device to output a haptic effect.

* * * * *