



US00RE46139E

(19) **United States**  
(12) **Reissued Patent**  
**Kida et al.**

(10) **Patent Number:** **US RE46,139 E**  
(45) **Date of Reissued Patent:** **Sep. 6, 2016**

(54) **LANGUAGE INPUT INTERFACE ON A DEVICE**  
  
(71) Applicants: **Yasuo Kida**, Palo Alto (CA); **Kenneth Kocienda**, San Jose, CA (US); **Elizabeth Caroline Furches Cranfill**, San Francisco, CA (US)  
  
(72) Inventors: **Yasuo Kida**, Palo Alto (CA); **Kenneth Kocienda**, San Jose, CA (US); **Elizabeth Caroline Furches Cranfill**, San Francisco, CA (US)

5,282,265 A 1/1994 Rohra Suda et al.  
5,379,057 A 1/1995 Clough et al.  
5,386,556 A 1/1995 Hedin et al.  
5,434,777 A 7/1995 Luciw  
5,479,488 A 12/1995 Lennig et al.  
5,526,259 A 6/1996 Kaji  
5,535,119 A 7/1996 Ito et al.  
5,577,241 A 11/1996 Spencer  
5,608,624 A 3/1997 Luciw  
5,675,362 A 10/1997 Clough et al.  
5,682,539 A 10/1997 Conrad et al.  
5,727,950 A 3/1998 Cook et al.

(Continued)

(73) Assignee: **APPLE INC.**, Cupertino, CA (US)

**FOREIGN PATENT DOCUMENTS**

(21) Appl. No.: **14/516,533**  
(22) Filed: **Oct. 16, 2014**

CN 1949158 A 4/2007  
CN 101021763 8/2007

(Continued)

**Related U.S. Patent Documents**

**OTHER PUBLICATIONS**

Reissue of:  
(64) Patent No.: **8,289,283**  
Issued: **Oct. 16, 2012**  
Appl. No.: **12/042,309**  
Filed: **Mar. 4, 2008**

“Iphone is Big in Japan”, Wall Street Journal May 17, 2000.

(Continued)

(51) **Int. Cl.**  
**G06F 3/041** (2006.01)  
**G06F 3/023** (2006.01)  
**G06F 3/0488** (2013.01)  
(52) **U.S. Cl.**  
CPC ..... **G06F 3/0237** (2013.01); **G06F 3/04886** (2013.01)  
(58) **Field of Classification Search**  
CPC .. G06F 17/2863; G06F 3/018; G06F 3/0237; G06F 3/04886  
USPC ..... 704/2, 3; 345/168, 173–182; 178/18.01; 200/512; 340/407.1  
See application file for complete search history.


*Primary Examiner* — Kenneth J Whittington  
(74) *Attorney, Agent, or Firm* — Morrison & Foerster LLP

(57) **ABSTRACT**

Methods, systems, and apparatus, including computer program products, for inputting text. A virtual keyboard is presented in a first region of a touch sensitive display of a device. An input representing a phonetic string is received on the virtual keyboard. The entered phonetic string is presented in a second region of the touch sensitive display. One or more candidates are identified based on the phonetic string. At least a subset of the candidates is presented. An input selecting one of the candidates is received. The entered phonetic string is replaced with the selected candidate.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
4,974,191 A 11/1990 Amirghodsi et al.  
5,128,672 A 7/1992 Kaehler

**107 Claims, 9 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,748,974 A	5/1998	Johnson	7,119,794 B2	10/2006	Kong
5,794,050 A	8/1998	Dahlgren et al.	7,127,046 B1	10/2006	Smith et al.
5,826,261 A	10/1998	Spencer	7,136,710 B1	11/2006	Hoffberg et al.
5,895,466 A	4/1999	Goldberg et al.	7,137,076 B2	11/2006	Iwema et al.
5,899,972 A	5/1999	Miyazawa et al.	7,137,126 B1	11/2006	Coffman et al.
5,915,249 A	6/1999	Spencer	7,139,714 B2	11/2006	Bennett et al.
5,959,629 A *	9/1999	Masui ..... 715/808	7,147,562 B2	12/2006	Ohara et al.
5,987,404 A	11/1999	Della Pietra et al.	7,177,798 B2	2/2007	Hsu et al.
6,052,656 A	4/2000	Suda et al.	7,200,559 B2	4/2007	Wang
6,081,750 A	6/2000	Hoffberg et al.	7,203,646 B2	4/2007	Bennett
6,088,731 A	7/2000	Kiraly et al.	7,216,073 B2	5/2007	Lavi et al.
6,115,053 A	9/2000	Perlin	7,216,080 B2	5/2007	Tsiao et al.
6,144,938 A	11/2000	Surace et al.	7,225,125 B2	5/2007	Bennett et al.
6,188,999 B1	2/2001	Moody	7,233,904 B2	6/2007	Luisi
6,233,559 B1	5/2001	Balakrishnan	7,277,854 B2	10/2007	Bennett et al.
6,278,968 B1	8/2001	Franz et al.	7,290,039 B1	10/2007	Lisitsa et al.
6,286,064 B1	9/2001	King	7,324,947 B2	1/2008	Jordan et al.
6,323,846 B1	11/2001	Westerman et al.	7,349,953 B2	3/2008	Lisitsa et al.
6,334,103 B1	12/2001	Surace et al.	7,376,556 B2	5/2008	Bennett
6,356,866 B1	3/2002	Pratley	7,376,645 B2	5/2008	Bernard
6,421,672 B1	7/2002	McAllister et al.	7,376,648 B2	5/2008	Johnson
6,434,524 B1	8/2002	Weber	7,379,874 B2	5/2008	Schmid et al.
6,446,076 B1	9/2002	Burkey et al.	7,386,449 B2	6/2008	Sun et al.
6,453,292 B2	9/2002	Ramaswamy et al.	7,392,185 B2	6/2008	Bennett
6,490,563 B2	12/2002	Hon	7,398,209 B2	7/2008	Kennewick et al.
6,499,013 B1	12/2002	Weber	7,403,888 B1 *	7/2008	Wang ..... G06F 3/018 704/2
6,501,937 B1	12/2002	Ho et al.	7,403,938 B2	7/2008	Harrison et al.
6,513,063 B1	1/2003	Julia et al.	7,409,337 B1	8/2008	Potter et al.
6,523,061 B1	2/2003	Halverson et al.	7,415,100 B2	8/2008	Cooper et al.
6,526,395 B1	2/2003	Morris	7,426,467 B2	9/2008	Nashida et al.
6,532,444 B1	3/2003	Weber	7,447,635 B1	11/2008	Konopka et al.
6,567,549 B1 *	5/2003	Marianetti et al. .... 382/189	7,454,351 B2	11/2008	Jeschke et al.
6,570,557 B1	5/2003	Westerman et al.	7,475,010 B2	1/2009	Chao
6,598,039 B1	7/2003	Livowsky	7,483,894 B2	1/2009	Cao
6,601,026 B2	7/2003	Appelt et al.	7,502,632 B2	3/2009	Ciminelli
6,615,172 B1	9/2003	Bennett et al.	7,502,738 B2	3/2009	Kennewick et al.
6,633,846 B1	10/2003	Bennett et al.	7,526,466 B2	4/2009	Au
6,650,735 B2	11/2003	Burton et al.	7,539,656 B2	5/2009	Fratkina et al.
6,661,409 B2	12/2003	Demartines et al.	7,546,382 B2	6/2009	Healey et al.
6,665,640 B1	12/2003	Bennett et al.	7,548,895 B2	6/2009	Pulsipher
6,677,932 B1	1/2004	Westerman	7,555,431 B2	6/2009	Bennett
6,691,111 B2	2/2004	Lazaridis et al.	7,599,918 B2	10/2009	Shen et al.
6,691,151 B1	2/2004	Cheyser et al.	7,616,190 B2	11/2009	Li
6,735,632 B1	5/2004	Kiraly et al.	7,620,549 B2	11/2009	Di Cristo et al.
6,742,021 B1	5/2004	Halverson et al.	7,624,007 B2	11/2009	Bennett
6,757,362 B1	6/2004	Cooper et al.	7,634,409 B2	12/2009	Kennewick et al.
6,757,718 B1	6/2004	Halverson et al.	7,640,160 B2	12/2009	Di Cristo et al.
6,766,179 B1	7/2004	Shiau et al.	7,647,225 B2	1/2010	Bennett et al.
6,778,951 B1	8/2004	Contractor	7,657,424 B2	2/2010	Bennett
6,789,231 B1	9/2004	Reynar	7,672,841 B2	3/2010	Bennett
6,792,082 B1	9/2004	Levine	7,676,026 B1	3/2010	Baxter, Jr.
6,807,574 B1	10/2004	Partovi et al.	7,684,985 B2	3/2010	Dominach et al.
6,810,272 B2	10/2004	Kraft	7,693,552 B2	4/2010	Ciminelli
6,822,585 B1	11/2004	Ni	7,693,720 B2	4/2010	Kennewick et al.
6,842,767 B1	1/2005	Partovi et al.	7,698,131 B2	4/2010	Bennett
6,848,080 B1	1/2005	Lee	7,702,500 B2	4/2010	Blaedow
6,851,115 B1	2/2005	Cheyser et al.	7,702,508 B2	4/2010	Bennett
6,859,931 B1	2/2005	Cheyser et al.	7,707,027 B2	4/2010	Balchandran et al.
6,888,536 B2	5/2005	Westerman et al.	7,707,267 B2	4/2010	Lisitsa et al.
6,895,380 B2	5/2005	Sepe, Jr.	7,711,672 B2	5/2010	Au
6,895,558 B1	5/2005	Loveland	7,716,056 B2	5/2010	Weng et al.
6,928,614 B1	8/2005	Everhart	7,720,674 B2	5/2010	Kaiser et al.
6,937,975 B1	8/2005	Elworthy	7,725,307 B2	5/2010	Bennett
6,964,023 B2	11/2005	Maes et al.	7,725,320 B2	5/2010	Bennett
6,980,949 B2	12/2005	Ford	7,725,321 B2	5/2010	Bennett
6,996,531 B2	2/2006	Korall et al.	7,729,904 B2	6/2010	Bennett
7,027,974 B1	4/2006	Busch et al.	7,729,916 B2	6/2010	Coffman et al.
7,030,863 B2	4/2006	Longe et al.	7,734,461 B2	6/2010	Kwak et al.
7,036,128 B1	4/2006	Julia et al.	7,752,152 B2	7/2010	Paek et al.
7,050,977 B1	5/2006	Bennett	7,783,486 B2	8/2010	Rosser et al.
7,062,428 B2	6/2006	Hogenhout et al.	7,801,722 B2	9/2010	Kotipalli
7,069,560 B1	6/2006	Cheyser et al.	7,809,570 B2	10/2010	Kennewick et al.
7,092,928 B1	8/2006	Elad et al.	7,818,176 B2	10/2010	Freeman et al.
7,096,432 B2	8/2006	Huapaya et al.	7,822,608 B2	10/2010	Cross, Jr. et al.
7,107,204 B1	9/2006	Liu	7,831,426 B2	11/2010	Bennett
			7,840,400 B2	11/2010	Lavi et al.
			7,873,519 B2	1/2011	Bennett
			7,873,654 B2	1/2011	Bernard



(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,881,936	B2	2/2011	Longé et al.	
7,912,702	B2	3/2011	Bennett	
7,917,367	B2	3/2011	Di Cristo et al.	
7,917,497	B2	3/2011	Harrison et al.	
7,920,678	B2	4/2011	Cooper et al.	
7,930,168	B2	4/2011	Weng et al.	
7,949,529	B2	5/2011	Weider et al.	
7,974,844	B2	7/2011	Sumita	
7,983,917	B2	7/2011	Kennewick et al.	
7,983,997	B2	7/2011	Allen et al.	
7,987,151	B2	7/2011	Schott et al.	
8,000,453	B2	8/2011	Cooper et al.	
8,005,679	B2	8/2011	Jordan et al.	
8,015,006	B2	9/2011	Kennewick et al.	
8,041,570	B2	10/2011	Mirkovic et al.	
8,055,708	B2	11/2011	Chitsaz et al.	
8,069,046	B2	11/2011	Kennewick et al.	
8,073,681	B2	12/2011	Baldwin et al.	
8,082,153	B2	12/2011	Coffinan et al.	
8,095,364	B2	1/2012	Longé et al.	
8,107,401	B2	1/2012	John et al.	
8,112,275	B2	2/2012	Kennewick et al.	
8,165,886	B1	4/2012	Gagnon et al.	
8,289,283	B2	10/2012	Kida	
8,564,541	B2	10/2013	Chou	
2002/0167545	A1	11/2002	Kang et al.	
2002/0168107	A1	11/2002	Tang et al.	
2003/0160817	A1	8/2003	Ishida et al.	
2003/0216913	A1	11/2003	Keely	
2004/0006458	A1 *	1/2004	Fux	G06F 17/2863 704/8
2004/0140956	A1 *	7/2004	Kushler et al.	345/168
2004/0230912	A1	11/2004	Clow et al.	
2005/0024341	A1	2/2005	Gillespie et al.	
2005/0071332	A1	3/2005	Ortega et al.	
2005/0080625	A1	4/2005	Bennett et al.	
2005/0099408	A1 *	5/2005	Seto et al.	345/179
2005/0119897	A1	6/2005	Bennett et al.	
2005/0152600	A1	7/2005	Chen et al.	
2005/0174333	A1	8/2005	Robinson et al.	
2006/0053387	A1	3/2006	Ording	
2006/0085757	A1	4/2006	Andre et al.	
2006/0117067	A1	6/2006	Wright et al.	
2006/0122834	A1	6/2006	Bennett	
2006/0143007	A1	6/2006	Koh et al.	
2006/0144211	A1	7/2006	Yoshimoto	
2006/0265668	A1 *	11/2006	Rainisto	G06F 3/0236 715/816
2006/0274051	A1	12/2006	Longe et al.	
2007/0055529	A1	3/2007	Kanevsky et al.	
2007/0088556	A1	4/2007	Andrew	
2007/0100790	A1	5/2007	Cheyser et al.	
2007/0120822	A1	5/2007	Iso	
2007/0139382	A1 *	6/2007	Kotipalli	G06F 3/0236 345/168
2007/0185917	A1	8/2007	Prahlad et al.	
2007/0282595	A1	12/2007	Tunning et al.	
2008/0015864	A1	1/2008	Ross et al.	
2008/0021708	A1	1/2008	Bennett et al.	
2008/0030481	A1	2/2008	Gunn et al.	
2008/0034032	A1	2/2008	Healey et al.	
2008/0052063	A1	2/2008	Bennett et al.	
2008/0094356	A1	4/2008	Ording et al.	
2008/0120112	A1	5/2008	Jordan et al.	
2008/0140657	A1	6/2008	Azvine et al.	
2008/0221903	A1	9/2008	Kanevsky et al.	
2008/0228496	A1	9/2008	Yu et al.	
2008/0247519	A1	10/2008	Abella et al.	
2008/0300878	A1	12/2008	Bennett	
2009/0006343	A1	1/2009	Platt et al.	
2009/0030800	A1	1/2009	Grois	
2009/0037837	A1 *	2/2009	Raghunath et al.	715/773
2009/0058823	A1	3/2009	Kocienda	
2009/0076796	A1	3/2009	Daraselina	
2009/0077464	A1	3/2009	Goldsmith et al.	

2009/0100049	A1	4/2009	Cao
2009/0150156	A1	6/2009	Kennewick et al.
2009/0157401	A1	6/2009	Bennett
2009/0164441	A1	6/2009	Cheyser
2009/0171664	A1	7/2009	Kennewick et al.
2009/0226091	A1	9/2009	Goldsmith et al.
2009/0265669	A1	10/2009	Kida et al.
2009/0295737	A1	12/2009	Goldsmith
2009/0299745	A1	12/2009	Kennewick et al.
2010/0005081	A1	1/2010	Bennett
2010/0023320	A1	1/2010	Di Cristo et al.
2010/0036660	A1	2/2010	Bennett
2010/0042400	A1	2/2010	Block et al.
2010/0145700	A1	6/2010	Kennewick et al.
2010/0204986	A1	8/2010	Kennewick et al.
2010/0217604	A1	8/2010	Baldwin et al.
2010/0228540	A1	9/2010	Bennett
2010/0235341	A1	9/2010	Bennett
2010/0277579	A1	11/2010	Cho et al.
2010/0280983	A1	11/2010	Cho et al.
2010/0286985	A1	11/2010	Kennewick et al.
2010/0299142	A1	11/2010	Freeman et al.
2010/0312547	A1	12/2010	van Os et al.
2010/0318576	A1	12/2010	Kim
2010/0332235	A1	12/2010	David
2011/0082688	A1	4/2011	Kim et al.
2011/0112827	A1	5/2011	Kennewick et al.
2011/0112921	A1	5/2011	Kennewick et al.
2011/0119049	A1	5/2011	Ylonen
2011/0125540	A1	5/2011	Jang et al.
2011/0131036	A1	6/2011	Dicristo et al.
2011/0131045	A1	6/2011	Cristo et al.
2011/0144999	A1	6/2011	Jang et al.
2011/0161076	A1	6/2011	Davis et al.
2011/0175810	A1	7/2011	Markovic et al.
2011/0184730	A1	7/2011	Lebeau et al.
2011/0231182	A1	9/2011	Weider et al.
2011/0231188	A1	9/2011	Kennewick et al.
2011/0279368	A1	11/2011	Klein et al.
2011/0306426	A1	12/2011	Novak et al.
2012/0002820	A1	1/2012	Leichter
2012/0016678	A1	1/2012	Gruber et al.
2012/0020490	A1	1/2012	Leichter
2012/0022787	A1	1/2012	Lebeau et al.
2012/0022857	A1	1/2012	Baldwin et al.
2012/0022860	A1	1/2012	Lloyd et al.
2012/0022868	A1	1/2012	Lebeau et al.
2012/0022869	A1	1/2012	Lloyd et al.
2012/0022870	A1	1/2012	Kristjansson et al.
2012/0022874	A1	1/2012	Lloyd et al.
2012/0022876	A1	1/2012	Lebeau et al.
2012/0023088	A1	1/2012	Cheng et al.
2012/0034904	A1	2/2012	Lebeau et al.
2012/0035908	A1	2/2012	Lebeau et al.
2012/0035924	A1	2/2012	Jitkoff et al.
2012/0035931	A1	2/2012	Lebeau et al.
2012/0035932	A1	2/2012	Jitkoff et al.
2012/0042343	A1	2/2012	Laligand et al.

## FOREIGN PATENT DOCUMENTS

EP	0930760	7/1999
EP	1245023	10/2002
EP	1245023 (A1)	10/2002
EP	1698982	9/2006
EP	1949158	7/2008
JP	6019965	1/1994
JP	08-272787	10/1996
JP	10-049272	2/1998
JP	2000-112636	4/2000
JP	2001-125896	5/2001
JP	2002-024212	1/2002
JP	2002-108543	4/2002
JP	3314276	8/2002
JP	2002-325965	11/2002
JP	2002-0325965	11/2002
JP	2003-517158	5/2003
JP	2003517158 (A)	5/2003
JP	2005-092441	4/2005



(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

JP	2009-036999	2/2009
KR	10-0776800	11/2007
KR	10-0776800 B1	11/2007
KR	10-0810500	3/2008
KR	10-0810500 B1	3/2008
KR	10 2008 109322 A	12/2008
KR	20080109322	12/2008
KR	10 2009 086805 A	8/2009
KR	20090086805	8/2009
KR	10-0920267	10/2009
KR	10-0920267 B1	10/2009
KR	10 2011 0113414 A	10/2011
KR	20110113414	10/2011
WO	WO-00/74240	12/2000
WO	WO-2005/008899	1/2005
WO	WO-2005/064587	7/2005
WO	WO-2007/037809	4/2007
WO	WO-2007/047188	4/2007
WO	WO-2007/070223	6/2007
WO	WO-2009/032483	3/2009
WO	WO-2009/111138	9/2009
WO	WO-2011/088053	7/2011
WO	WO 2011/088053 A2	7/2011

## OTHER PUBLICATIONS

“Japan belongs to Apple: iPhone claims top 10 spots in total smartphone sales in November,” Rocket News 24, Nov. 13, 2013. Alfred App, 2011, <http://www.alfredapp.com/>, 5 pages.

Ambite, J.L., et al., “Design and Implementation of the CALO Query Manager,” Copyright .COPYRGT. 2006, American Association for Artificial Intelligence, ([www.aaai.org](http://www.aaai.org)), 8 pages.

Ambite, J.L., et al., “Integration of Heterogeneous Knowledge Sources in the CALO Query Manager,” 2005, The 4th International Conference on Ontologies, DataBases, and Applications of Semantics (ODBASE), Agia Napa, Cyprus, <http://www.isi.edu/people/ambite/publications/integration.sub.--he-terogeneous.sub.--knowledge.sub.--sources.sub.--calo.sub.--query.sub.--man-ager>, 18 pages.

Belvin, R. et al., “Development of the HRL Route Navigation Dialogue System,” 2001, in Proceedings of the First International Conference on Human Language Technology Research, Paper, Copyright .COPYRGT. 2001 HRL Laboratories, LLC, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.10.6538>, 5 pages.

Cheyen, A. et al., “Spoken Language and Multimodal Applications for Electronic Realities,” .COPYRGT. Springer-Verlag London Ltd, Virtual Reality 1999, 3:1-15, 15 pages.

Elio, R. et al., (1999) “On Abstract Task Models and Conversation Policies,” <http://webdocs.cs.ualberta.ca/.about.ree/publications/papers2/ATS.AA99.pdf>, 10 pages.

Entry for “replace” from The American Heritage Dictionary 1048 (2nd ed. 1985).

Ericsson, S. et al., “Software illustrating a unified approach to multimodality and multilinguality in the in-home domain,” Dec. 22, 2006, Talk and Look: Tools for Ambient Linguistic Knowledge, <http://www.talk-project.eurice.eu/fileadmin/talk/publications.sub.--publi-c/deliverables.sub.--public/D1.sub.--6.pdf>, 127 pages.

Excerpt from Microsoft Computer Dictionary Release date: Mar. 22, 2002 ISBN: 0735614954.

Excerpt from Webster’s New World Computer Dictionary, 10th Edition release date: Apr. 18, 2003 ISBN: 076452478X.

Excerpt of Inside Macintosh, vol. 1, Addison-Wesley, Copyright 1985, ISBN 0-201-17731-5.

Excerpt of Running Microsoft Word 97 for Windows 95 and Windows 4.0, by Russell Borland, Microsoft Press, Copyright 1997.

Excerpt of Smalltalk-80: The Interactive Programming Environment, by Adele Goldberg, Addison-Wesley, Copyright 1984, ISBN 0-201-17732-4.

Gervasio, M. T., et al., Active Preference Learning for Personalized Calendar Scheduling Assistancae, Copyright .COPYRGT. 2005, <http://www.ai.sri.com/.about.gervasio/pubs/gervasio-iui05.pdf>, 8 pages.

Gruber, T. R., “It Is What It Does: The Pragmatics of Ontology for Knowledge Sharing,” (c) 2000, 2003, <http://www.cidoc-crm.org/docs/symposium.sub.--presentations/gruber.sub.--cidoc-ontology-2003.pdf>, 21 pages.

Gruber, T. R., “Siri, a Virtual Personal Assistant—Bringing Intelligence to the Interface,” Jun. 16, 2009, Keynote presentation at Semantic Technologies conference, Jun. 2009. <http://tomgruber.org/writing/semtech09.htm>, 22 pages.

Gruber, T. R., et al., “Nike: A National Infrastructure for Knowledge Exchange,” Oct. 1994, <http://www.eit.com/papers/nike/nike.html> and [nike.ps](http://www.eit.com/papers/nike/nike.ps), 10 pages.

Guzzoni, D., et al., “Active, A Platform for Building Intelligent Operating Rooms,” Surgetica 2007 Computer-Aided Medical Interventions: tools and applications, pp. 191-198, Paris, 2007, Sauramps Medical, <http://lsro.epfl.ch/page-68384-en.html>, 8 pages.

Guzzoni, D., et al., “Active, A Tool for Building Intelligent User Interfaces,” ASC 2007, Palma de Mallorca, <http://lsro.epfl.ch/page-34241.html>, 6 pages.

Guzzoni, D., et al., “Modeling Human-Agent Interaction with Active Ontologies,” 2007, AAAI Spring Symposium, Interaction Challenges for Intelligent Assistants, Stanford University, Palo Alto, California, 8 pages.

Hardawar, D., “Driving app Waze builds its own Siri for hands-free voice control,” Feb. 9, 2012, <http://venturebeat.com/2012/02/09/driving-app-waze-builds-its-own-siri-fo-r-hands-free-voice-control/>, 4 pages.

International Preliminary Report on Patentability in International Application No. PCT/US2008/072803 mailed Mar. 18, 2010.

International Preliminary Report on Patentability in PCT/US2009/033696 mailed Sep. 16, 2010, 6 pages.

International Search Report and Written Opinion dated Nov. 29, 2011, received in International Application No. PCT/US2011/20861, which corresponds to U.S. Appl. No. 12/987,982, 15 pages. (Thomas Robert Gruber).

International Search Report and Written Opinion, dated Apr. 29, 2009, issued in International Application No. PCT/US2009/033696. International Search Report and Written Opinion, dated Feb. 18, 2009, issued in International Application No. PCT/US2008/072803. Invitation to Pay Fees and Partial International Search Report, dated Nov. 11, 2008, issued in International Application No. PCT/US2008/072803.

Julia, L., et al., Un editeur interactif de tableaux dessines a main levee (An Interactive Editor for Hand-Sketched Tables), Traitement du Signal 1995, vol. 12, No. 6, 8 pages. No English Translation Available.

Karp, P. D., “A Generic Knowledge-Base Access Protocol,” May 12, 1994, <http://lecture.cs.buu.ac.th/.about.f50353/Document/gfp.pdf>, 66 pages.

Liu et al., “Online Recognition of Chinese Characters: The State-of-the-Art,” IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 26, No. 2, Feb. 2004, pp. 198-213.

Masui, “An Efficient Text Input Method for Pen-based Computers,” Proceedings of the ACM Conference on Human Factors in Computing System (CHI ’98), Apr. 1998, ACM press, pp. 328-335.

Masui, POBox: “An Efficient Text Input Method for Handheld and Ubiquitous Computers,” Proceedings of the International Symposium on Handheld and Ubiquitous Computer (HUC ’99), Sep. 1999, pp. 289-300.

McGuire, J., et al., “Shade: Technology for Knowledge-Based Collaborative Engineering,” 1993, Journal of Concurrent Engineering: Applications and Research (CERA), 18 pages.

Milward, D., et al., “D2.2: Dynamic Multimodal Interface Reconfiguration,” Talk and Look: Tools for Ambient Linguistic Knowledge, Aug. 8, 2006, <http://www.ihmc.us/users/nblaylock/Pubs/Files/talk.sub.--d2.2.pdf>, 69 pages.

Muhlhauser, M., “Context Aware Voice User Interfaces for Workflow Support,” Darmstadt 2007, <http://tuprints.ulb.tu-darmstadt.de/876/1/PhD.pdf>, 254 pages.



(56)

## References Cited

## OTHER PUBLICATIONS

Naone, E., "Trio: Intelligent Software Assistant," Mar.-Apr. 2009, Technology Review, <http://www.technologyreview.com/printer.sub.--friendly.sub.--article.aspx-?id=22117>, 2 pages.

Noth, E., et al., "Verbmobil: The Use of Prosody in the Linguistic Components of a Speech Understanding System," IEEE Transactions on Speech and Audio Processing, vol. 8, No. 5, Sep. 2000, 14 pages.

Rice, J., et al., (1995) "Monthly Program: Nov. 14, 1995," The San Francisco Bay Area Chapter of ACM SIGCHI, <http://www.baychi.org/calendar/19951114/>, 2 pages.

Rice, J., et al., (1996) "Using the Web Instead of a Window System," Knowledge Systems Laboratory, Stanford University, <http://tomgruber.org/writing/ksl-95-69.pdf>, 14 pages.

Rivlin, Z., et al., "Maestro: Conductor of Multimedia Analysis Technologies," 1999 SRI International, Communications of the Association for Computing Machinery (CACM), 7 pages.

Sacher, "Interactions in Chinese: Designing Interfaces for Asian Languages," Interactions Magazine, vol. 5, Issue 5, Sep.-Oct. 1998, pp. 28-38.

Seneff, S., et al., "A New Restaurant Guide Conversational System: Issues in Rapid Prototyping for Specialized Domains," Oct. 1996, [citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.16..rep...](http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.16..rep...), 4 pages.

Simonite, T., "One Easy Way to Make Siri Smarter," Oct. 18, 2011, Technology Review, <http://www.technologyreview.com/printersub.--friendly.sub.--article.aspx?id=389-15>, 2 pages.

Tofel, K., et al., "SpeakTolt: A personal assistant for older iPhones, iPads," Feb. 9, 2012, <http://gigaom.com/apple/speaktoit-siri-for-older-iphones-ipads/>, 7 pages.

Tucker, J., "Too lazy to grab your TV remote? Use Siri instead," Nov. 30, 2011, <http://www.engadget.com/2011/11/30/too-lazy-to-grab-your-tv-remote--use-siri-instead/>, 8 pages.

Tur, G., et al., "The-CALO-Meeting-Assistant System," IEEE Transactions on Audio, Speech, and Language Processing, vol. 18, No. 6, Aug. 2010, 11 pages.

Vlingo, "Vlingo Launches Voice Enablement Application on Apple App Store," Vlingo press release dated Dec. 3, 2008, 2 pages.

YouTube, "Knowledge Navigator," 5:34 minute video uploaded to YouTube by Knownav on Apr. 29, 2008, <http://www.youtube.com/watch?v=QRH8eimU.sub.--20on> Aug. 3, 2006, 1 page.

YouTube, "Send Text, Listen to and Send E-Mail 'By Voice' www.voiceassist.com," 2:11 minute video uploaded to YouTube by VoiceAssist on Jul. 30, 2009, <http://www.youtube.com/watch?v=0tEU61nHHA4>, 1 page.

YouTube, "Text'nDrive App Demo—Listen and Reply to your Messages by Voice while Driving!," 1:57 minute video uploaded to YouTube by TextnDrive on Apr 27, 2010, <http://www.youtube.com/watch?v=WaGfzoHsAMw>, 1 page.

Zue, V. W., "Toward Systems that Understand Spoken Language," Feb. 1994, ARPA Strategic Computing Institute, .COPYRGT.1994 IEEE, 9 pages.

Zue, V., "Conversational Interfaces: Advances and Challenges," Sep. 1997, <http://www.cs.cmu.edu/.about.dod/papers/zue97.pdf>, 10 pages.

H. Sacher, "Interactions in Chinese: Designing Interfaces for Asian Languages," Interactions Magazine, vol. 5, Issue 5, Sep.-Oct. 1998, pp. 28-38.

Translated First Office Action dated Jul. 29, 2010, issued in Chinese Patent Application No. 200910118235.X, 9 pages.

Invitation to Pay Fees and Partial International Search Report, dated Nov. 11, 2008, issued in International Application no. PCT/US2009/072803.

Kida et al., "Language Input Interface on a Device", U.S. Appl. No. 12/107,711, filed Apr. 22, 2008.

Goldsmith et al., "Identification of Candidate Characters for Text Input", U.S. Appl. No. 12/167,044, filed Jul. 2, 2008.

Chou, "Zhuyin Input Interface on a Device", U.S. Appl. No. 12/476,121, filed Jun. 1, 2009.

Authorized officer Philippe Becamel, International Preliminary Report on Patentability in PCT/US2009/033696 mailed Sep. 16, 2010, 7 pages.

Berry, P. M., et al., "PTIME: Personalized Assistance for Calendaring," ACM Transactions on Intelligent Systems and Technology, vol. 2, No. 4, Article 40, Publication date: Jul. 2011, 40:1-22, 22 pages.

Butcher, M., "EVI arrives in town to go toe-to-toe with Siri," Jan. 23, 2012, <http://techcrunch.com/2012/01/23/evi-arrives-in-town-to-go-toe-to-toe-with-siri/>, 2 pages.

Chen, Y., "Multimedia Siri Finds and Plays Whatever You Ask for," Feb. 9, 2012, <http://www.psfk.com/2012/02/nriultinnedia-siri.html>, 9 pages.

Cutkosky, M. R. et al., "PACT: An Experiment in Integrating Concurrent Engineering Systems," Journal, Computer, vol. 26 Issue 1, Jan. 1993, IEEE Computer Society Press Los Alamitos, CA, USA, <http://dl.acm.org/citation.cfm?id=165320>, 14 pages.

Evi, "Meet Evi: the one mobile app that provides solutions for your everyday problems," Feb. 8, 2012, <http://www.evi.com/>, 3 pages.

Feigenbaum, E., et al., "Computer-assisted Semantic Annotation of Scientific Life Works," 2007, <http://tomgruber.org/writing/stanford-cs300.pdf>, 22 pages.

Gannes, L., "Alfred App Gives Personalized Restaurant Recommendations," allthingsd.com, Jul. 18, 2011, <http://allthingsd.com/20110718/alfred-app-gives-personalized-restaurant-recommendations/>, 3 pages.

Gautier, P. O., et al. "Generating Explanations of Device Behavior Using Compositional Modeling and Causal Ordering," 1993, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.42.8394>, 9 pages.

Glass, A., "Explaining Preference Learning," 2006, <http://cs229.stanford.edu/proj2006/GlassExplainingPreferenceLearning.pdf>, 5 pages.

Gruber, T. R., et al., "An Ontology for Engineering Mathematics," in Jon Doyle, Piero Torasso, & Erik Sandewall, Eds., Fourth International Conference on Principles of Knowledge Representation and Reasoning, Gustav Stresemann Institut, Bonn, Germany, Morgan Kaufmann, 1994, <http://www-ksl.stanford.edu/knowledge-sharing/papers/engmath.html>, 22 pages.

Gruber, T. R., "A Translation Approach to Portable Ontology Specifications," Knowledge Systems Laboratory, Stanford University, Sep. 1992, Technical Report KSL 92-71, Revised Apr. 1993, 27 pages.

Gruber, T. R., "Automated Knowledge Acquisition for Strategic Knowledge," Knowledge Systems Laboratory, Machine Learning, 4, 293-336 (1989), 44 pages.

Gruber, T. R., "(Avoiding) the Travesty of the Commons," Presentation at NPUC 2006, New Paradigms for User Computing, IBM Almaden Research Center, Jul. 24, 2006. <http://tomgruber.org/writing/avoiding-travesty.htm>, 52 pages.

Gruber, T. R., "Big Think Small Screen: How semantic computing in the cloud will revolutionize the consumer experience on the phone," Keynote presentation at Web 3.0 conference, Jan. 27, 2010, <http://tomgruber.org/writing/web30jan2010.htm>, 41 pages.

Gruber, T. R., "Collaborating around Shared Content on the WWW," W3C Workshop on WWW and Collaboration, Cambridge, MA, Sep. 11, 1995, <http://www.w3.org/Collaboration/Workshop/Proceedings/P9.html>, 1 page.

Gruber, T. R., "Collective Knowledge Systems: Where the Social Web meets the Semantic Web," Web Semantics: Science, Services and Agents on the World Wide Web (2007), doi:10.1016/j.websem.2007.11.011, keynote presentation given at the 5th International Semantic Web Conference, Nov. 7, 2006, 19 pages.

Gruber, T. R., "Where the Social Web meets the Semantic Web," Presentation at the 5th International Semantic Web Conference, Nov. 7, 2006, 38 pages.

Gruber, T. R., "Despite our Best Efforts, Ontologies are not the Problem," AAAI Spring Symposium, Mar. 2008, <http://tomgruber.org/writing/aaai-ss08.htm>, 40 pages.

Gruber, T. R., "Enterprise Collaboration Management with Intraspect," Intraspect Software, Inc., Intraspect Technical White Paper Jul. 2001, 24 pages.



(56)

**References Cited**

## OTHER PUBLICATIONS

Gruber, T. R., "Every ontology is a treaty—a social agreement—among people with some common motive in sharing," Interview by Dr. Miltiadis D. Lytras, Official Quarterly Bulletin of AIS Special Interest Group on Semantic Web and Information Systems, vol. 1, Issue 3, 2004, <http://www.sigsemis.org> 1, 5 pages.

Gruber, T. R., et al., "Generative Design Rationale: Beyond the Record and Replay Paradigm," Knowledge Systems Laboratory, Stanford University, Dec. 1991, Technical Report KSL 92-59, Updated Feb. 1993, 24 pages.

Gruber, T. R., "Helping Organizations Collaborate, Communicate, and Learn," Presentation to NASA Ames Research, Mountain View, CA, Mar. 2003, <http://tomgruber.org/writing/organizational-intelligence-talk.htm>, 30 pages.

Gruber, T. R., "Intelligence at the Interface: Semantic Technology and the Consumer Internet Experience," Presentation at Semantic Technologies conference (SemTech08), May 20, 2008, <http://tomgruber.org/writing.htm>, 40 pages.

Gruber, T. R., Interactive Acquisition of Justifications: Learning "Why" by Being Told "What" Knowledge Systems Laboratory, Stanford University, Oct. 1990, Technical Report KSL 91-17, Revised Feb. 1991, 24 pages.

Gruber, T. R., et al., "Machine-generated Explanations of Engineering Models: A Compositional Modeling Approach," (1993) in Proc. International Joint Conference on Artificial Intelligence, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.34.930>, 7 pages.

Gruber, T. R., "2021: Mass Collaboration and the Really New Economy," TNTY Futures, the newsletter of the Next Twenty Years series, vol. 1, Issue 6, Aug. 2001, <http://www.tnty.com/newsletter/futures/archive/v01-05business.html>, 5 pages.

Gruber, T. R., "Ontologies, Web 2.0 and Beyond," Apr. 24, 2007, Ontology Summit 2007, <http://tomgruber.org/writing/ontolog-social-web-keynote.pdf>, 17 pages.

Gruber, T. R., "Ontology of Folksonomy: A Mash-up of Apples and Oranges," Originally published to the web in 2005, Int'l Journal on Semantic Web & Information Systems, 3(2), 2007, 7 pages.

Gruber, T. R., "TagOntology," Presentation to Tag Camp, [www.tagcamp.org](http://www.tagcamp.org), Oct. 29, 2005, 20 pages.

Gruber, T. R., et al., "Toward a Knowledge Medium for Collaborative Product Development," in Artificial Intelligence in Design 1992, from Proceedings of the Second International Conference on Artificial Intelligence in Design, Pittsburgh, USA, Jun. 22-25, 1992, 19 pages.

Gruber, T. R., "Toward Principles for the Design of Ontologies Used for Knowledge Sharing," in International Journal Human-Computer Studies 43, p. 907-928, substantial revision of paper presented at the International Workshop on Formal Ontology, Mar. 1993, Padova, Italy, available as Technical Report KSL 93-04, Knowledge Systems Laboratory, Stanford University, further revised Aug. 23, 1993, 23 pages.

Intraspect Software, "The Intraspect Knowledge Management Solution: Technical Overview," <http://tomgruber.org/writing/intraspect-whitepaper-1998.pdf>, 18 pages.

Lemon, O., et al., "Multithreaded Context for Robust Conversational Interfaces: Context-Sensitive Speech Recognition and Inter-

pretation of Corrective Fragments," Sep. 2004, ACM Transactions on Computer-Human Interaction, vol. 11, No. 3, 27 pages.

Leong, L., et al., "CASIS: A Context-Aware Speech Interface System," IUI'05, Jan. 9-12, 2005, Proceedings of the 10th international conference on Intelligent user interfaces, San Diego, California, USA, 8 pages.

Lieberman, H., et al., "Out of context: Computer systems that adapt to, and learn from, context," 2000, IBM Systems Journal, vol. 39, Nos. 3/4, 2000, 16 pages.

Lin, B., et al., "A Distributed Architecture for Cooperative Spoken Dialogue Agents with Coherent Dialogue State and History," 1999, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.42.272>, 4 pages.

Mitra, P., et al., "A Graph-Oriented Model for Articulation of Ontology Interdependencies," 2000, <http://ilpubs.stanford.edu:8090/442/1/2000-20.pdf>, 15 pages.

Moran, D. B., et al., "Multimodal User Interfaces in the Open Agent Architecture," Proc. of the 1997 International Conference on Intelligent User Interfaces (IUI97), 8 pages.

Mozer, M., "An Intelligent Environment Must be Adaptive," Mar./Apr. 1999, IEEE Intelligent Systems, 3 pages.

Neches, R., "Enabling Technology for Knowledge Sharing," Fall 1991, AI Magazine, pp. 37-56, (21 pages).

Sheth, A., et al., "Relationships at the Heart of Semantic Web: Modeling, Discovering, and Exploiting Complex Semantic Relationships," Oct. 13, 2002, Enhancing the Power of the Internet: Studies in Fuzziness and Soft Computing, SpringerVerlag, 38 pages.

Stent, A., et al., "The CommandTalk Spoken Dialogue System," 1999, <http://acl.ldc.upenn.edu/P/P99/P99-1024.pdf>, 8 pages.

Tur, G., et al., "The CALO Meeting Speech Recognition and Understanding System," 2008, Proc. IEEE Spoken Language Technology Workshop, 4 pages.

YouTube, "Text'nDrive App Demo—Listen and Reply to your Messages by Voice while Driving!," 1:57 minute video uploaded to YouTube by TextnDrive on Apr. 27, 2010, <http://www.youtube.com/watch?WaGfzoHsAMw>, 1 page.

YouTube, "Voice on the Go (BlackBerry)," 2:51 minute video uploaded to YouTube by VoiceOnTheGo on Jul. 27, 2009, <http://www.youtube.com/watch?v=pJqpWgQS98w>, 1 page.

Glass, J., et al., "Multilingual Spoken-Language Understanding in the MIT Voyager System," Aug. 1995, <http://groups.csail.mit.edu/sis/publications/1995/speechcomm95-voyager.pdf>, 29 pages.

Goddeau, D., et al., "A Form-Based Dialogue Manager for Spoken Language Applications," Oct. 1996, <http://phasedance.com/pdf/icslp96.pdf>, 4 pages.

Goddeau, D., et al., "Galaxy: A Human-Language Interface to On-Line Travel Information," 1994 International Conference on Spoken Language Processing, Sep. 18-22, 1994, Pacific Convention Plaza Yokohama, Japan, 6 pages.

Meng, H., et al., "Wheels: A Conversational System in the Automobile Classified Domain," Oct. 1996, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.16.3022>, 4 pages.

*Phoenix Solutions, Inc. v. West Interactive Corp.*, Document 40, Declaration of Christopher Schmandt Regarding the MIT Galaxy System dated Jul. 2, 2010, 162 pages.

Vlingo InCar, "Distracted Driving Solution with Vlingo InCar," 2:38 minute video uploaded to YouTube by Vlingo Voice on Oct. 6, 2010, <http://www.youtube.com/watch?v=Vqs8XfXgz4>, 2 pages.

\* cited by examiner




FIG. 1






FIG. 2






FIG. 3A






FIG. 3B






FIG. 3C






FIG. 3D






FIG. 3E





FIG. 3F



**FIG. 4**

## LANGUAGE INPUT INTERFACE ON A DEVICE

Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

### BACKGROUND

The subject matter of this specification is related generally to text input interfaces.

Traditional computer keyboards may be too large for portable devices, such as mobile phones, multimedia players, or personal digital assistants (PDAs). Some portable devices include a smaller version of the traditional computer keyboard or use a virtual keyboard to receive user input. A virtual keyboard can be of the form of a software application or a feature of a software application to simulate a computer keyboard. For example, in a portable device with a touch-sensitive display, a virtual keyboard can be used by a user to input text by selecting or tabbing areas of the touch-sensitive display corresponding to keys of the virtual keyboard.

These smaller keyboards and virtual keyboards may have keys that correspond to more than one character. For example, some of the keys can, by default, correspond to a character in the English language, for example, the letter "a," and may also correspond to other additional characters, such as another letter or the letter with an accent option, e.g., the character "ä," or other characters with accent options. Because of the physical limitations (e.g., size) of the virtual keyboard, a user may find it difficult to type characters not readily available on the virtual keyboard.

Input methods for devices having multi-language environments can present unique challenges with respect to input and spelling correction which may need to be tailored to the selected language to ensure accuracy and an efficient workflow.

### SUMMARY

In general, one aspect of the subject matter described in this specification can be embodied in methods that include the actions of presenting a virtual keyboard in a first region of a touch sensitive display of a device, receiving an input representing a phonetic string on the virtual keyboard, presenting the entered phonetic string in a second region of the touch sensitive display, identifying one or more candidates based on the phonetic string, presenting at least a subset of the candidates in the first region or the second region, receiving an input selecting one of the candidates, and replacing the entered phonetic string with the selected candidate. Other embodiments of this aspect include corresponding systems, apparatus, computer program products, and computer readable media.

Particular embodiments of the subject matter described in this specification can be implemented to realize one or more of the following advantages. Text in languages that require phonetic string-to-character conversion can be input more efficiently on a portable device. Error correction and word prediction techniques can be applied to entry of East Asian languages.

The details of one or more embodiments of the subject matter described in this specification are set forth in the

accompanying drawings and the description below. Other features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an example mobile device.

FIG. 2 is a block diagram of an example implementation of the mobile device of FIG. 1.

FIGS. 3A-3F illustrate an example user interface for entering text.

FIG. 4 illustrates an example text input process.

Like reference numbers and designations in the various drawings indicate like elements.

### DETAILED DESCRIPTION

#### Example Mobile Device

FIG. 1 is a block diagram of an example mobile device 100. The mobile device 100 can be, for example, a handheld computer, a personal digital assistant, a cellular telephone, a network appliance, a camera, a smart phone, an enhanced general packet radio service (EGPRS) mobile phone, a network base station, a media player, a navigation device, an email device, a game console, or a combination of any two or more of these data processing devices or other data processing devices.

#### Mobile Device Overview

In some implementations, the mobile device 100 includes a touch-sensitive display 102. The touch-sensitive display 102 can implement liquid crystal display (LCD) technology, light emitting polymer display (LPD) technology, or some other display technology. The touch sensitive display 102 can be sensitive to haptic and/or tactile contact with a user.

In some implementations, the touch-sensitive display 102 can comprise a multi-touch-sensitive display 102. A multi-touch-sensitive display 102 can, for example, process multiple simultaneous touch points, including processing data related to the pressure, degree, and/or position of each touch point. Such processing facilitates gestures and interactions with multiple fingers, chording, and other interactions. Other touch-sensitive display technologies can also be used, e.g., a display in which contact is made using a stylus or other pointing device. Some examples of multi-touch-sensitive display technology are described in U.S. Pat. Nos. 6,323, 846, 6,570,557, 6,677,932, and 6,888,536, each of which is incorporated by reference herein in its entirety.

In some implementations, the mobile device 100 can display one or more graphical user interfaces on the touch-sensitive display 102 for providing the user access to various system objects and for conveying information to the user. In some implementations, the graphical user interface can include one or more display objects 104, 106. In the example shown, the display objects 104, 106, are graphic representations of system objects. Some examples of system objects include device functions, applications, windows, files, alerts, events, or other identifiable system objects.

#### Example Mobile Device Functionality

In some implementations, the mobile device 100 can implement multiple device functionalities, such as a telephony device, as indicated by a phone object 110; an e-mail



device, as indicated by the e-mail object **112**; a network data communication device, as indicated by the Web object **114**; a Wi-Fi base station device (not shown); and a media processing device, as indicated by the media player object **116**. In some implementations, particular display objects **104**, e.g., the phone object **110**, the e-mail object **112**, the Web object **114**, and the media player object **116**, can be displayed in a menu bar **118**. In some implementations, device functionalities can be accessed from a top-level graphical user interface, such as the graphical user interface illustrated in FIG. 1. Touching one of the objects **110**, **112**, **114**, or **116** can, for example, invoke corresponding functionality.

In some implementations, the mobile device **100** can implement network distribution functionality. For example, the functionality can enable the user to take the mobile device **100** and provide access to its associated network while traveling. In particular, the mobile device **100** can extend Internet access (e.g., Wi-Fi) to other wireless devices in the vicinity. For example, mobile device **100** can be configured as a base station for one or more devices. As such, mobile device **100** can grant or deny network access to other wireless devices.

In some implementations, upon invocation of device functionality, the graphical user interface of the mobile device **100** changes, or is augmented or replaced with another user interface or user interface elements, to facilitate user access to particular functions associated with the corresponding device functionality. For example, in response to a user touching the phone object **110**, the graphical user interface of the touch-sensitive display **102** may present display objects related to various phone functions; likewise, touching of the email object **112** may cause the graphical user interface to present display objects related to various e-mail functions; touching the Web object **114** may cause the graphical user interface to present display objects related to various Web-surfing functions; and touching the media player object **116** may cause the graphical user interface to present display objects related to various media processing functions.

In some implementations, the top-level graphical user interface environment or state of FIG. 1 can be restored by pressing a button **120** located near the bottom of the mobile device **100**. In some implementations, each corresponding device functionality may have corresponding “home” display objects displayed on the touch-sensitive display **102**, and the graphical user interface environment of FIG. 1 can be restored by pressing the “home” display object.

In some implementations, the top-level graphical user interface can include additional display objects **106**, such as a short messaging service (SMS) object **130**, a calendar object **132**, a photos object **134**, a camera object **136**, a calculator object **138**, a stocks object **140**, a weather object **142**, a maps object **144**, a notes object **146**, a clock object **148**, an address book object **150**, and a settings object **152**. Touching the SMS display object **130** can, for example, invoke an SMS messaging environment and supporting functionality; likewise, each selection of a display object **132**, **134**, **136**, **138**, **140**, **142**, **144**, **146**, **148**, **150**, and **152** can invoke a corresponding object environment and functionality.

Additional and/or different display objects can also be displayed in the graphical user interface of FIG. 1. For example, if the device **100** is functioning as a base station for other devices, one or more “connection” objects may appear in the graphical user interface to indicate the connection. In some implementations, the display objects **106** can be con-

figured by a user, e.g., a user may specify which display objects **106** are displayed, and/or may download additional applications or other software that provides other functionalities and corresponding display objects.

In some implementations, the mobile device **100** can include one or more input/output (I/O) devices and/or sensor devices. For example, a speaker **160** and a microphone **162** can be included to facilitate voice-enabled functionalities, such as phone and voice mail functions. In some implementations, an up/down button **184** for volume control of the speaker **160** and the microphone **162** can be included. The mobile device **100** can also include an on/off button **182** for a ring indicator of incoming phone calls. In some implementations, a loud speaker **164** can be included to facilitate hands-free voice functionalities, such as speaker phone functions. An audio jack **166** can also be included for use of headphones and/or a microphone.

In some implementations, a proximity sensor **168** can be included to facilitate the detection of the user positioning the mobile device **100** proximate to the user’s ear and, in response, to disengage the touch-sensitive display **102** to prevent accidental function invocations. In some implementations, the touch-sensitive display **102** can be turned off to conserve additional power when the mobile device **100** is proximate to the user’s ear.

Other sensors can also be used. For example, in some implementations, an ambient light sensor **170** can be utilized to facilitate adjusting the brightness of the touch-sensitive display **102**. In some implementations, an accelerometer **172** can be utilized to detect movement of the mobile device **100**, as indicated by the directional arrow **174**. Accordingly, display objects and/or media can be presented according to a detected orientation, e.g., portrait or landscape. In some implementations, the mobile device **100** may include circuitry and sensors for supporting a location determining capability, such as that provided by the global positioning system (GPS) or other positioning systems (e.g., systems using Wi-Fi access points, television signals, cellular grids, Uniform Resource Locators (URLs)). In some implementations, a positioning system (e.g., a GPS receiver) can be integrated into the mobile device **100** or provided as a separate device that can be coupled to the mobile device **100** through an interface (e.g., port device **190**) to provide access to location-based services.

In some implementations, a port device **190**, e.g., a Universal Serial Bus (USB) port, or a docking port, or some other wired port connection, can be included. The port device **190** can, for example, be utilized to establish a wired connection to other computing devices, such as other communication devices **100**, network access devices, a personal computer, a printer, a display screen, or other processing devices capable of receiving and/or transmitting data. In some implementations, the port device **190** allows the mobile device **100** to synchronize with a host device using one or more protocols, such as, for example, the TCP/IP, HTTP, UDP and any other known protocol.

The mobile device **100** can also include a camera lens and sensor **180**. In some implementations, the camera lens and sensor **180** can be located on the back surface of the mobile device **100**. The camera can capture still images and/or video.

The mobile device **100** can also include one or more wireless communication subsystems, such as an 802.11b/g communication device **186**, and/or a Bluetooth™ communication device **188**. Other communication protocols can also be supported, including other 802.x communication protocols (e.g., WiMax, Wi-Fi, 3 G), code division multiple



access (CDMA), global system for mobile communications (GSM), Enhanced Data GSM Environment (EDGE), etc.

#### Example Mobile Device Architecture

FIG. 2 is a block diagram 200 of an example implementation of the mobile device 100 of FIG. 1. The mobile device 100 can include a memory interface 202, one or more data processors, image processors and/or central processing units 204, and a peripherals interface 206. The memory interface 202, the one or more processors 204 and/or the peripherals interface 206 can be separate components or can be integrated in one or more integrated circuits. The various components in the mobile device 100 can be coupled by one or more communication buses or signal lines.

Sensors, devices, and subsystems can be coupled to the peripherals interface 206 to facilitate multiple functionalities. For example, a motion sensor 210, a light sensor 212, and a proximity sensor 214 can be coupled to the peripherals interface 206 to facilitate the orientation, lighting, and proximity functions described with respect to FIG. 1. Other sensors 216 can also be connected to the peripherals interface 206, such as a positioning system (e.g., GPS receiver), a temperature sensor, a biometric sensor, or other sensing device, to facilitate related functionalities.

A camera subsystem 220 and an optical sensor 222, e.g., a charged coupled device (CCD) or a complementary metal-oxide semiconductor (CMOS) optical sensor, can be utilized to facilitate camera functions, such as recording photographs and video clips.

Communication functions can be facilitated through one or more wireless communication subsystems 224, which can include radio frequency receivers and transmitters and/or optical (e.g., infrared) receivers and transmitters. The specific design and implementation of the communication subsystem 224 can depend on the communication network(s) over which the mobile device 100 is intended to operate. For example, a mobile device 100 may include communication subsystems 224 designed to operate over a GSM network, a GPRS network, an EDGE network, a Wi-Fi or WiMax network, and a Bluetooth™ network. In particular, the wireless communication subsystems 224 may include hosting protocols such that the device 100 may be configured as a base station for other wireless devices.

An audio subsystem 226 can be coupled to a speaker 228 and a microphone 230 to facilitate voice-enabled functions, such as voice recognition, voice replication, digital recording, and telephony functions.

The I/O subsystem 240 can include a touch screen controller 242 and/or other input controller(s) 244. The touch-screen controller 242 can be coupled to a touch screen 246. The touch screen 246 and touch screen controller 242 can, for example, detect contact and movement or break thereof using any of a plurality of touch sensitivity technologies, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with the touch screen 246.

The other input controller(s) 244 can be coupled to other input/control devices 248, such as one or more buttons, rocker switches, thumb-wheel, infrared port, USB port, and/or a pointer device such as a stylus. The one or more buttons (not shown) can include an up/down button for volume control of the speaker 228 and/or the microphone 230.

In one implementation, a pressing of the button for a first duration may disengage a lock of the touch screen 246; and

a pressing of the button for a second duration that is longer than the first duration may turn power to the mobile device 100 on or off. The user may be able to customize a functionality of one or more of the buttons. The touch screen 246 can, for example, also be used to implement virtual or soft buttons and/or a keyboard.

In some implementations, the mobile device 100 can present recorded audio and/or video files, such as MP3, AAC, and MPEG files. In some implementations, the mobile device 100 can include the functionality of an MP3 player, such as an iPod™. The mobile device 100 may, therefore, include a 30-pin connector that is compatible with the iPod™. Other input/output and control devices can also be used.

The memory interface 202 can be coupled to memory 250. The memory 250 can include high-speed random access memory and/or non-volatile memory, such as one or more magnetic disk storage devices, one or more optical storage devices, and/or flash memory (e.g., NAND, NOR). The memory 250 can store an operating system 252, such as Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks. The operating system 252 may include instructions for handling basic system services and for performing hardware dependent tasks. In some implementations, the operating system 252 can be a kernel (e.g., UNIX kernel).

The memory 250 may also store communication instructions 254 to facilitate communicating with one or more additional devices, one or more computers and/or one or more servers. The memory 250 may include graphical user interface instructions 256 to facilitate graphic user interface processing; sensor processing instructions 258 to facilitate sensor-related processing and functions; phone instructions 260 to facilitate phone-related processes and functions; electronic messaging instructions 262 to facilitate electronic-messaging related processes and functions; web browsing instructions 264 to facilitate web browsing-related processes and functions; media processing instructions 266 to facilitate media processing-related processes and functions; GPS/Navigation instructions 268 to facilitate GPS and navigation-related processes and instructions; camera instructions 270 to facilitate camera-related processes and functions; and/or other software instructions 272 to facilitate other processes and functions, e.g., security processes and functions. The memory 250 may also store other software instructions (not shown), such as web video instructions to facilitate web video-related processes and functions; and/or web shopping instructions to facilitate web shopping-related processes and functions. In some implementations, the media processing instructions 266 are divided into audio processing instructions and video processing instructions to facilitate audio processing-related processes and functions and video processing-related processes and functions, respectively. An activation record and International Mobile Equipment Identity (IMEI) 274 or similar hardware identifier can also be stored in memory 250.

Language data 276 can also be stored in memory 250. Language data 276 can include, for example, word dictionaries (i.e., list of possible words in a language) for one or more languages, dictionaries of characters and corresponding phonetics, one or more corpora of characters and character compounds, and so on.

Each of the above identified instructions and applications can correspond to a set of instructions for performing one or more functions described above. These instructions need not be implemented as separate software programs, procedures, or modules. The memory 250 can include additional instruc-



tions or fewer instructions. Furthermore, various functions of the mobile device **100** may be implemented in hardware and/or in software, including in one or more signal processing and/or application specific integrated circuits.

#### Language Input Interface

FIGS. 3A-3F illustrate an example user interface for entering multi-lingual text on mobile device **100**. Mobile device **100** can display a text input area **302** and a virtual keyboard **304** on the touch-sensitive display **102**. The text input area **302** can be any area where input text can be displayed, e.g., a note-taking application, an email application, and so on. In some implementations, the text input area **302** can be one or more text fields located in a document (e.g., a web page rendered in a web browser application). The virtual keyboard **304** includes one or more virtual keys **303** that each correspond to a letter in an alphabet (e.g., Latin alphabet). The virtual keyboard **304** can include a keyboard toggle key **308** for toggling between letter keys and keys for numbers, punctuation, etc. (i.e., either letter keys or numbers/punctuation keys can be displayed in the virtual keyboard **304**). A user can enter text by touching the touch-sensitive display **102** on the areas of the desired keys of the virtual keyboard **304**; the user selects or hits the desired keys of the virtual keyboard **304**. Letters, numbers, etc. corresponding to the touched keys are displayed in the text input area **302** as unconverted current input **310-A**. The user can hit the backspace key **306** to delete the last input character.

In some implementations, the mobile device **100** includes capability to input text in a non-English language using Latin alphabet virtual keyboard. For example, the mobile device **100** can include capability for inputting Chinese and/or Japanese text, including Chinese or Japanese characters and symbols, using a Latin alphabet virtual keyboard (e.g., virtual keyboard with letters arranged in a QWERTY layout). For example, the device **100** can include a Chinese or Japanese text entry mode that utilizes a Latin alphabet keyboard. A user can use the virtual keyboard to enter a phonetic string of letters representing sounds or syllables in the non-English language. For example, a user can use the virtual keyboard to type in a romanization of one or more characters or symbols in Chinese or Japanese.

For convenience, the implementations in this specification will be described in reference to entry of Japanese language text. It should be appreciated, however, that the described implementations can be applied to other non-English languages (e.g., Chinese). More generally, the described implementations can be applied to any text input interface that involves identification, presentation, and selection of candidates for inputs, regardless of language (e.g., Latin alphabet romanization to non-Latin-alphabet text, spelling and grammar correction, thesaurus features, etc.).

When a user inputs in a first letter of a phonetic string, the letter is displayed in the text input area **302** as an unconverted current input **310-A**, as shown in FIG. 3A. In some implementations, the input **310-A** is displayed with underlining or some other formatting (e.g., bold text, italics, highlighting). The underlining/formatting indicates that the input is a provisional input subject to conversion pending additional input from the user, whether that additional input is additional letters or a selection of a candidate by the user. For example, in FIG. 3A, the user hits the “s” key, and the letter “s” is displayed in the text input area **302** as current input **310-A** with underlining.

The virtual keyboard **304** can include a “confirm” key **314** that, when hit by the user, accepts the displayed input **310-A**

as is. The accepted input is displayed without the underlining. For example, in FIG. 3A, the user can hit the “confirm” key **314** to accept the input string “s” as is; “s” is displayed without underlining. In some implementations, hitting of the “confirm” key **214** also adds a space after the accepted input. In some other implementations, the addition of the space after the accepted input depends on whether the accepted input is in a language where spaces separate words and/or whether the accepted input is the end of a sentence, to name a few example criteria. In some implementations, key **314** is a “space” key that, when pressed, accepts the current input as is, effectively serving as a “confirm” key.

The virtual keyboard **304** can also include a “show candidates” key **312**. By hitting the “show candidates” key **312**, the user can bring up a tray of candidate characters, symbols, and combinations thereof (e.g., kanji, kana combinations) with which to replace the input **310-A**. The tray of candidates is further described below.

Continuing from the example input **310-A** shown in FIG. 3A, the user next hits the letter “e” on the keyboard, resulting in the string “se.” The string “se” can be converted by the device **100** to the hiragana symbol “せ”, of which the string “se” is the romanization, and the hiragana symbol “せ”, is displayed as converted current input **310-B** with underlining, as shown in FIG. 3B. The user can hit the “confirm” key **314** to accept the hiragana symbol “せ”, as is; “せ”, is then displayed without underlining. Alternatively, the user can hit the “show candidates” key **312** to bring up the tray of candidates related to the string “se” (e.g., characters whose phonetic readings begin with “se”).

Continuing from the example input **310-B** as shown in FIG. 3B, the user next hits the “n” key, resulting in the string “sen.” The terminal “n” letter is converted to the hiragana symbol “ん”, of which the terminal “n” is the romanization, and appended to the already-converted hiragana symbol “せ”. The hiragana symbol “せん” is displayed as converted current input **310-B** with underlining, as shown in FIG. 3C.

In some implementations, the device **102** can display one or more suggested candidates **318** inline for the input **310-B**. The suggested candidates can include single characters, phonetic symbols (e.g., Japanese kana), and combinations of multiple characters and/or phonetic symbols. For example, in FIG. 3C, the kanji character “線” is displayed as a suggested candidate for “せん せん” (“sen”) is the onyomi reading for the kanji character “線”. In some implementations, the user can hit a suggested candidate (i.e., touch the touch-sensitive display **102** over the area of the desired suggested candidate) to select a suggested candidate, continue typing letter keys on the virtual keyboard **304** to add to the input **310-B**, or hit the “show candidates” key **312** to bring up the candidates tray, among other actions. If the user selects a suggested candidate, the selected suggested candidate is displayed as accepted input **336**, as shown in FIG. 3F. If the user continues typing on the letter keys on the virtual keyboard **304**, the current input **310-B** is extended and possible candidates for the current input **310-B** are narrowed down.

In some implementations, the one or more suggested candidates **318** that are presented to the user are determined by the device **100** to be the best match for the input **310-B** based on one or more criteria (e.g., frequency in the language, exact match, etc.).

In some implementations, more candidates can be displayed by the device **100** when the user hits an arrow graphical object **319** or the like on the touch-sensitive display **102**. For example, when the user hits the arrow **319**,



a candidates tray 322 can be displayed. Alternatively, the inline suggested candidates list 318 can expand to show more candidates. The arrow 319 gives the user a hint that there are additional candidates available.

In some implementations, the user can hit the confirm key 314 once to select the first candidate of the suggested candidates 318, hit the confirm key 314 twice in quick succession to select the second candidate of the suggested candidates 318, and so on.

If the user hits the “show candidates” key 312 or the arrow 319, a candidates tray 322 can be displayed, as shown in FIG. 3D. In some implementations, the candidates tray 322 is displayed in place of the virtual keyboard 304. In some other implementations, the candidates tray 322 is displayed over all or part of the text input area 302. In some implementations, the candidates tray 322 slides over the virtual keyboard 304 or the text input area 302, and the sliding is displayed as an animated effect. When the candidates tray 322 is removed from view, the candidates tray 322 can slide off the touch-sensitive display 102.

The candidates tray 322 can include one or more candidate keys 330, each of the candidate keys 330 corresponding to a candidate for conversion of the input 310-B. A candidate (whether for the candidate keys 330 or suggested candidates 318) can be a character, a phonetic or syllabic symbol (e.g., a kana symbol), romanization, multi-character combinations forming words or phrases, multi-symbol combinations forming words or phrases, a combination of characters and symbols forming words or phrases, and so on. The candidates can include characters whose phonetic reading is or begins with the input 310-B as a reading, words that begin with the input 310-B, and so on. For example, in FIG. 3D, the candidates tray 322 includes some candidate keys 330 that correspond to kanji characters that has “せん” as a reading. In some implementations, the candidates in the candidates tray are ordered based on various criteria as to which candidate is the best candidate.

In some implementations, the candidates for the suggested candidates 318 and the candidates tray 322 are identified and ordered using predictive text and/or error correction techniques, examples of which include fuzzy matching, techniques for determining cursor position based on a finger contact, and so on. An example of a predictive text technique is disclosed in Masui, “An Efficient Text Input Method for Pen-based Computers,” in Proceedings of the ACM Conference on Human Factors in Computing Systems (CHI '98), Addison-Wesley, April 1998, pp. 328-335, the disclosure of which is incorporated by reference herein in its entirety. An example of a techniques for determining cursor position based on a finger contact is disclosed in U.S. patent application Ser. No. 11/850,015, titled “Methods for Determining a Cursor Position from a Finger Contact with a Touch Screen Display,” filed Sep. 4, 2007, the disclosure of which is incorporated by reference herein in its entirety.

In some implementations, if the candidates tray 322 is displayed over the virtual keyboard 304, the candidates tray 322 can also include a keyboard switch key 328 for switching back to the virtual keyboard 304. The candidates tray 322 can also include back candidates key 326 and/or next candidates key 324 for moving back and forth between sets of candidate keys 330 within the candidates tray 322. In some implementations, the candidates tray 322 also includes the confirm key 314.

The user can hit a candidate key 330 to replace the input 310-B with the candidate corresponding to the hit candidate key 330. For example, from FIG. 3D, if the user hits the key that corresponds to the candidate character “千” (key 332),

the input 310-B is replaced with the character “せん” The character “せん” is displayed as accepted input 336, as shown in FIG. 3E. In FIG. 3E, the candidates tray 322 reverts back to virtual keyboard 304. The virtual keyboard 304 can include a “space” key 334 and a “return” key 332 in place of “confirm” key 314 and show candidate key 312, respectively. From FIG. 3F, the user can enter a new phonetic string input.

In some implementations, the virtual keyboard 304 can include a key for switching between multiple input keyboards for various languages.

In some implementations, the candidates tray 322 includes a cancel key 331 for reverting back to the virtual keyboard 304 from the candidates tray 322 without selecting a candidate.

In some implementations, a candidate in the suggested candidates 318 or candidates tray 322 is highlighted as the “currently selected” candidate. When the suggested candidates 318 or candidates tray 322 is first displayed after an input of a phonetic string, the initial highlighted candidate can be the phonetic string itself in the suggested candidates 318 or candidates tray 322 or the “best” candidate. Key 312 can be a “next candidate” key, where a press of the key moves the highlighting to the next candidate. In some implementations, there can be a “previous candidate” key to move the highlighting backward to a previous candidate. The confirm key 314 can be used to accept the highlighted candidate.

In some other implementations, when the user inputs a phonetic sting, no candidate is automatically selected or highlighted by default; the user can hit the confirm key 314 to accept the phonetic string as is. The user can hit the next candidate key (and optionally a previous candidate key) to move through the candidates and highlight one of them. As different candidates are highlighted, the current input 310-B changes to show the currently highlighted candidate, while still displayed with underlining or other formatting to indicate that the current input 310-B is still provisional. Hitting a return key (e.g., return key 332) confirms the currently selected candidate or the phonetic string (i.e., whatever phonetic string or candidate is shown in the current input 310-B). Adding more phonetic symbols by typing on the virtual keyboard 304 also automatically accepts the currently selected candidate or the phonetic string (i.e., whatever phonetic string or candidate is shown in the current input 310-B).

FIG. 4 illustrates an example text input process 400. For convenience, the process 400 will be described in reference to a device (e.g., device 100) that performs the process 400.

A virtual keyboard is displayed in a first region of a touch-sensitive display of a device (402). For example, the device displays virtual keyboard 304 on a portion of the touch-sensitive display 102.

An input is received entering a phonetic string on the virtual keyboard (404). A user can enter one or more letters using the virtual keyboard. The entered letters can constitute a phonetic string. The phonetic string can be a romanization of characters, words, and the like in a language that does not use the Latin alphabet, for example.

The input phonetic string is displayed in a second region of the display (406). The device 100 can display the phonetic string in a text input area on the touch-sensitive Display 102. In some implementations, the device 100 converts the phonetic string to, for example, symbols corresponding to the phonetic string (e.g., Japanese kana, Chinese zhuyin, etc.).

One or more candidates matching the phonetic string are identified (408). For example, the device 100 can look up the



## 11

phonetic string in a dictionary, character database, or the like, and finds matching characters for the phonetic string. In some implementations, the device **100** can segment the phonetic string based on syllables or another criteria and find candidates for each of the segments.

At least a subset of the identified candidates is displayed in the first region of the touch sensitive display (**410**). For example, the candidates can be displayed in a candidates tray **322** that is displayed in place of the virtual keyboard **304**. In some implementations, if there are more candidates than can fit in the tray **322**, the user can navigate to the overflow candidates by hitting the back candidates **326** or next candidates key **324**.

Input is received selecting one of the candidates (**412**). For example, a user can hit one of the candidate keys **330** in a candidates tray **322** to select the corresponding candidate.

The displayed phonetic string is replaced with the selected candidate (**414**). In some implementations, the selected candidate is displayed on the touch-sensitive display in place of the input phonetic string.

In some implementations, the virtual keyboard **304** and the candidates tray **322** can be dynamically resized based on the orientation of the touch-sensitive display **102**. For example, FIGS. 3A-3F show the virtual keyboard **304** or the candidates tray **322** in portrait orientation. If the device **100**, and thus the touch-sensitive display **102**, is rotated to landscape orientation, the device **100** can detect the rotation and resize the keyboard **304** and the candidates tray **322** to fit the landscape width of the touch-sensitive display **102**.

In some implementations, the suggested candidates **318** are displayed in the same orientation as the text input, whose orientation can vary by language. For example, if the text is displayed from left-to-right, the suggested candidates **318** are displayed from left to right. If the text is displayed from right to left, the suggested candidates **318** are displayed from right to left. If the text displayed from top to bottom, the suggested candidates **318** are displayed from top to bottom.

In some implementations, the phonetic string can be input by voice rather than typing on the virtual keyboard **304**. For example, the device **100** can include a voice recognition module that receives and processes a user's voice input and generates a phonetic string based on the voice input. The device **100** can identify candidates for the phonetic string generated by the voice recognition module for selection by the user.

The disclosed and other embodiments and the functional operations described in this specification can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. The disclosed and other embodiments can be implemented as one or more computer program products, i.e., one or more modules of computer program instructions encoded on a computer-readable medium for execution by, or to control the operation of, data processing apparatus. The computer-readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter effecting a machine-readable propagated signal, or a combination of one or more of them. The term "data processing apparatus" encompasses all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The apparatus can include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a

## 12

database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal, that is generated to encode information for transmission to suitable receiver apparatus.

A computer program (also known as a program, software, software application, script, or code) can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program does not necessarily correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub-programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

The processes and logic flows described in this specification can be performed by one or more programmable processors executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application-specific integrated circuit).

Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read-only memory or a random access memory or both. The essential elements of a computer are a processor for performing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto-optical disks, or optical disks. However, a computer need not have such devices. Computer-readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

To provide for interaction with a user, the disclosed embodiments can be implemented on a computer having a display device, e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor, for displaying information to the user and a keyboard and a pointing device, e.g., a mouse or a trackball, by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input.



## 13

The disclosed embodiments can be implemented in a computing system that includes a back-end component, e.g., as a data server, or that includes a middleware component, e.g., an application server, or that includes a front-end component, e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of what is disclosed here, or any combination of one or more such back-end, middleware, or front-end components. The components of the system can be interconnected by any form or medium of digital data communication, e.g., a communication network. Examples of communication networks include a local area network ("LAN") and a wide area network ("WAN"), e.g., the Internet.

While this specification contains many specifics, these should not be construed as limitations on the scope of what being claims or of what may be claimed, but rather as descriptions of features specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

Particular embodiments of the subject matter described in this specification have been described. Other embodiments are within the scope of the following claims. For example, the actions recited in the claims can be performed in a different order and still achieve desirable results. As one example, the processes depicted in the accompanying figures do not necessarily require the particular order shown, or sequential order, to achieve desirable results. In certain implementations, multitasking and parallel processing may be advantageous.

What is claimed is:

1. A method comprising:

presenting a virtual keyboard corresponding to a first alphabet in a first region of a touch-sensitive display of a device;

receiving an input on the virtual keyboard representing a phonetic string;

presenting the phonetic string in a second region of the touch-sensitive display;

identifying one or more candidate representations based on the phonetic string, wherein the candidate representations correspond to a second alphabet different from the first alphabet;

## 14

*identifying one or more additional candidate representations based on the phonetic string in a third alphabet different from the first and second alphabets;*

presenting a candidate tray including at least a subset of the candidate representations *and a subset of the additional candidate representations;*

receiving an input of a selected candidate representation of the candidate representations *and the additional candidate representations;* and

replacing the entered phonetic string with the selected candidate representation.

2. The method of claim 1, wherein:

the phonetic string comprises Chinese romanization; and the candidates comprise Chinese characters.

3. The method of claim 1, wherein:

the phonetic string comprises Japanese romanization; and the candidates comprise one or more of the group consisting of Japanese kanji characters and Japanese kana symbols.

4. The method of claim 1, wherein the virtual keyboard comprises keys corresponding to letters of the Latin alphabet.

5. The method of claim 1, wherein the candidates comprise multi-character words.

6. The method of claim 1, wherein identifying one or more candidates based on the phonetic string comprises identifying one or more candidates using text prediction from the phonetic string.

7. The method of claim 6, wherein presenting at least a subset of the candidates comprises presenting the subset of the candidates in an order determined based on the text prediction.

8. A portable device comprising:

a touch-sensitive display;

memory;

one or more processors; and

instructions stored in the memory and configured for execution by the one or more processors, the instructions comprising instructions to:

present a virtual keyboard corresponding to a first alphabet in a first region of the touch-sensitive display of a device;

receive an input on the virtual keyboard representing a phonetic string;

present the phonetic string in a second region of the touch-sensitive display;

identify one or more candidate representations based on the phonetic string, wherein the candidate representations correspond to a second alphabet different from the first alphabet;

*identify one or more additional candidate representations based on the phonetic string in a third alphabet different from the first and second alphabets;*

present a candidate tray including at least a subset of the candidate representations *and a subset of the additional candidate representations;*

receive an input of a selected candidate representation of the candidate representations *and the additional candidate representations;* and

replace the entered phonetic string with the selected candidate representation.

9. The device of claim 8, wherein:

the phonetic string comprises Chinese romanization; and the candidates comprise Chinese characters.



## 15

10. The device of claim 8, wherein:  
the phonetic string comprises Japanese romanization; and  
the candidates comprise one or more of the group con-  
sisting of Japanese kanji characters and Japanese kana  
symbols.

11. The device of claim 8, wherein the virtual keyboard  
comprises keys corresponding to letters of the Latin alpha-  
bet.

12. The device of claim 8, wherein the candidates com-  
prise multi-character words.

13. The device of claim 8, further comprising instructions  
to identify one or more candidates using text prediction from  
the phonetic string.

14. The device of claim 13, further comprising instruc-  
tions to present the subset of the candidates in an order  
determined based on the text prediction.

15. A computer program product, encoded on a tangible  
program carrier, operable to cause a portable device to  
perform operations comprising:

presenting a virtual keyboard corresponding to a first  
alphabet in a first region of a touch-sensitive display of  
a device;

receiving an input on the virtual keyboard representing a  
phonetic string;

presenting the phonetic string in a second region of the  
touch-sensitive display;

identifying one or more candidate representations based  
on the phonetic strings wherein the candidate repre-  
sentations correspond to a second alphabet different from the first alphabet;

*identifying one or more additional candidate representa-  
tions based on the phonetic string in a third alphabet  
different from the first and second alphabets;*

presenting a candidate tray including at least a subset of  
the candidate representations *and a subset of the addi-  
tional candidate representations;*

receiving an input of a selected candidate representation  
of the candidate representations *and the additional  
candidate representations;* and

replacing the entered phonetic string with the selected  
candidate representation.

16. The program product of claim 15, wherein:  
the phonetic string comprises Chinese romanization; and  
the candidates comprise Chinese characters.

17. The program product of claim 15, wherein:  
the phonetic string comprises Japanese romanization; and  
the candidates comprise one or more of the group con-  
sisting of Japanese kanji characters and Japanese kana  
symbols.

18. The program product of claim 15, wherein the virtual  
keyboard comprises keys corresponding to letters of the  
Latin alphabet.

19. The program product of claim 15, wherein the can-  
didates comprise multi-character words.

20. The program product of claim 15, wherein identifying  
one or more candidates based on the phonetic string com-  
prises identifying one or more candidates using text predic-  
tion from the phonetic string.

21. The program product of claim 20, wherein presenting  
at least a subset of the candidates comprises presenting the  
subset of the candidates in an order determined based on the  
text prediction.

22. A method comprising:

presenting a virtual keyboard corresponding to a first  
alphabet in a first region of a touch-sensitive display of  
a device;

## 16

receiving an input on the virtual keyboard representing a  
phonetic string;

presenting the phonetic string in a second region of the  
touch-sensitive display;

identifying one or more candidate representations based  
on the phonetic string, wherein the candidate represen-  
tations correspond to a second alphabet different from  
the first alphabet;

*identifying one or more additional candidate representa-  
tions based on the phonetic string in a third alphabet  
different from the first and second alphabets;*

presenting at least a subset of the candidate representa-  
tions *and a subset of the additional candidate repre-  
sentations* inline with the phonetic string in the second  
region, where the candidate representations are dis-  
played according to an orientation of text in the second  
region;

receiving an input selecting one of the candidate repre-  
sentations *and the additional candidate representa-  
tions;* and

replacing the entered phonetic string with the selected  
candidate representation.

[23. The method of claim 1, further comprising identify-  
ing one or more additional candidate representations based  
on the phonetic string in a third alphabet different from the  
first and second alphabets, wherein the candidate tray  
includes at least a subset of the additional candidate repre-  
sentations.]

24. The method of claim 1, wherein the candidate tray  
further includes the phonetic string.

25. The method of claim 1, wherein the second alphabet  
comprises logographic characters.

26. The method of claim 1, wherein the candidate tray is  
presented in place of the virtual keyboard.

27. The method of claim 8, wherein the candidate tray is  
presented in place of the virtual keyboard.

28. The method of claim 15, wherein the candidate tray is  
presented in place of the virtual keyboard.

29. *The method of claim 1, wherein presenting the can-  
didate tray comprises presenting the candidate tray in the  
second region of the touch-sensitive display.*

30. *The method of claim 1, wherein replacing the entered  
phonetic string comprises replacing the entered phonetic  
string in the second region of the touch-sensitive display.*

31. *The method of claim 1, wherein presenting the can-  
didate tray comprises presenting the candidate tray adjacent  
to the phonetic string.*

32. *The method of claim 1, wherein presenting the can-  
didate tray comprises presenting the candidate tray adjacent  
to the phonetic string in the second region.*

33. *The method of claim 1, further comprising:  
receiving an input on the virtual keyboard representing a  
second phonetic string;*

*presenting the second phonetic string in the second region  
of the touch-sensitive display; and*

*receiving an input confirming the second phonetic string.*

34. *The method of claim 1, further comprising:  
presenting an option to expand the candidate tray to  
include a larger subset of the candidate representa-  
tions.*

35. *The method of claim 1, further comprising:  
providing a confirm key.*

36. *The method of claim 35, wherein the received input of  
a selected candidate representation comprises a number of  
hits to the confirm key in succession.*



37. The method of claim 36, wherein each of the candidate representations presented in the candidate tray corresponds to a different number of hits of the confirm key.

38. The method of claim 1, further comprising:  
providing an option of replacing the virtual keyboard in the first region with at least a subset of the candidate representations.

39. The method of claim 1, further comprising:  
providing an option of presenting a different subset of the candidate representations in the candidate tray.

40. The method of claim 1, wherein presenting the phonetic string in the second region comprises:

displaying the phonetic string using a phonetic representation different from the first alphabet.

41. The method of claim 1, further comprising:  
displaying a visual indicator that identifies the presented phonetic string as a provisional input.

42. The method of claim 1, wherein presenting the candidate tray comprises:

presenting the subset of candidate representations according to a text orientation associated with the second alphabet.

43. The method of claim 42, wherein the text orientation comprises a left to right orientation.

44. The method of claim 42, wherein the text orientation comprises a right to left orientation.

45. The method of claim 42, wherein the text orientation comprises a top to bottom orientation.

46. The method of claim 1, further comprising:  
presenting a next candidate key configured to allow a user to select a next candidate of the one or more candidate representations.

47. The method of claim 1, further comprising:  
presenting a previous candidate key configured to allow a user to select a previous candidate of the one or more candidate representations.

48. The device of claim 8, wherein the instructions to present the candidate tray include instructions to present the candidate tray in the second region of the touch-sensitive display.

49. The device of claim 8, wherein the instructions to replace the entered phonetic string include instructions to replace the entered phonetic string in the second region of the touch-sensitive display.

50. The device of claim 8, wherein the instructions to present the candidate tray include instructions to present the candidate tray adjacent to the phonetic string.

51. The device of claim 8, wherein the instructions to present the candidate tray comprise instructions to present the candidate tray adjacent to the phonetic string in the second region.

52. The device of claim 8, further comprising instructions to:

receive an input on the virtual keyboard representing a second phonetic string;

present the second phonetic string in the second region of the touch-sensitive display; and

receive an input confirming the second phonetic string.

53. The device of claim 8, further comprising instructions to:

present an option to expand the candidate tray to include a larger subset of the candidate representations.

54. The device of claim 8, further comprising instructions to:

provide a confirm key.

55. The device of claim 54, wherein the instructions to receive an input of a selected candidate representation include instructions to recognize a number of hits to the confirm key in succession.

56. The device of claim 55, further comprising instructions to:

associate each of the candidate representations presented in the candidate tray with a different number of hits of the confirm key.

57. The device of claim 8, further comprising instructions to:

provide an option of replacing the virtual keyboard in the first region with at least a subset of the candidate representations.

58. The device of claim 8, further comprising instructions to:

provide an option of presenting a different subset of the candidate representations in the candidate tray.

59. The device of claim 8 wherein the instructions to present the phonetic string in the second region comprise instructions to display the phonetic string using a phonetic representation different from the first alphabet.

60. The device of claim 8, further comprising instructions to:

display a visual indicator that identifies the presented phonetic string as a provisional input.

61. The device of claim 8, wherein the instructions to present the candidate tray comprise instructions to present the subset of candidate representations according to a text orientation associated with the second alphabet.

62. The device of claim 61, wherein the text orientation comprises a left to right orientation.

63. The device of claim 61, wherein the text orientation comprises a right to left orientation.

64. The device of claim 61, wherein the F comprises a top to bottom orientation.

65. The device of claim 8, further comprising instructions to present a next candidate key configured to allow a user to select a next candidate of the one or more candidate representations.

66. The device of claim 8, further comprising instructions to present a previous candidate key configured to allow a user to select a previous candidate of the one or more candidate representations.

67. The program product of claim 15, wherein presenting the candidate tray comprises presenting the candidate tray in the second region of the touch-sensitive display.

68. The program product of claim 15, wherein replacing the entered phonetic string comprises replacing the entered phonetic string in the second region of the touch-sensitive display.

69. The program product of claim 15, wherein presenting the candidate tray comprises presenting the candidate tray adjacent to the phonetic string.

70. The program product of claim 15, wherein presenting the candidate tray comprises presenting the candidate tray adjacent to the phonetic string in the second region.

71. The program product of claim 15, wherein the operations further comprise:

receiving an input on the virtual keyboard representing a second phonetic string;

presenting the second phonetic string in the second region of the touch-sensitive display; and  
receiving an input confirming the second phonetic string.



72. The program product of claim 15, wherein the operations further comprise:

presenting an option to expand the candidate tray to include a larger subset of the candidate representations.

73. The program product of claim 15, wherein the operations further comprise:

providing a confirm key.

74. The program product of claim 73, wherein the received input of a selected candidate representation comprises a number of hits to the confirm key in succession.

75. The program product of claim 74, wherein each of the candidate representations presented in the candidate tray corresponds to a different number of hits of the confirm key.

76. The program product of claim 15, wherein the operations further comprise:

providing an option of replacing the virtual keyboard in the first region with at least a subset of the candidate representations.

77. The program product of claim 15, wherein the operations further comprise:

providing an option of presenting a different subset of the candidate representations in the candidate tray.

78. The program product of claim 15, wherein presenting the phonetic string in the second region comprises:

displaying the phonetic string using a phonetic representation different from the first alphabet.

79. The program product of claim 15, further comprising: displaying a visual indicator that identifies the presented phonetic string as a provisional input.

80. The program product of claim 15, wherein presenting the candidate tray comprises presenting the subset of candidate representations according to a text orientation associated with the second alphabet.

81. The program product of claim 80, wherein the text orientation comprises a left to right orientation.

82. The program product of claim 80, wherein the text orientation comprises a right to left orientation.

83. The program product of claim 80, wherein the text orientation comprises a top to bottom orientation.

84. The program product of claim 15, wherein the operations further comprise:

presenting a next candidate key configured to allow a user to select a next candidate of the one or more candidate representations.

85. The program product of claim 15, wherein the operations further comprise:

presenting a previous candidate key configured to allow a user to select a previous candidate of the one or more candidate representations.

86. The method of claim 22, wherein presenting the subset of candidate representations comprises presenting a candidate tray in the second region of the touch-sensitive display.

87. The method of claim 22, wherein replacing the entered phonetic string comprises replacing the entered phonetic string in the second region of the touch-sensitive display.

88. The method of claim 22, wherein presenting the subset of the candidate representations comprises presenting the candidate representations adjacent to the phonetic string.

89. The method of claim 22, wherein presenting the subset of candidate representations comprises presenting the candidate representations adjacent to the phonetic string in the second region.

90. The method of claim 22, further comprising: receiving an input on the virtual keyboard representing second phonetic string;

presenting the second phonetic string in the second region of the touch-sensitive display; and

receiving an input confirming the second phonetic string.

91. The method of claim 22, further comprising:

presenting an option to expand the subset of the candidate representations.

92. The method of claim 22, further comprising:

providing a confirm key.

93. The method of claim 92, wherein the received input of a selected candidate representation comprises a number of hits to the confirm key in succession.

94. The method of claim 93, wherein each of the candidate representations corresponds to a different number of hits of the confirm key.

95. The method of claim 22, further comprising:

providing an option of replacing the virtual keyboard in the first region with at least a subset of the candidate representations.

96. The method of claim 22, further comprising:

providing an option of presenting a different subset of the candidate representations.

97. The method of claim 22, wherein presenting the phonetic string in the second region comprises:

displaying the phonetic string using a phonetic representation different from the first alphabet.

98. The method of claim 22, further comprising:

displaying a visual indicator that identifies the presented phonetic string as a provisional input.

99. The method of claim 22, wherein the orientation of text comprises a left to right orientation.

100. The method of claim 22, wherein the orientation of text comprises a right to left orientation.

101. The method of claim 22, wherein the orientation of text comprises a top to bottom orientation.

102. The method of claim 22, further comprising:

presenting a next candidate key configured to allow a user to select a next candidate of the one or more candidate representations.

103. The method of claim 22, further comprising:

presenting a previous candidate key configured to allow a user to select a previous candidate of the one or more candidate representations.

104. A method comprising:

presenting a virtual keyboard corresponding to a first alphabet in a first region of a touch-sensitive display of a device;

receiving an input on the virtual keyboard representing a phonetic string;

presenting the phonetic string in a second region of the touch-sensitive display;

identifying one or more candidate representations based on the phonetic string, wherein the candidate representations correspond to a second alphabet different from the first alphabet;

identifying one or more additional candidate representations based on the phonetic string in a third alphabet different from the first and second alphabets;

presenting a candidate tray including at least a subset of the candidate representations and a subset of the additional candidate representations;

receiving an input of a selected candidate representation of the candidate representations and the additional candidate representations; and

removing the presented phonetic string and presenting the selected candidate representation.

105. A non-transitory computer-readable storage medium storing one or more programs, the one or more programs



21

comprising instructions, which when executed by an electronic device with a touch-sensitive display, cause the device to:

present a virtual keyboard corresponding to a first alphabet in a first region of the touch-sensitive display of the device; 5  
 receive an input on the virtual keyboard representing a phonetic string;  
 present the phonetic string in a second region of the touch-sensitive display; 10  
 identify one or more candidate representations based on the phonetic string, wherein the candidate representations correspond to a second alphabet different from the first alphabet;  
 identify one or more additional candidate representations based on the phonetic string in a third alphabet different from the first and second alphabets; 15  
 present a candidate tray including at least a subset of the candidate representations and a subset of the additional candidate representations; 20  
 receive an input of a selected candidate representation of the candidate representations and the additional candidate representations; and  
 remove the presented phonetic string and present the selected candidate representation. 25

106. A method comprising:

presenting a virtual keyboard corresponding to a first alphabet in a first region of a touch-sensitive display of a device;  
 receiving input representing a phonetic string corresponding to the first alphabet; 30  
 presenting the phonetic string in a second region of the touch-sensitive display;  
 identifying one or more candidate representations based on the phonetic string, wherein the candidate representations correspond to a second alphabet different from the first alphabet; 35  
 identifying one or more additional candidate representations based on the phonetic string in a third alphabet different from the first and second alphabets; 40  
 presenting a candidate tray including at least a subset of the candidate representations and a subset of the additional candidate representations;  
 receiving an input of a selected candidate representation of the candidate representations and the additional candidate representations; and 45  
 removing the presented phonetic string and presenting the selected candidate representation.

22

107. A method comprising:

presenting a virtual keyboard in a first region of a touch-sensitive display of a device;  
 receiving an input on the virtual keyboard representing a phonetic string;  
 presenting the phonetic string using a first alphabet in a second region of the touch-sensitive display;  
 identifying one or more candidate representations based on the phonetic string, wherein the one or more candidate representations correspond to a second alphabet different from the first alphabet;  
 identifying one or more additional candidate representations based on the phonetic string in a third alphabet different from the first and second alphabets;  
 presenting a candidate tray including at least a subset of the candidate representations and a subset of the additional candidate representations;  
 receiving an input of a selected candidate representation of the candidate representations and the additional candidate representations; and  
 removing the presented phonetic string and presenting the selected candidate representation.

108. A method comprising:

presenting one or more virtual keys corresponding to a first alphabet in a first region of a touch-sensitive display of a device;  
 receiving an input on the one or more virtual keys, wherein the input represents a phonetic string;  
 presenting the phonetic string in a second region of the touch-sensitive display;  
 identifying one or more candidate representations based on the phonetic string, wherein the one or more candidate representations correspond to a second alphabet different from the first alphabet;  
 identifying one or more additional candidate representations based on the phonetic string in a third alphabet different from the first and second alphabets;  
 presenting a candidate tray including at least a subset of the candidate representations and a subset of the additional candidate representations;  
 receiving an input of a selected candidate representation of the candidate representations and the additional candidate representations; and  
 removing the presented phonetic string and presenting the selected candidate representation.

\* \* \* \* \*



UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : RE46,139 E  
APPLICATION NO. : 14/516533  
DATED : September 6, 2016  
INVENTOR(S) : Yasuo Kida et al.

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

At Column 16, Claim number 27, Line number 37, DELETE “method” and ADD -- device --, therefor.

At Column 16, Claim number 28, Line number 39, DELETE “method” and ADD -- program product --, therefor.

Signed and Sealed this  
Thirtieth Day of May, 2017



Michelle K. Lee  
*Director of the United States Patent and Trademark Office*