

US00RE46221E

(19) **United States**
(12) **Reissued Patent**
Kister

(10) **Patent Number:** **US RE46,221 E**
(45) **Date of Reissued Patent:** ***Nov. 29, 2016**

(54) **PROBE SKATES FOR ELECTRICAL
TESTING OF CONVEX PAD TOPOLOGIES**

USPC 324/754, 758.01, 758.04, 754.03,
324/756.04, 756.05
See application file for complete search history.

(75) Inventor: **January Kister**, Portola Valley, CA
(US)

(56) **References Cited**

(73) Assignee: **MICROPROBE, INC.**, Carlsbad, CA
(US)

U.S. PATENT DOCUMENTS

(*) Notice: This patent is subject to a terminal disclaimer.

2,754,203 A 7/1956 Vordahl
4,314,855 A * 2/1982 Chang et al. 134/3
4,871,964 A 10/1989 Boll et al.

(Continued)

(21) Appl. No.: **13/545,571**

OTHER PUBLICATIONS

(22) Filed: **Jul. 10, 2012**

Bennett, Scott et al. "Precision Point Probe Card Analyzers: Probe Force," pp. 1-4, 2003. Applied Precision, www.appliedprecision.com.

Related U.S. Patent Documents

(Continued)

Reissue of:

(64) Patent No.: **7,436,192**
Issued: **Oct. 14, 2008**
Appl. No.: **11/701,236**
Filed: **Jan. 31, 2007**

Primary Examiner — Anjan Deb
(74) *Attorney, Agent, or Firm* — Peacock Myers, P.C.;
Deborah A. Peacock; Philip D. Askenazy

U.S. Applications:

(60) Division of application No. 12/903,566, filed on Oct. 13, 2010, now Pat. No. Re. 43,503, which is an application for the reissue of Pat. No. 7,436,192, which is a continuation-in-part of application No. 11/480,302, filed on Jun. 29, 2006, now Pat. No. 7,759,949.

(57) **ABSTRACT**


A probe for engaging a conductive pad is provided. The probe includes a probe contact end for receiving a test current, a probe retention portion below the contact end, a block for holding the probe retention portion, a probe arm below the retention portion, a probe contact tip below the arm, and a generally planar self-cleaning skate disposed perpendicular below the contact tip. The self-cleaning skate has a square front, a round back and a flat middle section. The conductive pad is of generally convex shape having a granular non-conductive surface of debris and moves to engage the skate, whereby an overdrive motion is applied to the pad causing the skate to move across and scrub non-conductive debris from the pad displacing the debris along the skate and around the skate round back end to a position on the skate that is away from the pad.

(51) **Int. Cl.**
G01R 31/00 (2006.01)
G01R 31/20 (2006.01)
G01R 3/00 (2006.01)
G01R 1/067 (2006.01)

(52) **U.S. Cl.**
CPC **G01R 3/00** (2013.01); **G01R 1/06733**
(2013.01)

(58) **Field of Classification Search**
CPC G01R 3/00; G01R 1/06733

16 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,973,903 A 11/1990 Schemmel
5,468,993 A 11/1995 Tani
5,642,056 A 6/1997 Nakajima et al.
6,359,452 B1 3/2002 Mozzetta
6,414,502 B1 7/2002 Sayre et al.
6,496,026 B1 12/2002 Long et al.
6,538,336 B1 3/2003 Secker et al.
6,768,331 B2 7/2004 Longson et al.
6,891,385 B2 5/2005 Miller
7,015,707 B2 * 3/2006 Cherian 324/754.14
7,036,221 B2 5/2006 Higashida et al.
7,061,257 B2 6/2006 Khandros et al.
7,068,057 B2 6/2006 Tervo et al.
7,109,731 B2 9/2006 Gleason et al.
7,143,500 B2 12/2006 Byrd
7,148,709 B2 * 12/2006 Kister 324/754
7,281,305 B1 10/2007 Iyer et al.
7,436,192 B2 * 10/2008 Kister 324/756.04
7,667,471 B2 2/2010 Kurotori et al.
7,733,101 B2 6/2010 Kister
7,733,103 B2 6/2010 Park et al.
RE43,503 E * 7/2012 Kister 324/758.01
8,230,593 B2 7/2012 Kister
8,299,394 B2 10/2012 Theppakuttai et al.
8,310,253 B1 11/2012 Mardi et al.
8,415,963 B2 4/2013 Kister
RE44,407 E 8/2013 Kister
2002/0177782 A1 11/2002 Penner

2003/0218244 A1 11/2003 Lahiri et al.
2003/0218865 A1 11/2003 Macias
2006/0186905 A1 8/2006 Kohashi et al.
2006/0189867 A1 8/2006 Revie et al.
2006/0208752 A1 9/2006 Tanioka et al.
2006/0261828 A1 11/2006 Cram et al.
2008/0001613 A1 * 1/2008 Kister 324/754
2009/0079455 A1 3/2009 Gritters
2012/0242363 A1 9/2012 Breinlinger et al.
2012/0286816 A1 11/2012 Kister
2012/0313621 A1 12/2012 Kister
2012/0313660 A1 12/2012 Kister
2013/0082729 A1 4/2013 Fan et al.
2013/0093450 A1 4/2013 Kister

OTHER PUBLICATIONS

Broz, Jerry J. et al. "Controlling Contact Resistance," pp. 1-4, May 2004, EE-Evaluation Engineering, www.evaluationengineering.com.
Stalnaker, Scott et al. "SWTW2003: Controlling Contact Resistance with Probe Tip Shape & Cleaning Recipe Optimization," pp. 1-31, Jun. 1-4, 2003. Southwest Test Workshop, Long Beach, CA.
Dabrowiecki, Krzysztof R&D Group. "Advances in Conventional Cantilever Probe Card," pp. 1-28, Jun. 6-9, 1999. Southwest Test Workshop, San Diego, CA.
Tunaboylu, Bahadir et al. "SWTW2003: Vertical Probe Development for Copper Bump Test Challenges," pp. 1-26, Jun. 2, 2003. Southwest Test Workshop, Long Beach CA.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7







FIG. 9

**FIG. 10**

PROBE SKATES FOR ELECTRICAL TESTING OF CONVEX PAD TOPOLOGIES

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 7,436,192. The reissue applications are application Ser. No. 12/903,566, filed on Oct. 13, 2010 (now U.S. Pat. No. Re. 43,503) and Ser. No. 13/545,571 (the present application), filed on Jul. 10, 2012, which is a divisional of application Ser. No. 12/903,566.

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a divisional reissue application of U.S. application Ser. No. 12/903,566 (now U.S. Pat. No. Re. 43,503), filed Oct. 13, 2010, which is a reissue of U.S. Pat. No. 7,436,192 issued Oct. 14, 2008, which is a continuation-in-part application of the inventor's prior U.S. application Ser. No. 11/480,302 (U.S. Pat. No. 7,759,949) filed Jun. 29, 2006, for PROBES WITH SELF-CLEANING SKATES FOR CONTACTING CONDUCTIVE PADS[, to which claims the benefit of U.S. application Ser. No. 10/850,921 filed on May 21, 2004, now U.S. Pat. No. 7,148,709, U.S. application Ser. No. 10/888,347 filed on Jul. 9, 2004 and U.S. application Ser. No. 11/450,977 filed on Jun. 9, 2006].

FIELD OF THE INVENTION

The invention relates generally to an apparatus and method of using contacting tips of probes in scrubbing and electrical testing of a device under test. More particularly, the invention relates to an apparatus and method of using contacting tips having probe skates with geometries that provide self-cleaning and a reduction in sensitivity to overdrive motion.

BACKGROUND

Semiconductor wafer testing before dicing is a necessary and critical process step. Such testing provides early verification of circuit design and fabrication integrity. Typically, test probes are placed in contact with conductive pads of a device under test (DUT) to provide a test signal for such verification of the circuit, where the conductive pads are positioned on the surface of a wafer or DUT. These pads are known to have bump-like or convex shape, with the base of the pad incorporated into the wafer surface. A problem exists with a non-conductive layer of debris on the pad such as a non-conductive oxide layer impeding the conductive pad from receiving the test signal, where the debris is an artifact of the fabrication process. Currently, a scrubbing method is used to remove some of the non-conductive layer from the pads before applying the test signal. Many methods exist for removing the debris layer such as using the probe tip itself to scrub the pad while applying the test signal. For information about corresponding probe designs and scrub motion mechanics the reader is referred to U.S. Pat. No. 5,436,571 to Karasawa; U.S. Pat. Nos. 5,773,987 and 6,433,571 both

to Montoya; U.S. Pat. No. 5,932,323 to Throssel and U.S. Appl. 2006/0082380 to Tanioka et al. Additional information about the probe-oxide semiconductor interface is found in U.S. Pat. No. 5,767,691 to Verkuil.

The scrub motion includes engaging a probe tip with a conductive pad, and applying an overdrive motion to the pad to cause the probe to scrub the layer of debris from the pad. Numerous problems arise from this method such as controlling the probe scrubbing action, managing undesirable debris accumulation on the probe tip, and the added need for a complicated and invasive probe cleaning processes to remove the debris from the probe tips. Consistent scrub control is of paramount importance. A probe is often too sensitive to the overdrive motion from the pad, causing a scrub depth that is too deep that not only removes a portion of the non-conductive layer, but also damages or breaches the conductive pad, thus rendering the wafer unusable. Debris accumulation on the probe tip degrades the electrical continuity between the probe and conductive pad, often times restricting the test signal and providing erroneous test results, where implementation of an undesirable test redundancy may then become necessary. Complicated probe tip cleaning methods, such as use of abrasion cleaning, have been used to remove debris from the probe tip by scouring. Such a technique not only disrupts the fabrication throughput, but also degrades the probe tip, resulting in shortened utility of the probes and requiring premature replacement.

Current attempts to address these issues have been met with shortcomings, where in one case a contact bump at the end of a probe has a nub made from rhodium nickel alloy fused to the contact bump. While such an alloy lends itself for creating a tip that is more robust for scrubbing, the need to disrupt fabrication throughput for a probe tip cleaning process still exists. Further, the geometry of the contact bump made from the alloy nub lends itself for undesirable accumulation of debris, thus necessitating relatively frequent cleaning. Another attempt has been implemented that includes a knife-like probe end in an effort to reduce debris accumulation for limiting the need for abrasive cleaning. Unfortunately, such geometry has been shown to lack scrubbing control and damage the pad due to the probe having a hypersensitivity to overdrive motion. For additional information about probe tip geometries the reader is referred to U.S. Pat. No. 6,633,176 and U.S. Appl. 2005/0189955 both to Takemoto et al., and U.S. Pat. No. 6,842,023 to Yoshida et al. employs contact probe whose tip tapers to a sloping blade or chisel.

It would be considered an advance in the art to provide a probe design having a probe tip with a self-cleaning skate that alleviates the need for using abrasion techniques to remove debris from the probe tip. A method of using a self-cleaning probe tip is needed that provides effective scrubbing for enabling testing. Further needed is a probe having a self-cleaning skate that is less sensitive to overdrive motion to enable consistent and predictable scrubbing for more reliable wafer testing and to alleviate the need for test redundancies.

SUMMARY OF THE INVENTION

The present invention provides a probe having a self-cleaning tip, or skate, for engaging a conductive pad. The probe includes a contact end for receiving a test current, a probe retention portion below the contact end and a block for holding the retention portion. Further, a probe arm below the retention portion has a probe contact tip there below and a generally planar self-cleaning skate disposed perpendicular

3

below the contact tip. The self-cleaning skate has a generally square front end, a generally round back end and a generally flat middle section therebetween.

In one embodiment of the invention, the skate has a skate height up to $\frac{1}{2}$ of the skate length and a skate width up to $\frac{1}{6}$ of the skate length. In one aspect of the current invention, the self-cleaning skate width is narrower than a width of the contacting tip. In another aspect of the invention, the skate may have different cross-sections such as a U-shape, a semi-circular shape, a V-shape, box-shape, or a parallelogram-shape, where the parallelogram cross-section has a first parallel side connected to the bottom of the contact tip and a second parallel side for contacting the conductive pad, whereby the first parallel side is larger than the second parallel side. Further, the box-shape cross-section has a first horizontal side connected to the bottom of the contact tip and a second horizontal side for contacting the conductive pad, where the second horizontal side further includes radii at each edge of the second horizontal side. According to the embodiments of the current invention, the self-cleaning skate length is aligned along a scrub direction.

The conductive pad is generally convex and has a granular non-conductive surface layer of debris such as a non-conductive oxidation surface. The pad is moved to engage the skate. Once engaged, an overdrive motion is applied to the conductive pad causing the probe to flex and move the skate across the conductive pad to scrub debris from the pad. The scrubbed debris is displaced along the skate and moved around the skate round back end to a position on the skate that is away from the conductive pad. In one aspect of the invention, the probe arm has a base arm below the retention portion, a knee below the base arm, and a reverse arm below the knee. Further, a contact tip is below the reverse arm and the self-cleaning skate is below the contact tip.

In one embodiment of the invention, the skate round back end has a radius with a size as large as the length of the skate height. In another embodiment of the invention, the round back end of the skate is a variable radius back end.

In one aspect of the invention, the overdrive motion causes the skate to pivot such that the middle section forms an angle up to 35 degrees with respect to a horizontal plane, while the round back end remains engaged with the conductive pad. Reversing the overdrive motion causes the skate to reverse its movement, where the skate moves from an up angle to approximately a horizontal position while maintaining engagement with the conductive pad. Here, the skate translates along the horizontal position in a direction towards the skate back end, where the debris is further displaced along the round back end and away from the conductive pad. Finally, the conductive pad moves away from the skate to disengage the probe from the conductive pad.

In one aspect of the invention, the pad is in an extended overdrive motion beyond the previous overdrive motion, causing the probe move in a manner to further displace the debris away from the conductive pad. Here, the extended overdrive motion is applied after at least two touch down cycles. Such overdrive motion of the conductive pad is between 1-5 mil.

As an advancement in removing the debris from the skate, in one aspect of the invention, the conductive pads for engaging the probe tip are replaced by a cleaning sheet having debris adhesion properties for removing the debris from the skate.

One aspect of the present invention is a method of using the self-cleaning skate by providing a conductive pad having a generally convex shape and a non-conductive layer of

4

debris, such as a granular non-conductive oxidation surface, and providing a conductive probe for engaging the conductive pad. The probe includes a contact end for receiving a test current, a retention portion below the contact end, a block for holding the retention portion, a probe arm below the retention portion, a probe contact tip below the arm, and a generally planar self-cleaning skate disposed perpendicular below the contact tip, where the skate has a generally square front end, a generally round back end and a generally flat middle section therebetween. The skate is positioned above the conductive pad, where the conductive pad is translated, causing the skate to engage the conductive pad. Overdrive motion is then provided to the conductive pad causing the skate to scrub the debris from the conductive pad and clean the debris from the region of the skate that contacts the conductive pad. The cleaning occurs from the overdrive motion moving the skate to form an angle between the skate middle section and a horizontal plane, while engaging the round back end with the conductive pad. The overdrive motion induces a translation motion of the skate back end along the pad in a direction towards the skate front end while the skate middle section is further angled with respect to the horizontal plane. As the skate back end translates across the conductive pad, debris and non-conductive oxides are displaced along the skate, where the debris moves around the round back end to a position on the skate that is away from the conductive pad. Reversing the overdrive motion to the pad causes the skate middle section to move from the angle to approximately the horizontal position, where the skate flat middle section is in contact with the conductive pad. Here, the debris on the skate back end moves to a position away from the conductive pad. Continuing to reverse the overdrive motion translates the skate along the horizontal position and further moving the debris around the round back end to a position on the skate that is away from the conductive pad. Finally, the pad is translated to cause the probe to disengage from the conductive pad. The method according to the current invention improves overdrive control by making the scrubbing and cleaning less sensitive to the overdrive motion, where the debris layer is removed without breaching or damaging the conductive pad and debris is displaced from the conductive pad to the skate. Further, a current (i) is applied to the probe after the self-cleaning skate contacts the conductive pad. Using the self-cleaning skate according to the invention is accomplished after at least two engagement cycles.

In one aspect of the method according to the current invention, the probe arm includes a base arm below the retention portion, a knee below the base arm, and a reverse arm below the knee, where the contact tip is below the reverse arm and the self-cleaning skate is below the contact tip.

In another aspect of the invention, the self-cleaning skate is positioned above the pad by disposing an approximate center location of the flat middle end above an edge of the conductive pad, where the skate engages the conductive pad with the center of the skate positioned on the conductive pad edge.

Some key advantages of the invention are the features of the self-cleaning skate extend the mean time between failure of the probe caused by debris buildup on the skate. Additionally, due to the unique skate design, a scrub channel may be made on irregularly shaped conductive pads at any location on the pad. The current invention provides better control of the skate during overdrive motion, where improved tolerance to overdrive motion enables reliable pad testing on silicon wafers before dicing.

5

BRIEF DESCRIPTION OF THE FIGURES

The objectives and advantages of the present invention will be understood by reading the following detailed description in conjunction with the drawings, in which:

FIG. 1 shows a planar view of a block holding a probe having a self-cleaning skate engaging a conductive pad according to the present invention.

FIG. 2 shows a planar view of a probe tip having a self-cleaning skate that is positioned over a conductive pad according to the present invention.

FIG. 3 shows a perspective view of a block holding multiple probes with self-cleaning skates positioned over multiple conductive pads according to the present invention.

FIGS. 4a-4c show planar views of some embodiments of the self-cleaning skate according to the present invention.

FIGS. 5a-5f show planar cross-section views of some embodiments of the self-cleaning skate according to the present invention.

FIGS. 6a-6b show planar views of the overdrive of the conductive pad operating on the probe according to the present invention.

FIGS. 7a-7i show a sequence of planar partial cutaway views of the self-cleaning skate scrubbing across a conductive pad according to the present invention.

FIGS. 8a-8i show a sequence of planar partial cutaway views of the self-cleaning skate scrubbing across a conductive pad with initial the skate position on a pad edge according to the present invention.

FIG. 9a-9d show planar views of a conductive pad before and after scrubbing.

FIG. 10 is a flow-chart that shows the steps for using the self-cleaning skate according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Although the following detailed description contains many specifics for the purposes of illustration, anyone of ordinary skill in the art will readily appreciate that many variations and alterations to the following exemplary details are within the scope of the invention. Accordingly, the following preferred embodiment of the invention is set forth without any loss of generality to, and without imposing limitations upon, the claimed invention.

Semiconductor wafer processing methods and technology have been dynamic fields and continue to be the focus of much research and development. Among the numerous areas of these fields, early verification of process integrity and circuit design is an important step for effective cost control and manufacturing efficiency. As new methods of fabrication and new semiconductor wafer features evolve, testing methods must adapt to these changes. For example, the conductive pad of a semiconductor wafer can be fabricated as a dome-shape, or even a pedestal having a dome-shape located at the pedestal top, where the dome feature may be non-uniform and asymmetric. New methods of testing and new conductive test probes are required to address these evolving fabrication technologies. Typically, the conductive pad has a non-conductive layer of debris that includes a non-conductive oxide layer on the dome surface that impedes electrical contact between the probe tip and the conductive pad. In the testing phase, this layer requires a scrubbing step to remove some of the non-conductive layer of debris to enable electrical contact between the conductive pad and the probe tip. It is desirable to remove this layer and apply a test current to the pad to verify circuit design and

6

fabrication integrity, while simultaneously controlling the probe tip position on the pad and cleaning the probe end. In the current invention, the scrubbing process requires the conductive pad to be positioned below the probe tip and then moved to make contact with the probe tip. Once engaged, an overdrive motion is applied to the conductive pad whereby the probe flexes to allow the probe tip to traverse the conductive pad and scrub the non-conductive layer of debris from the pad surface while applying a test current (i) through the probe. Problems arise when scrubbing and testing the dome-shaped conductive pads. These problems include controlling the probe tip to ensure it remains on the conductive pad during scrubbing and testing, ensuring the translation of the probe tip across the pad is not too sensitive to the overdrive motion, and managing the debris that is removed to ensure electrical continuity and prevent or limit accumulation of debris on the probe tip.

To address these issues, the present invention provides a probe having a self-cleaning tip, or skate, for engaging a conductive pad of the semiconductor wafer, where the conductive pad may have a dome-shape or be a pedestal having a dome-shape. The probe includes a contact end for receiving a test current, a probe retention portion below the contact end and a block for holding the retention portion. Further, a probe arm below the retention portion has a probe contact tip there below and a generally planar self-cleaning skate disposed perpendicular below the contact tip. The self-cleaning skate has a generally square front end, a generally round back end and a generally flat middle section therebetween. This configuration may be made into an array of probes suited for scrubbing and testing semiconductor wafers having many conductive pads arranged according to a circuit, or multiple circuits, integrated to the wafer.

The skate of the probe contacting tip may have a height up to $\frac{1}{2}$ of the skate length and a skate width up to $\frac{1}{6}$ of the skate length. Additionally, the self-cleaning skate may have a width that is generally narrower than a width of the contacting tip. These skates may have a cross-section such as a U-shape, semi-circular shape, V-shape, box-shape, and parallelogram-shape, where the parallelogram cross-section has a first parallel side connected to the bottom of the contact tip and a second parallel side for contacting the conductive pad, whereby the first parallel side is larger than the second parallel side. Further, the box-shape cross-section may have a first horizontal side connected to the contact tip and a second horizontal side for contacting the conductive pad, where the second horizontal side further includes radii at each edge of the second horizontal side. In these aspects, the self-cleaning skate length is aligned along a scrub direction.

One conductive pad addressed in the current invention is generally convex having a non-conductive layer, such as a granular non-conductive oxidation layer, that is an artifact of the wafer fabrication process. The conductive pad is moved to engage the skate. Once engaged, an overdrive motion is applied to the conductive pad causing the probe arm to flex. This flexing allows the skate to remain in contact with the conductive pad while moving across the pad to scrub the non-conductive layer of debris and remove the debris from the conductive pad. An intended consequence of the skate design according to the current invention, is the scrubbed debris is displaced along the skate and moved around the skate round back end to a position on the skate that is away from said conductive pad.

In one aspect of the invention, to enable further control of the skate as the pad is subject to the overdrive motion, the probe arm has a base arm below the retention portion, a knee below the base arm, and a reverse arm below the knee.

Further, the contact tip is below the reverse arm and the self-cleaning skate is below the contact tip.

According to the design of the self-cleaning skate, the skate round back end has a radius with a size up to the length of the skate height. Alternatively, the round back end of the skate may be a variable radius, or multiple radii, back end.

According to the aspects of the invention, the overdrive motion causes the skate to pivot such that the middle section forms an angle up to 35 degrees with respect to a horizontal plane, while the round back end is engaged with the conductive pad. Further, by reversing the overdrive motion, the skate moves in a reverse direction across the conductive pad, where the skate moves from an up angle to approximately a horizontal position while engaging the conductive pad. Here, the skate translates along the horizontal position in a direction towards the skate back end, where the debris is further displaced along the round back end and away from the conductive pad. Finally, the conductive pad moves away from the skate to disengage the probe from the conductive pad, whereby a scrub channel is evident on the surface of the pad.

In one aspect of the invention, the pad is extended in an overdrive motion that is beyond the previous overdrive motion, the probe is caused to move in a manner that further displaces the already displaced debris away from the conductive pad. Here, the extended overdrive motion is applied after at least two touch down cycles. Such overdrive motion of the conductive pad may be between 1-5 mil.

Prior to the current invention, a separate process was required for removing accumulated debris from probes, such as scouring or buffing the probe ends. This added step is known to be invasive to the fabrication process, where in addition to a need for a separate mechanical configuration in the fabrication process, the probes are subject to additional wear from abrasion that shortens their utility. As an advancement in removing the debris from the skate, in one aspect of the invention, the conductive pads are replaced by a cleaning sheet having debris adhesion properties for removing the debris from the skate.

A method of using the self-cleaning skate according to the current invention includes providing the conductive pad having with the generally convex shape and a non-conductive layer, such as a granular oxidation surface, and providing a conductive probe for engaging the conductive pad that includes a contact end for receiving a test current, a retention portion below the contact end, a block for holding the retention portion, a probe arm below the retention portion, a probe contact tip below the arm, and a generally planar self-cleaning skate disposed perpendicularly below the contact tip, where the skate has a generally square front end, a generally round back end and a generally flat middle section therebetween. The skate is positioned above the conductive pad, where the conductive pad is translated causing the skate to engage the conductive pad. Overdrive motion is provided to the conductive pad causing the skate to scrub the non-conductive layer of debris and remove it from the conductive pad and then clean the debris from the skate. The cleaning occurs by the overdrive motion flexing the probe and causing the skate to move across the pad to form an angle of the skate middle section with respect to a horizontal plane while still engaging the round back end with the conductive pad. The overdrive motion induces translation motion of the skate back end in a direction towards the skate front end across the conductive pad while the skate middle section is further angled with respect to the horizontal plane. As the skate back end translates across the conductive pad, debris, such as a non-conductive oxide, is displaced along

the skate, where the debris moves around the round back end to a position on the skate that is away from the conductive pad. Reversing the overdrive motion to the pad causes the skate middle section to move from the angle to approximately the horizontal position, where the skate flat middle section is in contact with the conductive pad. Here, the debris on the skate back end moves to a position away from the conductive pad. Continuing to reverse the overdrive motion of the conductive pad translates the skate along the horizontal position and further moves the debris around the round back end to a position on the skate that is away from the conductive pad. Finally, the pad is translated to cause the probe to disengage from the conductive pad. The method according to the current invention improves overdrive control by making the scrubbing and cleaning less sensitive to the overdrive motion, where the oxidation layer is removed without breaching the conductive pad and debris is displaced from the conductive pad to the skate. Accordingly, a current (i) is applied after said self-cleaning skate contacts the conductive pad.

Using the self-cleaning skate according to the invention is accomplished after at least two said engagement cycles.

In one aspect of the current invention, the probe arm includes a base arm below the retention portion, a knee below the base arm, and a reverse arm below the knee, where the contact tip is below the reverse arm and the self-cleaning skate is below the contact tip.

In another aspect of the invention, the self-cleaning skate is positioned above the pad by disposing an approximate center location of the flat middle end above an edge of the conductive pad, where the skate to engages the conductive pad with the center of the skate positioned on the conductive pad edge.

Referring now to the figures, FIG. 1 is a planar view of a scrubbing system **100** that includes a block **102** holding a probe **104** having a self-cleaning skate **106** for engaging a conductive pad **108** to scrub debris (see FIG. 2) from the conductive pad **108** while applying the test current (i), according to the present invention. The probe includes a contact end **110** for receiving the test current (i) (not shown), a probe retention portion **112**, below the contact end, that is held by the block **102**. A probe arm **114** below the retention portion **112** has a probe contact tip **116** at the end, with a generally planar self-cleaning skate **106** disposed perpendicularly below the contact tip **116**. According to one embodiment of the invention and depicted in FIG. 1, the probe arm **114** has a base arm **118** below the retention portion, a knee **120** below the base arm **118**, and a reverse arm **122** below the knee **120**, where the contact tip **116** is below the reverse arm **122** and the self-cleaning skate **106** is below the contact tip **116**.

Illustrated in FIG. 2 is a planar view of the probe tip **116** having the self-cleaning skate **106** positioned over a conductive pad **108** according to one embodiment of the present invention. Here, the self-cleaning skate **106** depicted is generally planar and disposed perpendicular below the contact tip **116**, where the skate **106** has a generally square front end **200**, a generally round back end **202** and a generally flat middle section **204** therebetween. Further depicted, the conductive pad **108** has a layer of non-conductive granular debris **208** formed in a generally convex shape on a generally cylindrical base **210**, where the non-conductive granular debris **208** can be a non-conductive oxide layer resulting from a breakdown of the surface of the metallic conductive pad in the fabrication processes.

FIG. 3 depicts a perspective view of the block **102** holding multiple probes **104** with self-cleaning skates **106** positioned

over multiple conductive pads **108** according to one embodiment of the present invention. The conductive pads **108** are embedded into a semiconductor wafer **300**, where the wafer **300** and pads **108** are driven upwards to cause the conductive pads **108** to engage the self-cleaning skates **106** for scrubbing and testing as will be described below.

FIGS. **4a-4c** show planar views the self-cleaning skate according to the present invention. In FIG. **4a**, a self-cleaning skate **106** is depicted that has a generally square front end **200**, a generally round back end **202** and a generally flat middle section **204** therebetween. FIG. **4b** depicts another embodiment of the invention with the generally round back end **202** of the self-cleaning skate **106** having a variable radius, or multiple radii, depicted here having a first radius **R1** and a second radius **R2** in this embodiment. Depicted in FIG. **4c** is an end planar view of the self-cleaning skate **106** connected perpendicularly to bottom of the contact tip **116** where shown are the skate width **400**, skate height **402** and the skate length **404** (see FIG. **4a**). According to one embodiment of the invention, the self-cleaning skate **106** has a height **402** up to $\frac{1}{2}$ of the skate length **404** and a skate width **400** up to $\frac{1}{6}$ of the skate length **404**, and the skate width **400** is narrower than the contacting tip width **406**. The self-cleaning skate **106** may have many different cross-section geometries. FIGS. **5a-5e** show planar views of some cross-section embodiments of the self-cleaning skate according to the present invention. FIG. **5a** depicts box-shape cross-section **500**, FIG. **5b** depicts a U-shape cross-section **502**, FIG. **5c** depicts a parallelogram-shape cross-section **504**, FIG. **5d** depicts a V-shape cross-section **506**, FIG. **5e** depicts a semi-circular shape cross-section **508**, and FIG. **5f** depicts a box-shape having rounded edges **510**. The parallelogram cross-section **504** has a first parallel side **512** connected to the bottom of the contact tip **116** and a second parallel side **514** for contacting the conductive pad (not shown), where the first parallel side **512** is larger than the second parallel side **514**. The cross-sections depicted here are a small sample of the many possible cross-section geometries that may be used with the current invention to obtain the desired results of scrubbing and testing the conductive pads **108**.

FIGS. **6a** and **6b** show planar views of the overdrive of the conductive pad operating on the probe according to the present invention. Depicted here, is the self-cleaning skate **108**, according to one embodiment of the current invention, that utilizes the round back end **202** to smoothly scrub across the conductive pad **108** when subject to overdrive motion **600** to scrub debris **208** while not breaching the conductive pad **108**. Overdrive motion **600** can range from 1-5 mil. In FIG. **6a**, the skate **106** is positioned with the center of the flat middle section **204** located near an edge of the conductive pad **108**, where the skate **106** is shown to contact the pad **108**.

Depicted in FIG. **6b** is an overdrive motion **600** applied to the conductive pad **108**, where dashed lines **602** are provided to show a relative overdrive displacement of the conductive pad **108**. One benefit of the round back end **202** is that it averts the skate **106** from binding in the debris **208** when the overdrive motion **600** is applied, preventing the probe **106** from unpredictably releasing from the debris **208** and springing off of the pad **108**, which is undesirable. Further, the added linear distance along the bottom surface of the skate **106** attained by having the round back end **202** provides improved tolerance to overdrive **600**.

The current invention improves the skate **106** response to overdrive motion **600** of the conductive pad **108**, where movement of the skate **106** having the generally round back

end **202** allows the skate **106** to smoothly scrub across the conductive pad **108**. A probe end not having the features according to the current invention is known to become caught in the debris **208** while the overdrive motion **600** continues, thus causing the probe arm to build up potential energy. The consequence of this undesirable state is the potential energy eventually surpasses the debris strength and the skate releases across the conductive pad **108**, rapidly and without control, swinging beyond the conductive pad **108** thus potentially damaging the skate **106** and/or the pad **108**.

FIGS. **7a-7i** show a sequence of planar partial cutaway views of the self-cleaning skate **106** that scrubs a channel **704** (see FIG. **7i**) in the conductive pad according to the present invention. Depicted in FIG. **7a** is the probe **104** having a contact tip **116** with the self-cleaning skate **106** attached at the bottom and positioned above the conductive pad **108**. The conductive pad **108** is depicted in a cutaway view for illustrative purposes, where a layer of granular debris **208**, such as a non-conductive oxide layer, is depicted as a convex shape on top of the conductive pad **108** (see FIG. **9** for drawing of the pad and granular debris). The conductive pad **108** is raised, or translated, to cause the self-cleaning skate **106** to engage the layer of debris **208** of the conductive pad **108**, as depicted in FIG. **7b**. Once engaged, a test current (**i**) is applied to the probe and the conductive pad **108** is provided an overdrive motion **600** causing the skate **106** to scrub the debris **208** from the conductive pad **108** and clean the debris **208** from the bottom of the skate **106** as illustrated in this sequence. FIG. **7c-7e** depict the response of the probe **104** when subject to overdrive motion **600** from the conductive pad **108**, where the probe **114** flexes and causes the contact tip **116** to rotate **700** and form an angle between the skate middle section **204** and a horizontal plane on the pad **108** while engaging the round back end **202** with the conductive pad **108**. Overdrive motion **600** is continued in FIGS. **7d** and **7e** to induce a horizontal translational motion **702** of the skate **106** in a direction from the back end **202** towards the front end **200** across the conductive pad **108** while the skate middle section **204** is further rotated **700** with respect to the horizontal plane. In this exemplary sequence, debris **208** is displaced along the skate **106** and moved around the round back end **202** to a position on the skate **106** that is away from the conductive pad **108**. By reversing the overdrive motion **600** to the conductive pad **108**, the skate **106** moves in a manner such that the skate middle section **204** rotates **700** from the angle to approximately the horizontal position, as depicted in FIG. **7f**, where the skate flat middle section **204** is in contact with the conductive pad **108**. Shown in FIG. **7g**, the debris **208** on the skate back end **202** moves to a position away from the conductive pad **108** as the flat middle section **204** is further rotated **700** down to a horizontal position. Continuing the reverse overdrive motion **600** causes the skate **106** to translate **702** in an opposite direction along the horizontal position on the conductive pad **108**, depicted in FIG. **7h**, and further moves the debris **208** around the round back end **202** to a position on the skate **106** that is away from the conductive pad **108**. Finally, the reverse overdrive motion **600** of the conductive pad **108** continues to cause the probe **104** to disengage from the conductive pad, as depicted in FIG. **7i**, where this scrubbing method improves overdrive **600** control by making the skate **106** movement less sensitive to the overdrive **600**. Accordingly, the oxidation layer **208** is removed without breaching the conductive pad **108** and the debris **208** is displaced from the conductive pad **108** along the skate **106** to a position away from the pad **108**. Further depicted in FIG. **7i** is a scrub channel **704** near the

11

pad center having a furrow-buildup of the debris 208 to illustrate how it responds to scrubbing from the self-cleaning skate according to the current invention, where the scrub channel 704 that exposes the conductive metal 706 of the conductive pad 108.

FIGS. 8a-8i show planar views of the overdrive motion 600 of the conductive pad 108 operating on the probe 114 having a self-cleaning skate 106 according to the present invention. Depicted in FIG. 8a is the probe 114 having a contact tip 116 with the self-cleaning skate 106 attached at the bottom. In this example, the skate 106 is positioned with the skate middle section 204 above the edge of the conductive pad 108. The conductive pad 108 is depicted in a cutaway view for illustrative purposes, where a layer of granular debris 208 is depicted on top of the conductive pad 108 (see FIG. 9 for drawing of the pad and granular debris). The conductive pad 106 is moved to cause the self-cleaning skate 106 to engage the debris layer 208 of the conductive pad 108, as depicted in FIG. 8b. Once engaged, the conductive pad 108 is provided an overdrive motion 600 causing the skate 106 to scrub the debris 208 from the conductive pad 108 and clean the debris 208 from the skate 106. FIGS. 8c-8e depict the response of the probe 114 when subject to overdrive motion 600 from the conductive pad 208 moving in an upward direction, where the probe 114 flexes and causes the contact tip 116 to rotate 700 and form an angle between the skate middle section 204 and a horizontal plane while engaging the round back end 202 with the conductive pad 108. Here, the square front end 200 is on the convex shape of the conductive pad 108 while the round back end 202 is off the pad 108. This way, as the probe 114 undergoes deflection, it rocks on the edge of the pad 108 to provide a highly concentrated force that helps the skate 106 penetrate the debris 208 (see FIG. 8d). Overdrive motion 600 is continued in FIG. 8e to induce a translation 702 of the skate 106 in a direction from the back end 202 towards the front end 200 across the conductive pad 108 while the skate middle section 204 further rotates 700 with respect to the horizontal plane. In this sequence, debris 208 is displaced along the skate 106 and moved around the round back end 202 to a position on the skate 106 that is away from the conductive pad 108. By reversing the overdrive motion 600 of the conductive pad 108, the skate 106 rotates 700 in a manner such that the skate middle section 204 forms a smaller angle with respect to the horizontal plane, while simultaneously translating 702 in a direction from the front end 200 towards the back end 202 across the conductive pad 108 as depicted in FIGS. 8f and 8g, where the skate flat middle section 204 is in contact with the conductive pad. The debris 208 on the skate back end 202 moves to a position away from the conductive pad 108 as the flat middle section 204 is further rotated down to a horizontal position. Depicted in FIG. 8h is the skate 106 translating 702 with the middle section 204 in a horizontal orientation, and the reverse overdrive motion 600 of the conductive pad 108 continues to cause the probe 114 to disengage from the conductive pad, as depicted in FIG. 8i. The sequence described here illustrates how the self-cleaning skate 106 improves overdrive control by making the skate 106 movement less sensitive to the overdrive. Accordingly, the debris layer 208 is removed without breaching the conductive pad 108, where the debris 208 is displaced from the conductive pad 108 to a position on the skate 106 that is away from the pad 108. Further depicted in FIG. 8i is a scrub channel 600 that exposes the conductive metal 706 of the conductive pad 108.

12

By selecting the initial position of the skate 106 relative to the pad 108, the scrub channel 600 can be made in all locations on the surface of the conductive pad 108, where the invention provides better control of the motion of the skate 106 across the pad 108, while preserving the integrity of the conductive pad 108 and the skate 106. FIGS. 9a-9d depict planar views of a conductive pad 108 before and after scrubbing. FIG. 9a shows a side planar view of a typical conductive pad 108 having a splayed-cylindrical conductive metal base 706 and a layer of debris 208, such as a non-conductive oxide layer, on a convex pad 108. FIG. 9b shows a top planar view of a typical conductive pad 108 having a generally granular surface of debris 208 to be scrubbed for enabling conduction of the test signal (i) from the skate 106 to the pad 108. FIG. 9c illustrates a scrub channel 704 made across the center of the pad 108 as per the description related to FIG. 7 above, and FIG. 9d illustrates a scrub channel 704 made near the edge of the pad 108 as per the description related to FIG. 8 above. Though the drawings of the conductive pad 108 are depicted to have a general convex shape, in practice the surface pad 108 can be an irregular shape. The self-cleaning skate 106 according to the embodiments described are able to provide useful scrub channels 704 in these irregular shapes and in numerous pad locations to provide conduction for the test signal (i) with tolerance to overdrive motion 600 and without breaching the pad 108, where the thickness of the pad may be only slightly more thick than the debris layer.

FIG. 10 is a flow diagram depicting the steps for using the self-cleaning skate according to the present invention. The steps include providing a conductive pad 1000, providing a conductive probe having a conductive self-cleaning skate with a square front end, a round back end and a flat middle section 1002, positioning the skate above the conductive pad 1004, translating the conductive pad to engage the skate 1006, and providing overdrive motion to the pad 1008 and moving the skate to scrub debris from the pad and clean debris from the skate 1008, wherein the method improves overdrive control by making the scrubbing and the cleaning less sensitive to the overdrive, where the debris layer is removed without breaching the conductive pad and debris is displaced from the conductive pad to a position on the skate that is away from the pad.

The present invention has now been described in accordance with several exemplary embodiments, which are intended to be illustrative in all aspects, rather than restrictive. Thus, the present invention is capable of many variations in detailed implementation, which may be derived from the description contained herein by a person of ordinary skill in the art. All such variations are considered to be within the scope and spirit of the present invention as defined by the following claims and their legal equivalents.

What is claimed is:

[1. A probe for engaging a conductive pad, said probe comprising:

- a. a probe contact end for receiving a test current;
- b. a probe retention portion below said contact end;
- c. a block holding said retention portion;
- d. a probe arm below said retention portion;
- e. a probe contact tip below said arm; and
- f. a generally planar self-cleaning skate disposed perpendicular below said contact tip having a generally square front end, a generally round back end and a generally flat middle section therebetween, wherein said conductive pad of generally convex shape and having a granular non-conductive surface layer of debris moves to engage said skate, whereby an overdrive motion is

13

applied to said conductive pad thereby causing said skate to move across said conductive pad to scrub non-conductive debris from said conductive pad and displace said debris along said skate and move said debris near said skate round back end to a position on said skate that is away from said conductive pad.]

[2. The probe according to claim 1, wherein said non-conductive surface layer of debris is a non-conductive oxide.]

[3. The probe according to claim 1, wherein said skate comprises a skate height up to $\frac{1}{2}$ of a skate length and a skate width up to $\frac{1}{6}$ of said skate length.]

[4. The probe according to claim 3, wherein said self-cleaning skate width is narrower than a width of said contacting tip.]

[5. The probe according to claim 1, wherein said skate has a cross-section selected from a group consisting of U-shape, semi-circular shape, V-shape, box-shape, and parallelogram-shape.]

[6. The probe according to claim 5, wherein said parallelogram cross-section has a first parallel side connected to said contact tip and a second parallel side for contacting said conductive pad, whereby said first parallel side is larger than said second parallel side.]

[7. The probe according to claim 5, wherein said box-shape cross-section comprises a first horizontal side connected to said contact tip and a second horizontal side for contacting said conductive pad, whereby said second horizontal side further comprises radii at each edge of said second horizontal side.]

[8. The probe according to claim 1, wherein said probe arm comprises a base arm below said retention portion, a knee below said base arm, and a reverse arm below said knee, whereby said contact tip is below said reverse arm and said self-cleaning skate is below said contact tip.]

[9. The probe according to claim 1, wherein said skate round back end has a radius with a size up to a length of said skate height.]

[10. The probe according to claim 1, wherein said round back end is a variable radius back end.]

[11. The probe according to claim 1, wherein said overdrive motion causes said skate to pivot, whereby said middle section forms an angle up to 35 degrees with respect to a horizontal plane while said round back end is engaged with said conductive pad.]

[12. The probe according to claim 1, wherein reversing said overdrive motion causes said skate to move in a reverse direction, whereby

- a. said skate moves from an angle to approximately a horizontal position while maintaining said engagement with said conductive pad;
- b. said skate translates along said horizontal position in a direction towards said skate back end, whereby said debris is further displaced along said round back end and away from said conductive pad; and
- c. said conductive pad moves away from said skate to disengage said probe from said conductive pad.]

[13. The probe according to claim 1, wherein in an extended overdrive motion beyond said overdrive motion is applied to said conductive pad causing said probe to move in a manner to further displace said displaced debris away from said conductive pad.]

[14. The probe according to claim 13, wherein said extended overdrive motion is applied after at least two touch down cycles.]

[15. The probe according to claim 1, wherein said conductive pad moves between 1-5 mil.]

14

[16. The probe according to claim 1, wherein said conductive pad is a cleaning sheet having debris adhesion properties for removing said debris from said skate.]

[17. The probe according to claim 1, wherein said self-cleaning skate length is aligned along a scrub direction.]

[18. A conductive probe for engaging a conductive pad comprising:

- a. a contact end for receiving a test current;
- b. a retention portion below said contact end;
- c. a block holding said retention portion;
- d. a base arm portion below said retention portion;
- e. a knee below said base arm portion;
- f. a reverse arm portion below said knee;
- g. a contact tip below said reverse arm portion; and
- h. a generally planar self-cleaning skate disposed perpendicular below said contact tip having a generally square front end, a generally round back end and a generally flat middle section therebetween, wherein said conductive pad is of generally convex shape and having a granular non-conductive surface layer of debris moves to engage said skate, whereby an overdrive motion is applied to said conductive pad thereby causing said skate to move across said conductive pad to scrub said debris from said conductive pad and displace said debris along said skate and move said debris near said skate round back end to a position on said skate that is away from said conductive pad.]

[19. A method of using a self-cleaning skate comprising:

- a. providing a conductive pad having a generally convex shape and a granular non-conductive surface layer of debris;
- b. providing a conductive probe for engaging said conductive pad, the conductive probe comprising:
 - i. a contact end for receiving a test current;
 - ii. a retention portion below said contact end
 - iii. a block holding said retention portion;
 - iv. a probe arm below said retention portion;
 - v. a probe contact tip below said arm; and
 - vi. a generally planar self-cleaning skate disposed perpendicular below said contact tip having a generally square front end, a generally round back end and a generally flat middle section therebetween;
- c. positioning said skate above said conductive pad;
- d. translating said conductive pad causing said skate to engage said conductive pad;
- e. providing an overdrive motion to said conductive pad causing said skate to scrub said debris to expose conductive material of said conductive pad and clean said debris from said skate wherein said cleaning comprises:
 - i. forming an angle of said skate middle section with respect to a horizontal plane while engaging said round back end with said conductive pad;
 - ii. inducing a translation motion of said skate back end in a direction towards said skate front end across said conductive pad while said skate middle section is further angled with respect to said horizontal plane;
 - iii. displacing said debris along said skate and moving said debris around said round back end to a position on said skate that is away from said conductive pad;
 - iv. reversing said overdrive motion to said pad causing said skate middle section to move from said angle to approximately said horizontal position, wherein said skate flat middle section is in contact with said conductive pad whereby said debris on said skate back end moves to a position away from said conductive pad; and

15

v. translating said skate along said horizontal position and further moving said debris around said round back end to a position on said skate that is away from said conductive pad; and

vi. translating said pad to cause said probe to disengage from said conductive pad,

wherein said method improves overdrive control by making said scrubbing and said cleaning less sensitive to said overdrive, whereby said non-conductive layer of debris is removed without breaching said conductive pad and debris is displaced from said conductive pad to said skate.]

[20. The method of claim 19, wherein using said self-cleaning method is accomplished after at least two said engagement cycles.]

[21. The method of claim 19, wherein said non-conductive layer of debris is a non-conductive oxide layer.]

[22. The method of claim 19, wherein a current (i) is applied after said self-cleaning skate contacts said conductive pad.]

[23. The method of claim 19, wherein said probe arm comprises a base arm below said retention portion, a knee below said base arm, and a reverse arm below said knee, whereby said contact tip is below said reverse arm and said self-cleaning skate is below said contact tip.]

[24. The method of claim 19, wherein positioning said self-cleaning skate above said pad comprises disposing said skate at an approximate center location of said flat middle end above an edge of said conductive pad.]

[25. The method of claim 24, wherein engaging said conductive pad comprises engaging said approximate center of said skate with said conductive pad edge.]

26. A method of using a self-cleaning skate comprising: positioning the self-cleaning skate having at least one rounded edge and at least one flat edge blade above a conductive pad;

engaging the skate and the conductive pad;

causing the skate to scrub at least a portion of debris disposed on the conductive pad thereby exposing conductive material; and

cleaning the debris from the skate.

27. The method of claim 26 wherein the conductive pad has a generally convex shape.

28. The method of claim 26 wherein the conductive pad has a non-conductive surface layer of debris.

29. The method of claim 28 wherein the conductive pad has a granular non-conductive surface layer of debris.

16

30. The method of claim 26 further comprising providing a motion to the conductive pad.

31. The method of claim 30 further comprising providing an overdrive motion to the conductive pad.

32. The method of claim 31 wherein the overdrive motion ranges from about 1 to about 5 millimeters.

33. The method of claim 26 wherein cleaning the debris from the skate comprises:

forming an angle of the skate middle section with respect to a horizontal plane while engaging the round back end with the conductive pad;

inducing a translation motion of the skate back end in a direction toward the skate front end across the conductive pad while the skate middle section is further angled with respect to the horizontal plane; and

displacing the debris along the skate and moving the debris around the round back end to a position on the skate that is away from the conductive pad.

34. The method of claim 33 further comprising reversing the motion to the pad causing the skate middle section to move from the angle to approximately the horizontal position, wherein the skate middle section is in contact with the conductive pad and whereby the debris on the skate back end moves to a position away from the conductive pad.

35. The method of claim 34 further comprising translating the skate along the horizontal position and further moving the debris around the round back end to a position on the skate that is away from the conductive pad.

36. The method of claim 33 further comprising translating the conductive pad to cause the probe to disengage from the conductive pad.

37. The method of claim 26 wherein the debris comprises a non-conductive oxide layer.

38. The method of claim 26 further comprising applying a current after the skate contacts the conductive pad.

39. The method of claim 26 wherein positioning the self-cleaning skate above the conductive pad comprises disposing the skate at an approximate center location of the flat middle end above an edge of the conductive pad.

40. The method of claim 26 further comprising translating the conductive pad causing the skate to engage the conductive pad.

41. The method of claim 40 further comprising engaging the conductive pad at an approximate center of the skate with the conductive pad.

* * * * *