



US00RE46255E

(19) **United States**
(12) **Reissued Patent**
Hendrickson et al.

(10) **Patent Number: US RE46,255 E**
(45) **Date of Reissued Patent: *Dec. 27, 2016**

(54) **FIBER OPTIC CABLE DISTRIBUTION BOX**

(56)

References Cited

(71) Applicant: **CommScope Technologies LLC**,
Hickory, NC (US)
(72) Inventors: **Daniel Hendrickson**, Roswell, GA
(US); **Hongbo Zhang**, Duluth, GA (US)

U.S. PATENT DOCUMENTS

1,276,825 A 8/1918 Swopo
1,442,999 A 1/1923 Boardman et al.
(Continued)

(73) Assignee: **CommScope Technologies LLC**,
Hickory, NC (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: This patent is subject to a terminal disclaimer.

DE 3841607 6/1990
DE 3841607 A1 6/1990
(Continued)

(21) Appl. No.: **14/492,970**

OTHER PUBLICATIONS

(22) Filed: **Sep. 22, 2014**

7 Inch Modules, ADC Telecommunications, Inc, © 1998, "7 Inch Connector Module with IFC", pp. 127.

Related U.S. Patent Documents

(Continued)

Reissue of:

(64) Patent No.: **7,522,806**
Issued: **Apr. 21, 2009**
Appl. No.: **12/156,297**
Filed: **May 30, 2008**

Primary Examiner — Deandra Hughes

(74) *Attorney, Agent, or Firm* — Merchant & Gould P.C.

U.S. Applications:

(63) Continuation of application No. 13/091,851, filed on Apr. 21, 2011, now Pat. No. Re. 45,153, which is a
(Continued)

(57)

ABSTRACT

(51) **Int. Cl.**
G02B 6/00 (2006.01)
G02B 6/44 (2006.01)


(52) **U.S. Cl.**
CPC **G02B 6/4441** (2013.01); **G02B 6/4466**
(2013.01); **G02B 6/4471** (2013.01)

(58) **Field of Classification Search**
CPC ... G02B 6/4477; G02B 6/4471; G02B 6/4441;
G02B 6/4478; G02B 6/4457; G02B
6/4458

A fiber optic cable distribution box has an interface compartment for interfacing a first set of fibers when routed inside the compartment, with a second set of fibers associated with a fiber optic cable that is routed to the box. A drum region is disposed beneath the interface compartment. The drum region includes a cylindrical wall for supporting a fiber optic cable wound about the wall. The drum region is formed so that the box can turn about the axis of the cylindrical wall when a cable is paid out from the drum region. The interface compartment and the drum region are constructed so that the first set of fibers inside the interface compartment, originate from an inside end portion of the cable wound on the drum region.

(Continued)

31 Claims, 7 Drawing Sheets



US RE46,255 E

(60)	(58)	(56)	6,220,413 B1	4/2001	Walters et al.	
			6,243,526 B1 *	6/2001	Garibay	G02B 6/3887 385/135
			6,315,598 B1	11/2001	Elliot et al.	
			6,347,462 B1	2/2002	Steinich	
			6,379,166 B1 *	4/2002	Hagarty	G02B 6/4466 439/134
			6,494,396 B2	12/2002	Sugata	
			6,522,826 B2	2/2003	Gregory	
			6,551,237 B2 *	4/2003	Matsui	600/118
			6,554,221 B2	4/2003	Hinds	
			6,591,051 B2	7/2003	Solheid et al.	
			6,616,080 B1	9/2003	Edwards et al.	
			6,669,129 B1	12/2003	Shah	
			6,694,084 B1 *	2/2004	Nakamura	G02B 6/4452 385/135
			6,711,339 B2	3/2004	Puetz et al.	
			6,834,517 B1	12/2004	Sheehy, Jr.	
			6,856,748 B1	2/2005	Elkins, II et al.	
			6,915,058 B2	7/2005	Pons	
			6,927,340 B1	8/2005	Binder et al.	
			6,937,725 B2	8/2005	Liao	
			6,948,680 B2 *	9/2005	Ganster	242/601
			6,997,410 B1	2/2006	Huang	
			7,000,863 B2	2/2006	Bethea et al.	
			7,011,538 B2	3/2006	Chang	
			7,016,590 B2	3/2006	Tanaka et al.	
			7,017,721 B1	3/2006	Bradford et al.	
			7,220,144 B1	5/2007	Elliot et al.	
			7,315,681 B2 *	1/2008	Kewitsch	G02B 6/4457 385/135
			7,346,253 B2 *	3/2008	Bloodworth	G02B 6/4453 385/134
			7,364,108 B2	4/2008	Kim et al.	
			7,369,739 B2 *	5/2008	Kline	B65H 75/44 385/135
			7,397,997 B2	7/2008	Ferris et al.	
			7,400,814 B1	7/2008	Hendrickson et al.	
			7,477,829 B2	1/2009	Kaplan	
			7,519,258 B2	4/2009	Wilken et al.	
			7,522,806 B2	4/2009	Hendrickson et al.	
			7,533,472 B2	5/2009	Birchinger et al.	
			7,533,841 B1 *	5/2009	Harrison	B65H 75/14 242/388.5
			7,546,018 B2	6/2009	Hendrickson et al.	
			7,676,136 B2	3/2010	Wakileh et al.	
			7,756,379 B2	7/2010	Kowalczyk et al.	
			7,809,234 B2	10/2010	Smith et al.	
			7,894,701 B2	2/2011	Kowalczyk et al.	
			2002/0023814 A1	2/2002	Poutiatine	
			2002/0122652 A1	9/2002	Gonzalez et al.	
			2002/0126980 A1	9/2002	Holman et al.	
			2002/0131749 A1 *	9/2002	Swenson	G02B 6/4453 385/135
			2002/0164121 A1	11/2002	Brennan et al.	
			2002/0171002 A1	11/2002	Krestsch et al.	
			2002/0172489 A1 *	11/2002	Daoud	G02B 6/4457 385/135
			2003/0037480 A1	2/2003	Davis	
			2004/0218887 A1	11/2004	Brown et al.	
			2004/0244430 A1	12/2004	Sheehy et al.	
			2005/0135771 A1 *	6/2005	Attanasio	G02B 6/4477 385/138
			2005/0163448 A1 *	7/2005	Blackwell, Jr.	G02B 6/4451 385/135
			2005/0213920 A1 *	9/2005	Tanaka	G02B 6/4466 385/135
			2005/0247136 A1	11/2005	Cross et al.	
			2005/0258411 A1	11/2005	Zeitler	
			2006/0008231 A1	1/2006	Reagan et al.	
			2006/0147172 A1 *	7/2006	Luther	G02B 6/4441 385/135
			2006/0163403 A1	7/2006	Dickson	
			2006/0183362 A1	8/2006	Mullaney et al.	
			2006/0210230 A1	9/2006	Kline et al.	
			2007/0025675 A1	2/2007	Kramer	
			2007/0058919 A1 *	3/2007	Desanti	G02B 6/4466 385/135

Related U.S. Application Data

continuation of application No. 11/728,785, filed on Mar. 27, 2007, now Pat. No. 7,400,814.

(60) Provisional application No. 60/880,169, filed on Jan. 13, 2007.

(58) **Field of Classification Search**
USPC 385/134, 135
See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

1,446,410 A	2/1923	McCormick et al.
1,474,580 A	11/1923	Clark et al.
RE20,995 E	2/1939	Beasley
2,502,496 A	4/1950	Wickman
2,521,226 A	9/1950	Keller
2,727,703 A	12/1955	Bonnett
3,131,729 A	5/1964	Leysinger
3,657,491 A	4/1972	Ryder et al.
3,667,417 A	6/1972	Clinkenbeard
3,920,308 A	11/1975	Murray
3,940,086 A	2/1976	Stoquelet
4,053,118 A	10/1977	Aikins
4,081,258 A	3/1978	Goell et al.
4,384,688 A	5/1983	Smith
4,587,801 A	5/1986	Missout et al.
4,635,875 A	1/1987	Apple
4,666,237 A	5/1987	Mallinson
4,767,073 A	8/1988	Malzacher
4,869,437 A	9/1989	Berz et al.
4,883,337 A	11/1989	Dahlgren
4,913,369 A	4/1990	Lia et al.
4,939,798 A	7/1990	Last
4,940,859 A	7/1990	Peterson
4,976,510 A	12/1990	Davila et al.
5,016,554 A	5/1991	Harris et al.
5,022,600 A	6/1991	Blanc et al.
5,066,256 A	11/1991	Ward
5,069,523 A	12/1991	Finzel et al.
5,074,863 A	12/1991	Dines
5,185,843 A	2/1993	Aberson et al.
5,185,853 A	2/1993	Cheng et al.
5,265,815 A	11/1993	Soyka et al.
5,280,861 A	1/1994	Corriveau
5,317,663 A	5/1994	Beard et al.
5,326,040 A	7/1994	Kramer
5,335,874 A	8/1994	Shrum et al.
5,434,944 A *	7/1995	Kerry G02B 6/4441 385/134
5,494,234 A	2/1996	Kramer
5,494,446 A	2/1996	De Lucia et al.
5,497,444 A	3/1996	Wheeler
5,519,275 A	5/1996	Scott et al.
5,522,561 A *	6/1996	Koyamatsu B65H 55/043 206/409
5,544,836 A	8/1996	Pera
5,551,545 A	9/1996	Gelfman
5,638,481 A	6/1997	Arnett
5,657,412 A	8/1997	Caudrelier
5,703,990 A	12/1997	Robertson et al.
5,709,347 A	1/1998	Hoffmann et al.
5,717,810 A	2/1998	Wheeler
5,718,397 A	2/1998	Stevens
5,749,148 A	5/1998	White et al.
5,758,004 A *	5/1998	Alarcon G02B 6/4471 174/93
5,787,219 A	7/1998	Muellet et al.
5,915,640 A	6/1999	Wagter et al.
5,987,203 A	11/1999	Abel et al.
5,992,787 A	11/1999	Burke
6,167,183 A *	12/2000	Swain G02B 6/4454 385/134
6,215,938 B1 *	4/2001	Reitmeier G02B 6/4441 385/134

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0165995	A1	7/2007	Reagan et al.	
2007/0189691	A1	8/2007	Barth et al.	
2007/0189694	A1*	8/2007	Mullaney	G02B 6/4441 385/135
2007/0274659	A1*	11/2007	Kaplan	G02B 6/4441 385/134
2008/0035778	A1	2/2008	Belden et al.	
2008/0037945	A1*	2/2008	Gniadek	B65H 49/20 385/135
2008/0118207	A1*	5/2008	Yamamoto	G02B 6/4457 385/88
2008/0218947	A1	9/2008	Atkinson	
2008/0315030	A1	12/2008	Hendrickson et al.	
2009/0190894	A1	7/2009	Nhep et al.	
2010/0054680	A1	3/2010	Lochkovic et al.	
2010/0166376	A1	7/2010	Nair et al.	

FOREIGN PATENT DOCUMENTS

DE	42 26 368	A1	2/1994
EP	0343057		11/1989
EP	0343057	A1	11/1989
EP	0725468	A1	8/1996
EP	1041417		10/2000
EP	1041417	A2	10/2000
EP	1107031		6/2001
FR	2566997		1/1986
FR	2586822		3/1987
FR	2586822	A1	3/1987
FR	2739460		4/1997
FR	2739460	A1	4/1997
JP	61-093410		12/1986
JP	6-27882		4/1994
JP	9-236709		9/1997
JP	11-349230		12/1999
JP	2000258672		9/2000
JP	2003114339		1/2003
JP	2005-73365		3/2005
JP	2005-249858		9/2005
JP	2005234216		9/2005
JP	2006173669		6/2006
WO	PCT/IT/00055		11/1993
WO	9723791	A1	7/1997
WO	PCT/US03/05238		9/2003
WO	PCT/US03/05238	A2	9/2003
WO	PCT/US2006/014764		10/2006
WO	PCT/US2006/014764	A2	10/2006

OTHER PUBLICATIONS

Description of, 30 pages.

F3DF Modules, ADC Telecommunications, Inc. © 1995, “Individual 12-Pack Assemblies”, pp. 90.

Fiber Cable Management Products, Third Edition, ADC Telecommunications, Inc., © 1995, 1998.

Fiber Distribution Frame, Pre-Terminated Rear Load Connector Module, Installation Instructions, ADC Telecommunications, Inc., © 2000.

Fiber Main Distribution Frame (FMDF), Fiber Terminal Block, Installation Instructions, ADC Telecommunications, Inc., © 2001.

Fiber Panel Products—Cable Management Tray Panels, ADC Telecommunications, Inc., © 1994, 1996 “72 Fiber Distribution Module (FDM) with Intrafacility Fiber Cable”, pp. 56.

Fiber Panel Products, Second Edition, ADC Telecommunications, Inc., © 1994, 1996.

FL2000 Products—Preconfigured Panels, ADC Telecommunications, Inc., © 2000 “Rack or Cabinet Mount Termination Panel with Multifiber Cable”, pp. 13.

FL2000 Products, ADC Telecommunications, Inc., © 1994, 1996.

FL2000 Products, ADC Telecommunications, Inc., © 1994, 1996, “Rack Mount Panel with Intrafacility Fiber Cable”, pp. 16.

IFC Style Frame Modules, ADC Telecommunications, Inc., ©1995, “Connector Module Equipped with IFC”, pp. 27.

Next Generation Frame (NGF), Product Family Ordering Guide, ADC Telecommunications, Inc., ©1996, 1999, 2000, “Fiber Termination Blocks (FTB) Preterminated”, pp. 8.

Next Generation Frame (NGF), Product Family Ordering Guide, ADC Telecommunications, Inc., ©1996, 1999, 2000.

Next Generation Frames—Fiber Termination Blocks, ADC Telecommunication, Inc., © 1998, “Fiber Termination Blocks (FTB) Preterminated” pp. 6.

Value-Added Module System, ADC Telecommunications, Inc., ©1993, 1194, 1998, “12-Pack Module Assemblies”, pp. 30-31.

Corning Cable Systems, Wall-Mountable Connector Housings (WCH), at www.corningcablesystymes.com (undated).

ADC Telecommunications, Inc., Indoor Fiber Distribution Terminals—CPE, at www.adc.com/productsandservices (undated).

Multilink, Inc., 2007 Multilink Catalog, vol. 24, at p. 87-94.

Extended European Search Report issued in European Application No. 16171981.0, dated Oct. 13, 2016 (9 pgs).

Corning Cable Systems, Wall-Mounted Connector Housings (WCH), at www.corningcablesystems.com (undated).

* cited by examiner

FIG. 1




FIG. 2




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12





FIG. 13



FIBER OPTIC CABLE DISTRIBUTION BOX

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS REFERENCE TO RELATED APPLICATION

This application is a reissue continuation of U.S. application Ser. No. 13/091,851, filed Apr. 21, 2011; which is an application for reissue of U.S. Pat. No. 7,522,806. U.S. Pat. No. 7,522,806 is a continuation of U.S. patent application Ser. No. 11/728,785, filed Mar. 27, 2007, now U.S. Pat. No. 7,400,814, and entitled "Wall-Mountable Optical Fiber and Cable Management Apparatus". The '785 application claims priority under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application No. 60/880,169 filed Jan. 13, 2007, and entitled "Multidwelling Unit (MDU) Drop Box for Fiber Optic Cables".

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to drop or distribution boxes for managing fiber optic cables in the deployment of fiber optic networks at subscriber premises.

2. Discussion of the Known Art

The deployment of fiber optic networks at multi-dwelling units (MDUs) and other subscriber premises, requires the use of so-called cable drop or distribution boxes that are designed for mounting on walls or other structures at the premises. Current industry practice calls for the boxes to have a cable entry port at the left side of the box for receiving a fiber optic cable originating from the network provider, and one or more ports at the right side of the box through which a number of fibers associated with individual subscribers at the premises are routed to connect with fibers in the provider cable. See, for example, Corning Cable Systems, Wall-Mountable Connector Housings, at <www.corningcablesystems.com>, and ADC Telecommunications, Indoor Fiber Distribution Terminals—Customer Premises Equipment (CPE), at <www.adc.com/product-sandservices/>. See also, 2007 Multilink Catalog, vol. 24, at pages 87-94, disclosing a family of wall mountable fiber optic cable enclosures available from Multilink, Inc., of Elyria, Ohio, USA.

U.S. Pat. No. 4,976,510 (Dec. 11, 1990) discloses a wall communications outlet wherein cables may enter the outlet through panels inserted at sides of the outlet, or through an opening formed in a backplate of the outlet. Two sets of sidewalls are arranged concentric with the opening in the backplate so that spare lengths of optical fibers can be placed between the sidewalls, according to the patent. International Application No. PCT/IT92/00055 published Nov. 11, 1993, discloses a distribution device for termination of optical ribbon cables. The device has two circular grooves about which a ribbon, and fibers of the ribbon, are wound.

Installation of the known cable boxes by a single worker at a subscriber premises can be difficult and time consuming, however. Further, the known boxes are dimensioned to accommodate older types of fiber optic cables which can not tolerate bend diameters of less than three inches (76.2 mm)

without impairing cable performance. Accordingly, the currently available boxes are relatively large, and are not well-suited for widespread deployment of fiber optic networks at multi-dwelling units or other kinds of premises without significant expenditures of time and labor.

SUMMARY OF THE INVENTION

According to the invention, a fiber optic cable distribution box includes an interface compartment for interfacing a first set of fibers when routed inside the compartment, with a second set of fibers associated with a cable routed to the box. A drum region extends beneath the interface compartment and includes a cylindrical wall having an axis for supporting a length of a cable wound about the wall. The drum region is constructed so that the box can turn about the axis of the cylindrical wall when a cable is paid out from the drum region. The interface compartment and the drum region are arranged so that the first set of fibers inside the interface compartment, originate from an inside end portion of the cable wound about the wall of the drum region.

For a better understanding of the invention, reference is made to the following description taken in conjunction with the accompanying drawing and the appended claims.

BRIEF DESCRIPTION OF THE DRAWING

In the drawing:

FIG. 1 is a perspective view of a first embodiment of a fiber optic cable distribution box according to the invention;

FIG. 2 is a cross-sectional elevation view of the box of FIG. 1, showing a cable drum region and other internal components of the box;

FIG. 3 is a view of the box of FIG. 1 as seen from the top with a cover lid removed;

FIG. 4 is a view of the box of FIG. 1 as seen from below;

FIG. 5 is a perspective view of a second embodiment of a fiber optic cable distribution box according to the invention;

FIG. 6 is a cross-sectional elevation view of the box of FIG. 5;

FIG. 7 is a side view of the box of FIG. 5, showing the location of a cable strain relief device according to the invention;

FIG. 8 is an enlarged perspective view of the cable strain relief device;

FIG. 9 is a view of the strain relief device in FIG. 8 with a top cover removed;

FIG. 9A is also a view of the strain relief device without the top cover, and shows a fiber optic cable entering one end of the device and individual fibers of the cable exiting from an opposite end of the device;

FIG. 9B shows the strain relief device in place in the drum region of the box;

FIG. 10 is a perspective view of a third embodiment of a fiber optic cable distribution box according to the invention;

FIG. 11 is a view of the box of FIG. 10 as seen from below;

FIG. 12 is a perspective view of a connector parking area on a base of the box of FIG. 10; and

FIG. 13 is a schematic diagram showing a number of the inventive cable boxes deployed throughout a multidwelling unit (MDU) premises, according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 shows a first embodiment of a fiber optic cable drop or distribution box 10 according to the invention. The

box 10 may be constructed of sheet metal, and/or plastics materials such as, without limitation, ABS or polycarbonate. Moisture proof seals, gaskets and the like may also be provided on or within the box 10 in a known manner if the box will be mounted outdoors at a subscriber premises. The box 10 has a base 12 which, in the disclosed embodiment, is generally square and measures, e.g., about 6.25 inches (158.75 mm) long on each side with mounting holes 14 formed at each corner of the base.

The box 10 also has a drum region 20 that extends axially upward from a central portion of the base 12. The drum region 20 includes an outer cylindrical wall 22 the outside periphery of which is partially visible in FIG. 1. The outside diameter of the wall 22 is sufficient to allow a length of a fiber optic cable (not shown) to be wound on the drum wall 22 for storage or retention, with at least the minimum bend diameter specified for the cable. For example, when using cables of Allwave® Flex™ fiber available from OFS Fitel, the outside diameter of the drum wall 22 can be about 3.0 inches (76.2 mm) or less. An inside end portion of the cable enters a cable entry port in the drum wall while being supported over a substantially straight path by a strain relief device 24 fitted within the entry port. The device 24 is described further below in connection with FIGS. 7 to 9B, and it guides the end portion of the cable through the cylindrical wall 22 along a line tangential to the circumference of the wall at the location of the device 24.

The cable distribution box 10 also has an interface compartment 30 that is disposed atop the drum region 20, and which has a peripheral side wall 31. In the embodiment of FIG. 1, the compartment 30 has a removable cover lid 32 constructed and arranged to permit an installer to access the interior of the compartment 30 from outside, and a connector guard or cover 34 that is hinged to the lid at 35. As explained below, the interface compartment 30 is dimensioned and formed to allow a first set of optical fibers that enter the compartment 30 and originate either from a cable wound over the drum region 20, or from a cable that enters a port in the compartment wall 31 (see FIGS. 2 and 3), to connect with a second set of optical fibers from another cable which fibers terminate in connectors 36 seen beneath the cover 34 in FIG. 1. A number of flat fingers or tabs 38 are formed to project outward from lower side edges of the compartment wall 31, and are parallel to the base 12. The tabs 38 and the base 12 together serve to confine a length of cable wound about the drum wall 22, in the region between the base and the interface compartment 30.

FIG. 2 is a cross sectional view in elevation of the box 10 in FIG. 1, and FIG. 3 is a view of the box 10 as seen from the top with the cover lid 32 removed. The interface compartment 30 features a connector panel 40 that is supported to occupy a cut out region 41 in the compartment sidewall 31. A number of optical connector adapters 42 are mounted to extend through corresponding openings in the panel 40, and the adapters 42 operate to couple the fiber optic connectors 36 at the external side of the panel 40, with corresponding connectors 44 at the internal side of the panel. Preferably, the panel 40 is mounted in the sidewall 31 so that it can be easily removed and exchanged with another panel of the same dimensions but in which adapters of a different type are mounted. For example, the panel 40 may be slid in or out of vertical channels 43 formed at both ends of the sidewall cut out region 41. A desired panel 40 may then be selected from among a number of different panels having adapters 42 which accommodate, for example, type LC, SC, FC, ST, MPO, or type MPX connectors, depending on the type of cable connectors used at a given deployment.

As mentioned, optical fibers routed into the interface compartment 30 may originate from the inside end portion of a cable wound over the drum region 20 and which passes through the drum wall 22 via the strain relief device 24. In such an application, the fibers are routed through an annular fiber routing region 46 that extends between the outer cylindrical wall 22, and an inner cylindrical wall 48 of the drum region which wall 48 is formed radially inward of the outer wall 22. The strain relief device 24 and the dimensions of the annular fiber routing region 46, are such that individual optical fibers will not be subject to a bend diameter less than that specified for the fibers before entering the interface compartment 30 and terminating in the connectors 44. For example, when using cables of Allwave® Flex™ fiber available from OFS Fitel, the inner wall 48 may have an outside diameter as small as 0.7874 inches (20 mm), and the mean diameter of the fiber routing region 46 may only be about 2.0 inches (50.8 mm).

The sidewall 31 of the interface compartment 30 also has a cable entry or pass through port 50 (FIGS. 2 & 3) in a rear section of the wall 31 for receiving an outside fiber optic cable or cable assembly (not shown) whose fibers are to be coupled with those fibers terminated by the connectors 36. Alternatively, the cable entry port 50 may be provided in the form of a large opening through a portion of an alternate connector panel 40 (not shown). In such applications, the fibers of the cable entering the rear port 50 may be routed directly to corresponding ones of the connectors 44 with little, if any, bending whatsoever. Moreover, the use of multifiber connectors such as type MPO in the connector panel 40 enables the box 10 to act as an aggregation box. That is, multiple cables originating from other like boxes at different levels of a multi-dwelling unit (MDU) may enter the rear port 50 of the interface compartment 30, to connect via the MPO connectors with a single cable routed to the box from an alternate location, e.g., the basement of the MDU. See FIG. 13 and related text below. If not used, the rear cable entry port 50 is preferably kept closed by a plug 52.

FIG. 4 is a bottom view of the cable box 10 of FIG. 1. A cylindrical tube 60 is formed with a central axial passage 62. The tube 60 extends axially between a top end of the tube 60 that fits through a clearance opening in the cover lid 32 to lie flush with the lid's top surface as shown in FIG. 1, and a bottom end of the tube where the tube passage 62 opens beneath the base 12 as seen in FIG. 4. The axis of the tube passage 62 coincides with the axis of the outer cylindrical wall 22 of the drum region 20. In the disclosed embodiment, the tube 60 extends above and below the center of a wall 63 that closes an upper axial end of the inner cylindrical wall 48, as seen in FIG. 2.

The diameter of the central passage 62 in the tube 60 is preferably sufficient to allow a long narrow tool such as a screwdriver shaft, bolt or other payoff mandrel, to be inserted through the passage from above or below the box 10 so that the tool will act as a spindle about which the box 10 can turn freely. This construction allows a single worker easily to pay out a cable wound on the drum region 20, as may be necessary for a network deployment at a MDU. For example, while holding the handle of an inserted screwdriver in one hand, the worker can use his or her other hand to pull and unwind a desired length of the cable from the drum region 20 while the box 10 is free to turn about the screwdriver shaft.

FIGS. 5 to 7 show a second embodiment of a cable distribution box 200 according to the invention. Compo-

5

nents of the box 200 that are identical or similar to those of the box 10 of FIGS. 1 to 4, have corresponding reference numerals increased by 200.

The box 200 has a single piece cover lid 232 with an integrated hinge 235 for a connector guard or cover 234. Further, a side wall 231 of an interface compartment 230 has a continuous circular disk flange 204 that extends radially outward beneath the compartment 230, parallel to a base 212 of the box. The flange 204 and the base 212 together serve to confine a length of fiber optic cable wound on the outer cylindrical wall 222, within the region between the flange 204 and the base 212. As with the box 10 of FIGS. 1 to 4, an inside end portion of the cable is guided by a strain relief device 224 to enter an annular fiber routing region 246 inside the box 200, over a substantially straight path tangential to the circumference of the wall 222 at the location of the device 224.

Also, as seen in FIG. 6, the base 212 of the box 200 may be formed as a separate piece that is fastened to the bottom of the drum region 220 by, e.g., screws or other fasteners that are formed to engage collars 206 fixed at the bottom of the annular fiber routing region 246.

FIG. 8 is an enlarged, perspective view of the strain relief device 224 which corresponds to the strain relief device 24 provided in the box 10 in FIG. 1. As seen in FIG. 9, the strain relief device 224 is comprised of an arcuately shaped device body 208 with a generally U-shaped cross section having an outer side wall 224a, an inner side wall 224b, a base wall 224c, and a cover 209 that fits atop and extends between the side walls 224a, 224b of the device.

Further, as shown in FIG. 9A, the outer side wall 224a has an opening 226 at one end of the device 224 for receiving the inner end portion of, e.g., a flat ribbon fiber optic cable 260 wound on the outer cylindrical wall 222 of the drum region 220. An opening 228 at the opposite end of the device 224 allows individual fibers of the cable to exit from the device and to enter the fiber routing region 246 of the box 200, preferably after each fiber is protected with, for example, a commercially available 900 μm sleeve.

The cable 260 and its individual fibers are guided over a substantially straight path between the device openings 226, 228, with the aid of a pair of parallel fingers or guides 211 that project upward from the base wall 224c of the device 224 as seen in FIGS. 9 and 9A. After outer jacketing is stripped away from the end portion of the cable 260, lengths of an arimid or Kevlar[®] yarn that surrounds the cable fibers and serves as a reinforcing or strength material for the cable, are wrapped about and secured to the guides 211 with an epoxy or other suitable adhesive. Commercially available protective sleeves (e.g., 900 μm) are placed over each of the individual cable fibers, and the sleeved fibers are guided out of the device opening 228. The device cover 209 is fixed to the body 208 via a suitable adhesive, and the assembled cable strain relief device 224 is fixed securely within a cable entry port 225 defined between the outer cylindrical wall 222 and the inner cylindrical wall 248 of the drum region 220, as shown in FIG. 9B.

Accordingly, the inside end portion of the cable 260 and its individual fibers pass tangentially with respect to the outer cylindrical wall 222 through the cable entry port 225 in the wall, and into the annular fiber routing region 246 of the box 200. Because the yarn surrounding the fibers is anchored to the guides 211 of the strain relief device 224, any force applied externally to the cable 260 when the cable is being wound on or off the outer cylindrical wall 222 of the drum region, will be transferred to the wall 222 in which the device 224 is fixed rather than to the fibers themselves.

6

FIGS. 10 to 12 show a third embodiment of a cable distribution box 300 according to the invention. Components of the box 300 that are identical or similar to those of the box 10 of FIGS. 1 to 4, have corresponding reference numerals increased by 300. The box 300 features an integral splice compartment 308 in its base 312, a connector parking area 313, and a number of security latch holes 315.

Splice Compartment 308

Typical MDU cable distribution box installations have single fiber breakouts that egress from the box, wherein each breakout is associated with a corresponding living unit of the premises where the box is installed. Single fiber cables from each living unit are often routed to a box without a terminating connector. The bare ends of these cables can be terminated at the box in various ways. For example, single ended fiber pigtailed can be spliced within the box so that splice sleeves are housed in a common space. This requires a chamber or compartment to house the splice in order to prevent damage and to manage fiber slack. Alternatives may include mechanical splicing of the pigtailed, which would require a similar chamber or housing. The individual single fiber cables may also be terminated directly with a field installable connector, thus obviating the need for a splice chamber.

The box 300 has an integrated splice chamber or compartment 308 attached or formed underneath the base 312, including a splice tray 309 mounted inside the base. The splice tray 309 may be fixed within the box 300, or affixed directly to a wall. In either case, the box 300 may be installed over the splice compartment 308. Pigtailed or terminated ends can then enter or exit a lower section of the compartment through corresponding clearance notches 311 that are cut in a side wall of the base 312.

Connector Parking Area 313

The connector parking area or block 313 allows terminated fiber ends to be stored while not in use. The block 313 is constructed and dimensioned to receive and secure a selected one of a number of different commercially available connector parking strips 307 (e.g., type SC) in the block 313. This feature enables the future use of alternate connector types without having to replace the box 300, but at the same time allows installers to forego parking

Latch Holes 315

Several latch or security holes 315 may be formed through corresponding feet on the hinged cover lid 332. The latch holes 315 allow the end user to utilize a number of safety lockout methods. For example, one hole 315 can be used with a standard plunger type latching mechanism simply to keep the lid closed. Other holes 315 can be used to receive wire ties, lockout tags, or other security locks.

FIG. 13 illustrates an example of a fiber optic network deployment at a multi-dwelling unit 400. A number of the inventive distribution boxes, for example, the box 10 of FIGS. 1 to 4, are mounted at corresponding locations in the MDU 400, for example, above a drop ceiling on each floor 414 of the MDU. Optical fibers 416 corresponding to network subscribers on a given floor 414 are terminated in the connectors 36 which, in turn, are connected to the adapters 42 on the external side of the box panel 40.

Each of the subscriber fibers 416 is connected with a corresponding fiber in a cable 418 associated with the box 10

in the ceiling of the subscriber's floor. The cable 418 may be wound initially about the drum region 20 of the box 10, to be partially or fully unwound later for routing to another box 10 that serves as an "aggregation" box which is located, e.g., between a basement 420 and a roof 422 of the MDU 400. The fibers of the cable 418 are terminated in the connectors 44 which, in turn, are connected to the adapters 42 on the internal side of the box connector panel 40.

At the aggregation box 10, each one of the cables 418 containing subscriber fibers from each floor of the MDU 400, enters the aggregation box through its rear pass through port 50 or a faceplate port. As mentioned earlier, the fibers of each cable 418 may be routed inside the box with little if any bending to connect via a multi-fiber connector 44 with a corresponding adapter 42 on the internal side of the box panel 40. A main fiber optic cable 424 serving all subscribers in the MDU 400, is routed between a cable entry box 426 in the basement 420, and the aggregation box 10 in which the main cable fibers connect to the adapters 42 on the external side of the box panel 40 via multifiber connectors 36. A network provider cable 430 is routed to the entry box 426 from outside the MDU 400, and fibers of the cable 430 are connected to corresponding subscriber fibers of the cable 424 inside the entry box 426.

The various embodiments disclosed herein incorporate the following important features in a fiber optic cable distribution box.

1. Reduced physical dimensions for use with newer types of fiber optic cable such as Allwave® Flex™ available from OFS Fitel and which have superior bending performance.

2. An axial drum region that provides for external cable storage and keeps internal fiber routing within safe bending limits.

3. A central through tube that facilitates pay-off of cable wound externally on the drum region, with the use of a common tool such as a screwdriver.

While the foregoing represents preferred embodiments of the invention, it will be understood by those skilled in the art that various modifications and changes may be made without departing from the spirit and scope of the invention, and that the invention includes all such modifications and changes as come within the scope of the following claims.

We claim:

[1. A fiber optic cable distribution box, comprising:
 an interface compartment constructed and arranged for interfacing a first set of fibers when routed inside the compartment, with a second set of fibers associated with a fiber optic cable that is routed to the box;
 a drum region extending beneath the interface compartment, wherein the drum region includes a first cylindrical wall having an axis, the wall is dimensioned to support a length of a first fiber optic cable wound about the wall, and the drum region is constructed and arranged so that the distribution box can turn about the axis of the cylindrical wall when a cable is paid out from the drum region; and
 the interface compartment and the drum region are constructed and arranged so that the first set of fibers inside the interface compartment, originate from an inside end portion of the cable wound about the first cylindrical wall of the drum region.]

[2. A cable distribution box according to claim 1, including a tube arranged to extend coaxially through the drum region, and the tube has a central passage through which an outside shaft or spindle is insertable.]

[3. A cable distribution box according to claim 1, wherein a first cable entry port is formed in the first cylindrical wall of the drum region for receiving the inside end portion of the first fiber optic cable.]

[4. A cable distribution box according to claim 1, wherein the drum region includes a second cylindrical wall arranged radially inward and coaxially with the first cylindrical wall, and an annular fiber routing region is defined between the first and the second walls.]

[5. A cable distribution box according to claim 3, including a strain relief device arranged at the first cable entry port for guiding the inside end portion of the first fiber optic cable through the first cylindrical wall over a path tangential to the circumference of the wall.]

[6. A cable distribution box according to claim 5, wherein the strain relief device is constructed and arranged to transfer a pull force applied externally to the first fiber optic cable, to the first cylindrical wall of the drum region when the cable is wound on or off the drum region.]

[7. A cable distribution box according to claim 5, wherein the strain relief device includes one or more guides for securing a strength material beneath an outer jacket of the cable.]

[8. A cable distribution box according to claim 1, wherein the interface compartment includes a connector panel, and a number of connector adapters mounted in the panel for coupling fiber optic connectors at an externally facing side of the panel, with corresponding fiber optic connectors at an internally facing side of the panel.]

[9. A cable distribution box according to claim 8, wherein the interface compartment is constructed and arranged to support the connector panel so that a first connector panel can be removed and exchanged with a second connector panel having connector adapters of a type different from a type of adapters mounted in the first connector panel.]

[10. A cable distribution box according to claim 1, wherein the interface compartment has a side wall, and a number of fingers or tabs that project outward from the side wall for confining the length of the first fiber optic cable when wound about the first cylindrical wall of the drum region.]

[11. A cable distribution box according to claim 1, including a disk flange that extends radially outward beneath the interface compartment for confining the length of the first fiber optic cable when wound on the first cylindrical wall of the drum region.]

[12. A cable distribution box according to claim 1, wherein the interface compartment has a side wall, and the side wall has a second cable entry port for receiving a fiber optic cable or cable assembly having a third set of fibers to be coupled via the connector panel with the second set of fibers of the second fiber optic cable routed to the box.]

[13. A cable distribution box according to claim 8, wherein one or more of the adapters mounted in the connector panel of the interface compartment are constructed and arranged to couple multi-fiber type connectors with one another.]

[14. A cable distribution box according to claim 1, including a length of the first fiber optic cable wound about the first cylindrical wall of the drum region, and a fiber optic connector for terminating an outside end of the cable.]

[15. A cable distribution box according to claim 14, wherein the fiber optic connector at the outside end of the cable is a multi-fiber type of connector.]

16. A method for installing a fiber optic cable distribution device at an installation location, the fiber optic cable distribution device including a housing defining an interface

compartment, the fiber optic cable distribution device also including a fiber optic connector adapter having first and second ports, at least the first port being accessible from inside the interface compartment, the fiber optic cable distribution device further including a drum coupled to the housing and a fiber optic cable coiled about the drum, the drum being located outside the interface compartment, the fiber optic cable including a plurality of optical fibers, at least one of the optical fibers being terminated by a fiber optic connector that is inserted within the first port of the fiber optic connector adapter, the method comprising:

paying out the fiber optic cable from the drum by rotating the fiber optic cable distribution device about an axis of rotation, wherein the housing, the drum, the fiber optic adapter and the fiber optic connector are rotated together about the axis of rotation as the fiber optic cable is paid out from the drum; and

installing the fiber optic cable distribution device at the installation location, wherein the drum remains coupled to the housing during and after installation of the fiber optic cable distribution device.

17. The method of claim 16, wherein the installation location is a wall.

18. The method of claim 16, wherein in the installation location is a wall of a multi-dwelling unit.

19. The method of claim 16, wherein an outer end of the fiber optic cable is terminated by a multi-fiber connector, and wherein the method further comprises plugging the multi-fiber connector into an adapter at an aggregation box.

20. The method of claim 19, wherein the fiber optic cable distribution device and the aggregation box are on different floors of a building.

21. The method of claim 20, wherein the fiber optic cable of the fiber optic cable distribution device is a first fiber optic cable, wherein the first fiber optic cable is connected to a second fiber optic cable at the aggregation box, and wherein the second fiber optic cable is routed to a cable entry box provided at a different floor of the building from the floors at which the aggregation box and the fiber optic cable distribution device are mounted.

22. The method of claim 21, wherein the building is a multi-dwelling unit.

23. A fiber optic cable distribution device comprising: an enclosure defining an interface compartment, the interface compartment having an interior region, the enclosure having a front side and a back side, the front side having a front cover that can be opened to access the interior region of the interface compartment;

a cable storage drum coupled to the back side of the enclosure, the cable storage drum being located outside the interior region of the interface compartment, the cable storage drum including a cable storage region;

a first fiber optic cable coiled about the drum in a direction extending from an inside of the cable storage region toward an outside of the cable storage region, wherein at least a first set of optical fibers of the first fiber optic cable extend from the inside of the cable storage region into the interface compartment through the back wall of the enclosure; and

the cable distribution device defining an axis of rotation about which the enclosure and the drum rotate together in unison as the first fiber optic cable is paid off from the drum.

24. The fiber optic cable distribution device of claim 23, further comprising a plurality of fiber optic adapters carried

by the enclosure, the fiber optic adapters including first ports that receive fiber optic connectors associated with the first set of optical fibers.

25. The fiber optic cable distribution device of claim 24, wherein at least the first set of fibers extend from directly the inside of the cable storage region into the interface compartment.

26. The cable distribution device of claim 23, wherein at least the first set of fibers extend from the inside of the cable storage region into the interface compartment without any intermediate coiling of the first set of fibers.

27. A fiber optic cable distribution device comprising: an enclosure defining an interface compartment, the interface compartment having an interior region;

a cable storage drum coupled to the enclosure, the cable storage drum being located outside the interior region of the interface compartment, the cable storage drum including a cable storage region;

a first fiber optic cable coiled about the drum in a direction extending from an inside of the cable storage region toward an outside of the cable storage region, wherein at least a first set of optical fibers of the first fiber optic cable extend from the inside of the cable storage region directly into the interface compartment; and

the cable distribution device defining an axis of rotation about which the enclosure and the drum rotate together in unison as the first fiber optic cable is paid off from the drum.

28. The fiber optic cable distribution device of claim 27, further comprising a plurality of fiber optic adapters carried by the enclosure, the fiber optic adapters including first ports that receive fiber optic connectors associated with the first set of optical fibers.

29. A fiber optic cable distribution device comprising: an enclosure defining an interface compartment, the interface compartment having an interior region;

a cable storage drum coupled to the enclosure, the cable storage drum being located outside the interior region of the interface compartment, the cable storage drum including a cable storage region;

a first fiber optic cable coiled about the drum in a direction extending from an inside of the cable storage region toward an outside of the cable storage region, wherein at least a first set of optical fibers of the first fiber optic cable extend from the inside of the cable storage region into the interface compartment without any intermediate coiling of the first set of optical fibers; and

the cable distribution device defining an axis of rotation about which the enclosure and the drum rotate together in unison as the first fiber optic cable is paid off from the drum.

30. The fiber optic cable distribution device of claim 29, further comprising a plurality of fiber optic adapters carried by the enclosure, the fiber optic adapters including first ports that receive fiber optic connectors associated with the first set of optical fibers.

31. A fiber optic cable distribution device comprising: an enclosure defining an interface compartment, the interface compartment having an interior region;

a cable storage drum associated with the enclosure, the cable storage drum including a cable storage region surrounding a drum wall, the drum wall having at least one outer cross-dimension of 3 inches or less;

a first fiber optic cable coiled within the cable storage region about the drum, the fiber optic cable including optical fibers;

a plurality of fiber optic adapters positioned at least partially within the interior region of the interface compartment, the fiber optic adapters including first ports that receive fiber optic connectors associated with the optical fibers of the first fiber optic cable; and the cable distribution device defining an axis of rotation about which the fiber optic adapters and the drum rotate together in unison as the first fiber optic cable is paid off from the drum.

32. A fiber optic cable distribution device comprising: an enclosure defining an interface compartment, the interface compartment having an interior region;

a cable storage drum coupled to the enclosure, the cable storage drum being located outside the interior region of the interface compartment, the cable storage drum including a cable storage region;

a first fiber optic cable coiled about the drum, wherein at least a first set of optical fibers of the first fiber optic cable extend into the interface compartment;

a plurality of fiber optic adapters carried by the enclosure, the fiber optic adapters including first ports that receive fiber optic connectors associated with the first set of optical fibers, the fiber optic adapters also including second ports accessible from outside the interior region of the enclosure; and

the cable distribution device defining an axis of rotation about which the enclosure, the fiber optic adapters and the drum rotate together in unison as the first fiber optic cable is paid off from the drum.

33. A fiber distribution system comprising:

A) a fiber optic cable distribution device including:

an enclosure defining an interface compartment, the interface compartment having an interior region;

a cable storage drum associated with the enclosure, the cable storage drum including a cable storage region surrounding a drum wall;

a first fiber optic cable coiled within the cable storage region about the drum, the fiber optic cable including at least one set of optical fibers;

a plurality of first fiber optic adapters positioned at least partially within the interior region of the interface compartment, the first fiber optic adapters including first ports;

single fiber optical connectors associated with the set of optical fibers of the first fiber optic cable at a first end of the first fiber optic cable, the single fiber optical connectors being inserted within the first ports of the first fiber optic adapters; and

a multi-fiber fiber optic connector associated with the set of optical fibers of the first fiber optic cable at a second end of the first fiber optic cable;

the fiber optic cable distribution device defining an axis of rotation about which the first fiber optic adapters and the drum rotate together in unison as the first fiber optic cable is paid off from the drum; and

B) an aggregation box including at least a second fiber optic adapter that receives the multi-fiber fiber optic connector of the fiber distribution device.

34. The fiber distribution system of claim 33, wherein the second fiber optic adapter connects the first fiber optic cable to a second fiber optic cable having a plurality of optical fibers, the second fiber optic cable being routed from the aggregation box to a cable entry box.

35. The fiber distribution system of claim 33, wherein the cable distribution device and the aggregation box are mounted on different floors of a building.

36. The fiber distribution system of claim 35, wherein the building is a multi-dwelling unit.

37. The fiber distribution system of claim 34, wherein the cable distribution device, the cable entry box and the aggregation box are mounted on different floors of a building.

38. The fiber distribution system of claim 37, wherein the cable entry box is in a basement of the building.

39. The fiber distribution system of claim 38, wherein the building is a multi-dwelling unit.

40. A method for installing a fiber optic distribution system, the fiber optic distribution system including a fiber optic cable distribution device including an enclosure defining an interface compartment, the interface compartment having an interior region; a cable storage drum associated

with the enclosure, the cable storage drum including a cable storage region surrounding a drum wall; a first fiber optic

cable coiled within the cable storage region about the drum, the fiber optic cable including at least one set of optical

fibers; a plurality of first fiber optic adapters positioned at

least partially within the interior region of the interface

compartment, the first fiber optic adapters including first

ports; single fiber optical connectors associated with the set

of optical fibers of the first fiber optic cable at a first end of

the first fiber optic cable, the single fiber optical connectors

being inserted within the first ports of the first fiber optic

adapters; and a multi-fiber fiber optic connector associated

with the set of optical fibers of the first fiber optic cable at

a second end of the first fiber optic cable, the fiber optic

cable distribution device defining an axis of rotation about

which the first fiber optic adapters and the drum rotate

together in unison as the first fiber optic cable is paid off

from the drum, the method comprising:

paying in the first fiber optic cable off of the drum by

rotating the drum and the first fiber optic adapters in

unison with one another about the axis of rotation of

the fiber optic cable distribution device;

installing the fiber optic cable distribution device at an

installation location, wherein the enclosure, the drum

and the first fiber optic adapters are installed as a unit

at the installation location;

routing the second end of the first fiber optic cable to an

aggregation box at a location remote from the installation

location of the fiber optic cable distribution

device; and

inserting the multi-fiber fiber optic connector at the

second end of the first fiber optic cable into a second

fiber optic adapter provided at the aggregation box.

41. The method of claim 40, wherein the second fiber optic

adapter connects the first fiber optic cable to a second fiber

optic cable having a plurality of optical fibers, the second

fiber optic cable being routed from the aggregation box to a

cable entry box.

42. The method of claim 40, wherein the cable distribution

device and the aggregation box are mounted on different

floors of a building.

43. The method of claim 42, wherein the building is a

multi-dwelling unit.

44. The method of claim 41, wherein the cable distribution

device, the cable entry box and the aggregation box are

mounted on different floors of a building.

45. The method of claim 44, wherein the cable entry box

is in a basement of the building.

46. *The method of claim 45, wherein the building is a multi-dwelling unit.*

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE46,255 E
APPLICATION NO. : 14/492970
DATED : December 27, 2016
INVENTOR(S) : Hendrickson et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

Column 9, Line 37, Claim 21: "second finer optic cable" should read --second fiber optic cable--

Column 12, Line 38, Claim 40: "paying in the first fiber optic cable" should read --paying the first fiber optic cable--

Signed and Sealed this
Second Day of January, 2018



Joseph Matal
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*