

US00RE46283E

(19) United States

(12) Reissued Patent

de Beaubien

(10) Patent Number:

US RE46,283 E

(45) Date of Reissued Patent:

Jan. 24, 2017

(54) ANTIBIOTIC DELIVERY SYSTEM AND METHOD FOR TREATING AN INFECTED SYNOVIAL JOINT DURING RE-IMPLANTATION OF AN ORTHOPEDIC PROSTHESIS

(71) Applicant: Joint Purification Systems LLC,

Solana Beach, CA (US)

(72) Inventor: Brian C. de Beaubien, Bay City, MI

(US)

(73) Assignee: Joint Purification Systems LLC,

Solana Beach, CA (US)

(21) Appl. No.: 14/817,103

(22) Filed: Aug. 3, 2015

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: 8,900,322
Issued: Dec. 2, 2014
Appl. No.: 13/759,239
Filed: Feb. 5, 2013

U.S. Applications:

(62) Division of application No. 12/712,748, filed on Feb. 25, 2010, now Pat. No. 8,454,706.

(Continued)

(51)	Int. Cl.
	A61F 2/3

A61F 2/30(2006.01)A61F 2/38(2006.01)A61M 37/00(2006.01)A61F 2/36(2006.01)A61F 2/48(2006.01)

(Continued)

(52) **U.S. Cl.**

 (2013.01); A61F 2002/30672 (2013.01); A61F 2002/30677 (2013.01); A61F 2002/368 (2013.01); A61F 2002/3621 (2013.01); A61F 2002/3694 (2013.01); A61F 2002/4685 (2013.01);

(Continued)

(58)	Field	of	Classification	Search
------	-------	----	----------------	--------

CPC	1F 2/4241
USPC	632/23.39
See application file for complete search hi	story.

(56) References Cited

U.S. PATENT DOCUMENTS

, ,		Malcom et al	
4,399,814 A * 8/1983 Pratt et al			

OTHER PUBLICATIONS


Co-pending U.S. Appl. No. 14/841,529, filed Aug. 31, 2015. (Continued)

Primary Examiner — Beverly M Flanagan (74) Attorney, Agent, or Firm — Wilson, Sonsini, Goodrich & Rosati

(57) ABSTRACT


An antibiotic delivery system including an intramedullary stem that is adapted to be removably mounted into a medullary canal of a bone. The stem includes a body having an inlet adapted to be in fluid communication with a source of liquid-borne antibiotic and a plurality of outlets disposed along the stem. A channel extends between the inlet and the plurality of outlets for delivering a fluid-borne antibiotic from the inlet to the plurality of outlets so as to distribute the antibiotic along the medullary canal in a controlled fashion. A method of treating an infected joint during a two-stage re-implantation of an orthopedic implant is also disclosed.


22 Claims, 9 Drawing Sheets





US RE46,283 E Page 2


	Related ILS.	Application Data	7,048,743 B2	5/2006	Miller et al.
			7,112,205 B2		Carrison
(60)	Provisional application	n No. 61/208,540, filed on Feb.	7,141,053 B2	11/2006	Rosa et al.
` ′	25, 2009.		7,211,113 B2	5/2007	Zelener et al.
	20, 2005.		7,250,055 B1	* 7/2007	Vanderwalle 606/92
(51)	Int Cl		7,255,713 B2	* 8/2007	Malek 623/17.12
(51)	Int. Cl.		7,427,296 B2	* 9/2008	Evans 623/20.14
	A61F 2/46	(2006.01)	7,429,346 B2	* 9/2008	Ensign et al 264/264
	A61F 2/42	(2006.01)	7,534,240 B1	* 5/2009	Johnson A61F 13/00063
(52)	U.S. Cl.				602/43
(32)		02 (2012 01) 4617 2250/0060	7,572,293 B2	* 8/2009	Rhodes et al 623/20.32
		82 (2013.01); A61F 2250/0068	7,601,157 B2		
	(2013.01); A61F 2310/00077 (2013.01)	7,601,176 B2	10/2009	Soffiati et al.
			7,862,619 B2		
(56)	Referer	nces Cited	7,914,585 B2		Keller 623/23.26
			8,038,682 B2		McGill et al.
	U.S. PATENT	DOCUMENTS	8,097,039 B2		Evans 623/20.14
			8,135,466 B2		Fuller et al
	4,488,549 A * 12/1984	Lee et al 606/94	8,388,881 B2		Giori
	4,711,233 A * 12/1987	Brown 606/81	8,454,706 B2		de Beaubien 623/23.39
	4,888,024 A * 12/1989	Powlan 623/23.19	8,652,216 B2		Chen et al 623/23.72
	4,892,550 A * 1/1990	Huebsch 623/23.19	8,673,018 B2 8,685,432 B2		Walls 623/23.57 Evans et al 424/426
		Skripitz et al 623/23.19	8,721,520 B2		Caira et al 600/30
		Frey et al 623/23.54	8,900,322 B2		
	•	Duncan et al 623/23.2	8,900,323 B2		
		Hack et al 623/23.19			Shah 623/22.13
	5,156,606 A 10/1992				Mitsugi et al.
	5,290,291 A 3/1994		2003/0187513 A1		Durniak 623/22.12
		Carbone	2004/0036189 A1		Ensign et al 264/40.1
	,	Klaue et al 623/23.19 Brinker 606/62			Grimes 623/22.12
		Willert et al 606/94	2004/0225360 A1	* 11/2004	Malone 623/17.11
		Coutts 606/62	2005/0021084 A1	* 1/2005	Lu et al 606/218
		Morrey et al 604/26	2005/0187555 A1	* 8/2005	Biedermann et al 606/72
	·	Ray et al 606/86 A	2006/0014120 A1		Sapian 433/173
	5,571,204 A 11/1996		2006/0093646 A1		Cima et al 424/425
	, , ,	Wilcox A61B 17/60	2006/0121083 A1		Mor 424/426
	, ,	604/175			Rhodes et al.
	5,702,446 A 12/1997	Schenck et al.			Royer 424/468
	, ,	Burke	2009/0069899 A1		Klein
	5,741,265 A 4/1998	Chan	2010/0042167 A1		Nebosky et al 606/315
	5,755,811 A 5/1998	Tanamal et al.	2010/0042213 A1 2010/0042214 A1		Nebosky et al 623/16.11 Nebosky et al 623/16.11
		Reiley et al.	2010/0042214 A1 2010/0042215 A1		Stalcup et al 623/16.11
		Richelsoph et al.	2010/0042213 A1 2010/0217401 A1		de Beaubien 623/20.34
	•	Shaffner 128/898	2010/0217 101 711 2010/0292803 A1		Giori 623/20.14
		Reiley et al.			Guelcher et al 424/549
		Ray et al 623/17.16	2013/0041472 A1		Rabiner et al 623/18.11
		Smith et al 425/318	2013/0209522 A1		Brooks et al 424/400
	, ,	Keller Dailary et al	2013/0211334 A1	* 8/2013	de Beaubien 604/175
	6,235,043 B1 5/2001	•	2013/0211369 A1	* 8/2013	de Beaubien 604/500
	6,248,110 B1 6/2001 6,361,731 B1 * 3/2002	Smith et al 264/271.1			
		Ley et al 424/400		THER DI	BLICATIONS
		Reiley et al.	O		DLICATIONS
	· · · · · · · · · · · · · · · · · · ·	Stalcup et al.	Notice of allowance	e dated Fe	b. 22, 2013 for U.S. Appl. No.
		Compton et al 419/2	12/712,748.	c dated i c	70. 22, 2013 for C.S. Appl. 140.
		Hyde, Jr.	·	a datad Ar	o 27 2014 for H.S. Appl. No.
	,	Margulies et al.	13/759,239.	c dated At	ig. 27, 2014 for U.S. Appl. No.
	6,740,090 B1* 5/2004	Cragg et al 606/79	,	e dated Au	ig. 27, 2014 for U.S. Appl. No.
	•	Grimes 623/22.12	13/759,253.	o aaroa At	-5. 27, 2011 101 0.5. Appl. 110.
		Miller et al.	,	Feb 22 201	12 for U.S. Appl. No. 12/712,748.
	·	Cragg et al 606/86 R		•	14 for U.S. Appl. No. 12/712,748.
	·	Mitsugi et al.		ŕ	14 for U.S. Appl. No. 13/759,239.
	,	Ferree 623/17.11		,	14 for U.S. Appl. No. 13/739,239.
		Durniak 606/92	omee action dated a	5 c p. 10, 20.	12 101 0.5. Appl. 110. 12//12,/40.
	6,981,981 B2 1/2006 6,989,033 B1 * 1/2006	-	* cited by examin	O.P.	
	D 909 H 3 3 K 1 7 H 7 H 10 M	- SCHOOL	· CHEO BY EVAMIN	C I	
































ANTIBIOTIC DELIVERY SYSTEM AND METHOD FOR TREATING AN INFECTED SYNOVIAL JOINT DURING RE-IMPLANTATION OF AN ORTHOPEDIC PROSTHESIS

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions 10 made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED APPLICATION(S)

This application is a divisional of U.S. patent application entitled "Antibiotic Delivery System and Method for Treating an Infected Synovial Joint During Re-implantation of an Orthopedic Prosthesis," having U.S. Ser. No. 12/712,748, and filed Feb. 25, 2010, which claims the benefit of U.S. provisional patent application entitled "Joint Purification type Systems," having Ser. No. 61/208,540, and filed on Feb. 25, 2009.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates, generally, to an antibiotic 30 delivery system and, more specifically, to such a system and method for treating an infected synovial joint and adjacent medullary canals as a means of eliminating infection during a two-stage re-implantation of an orthopedic prosthesis.

2. Description of the Related Art

A total joint replacement (TJR) is a medical procedure that involves the repair and replacement of joints, such as hips and knees. In these cases, the bones at the hip or knee joints are prepared in receive orthopedic implants that mimic the structure of the joint that is replaced. For example, a total 40 knee replacement is representatively shown at 10 in FIG. 1. The total knee replacement 10 includes tibial 12 and femoral 14 components that imitate the structure and function of the natural knee joint. The tibial component 12 is operatively mounted to the tibia bone 16 and the femoral component 14 is operatively mounted to the femoral bone (not shown). Similarly, a total hip replacement includes a femoral component that terminates in a neck having a hemispherical ball that mimics the upper terminal portion of the natural femoral bone.

Currently, there are approximately one million total joint replacement (TJR) surgeries involving either hips or knees performed annually in the United States. Obviously, more TJR surgeries are performed throughout the world. However, the demand for TJR surgery is expected to soar in the 55 future. Doctor-diagnosed arthritis is expected to increase 40% from 2005 to 2030. According to the 2003 National Institute of Health Census Panel Report on total knee replacement, only 9% to 13% of TJR candidates have been willing to undergo the procedure. As patients become more 60 aware of their options, as well as the success of TJR, demand may reach even higher levels.

Baby boomers will start reaching the age of 65 years in 2011. Also, over the past decade, the prevalence of TJR has increased not only in older patients (those who are 65 years 65 or older) but also in younger patients (those less than 65 years old). Premium implant technology such as hard-on-

2

hard bearings and hip resurfacing have been introduced to address the increased activity and longevity of younger patients. The demand for primary total hip and total knee replacements on patients younger than 65 years old was projected to exceed 50% of joint replacement recipients by 2011 and 2013, respectively. Demand for primary total hip replacement is expected to grow 174% and for total knee replacement by 673% by the year 2030. Data collected from the U.S. Nationwide Implant Sample (NIS) between 1993 and 2005 has also been evaluated. This data indicates that by 2030 future demand of primary and revision TJR procedures (where an older implant is replaced with a new one) will be significant. For example, primary total knee replacements are projected to be 4,580,000. The need to revise and 15 re-implant total knee replacements is projected to be 269, 000. Primary total hip replacements are projected to be 975,000. And the need to revise and re-implant total hip replacements is projected to be 103,000 per year. These estimated projections total 6,000,000 TJR surgeries annu-

In relatively rare cases, however, infection is a devastating complication of TJR surgeries. The rate of infection in these types of surgeries ranges between 0.5% and 1.5%. Unless an infection is properly diagnosed within the first two to four weeks following the original surgery (which is uncommon), the infected implant must be removed in combination with an extensive debridement of the surrounding joint tissue and bone. According to the Center for Disease Control, there are currently approximately 12,000 infected TJR cases annually in the United States. Obviously, this number increases when the entire worldwide scope of TJR surgeries is considered. At 1% infection rate, and assuming the projections noted above are generally accurate, there will be 60,000 instances of infected total joints annually in the future.

Over the past two decades, the standard of care for treatment of an infected TJR in the United States has included a two-stage re-implantation process. In the first stage of this process, the infected components are surgically exposed by incision. Scar tissue is then de-bulked as well as other soft tissue releases, and sometimes an osteotomy. This stage also includes the removal of all prosthetic components and foreign material including, for example, acrylic bone cement. After extensive joint debridement of infected soft tissue and bone, a spacer block consisting of heavily dosed antibiotic bone cement is placed temporarily into the joint space. The purpose of the antibiotic bone cement is to sterilize the joint environment and to serve as an antibiotic delivery system. Additionally, the bone cement acts as a spacer to preserve joint space and maintains ligament length. 50 However, the antibiotic released by the bone cement is uncontrolled and is quite costly to use. For example, a typical knee spacer may require three bags of acrylic bone cement, twelve vials of an antibiotic such as Tobramycin (1.2 g) at a cost of \$800 per vial, and six vials of an antibiotic such as Vancomycin (1 g) at \$17 per vial. This quickly adds up to about \$11,000 in material alone. In addition, more operating room time is necessary to prepare this spacer material. This increases the cost of the operation.

Under the current standard of care, following the removal of the infected implant and the insertion of the antibiotic bone cement spacer, the patient must generally wait between six and, more typically, twelve weeks before the second stage of the procedure can be performed. This period of time is necessary so that the medical professionals can be confident that the infection has been successfully eradicated. Only after the infectious condition has been eliminated, may the second stage proceed. During the second stage, the new

prosthesis is re-implanted. The success rate with this two-stage re-implantation process is typically around 90%.

In other countries, such as throughout Europe, a one-stage re-implantation process has been popular. This involves the removal of the infected implant, as noted above, followed by aggressive debridement and then immediate re-implantation of a new implant. The success rate for this technique has typically been in the 70%-85% range. However, this technique has not gained popularity to any degree in the United States. The one-state implantation process is generally 10 reserved for patients who are considered to be too feeble or sick to undergo the traditional two-stage re-implantation process.

Both the one-stage and two-stage surgical re-implantation protocols have their disadvantages. For example, and as 15 noted above, the two-stage re-implantation process requires six to twelve weeks between operations. This is a very difficult time for the patient as they do not have a functional joint in place and it is typically very painful to mobilize or ambulate with an antibiotic spacer. Articulating spacers are 20 somewhat better than static spacers, but are also more expensive as well as more difficult and time-consuming to place during the original stage one procedure. From a health care standpoint, the two-stage procedure also requires two separate hospitalizations. Finally, from a surgeon's stand- 25 point, a significant amount of scar tissue develops during the time span between the two procedures. This makes for a very difficult and time-consuming second stage operation. In addition, the two-stage re-implantation process involves not one, but two, very difficult surgical procedures. The estimated cost of removing the infected original implant, eliminating the infection, extended hospitalization, nursing home care or home health care during the period between the first and second operations, a well as re-implanting a new prosthesis is currently roughly \$100,000 per case. This is a 35 tremendous overall burden on the universal health care system and, in the United States alone, reaches approximately \$1.2 billion per year. This statistic does not begin to measure losses in patient economic productivity, quality of life, as well as pain and suffering. Moreover, this statistic 40 does not reflect the costs associated with the projected increase in TJR operations in the future as noted above.

On the other hand, a one-stage re-implantation surgical protocol requires absolute identification of the infecting organism in order to proceed. Unfortunately, it is very 45 difficult to achieve this absolute identification in the current health care systems. In addition, a one-stage re-implantation protocol requires the use of fully-cemented components. Fully-cemented components are typically not favored by U.S. surgeons for revision surgery. Fully-cemented components typically require very high amount of antibiotic. This often is as high as 10% by weight. For example, 4 g of antibiotic are required for a 40 g bag of cement. The increase of antibiotic by weight raises concerns regarding structural weakening of the cement.

Moreover, and in both one-stage and two-stage re-implantation surgical protocols, the release of the antibiotic from the bone cement is completely uncontrolled. This is a significant disadvantage of both protocols and essentially acts to lengthen the time between the first and the second 60 surgical procedures in the two-stage re-implantation process.

Thus, there remains a need in the art for a device that may be employed during re-implantation surgical procedures that may be used to deliver antibiotic in a controlled and titrat- 65 able manner directly into the synovial joint cavity and adjoining medullary canals as a means of eliminating the

4

infection following the removal of a previous orthopedic implant. In addition, there remains a need in the art for such a device that can provide stability and maintain the physical dimensions of joint space and normal soft tissue envelope in any joint undergoing the re-implantation of an orthopedic implant. In addition, there remains a need in the art for such a device that may be easily employed, facilitates the reduction in the time needed to conduct the stage one re-implantation surgery and that reduces the overall time between the first and second stages of a two-stage re-implantation surgical protocol.

SUMMARY OF THE INVENTION

The present invention is directed toward an antibiotic delivery system including a device and method for treating an synovial joint and adjacent tissues, including bone, during the re-implantation of an orthopedic prosthesis. The antibiotic delivery device includes an intramedullary stem adapted to be removably mounted in a medullary canal of a bone. The stem includes an inlet adapted to be in fluid communication with a source of fluid-borne antibiotic, a plurality of outlets disposed along the stem and a channel extending between the inlet and the plurality of outlets for delivering fluid-borne antibiotic from the inlet to the plurality of outlets so as to distribute the antibiotic along the medullary canal in a controlled fashion.

In addition, the present invention is also directed toward a method of treating an infected synovial joint and adjacent tissue during a two-stage re-implantation of an orthopedic implant. The method includes the steps of removing the infected implant mounted to the medullary canal of a bone and debriding the medullary canal. An intramedullary stem is then installed into the medullary canal. The stem includes an inlet, a plurality of outlets, and a channel extending between the inlet and the plurality of outlets. In addition, the method includes the step of providing a source of fluid-borne antibiotic to the inlet of the intramedullary stem so as to distribute the antibiotic through the channel and outlets into the medullary canal in a controlled fashion.

The antibiotic delivery system of the present invention, as well as the method overcomes the disadvantages in the related art in providing a modular, implantable device designed for short-term use of approximately one week as a part of an abbreviated two-stage re-implantation technique for treatment of septic TJR of either the knee or the hip. The present invention provides structural rigidity to the joint and the limb during the period of time between the removal of an infected prosthesis and the re-insertion of a new prosthesis. This allows the patient to be mobile, while minimizing pain. The present invention also eliminates the need for an external stabilizing device, such as a cast, between the first and second stages of the re-implantation process. In addition, the system maintains joint space while acting as a 55 temporary spacer. As explained in greater detail below, the implant assembly maintains the proper length of vital structures, including ligaments, muscles, tendons, neurovascular structures, etc., until the new prosthesis can be implanted. The system and method of the present invention act to deliver a controlled titratable antibiotic dosed directly into the synovial joint cavity and the medullary canals via an infusion system thereby attaining and maintaining much higher local joint space and tissue levels of antibiotics than can be obtained by current antibiotic spacers (static or articulating) as well as perental/I.V.-administered antibiotics. In addition, the system and method of the present invention act to irrigate and cleanse the synovial joint and

medullary canals through a novel concept utilizing intermittent pulsatile levage. In this way, the present invention facilitates the reduction in the time between the first and second stages of a two-stage re-implantation process from six to twelve weeks under the current standard of care to approximately one week.

Other objects, features, and advantages of the present invention will be readily appreciated as the same becomes better understood while reading the subsequent description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view illustrating a surgically exposed total joint replacement of a knee;

FIG. 2 is a perspective view of the antibiotic delivery system of the present invention;

FIG. 3 is an elevational view of one embodiment of an intramedullary stem of the present invention;

FIG. 4 is an end view of the distal end of the intramedullary stem illustrated in FIG. 3;

FIG. 4A is a cross-sectional view taken along lines 4A-4A of FIG. 3;

FIG. 5 is an end view of the proximal end of the 25 intramedullary stem illustrated in FIG. 3;

FIG. 6 is an elevational view of another embodiment of the intramedullary stem of the present invention;

FIG. 7 is a top plan view of the implant assembly of the present invention;

FIG. 8 is a perspective view of the implant assembly of the present invention;

FIG. 9 is a top plan view of the implant assembly of the present invention showing the anterior half of the coupler removed;

FIG. 10 is a partial enlarged exploded view of the coupler and tibial and femoral intramedullary stems;

FIG. 11 is a side exploded view of the implant assembly of the present invention illustrating the assembly of the anterior half to the posterior half of the coupler;

FIG. 12 is a partial cross-sectional plan view illustrating the implant assembly mounted in a human knee joint;

FIG. 13 is a partial cross-sectional side view of an alternate embodiment of the femoral intramedullary stem of the present invention; and

FIG. 14 is an exploded partial cross-sectional side view of the femoral intramedullary stem illustrated in FIG. 13.

DETAILED DESCRIPTION OF THE INVENTION

One embodiment of an antibiotic delivery system according to the present invention is generally indicated at 110 in FIG. 2, where like numerals are used to designate like structure throughout the figures. The antibiotic delivery 55 system 110 includes an implant assembly, generally indicated at 112, a pump, generally indicated at 114, and a source of fluid-borne antibiotic, generally indicated at 116. The antibiotic implant assembly 112 forms one component of the antibiotic delivery system 110. One of the assembly's basic 60 components includes an intramedullary stem. One embodiment of the intramedullary stem is generally indicated at 118 in FIGS. 3-5. In the case of a total knee replacements the assembly 112 includes a tibial intramedullary stem, generally indicated at 250, and a femoral intramedullary stem, 65 generally indicated at 350 in FIGS. 7-12. Each of these components will be described in greater detail below.

6

More specifically, various features of the intramedullary stem will now be described with respect to the embodiment designated 118 in FIGS. 3-5. Those having ordinary skill in the art will appreciate that the features described with respect to the embodiment illustrated in these figures are also generally present in the other embodiments described below. The intramedullary stem 118 is adapted to be removably mounted into a medullary canal of a bone. The stem 118 includes an inlet 120 that is adapted to be in fluid communication with the source of fluid-borne antibiotic 116 and other appropriate fluids, as will be described in greater detail below. In addition, the stem 118 includes a plurality of outlets 122 that are disposed along the stem 118. In addition, a channel 124 (FIG. 4A) extends between the inlet 120 and the plurality of outlets 122 for delivering fluid-borne antibiotic from the inlet 120 to the plurality of outlets 122 so as to distribute the antibiotic along the medullary canal in a controlled fashion.

In the embodiment illustrated in FIGS. 3-5, the antibiotic implant assembly 112 and the intramedullary stem 118, per se, is particularly adapted for use in connection with the first stage of a re-implantation of a total knee replacement where the first implant has become infected. As explained in greater detail below and as illustrated in FIG. 12, the antibiotic implant assembly 112 of the present invention may also be particularly adapted for use in the first stage of a total hip replacement where the first implant has become infected. Each of these assemblies will be described in greater detail below.

Referring now specifically to the device as it is employed in connection with a re-implantation of a knee, the intramedullary stem 118 illustrated in FIGS. 3-5 defines a body, generally indicated at 126, having a longitudinal axis A. The body 126 includes a plurality of fins 128 extending therealong and disposed in spaced angular relationship with respect to each other. In the embodiment illustrated herein, the body 126 includes four fins 128 spaced at 90° relative to one another. The fins 128 are adapted to engage the medullary canal in a removably stable fashion. However, those having ordinary skill in the art will appreciate that the body 126 of the intramedullary stem 118 may have any number of fins 128 disposed at any angle relative to each other and have any convenient shape. Alternatively, the body 126 may or may not employ fins of the type illustrated herein.

In one embodiment, the body **126** of the intramedullary stem 118 includes an intra-articular end 130 having base plate 132 disposed at the proximal end 134 of the body 126 and a distal end 136 disposed remote from the proximal end 50 134. The body 126 may also have a tapered cross-section disposed along the longitudinal axis A from the proximal end 134 to the distal end 136 of the body 126 of the intramedullary stem 118. In one embodiment, the fins 128 may have a 2° taper, gradually narrowing from the proximal end 134 to the distal end 136 of the stem. The distal end 136 may terminate in a bullet-like tip 140. However, those having ordinary skill in the art will appreciate that the exact shape of the distal end 136 can vary and that the taper may differ from approximately 2°. Moreover, the shape and size of the distal end 136 as well as the extent of the taper may be a function of the various sizes of the stems that may be employed with patients of different sizes. Those having ordinary skill in the art will appreciate from the description herein that the body 126 of the intramedullary stem 118, and its distal end 136, can have any shape that facilitates stability of the implant in the medullary canal and that further facilitates the insertion and removal of the device, and that

assists in providing a press-fit of the stem in the medullary canal, so as to provide axial and rotational stability.

The inlet 120 is located in the base plate 132 of the body **126.** Similarly, the plurality of cadets **122** are disposed between the outer surface 142 of at least one of the plurality 5 of fins 128. In the embodiment illustrated herein, the outlets **122** are disposed along the longitudinal length of the body 126 of the intramedullary stem 118 in the valleys 144 defined between adjacent fins. The size and shape of the plurality of outlets 122 may vary depending on a number of 10 factors including, but not limited to, the type of antibiotic fluid and other agents that pass through the stem 118, the desired pressure and flow of the fluid-borne antibiotic, as well as various patient factors, such as age. In addition and in one embodiment, the plurality of outlets **122** may vary in 15 size, ranging from a smaller size at the proximal end of the stem, to a larger size at the distal tip, in order to compensate for a loss in pressure. In any event, those having ordinary skill in the art will appreciate that the size, location along the body 126 of the intramedullary stem 118, as well as the 20 number of the outlets 122 may vary pursuant to a number of factors, all of which are within the scope of the present invention.

In the embodiment illustrated in FIGS. 3-5, the outer surface of the plurality of adjacent fins 128 is generally 25 planer or smooth. However, another embodiment of the intramedullary system is, generally indicated at **218** in FIG. **6**, where like numerals increased by 100 are used to designate like structure with respect to the stem illustrated in FIGS. 3-5. In this embodiment, the fins 228 may include 30 longitudinally extending irregular outer surfaces 242 that are adapted to engage the medullary canal and that allow the flow of fluid-borne antibiotic between the fins 228 and the medullary canal. More specifically, in the embodiment illustrated here, the irregular surfaces **242** may define a plurality 35 of serrations that present peaks 243 and valleys 245, whereby the peaks 243 are in contact with the medullary canal and the valleys 245 present openings through which fluid-borne antibiotic may pass. However, those having ordinary skill in the art will appreciate that the outer surface 40 142, 242 of the fins 128, 228 may take any geometric shape that is calculated to advance the dispersion fluid-borne antibiotic throughout the medullary canal.

As noted above, the intramedullary stem of the present invention forms a part of an antibiotic implant assembly 112. One such assembly is illustrated in FIGS. 7-12 and is particularly adapted for use in the first stage of a two-stage knee re-implantation process. To this end, the present invention may include a tibial intramedullary stem, generally indicated at **250**. The tibial intramedullary stem **250** is 50 adapted to be removably mounted within the medullary canal of a tibia bone. Similarly, the assembly of the present invention may also include a femoral intramedullary 350 stem that is adapted to be removably mounted within the medullary canal of the femoral bone. Like reference numer- 55 als increased by 100 with respect to the intramedullary stem 118 described in FIGS. 3-5, are used to describe like structure for the tibial intramedullary stem 250. Similarly, like reference numerals increased by 200 with respect to the intramedullary stem 118 described in FIGS. 3-5 are used to 60 designate like structure with respect to the femoral intramedullary stem **350** illustrated in FIGS. **7-12**. It should also be noted that the intramedullary stems 250, 350 employ the structure of the outer surface 242 of the fins 228 illustrated in FIG. **6**.

Like the intramedullary stem illustrated in FIGS. 3-5, the tibial intramedullary stem 250 includes a body 226 with an

8

intra-articular end 230 having a base plate 232 disposed at the proximal end 234 of the body and the distal end 236 disposed remote from the proximal end 234 (FIGS. 8-10). An inlet 220 (FIG. 9-11) is formed in the base plate 232 to the body 226 and a plurality of outlets 222 are disposed along the longitudinal length of the body 226. A channel 224 (FIG. 10) extends between the inlet 220 and the plurality of outlets 222 for purposes of distributing fluid-borne antibiotic and other fluid-borne agents into the medullary canal of a tibia bone. Similarly, like the intramedullary stem 118 illustrated in FIGS. 3-5, the femoral intramedullary stem 350 includes a body 326 with an intra-articular end 330 having a base plate 332 disposed at the proximal end 334 of the body 326 and the distal end 336 disposed remote from the proximal end 334. An inlet 320 is formed in the base plate 332 to the body 326 and a plurality of outlets 322 are disposed along the longitudinal length of the body 326. A channel 324 (FIG. 10) extends between the inlet 320 and the plurality of outlets 322 for purposes of distributing fluidborne antibiotic and other fluids into the medullary canal of a femur bone. From the description herein taken along with the drawings, and with the exception of the irregular outer surface of the fins, those having ordinary skill in the art will appreciate that both the tibial and femoral intramedullary stems 250, 350 include all of the features and structural components as the intramedullary stem 118 illustrated in FIGS. **3-5** and described above.

As noted above and illustrated in FIG. 2, the implant assembly also includes a coupler, generally indicated at 410. The coupler 410 operatively interconnects the tibial intramedullary stem 250 and the femoral intramedullary stem 350 and acts to stabilize the joint defined therebetween. The system also includes a pump, generally indicated at 114. The pump 114 is disposed in fluid communication with the source of fluid-borne antibiotic 116 as well as other fluidborne agents and the intramedullary stems 118, 250, 350 via the coupler 410. The pump 114 acts to control the delivery of titratable fluid-borne antibiotic from the source of fluidborne antibiotic to the inlet 120, 220, 320 of the intramedullary stems 118, 250, 350 via a conduit 412 or any suitable tubing or other delivery means. In addition, the system may also include a source of cleansing/debriding fluid. In this case, the pump 114 further acts to control the delivery of cleansing fluid in intermittent pulsatile levage fashion to the inlet 120, 220, 320 of the intramedullary stems, as will be described in greater detail below. In addition, the pump 114 may also be employed to remove excessive fluid from the medullary canal and surrounding tissue prior to the reintroduction of fresh antibiotic, irrigating fluid, or other fluidborne agents into the stem, the synovial joint, and the surrounding medullary canal to facilitate the cleaning of the treated tissue. From the preceding description, those having ordinary skill in the art will appreciate that the present invention facilitates the control of a the frequency, duration, dosage and pressure of the fluid-borne antibiotic and any other agents administered by the system in a sustainable and renewable manner. Thus, the present invention facilitates a far better sterile wound bed in a much shorter time than is achievable using the current standard of care.

As best shown in FIG. 10, the coupler 410 includes an inlet 414 that is adapted for fluid communication with the source of fluid-borne antibiotic 116 as well as at least one outlet 416, 418 in fluid communication with the inlets 220, 320 to the tibial 250 and femoral 350 intramedullary stems.

The coupler 410 acts to distribute the fluid-borne antibiotic from the source of fluid-home antibiotic 116 to the plurality of outlets 222, 322 through the channels 224, 324 of the

tibial and femoral intramedullary stems 230, 350. Likewise, those having ordinary skill in the art will appreciate that the coupler 410 also functions to distribute cleansing fluid and any other fluid-borne agents for any purpose directly into the synovial joint and into the medullary canal. In addition, as 5 best shown in FIGS. 7, 8 and 12, the coupler 410 acts to hold the tibial and femoral intramedullary stems 250, 350 rigidly together in longitudinal alignment.

More specifically and as best shown in FIGS. 9-11, the coupler 410 may be divided into anterior 420 and posterior 10 422 half sections that are operatively mounted together in sealed fashion using fasteners 424 of any suitable type. Together, the anterior 420 and posterior 422 halves of the coupler 410 define a reservoir 426 disposed in fluid communication with the inlet 414 to the coupler 410 as well as 15 the inlets 220, 320 to the tibial and femoral intramedullary stems 250, 350. The coupler 410 includes a tibial stem receptacle, generally indicated at 428, that is adapted to receive the proximal end 234 of the body 226 of the tibial intramedullary stem 250 so as to establish fluid communi- 20 cation between the reservoir 426 and the inlet 220 to the intramedullary stem 250. Referring specifically to FIG. 10, the tibial stem receptacle 428 includes an inlet port 430, a nipple section 432, and a transverse portion 434 extending between the inlet port 430 and the nipple 432. The intra- 25 articular end 234 of the intramedullary stem 250 is adapted to be snugly received in the inlet port 430. Similarly, the base plate 232 is adapted to be received in the transverse portion 434 and the inlet 220 is adapted to be received in the nipple portion 432 of the tibial stem receptacle 428. A gasket 30 (not shown) may be employed at the inlet 220 to the intramedullary stem 250 to provide a proper seal between the inlet 220 of the stem 250 and the nipple portion 432 of the tibial stem receptacle 428.

tacle, generally indicated at 438, adapted to receive the proximal end 334 of the body 326 of the femoral intramedullary stem 350 so as to establish fluid communication between the reservoir 426 and the inlet 320 to the femoral intramedullary stem 350. The femoral stem receptacle 438 40 includes an inlet port 440, a nipple section 442, and a transverse portion 444 extending between the inlet port 440 and the nipple section 442. The intra-articular end 334 of the femoral interamedullary stem 350 is adapted to be snugly received in the inlet port 440. Similarly, the base plate 332 45 is adapted to be received in the transverse portion **444** and the inlet 320 is adapted to be received in the nipple section 442 of the femoral stem receptacle 438. A gasket may also be employed at the inlet 320 to the femoral intramedullary stem **350** to establish an appropriate seal at this juncture with 50 the nipple section 442 and the stem receptacle 438. Other seals may be employed to make the coupler fluid-tight as necessary. Thus, the stem receptacles 428, 438 in both ends of the coupler 410 are complimentarily shaped with respect to the intra-articular ends 234, 334 of the tibial and femoral 55 intramedullary stems 250, 350 such that the stems are rigidly held in place by the coupler 410 when it is fully assembled, as illustrated, for example, in FIGS. 7, 8, 9 and 12.

As noted above, the tibial and femoral intramedullary stems 250, 350 may have a 2° taper gradually narrowing 60 from the proximal to the distal end of the device. The tibial and femoral stems 250, 350 may have increasing lengths with each increase in stem diameter. Both the tibial and femoral stems 250, 350 may increase in diameter by 1 mm increments from approximately 14 mm to 22 mm at the base 65 of the stems. This allows for a "press fit" in the intramedullary canal for axial and rotational stability. The intra-

articular ends 234, 334 of the stems may all have one standard diameter and may be solid circumferentially for an axial length, such as 25 mm so that any proximal end of any stem will fit into any coupler. In any event, those having ordinary skill in the art will appreciate that the dimensions set forth herein are merely representative and are not meant to limit the size and shape of the components of the system.

Another embodiment of the antibiotic implant assembly of the present invention is illustrated in FIGS. 14-15. In this embodiment, the antibiotic delivery device is particularly adapted for use in stage one of a two-stage re-implantation process for a hip prosthesis. Like reference numerals increased by 400 with respect to the intramedullary stem 118 described in FIGS. 3-5, are used to designate like structure for the femoral intramedullary stem **518**. Like the embodiment illustrated in FIGS. 3-12, the antibiotic delivery device includes a femoral intramedullary stem **518** that is adapted to be removably mounted into a medullary canal of a femur bone. In this case, the stem **518** is mounted at the upper portion of the femur bone. The femoral intramedullary stem 518 includes a body 526 having a proximate end 534 and a distal end 536 disposed remote from the proximate end 534. The stem **518** also includes a femoral head **560** and neck **562** extending from the proximal end 534 of the body 526 and between the body 526 and the femoral head 560. In one embodiment, the femoral head 560 and neck 562 are modular components. In its operative mode, the femoral neck **562** will be supplied in various incremental lengths, such as 5 mm increments, so that the space between the body **526** and the femoral head 560 may be customized for any given patient to maintain soft tissue tension of the hip in order to achieve stability and resistance to dislocation of the femoral head **560** and the socket. The femoral intramedullary stem **518** also includes at least one inlet **520**, **521**. However, in the Similarly, the coupler 410 includes a femoral stem recep- 35 embodiment illustrated herein, the body 526 includes more than one inlet, as will be described in greater detail below. In addition, the body **526** and the femoral head **560** have a plurality of outlets **522** and a channel **524** extending between the at least one inlet 520, 521 and the plurality of outlets 522 for delivering fluid-borne antibiotic from the inlet 520, 521 to the plurality of outlets **522** so as to distribute the antibiotic along the intramedullary canal as well as the socket of the hip joint in a controlled fashion. In this context, those having ordinary skill in the art will appreciate that the body **526** of the femoral intramedullary stem 518 illustrated in FIGS. 14-15 may have any of the other structure and features described with respect to the stems illustrated in FIGS. 3-12 above.

> In the embodiment illustrated in FIGS. 14-15, the body 526 includes an inlet 520 and the femoral bead includes a separate inlet 521. Both inlets 520, 521 are in fluid communication with the source of fluid-borne antibiotic **116**. The femoral head 560 has a hemispherical shape that is complimentarily received in the socket of the hip joint. In its operative mode, the femoral bead 560 will have a range of sizes in, for example, 1 mm increments, so that the head may be customized to fit a particular socket in any given patient. In this way, and as explained in greater detail below, the fluid-borne antibiotic is distributed directly through both the medullary canal of the femur bone as well as at the socket of the hip joint in a controlled fashion. Like the embodiment disclosed above, the flow of the antibiotic may be controlled by the pump 114. Similarly, the pump 114 may be used to disperse any type of fluid, such as cleansing fluid, in intermittent pulsatile levage fashion throughout the device.

> In its operative mode, the antibiotic implant assembly, its individual intramedullary stems, as well as the entire system

is employed in the first stage of what is an abbreviated two-stage re-implantation process. This process begins with the removal of the infected implants and aggressive debridement of the medullary canal. As noted above, in a traditional two-stage re-implantation, an antibiotic cement spacer 5 would be placed between the tibia and femur bones in a knee as well as the upper portion of the femur and hip socket, in connection with a re-implantation of a hip. The wound would then be closed and would heal completely in the next six to twelve weeks before the patient would return for the second stage. This extended period of time between the first and second stages is necessary, in part, because the antibiotic is distributed fern the cement using elusion principles and is essentially uncontrolled.

However, in the abbreviated two-stage re-implantation 15 employing the antibiotic delivery system of the present invention, the intramedullary stem 118, 218, 250, 350, 518 is mounted in the respective bone and provides direct antibiotic irrigation of the wound once the system is installed in both the tibia and femur (in the case of a knee 20 replacement) or in the upper portion of the femur and hip socket (in the case of a hip replacement). Moreover, as best show in FIG. 12, the coupler 410 in combination with the tibial and femoral intramedullary stems 250, 350 acts to stabilize the joint and provides the necessary spacing 25 between the tibia and femur bones. The wound may be covered with a polyurethane continuously connected porous sponge (for example, Granufoam manufactured by KCI). This porous sponge also occupies deep and superficial wound space. The incisional wound edges are then com- 30 pletely sewn over the negative pressure wound therapy sponge except for the area just large enough to allow a suction disk to be attached to the sponge. The open area of the incision is typically about 6 cm to 8 cm in length, however, those having ordinary skill in the art will appre- 35 ciate that the incision can have any suitable length. The location of the incision is proximal incision on the knee, and distal incision on the hip. An occlusive see-through dressing is then applied. This is incorporated directly over the antibiotic in flow tubing and the outgoing wound suction tubing.

The direct infusion of antibiotic, such as Vancomycin, into the infected joint cavity allows for a very high level of drug concentration to be delivered in a fast and titratable fashion. This is in contrast to solely relying on the traditional antibiotic cement spacer to release the antibiotic through 45 elusion principles alone, which is uncontrollable and typically starts out with most of the antibiotic released within the first few days, then gradually tapering off over the next weeks to months.

The present invention also takes advantage of concentra- 50 tion gradients. Over a typical 24-hour period, 4 g of Vancomposin could be delivered directly into the wound bed at the site of the infection at a concentration of approximately 13.3 mg per mm. In contrast, traditional IV antibiotic delivery systems, in which 1 g of antibiotic are given every 55 24 hours, will achieve a serum concentration level of around 10 μg to 20 μg per mm, and even less of a level in the actual joint space itself through diffusion. Those having ordinary skill in the art will appreciate that the practice among surgeons may vary and so different types of antibiotics in 60 different concentrations may be preferred by different surgeons under different circumstances. Nevertheless, in the example set forth above, there is a concentration difference of a 1,000 fold or more in what concentration the actual joint space itself is projected to see between the two techniques. 65 In addition, and using the traditional two-stage technique described in the background section of this application, there

12

is no way to control the overall amount or rate of antibiotic elusion from the cement spacer.

The intramedullary stems 118, 218, 250, 350, 518 of the present invention may be manufactured of any suitable material. However, one suitable material of note includes a copper alloy. Copper has recently been recognized by the U.S. Environmental Protection Agency as the first solid surface material to be registered under the Federal Insecticide, Fungicide and Rodentcide Act. According to the EPA registration, certain copper alloys continuously reduce bacterial contamination achieving approximately 99.9% reduction within two hours of exposure. In addition, copper alloys can also kill greater than 99.9% of bacteria within two hours of exposure. Moreover, certain copper alloys deliver continuous and ongoing antibacterial action, even alter repeated wear and re-contamination. Those having ordinary skill in the art will appreciate that many different types of copper alloys may be suitable for this purpose. However, in order for the alloys to have antibacterial properties, it is believed that they must contain at least 65% copper. As presently best understood, there are currently 48 cast alloys which are included in the Group II Copper Alloys which have between 85% and 95% copper. In any event, those having ordinary skill in the art will appreciate that the present invention is not limited to any specific copper alloy or any particular material.

Like the stems, in one preferred embodiment the coupler 410 may also be metallic and may be manufactured using a copper alloy. Multiple couplers may be available, each having a variable thickness and transverse dimension that act to separate the abutting ends of the stems by, for example 5 mm increments, to allow the distance between the tibial and femoral stems to be customized in order to allow proper distraction of the joint cavity (for example between 25 mm and 40 mm), until the desired tension on the ligaments could be obtained. As noted above, in addition to the pump delivering the antibiotic fluid, the system 110 may also employ a negative pressure wound therapy to remove antibiotic irrigation fluid and to aid in the eradication of infection through principles unique to that technology.

The antibiotic delivery system 110 and the associated implant 112 assembly of the present invention overcomes the disadvantages in the related art in providing a modular, implantable device designed for short-term use of approximately one week as a part of an abbreviated two-stage re-implantation technique for treatment of a septic (infected) TJR of either the knee or the hip. The present invention provides structural rigidity to the joint and the limb during the period of time between the removal of an infected prosthesis and the re-insertion of a new prosthesis. This allows the patient to be mobile, while minimizing pain. In addition, the implant assembly 112 maintains joint space while acting as a temporary spacer. This maintains proper length of vital structures, including ligaments, muscles, tendons, neurovascular structures, etc., until the new prosthesis can be implanted. The system **110** and the individual components thereof act to deliver a controlled and titratable antibiotic dosed directly into the synovial joint cavity and medullary canals via an infusion system. In addition, the system and its components act to irrigate and cleanse the medullary canals through a novel concept utilizing intermittent pulsatile levage.

The present invention has been described in an illustrative manner. It is to be understood that the terminology that has been used is intended to be in the nature of words of description rather than of limitation. Many modifications and variations of the present invention are possible in light

of the above teachings. Therefore, within the scope of the appended claims, the present invention may be practiced other than as specifically described. In addition, those having ordinary skill in the art will appreciate from the foregoing description, taken along with the drawings, that the term "system" as used in the claims may encompass individual components of the system, such as the intramedullary stems, the implant assembly for both a knee and hip, as well as the entire system, including the implant assembly, the pump, and the source of antibiotic fluid. Thus, the term "system" as it is used in the claims does not necessarily encompass all of the components of the system and, depending on the scope of the individual claims, may refer to merely a subcomponent of that system.

What is claimed is:

1. An antibiotic delivery system comprising:

- a femoral intramedullary stem adapted to be removably mounted into a medullary canal of a femur bone, said femoral intramedullary stem including a body having a proximate end and a distal end disposed remote from 20 said proximate end, said body including a plurality of fins extending therealong and disposed in spaced angular relationship with respect to each other so as to define valleys that provide fluid flow spaces disposed between adjacent fins, said fins adapted to engage said medul- 25 lary canal in a removably stable fashion, a femoral head and a neck extending from said proximal end of said body and between said body and said femoral head, said femoral intramedullary stem including at least one inlet, and a plurality of outlets disposed along said stem 30 and between an outer surface of one of said plurality of adjacent fins in said valleys and in fluid communication with said fluid flow spaces and a channel extending between said inlet and said plurality of outlets, said femoral head having a plurality of outlets and a channel 35 extending between said at least one inlet and said plurality of outlets for delivering fluid-borne antibiotics from said at least one inlet to said plurality of outlets so as to distribute said antibiotic along said intramedullary canal and the socket of a hip joint in a controlled 40 fashion.
- [2. An antibiotic delivery system as set forth in claim 1, wherein said body includes an inlet and said femoral head includes an inlet, both inlets being in fluid communication with a source of fluid-borne antibiotic.]
- [3. An antibiotic delivery system as set forth in claim 1, wherein said femoral head has a hemispherical shape so as to be complimentarily received in the socket of a hip joint.]
- 4. A method of treating an infected joint during a two-stage re-implantation of an orthopedic implant, said method 50 comprising the steps of:

removing [the] infected implants mounted to the medullary canal of a bone;

debriding the medullary canal; and

installing an intramedullary stem into the medullary canal 55 where the stem includes an inlet, a plurality of outlets and a channel extending between the inlet and the plurality of outlets, wherein installing the intramedullary stem includes installing a tibial intramedullary stem into the medullary canal of the tibia bone and 60 installing a femoral intramedullary stem into the medullary canal of a femur bone;

said *intramedullary* stem including a plurality of fins extending along a longitudinal axis of the *intramedullary* stem and disposed in spaced angular relationship 65 with respect to each other so as to define valleys that provide fluid flow spaces disposed between adjacent

14

fins and a plurality of outlets disposed along said intramedullary stem and between an outer surface of one of said plurality of adjacent fins in said valleys and in fluid communication with said fluid flow spaces providing a source of fluid-borne antibiotic to the inlet of the intramedullary stem so as to distribute the antibiotic into the medullary canal in a controlled fashion.

- 10 [5. A method of treating an infected orthopedic implant as set forth in claim 4, wherein said step of installing an intramedullary stem includes installing a tibial intramedullary stem into the medullary canal of the tibia bone and installing a femoral intramedullary stem into the medullary canal of a femur bone.]
 - 6. A method of treating an infected [orthopedic implant] *joint* as set forth in claim [5] 4, wherein the method further inludes [the step of] positioning a coupler between the tibial intramedullary stem and the femoral intramedullary stem so as to provide axial stability between the tibial and femoral intramedullary stems.
 - 7. A method of treating an infected [orthopedic implant] joint as set forth in claim 6, wherein the method further includes [the step of] establishing fluid communication between the coupler and the inlet of the tibial and femoral intramedullary stems and providing fluid communication between the coupler and [a] the source of fluid-borne antibiotic so as to distribute the antibiotic through the tibial and femoral intramedullary stems and along the medullary canals in a controlled fashion.
 - 8. A method of treating an infected area of bone comprising a first bone and a second bone, said method comprising: removing an infected intramedullary implant from the first bone;
 - disposing a first intramedullary implant in a medullary canal of the first bone, wherein the implant comprises an outer surface, an inlet, a plurality of outlets in fluid communication with the inlet, and a channel in fluid communication with the inlet and the plurality of outlets;
 - delivering a fluid from the plurality of outlets to the medullary canal of the first bone in a controlled fashion, wherein the plurality of outlets are disposed in one or more valley regions in the outer surface of the first intramedullary implant;

removing a second infected intramedullary implant from the second bone in the infected area;

- disposing a second intramedullary implant in a second medullary canal of the second bone, wherein the second implant comprises an outer surface, an inlet, a plurality of outlets in fluid communication with the inlet, and a channel in fluid communication with the inlet and the plurality of outlets; and
- delivering the fluid from the plurality of outlets to the second medullary canal of the second bone in a controlled fashion, wherein the plurality of outlets are disposed in one or more valley regions in the outer surface of the second intramedullary implant.
- 9. The method of claim 8, wherein the first bone comprises a femur or a tibia.
- 10. The method of claim 8, wherein disposing the first intramedullary implant in the medullary canal of the first bone comprises engaging a plurality of fins disposed on the first intramedullary implant with bone lining the intramedullary canal of the first bone.

11. The method of claim 8, wherein the first implant comprises a head coupled thereto, the head having a plurality of outlets fluidly coupled to the channel, the method further comprising:

disposing the head in a bone socket; and delivering the fluid from the plurality of outlets in the head to the bone socket in a controlled fashion.

- 12. The method of claim 8, wherein the head comprises a hemispherically shaped head.
- 13. The method of claim 8, wherein the fluid comprises an 10 antibiotic, an antibacterial, or an irrigation fluid.
- 14. The method of claim 8, further comprising applying negative pressure wound therapy to the infected area.
- 15. The method of claim 8, wherein removing the infected intramedullary implant from the first or the second bone 15 comprises removing a prosthetic joint from the first bone.
- 16. The method of claim 15, wherein the prosthetic joint comprises a prosthetic hip joint or a prosthetic knee joint.
- 17. The method of claim 8, further comprising coupling the first intramedullary implant to the second intramedul- 20 lary implant with a coupler.
- 18. A system for delivering fluid to an infected area of bone having a first bone, said system comprising:
 - a first intramedullary implant configured to be disposed in a medullary canal of the first bone, wherein the first 25 implant comprises an outer surface, an inlet, a plurality of outlets in fluid communication with the inlet, and a channel in fluid communication with the inlet and the plurality of outlets,
 - wherein the plurality of outlets are disposed in one or 30 more valley regions of the outer surface;
 - a source of fluid in fluid communication with the channel, wherein the fluid is delivered to the medullary canal via the plurality of outlets; and
 - a second intramedullary implant configured to be dis- 35 posed in a medullary canal of a second bone, wherein the second implant comprises an outer surface, an inlet, a plurality of outlets in fluid communication with

16

the inlet, and a channel in fluid communication with the inlet and the plurality of outlets,

wherein the plurality of outlets are disposed in one or more valley regions of the outer surface of the second intramedullary implant, and

wherein the source of fluid is in fluid communication with the channel of the second intramedullary implant, and wherein the fluid is delivered to the medullary canal of the second bone via the plurality of outlets of the second intramedullary implant.

19. The system of claim 18, wherein the first intramedullary implant comprises a femoral implant configured to be disposed in the medullary canal of a femur, or wherein the first intramedullary implant comprises a tibial implant configured to be disposed in the medullary canal of a tibia.

20. The system of claim 18, further comprising a coupler for coupling the first intramedullary implant to the second intramedullary implant.

- 21. The system of claim 18, wherein the first implant comprises a head coupled thereto, the head having a plurality of outlets fluidly coupled to the channel, wherein the head is configured to be disposed in a socket of a joint, and wherein the fluid is delivered to the socket in a controlled fashion via the plurality of outlets in the head.
- 22. The system of claim 21, wherein the head comprises a hemispherically shaped head.
- 23. The system of claim 18, wherein the fluid comprises an antibiotic, antibacterial, or an irrigation fluid.
- 24. The system of claim 18, further comprising a pump, wherein the pump pumps the fluid from the source of the fluid to the plurality of outlets.
- 25. The system of claim 18, further comprising a pump for applying negative pressure wound therapy to the infected area.
- 26. The system of claim 18, wherein the first intramedullary implant comprises a plurality of fins disposed thereon.

* * * *

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : RE46,283 E

APPLICATION NO. : 14/817103 DATED : January 24, 2017 INVENTOR(S) : de Beaubien

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification

Column 1, beginning at Line 15, replace the heading "CROSS-REFERENCE TO RELATED APPLICATION(S)" and the paragraph below the heading with the following:

Notice: More than one reissue application has been filed for the reissue of U.S. Patent No. 8,900,322. The reissue applications are U.S. Reissue Patent Application Serial No. 15/846,021, filed on December 18, 2017, which is a continuation reissue application of U.S. Reissue Patent Application Serial No. 15/336,472, filed on October 27, 2016, now U.S. Reissue Patent No. RE46,669 E, issued January 16, 2018, which is a continuation reissue application of U.S. Reissue Patent Application Serial No. 14/817,103 (the present application), filed on August 3, 2015, now U.S. Reissue Patent No. RE46,283 E, issued January 24, 2017.

CROSS-REFERENCE TO RELATED APPLICATION(S)

U.S. Patent Application Serial No. 13/759,239, filed February 5, 2013, now U.S. Patent No. 8,900,322, issued December 2, 2014, is a divisional application of U.S. Patent Application No. 12/712,748, filed February 25, 2010, now U.S. Patent No. 8,454,706, issued June 4, 2013, entitled "Antibiotic Delivery System and Method for Treating an Infected Synovial Joint During Re-implantation of an Orthopedic Prosthesis," which claims the benefit of U.S. Provisional Patent Application No. 61,208,540, filed February 25, 2009, now expired, entitled "Joint Purification Systems,".

Signed and Sealed this Twelfth Day of June, 2018

Andrei Iancu

Director of the United States Patent and Trademark Office