

US00RE46431E

(19) **United States**
(12) **Reissued Patent**
Jackson

(10) **Patent Number: US RE46,431 E**
(45) **Date of Reissued Patent: Jun. 13, 2017**

(54) **POLYAXIAL BONE ANCHOR WITH
HELICAL CAPTURE CONNECTION, INSERT
AND DUAL LOCKING ASSEMBLY**

(58) **Field of Classification Search**
None
See application file for complete search history.

(71) Applicant: **Roger P Jackson**, Prairie Village, KS
(US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventor: **Roger P Jackson**, Prairie Village, KS
(US)

154,864 A 9/1874 Harvey
791,548 A 6/1905 Fischer
(Continued)

(21) Appl. No.: **14/460,607**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Aug. 15, 2014**

DE 373809 4/1923
DE 3630863 3/1988
(Continued)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,967,850**
Issued: **Jun. 28, 2011**
Appl. No.: **12/290,244**
Filed: **Oct. 29, 2008**

OTHER PUBLICATIONS

Contour Spinal System Brochure, Ortho Development, no publish date.

(Continued)

U.S. Applications:

(63) Continuation-in-part of application No. 11/522,503, filed on Sep. 14, 2006, now Pat. No. 7,766,915, which is a continuation-in-part of application No. 11/024,543, filed on Dec. 20, 2004, now Pat. No. 7,204,838, said application No. 12/290,244 is a continuation-in-part of application No. 11/140,343, filed on May 27, 2005, now Pat. No. 7,776,067, and
(Continued)

Primary Examiner — Cary Wehner

(74) *Attorney, Agent, or Firm* — Polsinelli PC


(57) **ABSTRACT**

A medical implant assembly includes a polyaxial bone anchor having a shank, a receiver, a lower compression insert with surfaces for closely receiving an elongate connecting member and a dual closure structure that may include a single flange or helical flange. The dual closure structure independently engages the connecting member and the lower compression insert. A threaded capture connection of the bone anchor includes a shank upper surface exclusively engaging the lower compression insert and a retainer threadably attached to the shank and spaced from the upper surface, the retainer configured for polyaxial motion with respect to the receiver prior to locking.

(51) **Int. Cl.**
A61B 17/04 (2006.01)
A61B 17/70 (2006.01)
A61B 17/86 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 17/7032** (2013.01); **A61B 17/7037**
(2013.01); **A61B 17/86** (2013.01)

20 Claims, 15 Drawing Sheets



Related U.S. Application Data

a continuation-in-part of application No. 10/986,377, filed on Nov. 10, 2004, now Pat. No. 7,833,250, and a continuation-in-part of application No. 10/818,555, filed on Apr. 5, 2004, now Pat. No. 8,052,724, which is a continuation of application No. 10/464,633, filed on Jun. 18, 2003, now Pat. No. 6,716,214.

- (60) Provisional application No. 61/000,964, filed on Oct. 30, 2007, provisional application No. 60/722,300, filed on Sep. 30, 2005, provisional application No. 60/725,445, filed on Oct. 11, 2005, provisional application No. 60/728,912, filed on Oct. 21, 2005, provisional application No. 60/736,112, filed on Nov. 10, 2005, provisional application No. 60/832,644, filed on Jul. 21, 2006.

(56)

References Cited

U.S. PATENT DOCUMENTS

1,300,275 A	4/1919	Johnson	4,703,954 A	11/1987	Ortloff et al.
1,330,673 A	2/1920	Anderson	4,707,001 A	11/1987	Johnson
1,472,464 A	10/1923	Ellison	4,743,260 A	5/1988	Burton
2,083,092 A	6/1937	Richer	4,748,260 A	5/1988	Marlett
2,201,087 A	5/1940	Hallowell	4,759,672 A	7/1988	Nilsen et al.
2,239,352 A	4/1941	Cherry	4,763,644 A	8/1988	Webb
2,243,717 A	5/1941	Moreira	4,764,068 A	8/1988	Crispell
2,295,314 A	9/1942	Whitney	4,790,297 A	12/1988	Luque
2,346,346 A	4/1944	Anderson	4,805,602 A	2/1989	Puno et al.
2,362,999 A	11/1944	Elmer	4,815,453 A	3/1989	Cotrel
2,445,978 A	7/1948	Stellin	4,836,196 A	6/1989	Park et al.
2,531,892 A	11/1950	Reese	4,838,264 A	6/1989	Bremer et al.
2,532,815 A	12/1950	Kindsvatter et al.	4,850,775 A	7/1989	Lee et al.
2,537,029 A	1/1951	Cambern	4,877,020 A	10/1989	Vich
2,553,337 A	5/1951	Shafer	4,887,596 A	12/1989	Sherman
2,778,265 A	1/1957	Brown	4,917,606 A	4/1990	Miller
2,813,450 A	11/1957	Dzus	4,946,458 A	8/1990	Harms et al.
2,877,681 A	3/1959	Brown	4,950,269 A	8/1990	Gaines, Jr.
2,927,332 A	3/1960	Moore	4,961,740 A	10/1990	Ray et al.
2,969,250 A	1/1961	Kull	5,005,562 A	4/1991	Cotrel
3,013,244 A	12/1961	Rudy	5,019,080 A	5/1991	Hemer
3,143,029 A	8/1964	Brown	5,022,791 A	6/1991	Isler
D200,217 S	2/1965	Curtiss	5,034,011 A	7/1991	Howland
3,236,275 A	2/1966	Smith	5,056,492 A	10/1991	Banse
3,370,341 A	2/1968	Allsop	5,067,428 A	11/1991	Dickerson et al.
3,444,775 A	5/1969	Hills	5,067,955 A	11/1991	Cotrel
3,498,174 A	3/1970	Schuster et al.	5,073,074 A	12/1991	Corrigan et al.
3,584,667 A	6/1971	Reiland	5,084,048 A	1/1992	Jacob et al.
3,604,487 A	9/1971	Gilbert	5,092,635 A	3/1992	DeLange et al.
3,640,416 A	2/1972	Temple	5,102,412 A	4/1992	Rogozinski
3,812,757 A	5/1974	Reiland	5,129,388 A	7/1992	Vignaud et al.
3,963,322 A	6/1976	Gryctko	5,129,899 A	7/1992	Small et al.
3,989,284 A	11/1976	Blose	5,147,360 A	9/1992	Dubousset
3,997,138 A	12/1976	Crock et al.	5,147,363 A	9/1992	Harle
4,013,071 A	3/1977	Rosenberg	5,154,719 A	10/1992	Cotrel
4,033,139 A	7/1977	Frederick	5,176,483 A	1/1993	Baumann et al.
4,041,939 A	8/1977	Hall	5,176,678 A	1/1993	Tsou
4,103,422 A	8/1978	Weiss et al.	5,176,680 A	1/1993	Vignaud et al.
4,190,091 A	2/1980	Colognori	5,180,393 A	1/1993	Commarmond
4,269,246 A	5/1981	Larson et al.	5,201,734 A	4/1993	Cozad et al.
4,347,845 A	9/1982	Mayfield	5,207,678 A	5/1993	Harms et al.
4,369,769 A	1/1983	Edwards	5,217,497 A	6/1993	Mehdian
4,373,754 A	2/1983	Bollfrass et al.	5,257,993 A	11/1993	Asher et al.
4,409,968 A	10/1983	Drummond	5,261,907 A	11/1993	Vignaud et al.
4,448,191 A	5/1984	Rodnyansky et al.	5,261,912 A	11/1993	Frigg
4,484,570 A	11/1984	Sutter et al.	5,263,953 A	11/1993	Bagby
4,492,500 A	1/1985	Ewing	5,275,601 A	1/1994	Gogolewski et al.
4,506,917 A	3/1985	Hansen	5,282,707 A	2/1994	Palm
4,577,448 A	3/1986	Howorth	5,282,862 A	2/1994	Barker et al.
4,600,224 A	7/1986	Blose	5,282,863 A	2/1994	Burton
4,600,225 A	7/1986	Blose	5,306,275 A	4/1994	Bryan
4,641,636 A	2/1987	Cotrel	5,312,404 A	5/1994	Asher et al.
4,653,481 A	3/1987	Howland et al.	5,321,901 A	6/1994	Kelly
4,653,486 A	3/1987	Coker	5,330,472 A	7/1994	Metz-Stavenhagen
			5,334,203 A	8/1994	Wagner
			5,346,493 A	9/1994	Stahurski et al.
			5,354,292 A	10/1994	Braeuer et al.
			5,354,299 A	10/1994	Coleman
			5,358,289 A	10/1994	Banker et al.
			5,360,431 A	11/1994	Puno et al.
			5,364,400 A	11/1994	Rego, Jr. et al.
			5,375,823 A	12/1994	Navas
			5,382,248 A	1/1995	Jacobson et al.
			5,385,583 A	1/1995	Cotrel
			5,387,211 A	2/1995	Saadatmanesh et al.
			5,387,212 A	2/1995	Yuan et al.
			5,395,371 A	3/1995	Miller et al.
			5,409,489 A	4/1995	Sioufi
			5,415,661 A	5/1995	Holmes
			5,423,816 A	6/1995	Lin
			5,427,418 A	6/1995	Watts
			5,429,639 A	7/1995	Judet
			5,434,001 A	7/1995	Yamada et al.
			5,443,467 A	8/1995	Biedermann et al.
			5,466,237 A	11/1995	Byrd, III et al.
			5,468,241 A	11/1995	Metz-Stavenhagen et al.
			5,474,551 A	12/1995	Finn et al.
			5,474,555 A	12/1995	Puno et al.
			5,476,462 A	12/1995	Allard et al.

(56)

References Cited

U.S. PATENT DOCUMENTS							
5,476,464	A	12/1995	Metz-Stavenhagen et al.	5,863,293	A	1/1999	Richelsoph
5,480,401	A	1/1996	Navas	5,873,878	A	2/1999	Harms et al.
5,484,440	A	1/1996	Allard	D407,302	S	3/1999	Lawson
5,487,742	A	1/1996	Cotrel	5,876,402	A	3/1999	Errico et al.
5,489,307	A	2/1996	Kuslich et al.	5,879,350	A	3/1999	Sherman et al.
5,490,750	A	2/1996	Gundy	5,879,351	A	3/1999	Viard
5,496,321	A	3/1996	Puno et al.	5,882,350	A	3/1999	Ralph et al.
5,499,892	A	3/1996	Reed	5,885,286	A	3/1999	Sherman et al.
5,501,684	A	3/1996	Schlapfer et al.	5,891,145	A	4/1999	Morrison et al.
5,505,731	A	4/1996	Tornier	5,899,906	A	5/1999	Schenk
5,507,745	A	4/1996	Logroscino et al.	5,902,303	A	5/1999	Eckhof et al.
5,507,747	A	4/1996	Yuan et al.	RE36,221	E	6/1999	Breard et al.
5,534,001	A	7/1996	Schlapfer et al.	5,910,141	A	6/1999	Morrison et al.
5,540,688	A	7/1996	Navas	5,910,142	A	6/1999	Tatar
5,545,165	A	8/1996	Biedermann et al.	5,928,236	A	7/1999	Augagneur et al.
5,549,607	A	8/1996	Olson et al.	5,938,663	A	8/1999	Petreto
5,549,608	A	8/1996	Errico et al.	5,941,880	A	8/1999	Errico et al.
5,554,157	A	9/1996	Errico et al.	5,944,465	A	8/1999	Janitzki
5,562,660	A	10/1996	Grob	5,951,553	A	9/1999	Betz et al.
5,562,661	A	10/1996	Yoshimi et al.	5,954,725	A	9/1999	Sherman et al.
5,562,663	A	10/1996	Wisnewski et al.	5,961,517	A	10/1999	Biedermann et al.
5,569,247	A	10/1996	Morrison	5,964,760	A	10/1999	Richelsoph
5,569,251	A	10/1996	Baker et al.	5,964,767	A	10/1999	Tapia et al.
5,578,033	A	11/1996	Errico et al.	5,997,539	A	12/1999	Errico et al.
5,584,834	A	12/1996	Errico et al.	6,001,098	A	12/1999	Metz-Stavenhagen et al.
5,586,984	A	12/1996	Errico et al.	6,004,349	A	12/1999	Jackson
5,591,166	A	1/1997	Bernhardt et al.	6,010,503	A	1/2000	Richelsoph et al.
5,601,553	A	2/1997	Trebing et al.	6,019,759	A	2/2000	Rogozinski
5,605,458	A	2/1997	Bailey et al.	6,022,350	A	2/2000	Ganem
5,607,304	A	3/1997	Bailey et al.	6,050,997	A	4/2000	Mullane
5,607,425	A	3/1997	Rogozinski	6,053,078	A	4/2000	Parker
5,607,426	A	3/1997	Ralph et al.	6,053,917	A	4/2000	Sherman et al.
5,607,428	A	3/1997	Lin	6,056,753	A	5/2000	Jackson
5,609,593	A	3/1997	Errico et al.	6,063,088	A	5/2000	Winslow
5,609,594	A	3/1997	Errico et al.	6,063,090	A	5/2000	Schlapfer
5,611,800	A	3/1997	Davis et al.	6,074,391	A	6/2000	Metz-Stavenhagen et al.
5,628,740	A	5/1997	Mullane	6,077,262	A	6/2000	Schlapfer et al.
5,630,817	A	5/1997	Rokegem	6,086,588	A	7/2000	Ameil et al.
5,641,256	A	6/1997	Gundy	6,090,110	A	7/2000	Metz-Stavenhagen
5,643,260	A	7/1997	Doherty	6,090,111	A	7/2000	Nichols
5,643,261	A	7/1997	Schafer et al.	6,099,528	A	8/2000	Saurat
5,647,873	A	7/1997	Errico et al.	6,110,172	A	8/2000	Jackson
5,653,710	A	8/1997	Harle	6,113,601	A	9/2000	Tatar
5,662,652	A	9/1997	Schafer et al.	6,117,137	A	9/2000	Halm et al.
5,662,653	A	9/1997	Songer et al.	6,129,763	A	10/2000	Chauvin et al.
5,667,508	A	9/1997	Errico et al.	6,132,431	A	10/2000	Nilsson et al.
5,669,909	A	9/1997	Zdeblick et al.	6,132,432	A	10/2000	Richelsoph
5,669,911	A	9/1997	Errico et al.	6,132,434	A	10/2000	Sherman et al.
5,672,175	A	9/1997	Martin	6,136,002	A	10/2000	Shih et al.
5,672,176	A	9/1997	Biedermann et al.	6,136,003	A	10/2000	Hoeck et al.
5,676,665	A	10/1997	Bryan	6,143,032	A	11/2000	Schaefer et al.
5,676,703	A	10/1997	Gelbard	6,146,383	A	11/2000	Studer et al. 606/308
5,681,319	A	10/1997	Biedermann et al.	6,149,533	A	11/2000	Finn
5,683,390	A	11/1997	Metz-Stavenhagen et al.	6,168,597	B1	1/2001	Biedermann et al.
5,683,391	A	11/1997	Boyd	6,183,472	B1	2/2001	Lutz
5,690,630	A	11/1997	Errico et al.	6,186,718	B1	2/2001	Fogard
5,702,393	A	12/1997	Pfaifer	6,187,005	B1	2/2001	Brace et al.
5,711,709	A	1/1998	McCoy	6,193,719	B1	2/2001	Gournay et al.
5,713,705	A	2/1998	Grunbichler	6,193,720	B1	2/2001	Yuan et al.
5,713,898	A	2/1998	Stuecker et al.	6,214,012	B1	4/2001	Karpman et al.
5,716,356	A	2/1998	Biedermann et al.	RE37,161	E	5/2001	Michelson et al.
5,720,751	A	2/1998	Jackson	6,224,596	B1	5/2001	Jackson
5,723,013	A	3/1998	Jeanson et al.	6,224,598	B1	5/2001	Jackson
5,725,527	A	3/1998	Biedermann et al.	6,235,028	B1	5/2001	Brumfield et al.
5,725,528	A	3/1998	Errico et al.	6,235,034	B1	5/2001	Bray
5,728,098	A	3/1998	Sherman et al.	6,241,730	B1	6/2001	Alby
5,733,286	A	3/1998	Errico et al.	6,241,731	B1	6/2001	Fiz
5,738,685	A	4/1998	Halm et al.	6,248,105	B1	6/2001	Schlapfer et al.
5,741,254	A	4/1998	Henry et al.	6,248,107	B1	6/2001	Foley et al.
5,752,957	A	5/1998	Ralph et al.	6,251,112	B1	6/2001	Jackson
5,782,833	A	* 7/1998	Haider 606/266	6,254,602	B1	7/2001	Justis
5,797,911	A	8/1998	Sherman et al.	6,261,039	B1	7/2001	Reed
5,800,435	A	9/1998	Errico et al.	6,267,764	B1	7/2001	Elberg
5,800,547	A	9/1998	Schafer et al.	6,267,765	B1	7/2001	Taylor et al.
5,817,094	A	10/1998	Errico et al.	6,273,888	B1	8/2001	Justis
				6,280,442	B1	8/2001	Barker et al.
				6,280,445	B1	8/2001	Morrison et al.
				6,287,308	B1	9/2001	Betz et al.
				6,287,311	B1	9/2001	Sherman et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,296,642 B1	10/2001	Morrison et al.	6,706,045 B2	3/2004	Lin et al.
6,296,643 B1	10/2001	Hopf et al.	6,712,818 B1	3/2004	Michelson
6,299,613 B1	10/2001	Ogilvie et al.	6,716,213 B2	4/2004	Shitoto
6,299,616 B1	10/2001	Beger	6,716,214 B1	4/2004	Jackson
6,302,888 B1	10/2001	Mellinger et al.	6,716,247 B2	4/2004	Michelson
6,309,391 B1	10/2001	Crandall et al.	6,723,100 B2	4/2004	Biedermann et al.
6,315,564 B1	11/2001	Levisman	6,730,093 B2	5/2004	Saint Martin
6,322,108 B1	11/2001	Riesselmann et al.	6,730,127 B2	5/2004	Michelson
6,328,739 B1	12/2001	Liu et al.	6,733,502 B2	5/2004	Altarac et al.
6,331,179 B1	12/2001	Freid et al.	6,736,816 B2	5/2004	Ritland
6,355,040 B1	3/2002	Richelsoph et al.	6,736,820 B2	5/2004	Biedermann et al.
RE37,665 E	4/2002	Ralph et al.	6,740,086 B2	5/2004	Richelsoph
6,368,321 B1	4/2002	Jackson	6,743,231 B1	6/2004	Gray et al.
6,371,957 B1	4/2002	Amrein et al.	6,746,449 B2	6/2004	Jones et al.
6,379,356 B1	4/2002	Jackson	6,755,829 B1	6/2004	Bono et al.
6,402,752 B2	6/2002	Schaffler-Wachter et al.	6,755,835 B2	6/2004	Schultheiss et al.
6,402,757 B1	6/2002	Moore et al.	6,755,836 B1	6/2004	Lewis
6,440,133 B1	8/2002	Beale et al.	6,761,723 B2	7/2004	Buttermann et al.
6,440,137 B1	8/2002	Horvath et al.	6,767,351 B2	7/2004	Orbay et al.
6,443,956 B1	9/2002	Ray	6,770,075 B2	8/2004	Howland
6,451,021 B1	9/2002	Ralph et al.	6,778,861 B1	8/2004	Liebrecht et al.
6,467,958 B1	10/2002	Sasaki et al.	6,780,186 B2	8/2004	Errico et al.
6,471,703 B1	10/2002	Ashman	6,790,209 B2	9/2004	Beale et al.
6,471,705 B1	10/2002	Biedermann et al.	6,827,719 B2	12/2004	Ralph et al.
6,478,797 B1	11/2002	Paul	6,830,571 B2	12/2004	Lenke et al.
6,478,798 B1	11/2002	Howland	6,835,196 B2 *	12/2004	Biedermann et al. 606/308
6,485,491 B1	11/2002	Farris et al.	6,840,940 B2	1/2005	Ralph et al.
6,485,492 B1	11/2002	Halm et al.	6,843,791 B2	1/2005	Serhan
6,485,494 B1 *	11/2002	Haider 606/302	6,858,031 B2	2/2005	Morrison et al.
6,488,681 B2	12/2002	Martin et al.	6,869,432 B2	3/2005	Schlapfer et al.
6,508,818 B2	1/2003	Steiner et al.	6,869,433 B2	3/2005	Glascott
6,520,962 B1	2/2003	Taylor et al.	6,872,208 B1	3/2005	McBride et al.
6,527,804 B1	3/2003	Gauchet et al.	6,896,677 B1	5/2005	Lin
6,530,929 B1	3/2003	Jusis et al.	6,932,817 B2	8/2005	Baynham et al.
6,533,786 B1	3/2003	Needham et al.	6,945,972 B2	9/2005	Frigg et al.
6,547,790 B2	4/2003	Harkey, III et al.	6,953,462 B2	10/2005	Liebermann
6,551,320 B2	4/2003	Liebermann	6,955,677 B2	10/2005	Dahners
6,554,831 B1	4/2003	Rivard et al.	6,958,065 B2	10/2005	Ueyama et al.
6,554,832 B2	4/2003	Shluzas	6,964,664 B2	11/2005	Freid et al.
6,554,834 B1	4/2003	Crozet et al.	6,964,665 B2	11/2005	Thomas et al.
6,558,387 B2	5/2003	Errico et al.	6,974,460 B2	12/2005	Carbone et al.
6,562,040 B1	5/2003	Wagner	6,979,334 B2	12/2005	Dalton
6,565,565 B1	5/2003	Yuan et al.	6,981,973 B2	1/2006	McKinley
6,565,567 B1	5/2003	Haider	7,001,389 B1	2/2006	Navarro et al.
6,582,436 B2	6/2003	Schlapfer et al.	RE39,035 E	3/2006	Finn et al.
6,582,466 B1	6/2003	Gauchet	7,018,378 B2	3/2006	Biedermann et al.
6,585,740 B2	7/2003	Schlapfer et al.	7,018,379 B2	3/2006	Drewry et al.
6,595,992 B1	7/2003	Wagner et al.	7,022,122 B2	4/2006	Amrein et al.
6,595,993 B2	7/2003	Donno et al.	RE39,089 E	5/2006	Ralph et al.
6,602,255 B1	8/2003	Campbell et al.	7,066,062 B2	6/2006	Flesher
6,610,063 B2	8/2003	Kumar et al.	7,066,937 B2	6/2006	Shluzas
6,613,050 B1	9/2003	Wagner et al.	7,081,116 B1	7/2006	Carly
6,616,667 B1	9/2003	Steiger et al.	7,083,621 B2	8/2006	Shaolian et al.
6,623,485 B2	9/2003	Doubler et al.	7,087,057 B2	8/2006	Konieczynski et al.
6,626,907 B2	9/2003	Campbell et al.	7,090,674 B2	8/2006	Doubler et al.
6,626,908 B2	9/2003	Cooper et al.	7,121,755 B2	10/2006	Schlapfer et al.
6,635,059 B2	10/2003	Randall et al.	7,125,426 B2	10/2006	Moumene et al.
6,648,885 B1	11/2003	Friesem	7,128,743 B2	10/2006	Metz-Stavenhagen
6,648,887 B2	11/2003	Ashman	7,141,051 B2	11/2006	Janowski et al.
6,652,526 B1	11/2003	Arafiles	7,144,396 B2	12/2006	Shluzas
6,652,765 B1	11/2003	Beaty	7,163,538 B2	1/2007	Altarac et al.
6,656,179 B1	12/2003	Schaefer et al.	7,163,539 B2	1/2007	Abdelgany et al.
6,656,181 B2	12/2003	Dixon et al.	7,166,108 B2	1/2007	Mazda et al.
6,660,004 B2 *	12/2003	Barker et al. 606/328	7,186,255 B2	3/2007	Baynham et al.
6,663,632 B1	12/2003	Frigg	7,211,086 B2	5/2007	Biedermann et al.
6,663,635 B2	12/2003	Frigg et al.	7,211,087 B2	5/2007	Young
6,673,073 B1	1/2004	Schafer	7,214,227 B2	5/2007	Colleran et al.
6,676,661 B1	1/2004	Benlloch et al.	7,223,268 B2	5/2007	Biedermann
6,679,833 B2	1/2004	Smith et al.	7,250,052 B2	7/2007	Landry et al.
6,682,529 B2	1/2004	Stahurski	7,264,621 B2	9/2007	Coates et al.
6,689,133 B2	2/2004	Morrison et al.	7,270,665 B2	9/2007	Morrison et al.
6,689,134 B2	2/2004	Ralph et al.	7,291,151 B2	11/2007	Alvarez
6,695,843 B2	2/2004	Biedermann et al.	7,291,153 B2	11/2007	Glascott
6,695,851 B2	2/2004	Zdeblick et al.	7,294,128 B2	11/2007	Alleyne et al.
6,699,249 B2	3/2004	Schlapfer et al.	7,294,129 B2	11/2007	Hawkins et al.
			7,306,603 B2	12/2007	Boehm, Jr. et al.
			7,306,604 B2	12/2007	Carli
			7,306,606 B2	12/2007	Sasing
			7,314,467 B2	1/2008	Howland

US RE46,431 E

Page 5

(56)

References Cited

U.S. PATENT DOCUMENTS							
7,316,684	B1	1/2008	Baccelli et al.	2003/0028191	A1	2/2003	Shluzas
7,322,979	B2	1/2008	Crandall et al.	2003/0032957	A1	2/2003	McKinley
7,335,201	B2	2/2008	Doubler et al.	2003/0055426	A1	3/2003	Carbone et al.
7,335,202	B2	2/2008	Matthis et al.	2003/0055427	A1	3/2003	Graf
7,338,490	B2	3/2008	Ogilvie et al.	2003/0060826	A1	3/2003	Foley et al.
7,338,491	B2	3/2008	Baker et al.	2003/0073995	A1	4/2003	Reed
7,776,067	B2*	8/2010	Jackson 606/246	2003/0073996	A1	4/2003	Doubler et al.
7,789,896	B2*	9/2010	Jackson 606/266	2003/0073998	A1	4/2003	Pagliuca et al.
2001/0001119	A1	5/2001	Lombardo	2003/0078580	A1	4/2003	Shitoto
2001/0007941	A1	7/2001	Steiner et al.	2003/0083657	A1	5/2003	Drewry et al.
2001/0010000	A1	7/2001	Gertzbein et al.	2003/0083667	A1	5/2003	Ralph et al.
2001/0011172	A1	8/2001	Orbay et al.	2003/0093077	A1	5/2003	Schlapfer et al.
2001/0012937	A1	8/2001	Schaffler-Wachter et al.	2003/0093078	A1	5/2003	Ritland
2001/0023350	A1	9/2001	Choi	2003/0100896	A1	5/2003	Biedermann et al.
2001/0037111	A1	11/2001	Dixon et al.	2003/0100897	A1	5/2003	Metz-Stavenhagen
2001/0041894	A1	11/2001	Campbell et al.	2003/0100904	A1	5/2003	Biedermann
2001/0047173	A1	11/2001	Schlapfer et al.	2003/0105460	A1	6/2003	Crandall et al.
2001/0047174	A1	11/2001	Donno et al.	2003/0109880	A1	6/2003	Shirado et al.
2001/0047175	A1	11/2001	Doubler et al.	2003/0114852	A1	6/2003	Biedermann et al.
2001/0052438	A1	12/2001	Spencer	2003/0120275	A1	6/2003	Lenke et al.
2002/0004683	A1	1/2002	Michelson	2003/0125741	A1	7/2003	Biedermann et al.
2002/0007184	A1	1/2002	Ogilvie et al.	2003/0125749	A1	7/2003	Yuan et al.
2002/0010467	A1	1/2002	Cooper et al.	2003/0130659	A1	7/2003	Haider
2002/0013586	A1	1/2002	Justis et al.	2003/0130661	A1	7/2003	Osman
2002/0016594	A1	2/2002	Schlapfer et al.	2003/0135210	A1	7/2003	Dixon et al.
2002/0022764	A1	2/2002	Smith et al.	2003/0135217	A1	7/2003	Buttermann et al.
2002/0022842	A1	2/2002	Horvath et al.	2003/0139745	A1	7/2003	Ashman
2002/0026193	A1	2/2002	Barker et al.	2003/0149431	A1	8/2003	Varieur
2002/0029040	A1	3/2002	Morrison et al.	2003/0149432	A1	8/2003	Frigg et al.
2002/0035365	A1	3/2002	Kumar et al.	2003/0149435	A1	8/2003	Baynham et al.
2002/0035366	A1	3/2002	Walder et al.	2003/0153911	A1	8/2003	Shluzas
2002/0035367	A1	3/2002	Ritland	2003/0153912	A1	8/2003	Graf
2002/0045898	A1	4/2002	Freid et al.	2003/0153920	A1	8/2003	Ralph et al.
2002/0045899	A1	4/2002	Errico et al.	2003/0163133	A1	8/2003	Altarac et al.
2002/0049446	A1	4/2002	Harkey, III et al.	2003/0167058	A1	9/2003	Shluzas
2002/0055740	A1	5/2002	Lieberman	2003/0171749	A1	9/2003	Le Couedic et al.
2002/0055741	A1	5/2002	Schlapfer et al.	2003/0176862	A1	9/2003	Taylor et al.
2002/0058942	A1	5/2002	Biedermann et al.	2003/0176863	A1	9/2003	Ueyama et al.
2002/0068975	A1	6/2002	Teitelbaum et al.	2003/0181913	A1	9/2003	Lieberman
2002/0072750	A1	6/2002	Jackson	2003/0187433	A1	10/2003	Lin
2002/0072751	A1	6/2002	Jackson	2003/0187434	A1	10/2003	Lin
2002/0082602	A1	6/2002	Biedermann et al.	2003/0191470	A1	10/2003	Ritland
2002/0082603	A1	6/2002	Dixon et al.	2003/0199872	A1	10/2003	Markworth et al.
2002/0087159	A1	7/2002	Thomas	2003/0199873	A1	10/2003	Richelsoph
2002/0087161	A1	7/2002	Randall et al.	2003/0208204	A1	11/2003	Bailey et al.
2002/0091386	A1	7/2002	Martin et al.	2003/0212398	A1	11/2003	Jackson
2002/0095153	A1	7/2002	Jones et al.	2003/0216735	A1	11/2003	Altarac et al.
2002/0095154	A1	7/2002	Atkinson et al.	2003/0220642	A1	11/2003	Freudiger
2002/0095881	A1	7/2002	Shreiner	2003/0220643	A1	11/2003	Ferree
2002/0103487	A1	8/2002	Errico et al.	2003/0225408	A1	12/2003	Nichols et al.
2002/0111626	A1	8/2002	Ralph et al.	2003/0229345	A1	12/2003	Stahurski
2002/0111627	A1	8/2002	Vincent-Prestigiacommo	2003/0229347	A1	12/2003	Sherman et al.
2002/0116001	A1	8/2002	Schaefer et al.	2003/0236529	A1	12/2003	Shluzas et al.
2002/0120270	A1	8/2002	Trieu et al.	2004/0006342	A1	1/2004	Altarac et al.
2002/0123752	A1	9/2002	Schultheiss et al.	2004/0039383	A1	2/2004	Jackson
2002/0133154	A1	9/2002	Saint Martin	2004/0039384	A1	2/2004	Boehm, Jr. et al.
2002/0133158	A1	9/2002	Saint Martin	2004/0039385	A1	2/2004	Mazda et al.
2002/0133159	A1	9/2002	Jackson	2004/0049189	A1	3/2004	Le Couedic et al.
2002/0138076	A1	9/2002	Biedermann et al.	2004/0049190	A1	3/2004	Biedermann et al.
2002/0138077	A1	9/2002	Ferree	2004/0073215	A1	4/2004	Carli
2002/0143328	A1	10/2002	Shluzas et al.	2004/0073218	A1	4/2004	Dahners
2002/0143330	A1	10/2002	Shluzas	2004/0078051	A1	4/2004	Davison et al.
2002/0143332	A1	10/2002	Lin et al.	2004/0078082	A1	4/2004	Lange
2002/0143338	A1	10/2002	Orbay et al.	2004/0087949	A1	5/2004	Bono et al.
2002/0143341	A1	10/2002	Biedermann et al.	2004/0087950	A1	5/2004	Teitelbaum
2002/0161368	A1	10/2002	Foley et al.	2004/0087952	A1	5/2004	Borgstrom et al.
2002/0161370	A1	10/2002	Frigg et al.	2004/0092934	A1	5/2004	Howland
2002/0173789	A1	11/2002	Howland	2004/0092938	A1	5/2004	Carli
2002/0173791	A1	11/2002	Howland	2004/0097933	A1	5/2004	Lourdel et al.
2002/0183747	A1	12/2002	Jao et al.	2004/0106925	A1	6/2004	Culbert
2002/0193795	A1	12/2002	Gertzbein et al.	2004/0111091	A1	6/2004	Ogilvie et al.
2002/0198526	A1	12/2002	Shaolian et al.	2004/0116929	A1	6/2004	Barker et al.
2003/0004519	A1	1/2003	Torode et al.	2004/0122442	A1	6/2004	Lewis
2003/0023240	A1	1/2003	Amrein et al.	2004/0127904	A1	7/2004	Konieczynski et al.
2003/0023243	A1	1/2003	Biedermann et al.	2004/0133207	A1	7/2004	Abdou
				2004/0138660	A1	7/2004	Serhan
				2004/0138662	A1	7/2004	Landry et al.
				2004/0143265	A1	7/2004	Landry et al.
				2004/0147928	A1	7/2004	Landry et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0147929 A1	7/2004	Biedermann et al.	2005/0141986 A1	6/2005	Flesher
2004/0147937 A1	7/2004	Dunbar, Jr. et al.	2005/0143737 A1	6/2005	Pafford et al.
2004/0153068 A1	8/2004	Janowski et al.	2005/0143823 A1	6/2005	Boyd et al.
2004/0158245 A1	8/2004	Chin	2005/0149020 A1	7/2005	Jahng
2004/0158247 A1	8/2004	Sitiso et al.	2005/0149023 A1	7/2005	Ritland
2004/0158258 A1	8/2004	Bonati et al.	2005/0149053 A1	7/2005	Varieur
2004/0162560 A1	8/2004	Raynor et al.	2005/0154389 A1	7/2005	Selover et al.
2004/0167523 A1	8/2004	Jackson	2005/0154390 A1	7/2005	Biedermann et al.
2004/0167525 A1	8/2004	Jackson	2005/0154391 A1	7/2005	Doherty et al.
2004/0172022 A1	9/2004	Landry et al.	2005/0159750 A1	7/2005	Doherty
2004/0172025 A1	9/2004	Drewry et al.	2005/0165400 A1	7/2005	Fernandez
2004/0172031 A1	9/2004	Rubecamp et al.	2005/0171540 A1	8/2005	Lim et al.
2004/0172032 A1	9/2004	Jackson	2005/0171543 A1	8/2005	Timm et al.
2004/0176766 A1	9/2004	Shluzas	2005/0177154 A1	8/2005	Moumene et al.
2004/0176776 A1	9/2004	Zubok et al.	2005/0177166 A1	8/2005	Timm et al.
2004/0186473 A1	9/2004	Cournoyer et al.	2005/0182401 A1	8/2005	Timm et al.
2004/0186474 A1	9/2004	Matthis et al.	2005/0182410 A1	8/2005	Jackson
2004/0186475 A1	9/2004	Falahee	2005/0187548 A1	8/2005	Butler et al.
2004/0210216 A1	10/2004	Farris et al.	2005/0187555 A1	8/2005	Biedermann et al.
2004/0210227 A1	10/2004	Trail et al.	2005/0192571 A1	9/2005	Abdelgany
2004/0215190 A1	10/2004	Nguyen et al.	2005/0192572 A1	9/2005	Abdelgany et al.
2004/0215191 A1	10/2004	Kitchen	2005/0192573 A1	9/2005	Abdelgany et al.
2004/0220567 A1	11/2004	Eisermann et al.	2005/0192579 A1	9/2005	Jackson
2004/0220671 A1	11/2004	Ralph et al.	2005/0192580 A1	9/2005	Dalton
2004/0225289 A1	11/2004	Biedermann et al.	2005/0192589 A1	9/2005	Raymond et al.
2004/0230100 A1	11/2004	Shluzas	2005/0203511 A1	9/2005	Wilson-MacDonald et al.
2004/0236327 A1	11/2004	Paul et al.	2005/0203513 A1	9/2005	Jahng et al.
2004/0236328 A1	11/2004	Paul et al.	2005/0203514 A1	9/2005	Jahng et al.
2004/0236330 A1	11/2004	Purcell et al.	2005/0203516 A1	9/2005	Biedermann et al.
2004/0249378 A1	12/2004	Saint Martin et al.	2005/0203518 A1	9/2005	Biedermann et al.
2004/0249380 A1	12/2004	Glascott	2005/0203519 A1	9/2005	Harms et al.
2004/0254574 A1	12/2004	Morrison et al.	2005/0215999 A1	9/2005	Birkmeyer et al.
2004/0260283 A1	12/2004	Wu et al.	2005/0216000 A1	9/2005	Colleran et al.
2004/0267264 A1	12/2004	Konieczynski et al.	2005/0216001 A1	9/2005	David
2005/0010219 A1	1/2005	Dalton	2005/0216003 A1	9/2005	Biedermann et al.
2005/0020351 A1	1/2005	Baerlocher et al.	2005/0228326 A1	10/2005	Kalfas et al.
2005/0027296 A1	2/2005	Thramann et al.	2005/0228379 A1	10/2005	Jackson
2005/0033298 A1	2/2005	Hawkes et al.	2005/0228385 A1	10/2005	Lee et al.
2005/0033436 A1	2/2005	Schlapfer et al.	2005/0228400 A1	10/2005	Chao
2005/0033439 A1	2/2005	Gordon et al.	2005/0228501 A1	10/2005	Miller et al.
2005/0038430 A1	2/2005	McKinley	2005/0234450 A1	10/2005	Barker
2005/0038432 A1	2/2005	Shaolian et al.	2005/0234451 A1	10/2005	Markworth
2005/0038433 A1	2/2005	Young	2005/0234452 A1	10/2005	Malandain
2005/0049588 A1	3/2005	Jackson	2005/0234453 A1	10/2005	Shaolian et al.
2005/0049589 A1	3/2005	Jackson	2005/0234454 A1	10/2005	Chin
2005/0055026 A1	3/2005	Biedermann et al.	2005/0234456 A1	10/2005	Malandain
2005/0065514 A1	3/2005	Studer	2005/0234459 A1	10/2005	Falahee et al.
2005/0065515 A1	3/2005	Jahng	2005/0240181 A1	10/2005	Boomer et al.
2005/0065516 A1	3/2005	Jahng	2005/0240183 A1	10/2005	Vaughan
2005/0065517 A1	3/2005	Chin	2005/0245930 A1	11/2005	Timm et al.
2005/0070899 A1	3/2005	Doubler et al.	2005/0251137 A1	11/2005	Ball
2005/0070901 A1	3/2005	David	2005/0251139 A1	11/2005	Roh
2005/0080415 A1	4/2005	Keyer et al.	2005/0251140 A1	11/2005	Shaolian et al.
2005/0085812 A1	4/2005	Sherman et al.	2005/0251141 A1	11/2005	Frigg et al.
2005/0085813 A1	4/2005	Spitler et al.	2005/0260058 A1	11/2005	Casagne, III
2005/0085816 A1	4/2005	Michelson	2005/0261687 A1	11/2005	Garamszegi et al.
2005/0090821 A1	4/2005	Berrevoets et al.	2005/0267470 A1	12/2005	McBride
2005/0096652 A1	5/2005	Burton	2005/0267471 A1	12/2005	Biedermann et al.
2005/0096653 A1	5/2005	Doubler et al.	2005/0267472 A1	12/2005	Biedermann et al.
2005/0096654 A1	5/2005	Lin	2005/0267474 A1	12/2005	Dalton
2005/0107788 A1	5/2005	Beaurain et al.	2005/0267477 A1	12/2005	Jackson
2005/0113927 A1	5/2005	Malek	2005/0273099 A1	12/2005	Baccelli et al.
2005/0119658 A1	6/2005	Ralph et al.	2005/0273101 A1	12/2005	Schumacher
2005/0124991 A1	6/2005	Jahng	2005/0277919 A1	12/2005	Slivka et al.
2005/0131404 A1	6/2005	Mazda et al.	2005/0277922 A1	12/2005	Trieu et al.
2005/0131405 A1	6/2005	Molz, IV et al.	2005/0277923 A1	12/2005	Sweeney
2005/0131406 A1	6/2005	Reiley et al.	2005/0277925 A1	12/2005	Mujwid
2005/0131407 A1	6/2005	Sicvol et al.	2005/0277927 A1	12/2005	Guenther et al.
2005/0131408 A1	6/2005	Sicvol et al.	2005/0277928 A1	12/2005	Boschert
2005/0131413 A1	6/2005	O'Driscoll et al.	2005/0277931 A1	12/2005	Sweeney et al.
2005/0131419 A1	6/2005	McCord et al.	2005/0277934 A1	12/2005	Vardiman
2005/0131421 A1	6/2005	Anderson et al.	2005/0278023 A1	12/2005	Zwirkoski
2005/0131422 A1	6/2005	Anderson	2005/0283152 A1	12/2005	Lindemann et al.
2005/0137594 A1	6/2005	Doubler et al.	2005/0283157 A1	12/2005	Coates et al.
2005/0137597 A1	6/2005	Butler et al.	2005/0283238 A1	12/2005	Reiley
			2005/0283244 A1	12/2005	Gordon et al.
			2005/0288669 A1	12/2005	Abdou
			2005/0288670 A1	12/2005	Panjabi
			2005/0288671 A1	12/2005	Yuan et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0282078	A1	12/2006	Labrom et al.	2007/0161997	A1	7/2007	Thramann et al.
2006/0282079	A1	12/2006	Labrom et al.	2007/0161999	A1	7/2007	Biedermann et al.
2006/0282080	A1	12/2006	Albert	2007/0167948	A1	7/2007	Abdou
2006/0293657	A1	12/2006	Hartmann	2007/0167949	A1	7/2007	Altarac et al.
2006/0293659	A1	12/2006	Alvarez	2007/0173818	A1	7/2007	Hestad et al.
2006/0293663	A1	12/2006	Walkenhorst	2007/0173819	A1	7/2007	Sandlin
2006/0293665	A1	12/2006	Shluzas	2007/0173820	A1	7/2007	Trieu
2006/0293666	A1	12/2006	Matthis et al.	2007/0173822	A1	7/2007	Bruneau et al.
2006/0293693	A1	12/2006	Farr et al.	2007/0173828	A1	7/2007	Firkins et al.
2007/0005062	A1	1/2007	Lange et al.	2007/0173832	A1	7/2007	Tebbe et al.
2007/0005063	A1	1/2007	Bruneau et al.	2007/0191832	A1	8/2007	Trieu
2007/0005137	A1	1/2007	Kwak	2007/0191839	A1	8/2007	Justis et al.
2007/0016188	A1	1/2007	Boehm, Jr. et al.	2007/0191841	A1	8/2007	Justis et al.
2007/0016190	A1	1/2007	Martinez et al.	2007/0191846	A1	8/2007	Bruneau et al.
2007/0016194	A1	1/2007	Shaolian et al.	2007/0198014	A1	8/2007	Graf et al.
2007/0016198	A1	1/2007	Boehm, Jr. et al.	2007/0208344	A1	9/2007	Young
2007/0016200	A1	1/2007	Jackson	2007/0213720	A1	9/2007	Gordon et al.
2007/0021750	A1	1/2007	Shluzas et al.	2007/0225707	A1	9/2007	Wisnewski et al.
2007/0032123	A1	2/2007	Timm et al.	2007/0225708	A1	9/2007	Biedermann et al.
2007/0043355	A1	2/2007	Bette et al.	2007/0225711	A1	9/2007	Ensign
2007/0043356	A1	2/2007	Timm et al.	2007/0233073	A1	10/2007	Wisnewski et al.
2007/0043357	A1	2/2007	Kirschman	2007/0233078	A1	10/2007	Justis et al.
2007/0043358	A1	2/2007	Molz, IV et al.	2007/0233080	A1	10/2007	Na et al.
2007/0043359	A1	2/2007	Altarac et al.	2007/0233085	A1	10/2007	Biedermann et al.
2007/0043364	A1	2/2007	Cawley et al.	2007/0233086	A1	10/2007	Harms et al.
2007/0049931	A1	3/2007	Justis et al.	2007/0233087	A1	10/2007	Schlapfer
2007/0049933	A1	3/2007	Ahn et al.	2007/0233089	A1	10/2007	Dipoto et al.
2007/0049936	A1	3/2007	Colleran et al.	2007/0233092	A1	10/2007	Falahee
2007/0055235	A1	3/2007	Janowski et al.	2007/0233094	A1	10/2007	Colleran et al.
2007/0055236	A1	3/2007	Hudgins et al.	2007/0233095	A1	10/2007	Schlapfer
2007/0055238	A1	3/2007	Biedermann et al.	2007/0233155	A1	10/2007	Lovell
2007/0055239	A1	3/2007	Sweeney et al.	2007/0244481	A1	10/2007	Timm
2007/0055240	A1	3/2007	Matthis et al.	2007/0244482	A1	10/2007	Aferzon
2007/0055241	A1	3/2007	Matthis et al.	2007/0250061	A1	10/2007	Chin et al.
2007/0055242	A1	3/2007	Bailly	2007/0260243	A1	11/2007	Kagami
2007/0055244	A1	3/2007	Jackson	2007/0260246	A1	11/2007	Biedermann
2007/0073289	A1	3/2007	Kwak et al.	2007/0270806	A1	11/2007	Foley et al.
2007/0073290	A1	3/2007	Boehm	2007/0270807	A1	11/2007	Armstrong et al.
2007/0073291	A1	3/2007	Cordaro et al.	2007/0270810	A1	11/2007	Sanders
2007/0073293	A1	3/2007	Martz et al.	2007/0270813	A1	11/2007	Garamszegi
2007/0073294	A1	3/2007	Chin et al.	2007/0270815	A1	11/2007	Johnson et al.
2007/0078460	A1	4/2007	Frigg et al.	2007/0270821	A1	11/2007	Trieu et al.
2007/0078461	A1	4/2007	Shluzas	2007/0270830	A1	11/2007	Morrison
2007/0083199	A1	4/2007	Baccelli	2007/0270831	A1	11/2007	Dewey et al.
2007/0088357	A1	4/2007	Johnson et al.	2007/0270832	A1	11/2007	Moore
2007/0088359	A1	4/2007	Woods et al.	2007/0270835	A1	11/2007	Wisnewski
2007/0090238	A1	4/2007	Justis	2007/0270836	A1	11/2007	Bruneau et al.
2007/0093813	A1	4/2007	Callahan et al.	2007/0270837	A1	11/2007	Eckhardt et al.
2007/0093814	A1	4/2007	Callahan, II et al.	2007/0270838	A1	11/2007	Bruneau et al.
2007/0093815	A1	4/2007	Callahan, II et al.	2007/0270839	A1	11/2007	Jeon et al.
2007/0093817	A1	4/2007	Barrus et al.	2007/0270843	A1	11/2007	Matthis et al.
2007/0093818	A1	4/2007	Biedermann et al.	2007/0270869	A1	11/2007	Young et al.
2007/0093819	A1	4/2007	Albert	2007/0276371	A1	11/2007	Baynham et al.
2007/0093824	A1	4/2007	Hestad et al.	2007/0276379	A1	11/2007	Miller et al.
2007/0093826	A1	4/2007	Hawkes et al.	2007/0276380	A1	11/2007	Jahng et al.
2007/0093827	A1	4/2007	Warnick	2007/0288004	A1	12/2007	Alvarez
2007/0093831	A1	4/2007	Abdelgany et al.	2007/0288012	A1	12/2007	Colleran et al.
2007/0093833	A1	4/2007	Kuiper et al.	2007/0293862	A1	12/2007	Jackson
2007/0100341	A1	5/2007	Reglos et al.	2008/0009862	A1	1/2008	Hoffman
2007/0118117	A1	5/2007	Altarac et al.	2008/0009864	A1	1/2008	Forton et al.
2007/0118118	A1	5/2007	Kwak et al.	2008/0015578	A1	1/2008	Erickson et al.
2007/0118119	A1	5/2007	Hestad	2008/0015579	A1	1/2008	Whipple
2007/0118122	A1	5/2007	Butler et al.	2008/0015580	A1	1/2008	Chao
2007/0118123	A1	5/2007	Strausbaugh et al.	2008/0015584	A1	1/2008	Richelsoph
2007/0118124	A1	5/2007	Biedermann et al.	2008/0015586	A1	1/2008	Krishna et al.
2007/0123862	A1	5/2007	Warnick	2008/0015597	A1	1/2008	Whipple
2007/0123864	A1	5/2007	Walder et al.	2008/0021454	A1	1/2008	Chao et al.
2007/0123867	A1	5/2007	Kirschman	2008/0021455	A1	1/2008	Chao et al.
2007/0123870	A1	5/2007	Jeon et al.	2008/0021462	A1	1/2008	Trieu
2007/0156142	A1	7/2007	Rezach et al.	2008/0021464	A1	1/2008	Morin et al.
2007/0161986	A1	7/2007	Levy	2008/0021465	A1	1/2008	Shaddock et al.
2007/0161991	A1	7/2007	Altarac et al.	2008/0021473	A1	1/2008	Butler et al.
2007/0161994	A1	7/2007	Lowery et al.	2008/0027432	A1	1/2008	Strauss et al.
2007/0161995	A1	7/2007	Trautwein et al.	2008/0039838	A1	2/2008	Landry et al.
2007/0161996	A1	7/2007	Biedermann et al.	2008/0039843	A1	2/2008	Abdou
				2008/0045951	A1	2/2008	Fanger et al.
				2008/0045955	A1	2/2008	Berrevoets et al.
				2008/0045957	A1	2/2008	Landry et al.
				2008/0051780	A1	2/2008	Vaidya et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0051787 A1 2/2008 Remington et al.
 2008/0058811 A1 3/2008 Alleyne et al.
 2008/0058812 A1 3/2008 Zehnder
 2008/0065071 A1 3/2008 Park
 2008/0065073 A1 3/2008 Perriello et al.
 2008/0065075 A1 3/2008 Dant
 2008/0065077 A1 3/2008 Ferree
 2008/0065079 A1 3/2008 Bruneau et al.
 2008/0071273 A1 3/2008 Hawkes et al.
 2008/0071274 A1 3/2008 Ensign
 2008/0071277 A1 3/2008 Warnick
 2008/0077136 A1 3/2008 Triplett et al.
 2008/0077138 A1 3/2008 Cohen et al.
 2008/0077139 A1 3/2008 Landry et al.
 2008/0077143 A1 3/2008 Shluzas
 2008/0086131 A1 4/2008 Daly et al.
 2008/0086132 A1 4/2008 Biedermann et al.
 2008/0091213 A1 4/2008 Jackson
 2008/0097441 A1 4/2008 Hayes et al.
 2008/0097457 A1 4/2008 Warnick
 2008/0103502 A1 5/2008 Capote et al.
 2008/0108992 A1 5/2008 Barry et al.
 2008/0114362 A1 5/2008 Justis et al.
 2008/0114403 A1 5/2008 Kuester et al.
 2008/0119849 A1 5/2008 Beardsley et al.
 2008/0119857 A1 5/2008 Potash et al.
 2008/0119858 A1 5/2008 Potash
 2008/0125777 A1 5/2008 Veldman et al.
 2008/0125787 A1 5/2008 Doubler et al.
 2008/0125813 A1 5/2008 Erickson et al.
 2008/0132957 A1 6/2008 Matthis et al.
 2008/0140075 A1 6/2008 Ensign et al.
 2008/0140076 A1 6/2008 Jackson
 2008/0140133 A1 6/2008 Allard et al.
 2008/0140136 A1 6/2008 Jackson
 2008/0147121 A1 6/2008 Justis et al.
 2008/0147122 A1 6/2008 Jackson
 2008/0147129 A1 6/2008 Biedermann et al.
 2008/0147195 A1 6/2008 Kwak et al.
 2008/0154279 A1 6/2008 Schumaker et al.
 2008/0154315 A1 6/2008 Jackson
 2008/0161857 A1 7/2008 Hestad et al.
 2008/0161859 A1 7/2008 Nilsson
 2008/0161863 A1 7/2008 Arnold et al.
 2008/0167687 A1 7/2008 Colleran et al.
 2008/0172090 A1 7/2008 Molz
 2008/0172091 A1 7/2008 Anderson
 2008/0172096 A1 7/2008 Hawkins
 2008/0177316 A1 7/2008 Bergeron et al.
 2008/0177317 A1 7/2008 Jackson
 2008/0177321 A1 7/2008 Drewry et al.
 2008/0177322 A1 7/2008 Davis et al.
 2008/0177323 A1 7/2008 Null et al.
 2008/0177332 A1 7/2008 Reiley et al.
 2008/0177388 A1 7/2008 Patterson et al.
 2008/0183212 A1 7/2008 Veldman et al.
 2008/0183213 A1 7/2008 Veldman et al.
 2008/0183215 A1 7/2008 Altarac et al.
 2008/0183216 A1 7/2008 Jackson
 2008/0183223 A1 7/2008 Jeon et al.
 2008/0188898 A1 8/2008 Jackson
 2008/0195155 A1 8/2008 Hoffman et al.
 2008/0195159 A1 8/2008 Kloss et al.
 2008/0200918 A1 8/2008 Spitler et al.
 2008/0200956 A1 8/2008 Beckwith et al.
 2008/0215095 A1 9/2008 Biedermann et al.
 2008/0215100 A1 9/2008 Matthis et al.
 2008/0228184 A1 9/2008 Hestad et al.
 2008/0228228 A1 9/2008 Hestad et al.
 2008/0234736 A1 9/2008 Trieu et al.
 2008/0234737 A1 9/2008 Boschert
 2008/0234738 A1 9/2008 Zylber et al.
 2008/0234739 A1 9/2008 Hudgins et al.
 2008/0234744 A1 9/2008 Zylber et al.
 2008/0234756 A1 9/2008 Sutcliffe et al.

2008/0234759 A1 9/2008 Marino
 2008/0234761 A1 9/2008 Jackson
 2008/0243052 A1 10/2008 Pond et al.
 2008/0243185 A1 10/2008 Felix et al.
 2008/0243193 A1 10/2008 Ensign et al.
 2008/0249570 A1 10/2008 Carson et al.
 2008/0262548 A1 10/2008 Lange et al.
 2008/0262551 A1 10/2008 Rice et al.
 2008/0262554 A1 10/2008 Hayes et al.
 2008/0262556 A1 10/2008 Jacofsky et al.
 2010/0030280 A1 2/2010 Jackson
 2010/0036433 A1 2/2010 Jackson
 2016/0183984 A1 6/2016 Jackson

FOREIGN PATENT DOCUMENTS

DE 9202745.8 4/1992
 DE G9202745.8 4/1992
 DE 4425392 11/1995
 DE 19507141 9/1996
 DE 29806563 6/1998
 DE 29810798 12/1999
 DE 19951145 5/2001
 DE 20207850 U1 10/2002
 DE 102007055745 7/2008
 EP 0195455 9/1986
 EP 0172130 2/1987
 EP 0276153 7/1988
 EP 0667127 8/1995
 EP 0669109 8/1995
 EP 0677277 10/1995
 EP 1121902 1/2001
 EP 1121902 8/2001
 EP 1190678 3/2002
 EP 1277444 1/2003
 EP 1570795 9/2005
 EP 1579816 9/2005
 EP 1634537 3/2006
 EP 1925263 5/2008
 FR 2467312 4/1981
 FR 2717370 9/1995
 FR 2729291 7/1996
 FR 2718946 10/1996
 FR 2796545 1/2001
 FR 2799949 4/2001
 FR 2814936 4/2002
 FR 2815535 4/2002
 FR 2856578 6/2003
 FR 2865373 1/2004
 FR 2865375 1/2004
 FR 2865377 1/2004
 FR 2846223 4/2004
 FR 2857850 4/2004
 FR 2865378 10/2004
 GB 203508 9/1923
 GB 2082709 3/1982
 GB 2140523 11/1984
 GB 2365345 2/2002
 GB 2382304 5/2003
 JP S4867159 9/1973
 JP S50106061 8/1975
 JP H10277070 10/1998
 JP 2000325358 3/2000
 JP 2002052030 2/2002
 JP 2002221218 8/2002
 SU 371359 2/1973
 WO 8909030 10/1989
 WO 8912431 12/1989
 WO 9116018 10/1991
 WO 9116020 10/1991
 WO 9203100 3/1992
 WO 9321848 11/1993
 WO 9325161 12/1993
 WO 9410927 5/1994
 WO 9410944 5/1994
 WO 9426191 11/1994
 WO 9428824 12/1994
 WO 9501132 1/1995
 WO 9513755 5/1995

(56)

References Cited

FOREIGN PATENT DOCUMENTS			WO		
WO	95/13755	5/1995	WO	2005072632	8/2005
WO	9528889	11/1995	WO	2005082262	9/2005
WO	9531947	11/1995	WO	2005087121	9/2005
WO	9535067	12/1995	WO	2005099400	10/2005
WO	9606576	3/1996	WO	2005102195	11/2005
WO	9621396	7/1996	WO	2005104969	11/2005
WO	9625104	8/1996	WO	2006005198	1/2006
WO	9628105	9/1996	WO	2006017616	2/2006
WO	9628118	9/1996	WO	2006020530	2/2006
WO	9641582	12/1996	WO	WO2006/012088	2/2006
WO	9714366	4/1997	WO	WO2006/028537	3/2006
WO	9714368	4/1997	WO	2006042188	4/2006
WO	9727812	8/1997	WO	2006047711	5/2006
WO	9730649	8/1997	WO	2006054111	5/2006
WO	9737604	10/1997	WO	2006065607	6/2006
WO	9737605	10/1997	WO	2006066685	6/2006
WO	9812977	4/1998	WO	2006068711	6/2006
WO	9815233	4/1998	WO	2006071742	7/2006
WO	9825534	6/1998	WO	2006079531	8/2006
WO	9832386	7/1998	WO	2006096240	9/2006
WO	9834554	8/1998	WO	2006096351	9/2006
WO	9834556	8/1998	WO	2006104874	10/2006
WO	9838924	9/1998	WO	2006110463	10/2006
WO	9903415	1/1999	WO	2006116437	11/2006
WO	9905980	2/1999	WO	2006119447	11/2006
WO	9932084	7/1999	WO	WO2006/119241	11/2006
WO	9938463	8/1999	WO	2007002409	1/2007
WO	9947083	9/1999	WO	2007038350	4/2007
WO	9949802	10/1999	WO	2007040750	4/2007
WO	0015125	3/2000	WO	2007040888	4/2007
WO	0022997	4/2000	WO	2007041702	4/2007
WO	0027297	5/2000	WO	2007053566	5/2007
WO	0072769	7/2000	WO	2007060534	5/2007
WO	0065268	11/2000	WO	2007075454	7/2007
WO	0066045	11/2000	WO	2007081849	8/2007
WO	0106940	2/2001	WO	2007087469	8/2007
WO	0108574	2/2001	WO	2007087628	8/2007
WO	0110317	2/2001	WO	2007090021	8/2007
WO	0115612	3/2001	WO	2007092056	8/2007
WO	0122893	4/2001	WO	2007092870	8/2007
WO	0128435	4/2001	WO	2007097905	8/2007
WO	0128436	4/2001	WO	2007109470	9/2007
WO	0145576	6/2001	WO	2007114834	10/2007
WO	0149191	7/2001	WO	2007118045	10/2007
WO	0158370	8/2001	WO	2007121030	10/2007
WO	0167972	9/2001	WO	2007121057	10/2007
WO	0167974	9/2001	WO	2007121271	10/2007
WO	0222030	3/2002	WO	WO2007/118045	10/2007
WO	0234150	5/2002	WO	2007123920	11/2007
WO	02054966	7/2002	WO	2007124222	11/2007
WO	02102259	12/2002	WO	2007124249	11/2007
WO	03007828	1/2003	WO	2007127595	11/2007
WO	03026523	4/2003	WO	2007127604	11/2007
WO	03037199	5/2003	WO	2007130835	11/2007
WO	03047442	6/2003	WO	2007130840	11/2007
WO	03068083	8/2003	WO	2007130941	11/2007
WO	03068088	8/2003	WO	WO2007/124222	11/2007
WO	03084415	10/2003	WO	WO2007/130835	11/2007
WO	03094699	11/2003	WO	WO2007/130840	11/2007
WO	2004021900	3/2004	WO	WO2007/130941	11/2007
WO	2004022108	3/2004	WO	2007138270	12/2007
WO	2004041100	5/2004	WO	2007146032	12/2007
WO	2004075778	9/2004	WO	2008005740	1/2008
WO	2004089245	10/2004	WO	2008006098	1/2008
WO	2004098452	11/2004	WO	2008008511	1/2008
WO	2004105577	12/2004	WO	2008013892	1/2008
WO	2004107997	12/2004	WO	2008027860	3/2008
WO	2005000136	1/2005	WO	2008033742	3/2008
WO	2005000137	1/2005	WO	2008036975	3/2008
WO	2005013839	2/2005	WO	2008037256	4/2008
WO	2005018466	3/2005	WO	2008039777	4/2008
WO	2005018471	3/2005	WO	2008042948	4/2008
WO	2005020829	3/2005	WO	2008048923	4/2008
WO	2005030068	4/2005	WO	2008048953	4/2008
WO	2005065374	7/2005	WO	2008069420	6/2008
			WO	2008070716	6/2008
			WO	2008134703	6/2008
			WO	2008078163	7/2008
			WO	2008082737	7/2008

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO2008/088731	7/2008
WO	2008100590	8/2008
WO	2008118295	10/2008
WO	2008119006	10/2008
WO	2008124772	10/2008

OTHER PUBLICATIONS

Xia Spinal System Brochure, Stryker Howmedica Osteonics, no publish date.

Silhouette Spinal Fixation System Brochure, Sulzer Medica Spine-Tech, no publish date.

The Strength of Innovation Advertisement, Blackstone Medical Inc., no publish date.

The Moss Miami 6.0mm System Advertisement, author unknown, no publish date.

European Search Report, EP 14189707.4, dated Feb. 25, 2015.

EBI Omega 21 Brochure, EBI Spine Systems, pub. 1999.

Claris Instrumentation Brochure, G Med, pub. 1997.

VLS System Variable Locking Screw Brochure, Interpore Cross International, 1999.

CD Horizon M8 Multi Axial Screw Spinal System Brochure, Medtronic Sofamor Danek, no publish date.

The Rod Plate System Brochure, Stryker Howmedica Osteonics, pub. Oct. 1999.

SDRS Surgical Dynamics Rod System Brochure, Surgical Dynamics, pub. 1998-99.

Versalok Low Back Fixation System Brochure, Wright Medical Technology, Inc., pub. 1997.

* cited by examiner

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.





Fig. 5.





Fig. 7.

Fig. 8.




Fig. 10.




Fig. 11.





Fig. 9.






Fig. 12.




Fig. 13.




Fig. 15.




Fig. 16.




Fig. 14.





Fig. 17.




Fig. 19.





Fig. 21.






Fig.23.




Fig.24.





Fig.25.







Fig. 30.




Fig.31.




Fig.32.




Fig.33.




Fig. 34.







Fig. 35.






Fig. 38.

Fig. 39.





Fig. 40.



**POLYAXIAL BONE ANCHOR WITH
HELICAL CAPTURE CONNECTION, INSERT
AND DUAL LOCKING ASSEMBLY**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. [60/000,964] 61/000,964, filed Oct. 30, 2007, incorporated by reference herein. This application is also a continuation-in-part of U.S. patent application Ser. No. 11/522,503 filed Sep. 14, 2006 that is a continuation-in-part of U.S. patent application Ser. No. 11/024,543 filed Dec. 20, 2004, both of which are incorporated by reference herein. *U.S. patent application Ser. No. 11/522,503 claims the benefit of U.S. Prov. Pat. App. Ser. Nos. 60/722,300, filed Sep. 30, 2005; 60/725,445, filed Oct. 11, 2005; 60/728,912, filed Oct. 21, 2005; 60/736,112, filed Nov. 10, 2005; 60/832,644, filed Jul. 21, 2006.* This application is also a continuation-in-part of U.S. patent application Ser. No. 11/140,343 filed May 27, 2005, incorporated by reference herein. This application is also a continuation-in-part of U.S. patent application Ser. No. 10/986,377 filed Nov. 10, 2004, incorporated by reference herein. This application is also a continuation-in-part of U.S. patent application Ser. No. 10/818,555 filed Apr. 5, 2004 that is a continuation of U.S. patent application Ser. No. 10/464,633 filed Jun. 18, 2003, now U.S. Pat. No. 6,716,214, both of which are incorporated by reference herein.

BACKGROUND OF THE INVENTION

The present invention is directed to polyaxial bone screws for use in bone surgery, particularly spinal surgery, and cooperating elongate connecting members that are at least somewhat plastically deformable. Such screws have a receiver or head that can swivel about a shank of the bone screw, allowing the receiver to be positioned in any of a number of angular configurations relative to the shank.

Many spinal surgery procedures require securing various implants to bone and especially to vertebrae along the spine. For example, elongate members, such as solid rigid rods are often utilized that extend along the spine to provide support to vertebrae that have been damaged or weakened due to injury or disease. Such elongate members must be supported by certain vertebrae and support other vertebrae.

The most common mechanism for providing vertebral support is to implant bone screws into certain bones which then in turn support the elongate member or are supported by the elongate member. Bone screws of this type may have a fixed head or receiver relative to a shank thereof. In the fixed bone screws, the head cannot be moved relative to the shank and the rod or other elongate member must be favorably positioned in order for it to be placed within the head. This is sometimes very difficult or impossible to do. Therefore, polyaxial bone screws are commonly preferred.

Polyaxial bone screws allow rotation of the receiver about the shank until a desired rotational position of the receiver is achieved relative to the shank. Thereafter, a rod or other

elongate connecting member can be inserted into the receiver and eventually the rod and the receiver are locked or fixed in a particular position relative to the shank.

A variety of polyaxial or swivel-head bone screw assemblies are available. One type of bone screw assembly includes an open head or receiver that allows for placement of a rod or other elongate member within the receiver. A closure top or plug is then used to capture the rod in the receiver of the screw. Thus, the closure top or plug pressing against the rod not only locks the rod in place but also locks the bone screw shank in a desired angular position with respect to the receiver. A drawback to such a system occurs when the rod or other elongate connecting member is made from a material that exhibits creep or viscoelastic behavior. Creep is a term used to describe the tendency of a material to move, flow or to deform permanently to relieve stresses. Material deformation occurs as a result of long term exposure to levels of stress that are below the yield or ultimate strength of the material. Rods and other longitudinal connecting members made from polymers, such as polyetheretherketone (PEEK), especially pure PEEK and rubbers, have a greater tendency to exhibit creep, than, for example metals or metal alloys, such as stainless steel, titanium and nickel titanium (commonly referred to by its trade name Nitinol). When a rod or other longitudinal connecting member exhibits creep deformation over time, the closure top may no longer tightly engage the connecting member. This in itself is not necessarily problematic. However, such loosening also results in loosening of the frictional engagement between the receiver and the bone screw shank that locks the angular orientation of the shank with respect to the receiver. Body movement and stresses may then result in undesirable pivoting of the shank with respect to the receiver causing misalignment, greater stress and further loosening of the various polyaxial bone screw components.

It is known to equip a bone screw assembly with an upper and/or a lower pressure insert located within the receiver for engaging and closely holding one or more surfaces of a rod or other longitudinal connecting member. Nested closure tops are known in the art that include a fastening portion having an outer thread for engaging an interior threaded surface of the receiver arms and also an inner thread for engaging a threaded set screw. The fastening portion of the closure top is disposed within the receiver arms but does not operationally abut against a rod or other longitudinal connecting member. Rather, the fastening portion abuts against one or more pressure inserts also located in the receiver that in turn engage a polyaxial bone screw mechanism so that the shank may be set and locked at a desired angular position with respect to the receiver prior to locking the rod or other longitudinal connecting member in place by direct or indirect pressure thereon by the independently rotatable inner set screw. However, one of the drawbacks to such a polyaxial implant is that to maintain a relatively non-bulky, low profile assembly, the numerous inserts and other component parts of such an assembly have thin walls that provide the desired low profile but otherwise lack sufficient strength to withstand the stresses placed thereon by the human body and other component parts of the bone screw assembly. In order to remedy this problem, it is further known in the art to equip such an assembly with an outer nut (located outside of the receiver arms) to keep the arms of the receiver from splaying and aid in securely holding any inserts and other small component parts within the receiver of the bone screw assembly so that the parts do not loosen or disassemble within the body. However, such a nut adds undesirable bulk

to the assembly and may lead to undesirable interference with vertebrae and other medical implants.

SUMMARY OF THE INVENTION

A polyaxial bone screw assembly of the present invention includes a shank having a generally elongate body with an upper end portion and a lower threaded portion for fixation to a bone. The bone screw assembly further includes a receiver having a top portion and a base. The top portion is open and has a channel. The base includes an inner seating surface partially defining a cavity and has a lower aperture or opening. The channel of the top portion communicates with the cavity, which in turn communicates with an opening to an exterior of the base. The shank upper portion is disposed in the receiver cavity and the shank extends through the receiver base opening. A shank capture connection is provided by the upper portion that includes a first helical guide and advancement structure that mates with a second helical guide and advancement structure on a retaining structure, the retaining structure configured for polyaxial motion with respect to the receiver. The shank has an upper surface that exclusively engages a compression insert that in turn engages a longitudinal connecting member being supported within the receiver. In certain embodiments, the compression insert includes a planar seat and spaced planar sides for closely receiving a variety of elongate connecting members including members having planar or cylindrical surfaces. A closure structure of the invention may be dual locking and include an outer fastener and an inner set screw. The outer fastener is sized and shaped for engaging the compression insert independent of the longitudinal connecting member for securing the assembly in a wide range of angular orientations. The inner set screw exclusively engages the longitudinal connecting member. In an illustrated embodiment the outer fastener includes a pair of opposed flanges for interlocking engagement with a pair of opposed flange tracks of the receiver. In another embodiment, the outer fastener includes an outer helical flange for interlocking engagement with a discontinuous helical guide and advancement structure located on the receiver.

OBJECTS AND ADVANTAGES OF THE INVENTION

Objects of the invention include one or more of the following: providing a polyaxial bone screw having a shank with an integral upper end portion that threadably mates with a retaining structure configured for polyaxial motion with respect to the receiver prior to locking; providing such a polyaxial bone screw that includes a pressure insert that exerts pressure exclusively on an upper surface of the integral and stronger shank upper end portion, the upper surface being substantially spaced from the retaining structure; providing such an implant wherein all of the parts remain together and do not separate; providing a lightweight, low profile polyaxial bone screw that assembles in such a manner that the components cooperate to create an overall structure that prevents unintentional disassembly; providing a polyaxial bone screw that provides independent locking for the bone screw shank and the longitudinal connecting member; providing such an assembly that includes a longitudinal connecting member that may be of non-circular or circular cross-section; providing such an assembly that remains in a locked position even if the longitudinal connecting member undergoes deformation such as creep; providing a polyaxial bone screw with

features that provide adequate frictional or gripping surfaces for bone implantation tools and may be readily, securely fastened to each other and to bone; and providing apparatus and methods that are easy to use and especially adapted for the intended use thereof and wherein the apparatus are comparatively inexpensive to make and suitable for use.

Other objects and advantages of this invention will become apparent from the following description taken in conjunction with the accompanying drawings wherein are set forth, by way of illustration and example, certain embodiments of this invention.

The drawings constitute a part of this specification and include exemplary embodiments of the present invention and illustrate various objects and features thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an enlarged, partial and exploded perspective view of a bone screw assembly according to the invention including a bone screw shank, a receiver, a lower compression insert and a closure structure having an outer fastener and an inner set screw and shown with a longitudinal connecting member in the form of a rod.

FIG. 2 is an enlarged front elevational view of the receiver of FIG. 1.

FIG. 3 is an enlarged cross-sectional view taken along the line 3-3 of FIG. 1.

FIG. 4 is an enlarged side elevational view of the receiver of FIG. 1.

FIG. 5 is an enlarged cross-sectional view taken along the line 5-5 of FIG. 4.

FIG. 6 is an enlarged top plan view of the receiver of FIG. 1.

FIG. 7 is an enlarged side elevational view of the lower compression insert of FIG. 1.

FIG. 8 is a cross-sectional view taken along the line 8-8 of FIG. 7.

FIG. 9 is an enlarged top plan view of the lower compression insert of FIG. 1.

FIG. 10 is an enlarged and partial perspective view of the shank, receiver and compression insert of FIG. 1, shown assembled.

FIG. 11 is a second enlarged and partial perspective view, similar to FIG. 10.

FIG. 12 is an enlarged side elevational view of the closure structure of FIG. 1.

FIG. 13 is an enlarged top plan view of the closure structure of FIG. 1.

FIG. 14 is an enlarged top plan view of the set screw of the closure structure of FIG. 1.

FIG. 15 is an enlarged and exploded front elevational view of the closure structure of FIG. 1.

FIG. 16 is an enlarged perspective view of the closure structure of FIG. 1 with portions removed to show the detail thereof.

FIG. 17 is an enlarged and partial front elevational view of the assembly of FIG. 1 shown in a stage of assembly and with portions broken away to show the detail thereof.

FIG. 18 is an enlarged and partial side elevational view of the assembly of FIG. 1 shown fully assembled and with a break-off top removed.

FIG. 19 is a cross-sectional view taken along the line 19-19 of FIG. 18.

FIG. 20 is an enlarged and partial perspective view of the assembly of FIG. 1 shown with a bar in lieu of the rod shown in FIG. 1 and with portions broken away to show the detail thereof.

5

FIG. 21 is an enlarged and partial front elevational view of the assembly shown in FIG. 20.

FIG. 22 is an enlarged, partial and exploded perspective view of a second, alternative bone screw assembly according to the invention including a bone screw shank, a receiver, a retaining structure, a first lower compression insert, a second upper compression insert and a closure member and shown with a longitudinal connecting member in the form of a rod.

FIG. 23 is an enlarged front elevational view of the closure member of FIG. 22.

FIG. 24 is a cross-sectional view taken along the line 24-24 of FIG. 23.

FIG. 25 is an enlarged top plan view of the closure member of FIG. 23.

FIG. 26 is an enlarged perspective view of the upper compression insert of FIG. 22.

FIG. 27 is an enlarged front elevational view of the upper compression insert of FIG. 22.

FIG. 28 is an enlarged side elevational view of the upper compression insert of FIG. 22.

FIG. 29 is an enlarged and partial cross-sectional view of the closure member, similar to FIG. 24 and further showing the upper compression insert in front elevation prior to attachment to the closure member.

FIG. 30 is an enlarged and partial cross-sectional view of the closure member and front elevational view of the upper compression member, similar to FIG. 29, showing the upper compression member rotatably attached to the closure member.

FIG. 31 is an enlarged front elevational view of the bone screw shank of FIG. 22 with portions broken away to show the detail thereof.

FIG. 32 is an enlarged front elevational view of the receiver and retaining structure of FIG. 22 with portions broken away to show the detail thereof and further showing the retaining structure in phantom in an early step of assembly of the bone screw assembly of FIG. 22.

FIG. 33 is an enlarged and partial front elevational view of the receiver, the retaining structure and the bone screw shank of FIG. 22 with portions broken away to show the detail thereof and shown in a step of assembly subsequent to that shown in FIG. 32.

FIG. 34 is a reduced front elevational view of the receiver, the bone screw shank and the retaining structure of FIG. 22 with portions broken away to show the detail thereof and shown with a tool driving the bone screw shank into a vertebrae, also with portions broken away to show the detail thereof.

FIG. 35 is an enlarged and partial front elevational view of the receiver, bone screw shank, retaining structure and lower compression insert of FIG. 22 with portions broken away to show the detail thereof and shown with the rod illustrated in FIG. 22, also with portions broken away to show the detail thereof.

FIG. 36 is an enlarged and partial front elevational view of the assembly of FIG. 22 with portions broken away to show the detail thereof and further showing the upper compression insert and closure member partially inserted in the receiver.

FIG. 37 is an enlarged and partial front elevational view similar to FIG. 36 showing the upper compression insert and closure member fully seated in the receiver prior to removal of the closure member break-off head.

FIG. 38 is an enlarged and partial front elevational view of the assembly of FIG. 22 with portions broken away to show the detail thereof, and further showing the closure member break-off head removed.

6

FIG. 39 is an enlarged and partial front elevational view of an alternative embodiment according to the invention, similar to the assembly of FIG. 22, but without the upper compression insert, shown assembled, with break-off top removed and with portions broken away to show the detail thereof and further showing the assembly cooperating with a longitudinal connecting member in the form of a bar of rectangular cross-section in lieu of the rod shown in FIG. 22.

FIG. 40 is an enlarged and partial front elevational view of another embodiment according to the invention, similar to the assembly of FIG. 22, but with a different compression insert, shown assembled with the break-off top removed, with portions broken away to show the detail thereof and further showing the assembly cooperating with a longitudinal connecting member in the form of a bar of rectangular cross-section.

DETAILED DESCRIPTION OF THE INVENTION

As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which may be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present invention in virtually any appropriately detailed structure. It is also noted that any reference to the words top, bottom, up and down, and the like, in this application refers to the alignment shown in the various drawings, as well as the normal connotations applied to such devices, and is not intended to restrict positioning of bone attachment assemblies of the application and cooperating connecting members in actual use.

With reference to FIGS. 1-21, the reference number 1 generally represents an embodiment of a polyaxial bone screw apparatus or assembly according to the present invention. The assembly 1 includes a shank 4 that further includes a threaded body 6 integral with an upper portion 8; a receiver 10; a lower compression insert 12; and a dual closure structure, generally 14. The shank 4, receiver 10, and compression insert 12 are typically factory assembled prior to implantation of the shank body 6 into a vertebra (not shown). However, if desirable in certain situations, the shank may be implanted into a vertebra first and thereafter the receiver threadably connected thereto.

With further reference to FIG. 1, the closure structure 14 further includes an outer fastener 18 and an inner set screw 20 for engaging a longitudinal connecting member such as a rod 21 having a cylindrical surface 22 shown in FIGS. 1 and 17-19, for example, or a longitudinal connecting member that does not have a circular cross-section, such as the bar 24 having a square or rectangular cross-section and planar surfaces 25 shown in FIGS. 20 and 21. The outer fastener 18 presses against the compression insert 12 that in turn presses upon the shank upper portion 8 which biases the portion 8 into fixed frictional contact with the receiver 10, so as to fix the rod 21 or the bar 24 relative to the vertebra (not shown). The receiver 10 and the shank 4 cooperate in such a manner that the receiver 10 and the shank 4 can be secured at any of a plurality of angles, articulations or rotational alignments relative to one another and within a selected range of angles both from side to side and from front to rear, to enable flexible or articulated engagement of the receiver 10 with respect to the shank 4 until both are locked or fixed

relative to each other near the end of an implantation procedure. The rod 21 or the bar 24 may be advantageously manipulated independently of locking the shank 4 with respect to the receiver 10 and then ultimately locked into place in the receiver 10 by rotation of the set screw 20 into direct engagement with the rod 21 or bar 24. Thus, if the rod 21 or the bar 24 is made from a material such as rubber or PEEK, that exhibits any viscoelastic flow or creep, any resultant loosening of the rod 21 or the bar 24 with respect to the set screw 20 would have no impact on the security of the polyaxial locking of the shank 4 with respect to the receiver 10 provided by the pressure placed on the polyaxial mechanism by the outer fastener 18 through the insert 12.

With particular reference to FIGS. 1, 18 and 19, the shank 4 is elongate, with the shank body 6 having a helically wound bone implantable thread 28 extending from near a neck 30 located adjacent to the upper portion 8 to a tip 32 of the body 6 and extending radially outwardly therefrom. During use, the body 6 utilizing the thread 28 for gripping and advancement is implanted into the vertebra (not shown) leading with the tip 32 and driven down into the vertebra with an installation or driving tool, so as to be implanted in the vertebra to near the neck 30, and as is described more fully in the paragraphs below. The shank 4 has an elongate axis of rotation generally identified by the reference letter A.

The neck 30 extends axially upwardly from the shank body 6. The neck 30 is of slightly reduced radius as compared to an adjacent top 33 of the threaded body 6. Further extending axially upwardly from the neck 30 is the shank upper portion 8 that provides a connective or capture apparatus disposed at a distance from the threaded body top 33 and thus at a distance from the vertebra when the body 6 is implanted in the vertebra.

The shank upper portion 8 is configured for a polyaxial connection between the shank 4 and the receiver 10 and capturing the shank 4 upper portion 8 in the receiver 10. The neck 30 extends axially upwardly from the shank body 6 to a base 34 of the upper portion 8. The upper portion 8 has an outer partially spherically shaped surface 40 extending from the base 34 to a planar top portion 42. Formed in the top portion 42 is an internal drive mechanism 44 illustrated as a hex drive. The internal drive 44 is coaxial with the shank 4. The drive 44 is sized and shaped for engagement with a driving tool (not shown) that is received by the drive 44 so as to form a socket and mating projection combination for both operably driving and rotating the shank body 6 into a vertebra.

The illustrated base 34 of the portion 8 has a smooth surface, but it is foreseen that the base 34 may have a high-friction or roughened surface, such as a scored or knurled surface. Formed on the spherical surface 40 is a helical guide and advancement structure 48. The guide and advancement structure 48 retains the substantially spherical outer shape of the surface 40 at a crest thereof, but may be otherwise described as a substantially buttress thread form, sized and shaped to mate with a cooperating guide and advancement structure 50 disposed on an inner surface 52 of the receiver 10 disposed adjacent to and defining an opening 54 of a lower end or bottom 56 of the receiver 10 (see FIGS. 2 and 3). Preferably, the guide and advancement structure 48 is relatively thick and heavy to give strength to the thread and prevent the thread from being easily bent or deformed when axial pressure is applied to the shank 4 to maintain the upper portion 8 in the receiver 10. The guide and advancement structure 48 winds about the spherical surface 40 in a generally helical pattern or configuration that is typical of threads and can have various pitches, be clockwise or

counterclockwise advanced, or vary in most of the ways that conventional buttress or square threads vary. The guide and advancement structure 48 has a leading surface or flank 58 and a trailing surface or flank 59. As used herein, the terms leading and trailing refer to the direction of advancement of the upper portion 8 into the guide and advancement structure 50 of the receiver 10 aligning the axis A of the shank 4 with an elongate axis of rotation B of the receiver 10 and directing the upper portion 8 toward the receiver 10, as shown by the straight arrow C illustrated in FIG. 1. Although the substantially buttress thread form 48 is described herein, it is foreseen that other thread types, such as square threads, V-threads, inverted thread types, other thread-like or non-thread-like guide and advancement structures, such as flange form helically wound advancement structures may be utilized according to the invention.

Advancement of the upper portion 8 into the receiver 10 is accomplished by rotating the shank 4 in a clockwise or counterclockwise direction about the axes A and B and into the receiver 10. A crest surface 60 connecting the leading surface 58 and the trailing surface 59 is a loading surface after the upper portion 8 is fully disposed in the receiver 10. Although discontinuous, the spherical surface 40 that includes the crest surface 60 has an outer radius that is approximately equal to a radius of an inner seating surface of the receiver 10, allowing for slidable mating contact between the surface 60 and the inner seating surface of the receiver 10.

An upper portion 62 of the spherical surface 40 located adjacent to the top planar surface 42 is advantageously substantially spherical for sliding engagement and ultimate positive frictional mating engagement with the compression insert 12, when the bone screw assembly 1 is assembled, as shown in FIG. 19 and in any alignment of the shank 4 relative to the receiver 10. In certain embodiments, the surface 62 is smooth. While not required in accordance with the practice of the invention, the surface 62 may be scored or knurled to further increase frictional positive mating engagement between the surface 62 and the compression insert 12.

The shank 4 shown in the drawings is cannulated, having a small central bore 64 extending an entire length of the shank 4 along the axis A. The bore 64 is defined by an inner cylindrical wall of the shank 4 and has a circular opening at the shank tip 32 and an upper opening communicating with the internal drive 44. The bore 64 provides a passage through the shank 4 interior for a length of wire (not shown) inserted into the vertebra (not shown) prior to the insertion of the shank body 6, the wire providing a guide for insertion of the shank body 6 into the vertebra (not shown).

To provide a biologically active interface with the bone, the threaded shank body 6 may be coated, perforated, made porous or otherwise treated. The treatment may include, but is not limited to a plasma spray coating or other type of coating of a metal or, for example, a calcium phosphate; or a roughening, perforation or indentation in the shank surface, such as by sputtering, sand blasting or acid etching, that allows for bony ingrowth or ongrowth. Certain metal coatings act as a scaffold for bone ingrowth. Bio-ceramic calcium phosphate coatings include, but are not limited to: alpha-tri-calcium phosphate and beta-tri-calcium phosphate ($\text{Ca}_3(\text{PO}_4)_2$), tetra-calcium phosphate ($\text{Ca}_4\text{P}_2\text{O}_9$), amorphous calcium phosphate and hydroxyapatite ($\text{Ca}_{10}(\text{PO}_4)_6(\text{OH})_2$). Coating with hydroxyapatite, for example, is desirable as hydroxyapatite is chemically similar to bone with respect to

mineral content and has been identified as being bioactive and thus not only supportive of bone ingrowth, but actively taking part in bone bonding.

Referring to FIGS. 1-6 and 10-11, the receiver 10 has a generally squared-off U-shaped appearance with a partially cylindrical inner profile and a substantially faceted outer profile; however, the outer profile could also be of another configuration, for example, curved or cylindrical. The receiver axis of rotation B, as shown in FIG. 1, is aligned with the axis of rotation A of the shank 4 during assembly of the receiver 10 with the shank 4 and the insert 12. After the receiver 10 is pivotally attached to the shank 4, and the assembly 1 is implanted in a vertebra (not shown), the axis B is typically disposed at an angle with respect to the axis A of the shank 4.

The receiver 10 includes a base 70 integral with a pair of opposed substantially similar or identical upstanding opposed arms 72 and 72' forming a squared-off U-shaped cradle and defining a channel 76 between the arms 72 and 72' with an upper opening 77 and a lower seat 78, the channel 76 sized and shaped for operably receiving the rod 21 or the bar 24. Each of the arms 72 and 72' has an interior surface 80 and 80', respectively, each having an inner cylindrical profile with opposed sloping interlocking flanged recesses or tracks 82 and 82' configured to mate under rotation with a pair of opposed interlocking flange forms 84 and 84' on the fastener 18, as described more fully below. Each of the tracks 82 and 82' run between and through pairs of parallel side surfaces 86 and 86' of respective arms 72 and 72'. With particular reference to FIG. 19, each track 82 and 82' is defined by a respective lower substantially planar surface 88 and 88' running about the respective cylindrical interior surface 80 and 80'; a respective outer cylindrical surface 90 and 90' running substantially parallel to the respective surfaces 80 and 80', and a respective upper flanged portion 92 and 92' also running about the respective interior surfaces 80 and 80' and having a respective surface 94 and 94' that extends downwardly (toward the base 70) and inwardly (toward the axis B) from the respective surface 90 and 90'. As best shown in FIG. 5, the tracks 82 and 82' are substantially identical in form and are located similarly on the respective arms 72 and 72' with the exception that such tracks slope in opposite directions, each having a higher end disposed near a respective planar stepped or lower top surface portion 96 and 96' of the respective arms 72 and 72' and a lower end disposed near a respective planar upper top surface 98 and 98' of the arms 72 and 72'. The respective lower surfaces 96 and 96' connected to respective upper surface 98 and 98' by respective planar walls or stops 100 and 100'. The walls or stops 100 and 100' are each disposed parallel to the axis B.

Opposed tool engaging apertures 105 are formed on or through surfaces of the arms 72 and 72' that may be used for holding the receiver 10 during assembly with the shank 4 and the retainer structure 12 and also during the implantation of the shank body 6 into a vertebra (not shown). It is foreseen that tool receiving grooves or apertures may be configured in a variety of shapes and sizes and be disposed at other locations on the receiver arms 72 and 72'. A pair of opposed spring tabs 106, each having an upper body portion integral with a respective arm 72 or 72', and a lower insert engaging surface 110 extending downwardly and inwardly from the respective upper body portion. The tabs 106 are generally directed towards the axis B and extend downwardly away from the guide tracks 82 and 82'. The lower end surfaces 110 are thus positioned to engage the compression insert 12 and hold such insert in a desired position as will be

described in greater detail below. The tabs 106 are typically initially disposed parallel to the axis B and then a tool (not shown) is inserted into the aperture 105 from outside of the receiver 10 to engage and push the respective tab 106, thereby bending the tab 106 inwardly in a direction toward the axis B until the tab 106 is at a desired angular position, such as is illustrated in FIG. 5. Such bending of the tabs 106 may be performed either prior to or after assembly of the receiver 10 with the shank 4 and the compression insert 12. In the illustrated embodiment, the tabs 106 are bent inwardly prior to installation with the components 4 and 12. It is also foreseen that the tabs 106 may be machined or otherwise pre-fabricated to be angled or directed toward the axis B so as to engage the insert 12 as shown in the drawing figures. The illustrated tabs 106 are resilient, having a spring-like nature. Thus, when operatively cooperating with the insert 12, the tabs 106 bias against the insert 12, holding such insert in a desired position; and yet the tabs 106 are flexible enough to allow a user to make desired adjustments of the position of the insert 12 within the receiver 10.

With further reference to FIGS. 1-5, communicating with and located beneath the channel 76 of the receiver 10 is a chamber or cavity, generally 112, defined in part by an inner substantially cylindrical surface 114 and also the lower internal surface 52 previously described herein that includes the guide and advancement structure 50 and also includes a substantially spherical seating surface portion 116. The cylindrical surface 114 that defines a portion of the cavity 112 opens upwardly into the channel 76. The inner surface 116 that is located below the surface 114 is sized and shaped for mating with the shank upper portion 8 spherical surface 40 that includes the crest surfaces 60.

As described above, the surface portion 116 is part of the inner surface 52 that includes the opening 54. The opening 54 communicates with both the cavity 112 and the receiver lower exterior or bottom 56 of the base 70. The opening 54 is substantially coaxially aligned with respect to the rotational axis B of the receiver 10. The opening 54 is also sized and shaped to be smaller than an outer radial dimension of the shank upper portion 8 after the portion 8 has been threadably rotated through the opening 54, so as to form a restriction to prevent the portion 8 from passing through the cavity 112 and out into the lower exterior 56 of the receiver 10 during operation thereof.

With particular reference to FIGS. 1 and 7-11 and 19, the compression insert 12 is sized and shaped to be received by and downloaded into the receiver 10 through the opening 77. In operation, a portion of the insert 12 is disposed between the rod 21 or the bar 24 and the upper portion 8 of the bone screw 4 as illustrated, for example, in FIG. 19. In operation, the closure structure 14 outer fastener 18 presses directly upon the insert 12 that in turn presses upon the shank upper portion 8, pressing the upper portion 8 against the seating surface portion 116 of the receiver 10, resulting in frictional engagement and locking of the angular position of the bone screw shank 4 with respect to the receiver 10 while allowing for further manipulation of the rod 21 or bar 24 until such rod or bar is locked into place by engagement with the inner set screw 20. The compression insert 12 has an operational central axis D that is the same as the central axis B of the receiver 10.

With particular reference to FIGS. 7-9, the compression insert 12 has a central channel or through bore substantially defined by an inner cylindrical surface 120 and an inner partially spherical surface 122, both having the central axis D. The compression insert 12 through bore is sized and shaped to receive a driving tool (not shown) therethrough

11

that engages the shank drive feature 44 when the shank body 6 is driven into bone. The surface 122 is sized and shaped to cooperate with the spherical surface 62 of the shank upper portion 8 such that the surface 122 slidingly and pivotally mates with the spherical surface 62. The surface 122 may include a roughening or surface finish to aid in frictional contact between the surface 122 and the surface 62, once a desired angle of articulation of the shank 4 with respect to the receiver 10 is reached.

The compression insert 12 also includes a pair of arms 124 with a squared-off U-shaped surface or saddle 126 formed therebetween. The saddle 126 defines a channel that communicates with the bore defined by the cylindrical surface 120 and the spherical surface 122. The saddle 126 is substantially defined by a pair of planar opposed parallel surfaces 128 and a planar bottom or seating surface 130, the surfaces 128 and 130 being sized and shaped to closely receive the cylindrical rod 21 or the bar 24 planar surfaces 25. The saddle 126 extends from top surfaces 132 to the bottom seating surface 130. A base having an outer cylindrical surface 134 is disposed between the saddle 126 and an annular bottom surface 135. The cylindrical surface 134 also extends about the arms 124. Formed in the surface 124 and located centrally with respect to each arm 124 outer cylindrical surface is a shallow groove 136 having a substantially flat surface. In the illustrated embodiment a surface portion 137 disposed adjacent to each groove 136 and located between such groove 136 and the bottom surface 135 includes a plurality of ridges or other roughened surface features. The grooves 136 are sized and shaped to cooperate with the tabs 106 of the receiver 10 as will be described in greater detail below. The roughened surface portions 137 further cooperate with the tabs 106 to frictionally check or otherwise prohibit relative movement between the tabs 106 and such surfaces 137 during assembly and operation of the assembly 1. The grooves 136 may be of any shape, but are preferably elongate with the flat surface running parallel to the axis D and having a width that receives the respective tab 106. The illustrated bottom surface 135 is substantially planar and annular and disposed perpendicular to the axis D. Formed on the planar side surfaces 128 and also formed into the top surface 132 are a pair of opposed recesses 138, each recess having a cylindrical surface 140 running parallel to the axis D and a planar bottom surface 141 disposed perpendicular to the axis D. The recesses 138 are sized and shaped to provide clearance for the inner set screw 20 of the closure structure 14 as the set screw 20 is rotated down into engagement with the rod 21 or the bar 24 as will be described in greater detail below.

The compression or pressure insert 12 ultimately seats on the shank upper portion 8 and is disposed substantially in the upper cylindrical portion 114 of the cavity 112, with the tabs 106 engaging the insert 12 at the grooves 136, thereby holding the insert 12 in a desired alignment within the receiver 10 as will be described in greater detail below. In operation, the insert 12 extends at least partially into the receiver channel 76 such that the saddle 126 surface substantially contacts and engages the outer surface 22 of the rod 21 (or one of the planar surfaces 25 of the bar 24) when such rod or bar is placed in the receiver 10, keeping the rod or bar in spaced relation with the receiver 10 lower seating surface 78.

FIGS. 1 and 12-16 illustrate the nested closure structure or closure top 14 that includes the outer fastener 18 and the uploaded inner set screw 20 that are coaxial along a central axis E that in operation is the same as the axis B of the receiver 10. The fastener 18 further includes a base 146

12

integral or otherwise attached to a break-off head 148. The base 146 cooperates with the receiver 10 to capture the rod 21 or the bar 24 (or any other longitudinal connecting member) within the bone screw receiver 10. The break-off installation head 148 is in the form of a hex-shaped external drive feature having six planar surfaces 150 sized and shaped for engagement with a socket tool (not shown) for installing the fastener 14 to the bone screw receiver 10 and thereafter separating the break-off head 148 from the respective base 146 when installation torque exceeds selected levels. A through slot 151 formed in a top surface 152 of the break-off head 148 and disposed perpendicular to the axis E may also be utilized to manipulate and/or rotate the closure 14. A through-bore 154 extends along the axis E completely through the fastener 18 from the top surface 152 of the break-off head 148 to a bottom surface 156 of the base 146. As illustrated in FIG. 13, the portion of the bore 154 running through the break-off head 148 is sized and shaped to receive and provide some clearance around a tool (not shown) engaging an inner drive 158 of the inner set screw 20.

The base 146 of the fastener 18 is substantially cylindrical, having an external surface 160. The flange forms 84 and 84' project substantially radially and oppositely from the surface 160 near the bottom surface 156. A pair of opposed substantially flat wing members 164 and 164' also extend radially from the surface 160 and are located near a top surface 166 of the base 146. The flanges 84 and 84' are sized and shaped to slidingly mate with respective lower surfaces 88 and 88', cylindrical surfaces 90 and 90' and flanged portions 92 and 92' of the respective tracks 82 and 82' of the receiver 10. Inwardly facing surfaces 168 and 168' of the respective flanges 84 and 84' slidingly cooperate and engage the flanged portions 92 and 92', respectively, to provide an interlocking relationship between the fastener 18 and the receiver arms 72 and 72' and are thus splay resistant and do not exert radially outward forces on the arms of the receiver 10, thereby avoiding tendencies toward splaying of the receiver arms when the fastener 18 is tightly torqued into the receiver 10. The wing members 164 and 164' are plate-like with upper and lower parallel substantially planar surfaces. The wing members 164 and 164' are sized and shaped to slidingly mate with respective step surfaces 96 and 96' of the receiver 10 and abut against respective surfaces 100 and 100' when the flanges 84 and 84' are rotated into a final fixed frictional engagement with respective tracks 82 and 82' as illustrated, for example, in FIGS. 19 and 20.

At the fastener base 146 the bore 154 is substantially defined by a guide and advancement structure shown in the drawing figures as an internal V-shaped thread 176. The thread 176 is sized and shaped to receive the threaded set screw 20 therein as will be discussed in more detail below. Although a traditional V-shaped thread 176 is shown, it is foreseen that other types of helical guide and advancement structures may be used. Near a top of the base 146, an abutment shoulder 178, extends uniformly radially inwardly. The abutment shoulder 178 is spaced from the V-shaped thread 176 and sized and shaped to be a stop for the set screw 20, prohibiting the set screw 20 from advancing upwardly out of the base 146. It is foreseen that alternatively, the set screw may be equipped with an outwardly extending abutment feature near a base thereof, with complimentary alterations made in the fastener base 146, such that the set screw 20 would be prohibited from advancing upwardly out of the top of the base 146 due to abutment of such outwardly extending feature against a surface of the base 146.

An inner cylindrical wall 180 separates the abutment shoulder 178 from the thread 176. The cylindrical wall 180

13

has a diameter equal to or slightly greater than a root or major diameter of the internal thread 176. The wall 180 partially defines a cylindrical space or passage for axial adjustable placement of the screw 20 with respect to the longitudinal connecting member 21 or 24.

The fastener break-off head 148 is integral or otherwise attached to the fastener base 146 at a neck or weakened region 182. The neck 182 is dimensioned in thickness to control the torque at which the break-off head 148 separates from the fastener base 146. The preselected separation torque of the neck 182 is designed to provide secure engagement between the fastener base 146 and the lower compression insert 12 that in turn presses against the shank upper portion 8, clamping the shank 4 in a desired angular orientation with respect to the receiver 10. The fastener 18 captures the longitudinal connecting member 21 or 24 within the receiver 10 before the head 148 separates, by abutting against the lower compression insert 12 without making contact with the rod 21 or the bar 24. For example, 120 inch pounds of force may be a selected break-off torque to lock the bone screw shank in place without placing any pressure on the rod 21 or the bar 24. Separation of the break-off head 148 leaves only the more compact base 146 of the fastener 18 installed in the bone screw receiver 10, so that the installed fastener 18 has a low profile. As will be described in greater detail below, the set screw 20 may then be rotated and moved downwardly into secure engagement with the rod 21 or the bar 24. Thus, if the rod 21 or bar 24 experiences viscoelastic flow and the engagement between the screw 20 and the rod 21 or bar 24 is loosened, such loosening will not loosen frictional engagement between the fastener base 146, the insert 12, the shank upper portion 8 and the surface 116 of the receiver 10.

The uploadable set screw 20 has a substantially annular and planar top 186 and a substantially annular and planar bottom 187. The screw 20 is substantially cylindrical in shape and coaxial with the fastener 18. The screw 20 includes an outer threaded cylindrical surface 188 extending from the top 186 to the bottom surface 187. The v-shape thread of the surface 188 is sized and shaped to be received by and mated with the inner thread 176 of the fastener base 146 in a nested, coaxial relationship.

As illustrated, for example, in FIGS. 13, 14 and 19, the set screw 20 includes a central aperture or drive 190 formed in the top 186 and sized and shaped for a positive, non-slip engagement by a set screw installment and removal tool (not shown) that may be inserted through the bore 154 of the fastener 18 and then into the drive aperture 190. With particular reference to FIGS. 16, 17 and 19, the central set screw aperture 190 cooperates with the central internal bore 154 of the fastener 18 for accessing and uploading the set screw 20 into the fastener 18 prior to engagement with the bone screw receiver 10. After the closure structure 14 is inserted and rotated into the tracks 82 and 82' of the bone screw receiver 10, and the break-off head 148 is broken off, the set screw 20 is rotated by a tool engaging the drive feature 190 to place the set screw bottom 187 into frictional engagement with the rod 21 or the bar 24. Such frictional engagement is therefore readily controllable by a surgeon so that rod 21 or the bar 24 may be readily manipulated until late in the surgery, if desired. Thus, at any desired time, the set screw 20 may be rotated to drive the screw 20 into fixed frictional engagement with the rod 21 or the bar 24 without varying the angular relationship between the receiver 10 and the bone screw shank 4.

It is foreseen that the set screw 20 may further include a cannulation through bore extending along a central axis

14

thereof for providing a passage through the closure 14 interior for a length of wire (not shown) inserted therein to provide a guide for insertion of the closure top into the receiver arms 72 and 72'.

The elongate longitudinal connecting member that are illustrated in this application include the cylindrical rod 21 and the bar 24 of square or other rectangular cross-section. A variety of shapes are possible, including but not limited to rods or bars of oval or other curved or polygonal cross-section. Furthermore, the rod 21 or bar 24 may be a component of a dynamic stabilization connecting member, with the cylindrical or bar-shaped portions sized and shaped for being received by the insert saddle 126 also being integral or otherwise fixed to a more flexible, bendable or damping component that extends between adjacent pairs of bone screw assemblies 1. Such a rod or bar component may be made from a variety of materials including metal, metal alloys or other suitable materials, including, but not limited to plastic polymers such as polyetheretherketone (PEEK), ultra-high-molecular weight-polyethylene (UHMWP), polyurethanes and composites, including composites containing carbon fiber, as well as resorbable materials, such as polylactic acids.

With particular reference to FIGS. 1 and 17, prior to the polyaxial bone screw assembly 1 being placed in use according to the invention, the shank upper portion is pre-loaded by insertion or bottom-loading into the receiver 10 through the opening 54. The upper portion 8 is aligned with the receiver 10, with the axes A and B aligned so that the buttress thread 48 of the upper portion 8 is inserted into and rotatably mated with the guide and advancement structure 50 on the receiver 10. The shank 4 is rotated in a clockwise or counter-clockwise direction to fully mate the structures 48 and 50, and the rotation is continued until the thread 48 disengages from the thread 50 and the upper portion 8 is fully disposed in the receiver cavity 112. The shank upper portion 8 is thus in a slidable and rotatable engagement with the receiver 10, while the upper portion 8 is maintained in the receiver 10 with the shank body 6 in pivotal or swivelable relation with the receiver 10. The shank body 6 can be pivoted or rotated through a substantial angular rotation relative to the receiver 10, both from side to side and from front to rear so as to substantially provide a universal or ball joint. The discontinuous spherical surface 40 defined by the crest surface 60 is in slidable engagement with the receiver spherical seating surface 116.

The compression or pressure insert 12 is then inserted or top loaded into the upper opening 77 of the channel 76 of the receiver 10 with the bottom surface 135 facing the top surface 42 of the shank upper portion 8 and the arms 124 aligned with the arms 72 and 72' of the receiver 10. As the insert 12 is moved downwardly toward the cavity 112, the tabs 106 are received in respective grooves 136. The tabs 106 press against the insert 12 at the grooves 136, allowing for some upward and downward adjustment of the insert 12. However, rotation of the insert 12 about the receiver axis B is prohibited by the tabs 106 abutting against cylindrical surfaces of the arms 124 and upward movement of the insert 12 out of the grip of the tabs 106 is further prohibited by the ridges of the surface portion 137. Ridges defining the surface portion 137 located at the lower curved portion of the grooves 136 also prohibit the tabs 106 from sliding along the outer cylindrical surface of the base 134, thus resisting upward movement of the insert 12 out of the receiver 10. As illustrated in FIG. 19, the insert 12 seats on the shank upper portion 8 with the surface 122 in sliding engagement with

15

the surface 62. The bone screw is typically factory assembled with the insert 12 as shown in FIGS. 10 and 11.

In use, the bone screw with assembled insert 12 (as shown in FIGS. 10 and 11) is typically screwed into a bone, such as a vertebra (not shown), by rotation of the shank 4 using a driving tool (not shown) that operably drives and rotates the shank 4 by engagement thereof with the internal drive 44. The vertebra (not shown) may be pre-drilled to minimize stressing the bone and have a guide wire (not shown) that is shaped for the cannula 64 and inserted to provide a guide for the placement and angle of the shank 4 with respect to the vertebra. A further tap hole may be made using a tap with the guide wire as a guide. Then, the assembly 1 is threaded onto the guide wire utilizing the cannulation bore 64 by first threading the wire into the bottom opening 32 and then out of the top at the internal drive 44. The shank 4 is then driven into the vertebra, using the wire as a placement guide.

With reference to FIGS. 15 and 16, prior to implantation of the fastener 14 into the receiver 10, the set screw 20 is inserted into the base 146 of the outer fastener 18 at the bore 154 that opens to the bottom surface 156. The screw 20 is rotated and drawn upwardly toward the top surface 166 of the base 146, mating the threaded surface 188 with the fastener inner thread 176. Initially, the screw 20 is rotated until the screw 20 is disposed entirely within the fastener 18 with the top surface 186 of the screw 20 being closely adjacent to or in contact with the abutment shoulder 178 as illustrated in FIG. 16.

With reference to FIG. 17, the rod 21 or other longitudinal connecting member, such as the bar 24 shown in FIGS. 20 and 21, is eventually positioned in an open or percutaneous manner within the receiver channel 76, and the closure structure 14 is then inserted into the receiver 10 by placing the flange forms 84 and 84' between the arms 72 and 72' followed by aligning the forms 84 and 84' with the respective tracks 82 and 82' of the receiver 10. Such alignment also aligns the opposed wing members 164 and 164' with the respective upper step surfaces 96 and 96'. With reference to FIG. 17, the closure structure is then rotated about the axis B to mate the flange forms 84 and 84' with the tracks 82 and 82'. Alignment of the rod surface 22 or the bar surfaces 25 with respect to the receiver channel 76 and the saddle 126 of the insert 14 is initially provided and then maintained by pressure placed at the insert grooves 136 by the tabs 106. The closure fastener 14 is rotated, using a tool engaged with the break-off head 148 hex drive 150 until a selected pressure is reached at which point the head 148 separates from the fastener base 146. Also with reference to FIG. 17, at this time, the set screw 20 is still entirely disposed within the base 146 and does not engage the rod 21 or the bar 24. However, the outer fastener 18 is in engagement with the insert 12 at the top surface 132 of the arms 124, placing the insert 12 surface 122 into frictional engagement with the surface 62 of the shank upper portion 8 that in turn places the upper portion 8 into frictional engagement with the surface 116 of the receiver 10, locking the shank 4 with respect to the receiver 10 in a desired angle with respect thereto. For example, about 80 to about 120 inch pounds pressure may be required for removing the break-off head 148 and fixing the bone screw shank 4 with respect to the receiver 10.

With reference to FIG. 19, the rod 21 (or bar 24) is eventually locked into place by utilizing a tool (not shown) inserted into the bore 154 and into engagement with the set screw inner drive 158. The tool is used to rotate the set screw 20 and drive the screw 20 downwardly until the surface 187 is in frictional engagement with the rod 21 surface 22 (or the bar 24 surface 25). With reference to FIGS. 17 and 19, as the

16

screw 20 advances downwardly toward the rod surface 22, the screw 20 remains in spaced relation with the insert 12 with the recessed portions 138 of the insert 12 providing clearance for such downward advancement of the screw 20.

Thus, when the screw 20 is pressing firmly against the rod 21, the screw 20 does not make contact with any portion of the insert 12. Only the rod 21 (or bar 24) is pressed into frictional engagement with the seating surface 130 of the insert 12. FIGS. 20 and 21 also illustrate that the set screw 20 may be rotated and driven downwardly into contact with the bar 24 (or the rod 21), if desired, prior to final torquing of the fastener 14 and removal of the break-off head 148.

As discussed above, if the frictional engagement between the set screw 20 and the rod 21 (or the bar 24) eventually loosens due to creep or other viscoelastic flow of the rod 21 (or bar 24), such loosening will not in turn loosen the lock between the receiver 10 and the bone screw shank 4. Therefore, the dual closure 14 advantageously allows for the use with a variety of longitudinal members made from a wide range of materials. As illustrated in FIGS. 20 and 21, the assembly 1 advantageously cooperates with both cylindrical rods and with bars of square or rectangular cross-section, such as the bar 24 of substantially square cross-section. The bar 24 made from PEEK, for example, provides for some dynamic, flexible support and yet due to the geometry thereof provides greater support with respect to torsional forces, for example, than would a cylindrical PEEK rod. However, whether greater or lesser stability is required, the squared-off channel provided by the insert 12 allows for the easy substitution of connecting members of round, square, rectangular or other cross-sectional shape.

It is noted that in certain embodiments according to the invention, a second pressure insert may be located between the set screw 20 and the rod 21 or bar 24. Furthermore, the rod 21 or the bar 24 may include a central through bore or lumen (not shown) allowing for threading of such rod or bar and implantation in a percutaneous or less invasive procedure.

If removal of the rod 21 or bar 24 from any of the bone screw assemblies 1 is necessary, or if it is desired to release the rod 21 or bar 24 at a particular location, such is accomplished by using the driving tool (not shown) that mates with the internal drive 158 on the set screw 20 to rotate and first loosen the rod 21 or bar 24 from the receiver 10. Continued rotation of the set screw 20 causes the set screw 20 to contact the abutment shoulder 178 and thereafter further rotation causes the outer fastener 18 to disengage from the flange tracks 82 and 82' of the receiver 10, thus removing the entire closure structure 14 from the cooperating receiver 10. Disassembly is then accomplished in reverse order to the procedure described previously herein for assembly.

With reference to FIGS. 22-40, the reference numeral 201 generally designates an alternative polyaxial bone screw assembly according to the invention for use with the rod 21 or the bar 24 previously described herein with respect to the assembly 1 and also with a variety of rigid or dynamic stabilization longitudinal connecting member assemblies. The bone screw assembly 201 is substantially similar to the bone screw assembly 401 disclosed in Applicant's US Patent Publication No. 2007/0055244, published Mar. 8, 2007 (U.S. patent application Ser. No. 11/522,503 filed Sep. 14, 2006) and incorporated by reference herein (hereafter the '244 publication) and illustrated in FIGS. 22-34 therein. There are a few exceptions, however, including a preferred polyaxial bone screw shank and retainer connection that allows for the lower pressure insert to exclusively directly

frictionally engage the bone screw shank rather than pressing upon the retainer that is threadably attached to the shank and configured for polyaxial motion with respect to the receiver; the addition of receiver spring tabs for holding the lower pressure insert in alignment; and squared-off channels 5 formed by the receiver and the lower pressure insert for closely receiving connecting members of rectangular cross-section as well as cylindrical members, all of which will be described in greater detail in the following paragraphs.

The bone screw assembly 201 of the present invention 10 includes a shank 204 that further includes a body 206 integral with an upwardly extending, substantially cylindrical upper portion or capture structure 208 operationally disposed primarily within a receiver 210. The shank 204 is similar to the shank 414 disclosed in the '244 publication in 15 that the body 206 includes a helical thread 211 for attachment to a vertebrae. The assembly 201 further includes a retainer in the form of a retaining and articulating structure 212 that is similar but not identical to the retainer disclosed in the '244 publication. The shank upper portion 208 also 20 includes a substantially spherically shaped upper or top surface 213 sized and shaped to slidingly mate with a lower spherical surface of a lower pressure insert 214. Therefore, unlike the bone screw disclosed in the '244 publication, the pressure insert 214 operationally presses directly against the shank upper portion 208 and not the retainer 212. The shank 204, the receiver 210, the retaining and articulating structure 212 and the first or lower compression insert 214 are preferably assembled prior to implantation of the shank 25 body 206 into a vertebra. The shank body may include a cannulation bore 264 similar in form and function to the bore 64 of the shank 4 of the assembly 1.

With particular reference to FIGS. 22 and 31-35, the shank upper portion 208 further includes a substantially cylindrical portion 215 having a helical thread 216 thereon, 35 the portion 215 disposed adjacent to the spherical surface 213 and extending along an axial length thereof. The threaded cylindrical portion 215 flares or widens outwardly near an end 217 thereof into a portion 218 of slightly greater diameter than a remainder of the cylindrical portion 215. 40 The thread 216 or other helically wound guide and advancement structure is sized and shaped to mate with an inner portion 220 of the retainer 212 having a thread 221 or other helically wound guide and advancement structure. The upper portion 208 further includes a top surface 222 having an internal drive 223 formed therein for engaging with a driving tool (not shown) for rotating the shank 204 and driving the shank 204 into a vertebra (not shown). When the retainer 212 is mated with the shank upper portion 208, an outer substantially spherical surface 224 of the retainer 212 45 is in sliding engagement with an inner substantially spherical seating surface 228 of the receiver 210 as described previously herein with respect to the upper portion 8 and the seating surface 116 of the assembly 1. The retainer 212 further includes a sloped or frusto-conical top surface 225 50 located between the inner threaded surface 220 and the outer spherical surface 224. In some embodiments of the invention the top surface 225 may be planar. With particular reference to FIG. 35, the sloped surface 225 advantageously provides for additional clearance between the retainer 212 55 and the lower pressure insert 214, ensuring that the insert 214 engages only the bone screw shank at the surface 213 and not any portion of the retainer 212.

With particular reference to FIGS. 23-30, the assembly 201 further includes an upper insert 226 and a closure 65 structure, generally 230, having an outer fastener 232 and an uploaded inner set screw 234. The outer fastener 232

includes a base 236 integral or otherwise attached to a break-off head 238. The base 236 cooperates with the receiver 210 to capture the rod 21 or the bar 24 within the bone screw receiver 210. The break-off installation head 238 5 includes an internal drive or aperture 240 sized and shaped for engagement with a tool (not shown) for installing the fastener 232 to the bone screw receiver 210 and thereafter separating the break-off head 238 from a respective base 236 when installation torque exceeds selected levels.

The base 236 of the fastener portion 232 is substantially cylindrical, having an axis of rotation G and an external surface 250 having a guide and advancement structure 252 10 disposed thereon. The guide and advancement structure 252 is matingly attachable to a guide and advancement structure 253 of the bone screw receiver 210. The cooperating guide and advancement structures 252 and 253 can be of a variety of types, including, but not limited to buttress threads, 15 reverse angle threads, or square threads, and are preferably helically wound flange forms that interlock and are splay resistant, and thus do not exert radially outward forces on the arms of the receiver 210, thereby avoiding tendencies toward splaying of the receiver arms when the fastener portion 232 is tightly torqued into the receiver 210. 20

The fastener portion 232 includes an internal, centrally 25 located bore 254. At the base 236, the bore 254 is substantially defined by a guide and advancement structure, shown in FIG. 24 as an internal V-shaped thread 256. The thread 256 is sized and shaped to receive the threaded set screw 234 therein as will be discussed in more detail below. Although 30 a traditional V-shaped thread 256 is shown, it is foreseen that other types of helical guide and advancement structures may be used. Near a top of the base 236, an abutment shoulder 260, extends uniformly radially inwardly. The abutment shoulder 260 is spaced from the V-shaped thread 256 and 35 sized and shaped to be a stop for the set screw 234, prohibiting the set screw 234 from advancing upwardly out of the base 236. It is foreseen that alternatively, the set screw may be equipped with an outwardly extending abutment feature near a base thereof, with complimentary alterations 40 made in the fastener base 236, such that the set screw 234 would be prohibited from advancing upwardly out of the top of the base 236 due to abutment of such outwardly extending feature against a surface of the base 236.

An inner cylindrical wall 262 separates the abutment 45 shoulder 260 from the thread 256. The cylindrical wall 262 has a diameter equal to or slightly greater than a root or major diameter of the internal thread 256. The wall 262 partially defines a cylindrical space or passage 264 for axial adjustable placement of the screw 234 with respect to the longitudinal connecting member 21 or 24. 50

The fastener break-off head 238 is integral or otherwise attached to the fastener 232 at a neck or weakened region 266. The neck 266 is dimensioned in thickness to control the torque at which the break-off head 238 separates from the fastener 232. The preselected separation torque of the neck 266 is designed to provide secure engagement between the fastener 232 and the lower compression structure or insert 214 that in turn presses directly against the shank upper portion 208 that is threadably mated to the retainer 212, 55 pressing the retainer 212 against the receiver 210 and thus clamping the shank 204 in a desired angular orientation with respect to the receiver 210 and the rod 21 or the bar 24. The fastener 232 thus captures the longitudinal connecting member 21 or 24 within the receiver 210 before the head 238 60 separates, by abutting against the lower compression member 214 without making contact with the rod 21 or the bar 24. For example, 120 inch pounds of force may be a selected

break-off torque to lock the bone screw shank in place without placing any pressure on the rod **21** or the bar **24**. The illustrated internal driving feature **240** of the break-off head **238** enables positive, non-slip engagement of the head **238** by an installation and torquing tool. Separation of the break-off head **238** leaves only the more compact base **236** of the fastener **232** installed in the bone screw receiver **210**, so that the installed fastener **232** has a low profile. As will be described in greater detail below, the set screw **234** may then be rotated and moved downwardly into secure engagement with the rod **21** or the bar **24**.

The base **236** of the fastener **232** includes a planar bottom surface **268** disposed substantially perpendicular to the axis G for abutting the top surfaces **269** of arms of the compression insert **214**. However, the bottom surface may also be ramped or inclined as described in the '244 publication (with cooperating ramped surface on the insert **214**).

The uploadable set screw **234** has a substantially annular and planar top **276** and a substantially annular and planar bottom **277**. The screw **234** is substantially cylindrical in shape and coaxial with the fastener **232**. The screw **234** includes an outer cylindrical surface **278** disposed near the bottom **277** and a threaded surface **280** extending from the top **276** to the cylindrical surface **278**. The v-shaped thread **280** is sized and shaped to be received by and mated with the inner thread **256** of the fastener base **236** in a nested, coaxial relationship.

As illustrated, for example, in FIGS. **24** and **25**, the set screw **234** includes a central aperture **286** formed in the top **276** and defined by side walls **288** that define a driving feature similar to but of smaller dimensions than the driving feature **240** of the fastener **232**. The driving feature further includes a seating surface or bottom **289**, aiding in a positive, non-slip engagement by a set screw installment and removal tool (not shown) that may be inserted through the aperture formed by the driving feature **240** of the fastener **232** and then into the aperture **286** and into engagement with the walls **288** defining the set screw driving feature. A lower central aperture or bore **290** extends between the central aperture **286** and the bottom **277** of the set screw **234**. The bore **290** is sized and shaped to receive and hold an upper portion of the upper compression structure **226** as will be described more fully below.

With further reference to FIG. **24**, the central set screw aperture **286** cooperates with the central internal bore **254** of the fastener **232** for accessing and uploading the set screw **234** into the fastener **232** prior to engagement with the bone screw receiver **220**. After the closure structure **230** is inserted and rotated in the bone screw receiver **210**, and the break-off head **238** is broken off, the set screw **234** is rotated by a tool engaging the drive feature walls **288** to place the set screw bottom **277** into frictional engagement with the rod **21** or bar **24**.

There are circumstances under which it is desirable or necessary to release the longitudinal connecting member **21** or **24** from the bone screw assembly **201**. For example, it might be necessary for a surgeon to re-adjust components of a spinal fixation system, including the longitudinal connecting member **21** or **24**, during an implant procedure, following an injury to a person with such a system implanted. In such circumstances, the tool that engages and rotates the set screw **234** at the driving feature **288** may be used to remove both the set screw **234** and attached fastener base **236** as a single unit, with the set screw **234** contacting and contained within the base **236** by the abutment shoulder **260**. Thus, rotation of the set screw tool engaged with the set screw **234** backs both the set screw **234** and the fastener base **236** out

of the guide and advancement structure **253** in the receiver **210**, thereby releasing the longitudinal connecting member **21** or **24** for removal from the bone screw receiver **210** or repositioning of the longitudinal connecting member **21** or **24**. It is foreseen that other removal structures such as side slots or other screw receiving and engagement structures may be used to engage the set screw **234** that is nested in the fastener base **236**.

With particular reference to FIGS. **22** and **35-37**, the lower compression insert **214** includes a substantially cylindrical body **310** integral with a pair of upstanding arms **312**. The body **310** and arms **312** form a generally squared-off U-shaped, open, through-channel **314** with planar side surfaces **315** disposed perpendicular to a planar bottom seating surface **316**, the channel **314** and seating surface **316** sized and shaped to receive either the rod **21** or the planar surfaces **25** of the bar **24**. In the illustrated embodiment, the channel surfaces **315** do not closely receive the rod **21** and as will be described below, the rod **21** is held substantially centrally in place by the upper compression insert **226**. However, in other embodiments according to the invention, the lower insert may be sized and shaped to closely receive the rod **21** as well as the bar **24** as shown in FIG. **34**. The arms **312** of the inert **214** disposed on either side of the channel **314** each include a top flanged portion **318**, each portion **318** including the planar top surface **269** previously described herein, sized and shaped to engage the surface **268** of the fastener **232**. The compression insert **214** further includes a bottom surface **320** and a substantially cylindrical outer surface **322**. An inner cylindrical wall **324** defining a central through-bore extends along a central axis of the compression structure **214** and extends between the seating surface **316** and a substantially spherical surface **326**. The surface **326** extends between the inner cylindrical wall **324** and the bottom surface **320**. The surface **326** is substantially similar to the spherical surface **122** of the compression insert **12** previously described herein, the surface **326** being sized and shaped to frictionally engage and mate with the upper spherical surface **213** of the shank upper portion **208**.

The cylindrical surface **322** has an outer diameter slightly smaller than a diameter between crests of the guide and advancement structure **253** of the receiver **210** allowing for top loading of the compression insert **214**. During top load installation, the top surface portions **318** disposed on each of the upstanding arms **312** are inserted into the channel between the receiver **210** upstanding arms and then the insert **214** is rotated about the axis F with the portion **318** sized and shaped to be received into a run-out or recess located beneath the guide and advancement structure **253**. The receiver **210** fully receives the lower compression insert **214** and blocks the insert **214** from spreading or splaying in any direction. It is noted that assembly of the shank **204** and the retainer **212** within the receiver **210**, followed by insertion of the lower compression insert **214** into the receiver **210** are assembly steps typically performed at the factory, advantageously providing a surgeon with a polyaxial bone screw with the lower insert firmly snapped into place and thus ready for insertion into a vertebra. The through-channel **314** is sized and shaped such that the upper compression structure or insert **226** is receivable in the channel **314** between opposed upper substantially planar walls **315** that define the channel **314** from the base **316** to the top surfaces **269**. Adequate clearance is provided such that the upper compression insert **226** is in slightly spaced or in sliding relationship with the walls **315**, allowing for independent movement of the upper compression insert **226** with respect to the lower compression insert **214**.

The lower insert **214** further includes opposed grooves **328** formed on outer surfaces of the arms **312**. The grooves **328** are substantially similar in form and function to the grooves **136** of the insert **12** of the assembly **1**. The grooves **328** are sized and shaped to receive spring tabs **329** of the receiver **210**. The spring tabs **329** are similar in form and function to the tabs **106** previously described herein with respect to the receiver **10** of the assembly **1** with the exception that the spring tabs **329** extend from a lower portion of the receiver **210** in a direction upwardly toward the guide and advancement structure **253** as well as inwardly toward the axis F of the receiver **210**.

With reference to FIGS. **26-30**, the upper or second compression structure or insert **226** includes a body **330** having a pair of downwardly extending legs **332**. The body **330** and the legs **332** form a generally U-shaped, open, through-channel having a substantially U-shaped seating surface **336** having a radius substantially conforming to the outer radius of the rod **21** and thus configured to operably snugly engage the rod **21** at the external surface **22** thereof opposite the seating surface **316** of the lower compression insert **214**. FIG. **40** illustrates an alternative embodiment wherein an upper insert **226'** includes a planar bottom surface **338'** for engaging a planar top surface **25'** of a bar **24'**. It is further noted that the polyaxial bone screw shank **204** and cooperating threaded retainer **212** capture connection provided in the assembly **201** may also be used without an upper pressure insert and in combination with the dual closure structure **14** of the assembly **1**, or alternatively, with a one-piece closure assembly.

Returning to the insert **226** of the assembly **201**, the legs **332** each include a bottom surface **338** that is substantially parallel to a planar top surface **340**. The compression insert **226** includes a pair of opposed curved outer surfaces **342** substantially perpendicular to the top surface **340** and extending between the top surface **340** and the seating surface **336**. The curved surfaces **342** further extend along the legs **332** and terminate at the bottom surfaces **338**. A pair of opposed substantially planar outer surfaces **343** are disposed between the curved surfaces **342** and are also disposed substantially perpendicular to the top surface **340**, each planar surface **343** extending between the top surface **340** and a respective bottom surface **338**.

A pin **344** of substantially circular cross section is disposed centrally on the top surface **340** and extends upwardly therefrom, being sized and shaped to fit within the centrally located lower bore **290** formed in the set screw **234**. The pin **344** further includes a substantially cylindrical base **346** and a U-shaped channel **348** formed by a pair of opposed, flanged arms **350** that extend from the base **346** upwardly and substantially parallel to one another. Each of the flanged arms includes a partially conical surface portion **351** and a flat bottom surface **352** that is substantially parallel to the top planar surface **340** of the compression structure body **330**. As illustrated in FIGS. **29** and **30**, the pin **344** is receivable in the bore **240** with surfaces forming the bore pressing and deforming the flanged arms **350** toward one another as the upper compression structure **226** is pressed against the set screw **234** that has already been up-loaded into a fastener portion **232**. Once the conical surface portions **351** clear the bore **240** and enter the set screw aperture **286**, the flanged arms **350** return to the original upright and substantially parallel form with the surfaces **352** being in contact with and seated upon a portion of the bottom surface **289** as illustrated in FIG. **30**. The flanged arms **350** thus keep the compression structure **226** attached to the set screw **234** and yet rotatable with respect thereto about an axis of rotation H of the

cylindrical base **346** of the structure that is coaxial with the axis G of the set screw **234** and fastener **232**, providing a centered relationship between the closure structure **230** and the compression structure **226** while allowing the compression structure **226** to freely rotate into a position centered over and in gripping engagement with the longitudinal connecting member **21** when assembled thereon. Furthermore, if removal of the fastener and up-loaded set screw is desired, the attached compression structure **226** is advantageously removed along therewith.

With particular reference to FIGS. **24**, **29**, **30** and **36-38**, in use, the set screw **234** is assembled with the fastener **232** by inserting a set screw tool (not shown) through the bore **254** of the fastener **232** and into the aperture **286** of the set screw **234**, with outer features of the tool engaging the inner walls **288** of the set screw **234**. The set screw **234** is then up-loaded into the fastener **232** by rotation of the set screw **234** with respect to the fastener **232** to mate the set screw thread **280** with the fastener inner thread **256** until the set screw top surface **276** is spaced from the abutment shoulder **260**, but substantially nested in the fastener **232**, with possibly only the cylindrical surface **278** extending from the fastener base **236**. The upper compression structure **224** is then attached to the set screw **234** as previously described with the pin **344** being received by the bore **290** and inserted therethrough until the arms **350** are disposed within the aperture **286**, with the lower surfaces **352** of the flanged arms seated on the bottom **289** of the set screw aperture **286**, capturing the flanged arms **350** within the aperture **286**. The nested assembly shown in FIG. **24** and attached to an upper compression structure as shown in FIGS. **29** and **30** is now pre-assembled and ready for use with a bone screw receiver **210** and cooperating rod **21**.

With particular reference to FIGS. **22** and **32-35**, the retainer **212** is typically first inserted or top-loaded, into the receiver squared-off U-shaped channel and then into the receiver cavity. Then, the retainer **212** is rotated approximately 90 degrees so as to be coaxial with the receiver **210** axis F and then seated in sliding engagement with the inner seating surface of the receiver **210** as shown in FIG. **32**. With reference to FIG. **33**, the shank upper portion **208** is then inserted or bottom-loaded into the receiver **210**. The retainer **212**, now disposed in the receiver **210** is coaxially aligned with the shank **204** and the upper portion **208** is generally rotated about the axis F mating the threaded surface **215** with the threaded surface **220** of the retainer **212**. Rotation continues until the retainer **212** engages the flared portion **218** and is tightened thereon, fixing the retainer **212** to the shank upper portion **208** as shown, for example, in FIG. **35**. Preferably, the shank **204** and or the retainer **212** are rotated to fully mate such structures at a factory setting that includes tooling for holding and precisely rotating the shank **204** and/or the retainer **212** until locking frictional engagement therebetween is accomplished. At this time both the shank **204** and the retainer **212** are in rotatable and swivelable engagement with the receiver **210**, while the shank upper portion **208** and the lower aperture or neck of the receiver **210** cooperate to maintain the shank body **206** in swivelable relation with the receiver **210**. Only the retainer **212** is in slidable engagement with the receiver **210** spherical seating surface. The spherical shank upper surface **213** is in spaced relation with the receiver **210**. The shank body **206** can be rotated and pivoted through a substantial angular rotation relative to the receiver **210**, both from side to side and from front to rear so as to substantially provide a universal or ball joint.

With reference to FIG. 35, the insert 214 may be top loaded into the receiver 210 with the flanged portions 318 aligned in the receiver channel, each flanged portion 318 being located between a pair of opposed walls partially defining the receiver arms. The insert 214 is then moved downwardly into the receiver and past the guide and advancement structure 253. Once the flanged portions 318 are located below the guide and advancement structure 253 and adjacent the run-out relief below the structure 253, the insert 214 is rotated about the axis F of the receiver 210 as illustrated by the arrow 380 in FIG. 22. The flanged portions 318 fit within such relief. Once each flanged portion 318 is located centrally with a respective arm of the receiver 210, rotation is ceased and the spring tabs 329 may be pressed into the grooves 328 or the spring tabs 329 simply snap into the grooves 328 as in the illustrated embodiment of the receiver 210 wherein the tabs are directed inwardly toward the axis F prior to assembly with the lower pressure insert 214. The insert 214 is now locked into place inside the receiver 210 with the guide and advancement structure 253 prohibiting upward movement of the insert out of the receiver 210 and the spring tabs 329 that are biasing against the insert 214 at the grooves 328 prohibiting rotational movement of the insert 214 with respect to the receiver 210 about the receiver axis F. The insert 214 seats on the shank upper portion 208 with the partially spherical surface 326 in sliding engagement with the cooperating partially spherical surface 213 as best shown in FIG. 35 (and also shown in locked mated engagement in FIG. 38). It is noted that FIG. 35 illustrates the shank 204 and attached retainer 212 swiveled at an angle with respect to the receiver 210 wherein the shank body 206 is extending forward from the plane of the drawing illustration as well as at an angle with respect to the two dimensions of the drawing figure. The run-out or relief under the guide and advancement structure 253 is sized and shaped to allow for some upward and downward movement of the insert 214 toward and away from the shank upper portion 208 such that the shank upper portion 208 is freely pivotable with respect to the receiver 210 until the closure structure fastener base 236 presses on the insert 214 that in turn presses upon the upper portion 208 into locking frictional engagement with the receiver 210. Similarly, the spring tabs 329 are sized, shaped and positioned within the grooves 328 to allow for upward and downward movement of the insert 214 and pivoting of the shank 204 prior to locking in place.

With reference to FIG. 34, in use, the bone screw shank 206 is typically screwed into a bone, such as a vertebra 380 by rotation of the shank 204 using a driving tool 382 that operably drives and rotates the shank 204 by engagement thereof with the tool engagement structure 223. With reference to FIGS. 35-37, the rod 21 is eventually placed in the bone screw receiver 210 that has been previously attached to the bone screw shank 204 utilizing the retaining and articulating structure 212 and loaded with the lower compression insert 214. A driving tool (not shown) is used to rotate the closure structure by engagement with the drive feature 240 of the break-off head 238, mating the guide and advancement structures 252 and 253. During installation, the fastener surface 268 frictionally engages the surface 269 of the lower compression insert 214, that in turn presses the surface 326 exclusively against the shank upper portion 208 at the surface 213 at a location substantially spaced from the retainer 212 as shown in FIG. 38, biasing the retainer 212 at the surface 224 into fixed frictional contact with the receiver 210 at the seating surface 228, such that the receiver 210 and the shank 204 can be independently secured at a desired

angle with respect to the receiver while the rod 21 remains movable within the receiver and yet substantially captured between the compression structures 212 and 226. Also with reference to FIG. 38, the closure structure is rotated until a selected pressure is reached at which time the head 238 breaks off, preferably about 80 to about 120 inch pounds that adequately fixes the bone screw shank 204 with respect to the receiver 210. When the break-off head is removed, the upper compression insert 226 is preferably in contact with the rod 21, but placing little if any pressure thereon. Then, a set screw driving tool (not shown) is inserted into the drive feature 288 and the set screw 234 is rotated downwardly, pressing against the insert 226 that in turn presses against the rod 21.

The polyaxial bone screw assembly 201 according to the invention advantageously allows for the removal and replacement of the rod 21 with another longitudinal connecting member having a different overall cross-sectional width or outer diameter, utilizing the same receiver 210 and the same lower compression insert 214. For example, as illustrated in FIG. 39, an assembly 201A is illustrated wherein the rod 21 is replaced by the bar 24 and the upper insert 226 is not utilized.

With reference to FIG. 40, another assembly according to the invention, generally 201B, includes a shank 204', a receiver 210', a set screw 234' and cooperating outer fastener 236', and a lower insert 312' substantially similar to the respective shank 204, receiver 210, set screw 234 and fastener 236, and insert 312 previously described herein with respect to the assembly 201. It is noted that the neck of the shank 204' is substantially cylindrical as compared to the curved neck of the shank 204. Shanks according to the invention may include a variety of geometries including, but not limited to straight cylinders, curved necks, conical necks, and the like.

The assembly 201B further includes an upper insert 226' that attaches to the set screw 234' in a manner similar to the previously described cooperation between the set screw 234 and insert 226. However, the insert 226' includes a planar bottom surface 338' for substantially full frictional contact with a planar surface 25' of a bar 24' of rectangular cross-section.

It is to be understood that while certain forms of the present invention have been illustrated and described herein, it is not to be limited to the specific forms or arrangement of parts described and shown.

What is claimed and desired to be secured by Letters Patent is as follows:

1. A polyaxial bone anchor comprising:
 - a) a shank having a body for fixation to a bone and an integral upper portion, the upper portion having an upper end surface and an outer surface with a first helically wound guide and advancement structure thereon;
 - b) a receiver having a top portion and a base, the receiver top portion defining an open channel, the base having a seating surface partially defining a cavity, the channel communicating with the cavity, the cavity communicating with an external of the base through an opening sized and shaped to receive the shank upper portion therethrough;
 - c) a compression insert disposed in the receiver, the insert having a mating surface exclusively frictionally engageable with the upper end surface of the shank upper portion; and
 - d) a retainer having an external surface and a central bore with an internal surface defining the central bore having

25

a second helically wound guide and advancement structure thereon, the first helically wound guide and advancement structure configured to rotatably mate with the second helically wound guide and advancement structure to secure the retainer to the shank upper portion within the receiver, the shank upper portion and the retainer being in fixed relation to one another, both the upper portion and the retainer being in swivelable relation within the receiver, providing selective angular positioning of the shank with respect to the receiver, the retainer external surface being in slidable engagement with the receiver seating surface, the retainer being substantially spaced from the compression insert at any and all angular positions of the shank with respect to the receiver.

2. The bone anchor of claim 1 wherein the compression insert mating surface is concave and the shank upper end surface is convex.

3. The bone anchor of claim 1 wherein the receiver seating surface is at least partially spherical and the retainer external surface is at least partially spherical.

4. The bone anchor of claim 1 wherein the shank upper portion has a tool engagement formation formed thereon adapted for non-slip engagement by a tool for driving the bone screw shank body into bone.

5. The bone anchor of claim 1 wherein the shank upper portion has a flared portion disposed adjacent the first guide and advancement structure, the retainer having a cooperating surface abutting against the flared portion when the first guide and advancement structure is fully mated with the second guide and advancement structure.

6. The bone anchor of claim 1 further comprising a closure structure insertable into the receiver, the closure structure for operably urging the insert into fixed frictional engagement with the bone screw shank upper portion and moving the shank in a direction to frictionally lock the position of the retainer with respect to the receiver, thereby locking the shank body in a selected angle with respect to the receiver.

7. The bone anchor of claim 1 wherein the compression insert has a seating surface and first and second upstanding arms, the arms operatively receiving a longitudinal connecting member; and further comprising a two-piece closure having an outer fastener and an inner set screw, the outer fastener directly engaging the first and second arms of the compression insert and independently locking the shank with respect to the receiver, the outer fastener having an outer flange in interlocking engagement with a flange track of the receiver, the inner set screw biasing the longitudinal connecting member toward the compression insert seating surface.

8. The bone anchor of claim 7 wherein the flange is a helical flange.

9. The bone anchor of claim 7 wherein the flange is a first flange and further comprising a second, opposed flange.

10. The bone anchor of claim 9 wherein the outer fastener has first and second opposed upper wings frictionally engaged with top surfaces of the receiver.

11. The bone anchor of claim 1 further comprising resilient structure extending from the receiver and biasing against the compression insert at a depression formed in a surface of the insert, the resilient structure prohibiting rotational movement of the compression insert within the receiver.

26

12. The bone anchor of claim 11 wherein the resilient structure is a pair of opposed spring tabs attached to the receiver and extending toward a central axis of the receiver.

13. The bone anchor of claim 1 wherein the compression insert is a lower compression insert and further comprising an upper compression insert disposed in the receiver, a longitudinal connecting member being closely received between the lower and upper inserts.

14. The bone anchor of claim 13 wherein the upper compression insert is attached to a closure structure.

15. In a polyaxial bone screw assembly for surgical implantation and including a shank having an upper end and a threaded body for inserting into a bone, a receiver having an outward opening channel adapted to receive a longitudinal connecting member within the channel, the receiver having a shank receiving opening, and a closure structure also being received in the receiver for locking the assembly, the improvement comprising:

(a) a first helical guide and advancement structure located on the shank spaced from the upper end;

(b) a retainer having an outer surface and an inner substantially cylindrical surface, the outer surface being in swivelable sliding engagement with the receiver prior to locking of the assembly with the closure structure, the inner surface having a second helical guide and advancement structure thereon, the inner surface at least partially defining a central through bore of the retainer, the second guide and advancement structure sized and shaped to receive and mate with the first guide and advancement structure to fix the retainer to the shank with the retainer being spaced from the upper end; and

(c) a compression insert engaging the shank upper end and spaced from the retainer at any and all angular positions of the retainer with respect to the receiver.

16. The improvement of claim 15 wherein the closure structure operably urges the compression insert into fixed frictional engagement with the bone screw shank upper end and moves the shank in a direction to frictionally lock the position of the retainer with respect to the receiver, thereby locking the shank in a selected angle with respect to the receiver.

17. The improvement of claim 15 wherein the compression insert has a seating surface and first and second upstanding arms, the arms operatively receiving a longitudinal connecting member and wherein the closure structure is a two-piece closure structure having an outer fastener and an inner set screw, the outer fastener directly engaging the first and second arms of the compression insert and independently locking the shank with respect to the receiver, the outer fastener having an outer flange in interlocking engagement with a flange track of the receiver, the inner set screw biasing the longitudinal connecting member toward the compression insert seating surface.

18. The improvement of claim 17 wherein the flange is a helical flange.

19. The improvement of claim 17 wherein the flange is a first flange and further comprising a second, opposed flange.

20. The improvement of claim 19 wherein the outer fastener has first and second opposed upper wings frictionally engaged with top surfaces of the receiver.