



US00RE46600E

(19) **United States**  
(12) **Reissued Patent**  
**Albizuri**

(10) **Patent Number: US RE46,600 E**  
(45) **Date of Reissued Patent: \*Nov. 7, 2017**

(54) **MULTI-GAS VALVE FOR A GAS BURNING APPLIANCE**

(58) **Field of Classification Search**  
CPC ... F23C 1/08; F23N 7/007; F23N 3/02; F23N 2035/16; F23N 2037/08; F23N 2041/04  
(Continued)

(71) Applicant: **COPRECITEC, S.L.**, Aretxabaleta (Guipuzcoa) (ES)

(56) **References Cited**

(72) Inventor: **Iñigo Albizuri**, Muxika (ES)

U.S. PATENT DOCUMENTS

(73) Assignee: **COPRECITEC, S.L.**, Aretxabaleta (ES)

596,871 A 1/1898 Grist  
787,914 A 4/1905 Gibson  
(Continued)

(\* ) Notice: This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **13/859,576**

CN 201121736 9/2008  
CN 201121736 Y 9/2008  
(Continued)

(22) Filed: **Apr. 9, 2013**

**Related U.S. Patent Documents**

**OTHER PUBLICATIONS**

Reissue of:

(64) Patent No.: **7,963,763**  
Issued: **Jun. 21, 2011**  
Appl. No.: **12/639,856**  
Filed: **Dec. 16, 2009**

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435, Corrected Petition for Inter Partes Review of U.S. Pat. No. 8,449,289; the corrected petition dated Jul. 22, 2013.

(Continued)

U.S. Applications:

(63) Continuation of application No. 12/069,657, filed on Feb. 12, 2008, now Pat. No. 7,641,470, which is a  
(Continued)

*Primary Examiner* — Gregory Huson  
*Assistant Examiner* — Daniel E Namay

(74) *Attorney, Agent, or Firm* — Edell, Shapiro & Finnan LLC

(30) **Foreign Application Priority Data**


Feb. 10, 2005 (ES) ..... 200500309 U

(57) **ABSTRACT**

(51) **Int. Cl.**  
**F23N 3/02** (2006.01)  
**F23C 1/08** (2006.01)  
**F23N 1/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **F23C 1/08** (2013.01); **F23N 1/007** (2013.01); **F23N 3/02** (2013.01); **F23N 2035/16** (2013.01);  
(Continued)

[The cooking appliance (1) having a control panel (2) is equipped with one or more gas flow (Q) regulating valves, wherein the rotary regulating plug (6) is provided with various peripheral through holes (16-19). The control knob (9) being interchangeable for fitting to the actuating shaft (7), is chosen from the two units available, one and the other permitting different angular limit positions of the regulating plug (6) for the supply of a constant minimum gas flow  $Q_{min}$ , adjusted each one for a different type of gas N gas or  
(Continued)



LP gas. The outlet conduit (5) of the valve is equipped with a further injector nozzle (21,23) for adjusting a constant gas flow Q<sub>max</sub> to be fed into the conduit (25) of the correspondent burner, when the cooking appliance is supplied with a LP gas.] *A valve adapted to regulate the flow of both a natural gas and a liquefied petroleum gas. According to one implementation the valve includes a valve body having a rotatable regulating organ positioned between a valve inlet and a valve outlet, the valve outlet having a first restriction and a second restriction successive to the first restriction, the first restriction including a first hole calibrated to provide a given maximum flow rate of the natural gas at a first pressure in the absence of the second restriction, the second restriction removeably attached to the valve outlet, the second restriction including a second hole calibrated to provide a given maximum flow rate of the liquefied petroleum gas at a second pressure.*

**15 Claims, 1 Drawing Sheet**

**Related U.S. Application Data**

continuation of application No. 11/143,785, filed on Jun. 1, 2005, now abandoned.

- (52) **U.S. Cl.**  
CPC ..... F23N 2037/08 (2013.01); F23N 2041/04 (2013.01)
- (58) **Field of Classification Search**  
USPC ..... 126/25 R, 39 E, 39 N, 39 R; 137/269, 137/270; 251/127, 205-209, 92; 16/441; 431/2, 12, 18, 61, 62, 65, 72, 354  
IPC ..... F23N 1/00, 3/02, 14/00, 14/02, 14/04  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

791,260	A	5/1905	Fuller
993,714	A	5/1911	Popp
1,215,653	A	2/1917	Hale
1,296,406	A	3/1919	Kyriakos
1,421,591	A	7/1922	Shuler
1,526,500	A *	2/1925	Kasch ..... 74/553
1,590,882	A *	6/1926	Brown et al. .... 239/430
1,711,436	A	4/1929	Williams
1,829,365	A	10/1931	Meyer
1,869,764	A *	8/1932	Methudy ..... 126/39 B
1,921,762	A *	8/1933	Leins ..... 126/39 N
1,940,171	A	12/1933	Huss
2,101,356	A *	12/1937	Zak ..... 251/207
2,512,404	A	6/1950	Williams
2,540,056	A	1/1951	Robinson
2,626,160	A	1/1953	Brumbaugh
2,650,610	A	9/1953	Brumbaugh
2,650,612	A *	9/1953	Brumbaugh ..... 137/637.4
2,650,613	A *	9/1953	Brumbaugh ..... 137/637.4
2,661,732	A	12/1953	O'Keefe
2,723,102	A	11/1955	Mueller
2,893,426	A	7/1959	Brumbaugh
2,987,078	A	9/1961	Du Perow
3,001,547	A	9/1961	Brumbaugh
3,068,902	A	12/1962	Brumbaugh
3,093,155	A	6/1963	Dawes
3,107,082	A	10/1963	Reynolds
3,224,122	A *	12/1965	Jepson et al. .... 38/77.2
3,313,490	A *	4/1967	Loveland ..... 239/596
3,376,097	A *	4/1968	Biber et al. .... 431/9
3,448,923	A *	6/1969	Domenick ..... 236/99 R

3,537,473	A *	11/1970	Dezurik, Jr. .... 137/556.6
3,643,688	A	2/1972	Meinert
3,949,966	A	4/1976	Fabish
3,964,514	A	6/1976	Manoogian et al.
4,020,870	A	5/1977	Carlson
4,093,178	A	6/1978	Hughes et al.
4,140,297	A	2/1979	Bussell
4,355,659	A	10/1982	Kelchner
4,366,947	A	1/1983	Voegel
4,499,630	A *	2/1985	Harris et al. .... 16/441
4,614,490	A *	9/1986	Kiczek et al. .... 431/4
4,637,429	A	1/1987	Dietiker et al.
4,740,154	A *	4/1988	Cantoni ..... 431/36
4,804,324	A *	2/1989	Yoshinaga ..... 431/255
4,862,917	A	9/1989	Genbauffe
4,947,891	A	8/1990	Genbauffe
5,009,393	A	4/1991	Massey
5,014,528	A	5/1991	Roberts
5,020,774	A	6/1991	Christianson
5,082,023	A	1/1992	D'Alayer de Costemore d'Arc
5,141,018	A *	8/1992	Guterman ..... 137/375
5,238,398	A	8/1993	Harris
5,259,589	A	11/1993	Posner
5,345,838	A *	9/1994	Howie, Jr. .... 74/553
5,413,141	A	5/1995	Dietiker
5,435,343	A	7/1995	Buezis
5,522,429	A	6/1996	Bechte
5,899,439	A	5/1999	Gottwald
5,931,387	A	8/1999	Hurley et al.
5,937,847	A *	8/1999	Garceau et al. .... 126/39 H
5,975,072	A *	11/1999	Garceau et al. .... 126/39 G
5,983,884	A *	11/1999	Lee ..... 126/39 R
5,992,457	A	11/1999	Humpert
6,027,335	A *	2/2000	Griffioen ..... 431/266
6,068,017	A	5/2000	Haworth et al.
6,162,048	A	12/2000	Griffioen
6,170,507	B1	1/2001	Dalton et al.
6,341,760	B1	1/2002	Rawlings
6,347,784	B1 *	2/2002	Philipps-Liebich et al. ... 251/92
6,357,721	B1	3/2002	Maurer
RE37,617	E *	4/2002	Sherman ..... 137/557
6,394,081	B1 *	5/2002	Aguirre-Esponda et al. .. 126/42
6,446,935	B1	9/2002	Winkler
6,520,481	B2	2/2003	Harneit
6,640,390	B1 *	11/2003	Lai ..... 16/441
6,666,227	B2	12/2003	Erickson
6,758,242	B2 *	7/2004	Jones et al. .... 137/625.41
D498,657	S	11/2004	Milrud et al.
6,871,803	B1	3/2005	Ohmi et al.
6,941,962	B2	9/2005	Haddad
7,036,188	B1 *	5/2006	Howie, Jr. .... 16/441
7,096,887	B2	8/2006	Tupa
7,156,370	B2	1/2007	Albizuri
7,237,570	B2	7/2007	Gamard
7,458,386	B2	12/2008	Zhang
7,641,470	B2	1/2010	Albizuri
7,651,330	B2	1/2010	Albizuri
7,931,216	B2	4/2011	Chung
7,950,384	B2	5/2011	Albizuri
7,963,763	B2	6/2011	Albizuri
7,967,005	B2	6/2011	Parrish
8,092,212	B2	1/2012	Albizuri
8,281,780	B2	10/2012	Carvalho et al.
8,282,390	B2	10/2012	Albizuri
8,449,289	B2	5/2013	Albizuri
2003/0010952	A1	1/2003	Morete
2004/0089830	A1	5/2004	Beyrak
2004/0238029	A1	12/2004	Haddad
2005/0109967	A1 *	5/2005	Ohmi et al. .... 251/127
2005/0202361	A1	9/2005	Albizuri
2006/0060251	A1 *	3/2006	Gamard et al. .... 137/613
2006/0175566	A1 *	8/2006	Albizuri ..... 251/207
2006/0197043	A1	9/2006	Santinavat et al.
2006/0201496	A1 *	9/2006	Shingler ..... 126/39 N
2008/0138749	A1	6/2008	Albizuri
2008/0156378	A1	7/2008	Zhang
2008/0202496	A1	8/2008	Albizuri
2008/0227045	A1	9/2008	Deng
2008/0289615	A1	11/2008	Parrish

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0047610	A1 *	2/2009	Teng	431/18
2010/0035196	A1	2/2010	Deng	
2010/0089385	A1	4/2010	Albizuri	
2010/0089386	A1	4/2010	Albizuri	
2010/0154777	A1	6/2010	Carvalho et al.	
2010/0330513	A1	12/2010	Deng	
2010/0330518	A1	12/2010	Deng	
2011/0005508	A1	1/2011	Albizuri	
2011/0030501	A1	2/2011	May	
2011/0143294	A1	6/2011	Deng	
2012/0006091	A1	1/2012	Deng	
2012/0031391	A1 *	2/2012	Albizuri	126/39 BA
2012/0073560	A1	3/2012	Parrish	
2012/0073562	A1 *	3/2012	Albizuri	126/39 E
2013/0213384	A1 *	8/2013	Albizuri	126/39 R

FOREIGN PATENT DOCUMENTS

DE	3039378	5/1982
DE	3039378 A1	5/1982
EP	0805310	11/1997
ES	1069849	5/2009
FR	1517003	2/1968
FR	2642148	7/1990
GB	1165762 A	10/1969
GB	1298809	12/1972
GB	1329893	9/1973
GB	1444673	8/1976
JP	62188867	8/1987
JP	02286971 A	11/1990
WO	WO/2006/084690	8/2006
WO	WO/2006/084690 A2	8/2006

OTHER PUBLICATIONS

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435, The Brinkman Corporation's Amended Exhibit List (for Inter Partes Review of U.S. Pat. No. 8,449,289; the corrected petition dated Jul. 22, 2013).

United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, Case IPR2013-00435, U.S. Pat. No. 8,449,289; Notice of Filing Date Accorded to Petition and Time for Filing Patent Owner Preliminary response mailed Jul. 17, 2013.

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435, Petition for Inter Partes Review of U.S. Pat. No. 8,449,289; and Exhibit list; the petition dated Jul. 10, 2013.

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435; Exhibit TBC 1001, 1002, and 1003 dated Jul. 10, 2013.

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435; Exhibit TBC 1004, Declaration of Randall L. May (Inter Partes review of U.S. Pat. No. 8,449,289) dated Jul. 10, 2013.

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued

May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435; Exhibit TBC 1005, File History of U.S. Pat. No. 8,449,289.

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435; Exhibit TBC 1006, File History of U.S. Pat. No. 8,449,289 (with pagination).

In the United States Patent and Trademark Office Before the Patent Trial and Appeal Board, *The Brinkmann Corporation*, Petitioner, v. *Coprecitec, S.L.*, Patent Owner, U.S. Pat. No. 8,449,289, Issued May 28, 2013, title Multi-Gas Appliance; Inter Partes Review No. IPR2013-00435; Patent Owner's Mandatory Notices Pursuant to 37 C.F.R. § 42.8 dated Jul. 31, 2013.

Protest Under 37 CFR § 1.291 in U.S. Appl. No. 13/859,576, (Reissue application of U.S. Pat. No. 7,963,763; reissue application filed Apr. 9, 2013) Protest filed Jul. 25, 2013, In the United States Patent and Trademark Office, filed by The Brinkmann Corporation with Exhibit A, GB Patent No. 1,165,762 published Oct. 1, 1969. Protest Under 37 CFR § 1.291 in U.S. Appl. No. 13/859,576, (Reissue application of U.S. Pat. No. 7,963,763; reissue application filed Apr. 9, 2013) Protest filed Jul. 25, 2013, In the United States Patent and Trademark Office, filed by The Brinkmann Corporation, Exhibit B, GB Patent No. 1,444,673 published Aug. 4, 1976.

Protest Under 37 CFR § 1.291 in U.S. Appl. No. 13/859,576, (Reissue application of U.S. Pat. No. 7,963,763; reissue application filed Apr. 9, 2013) Protest filed Jul. 25, 2013, In the United States Patent and Trademark Office, filed by The Brinkmann Corporation, Exhibit C, U.S. Pat. No. 5,983,884 issued Nov. 16, 1999.

Protest Under 37 CFR § 1.291 in U.S. Appl. No. 13/859,576, (Reissue application of U.S. Pat. No. 7,963,763; reissue application filed Apr. 9, 2013) Protest filed Jul. 25, 2013, In the United States Patent and Trademark Office, filed by The Brinkmann Corporation, Exhibit D, Randall L. May Declaration dated Jul. 25, 2013.

Protest Under 37 CFR § 1.291 in U.S. Appl. No. 13/859,576, (Reissue application of U.S. Pat. No. 7,963,763; reissue application filed Apr. 9, 2013) Protest filed Jul. 25, 2013, In the United States Patent and Trademark Office, filed by The Brinkman Corporation; Exhibit E, U.S. Pat. No. 7,963,763 issued Jun. 21, 2011 and Exhibit F, PTO/SB/08a.

International Preliminary Report on Patentability Application No. PCT/EP2006/001143 issued by The International Bureau of WIPO, Geneva, Switzerland, dated Aug. 14, 2007.

International Search Report Application No. PCT/EP2006/001143 issued by European Patent Office, Rijswijk, Netherlands, dated Aug. 1, 2006.

Defendant's Initial Disclosures; *Coprecitec, S.L., et al. v. The Brinkmann Corporation*, United States District Court, Northern District of Georgia, Atlanta Division, civil action file No. 1:12-CV-1480-AT, all pp. 1-16 thereof, together with Attachments A and C, all pages thereof and the Certificate of Service, one page, all pages of the document attached hereto, filing dated Aug. 13, 2012, filed by Angela M. Spivey of McGuire Woods LLP, Atlanta, Georgia.

Defendant's Invalidity Contentions; *Coprecitec, S.L., et al. v. The Brinkmann Corporation*, United States District Court, Northern District of Georgia, Atlanta Division, civil action No. 1:12-CV-1480-AT, all pp. 1-16 thereof, together with Attachment, Exhibit A, all pp. 1-23 thereof and the Certificate of Service, two pages; all pages of the document attached hereto, filing dated Oct. 19, 2012, filed by Angela M. Spivey of McGuire Woods LLP, Atlanta, Georgia.

Defendant's Response to Plaintiff's Infringement Contentions; *Coprecitec, S.L., et al. v. The Brinkmann Corporation*, United States District Court, Northern District of Georgia, Atlanta Division, civil action file No. 1:12-CV-1480-AT, all pages 1-4 thereof, together with Attachment, Exhibit A, all pp. 1-18 thereof and the Certificate of Service, two pages; all pages of the document attached hereto, filing dated Oct. 19, 2012, filed by Angela M. Spivey of McGuire Woods LLP, Atlanta Georgia.


(56)

**References Cited**

OTHER PUBLICATIONS

PCT/EP2006/001143 International Search Report dated Aug. 1, 2008.

\* cited by examiner



**MULTI-GAS VALVE FOR A GAS BURNING  
APPLIANCE**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.**

The present application is a continuation application of copending patent application Ser. No. 12/069,657, filed on Feb. 12, 2008, which is entitled "MULTI-GAS COOKER, WITH A ROTARY VALVE PROVIDED WITH INTER-CHANGEABLE REGULATING MEANS", which is a continuation of patent application U.S. Ser. No. 11/143,785, which was filed on Jun. 1, 2005, and claims priority to Spanish Patent Application ES-U200500309, which was filed on Feb. 10, 2005, the disclosures of all of which being herein incorporated by reference.

TECHNICAL FIELD

The present invention relates to a gas valve of the conical rotary plug type attached to an actuating shaft, being the gas valve mounted on the panel of a cooking appliance and its outlet conduit faced to a burner inlet, wherein the rotary plug is provided with a control knob, and aperture means for adjusting the flow rate according to the fuel gas family supplied to the cooking appliance, and the outlet conduit with an injection means.

PRIOR ART

Gas valves of the above-defined type are already known, wherein the gas valve is mounted on the front control panel with the actuating shaft passing through a external control panel in the appliance, and the valve body resting inside the appliance faced to the fuel inlet of a burner. The external free end of the actuating shaft is fitted with a rotary control knob inserted in the latter. The control knob is removable from the shaft by pulling it out. The hollow body of the valve has its own gas outlet conduit which is connected to the respective appliance burner. The outlet conduit is provided with an injector nozzle having a calibrated discharge orifice in correspondence with the gas family supplied to the appliance, LP gas or N gas. In the spacing apart between the discharge nozzle of the valve and the burner inlet, is taken the primary air to feed the fuel mixture into the burner.

An example of rotary valve of the above type is disclosed in U.S. Pat. No. 6,520,481-B2, having its actuating shaft coupled to a frusto-conical regulating plug or valve plug, which is able to rotate a given angle for the supply of a gas flow from two angular positions spaced around 120.degree. apart, corresponding respectively to a high or maximum flow "Qmax" and to a low or minimum flow "Qmin", the latter applied to "gentle boiling". The rotation of the shaft as far as one of the angular positions, is started from an initial valve closed "OFF" position.

In this type of known valves the actuating shaft has a pin protruding in a radial direction to limit its angular travel, guided on a circular surface in the inner face of the body cover or valve cap, or in some other part of the valve body. The total travel of the regulating plug thus limited is, for instance, 270 degrees from the OFF position. The end

position corresponds to Qmin. Any of the flows Qmax, Qint (intermediate flow) and Qmin is regulated by way of a corresponding hole or groove in the regulating plug facing the outlet conduit. All the flow rate are supplied from a common inlet conduit through an inner chamber in the regulating plug which is in communication with an outlet conduit. The Qmin outlet hole or groove shaped opening has an area of calibrated section for a standard type of given fuel gas, adjusted according to the output power of the cooking appliance burner.

Solutions are already known for a single valve to be mounted on cooking appliances that use two different types of gas, such as natural gas (NG) or liquefied petroleum gas (LPG). For example in U.S. Pat. No. 5,009,393, an additional valve element in the form of a sleeve is inserted in the inner chamber of the valve regulating plug. The area of the opening section for the passage of gas flow towards the outlet, that which corresponds to low flow or minimum flow Qmin, is adjusted by rotating this added valve sleeve which thus modifies the uncovered section area of the outlet opening. This known solution has the disadvantage that for adjusting the Qmin for the rotation of the valve sleeve, it is necessary to use a screwdriver, which has to be inserted from an opening in the actuating shaft until it reaches the valve sleeve and to transmit a precise turn. A known regulating gas valve, for example the disclosed in U.S. Pat. No. 4,947,891-A, comprises a rotary valve plug coupled to a passage disc provided aperture means for regulating the gas flow supplied to the burner, and an injector nozzle threaded to the outlet conduit. The passage disc is held stationary in the valve housing, and provides an arc groove restricting the passage area for the flow, for use with both LP gas and N gas, while the injection orifice of the nozzle is limiting the large changes of gas flow.

DISCLOSURE OF THE INVENTION

The object of the invention is a gas domestic cooking appliance, provided with at least a rotary valve of the type with a frusto-conical regulating plug coupled to an actuating shaft and to a control knob, being capable of supplying the different required flows of gas lying at a plurality of angular positions, of either of the two different types of gas, N gas or LP gas, the valve having a control knob being interchangeable on the actuating shaft, with a means for limiting the angle of rotation of the regulating plug, and a mountable injector nozzle in the valve outlet conduit, which can be or not provided, in order the valve to be adapted to the type of gas used by the appliance.

The use of a single valve unit for regulating the flow of two different gas families is an advantage of the gas valve invention, when mounted on a cooking appliance. During the startup of the cooking appliance the user only has to carry out a choice for a control knob from the two possible units accompanying the valve in accordance with the type of fuel gas NG or LP appropriate for the cooking appliance. In this way, there is no need to use tools for adjusting the flow, nor to learn how to adjust the regulating plug as is required in the prior art valve.

The gas valve according to the invention is capable of providing two angular positions of the regulating plug, both spaced apart from each other to supply a different minimum flow Qmin according to the type of gas, NG or standard LPG, used as the fuel for the appliance, being the two different angular positions established by means of a respective rotation stop. At the same time, the user chooses for providing or not the outlet conduit of the valve with an

3

injector nozzle to supply a maximum flow,  $Q_{max}$ , of LP gas or N gas respectively. Neither it is necessary to use tools for carrying out this mounting operation.

#### DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sectional view of a gas valve according to the invention, fitted on a panel of a cooking appliance.

#### DETAILED DESCRIPTION OF AN EMBODIMENT OF THE INVENTION

In reference to FIG. 1, an embodiment of a gas cooking appliance 1 such as a barbecue comprises a control panel 2 on which are mounted one or more rotary gas valves 3 of the type with a frusto-conical regulating plug 6. The cooking appliance 1 may be of two types in respect of the type of gas supplied, natural gas (NG) or liquefied gas (LPG) from the external source—GAS IN—through a valve inlet conduit 4 in the valve body 3a. Each one of the valves 3 mounted on the panel 2 is always of a single type, all with a same valve body 3a and regulating plug 6. The inlet flow “Q” is transmitted to an internal chamber 8 in regulating plug 6 in communication with an outlet conduit 5 in the valve body 3a. The regulating plug 6 rotates around a central axis 10 actuated by shaft 7 for the supply of the flow “Q”, which is directed towards a burner inlet duct 25 on the appliance, being the latter specifically adapted to either N gas or LP gas supplying.

The valve body 3a has an elongated shape with a frusto-conical central housing cavity 15, wherein the regulating plug 6 is pushed by a spring 11 for a tight sealing. The free end of the actuating shaft 7 is installed passing through a hole 2a in the appliance panel 2, and afterwards the user fits it with a control knob 9, which is chosen from the two different units of control knob 9, both supplied to the user with each valve unit 3. A cover or valve cap 12 protecting the housing cavity 15, has a tubular bushing 12b for guiding the actuating shaft 7 in rotation.

The regulating plug 6 may rotate with the shaft 7 an angle “A” in either of the two directions from an initial angular position “zero” degrees corresponding to the valve closed condition “OFF”, to an angular position “A” between 90.degree. and 270.degree. The OFF position is the initial end of the rotational travel “A”, and it is established for example by a radial pin 13 on the shaft. The cover 12 presents a sliding surface for the radial pin 13, up to a recess 12a in the cover acting as a stop for the rotation of the radial pin 13.

In reference to the valve embodiment represented in FIG. 1, from the angular position OFF rotating in a clockwise direction, the frusto-conical plug 6 may regulate the supply of different gas flows, a maximum flow “ $Q_{max}$ ”, a minimum “ $Q_{min}$ ” and an intermediate flow “ $Q_{int}$ ” between the  $Q_{max}$  and the  $Q_{min}$ , in function of the rotated angle “A”. A constant minimum flow “ $Q_{min}$ ” of the N gas must be higher than a “ $Q_{min}$ ” of the LP gas, when supplied to a respective burner in both cases of the same power. In function of whether N or LP gas is supplied to the cooking appliance, the control knob 9 to be fitted on the actuating shaft 7 is distinguished for example by means of a lug 14 integral with the control knob. The control knob 9 represented on the appliance in FIG. 1 is adapted for the supply of N gas, having a protuberance or lug 14 projecting from a knob base 9a facing the panel 2. The second type of control knob 9 having not the protuberance 14, is chosen for its mounting on a cooking appliance that uses LP gas.

4

The regulating plug 6 rotates to a determined angular position for the supply of a maximum flow “ $Q_{max}$ ” of either NG or LPG on both types of cooking appliance 1. The  $Q_{max}$  inflow is regulated by a through hole 16 in the regulating plug, facing the inlet conduit 4. If the regulating plug 6 is rotated further, an intermediate flow “ $Q_{int}$ ” will be supplied through a groove which has a decreasing area. In accordance with the angle rotated, a through hole 18 or a through hole 19 for a “ $Q_{min}$ ” flow is facing the inlet conduit 4 at an ensuing angular position different from one another depending on the gas supplied to the valve, N gas or LP gas respectively. Diameter of each one of holes 18 and 19 are calibrated for the correspondent supply of a  $Q_{min}$ .

When installed on the panel 2, the control knob unit 9 chosen for the supply of LPG, this has no lug 14 or any other element for limiting the angle “A” of rotation. Thus, the regulating plug 6 may rotate as far as an angular position of 270 degrees. The cover 12, provided with the tubular portion 12b for guiding the valve shaft 7, and said recess 12a for limiting said longer angular travel corresponding to the LP gas  $Q_{min}$ , is made economically by die-stamping operations only. The economical cost of moulding two types of control knob 9, with and without integral lug 14 for guiding its rotation, is also low.

Besides that described above, other embodiments of the regulating passage openings 18,19 for the different values of  $Q_{min}$  are possible. Half of the control knob 9 units of the kind applied to the NG appliance, may be manufactured with some integrated guiding means 14 on the control knob 9, and interact with some part of the cooking appliance 1 associated with the panel 2, for example a running slot 20 in a panel wall, in order a limit position to be arranged of rotation travel other than that imposed by the actuating shaft.

The arrangement of the two different stop means 12a and 20, respectively in the valve body 3a and on the control panel 2, each one with a pre-set circular extension, matches up with the two angular travels “A” corresponding to that of the two hole passages 18 and 19 for supplying a constant NG  $Q_{min}$  or a constant LPG  $Q_{min}$ . In this way, a single valve unit 3 is used, without having to make any adjustment, valid for any type of gas supplied to the cooking appliance 1.

The burner of the cooker appliance (not represented in the drawing), supplied by the valve unit 3, is placed with its feed conduit 25 facing the valve outlet conduit 5. The space of air apart from the burner conduit 25 permits the fuel mixture 26 of primary air with the  $Q_{max}$  flow of outgoing gas from the valve 3 for injection into the burner feed conduit 25.

In accordance with the type of gas, N gas or LP gas, in order to provide the valve 3 with means for adjustment and injection of the  $Q_{max}$  gas flow outgoing from the regulating plug 6, the valve outlet conduit 5 has a press-in or threaded disc 21 inserted for the restriction of the  $Q_{max}$  flow through a calibrated central hole 22, which permits the passage of a given  $Q_{max}$  flow of N gas, substantially higher than the  $Q_{max}$  of LP gas which it is necessary to inject into the burner of the same output. The restrictor disc 21 remains fitted on the valve all the time irrespective of the type of gas used. When the cooker appliance 1 is supplied with LP gas, it is necessary to restrict the outgoing  $Q_{max}$  flow so as to adapt the output of the burner, so the valve outlet conduit 5 is also fitted with an injection nozzle 23, threaded manually into the mouth of the conduit 5, and it has a calibrated hole 24 for a given  $Q_{max}$  flow of LP gas, substantially smaller than the hole in the restrictor disc, the latter secured in a manner valid for the passage of a  $Q_{max}$  both of N gas and of LP gas.

5

Thus, by means of the interchangeable control knob **9** and the installation or otherwise of the injection nozzle **23**, all the cooker appliances, whether they be N gas or LP gas, are fitted with the same valve units **3** without the need to make any flow regulating adjustment. Together with the valve unit **3**, the user receives a kit containing two different control knob units **9**, easily distinguishable from each other, and an injection nozzle **23**. In accordance with the type of gas used, the user chooses one of the controls **9** for manual installation on the actuating shaft **7**, and also decides whether or not to install the injection nozzle **23**, which is also fitted manually for the injection of LP gas without the need for tools.

What is claimed is:

**[1.** A valve comprising:

a valve body having a rotatable regulating organ positioned between a valve inlet and a valve outlet, the regulating organ configured to vary the flow rate of the gaseous fuel at the valve outlet as a function of an angular position of the regulating organ, a first angular position of the regulating organ determines a first minimum flow rate of a natural gas, and a second angular position of the regulating organ, successive to the first angular position, determines a second minimum flow rate of a liquefied petroleum gas,

a control knob used to manipulate the angular position of the regulating organ coupled to the regulating organ by an actuating shaft, the control knob having a feature to prevent rotation of the regulating organ beyond the first angular position, absent the presence of the feature on the control knob the regulating organ is rotatable to the second angular position,

the valve outlet having a restriction that determines a maximum flow rate of the natural gas.]

**[2.** A gas burning appliance adapted for a supply of natural gas and liquefied petroleum gas to a burner comprising:

at least one regulating valve with a valve body, the valve body having a rotatable regulating organ operationally coupled to an actuating shaft that protrudes from a control panel of the cooking appliance, the regulating organ positioned between a valve inlet and a valve outlet and configured to vary the flow rate of the gaseous fuel at the valve outlet as a function of an angular position of the regulating organ, a first angular position of the regulating organ determining a first minimum flow rate of the natural gas, and a second angular position of the regulating organ, successive to the first angular position, determining a second minimum flow rate of the liquefied petroleum gas,

a control knob attached to the actuating shaft useable to manipulate the angular position of the regulating organ, the control knob having a feature that cooperates with a part of the appliance other than the valve to prevent rotation of the regulating organ beyond the first angular position, the regulating organ rotatable to the second angular position successive to the first angular position absent the presence of the feature on the control knob, the valve outlet having a restriction that determines a maximum flow rate of the natural gas.]

**[3.** The gas burning appliance of claim **2** wherein the feature of the control knob projects from a base of the control knob facing the control panel and travels within a groove in the control panel, the groove having an end corresponding to the first angular position.]

**[4.** The gas burning appliance of claim **2** wherein the actuating shaft has associated with it an engagement feature that cooperates with a part of the valve to impede rotation of the regulating organ beyond the second angular position.]

6

*5. A valve adapted to regulate the flow of both a natural gas and a liquefied petroleum gas comprising:*

*a valve body having disposed therein a rotatable regulating organ positioned between a valve inlet and a valve outlet, the valve outlet having a first restriction and a second restriction successive to the first restriction, the first restriction comprising a first hole calibrated to provide a given maximum flow rate of the natural gas at a first pressure in the absence of the second restriction, the second restriction removeably attached to the valve outlet, the second restriction comprising a second hole calibrated to provide a given maximum flow rate of the liquefied petroleum gas at a second pressure, the second hole being smaller than the first hole, the regulating organ being configured to vary the flow rate of the gaseous fuel at the valve outlet as a function of an angular position of the regulating organ, a first angular position of the regulating organ determines a first minimum flow rate of the natural gas, and a second angular position of the regulating organ, successive to the first angular position, determines a second minimum flow rate of the liquefied petroleum gas, the valve further comprising a stop that prevents rotation of the regulating organ beyond the second angular position.*

*6. The valve according to claim 5, wherein the first restriction is formed within a press-in disc that is pressed in the valve outlet.*

*7. The valve according to claim 6, wherein the first restriction is formed within a press-in disc that is pressed in the valve outlet.*

*8. The valve according to claim 6, wherein the first restriction is formed within a threaded disc that is threaded in the valve outlet.*

*9. The valve according to claim 5, wherein the first restriction is formed within a press-in disc that is pressed in the valve outlet.*

*10. The valve according to claim 5, wherein the first restriction is formed within a threaded disc that is threaded in the valve outlet.*

*11. The valve according to claim 5, further comprising a control knob used to manipulate the angular position of the regulating organ coupled to the regulating organ by an actuating shaft, the control knob having a feature to prevent rotation of the regulating organ beyond the first angular position, absent the presence of the feature on the control knob the regulating organ is rotatable to the second angular position.*

*12. A gas burning appliance adapted for a supply of natural gas and liquefied petroleum gas to a burner, the gas burning appliance comprising:*

*at least one regulating valve with a valve body, the valve body having disposed therein a rotatable regulating organ operationally coupled to an actuating shaft that protrudes from a control panel of the cooking appliance, the rotatable regulating organ positioned between a valve inlet and a valve outlet, the valve outlet being in fluid communication with the burner,*

*the valve outlet having a first restriction and a second restriction successive to the first restriction, the first restriction comprising a first hole calibrated to provide a given maximum flow rate of the natural gas at a first pressure in the absence of the second restriction, the second restriction removeably attached to the valve outlet, the second restriction comprising a second hole calibrated to provide a given maximum flow rate of the liquefied petroleum gas at a second pressure, the sec-*



7

ond hole being smaller than the first hole, the regulating organ being configured to vary the flow rate of the gaseous fuel at the valve outlet as a function of an angular position of the regulating organ, a first angular position of the regulating organ determines a first minimum flow rate of a natural gas, and a second angular position of the regulating organ, successive to the first angular position, determines a second minimum flow rate of a liquefied petroleum gas, the valve further comprising a stop that prevents rotation of the regulating organ beyond the second angular position.

13. The gas burning appliance according to claim 12, wherein the second restriction is removeably attached to the valve outlet by a threaded connection.

14. The gas burning appliance according to claim 13, wherein the first restriction is formed within a press-in disc that is pressed in the valve outlet.

15. The gas burning appliance according to claim 13, wherein the first restriction is formed within a threaded disc that is threaded in the valve outlet.

8

16. The gas burning appliance according to claim 12, wherein the first restriction is formed within a press-in disc that is pressed in the valve outlet.

17. The gas burning appliance according to claim 12, wherein the first restriction is formed within a threaded disc that is threaded in the valve outlet.

18. The gas burning appliance according to claim 12, further comprising a control knob attached to the actuating shaft useable to manipulate the angular position of the regulating organ, the control knob having a feature that cooperates with a part of the appliance other than the valve to prevent rotation of the regulating organ beyond the first angular position, the regulating organ rotatable to the second angular position successive to the first angular position absent the presence of the feature on the control knob.

19. The gas burning appliance according to claim 18, wherein the feature of the control knob projects from a base of the control knob facing the control panel and travels within a groove in the control panel, the groove having an end corresponding to the first angular position.

\* \* \* \* \*