

US00RE46858E

(19) **United States**
(12) **Reissued Patent**
Harif

(10) **Patent Number: US RE46,858 E**
(45) **Date of Reissued Patent: May 22, 2018**

(54) **CUTTING TOOL, CUTTING TOOL HOLDER AND CUTTING INSERT THEREFOR**

(71) Applicant: **No Screw Ltd.**, Holon (IL)
(72) Inventor: **Gershon Harif**, Ramat Gan (IL)
(73) Assignee: **NO SCREW LTD.**, Holon (IL)

(21) Appl. No.: **15/348,336**
(22) Filed: **Nov. 10, 2016**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,882,404**
Issued: **Nov. 11, 2014**
Appl. No.: **13/203,534**
PCT Filed: **Feb. 25, 2010**
PCT No.: **PCT/IL2010/000162**
§ 371 (c)(1),
(2) Date: **Aug. 26, 2011**
PCT Pub. No.: **WO2010/097797**
PCT Pub. Date: **Sep. 2, 2010**

U.S. Applications:

(60) Provisional application No. 61/202,445, filed on Feb. 27, 2009, provisional application No. 61/202,771, filed on Apr. 2, 2009.

(51) **Int. Cl.**
B23C 5/22 (2006.01)
B23C 5/06 (2006.01)
B23C 5/10 (2006.01)

(52) **U.S. Cl.**
CPC **B23C 5/221** (2013.01); **B23C 5/06** (2013.01); **B23C 5/109** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **B23C 5/06**; **B23C 5/109**; **B23C 5/221**;
B23C 2200/206; **B23C 2200/361**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,027,623 A 4/1962 Severson et al.
3,138,846 A 6/1964 Conti et al.
(Continued)

FOREIGN PATENT DOCUMENTS

AT 6206 6/2003
AT 006206 U1 6/2003
(Continued)

OTHER PUBLICATIONS

Thomson Scientific , XP-002587912 Abstract, WPI Week 198537, Jan. 8, 1984.

(Continued)


Primary Examiner — Jeffrey R Jastrzab

(74) *Attorney, Agent, or Firm* — Dorsey & Whitney LLP

(57) **ABSTRACT**

A cutting tool comprising a cutting tool holder and a cutting insert adapted to be mounted thereon. The tool holder comprises an insert seat defined by a base and at least one side wall extending from the base to define an insert seat space adapted to receive therein the insert. The seat comprises a support element extending into the insert seat from the base, and a fastening member engageable with the seat. The fastening member is displaceable with respect thereto between a mounting position adapted to allow the insert to be mounted onto the seat and a securing position adapted for securing the insert within the seat. The insert is formed with a securing cavity and when the insert is mounted onto the tool holder and is in the securing position, a portion of the support element and the fastening member is received within the cavity of the insert.

19 Claims, 53 Drawing Sheets



(52) **U.S. Cl.**
 CPC .. B23C 2200/128 (2013.01); B23C 2200/165 (2013.01); B23C 2200/206 (2013.01); B23C 2200/361 (2013.01); B23C 2200/367 (2013.01); B23C 2210/16 (2013.01); B23C 2210/165 (2013.01); B23C 2210/168 (2013.01); B23C 2260/84 (2013.01); Y10T 407/192 (2015.01); Y10T 407/1922 (2015.01); Y10T 407/1924 (2015.01); Y10T 407/1936 (2015.01); Y10T 407/2276 (2015.01); Y10T 407/23 (2015.01); Y10T 407/28 (2015.01)

(58) **Field of Classification Search**
 CPC B23C 2200/367; B23C 2210/16; B23C 2210/165; B23C 2210/168; B23C 2260/84; Y10T 407/23; Y10T 407/28; Y10T 407/2276; Y10T 407/1936
 USPC 407/40-42, 47-50, 103, 104, 113
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,341,919	A	9/1967	Lovendahl et al.	
3,341,921	A *	9/1967	Weller et al.	407/104
3,648,341	A	3/1972	Vielle et al.	
3,740,807	A	6/1973	Getts et al.	
3,747,179	A	7/1973	Lovendahl et al.	
3,805,351	A	4/1974	Mayer et al.	
3,913,197	A	10/1975	Wolf et al.	
3,925,868	A *	12/1975	Singh	407/104
3,946,473	A	3/1976	Petersen et al.	
4,035,887	A	7/1977	Hertel et al.	
4,044,440	A	8/1977	Stier et al.	
4,283,163	A	8/1981	Graefe et al.	
4,397,592	A	8/1983	Erickson et al.	
4,507,023	A	3/1985	Shikata	
4,527,930	A	7/1985	Harroun et al.	
5,199,828	A	4/1993	Jansson et al.	
5,836,724	A	11/1998	Satran et al.	
6,155,754	A *	12/2000	Jonsson	B23B 27/1622
				407/103
6,158,928	A *	12/2000	Hecht	407/102
6,168,356	B1 *	1/2001	Sjoo	B23B 27/065
				407/104
6,579,042	B1	6/2003	Shiraiwa	
7,264,424	B2	9/2007	Berminge et al.	
7,273,331	B2	9/2007	Giannetti et al.	
7,677,842	B2 *	3/2010	Park	407/113
7,775,750	B2	8/2010	Satran et al.	
7,780,380	B2	8/2010	Watanabe et al.	
8,568,064	B2	10/2013	Carl	
8,821,079	B2	9/2014	Hecht	
8,882,404	B2	11/2014	Harif	
9,120,154	B2	9/2015	Hen et al.	
2003/0031519	A1	2/2003	Hecht	
2005/0152754	A1 *	7/2005	Wiman et al.	407/103
2007/0003384	A1	1/2007	Ballas et al.	
2008/0166191	A1 *	7/2008	Andersson	B23C 5/2208
				407/103
2008/0193233	A1	8/2008	Park	
2009/0092451	A1	4/2009	Harif	
2009/0238651	A1	9/2009	Nguyen	
2010/0272522	A1	10/2010	Hecht	
2011/0305532	A1	12/2011	Harif	
2012/0082521	A1	4/2012	Burtscher et al.	

2012/0170988	A1	7/2012	Kountanya et al.
2013/0004252	A1	1/2013	Yoshioka
2013/0051938	A1	2/2013	Tulchinsky et al.

FOREIGN PATENT DOCUMENTS

CN	1368416	A	9/2002	
CN	1623725	A	6/2005	
CN	101028654	A	9/2007	
CN	102781613	A	11/2012	
DE	2853313	A1	6/1980	
DE	3301191		7/1984	
DE	3301191	A1 *	7/1984 B23B 5/22
EP	0001764	A1	5/1979	
EP	37554	A1	10/1981	
EP	0179033	A2 *	4/1986 B23B 27/00
EP	0300172	A2 *	1/1989 B23B 27/1622
EP	0402854		12/1990	
EP	0487478	A1	5/1992	
EP	0730926	A1	9/1996	
EP	2487001	A2	8/2012	
EP	2614907	A1	7/2013	
GB	1011658		12/1965	
GB	1527091	A	10/1978	
GB	1584237	A	2/1981	
GB	2057940	A	4/1981	
GB	2098105		11/1982	
JP	Hei1-132319		9/1989	
JP	9-108909		4/1997	
JP	2001-507287		6/2001	
JP	2004-521767		7/2004	
JP	2010/507496		3/2010	
SE	463703	B	1/1991	
SE	502241	A	9/1995	
SE	529642	C2	10/2007	
SU	665993	A1	6/1979	
SU	703248	A1	12/1979	
SU	831394	A1	5/1981	
SU	848158	A1	7/1981	
SU	1079370	A1	3/1984	
WO	93/17822		9/1993	
WO	96/26802		9/1996	
WO	98/30349		7/1998	
WO	99/54078		10/1999	
WO	2003004204	A1	1/2003	
WO	20030042404	A1	1/2003	
WO	03/022495		3/2003	
WO	03/101653		12/2003	
WO	WO 2007/067138	A1	6/2007	
WO	2007/098043		8/2007	
WO	2007/134930		11/2007	
WO	2008114242	A1	9/2008	
WO	2008/149371		12/2008	
WO	2009028747	A1	3/2009	
WO	2015033338	A2	3/2015	

OTHER PUBLICATIONS

International Search Report and Written Opinion from International Application No. PCT/IL2010/000162 dated Jun. 30, 2010.
 Thomson Scientific, London GB. AN 1980-H5598C, Week 198537, for SU 709261.
 Database WPI Week 198537, Thomson Scientific, XP-002587912, retrieved on Jun. 24, 2010.
 International Search Report and Written Opinion from International Application No. PCT/IL2010/000162 dated Jun. 30, 2011.

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 2A




Fig. 2B




Fig. 2D




Fig. 2C




Fig. 2F

Fig. 2E




Fig. 3A




Fig. 3B




Fig.4A




Fig.4B




Fig.4C




Fig. 5A




Fig. 5B




Fig. 5C




Fig. 6A




Fig. 6B






Fig. 7






Fig. 9A




Fig. 9B




Fig. 10B




Fig. 10C




Fig. 10A




Fig. 11A




Fig. 11B




Fig. 12A




Fig. 13B




Fig. 13C




Fig. 13A




Fig. 14A




Fig. 14B




Fig. 14C




Fig. 15A




Fig. 15B




Fig. 15C




Fig. 15D




Fig. 16B




Fig. 16C




Fig. 16A




Fig. 17A




Fig. 17B




Fig. 18




Fig. 19




Fig. 20A




Fig. 20C

Fig. 20B




Fig. 21




Fig. 22A




Fig. 22B






Fig. 23






Fig. 25




Fig. 26A




Fig. 26B




Fig. 26C




Fig. 27A




Fig. 27B




Fig. 28A




Fig. 28B




Fig. 28C




Fig. 28D




Fig. 28E




Fig. 29




Fig. 30A




Fig. 30B




Fig. 30C




Fig. 30D




Fig. 30E




Fig. 31A




Fig. 31B




Fig. 32A




Fig. 32B




Fig. 32C




Fig. 32D




Fig. 33B




Fig. 33C




Fig. 33D




Fig. 33E




Fig. 34A




Fig. 34B




Fig. 34C




Fig. 35A

Fig. 35B

Fig. 35C

CUTTING TOOL, CUTTING TOOL HOLDER AND CUTTING INSERT THEREFOR

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a U.S. Nationalization of PCT International Application No. PCT/IL2010/000162 filed 25 Feb. 2010, entitled "CUTTING TOOL, CUTTING TOOL HOLDER AND CUTTING INSERT THEREFOR," which claims priority to U.S. Provisional Patent Application No. 61/202,445 filed 27 Feb. 2009 and U.S. Provisional Patent Application No. 61/202,771 filed 2 Apr. 2009, the contents of each of the foregoing applications are incorporated herein, in their entirety, by this reference.

FIELD OF THE INVENTION

This invention relates to cutting tools, cutting tool holders and cutting inserts to be used therein.

BACKGROUND OF THE INVENTION

A cutting tool is generally formed with at least one cutting edge, and is adapted for the removal of material from a workpiece by bringing the cutting edge into contact with the workpiece and displacing the cutting edge with respect to the workpiece either by displacing the cutting tool with respect to the workpiece or vice versa.

The cutting edges of cutting tools wear rapidly when used for cutting operations, particularly when cutting hard materials such as metal, and therefore they must be frequently replaced or re-sharpened. In many types of cutting tools, such as tool adapted for milling/drilling/turning machines, the cutting tool may comprise a plurality of cutting inserts, each being formed with at least one cutting edge, the inserts being fixed within seats of a cutting tool holder to form a cutting tool.

In a conventional cutting tool, the cutting insert is attached within the seat of the cutting tool by a fastener passing through a bore in the cutting insert into the bottom of the seat of the cutting tool. Indexing the cutting insert to enable the use of another cutting edge requires the removal of the fastener, the reorientation of the cutting insert, and the reattachment of the cutting insert within the seat of the cutting tool by the fastener. Each of these operations involves time and labor, and since cutting tools generally include a plurality of such cutting inserts, the time and labor costs involved in indexing the cutting inserts in a cutting tool are considerable.

In order to overcome technical problems, among which is the one presented above, alternative methods of mounting the cutting inserts onto the cutting tool holder have been devised as disclosed in WO2008/149371 and U.S. Ser. No. 12/314,428 to the applicant.

SUMMARY OF THE INVENTION

According to one aspect of the disclosed subject matter of the present application there is provided a cutting tool holder

adapted for mounting thereon a cutting insert to form a cutting tool, said cutting tool holder comprising an insert seat defined by at least a base and at least one side wall extending from said base to defined an insert seat space adapted to receive said cutting insert, said insert seat further comprising a support element extending into said insert seat from said base, and, at least in operation, a fastening member engageable with said insert seat and displaceable with respect thereto between a mounting position adapted to allow said cutting insert to be mounted onto said insert seat and a securing position adapted for securing the cutting insert within said insert seat, wherein, in said securing position, said support element and said fastening member constitute together no less than 15% of said insert seat space.

According to another aspect of the disclosed subject matter of the present application there is provided a cutting tool holder adapted for mounting thereon a cutting insert to form a cutting tool, said cutting tool holder having a base surface defined by a circumferential edge, said base surface being provided with a support element extending therefrom, wherein an insert seat space may be defined by the base surface, a support plane parallel to the base surface intersecting said support element and a plurality of side planes extending between the base surface and the support plane along said circumferential edge, wherein the volume of said support element and fastening member is at least no less than 15% of the overall insert seat space.

According to a particular example, said support element and said fastening member may constitute together no less than 20% of the insert seat space, even more preferably no less than 25% of the insert seat space, and even more preferably no less than 30% of the insert seat space, and even more preferably no less than 50% of the insert seat space.

In particular, the volume of said support element alone may preferably constitute at least 15% of the overall volume of the cutting insert, even more preferably at least 20% of the overall volume of the cutting insert, and even more preferably at least 35% of the overall volume of the cutting insert.

In addition, in each cross-section of said insert seat space taken along a plane generally parallel to said base, the cross-sectional areas of both said support element and said fastening member may constitute together no less than 15% of the entire cross-sectional area of the insert seat space. In particular, the cross-sectional areas of both said support element and said fastening member may constitute together no less than 20% of the entire cross-sectional area of the insert seat space, even more preferably no less than 25% of the entire cross-sectional area of the insert seat space, and even more preferably no less than 30% of the entire cross-sectional area of the insert seat space, and even more preferably no less than 50% of the entire cross-sectional area of the insert seat space.

According to one particular example, said support element may be integrally formed with said cutting tool holder. According to another example, said support element may be adapted to engage said cutting tool holder in a detachable manner. In the latter case, according to one design, engagement between the support element and the cutting tool holder may be provided by the cutting tool being formed with a threaded support bore adapted to threadingly receive the support element, a portion of which is threaded. According to another design, said support element may be snap fitted to said cutting tool holder.

It should be appreciated that the term 'provided' is used heretofore both for a support element integrally formed with

3

said cutting tool holder and a support element adapted to engage said cutting tool holder.

In addition, said support element may be formed such that it has no point of contact with either of said two side walls of the insert seat. In other words, the support element extends from the base of the insert seat like a pillar.

The cutting tool formed upon mounting of the cutting insert onto the cutting tool holder may be adapted to rotate in a first direction about a central axis thereof, and the design of the support element may be formed with a first side wall generally perpendicular to said base and facing in said first direction, and a second side wall extending from said first wall in a direction opposite said first direction, at an acute angle θ to said first wall, both said first side wall and said second side wall being adapted for simultaneous engagement with said cutting insert. Furthermore, said second side wall may be formed with a recess adapted to receive a corresponding portion of the cutting insert when the latter is mounted onto the insert seat, in order to better secure the cutting insert within the insert seat.

In accordance with one example of the disclosed subject matter of the present invention, the fastening member may be displaceable with respect to the insert seat between a mounting position in which it is adapted to allow said cutting insert to be mounted onto said insert seat and a securing position in which it is adapted for securing the cutting insert within said insert seat.

According to a particular example, the fastening member may be such that in the mounting position it is disengaged from the insert seat and in said securing position it is engaged therewith. Alternatively, the fastening member may be such that in both said mounting position and said securing position, said fastening member remains in engagement with said insert seat. In the latter case, in said mounting position said fastening member may protrude to a first extent into the insert seat space, and in said securing position, it may protrude to a second extent into the insert seat space, greater than the first extent.

The fastening member may have a threaded portion, and adapted for threading into a corresponding threaded bore of said insert seat. Alternatively, said fastening member may be in the form of a securing pin adapted to be received within a corresponding bore of said insert seat. In the latter case, said securing pin may be spring biased into said securing position. In addition, said securing pin may also be faceted.

In all of the above examples, when in said securing position, said fastening member may be adapted to engage the support element.

According to another aspect of the disclosed subject matter of the present application there is provided a cutting insert adapted for mounting onto the cutting tool holder of the previous aspect, said cutting insert comprising a central securing cavity adapted to simultaneously receive therein at least a portion of both said support element and said fastening member.

According to particular example, the volume of said cavity may constitute at least 15% of the overall volume of the cutting insert. In particular, it may constitute no less than 20% of the overall volume of the cutting insert, even more preferably no less than 25% of the overall volume of the cutting insert, even more preferably no less than 30% of the overall volume of the cutting insert, and even more preferably no less than 50% of the overall volume of the cutting insert.

According to a specific design of the cutting insert, said cavity may have an inner surface formed with a first securing portion and a second securing portion opposite said first

4

portion, such that when said cutting insert is mounted onto the cutting tool holder, said first securing portion is adapted for engaging said support element, and said second securing portion is adapted for engaging said fastening member.

According to one example, said first portion may be in the form of an arced surface and said second portion may be planar. According to another example, said first portion and said second portion may both be in the form of arced surfaces.

The above cutting insert may be reversible.

According to yet another aspect of the disclosed subject matter of the present application there is provided a cutting tool comprising the cutting tool holder and the cutting insert of the previous aspects of the present invention.

Thus, the cutting insert of the cutting tool may be formed with a central opening, and said cutting tool holder may comprise an insert seat, a support element extending into said insert seat, and a fastening member displaceable with respect to said insert seat, wherein, when said cutting insert is mounted onto said insert seat, at least a portion of each of said support element and said fastening member is received within said central opening.

According to a particular example, at least one of the following may take place in said securing position:

the inner surface of said cavity may simultaneously engage both said support element and said fastening member, such that the inner surface of said cutting insert has thereon at least one contact point $[C_1]$ with said support element and at least one contact point $[C_2]$ with said fastening member;

said fastening member may simultaneously engage both said support element and said cutting insert, such that said fastening member has thereon at least one contact point $[C_2]$ with said cutting insert and at least one contact point $[C_3]$ with said support element; and

said support element may simultaneously engage both said fastening member and said cutting insert, such that said support element has thereon at least one contact point $[C_1]$ with said cutting insert and at least one contact point $[C_3]$ with said fastening member.

According to a particular design, the above contact points $[C_1, C_2$ and $C_3]$ may all be disposed along a single straight line.

The cutting tool may be such that it is adapted to revolve about a central axis thereof in a first direction, and when said cutting insert is mounted onto the cutting tool holder said fastening member is adapted to apply a force F_1 on said cutting insert in a direction generally along said central axis, said force F_1 pushing the cutting insert against the support element which is thereby adapted to apply a force F_2 on said cutting insert in a direction generally perpendicular to said central axis, the resultant force F_T of the two forces F_1 and F_2 being in a direction transverse to said central axis and opposite said first direction.

The cutting tool may be formed with two or more cutting portions, each cutting portion comprising two or more cutting inserts, the cutting edges of which form a continuous cutting edge in each cutting portion, wherein the special arrangement of the cutting inserts of the same cutting portion varies from one cutting portion to another. In particular, the cutting inserts in each cutting portion may be shifted at a distance d with respect to one another, and wherein the shift d varies from one cutting portion to another.

According to still another aspect of the disclosed subject matter of the present application, there is provided a cutting insert adapted for mounting onto a cutting tool holder in

5

order to form a cutting tool, said cutting insert having a top face and a bottom face with at least one side wall extending therebetween and being formed with a central cavity extending between said top face and said bottom face along a central axis, said cavity being adapted, when the cutting insert is mounted onto the cutting tool holder, for receiving within said cavity a securing element, said cavity taking up no less than 15% of the overall volume of the cutting insert.

The volume of said securing cavity may preferably constitute at least 20% of the overall volume of the cutting insert, even more preferably at least 25% of the overall volume of the cutting insert, even more preferably at least 30% of the overall volume of the cutting insert, and even more preferably at least 50% of the overall volume of the cutting insert.

In addition, in each cross-section of said cutting insert taken along a plane generally parallel to said top face or bottom face, the cross-sectional area of said cavity may constitute no less than 15% of the entire cross-sectional area of the cutting insert. In particular, the cross-sectional area of said cavity may constitute no less than 20% of the entire cross-sectional area of the cutting insert, even more preferably no less than 25% of the entire cross-sectional area of the cutting insert, even more preferably no less than 30% of the entire cross-sectional area of the cutting insert, and even more preferably no less than 50% of the entire cross-sectional area of the cutting insert.

Furthermore, in each cross-section taken generally parallel to said top face or said bottom face, the ratio D/T between the dimension of the cavity D and the dimension of the entire cutting insert T may be no less than 0.4, where both dimensions D and T are taken along a direction perpendicular to said at least one side face and passing through said central axis. In particular, the ratio D/T may be no less than 0.5, preferably no less than 0.6, even more preferably no less than 0.7 and even more preferably no less than 0.8.

The cutting insert may have an inner surface formed with a first securing portion and a second securing portion opposite said first portion, such that when said cutting insert is mounted onto the cutting tool holder, said first securing portion is adapted for engaging a support element of the cutting tool holder, and said second securing portion is adapted for simultaneously engaging a fastening member of the cutting tool holder.

According to one example, said first portion may be in the form of an arced surface and said second portion is planar. Alternatively, said first portion and said second portion may be in the form of arced surfaces.

The cutting insert may be reversible.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the invention and to see how it may be carried out in practice, embodiments will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

FIG. 1A is a schematic isometric view of a cutting tool according to one embodiment of the disclosed subject matter of the present application;

FIG. 1B is a schematic exploded isometric view of the cutting tool shown in FIG. 1A;

FIGS. 2A to 2D are respective schematic isometric, left side, right side and bottom views of a cutting insert used in the cutting tool shown in FIGS. 1A and 1B;

FIGS. 2E and 2F are schematic isometric cross-section views taken along lines A-A and B-B shown in FIG. 2D;

6

FIG. 3A is a schematic front view of the cutting tool holder shown in FIG. 3A;

FIG. 3B is a schematic isometric view of a mounting portion of a cutting tool holder used in the cutting tool shown in FIGS. 1A and 1B;

FIG. 4A is a schematic isometric enlarged view of detail A shown in FIG. 1A;

FIG. 4B is a schematic isometric cross-section view of the cutting tool shown in FIG. 4A taken along line I-I shown therein;

FIG. 4C is a schematic isometric view of the cutting tool shown in FIG. 4A, shown during assembly of the cutting insert thereof, prior to insertion of a fastening element;

FIG. 5A is a schematic isometric view of a cutting tool according to another embodiment of the disclosed subject matter of the present application;

FIG. 5B is a schematic isometric view of a mounting portion of a cutting tool holder used in the cutting tool shown in FIG. 5A;

FIG. 5C is a schematic isometric cross-section view of the cutting tool shown in FIG. 5A taken along line II-II shown therein;

FIG. 6A is a schematic isometric view of a cutting tool according to yet another embodiment of the disclosed subject matter of the present application;

FIG. 6B is a schematic exploded isometric view of the cutting tool shown in FIG. 6A;

FIG. 7 is a schematic isometric view of a mounting portion of a cutting tool holder used in the cutting tool shown in FIGS. 6A and 6B;

FIG. 8A is a schematic isometric cross-section view of the cutting tool shown in FIG. 6A taken along line III-III shown therein;

FIG. 8B is a schematic isometric of the cutting tool as shown in FIG. 8A, with the securing pin thereof removed;

FIG. 9A is a schematic isometric view of a cutting tool according to a further embodiment of the disclosed subject matter of the present application;

FIG. 9B is a schematic enlarged view of detail B shown in FIG. 9A;

FIGS. 10A to 10C are respective schematic isometric, front and side views of a cutting insert used in the cutting tool shown in FIGS. 9A and 9B;

FIG. 11A is a schematic enlarged view of a mounting portion of a cutting tool holder used in the cutting tool shown in FIGS. 9A and 9B;

FIG. 11B is isometric cross-section view of the cutting tool shown in FIG. 9B taken along line C-C shown therein;

FIGS. 12A to 12D are respective schematic isometric, front, top and bottom views of a cutting tool according to still another embodiment of the disclosed subject matter of the present application;

FIGS. 13A to 13C are respective schematic isometric, front and side views of a cutting insert used in the cutting tool shown in FIGS. 12A to 12D;

FIG. 14A is a schematic enlarged view of detail C shown in FIG. 12A;

FIG. 14B is a schematic enlarged isometric view of a mounting portion of a cutting tool holder used in the cutting tool shown in FIGS. 12A to 12D;

FIG. 14C is a schematic isometric view of the mounting portion shown in FIG. 14B with part of a securing mechanism thereof removed;

FIGS. 15A to 15D are respective schematic isometric, front, top and bottom views of a cutting tool according to still another embodiment of the disclosed subject matter of the present application;

FIGS. 16A to 16C are respective schematic isometric, front and side views of a cutting insert used in the cutting tool shown in FIGS. 15A to 15D;

FIG. 17A is a schematic enlarged view of detail D shown in FIG. 15A;

FIG. 17B is a schematic enlarged isometric view of a mounting portion of a cutting tool holder used in the cutting tool shown in FIGS. 15A to 15D;

FIG. 18 is schematic isometric view of a cutting tool according to still another embodiment of the disclosed subject matter of the present application;

FIG. 19 is a schematic isometric view of a mounting portion of a cutting tool holder used in the cutting tool shown in FIG. 18;

FIG. 20A is a schematic cross-section view of the cutting tool shown in FIG. 18 taken along line IV-IV therein;

FIG. 20B is a schematic cross-section view of the cutting tool shown in FIG. 18 taken along line V-V therein;

FIG. 20C is a schematic top planar view of the cutting tool shown in FIG. 20B;

FIG. 21 is a schematic isometric view of a cutting insert used in the cutting tool shown in FIG. 18;

FIG. 22A is a schematic isometric view of a cutting tool according to yet another embodiment of the disclosed subject matter of the present application; and

FIG. 22B is a schematic enlarged front view of detail F shown in FIG. 22A;

FIG. 23 is a schematic isometric view of a cutting tool holder used in the cutting tool shown in FIG. 22A;

FIG. 24A is a schematic isometric view of a cutting tool according to another embodiment of the disclosed subject matter of the present application;

FIG. 24B is a schematic isometric view of a cutting insert used in the cutting tool shown in FIG. 24A;

FIG. 25 is a schematic front view of a detail C shown in FIG. 12A;

FIG. 26A is a schematic isometric view of a cutting tool according to yet another embodiment of the disclosed subject matter of the present application;

FIG. 26B is a schematic isometric view of the cutting tool shown in FIG. 26A, with the cutting insert removed therefrom;

FIG. 26C is a schematic front view of the cutting tool shown in FIG. 26A;

FIGS. 27A and 27B are respective longitudinal and lateral cross-section views of a cutting insert used in the cutting tool shown in FIG. 26A, taken along respective lines VI-VI and VII-VII shown in FIG. 26A;

FIG. 28A is a schematic front view of a cutting tool according to yet another embodiment of the disclosed subject matter of the present application;

FIG. 28B is a schematic isometric enlarged view of a detail G shown in FIG. 28A;

FIG. 28C is a schematic isometric view of detail G shown in FIG. 28B, with the cutting insert removed;

FIG. 28D is a schematic isometric view of detail G shown in FIG. 28C, with the support element and fastening member removed therefrom;

FIG. 28E is a schematic isometric section view of detail G shown in FIG. 28A, taken along line VIII-VIII in FIG. 28A;

FIG. 29 is a schematic front view of detail G shown in FIG. 28A;

FIG. 30A is a schematic isometric view of the cutting insert used in the cutting tool shown in FIG. 28A;

FIGS. 30B and 30C are respective right and left isometric cross-sectional views taken along line VIII-VIII in FIG. 30A;

FIGS. 30D and 30E are respective right and left isometric cross-sectional views taken along line X-X in FIG. 30A;

FIGS. 31A and 31B are schematic front and rear views of a cutting insert of the when mounted onto the cutting tool shown in FIG. 28A and secured by a support element and a fastening member thereof, with the cutting tool holder not shown;

FIG. 32A is a schematic front view of a cutting tool according to still another embodiment of the disclosed subject matter of the present application;

FIG. 32B is a schematic isometric enlarged view of a detail H shown in FIG. 28A, with the cutting insert removed therefrom;

FIG. 32C is a schematic isometric view of detail H shown in FIG. 32C, with the support element and fastening member removed therefrom;

FIG. 32D is a schematic isometric section view of detail H shown in FIG. 32A, taken along line XI-XI in FIG. 32A;

FIG. 33A is a schematic isometric view of the cutting insert used in the cutting tool shown in FIG. 32A;

FIGS. 33B and 33C are respective right and left isometric cross-sectional views taken along line XII-XII in FIG. 33A;

FIGS. 33D and 33E are respective right and left isometric cross-sectional views taken along line XIII-XIII in FIG. 33A;

FIGS. 34A to 34C are respective schematic front views of a respective first row, second row and third row of cutting inserts of a cutting tool according to yet another embodiment of the disclosed subject matter of the present application; and

FIGS. 35A to 35C are respective schematic enlarged views of details I, II and III taken from respective FIGS. 34A to 34C.

DETAILED DESCRIPTION OF EMBODIMENTS

Attention is first drawn to FIGS. 1A and 1B in which a cutting tool generally designated as 1 is shown comprising a cutting tool holder 10 and three cutting inserts 20 mounted onto insert seats 30, each being secured in place by a securing arrangement comprising a support element 40, being integrally formed with the cutting tool holder 10, and a fastening member 50 adapted for dynamically engaging the cutting tool holder 10.

Turning now to FIGS. 2A through 2F, the cutting insert 20 is formed with a body 21 having a top face 22T and a bottom face 22B, and side faces 22S, 22S' extending therebetween. The top face 22T is formed with two peripheral slanting surfaces 22T' wherein a cutting edge 24 is defined at the intersection between two of the side faces 22S and the peripheral slanting surfaces 22T'. Each of the side walls 22S is formed with a v-shaped groove G adapted to engage a corresponding sidewall 34a of the insert seat 30 (shown FIGS. 3A, 3B).

The body 21 is further formed with a central cavity 23 having an opening 23T, 23B at the respective top and bottom faces 22T, 22B, the cavity being defined about a central axis X extending generally perpendicular to the top and bottom faces 22T, 22B.

The cavity 23 defines an inner surface 25 of the cutting insert 20, extending between the top face 22T and the bottom face 22B. The inner cavity has a nominal dimension D sufficient for accommodating therein, when the cutting

insert **20** is mounted onto the cutting tool holder **10**, both the support element **40** and the fastening member **50**.

Thus, it should be pointed out that, whereas in common cutting inserts the central opening is designed for accommodating only a fastening member (e.g. a fastening screw) of a predetermined diameter corresponding to the dimensions of the central opening, in the present example, as well as in all of the following embodiments to be described, the central cavity **23** corresponds in dimension to the mutual dimension of both the fastening member **50** and the support element **40** together. In other words, for a fastening member of a nominal dimension M , cavity **23** of presently disclosed subject matter has a nominal dimension $D \cong 2M$, compared to a dimension $D' \cong M$ in common cutting inserts, thereby allowing it to accommodate both the fastening member **50** and the support element **40** together.

It is thus appreciated, that the cavity **23** comprises, volumetrically, a greater percent of the overall volume of the cutting insert than in known cutting inserts. In particular, the cavity **23** may take up to no less than 15% of the overall volume of the cutting insert. The cavity may preferably constitute at least 20% of the overall volume of the cutting insert, even more preferably at least 25% of the overall volume of the cutting insert, even more preferably at least 30% of the overall volume of the cutting insert, and even more preferably at least 50% of the overall volume of the cutting insert.

Furthermore, the cutting insert **20** may be designed such that in each of its cross-sections taken along a plane generally parallel to the top face **22T** or bottom face **22B**, the cross-sectional area of the cavity **23** constitutes up to no less than 15% of the entire cross-sectional area of the cutting insert. In particular, the cross-sectional area of the cavity may constitute no less than 20% of the entire cross-sectional area of the cutting insert, even more preferably no less than 25% of the entire cross-sectional area of the cutting insert, even more preferably no less than 30% of the entire cross-sectional area of the cutting insert, and even more preferably no less than 50% of the entire cross-sectional area of the cutting insert.

In addition, it will be observed from FIGS. **2A** to **2F**, that the ratio D/T between the dimension of the cavity D and the dimension of the entire cutting insert T is about 0.4. However, this ratio may vary and be up to no less than 0.5, preferably no less than 0.6, even more preferably no less than 0.7 and even more preferably no less than 0.8. It should be noted that the same ratio applies for the corresponding dimensions when measured between the central axis X , i.e. the distance (D_{half}) measured between the side wall **22S** and the inner surface of the cavity **23**, and the distance (T_{half}) measured between the side wall **22S** and the central axis X . The dimensions D , D_{half} , T and T_{half} are taken along a direction perpendicular to the side walls **22S** and passing through said central axis.

It is appreciated that the volumetric, areal and linear dimensions and ratios mentioned above with respect to cutting insert **20** may apply to each of the following cutting inserts to be described in connection with the following figures (FIG. **5A** to FIG. **35C**).

The inner surface **25** of the cavity **23** is of a generally rectangular shape being defined by four side faces—one pair of opposite side faces **26S** and another pair of opposite side faces **26S'**, such that each side face **26S** is neighbored by side faces **26S'** and vice versa. The side faces **26S**, **26S'** are formed with securing portions **26a**, **26a'**, and **26b** adapted for engaging the support element **40** and the fastening member **50** respectively.

With particular reference being made to FIGS. **2E** and **2F**, each of the side faces **26S** is formed with a securing portion **26a**, being in the form of a protrusion projecting into the cavity **23**. The securing portion **26a** is formed of three surfaces I, II and III, the surface II being generally parallel to the side face **26S**, and the surfaces I and III tapering between the former two (i.e. between **26S** and II). The surfaces I, II and III are adapted, when the cutting insert **20** is mounted onto the cutting tool holder **10**, for engaging corresponding surfaces of the support element **40** as will be explained with respect to FIG. **4B**.

The side faces **26S'** are each formed with a securing portion **26a'**, also adapted to engage the support element **40**. However, the securing portions **26a'** are simply in the form of a planar surface constituting part of the side face **26S'**, so that the securing portion **26a'** is adapted, when the cutting insert **20** is mounted onto the cutting tool holder **10**, to engage a corresponding surface of the support element **40**.

Each of the securing portions **26b** adapted to engage the fastening member **50** is in the shape of a concave curved surface (in this example almost semi-conical), i.e. it extends into the securing portion **26a** to define a recess therein. The securing portion **26b** is only partially formed within the securing portion **26a**, i.e. the curved surface extends slightly towards one of the side faces **26S'** (FIG. **2F**). The securing portion **26b** is adapted, when the cutting insert **20** is mounted onto the cutting tool holder **10**, to engage a corresponding curved (convex) surface of the fastening member **40**.

Turning now to FIGS. **3A** and **3B**, the cutting tool holder **10** is shown comprising a body **12** extending along a central axis X , and having an attachment portion **12a** adapted for attachment to an apparatus (not shown) and a mounting portion **12b** adapted for mounting thereon the cutting insert **20**. The cutting tool holder **10** is further formed with three spirally extending chip evacuation channels **14** and corresponding cooling holes **16** for providing therethrough a cooling fluid during a cutting operation.

The mounting portion **12b** is formed with three cutting insert seats **30**, each being formed with a base surface **32B** and side surfaces **34a** and **34b** extending from the base surface **32B** and separated by a release gap **33**. The insert seat **30** is integrally formed with the support element **40**, the latter being in the form of a shoulder **42** and extending generally perpendicular to the base surface **32B**. The insert seat **30** is also formed with a threaded fastening bore **36** adapted to accommodate therein the fastening member **50**.

The shoulder **42** is formed with a top surface **42T** being elevated from the base surface **32B** of the insert seat **30**, and has four side walls **43a**, **43b**, **44** and **46** extending between the base surface **32B** and the top surface **42T**. When the cutting insert **20** is mounted onto the insert seat **30**, the side walls **43a**, **43b** are adapted for engaging the respective securing portions **26a**, **26a'** of the cutting insert **20** for securing it in place, while the side wall **46** is adapted to engage the fastening member **50**.

In particular, the side wall **43b** is formed with a nook **45** defined by three surfaces I', II' and III' adapted to engage the corresponding surfaces I, II and III of the securing portion **26a** of the cutting insert, and the side wall **43a** is adapted to engage the securing portion **26a'** of the cutting insert.

Reverting now to FIG. **1B**, the fastening member **50** is in the form of a fastening screw **52** having a stem portion **54** and a head portion **56**. The stem portion **54** is threaded and is adapted for insertion into the threaded fastening bore **36** of the insert seat **30**. The head portion **56** is of a conical shape and has an external surface **57**, adapted to engage the side wall **46** of the shoulder **42**, when the fastening member

11

50 is inserted into the fastening bore 36 of the insert seat 30. The conical shape of the head portion 56 is such that the diameter of the cross-section of the external surface 57 is greater at an end remote from the stem 54 than at the end bordering the stem 54.

Turning now to FIG. 4C, the cutting insert 20 is shown during mounting onto the insert seat 30, before the fastening member 50 has been inserted into the insert seat 30. In mounting, the cutting insert 20 is placed over the shoulder 42 such that the shoulder 42 is received within the opening 23 of the cutting insert 20. In this position, the securing portion 26b of the cutting insert and the opposite side wall 46 of the shoulder 42 form together part of a conical space 58 adapted to receive the fastening member 50, and corresponding in shape thereto, i.e. the diameter of the cross-section of the space 58 decreasing towards the base surface 32B. It should be noted that the side wall 46 of the shoulder 42 is a direct extension of the inner surface of the fastening bore 36. Also, in this position, the cutting insert 20 is still loosely mounted onto the insert seat 30 and may displace laterally back and forth in the direction of arrow R.

Once positioned on the insert seat 30, the fastening member 50 (shown FIGS. 4A, 4B) is inserted into the conical space 58 such that the stem 54 of the fastening member 50 is threaded into the fastening bore 36 of the insert seat 30. Threading of the fastening member causes displacement of the head portion 56 towards the base surface 32B of the insert seat 30, subsequently causing the conical surface 57 to apply a biasing force to both the cutting insert 20 and the shoulder 42, attempting to push them away from one another. In other words, the head portion 56 acts as a wedge, trying to push the cutting insert 20 away from the shoulder 42.

Since the shoulder is integrally formed with the cutting tool holder 10, and since the cutting insert 20 is laterally displaceable, the biasing force causes the cutting insert 20 to be pushed towards the side walls 34a, 34b to assume the position shown in FIGS. 4A and 4B. It is also important to note that since the cutting insert 20 is biased in the direction of arrow R, the securing portions 26a, 26a' of the cutting insert 20 are simultaneously biased towards the shoulder 42.

Turning now to FIGS. 4A and 4B, the cutting tool 1 is shown with the cutting inserts 20 mounted onto the cutting tool holder 10, and secured thereto using the fastening member 50 and the support element 40. It is observed that in this position, the support element 40, and the fastening member 50 are both received within the same central opening 23 of the cutting insert 20. In particular, the side face 22S' of the cutting insert 20 engages the side wall 34b of the insert seat 30, the external surface 57 of the head portion 56 of the fastening member 50 engages both the securing portion 26b and the side wall 46 of the shoulder 42, and that the side walls 43a, 43b of the shoulder 42 engage the securing portions 26a, 26a' of the cutting insert 20. With particular reference to FIG. 4B, it is observed that the ledge of the securing portion 26a of the cutting insert 20 is received within the nook 45 of the shoulder 42.

In this position, the fastening member 50 applies a biasing force F to the cutting insert 20 towards the corner between the side walls 34a, 34b of the insert seat 30. Due to this biasing force F, the securing portions 26a, 26a' are biased against the side walls 43a, 43b of the shoulder 42, further securing the cutting insert 20. It is also noted that in this position, there is a continuous line of material between a corner C of the cutting insert 20 and the release gap 33 at the

12

corner between the side walls 34a, 34b, being constituted by portions of the cutting insert 20, the shoulder 42 and the fastening member 50.

It is also appreciated, that the cutting inserts 20 used in the cutting tool 1 described above are indexable cutting inserts 20 having two cutting edges 24 each. When it is desired to change the cutting edge 24, the fastening member 50 is removed or slightly unthreaded from the fastening bore 36, and the cutting insert 20 is rotated 180° about the central axis of the fastening bore 36, such that the opposite cutting edge 24 is in effect.

In operation, the side walls 22S of the cutting insert 20 are adapted to serve as rake surfaces, and the peripheral slanting surfaces 22T' are adapted to serve as relief surfaces. It is also important to note in this respect that when the cutting edge 24 in use, i.e. positioned remotely from the side wall 34a, the groove G serves as a rake surface, and when the cutting edge 24 is not in use, i.e. positioned adjacent the side wall 34a, the groove G serves for securing to cutting insert by engaging the shaped side wall 34a of the insert seat.

Turning now to FIGS. 5A to 5C, another cutting tool is shown, generally designated as 100, comprising a cutting tool holder 110, and three cutting inserts 120 mounted onto insert seats 130, each being secured in place by a securing arrangement comprising a support element 140, being integrally formed with the cutting tool holder 110, and a fastening member 150 adapted to dynamically engage the cutting tool holder 110. For the sake of simplicity, the reference numerals of the cutting tool 100 designating similar elements as elements of the cutting tool 1 have been upped by 100.

The cutting tool 100 is generally similar to the cutting tool 1 with the difference being that, contrary to the previous example, in this case, the conical shape of the head portion 156 is such that the diameter of the cross-section of the external surface 157 is smaller at an end remote from the stem 154 than at the end bordering the stem 154.

Correspondingly, the securing portions 126b of the cutting insert 120, as well as the side walls 146 of the shoulder 142 are tapered to form a conical space 158 which matches the external surface 157 of the head portion 156, i.e. the diameter of the cross-section of the space 158 increases towards the base surface 32B.

In assembly, mounting the cutting insert 120 is fairly similar to that described with respect to the cutting tool 1, however, in the present example, the fastening member 150 is first screwed into the fastening bore 136, then the cutting insert 120 is positioned in the insert seat 130, and finally, the fastening member 150 may be partially unscrewed from the fastening bore 136 until the cutting insert 120 is secured in place.

It is important to emphasize that the difference between the present example (cutting tool 100) and the previous example (cutting tool 1), is that, in the present example the fastening member 150 is not required to disengage from the cutting tool holder 110 in order to allow the cutting insert 120 to be mounted onto the cutting tool holder 110. In particular, the fastening member 150 is adapted to assume a first, mounting position, in which it is threaded into the fastening bore 136 of the insert seat 130 and protrudes from the base surface 132B to a first extent, allowing the cutting insert 120 to be mounted onto the insert seat 130, and a second, securing position, in which it is threaded into the fastening bore 136 of the insert seat 130 and protrudes from the base surface 132B to a second extent, greater than the first extent, allowing the cutting insert 120 to be secured onto the insert seat 130.

Thus, throughout the entire use of the cutting tool **100** there is no requirement of removing/disengaging the fastening member **150** from the insert seat **130**. This, in turn, may provide, inter alia, a more time-efficient indexing/replace-
ment of the cutting insert as well as prevention of loss of the
fastening member during the mounting/dismounting process
of the cutting insert **120**.

Turning now to FIGS. **6A** to **8B**, another cutting tool is shown, generally designated as **200**. For the sake of simplicity, the reference numerals of the cutting tool **200** designating similar elements as elements of the cutting tool **1** have been upped by **200**. The cutting tool **200** comprises a cutting tool holder **210**, and three cutting inserts **220** mounted onto insert seats **230**, and each being secured in place by a securing arrangement comprising a support element **240**, being integrally formed with the cutting tool holder **210**, and a fastening member **250** adapted to dynamically engage the cutting tool holder **210**.

The cutting tool **200** is generally of similar design to that of cutting tool **1**, with the difference being that, in the present example, the fastening member is constituted by a spring biased securing pin **250** positioned within a non-threaded fastening bore **236** of the insert seat **230**. In addition, the tapering angle of the securing portions **226b** of the cutting insert and of the side walls **243b** of the shoulder **242** differs from the previous examples. In the present example, the above securing portions **226b** and side walls **243** form a straight cylindrical space **258** adapted for receiving the securing pin **250**.

The operation mechanism of the biased securing pin **250** is generally similar to that disclosed in U.S. patent application Ser. No. 12/314,428 to the applicant, which is incorporated herein by reference, in particular, the portions of the specification of the above application pertaining to FIGS. **2A** to **44**, FIGS. **47** to **49C** and FIGS. **59A** to **66B** therein.

However, contrary to the disclosed in the above referenced application, in the present application the securing pin **250** is supported by the support element **240**, in particular, on a side opposite the side which engages the cutting insert **220**, thus creating a much more robust structure. In addition, due to the shoulder **242**, the diameter of the securing pin may be reduced with respect to the diameter of the securing pin used in the above referenced application, this being done on expense of the shoulder **242**. According to a particular example, the diameter of the securing pin **250** of the disclosed subject matter of the present application may be about 5 mm, as opposed to a diameter of 6.5 mm required in the above referenced application, not comprising a support element **240**.

Turning now to FIGS. **9A** and **9B**, another cutting tool is shown, generally designated as **300**. For the sake of simplicity, the reference numerals of the cutting tool **300** designating similar elements as elements of the cutting tool **1** have been upped by **300**. The cutting tool **300** comprises a cutting tool holder **310**, and six cutting inserts **320** mounted onto insert seats **330**, and each being secured in place by a securing arrangement comprising a support element **340**, being integrally formed with the cutting tool holder **310**, and a fastening member **350** adapted to dynamically engage the cutting tool holder **310**.

The cutting tool **300** is generally of similar design to that of cutting tool **200**, with the difference being that, contrary to the previous cutting tool (**200**), the present cutting tool **300** is an axial cutting tool and comprises six cutting inserts **320**.

With particular attention drawn to FIGS. **10A** to **10C**, each insert **320** is an indexible and reversible cutting insert **320**.

In particular, each cutting insert **320** is formed with respective top face and bottom face **322T**, **322B**, with four side walls **322S** extending therebetween, such that for each side wall **322S**, two cutting edges **324T**, **324B** are defined—one at the intersection of the side walls **322S** with the top face **324T**, and one at the intersection between the side wall **322S** and the bottom face **322B**. Thus, each cutting insert **320** is formed with eight cutting edges—four top cutting edges **324T**, and four bottom cutting edges **324B**.

During a cutting operation, the side walls **322S** of the cutting insert **320** are adapted to serve as rake surfaces, and the top and bottom faces **322T**, **322B** are adapted to serve as relief surfaces.

It is further observed that since the cutting insert **320** is indexible and reversible, and has eight cutting edges **324T**, **324B** respectively, the central opening **323** thereof has a unique design, being formed with four sets of first securing portions **326a**, **326a'** associated with the four top cutting edges **324T** and additional four sets of first securing portions **326a**, **326a'** associated with the four bottom cutting edges **324B**. The cutting insert **320** is also formed with four sets of second securing portions **326b**, associated with the four top cutting edges **324T** and additional four sets of second securing portions **326b**, associated with the four bottom cutting edges **324B**.

It is observed that in this particular example, the central cavity **323** is of a generally square shape such that each of the securing portions **326a**, **326a'** is constituted by one of the four side walls **326S** of the inner surface of the cavity **323** and each of the securing portions **326b** is constituted by one of the four rounded corners **326R**.

In addition, contrary to the previous example, in the present example the side walls **322S** of the cutting insert **320** have a slightly protruding ridge **R** (instead of a groove **G** as in the example of FIGS. **1A** to **4B**). With particular reference to FIGS. **11A** and **11B**, it is noticed that correspondingly, the side walls **334a**, **334b** of the insert seat **330** of the cutting tool holder **310** are tapered inwardly in a matching (negative) angle, so as to properly engage the cutting insert **320** when positioned in place.

In the cutting tool **300**, the fastening member **350** is a securing pin **352** adapted to function in a similar manner to the securing pin **252** of the cutting tool **200**, and therefore will not be described in detail with respect to the above example.

Turning now to FIGS. **12A** to **14C**, still another cutting tool is shown, generally designated as **400**. For the sake of simplicity, the reference numerals of the cutting tool **400** designating similar elements as elements of the cutting tool **1** have been upped by **400**. The cutting tool **400** comprises a cutting tool holder **410**, and six cutting inserts **420** mounted onto insert seats **430**, and each being secured in place by a securing arrangement comprising a support element **440**, being integrally formed with the cutting tool holder **410**, and a fastening member **450** adapted to dynamically engage the cutting tool holder **410**.

The cutting tool **400** is generally of similar design to that of cutting tool **300**, with the difference being that it is a tangential cutting tool and comprises six cutting inserts **420**.

With reference to FIGS. **13A** to **13C**, each cutting insert **420** is indexible and reversible. In particular, each cutting insert **420** is formed with respective top face and bottom face **422T**, **422B**, with four side walls **422S**, **422S'** extending therebetween, such that for each of the side walls **422S**, two cutting edges **424T**, **424B** are defined—one at the intersection of the side wall **422S** with the top face **424T**, and one at the intersection between the side wall **422S** and the

bottom face **422B**. Thus, each cutting insert **420** is formed with four cutting edges—two top cutting edges **424T**, and two bottom cutting edges **424B**.

It is further observed that since the cutting insert **420** is indexible and reversible, and has four cutting edges **424T**, **424B** respectively, the central opening **423** thereof has a unique design, being formed with four sets of first securing portions **426a**, **426a'** associated with the four top cutting edges **424T** and additional four sets of first securing portions **426a**, **426a'** associated with the four bottom cutting edges **424B**. The cutting insert **420** is also formed with four sets of second securing portions **426b**, associated with the four top cutting edges **424T** and additional four sets of second securing portions **426b**, associated with the four bottom cutting edges **424B**.

In addition, contrary to the previous example, in the present example, only the side walls **422S** are formed with cutting edges **424T**, **424B**, and thus are also the only one to be formed with a double set of grooves G' . With particular reference to FIGS. **14B** and **14C**, it is noticed that correspondingly, the side walls **434a**, **434b** of the insert seat **430** of the cutting tool holder **410** are formed with respective v-shaped protrusions P adapted to be received within the grooves G' so as to properly engage the cutting insert **420** when positioned in place.

In the cutting tool **400**, the fastening member **450** is a securing pin **452** adapted to function in a similar manner to the securing pin **252** of the cutting tool **200**, and therefore will not be described in detail for the present application. Attention is drawn to FIG. **14C**, in which it is observed that, similarly to the previous embodiments, the side wall **446** of the support element **440** has a cylindrical shape, whereby, when the cutting insert **420** is mounted onto the insert seat **430**, the side wall **446** of the support element and the securing portion **426b** of the cutting insert **420** form together a space into which the securing pin **452** is adapted to extend to thereby secure the cutting insert **420** in place.

In operation, the side walls **422S** of the cutting insert **420** are adapted to serve as rake surfaces, and the top and bottom faces **422T**, **422B** are adapted to serve as relief surfaces.

Attention is now drawn to FIGS. **15A** to **17B**, in which another cutting tool is shown generally designated as **500**. For the sake of simplicity, the reference numerals of the cutting tool **500** designating similar elements as elements of the cutting tool **1** have been upped by **500**. The cutting tool **500** comprises a cutting tool holder **510**, and six cutting inserts **520** mounted onto insert seats **530**, and each being secured in place by a securing arrangement comprising a support element **540**, being integrally formed with the cutting tool holder **510**, and a fastening member **550** adapted to dynamically engage the cutting tool holder **510**.

With particular reference to FIGS. **16A** to **16C**, the cutting tool **500** is generally of similar design to that of cutting tool **400**, with the difference being in the design of the cutting inserts **520** and the insert seats **530** of the cutting tool holder **510**. In particular, the cutting tool **500** comprises six cutting inserts **520**. Each cutting insert **520** is an indexible and reversible cutting insert **520**. In particular, each cutting insert **520** is formed with respective top face and bottom face **522T**, **522B**, with four side walls **522S** extending therebetween, such that for each of the side walls **522S**, two cutting edges **524T**, **524B** are defined—one at the intersection of the side wall **522S** with the top face **524T**, and one at the intersection between the side wall **522S** and the bottom face **522B**. Thus, each cutting insert **520** is formed with eight cutting edges—four top cutting edges **524T**, and four bottom cutting edges **524B**.

It is further observed that since the cutting insert **520** is indexible and reversible, and has eight cutting edges **524T**, **524B** respectively, the central opening **523** thereof has a unique design—contrary to the previous examples, the design of the central opening **523** of the cutting insert **520** is completely symmetric, being formed with four sets of first securing portions **526a**, and four sets of second securing portions **526b**. The arrangement is such that each of the first securing portions **526a** is in the form of a v-shaped ridge adapted to be received within the corresponding nook **545** of the support element **540**, when the cutting insert **520** is mounted into the insert seat **530**.

Furthermore, it is noted that each side wall **522S** is formed with a set of two v-shaped indents G' , the arrangement being such that when the cutting insert **520** is mounted onto the insert seat **530**, the indents G' of the side wall **522** facing the side wall **534a** of the insert seat **530** engage the v-shaped ridges P' of the side wall **534a**, thereby further securing the cutting insert **520** in place.

Attention is now drawn to FIGS. **17A** and **17B**, in which it is observed that the shoulder **542** is formed with a cut-out corner C between the side walls **543a** and **543b**. It is also noted that when the cutting insert **520** is mounted onto the insert seat **530**, the second securing portion **526b** located diagonally opposite the securing portion **526b** engaging the securing pin **552**, engages the corner C of the shoulder **542**. Thus, it should be understood that the second securing portion **526b**, when located diagonally opposite from the portion **526b** engaging the securing pin **552**, also serves as a securing portion for the shoulder **542**, further increasing the firmness of the entire cutting tool **500**.

In the cutting tool **500**, the fastening member **550** is a securing pin **552** adapted to function in a similar manner to the securing pin **252** of the cutting tool **200**, and therefore will not be described in detail with respect to the above example.

In operation, the side walls **522S** of the cutting insert **520** are adapted to serve as relief surfaces and the top and bottom faces **522T**, **522B** are adapted to serve as rake surfaces.

Turning now to FIGS. **18** through **21**, another cutting tool is shown, generally designated **600**. For the sake of simplicity, the reference numerals of the cutting tool **600** designating similar elements as elements of the cutting tool **1** have been upped by **600**.

The cutting tool **600** is generally of similar design to that of cutting tool **300**, with the difference being at least in the following elements:

the head portion **656** of the securing pin **650** is faceted rather than being round. In this particular example, the securing pin **650** has eight facets **653**;

The second securing portions **626b** of the cutting insert **620** are straight, and are at an angle corresponding to the angle γ of the facets **653**, and inclination angle δ of the securing pin **650**.

Thus, it is appreciated that the difference between the present cutting tool **600** including a faceted pin **650** and previously described cutting tools (**200**, **300**, **400** and **500**) including a rounded securing pin, is that in the present cutting tool **600** the contact between the securing pin **650** and the securing portion **626b** of the cutting insert **620** is provided along two surfaces rather than along a single line of contact.

Furthermore, the facets **653** of the securing pin **650** allow it to align one of its facets **653** against the securing portion **626b** by spontaneously rotating about its axis due to a force applied thereto by biasing spring and pressure from the support element **640**.

In general, the manner of operation and advantages of the faceted securing pin **650** are similar to those of the faceted pin disclosed in U.S. patent application Ser. No. 12/314,428 to the applicant, which is incorporated herein by reference, in particular, the portions of the specification of the above application pertaining to FIGS. **59A** to **65** therein.

Turning now to FIGS. **22A** to **23**, still another cutting tool is shown generally designated **700**. For the sake of simplicity, the reference numerals of the cutting tool **700** designating similar elements as elements of the cutting tool **1** have been upped by **700**. The cutting tool **700** comprises a cutting tool holder **710**, and nine cutting inserts **720** mounted onto insert seats **730**, and each being secured in place by a securing arrangement comprising a support element **740**, being integrally formed with the cutting tool holder **710**, and a fastening member **750** adapted to dynamically engage the cutting tool holder **710**.

The cutting tool **700** and the cutting tool **200** is generally of similar design to that of cutting tool **200** previously described, with the difference being that, in the present example, the mounting portion **712b** of the cutting tool holder **710** is formed with three mounting paths **715**, each mounting path being constituted, in turn, by three subsequent insert seats **730₁**, **730₂**, **730₃**, each being adapted to receive therein a cutting insert **720**, this contrary to the cutting tool **200** in which each spiral is formed with only one insert seat **230**. Thus, it is noted that when the cutting inserts **720** are mounted onto the insert seats **730**, the cutting edges **724** of three cutting inserts **720** disposed along a single mounting path **715** form a continuous cutting edge **725**.

In particular, with reference being drawn to FIG. **22B**, it is noted that when the cutting insert **720** are mounted onto a cutting path **715**, the cutting edge **724₂** of one cutting insert **720₂** overlaps the cutting edge **724₁** of the cutting insert **720₁** located below it such that a continuous cutting edge **724** is formed. This overlap **d** is also useful in protecting the cutting insert **720₁**. It is also observed that there extends a slight gap ϵ between two adjacent cutting inserts **720₁**, **720₂**. This gap is essential, allowing for handling various differences in tolerances created during manufacture of the cutting inserts **720**.

The cutting inserts **720** used in the cutting tool **700** are generally similar to the cutting insert **220** used in the cutting tool **200**, i.e. they have a similar construction, and they are also indexible, similar to cutting inserts **220**.

Turning now to FIGS. **24A** and **24B**, yet another cutting tool is shown, generally designated **800**. For the sake of simplicity, the reference numerals of the cutting tool **800** designating similar elements as elements of the cutting tool **1** have been upped by **800**.

The cutting tool **800** is generally of similar design to that of the cutting tool **700**, with the difference being that the cutting inserts **820** thereof are intended for rough milling. Therefore, the cutting edges **824** of the cutting inserts are not straight, but rather sinusoidal, having crests **C** and troughs **T**.

Since the cutting inserts **820** are intended for rough milling, it is not compulsory for the cutting edges **824₁**, **824₂** of two adjacent cutting inserts **820₁**, **820₂** to form a continuous cutting edge **815**. Thus, the present cutting tool **800** provides greater flexibility in the positioning of the cutting inserts **820** along the mounting path **815**.

Particular attention is now drawn to FIG. **25**, in which one exemplary cutting insert **CI** of a tangential cutting tool is shown during contact with a workpiece **WP**. When the cutting insert **CI** come in contact with the workpiece **WP**, a force **F₁** is applied thereto by the workpiece **WP**, causing the cutting insert **CI** to slightly elastically deform in the direc-

tion of **F₁**, i.e. become somewhat shrunk in that dimension. Upon disengaging from the workpiece **WP** due to rotation of the cutting tool (not shown), the cutting insert **CI** strives to return to its original dimensions, i.e. perform elastic deformation in an opposite direction of **F₂**. Taking into consideration that a cutting tool revolves at a speed of about 1500 RPM, such elastic deformation occurs repeatedly and aggressively.

Thus, each time the cutting insert **CI** comes in contact with the workpiece **WP** and then disengages therefrom, it behaves like a coiled spring. Upon 're-coiling' of the cutting insert **CI**, the cutting insert **CI** is urged in the direction **F₂**, and 'strives' to disengage from the side wall of the insert seat. However, according to the present example, the support element (shoulder) is always formed with an acute angle θ corresponding to an acute angle θ within the central opening of the cutting insert, and disposed so as to prevent any lateral movement of the cutting insert **CI** in direction **F₂**.

Under the above arrangement, since the support element is responsible for preventing lateral movement of the cutting insert **CI** in a direction opposite the side wall of the insert seat, the responsibility of the fastening member is mostly preventing the cutting insert **CI** from disengaging from the base surface of the insert seat and from the support element. Thus, in the present cutting tools employing both the support element and the fastening member, the fastening member may be considerably smaller in dimensions with respect to a corresponding cutting tool comprising only a fastening member.

It should be appreciated that the above discussed exemplary insert, and in particular the acute angle θ , the manner of its operation and the advantages provided thereby apply to all the cutting tools of the disclosed subject matter of the present application (all examples previously described in FIGS. **1A** to **24B**, and examples to be described in FIGS. **26A** to **35C**).

Turning now to FIGS. **26A** to **27B**, another cutting tool, generally designated **1000** is shown. For the sake of simplicity, the reference numerals of the cutting tool **1000** designating similar elements as elements of the cutting tool **1** have been upped by **1000**. The cutting tool **1000** comprises a cutting tool holder **1010**, three cutting inserts **1020** mounted onto insert seats **1030**, and each being secured in place by a securing arrangement comprising a support element **1040**, being integrally formed with the cutting tool holder **1010**, and a fastening member **1050** adapted to dynamically engage the cutting tool holder **1010**.

With particular reference to FIG. **26C**, the cutting tool **1000** is generally of similar design to the previous cutting tools, with the difference being that in this cutting tool **1000**, the angle θ (about 30°) of the support element is more acute than in the previous examples. It is observed that, after a cutting insert **1020** is mounted onto the seat **1030** of the cutting tool holder **1010**, and when the fastening member **1050** is fastened to the cutting tool holder **1010**, it applies a force **F₁** pushing the cutting insert **1020** along a generally upward axial direction. This upward axial movement of the cutting insert **1020** causes the respective securing portions **1026a**, **1026a'** (shown FIGS. **27A**, **27B**) to engage the undercut **1043b'** of the side wall **1043b** of the support element **1040**. Due to this engagement, and the acute angle θ , the application of force **F₁** entails the application of a force **F₂** to the cutting insert **1020** by the support element **1040**, urging it to displace in a generally lateral direction. The resultant combined force **F_T** of the two forces **F₁** and **F₂**,

is directed to an angle of the insert seat **1030**, between the side walls **1034a** and **1034b**, thus firmly securing the cutting insert **1020** in place.

With reference to FIGS. **27A** and **27B**, the cutting insert **1020** has a similar design to that of the cutting insert **820** previously described, however, its securing portions **1026a** and **1026a'** are specifically designed to engage the support element **1040**. In particular, the securing portion **1026a** is designed to match the shape of the undercut **1043b'**, and the securing portion **1026a'** is designed to match the shape of the side wall **1043a** (not shown) of the support element **1040**.

During a cutting operation, the side walls **1022S** of the cutting insert **20** are adapted to serve as rake surfaces, and the top surface **1022T** is adapted to serve as a relief surface.

In all other aspects, the cutting tool **1000**, cutting tool holder **1010** and cutting insert **1020** operate much in the same manner as previously described cutting tools **1**, **100**, **200**, **700** and **800**.

Attention is now drawn to FIGS. **28A** to **28D**, in which a cutting tool, generally designated as **1100** is shown. For the sake of simplicity, the reference numerals of the cutting tool **1100** designating similar elements as elements of the cutting tool **1** have been upped by **1100**. The cutting tool **1100** comprises a cutting tool holder **1110**, and six cutting inserts **1120** mounted onto insert seats **1130**, and each being secured in place by a securing arrangement comprising a support element **1140** securely engaged with the cutting tool holder **1110**, and a fastening member **1150** adapted to dynamically engage the cutting tool holder **1110**. The fastening member **1150** is a screw similar to that used in the cutting tool **1** previously described.

The cutting tool **1100** is generally of similar design to that of cutting tool **1000**, with the difference being that in this cutting tool **1100** the support element **1140** is not integrally formed with the cutting tool holder **1110**, but rather is attachable to the cutting tool holder **1110** in a detachable manner. In particular, the support element **1140** is a screw **1142** adapted to be threaded into a corresponding support bore **1137** formed in the insert seat **1130** of the cutting tool holder **1110**.

The screw **1142** has a threaded engagement portion **1144** adapted to be threaded into the support bore **1137**, and a securing portion **1146a** adapted to engage a corresponding securing portion **1126a** of the cutting insert **1120** when the latter is mounted onto the cutting tool **1110**. The securing portion **1146a** is of conical shape increasing in diameter away from the seat **1130** when the support element **1130** is mounted thereto, i.e. defined between a first diameter D_1 remote from the base surface **1132** of the seat **1130**, and a second diameter $D_2 < D_1$ closer to the base surface **1132**.

The threaded portion **1144** and the securing portion **1146a** are separated from one another by an intermediate portion **1146b**, having a diameter D_2 greater than a diameter D_3 of the threaded portion, whereby, when the support element **1140** is mounted onto the seat **1130**, the bottom surface **1149** of the intermediate portion **1146b** abuts the base surface **1132** of the seat **1130** of the cutting tool holder **1110**. This allows providing the securing portion **1146a** of the support element **1140** with a firm support against the cutting insert **1120** when mounted thereon.

The above design provides, inter alia, at least the advantage of simplifying the manufacturing of the cutting tool holder **1110**. Forming an integral support element as described with respect to previous embodiments requires a considerable amount of work and time, whereas, in the present embodiment of cutting tool **1100**, the only thing required for providing the support element **1140** is forming

another threaded bore (**1137**) in the base surface **1132** of the seat **1130**, in addition to the threaded fastening bore **1136** adapted for receiving the fastening member **1150**.

Turning now to FIG. **29**, It is observed that, after a cutting insert **1120** is mounted onto the seat **1130** of the cutting tool holder **1110**, and when the fastening member **1150** is fastened to the cutting tool holder **1110**, it applies a force F_1 pushing the cutting insert **1120** along a generally upward axial direction. This upward axial movement of the cutting insert **1120** causes the securing portion **1126a** thereof (shown FIGS. **30A** to **30E**) to engage the securing portion **1146a** of the support element **1140**. This engagement takes place along a contact line C (also shown FIG. **28E**) which is located angled to the center line CL by an angle θ . Due to this engagement, and the acute angle θ , the application of force F_1 entails the application of a force F_2 to the cutting insert **1120** by the support element **1140**, urging it to displace in a generally lateral direction. The resultant combined force F_T of the two forces F_1 and F_2 , is directed to an angle of the insert seat **1130**, between the side walls **1134a** and **1134b**, thus firmly securing the cutting insert **1120** in place.

Turning now to FIGS. **30A** through **31B**, the cutting insert **1120** is shown formed with a body **1121** having a top face **1122T** and a bottom face **1122B**, and side faces **1122S**, **1122S'** extending therebetween, wherein four cutting edges **1124** are defined at the intersections between the side faces **1122S** and the top and bottom face **1122T** and **1122B**. The body **1121** is further formed with a central cavity **1123** having an opening **1123T**, **1123B** at the respective top and bottom faces **1122T**, **1122B**, the cavity being defined about a central axis X extending generally perpendicular to the top and bottom faces **1122T**, **1122B**. Each of the side walls **1122S** is formed with a v-shaped groove G' adapted to engage a corresponding sidewall **1134a** of the insert seat **1130** (shown FIG. **28C**).

During a cutting operation, the side walls **1122S** of the cutting insert **1120** are adapted to serve as rake surfaces, and the top and bottom surfaces **1122T**, **1122B** are adapted to serve as relief surfaces.

The cavity **1123** defines an inner surface **1125** of the cutting insert **1120**, having a first set of securing portions **1126a** and a second set of securing portions **1126b**, adapted, when the cutting insert **1120** is mounted onto the cutting tool holder **1110**, for engaging the respective support element **1140** and the fastening member **1150**.

The cutting insert **1120** is designed such that the inner surface **1125** thereof is constituted by four adjacent sections, each section extending between the top face **1122T** and the bottom face **1122B** of the cutting insert **1120**, and each such section being constituted by a first securing portion **1126a** adjacent one face of the cutting insert (top or bottom), and a second securing portion **1126b** adjacent the opposite face of the cutting insert. The sections are arranged in a counter-opposed manner, i.e. for a section having a first securing portion **1126a** adjacent the top face **1122T**, the two adjacent sections on the right and left side thereof will have their first securing portion **1126a** adjacent the bottom face **1122B**. Hence, the same applies to the second securing portions **1126b**.

It is also noted that due to the above design, and since the securing portion **1126a** adapted to engage the support element **1140** is greater in dimension than the second securing portion **1126b** adapted to engage the fastening member **1150**, the top and bottom openings **1123T**, **1123B** have the same shape, but are a mirror image one of the other.

As in the previous examples, the inner cavity **1123** is sufficiently large for accommodating therein, when the cut-

ting insert **1120** is mounted onto the cutting tool holder **1110**, both the support element **1140** and the fastening member **1150**.

With particular reference to FIGS. **31A** and **31B**, it is noted that the cutting insert **1120** is designed such that, when mounted onto the cutting tool holder **1110** and engagement takes place between the first securing portion **1126a** and the support element **1140**, the second securing portion **1126b** of the same section of the inner surface **1125** does not come in contact with the intermediate portion **1146b** of the support element **1140**, i.e. there extends a gap t between the securing portion **1126b** and the intermediate portion **1146b**.

Attention is now drawn to FIGS. **32A** to **32D**, in which a cutting tool, generally designated as **1200** is shown. For the sake of simplicity, the reference numerals of the cutting tool **1200** designating similar elements as elements of the cutting tool **1100** have been upped by **100**. The cutting tool **1200** comprises a cutting tool holder **1210**, and six cutting inserts **1220** mounted onto insert seats **1230**, and each being secured in place by a securing arrangement comprising a support element **1240** securely engaged with the cutting tool holder **1210**, and a fastening member **1250** adapted to dynamically engage the cutting tool holder **1210**.

The difference between the cutting tool **1200** and the cutting tool **1100** previously described is that the fastening member **1250** is not a screw (**1152** shown FIG. **28A**), but rather a securing pin **1252**, similar to the securing pins of cutting tools **200**, **300**, **400** etc., and operates in much the same manner as described there.

Another difference between the cutting tools **1100** and **1200** is that the support element **1240** is designed with a conical intermediate portion **1246b**, as opposed to a straight intermediate portion (**1146a** shown FIG. **28D**). The intermediate portion **1246b** has a greater diameter at a point adjacent the base surface **1232** of the seat **1230** than at a point remote from the base surface **1232**. This grants the support element **1250** a more robust structure than previously described.

Turning to FIGS. **33A** to **33D**, it is observed that the design of the cutting insert **1220** is generally similar to the design of the cutting insert **1120** previously described, i.e. the inner surface **1225** is also constituted by four sections, each having a first securing portion **1226a** adapted to engage the support element **1240** and adjacent one of the top and bottom faces **1222T**, **1222B**, and a second securing portion **1226b** adapted to engage the fastening member **1250** and adjacent a face opposite to that which the first securing portion **1226a** is adjacent.

The cutting insert **1220** similarly maintains the counter-opposed design in which for a section having a first securing portion **1126a** adjacent the top face **1122T**, the two adjacent sections on the right and left side thereof will have their first securing portion **1126a** adjacent the bottom face **1122B**. Hence, the same applies to the second securing portions **1126b**.

During a cutting operation, the side walls **1222S** of the cutting insert **1220** are adapted to serve as rake surfaces, and the top and bottom surfaces **1222T**, **1222B** are adapted to serve as relief surfaces.

Turning now to FIGS. **34A** to **34C**, another cutting tool generally designated **1300** is shown, being of a generally similar design to that of the cutting tool **700** previously described. For the sake of simplicity, the reference numerals of the cutting tool **1300** designating similar elements as elements of the cutting tool **700** have been upped by **600**. The cutting tool **1300** comprises a cutting tool holder **1310**, and nine cutting inserts **1320** mounted onto insert seats **1330**

in three rows (a), (b) and (c), three cutting inserts **1320** per row, each cutting insert being secured in place by a securing arrangement comprising a support element **1340** securely engaged with the cutting tool holder **1310**, and a fastening member **1350** adapted to dynamically engage the cutting tool holder **1310**.

The difference between the cutting tool **1300** and the cutting tool **700** previously described is the arrangement of the cutting insert **1320** in each row. In particular, the support elements **1340** of the cutting tool holder **1310** is designed such that an overlap ϵ between two adjacent cutting inserts **1320** in the same row changes from row to row. The change in overlap ϵ is achieved by the slightly different design of the seats **1330** of each row, in particular, the location of the support element **1340**.

Attention is thus drawn to FIGS. **35A** to **35C** in which the area between the second and third cutting insert of each row is shown, i.e. **1320a₂** and **1320a₃**, **1320b₂** and **1320b₃**, and **1320c₂** and **1320c₃** respectively. It is first observed that in all three rows, there is a gap n between two adjacent cutting inserts **1320** of the same row. It is further observed that the overlap ϵ_a of the third cutting insert **1320a₃** over the second cutting insert **1320a₂** in the first row (a) is smaller than the overlap ϵ_b of the third cutting insert **1320b₃** over the second cutting insert **1320b₂** in the second row (b) which is, in turn, smaller than the overlap ϵ_c of the third cutting insert **1320c₃** over the second cutting insert **1320c₂** in the third row (c).

The above design allows the cutting tool **1300** to operate such that any material not removed from the workpiece (not shown) by one row of cutting inserts **1320**, is removed by the following row as the cutting tool **1300** keeps revolving about its axis, and so on.

In general, with respect to all of the above cutting tools **1**, **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**, **1000**, **1100**, **1200** and **1300**, the use of a cutting insert accommodating therein both a displaceable fastening member and a fixed support element provides, inter alia, at least the following advantages:

continuous line of material extending within the central opening of the cutting insert, thereby securing the cutting insert not only to the base surface of the insert seat and/or to a side wall of the insert seat, but also to an additional member—the support element, allowing for much firmer securing of the cutting insert;

the majority of forces exerted by the fastening member are directed to prevention of disengagement of the cutting insert from the base surface of the seat, while the remainder of the forces required to prevent lateral displacement of the cutting insert along the base surface of the insert seat are taken by the support element which is fixed to the cutting tool holder; and

a wedge mechanism which presses the cutting insert against the base surface of the insert seat while simultaneously biasing the cutting insert towards one of the side walls of the insert seat, thereby also preventing lateral movement thereof.

It should be clear that most principles and features described above with respect to cutting tools **1**, **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**, **1000**, **1100** and **1200** and/or shown in FIGS. **1A** to **35C**, are not restricted to those cutting tools (**1**, **100**, **200**, **300**, **400**, **500**, **600**, **700**, **800**, **1000**, **1100** and **1200**) in connection with which they are described/shown, and may independently be applied, mutatis mutandis, to each other or to any other tools, in any combination considered to be appropriate by a person skilled in the art.

Those skilled in the art to which this invention pertains will readily appreciate that numerous changes, variations,

23

and modification can be made without departing from the scope of the invention, mutatis mutandis.

The invention claimed is:

1. A cutting tool holder adapted for mounting thereon a cutting insert to form a cutting tool, the cutting tool holder comprising:

an insert seat *space configured for receiving therein the cutting insert, the insert seat space being defined by a base and at least one side wall extending from the base [to define an insert seat space adapted for receiving the cutting insert];*

a support element comprising a shoulder spaced from said at least one side wall, the support element being fixedly and integrally formed with the base and extending therefrom into the insert seat space;

a fastening member; and

a bore [formed in the insert seat] open at the base to the insert seat space adjacent the support element and between said side wall and said support element, and configured for receiving [a] the fastening member for engagement [with the insert seat];

a support element extending into the insert seat from the base so that the bore is disposed between the side wall and the support element, and being one of the following: integrally formed with the insert seat; or

at least during operation, fixedly attached to the insert seat by means other than the fastening member;] therewith, wherein when the fastening member [being] is received within the bore, the fastening member is displaceable with respect to the [insert seat] base between a mounting position configured for allowing the cutting insert to be mounted [onto] within the insert seat space and a securing position adapted for securing the cutting insert within the insert seat space; and

wherein the fastening member, in the securing position, is configured to engage a sidewall of the support element and apply on the cutting insert a biasing force, directed away from the support element and towards the side wall defining the insert seat space, thereby securing the cutting insert within said insert seat space.

[2. The cutting tool holder according to claim 1, wherein fixed attachment of the support element is achieved via a screwing engagement between the support element and the insert seat.]

3. The cutting tool holder according to claim 1, wherein the cutting tool is adapted to rotate in a first direction about a central axis thereof, and the support element is formed with a first side wall generally perpendicular to the base and facing in the first direction, and a second side wall extending from the first wall in a direction opposite the first direction, at an acute angle θ to the first wall, both the first side wall and the second side wall being adapted for simultaneous engagement with the cutting insert.

4. The cutting tool holder according to claim 3, wherein the second side wall is formed with a recess adapted to receive a corresponding portion of the cutting insert when the latter is mounted onto the insert seat space.

[5. The cutting tool holder according to claim 1, wherein, in both the mounting position and the securing position, the fastening member remains in engagement with the insert seat.]

6. The cutting tool holder according to claim [5] 1, wherein in the mounting position the fastening member protrudes to a first extent into the insert seat space, and in the securing position, the fastening member protrudes to a second extent into the insert seat space, greater than the first extent.

24

7. The cutting tool holder according to claim [5] 1, wherein the fastening member [is in the form of] comprises a securing pin [adapted to be] received within [a corresponding] said bore [of the insert seat].

8. The cutting tool holder according to claim 7, wherein the securing pin is spring biased into the securing position.

9. A cutting insert configured for mounting onto a cutting tool holder to form the cutting tool, the cutting tool holder [including] comprising:

an insert seat *space configured for receiving therein the cutting insert, the insert seat space being defined by a base and at least one side wall extending from the base [to define an insert seat space adapted for receiving the cutting insert];*

a support element fixedly and integrally formed with the base and extending therefrom into the insert seat space; a fastening member; and

a bore [formed in the insert seat configured for receiving a fastening member for engagement with the insert seat; a support element extending into the insert seat from the base so that the bore is disposed between the side wall and the support element, and being one of the following: integrally formed with said insert seat; or at least during operation, fixedly attached to the insert seat by means other than the fastening member] open at the base to the insert seat space adjacent the support element and between said side wall and said support element, and configured for receiving the fastening member for engagement therewith, the bore being;

[and] the fastening member, when received within the bore, being displaceable with respect to the [insert seat] base between a mounting position configured for allowing the cutting insert to be mounted [onto] within the insert seat space and a securing position adapted for securing the cutting insert within the insert seat[,] space;

the fastening member, in the securing position, being configured to engage a sidewall of the support element and apply on the cutting insert a biasing force, directed away from the support element and towards the side wall defining the insert seat space, thereby securing the cutting insert within said insert seat space;

the cutting insert comprising:

a top face;

a bottom face; and

a cavity extending between the top face and the bottom face, the cavity taking up no less [that] than 15% of the overall volume of the cutting insert, the cavity defining a central axis extending between the top face and the bottom face through the center of an inscribing circle of the cavity, located on a plane substantially perpendicular to the axis, the cavity being formed with an inner surface having a first securing portion with a first geometric shape configured for engagement with the support element, and a second securing portion located at an opposite side of the cavity with respect to the central axis, and having a second geometric shape configured for engagement with the fastening member, both the first and the second securing portion being configured for simultaneously engaging the respective support element and fastening member in the same mounting position.

10. The cutting insert according to claim 9, wherein the first securing portion is closer to one of the top face and the bottom face, and the second securing portion is closer to the other of the top face and the bottom face.

25

11. The cutting insert according to claim 9, wherein the first securing portion is in the form of an arced surface and the second securing portion is substantially planar.

12. The cutting insert according to claim 9, wherein both the first securing portion and the second securing portion are in the form of arced surfaces.

13. The cutting insert according to claim 9, wherein the cutting insert is reversible, [so that] the inner cavity [comprises] *comprising*:

a first-side pair of securing portions:

a first securing portion oriented closer to the top face; and
a second securing portion oriented closer to the bottom face; and

at least a second-side pair of securing portions:

a first securing portion oriented closer to the bottom face; and
and

a second securing portion oriented closer to the top face.

14. The cutting insert according to claim 9, wherein the cutting insert is indexible, [so that] the inner cavity [comprises] *comprising* a first pair of securing portions and a second pair of securing portions, each pair comprising:

a first securing portion oriented closer to the top face; and
a second securing portion oriented closer to the bottom face.

15. The cutting insert according to claim 9, wherein the inner surface of the cavity is further formed with a first inner wall and a second inner wall forming therebetween an acute angle θ , both the first side wall and the second side wall being adapted for simultaneous engagement with the support element.

[16. A cutting tool comprising the cutting tool holder of claim 1, wherein, at least during operation, the cutting insert is mounted onto the cutting tool holder and secured therein so that the cavity of the cutting insert receives therein at least a portion of both the support element and the fastening element.]

[17. The cutting tool according to claim 16, wherein the cutting tool is adapted to revolve about a central axis thereof in a first direction, and wherein when the cutting insert is mounted onto the cutting tool holder the fastening member is adapted to apply a force F_1 on the cutting insert in a

26

direction generally along the central axis, the force F_1 pushing the cutting insert against the support element which is thereby adapted to apply a force F_2 on the cutting insert in a direction generally perpendicular to the central axis, the resultant force F_T of the two forces F_1 and F_2 being in a direction transverse to the central axis and opposite the first direction.]

[18. The cutting tool according to claim 16, wherein the cutting tool is formed with two or more cutting portions, each cutting portion comprising two or more of the cutting inserts, the cutting edges of which form a continuous cutting edge in each cutting portion, wherein the spatial arrangement of the cutting inserts of the same cutting portion varies from one cutting portion to another.]

[19. The cutting tool according to claim 18, wherein the cutting inserts in each cutting portion are shifted at a distance d with respect to one another, and wherein the shift d varies from one cutting portion to another.]

20. The cutting tool holder according to claim 1, wherein the support element is formed with an undercut surface extending, at least during operation, at an acute angle to the base and away from the side wall.

21. The cutting insert according to claim 9, wherein the cavity takes up no less than 30% of the overall volume of the cutting insert.

22. The cutting insert according to claim 9, wherein, in each cross-section of the cutting insert taken along a plane generally parallel to the top face or bottom face, a cross-sectional area of the cavity constitutes no less [that] than 15% of the entire cross-sectional area of the cutting insert.

23. The cutting tool holder according to claim 22, wherein the cross-sectional *area* of the cavity constitutes no less than 30% of the entire cross-sectional area of the cutting insert.

24. *The cutting tool holder according to claim 1, wherein, when in the securing position, said fastening member engages with said support element and said cutting insert.*

25. *The cutting insert according to claim 9, wherein the cavity takes up no less than 15% of the overall volume of the cutting insert.*

* * * * *