



US00RE46964E

(19) **United States**  
(12) **Reissued Patent**  
**Chen**

(10) **Patent Number:** **US RE46,964 E**  
(45) **Date of Reissued Patent:** **Jul. 24, 2018**

(54) **TWO-WHEEL SELF-BALANCING VEHICLE WITH INDEPENDENTLY MOVABLE FOOT PLACEMENT SECTIONS**

6,920,947 B2	7/2005	Kamen et al.
7,023,330 B2	4/2006	Kamen et al.
7,083,178 B2	8/2006	Potter
7,090,040 B2	8/2006	Kamen et al.
7,195,259 B2	3/2007	Gang
7,275,607 B2	10/2007	Kamen et al.
7,338,056 B2	3/2008	Chen
7,363,993 B2	4/2008	Ishii
7,367,572 B2	5/2008	Jiang
7,467,681 B2	12/2008	Hiramatsu

(Continued)

(71) Applicant: **Shane Chen**, Camas, WA (US)

(72) Inventor: **Shane Chen**, Camas, WA (US)

(73) Assignee: **Solowheel Inc.**, Camas, WA (US)

(21) Appl. No.: **15/165,654**

(22) Filed: **May 26, 2016**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **8,738,278**  
 Issued: **May 27, 2014**  
 Appl. No.: **13/764,781**  
 Filed: **Feb. 11, 2013**

(51) **Int. Cl.**  
**B62K 11/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B62K 11/007** (2016.11)

(58) **Field of Classification Search**  
 CPC ... B62D 1/00; B62D 1/02; B62K 3/02; B62K 3/06; B62K 11/00; B62K 11/07; B62K 17/00; B62K 21/00; B62K 21/22; B62K 23/08; B62K 2202/00

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,302,230 B1	10/2001	Kamen et al.
6,367,817 B1	4/2002	Kamen et al.
6,538,411 B1	3/2003	Field et al.
6,581,714 B1	6/2003	Kamen et al.
6,651,763 B1	11/2003	Kamen et al.

**FOREIGN PATENT DOCUMENTS**

CN	100431906 C	11/2008
CN	101353070 A	1/2009

(Continued)

**OTHER PUBLICATIONS**

Decision Denying Institution of Inter Partes Review under 37 C.F.R. 42.108, Petravick et al., Administrative Patent Judges, Inter Partes Review No. IPR2016-01778, Mar. 16, 2017, pp. 1-20.

(Continued)


*Primary Examiner* — Sam Rimell

(74) *Attorney, Agent, or Firm* — Foster Pepper PLLC

(57) **ABSTRACT**

A two-wheel, self-balancing personal vehicle having independently movable foot placement sections. The foot placement sections have an associated wheel, sensor and motor and are independently self-balancing which gives the user independent control over the movement of each platform section by the magnitude and direction of tilt a user induces in a given platform section. Various embodiments are disclosed including those with a continuous housing, discrete platform sections and/or tapering platform sections.

**16 Claims, 4 Drawing Sheets**





(56)

References Cited

U.S. PATENT DOCUMENTS

7,479,872 B2 1/2009 Cedarbaum  
 7,481,291 B2 1/2009 Nishikawa  
 D601,922 S \* 10/2009 Imai et al. .... D12/1  
 7,740,099 B2 6/2010 Field et al.  
 7,775,534 B2 8/2010 Chen et al.  
 7,783,392 B2 8/2010 Oikawa  
 7,857,088 B2 12/2010 Field et al.  
 7,958,956 B2 6/2011 Kakinuma et al.  
 8,014,923 B2 9/2011 Ishii et al.  
 8,028,777 B2 10/2011 Kakinuma et al.  
 8,047,556 B2 11/2011 Jang et al.  
 8,113,524 B2 2/2012 Karpman  
 8,157,274 B2 4/2012 Chen  
 8,170,780 B2 5/2012 Field et al.  
 8,225,891 B2 \* 7/2012 Takenaka et al. .... 180/7.1  
 8,408,565 B2 4/2013 An  
 8,459,668 B2 6/2013 Yoon  
 8,467,941 B2 6/2013 Field et al.  
 8,490,723 B2 7/2013 Heinzmann et al.  
 8,606,468 B2 12/2013 Kosaka  
 8,738,278 B2 5/2014 Chen  
 8,978,791 B2 3/2015 Ha et al.  
 2004/0005958 A1 \* 1/2004 Kamen et al. .... 482/51  
 2004/0262871 A1 \* 12/2004 Schreuder et al. .... 280/87.1  
 2006/0202439 A1 \* 9/2006 Kahlert et al. .... 280/47.24  
 2006/0260857 A1 11/2006 Kakinuma et al.  
 2007/0273118 A1 11/2007 Conrad  
 2008/0029985 A1 \* 2/2008 Chen .... 280/87.042  
 2008/0147281 A1 \* 6/2008 Ishii et al. .... 701/49  
 2009/0032323 A1 \* 2/2009 Kakinuma et al. .... 180/218  
 2009/0078485 A1 \* 3/2009 Gutsch et al. .... 180/218  
 2009/0105908 A1 \* 4/2009 Casey et al. .... 701/41  
 2009/0115149 A1 5/2009 Wallis et al.  
 2009/0200746 A1 8/2009 Yamamoto  
 2009/0315293 A1 12/2009 Kosaka  
 2010/0025139 A1 \* 2/2010 Kosaka et al. .... 180/218  
 2010/0114468 A1 \* 5/2010 Field et al. .... 701/124  
 2010/0121538 A1 \* 5/2010 Ishii et al. .... 701/48  
 2010/0222994 A1 \* 9/2010 Field et al. .... 701/124  
 2010/0225080 A1 9/2010 Smith  
 2010/0237645 A1 \* 9/2010 Trainer .... 296/21  
 2011/0131759 A1 6/2011 An  
 2011/0209929 A1 \* 9/2011 Heinzmann et al. .... 180/6.2  
 2011/0220427 A1 \* 9/2011 Chen .... 189/21  
 2011/0221160 A1 \* 9/2011 Shaw .... 280/205  
 2011/0238247 A1 \* 9/2011 Yen et al. .... 701/22  
 2011/0282532 A1 11/2011 Kosaka et al.  
 2012/0035809 A1 2/2012 Kosaka  
 2012/0205176 A1 \* 8/2012 Ha et al. .... 180/220  
 2012/0239284 A1 \* 9/2012 Field et al. .... 701/124  
 2012/0290162 A1 \* 11/2012 Stevens et al. .... 701/22  
 2013/0032422 A1 \* 2/2013 Chen .... 180/218  
 2013/0032423 A1 \* 2/2013 Chen .... 180/218  
 2013/0105239 A1 \* 5/2013 Fung .... 180/218  
 2013/0228385 A1 \* 9/2013 Chen .... 180/6.5

FOREIGN PATENT DOCUMENTS

CN 101920728 12/2010  
 CN 101920728 A 12/2010  
 CN 301604610 S 7/2011  
 CN 202201103 U 4/2012  
 CN 10251663 B 6/2012  
 CN 102514662 A 6/2012  
 CN 102514662 B 6/2012  
 CN 102602481 A 7/2012  
 EP 1791609 B1 11/2011  
 JP 2004359094 A 12/2004  
 JP 2005094898 4/2005  
 JP 2005094898 A 4/2005  
 JP 2005335471 A 12/2005  
 JP 2006001385 A 1/2006  
 JP 2006008013 A 1/2006  
 JP 3981733 A 9/2007  
 JP 2010030436 A 2/2010

JP 2010030437 A 2/2010  
 JP 2010030438 A 2/2010  
 JP 2010030568 A 2/2010  
 JP 2010030569 A 2/2010  
 JP 2010035330 A 2/2010

OTHER PUBLICATIONS

Sasaki, Makiko et al., Steering Control of the Personal Riding-type Wheeled Mobile Platform (PMP), IEEE, International Conference on Intelligent Robots and Systems, Dec. 5, 2005, pp. 3821-3826, Edmonton, Alberta, Canada.  
 Initial Determination on Violation of Section 337 and Recommended Determination on Remedy and Bond, ITC Case No. 337-TA-1000, May 26, 2017, pp. 1-93.  
 U.S. Appl. No. 61/597,777, filed Feb. 12, 2012, Applicant: Shane Chen, 8 pages.  
 Abeygunawardhana et al., Vibration Suppression of Two-Wheel Mobile Manipulator Using Resonance-Ratio-Control-Based Null-Space Control, IEEE Transactions on Industrial Electronics, vol. 57, No. 12, pp. 4137-4146 (2010).  
 Kim et al., Development of a Two-Wheeled Mobile Tilting & Balancing (MTB) Robot, 2011 11th International Conference on Control, Automation and Systems (ICCAS), Gyeonggi-do, 2011, pp. 1-6.  
 Azizan et al., Fuzzy Control Based on LMI Approach and Fuzzy Interpretation of the Rider Input for Two Wheeled Balancing Human Transporter, 2010 8th IEEE International Conference on Control and Automation, Xiamen, 2010, pp. 192-197.  
 Cardozo et al., Prototype for a Self-Balanced Personal Transporter, 2012 Workshop on Engineering Applications (WEA), Bogota, 2012, pp. 1-6.  
 Chiu et al., Design and implement of the self-dynamic controller for two-wheel transporter, 2006 IEEE International Conference on Fuzzy Systems, Vancouver, BC, 2006, pp. 480-483.  
 Tsai et al., Intelligent Adaptive Motion Control Using Fuzzy Basis Function Networks for Self-Balancing Two-Wheeled Transporters, 2010 IEEE Conference on Fuzzy Systems, Barcelona, 2010 pp. 1-6.  
 Choi et al., Four and Two Wheel Transformable Dynamic Mobile Platform, 2011 IEEE International Conference on Robotics and Automation (ICRA), Shanghai, pp. 1-4.  
 Clark, et al. "Edgar, A Self-Balancing Scooter Final Report" (2005). (Divided in to 2 parts for submission).  
 Coelho et al., Development of a Mobile Two-Wheel Balancing Platform for Autonomous Applications, 15th International conference on Mechatronics and Machine Vision in Practice, Auckland, 2008, pp. 575-580.  
 Rebuttal Expert Report of William Singhose, Ph.D., on Claim Construction Issues (dated Aug. 10, 2016), including all attachments thereto and exhibits thereto.  
 Sasaki et al., Forward and Backward Motion Control of Personal Riding-type Wheeled Mobile Platform, Proceedings of the 2004 IEEE International Conference on Robotics and Automation, vol. 4, pp. 3331-3336.  
 Li et al., A coaxial couple wheeled equilibrium robot with T-S fuzzy equilibrium control, Industrial Robot: An International Journal, vol. 38, Issue 3, pp. 292-300, 2011.  
 Li et al., Controller Design of a Two-Wheeled Inverted Pendulum Mobile Robot, 2008 IEEE International Conference on Mechatronics and Automation, Takamatsu, pp. 7-12.  
 Seo et al., Simulation of Attitude Control of a Wheeled Inverted Pendulum, International Conference on Control, Automation, and Systems, 2007, Seoul, pp. 2264-2269.  
 Li et al., Mechanical Design and Dynamic Modeling of a Two-Wheeled Inverted Pendulum Mobile Robot, Proceedings of the 2007 IEEE International Conference on Automation and Logistics, Jinan, 2007, pp. 1614-1619.  
 Lin et al., Adaptive Robust Self-Balancing and Steering of a Two-Wheeled Human Transportation Vehicle, 62 J Intell Robot Syst, pp. 103-123 (2011) (first published online Aug. 27, 2010).  
 Quick, Darren, Nissan joins personal mobility field with Segway-skis, www.gizmag.com, Oct. 27 2009.



(56)

**References Cited**

## OTHER PUBLICATIONS

Sasaki, Makiko, et al., Steering Control of the Personal Riding-type Wheeled Mobile Platform (PMP), 2005 IEEE, International Conference on Intelligent Robots and Systems, Aug. 2005, pp. 54-60.

Hornyak, Tim, Robot roller skates less bulky than Segway, [www.cnet.com](http://www.cnet.com), Nov. 27, 2009.

Kim, Sangtae et al., Development of a Two-Wheeled Mobile Tilting & Balancing (MTB) Robot, 11th International conference on Control, Automation and Systems (ICCAS), Oct. 26-29, 2011, pp. 1-6, Kintex, Gyeonggi-do, Korea.

Quirk, Trevor, "Why you shouldn't expect a hoverboard any time soon," *Christian Science Monitor*, URL=<https://www.csmonitor.com/Science/2012/0213/Why-you-shouldn-t-expect-a-hoverboard-any-time-soon>, Feb. 13, 2012, Web. Jul. 5, 2016, pp. 1-5.

Quick, Darren, Nissan Joins Personal Mobility Field with "Segway-skis", <http://www.gizmag.com/nissan-personal-mobility-device/13210/>, *New Atlas, Urban Transport*, Oct. 27, 2009, pp. 1-9.

Bash, John D., "How Do Self Balancing Scooters Work?" URL=<https://bestelectrichoverboard.com/hoverboard-faq/how-do-self-balancing-scooters-work/>, Exhibit 2012, Inter Partes Review No. IPR2016-01778, Nov. 12, 2015, Web. Oct. 8, 2016, pp. 1-7.

Wells, Georgia, "What It's Like to Have Wheels for Feet: Test Driving the Latest 'Hoverboards,'" *The Wall Street Journal*, URL=<https://www.wsj.com/articles/what-its-like-to-have-wheels-for-feet-test-driving-the-latest-hoverboards-1446055640>, Exhibit 2011, Oct. 28, 2015, Web. Oct. 8, 2016, Inter Partes Review No. IPR2016-01778, pp. 1-5.

Google Trends—Web Search Interest: hoverboard—United States, Jan. 2004-Jul. 2016, Jul. 5, 2016, Exhibit 2010, Inter Partes Review No. IPR2016-01778, pp. 1-6.

Banks, Alec, "Everything You Need to Know About the 'Hoverboard' Craze," URL=<http://www.highsnobiety.com/2015/10/14/hoverboard-history/>, Exhibit 2004, Inter Partes Review No. IPR2016-01778, Oct. 14, 2015, Web. Jul. 25, 2016, pp. 1-13.

Detrick, Ben, "Celebrities on Scooters (Catch Them if You Can)," *The New York Times*, URL=<https://www.nytimes.com/2015/08/16/fashion/cara-delevingne-justin-bieber-meek-mill-stephen-curry-on-scooters.html>, Exhibit 2005, Inter Partes Review No. IPR2016-01778, Aug. 15, 2015, Web. Jul. 25, 2016, pp. 1-6.

Murphy, Mike, "Everything you've ever wanted to know about the hoverboard craze," *Quartz*, URL=<https://qz.com/495935/everything-youve-ever-wanted-to-know-about-the-hoverboard-craze/>, Exhibit 2006, Inter Partes Review No. IPR2016-01778, Nov. 11, 2015, Web. Jul. 25, 2016, pp. 1-12.

Kantrowitz, Alex, Everything You Need to Know About the Hoverboard Craze, *BuzzFeed News*, URL=[https://www.buzzfeed.com/alexkantrowitz/a-crash-course-in-hoverboards?utm\\_term=.qwV3MnB77#.debmbaMji](https://www.buzzfeed.com/alexkantrowitz/a-crash-course-in-hoverboards?utm_term=.qwV3MnB77#.debmbaMji), Exhibit 2007, Inter Partes Review No. IPR2016-01778, Aug. 27, 2015, Web. Dec. 26, 2016, pp. 1-9.

Hoverguru, <http://hoverguru.com/>, "They're completely different products': IO Hawk President John Soibatian not concerned about infringing on Hovertrax patent," URL=<http://hoverguru.com/posts/theyre-completely-different-products-io-hawk-president-john-soibatian-not-concerned-about-infringing-on-hovertrax-patent/>, Exhibit 2008, Inter Partes Review No. IPR2016-01778, Aug. 31, 2015, pp. 1-5.

Robinson, Mandy, "Hoverboard Black Friday Sales: Best Places to Get One Before Christmas," URL=<https://www.inquisitr.com/2589773/hoverboard-black-friday-sales-best-places-to-get-one-before-christmas/>, *Gadgets, inquisitr.com*, Exhibit 2009, Inter Partes Review No. IPR2016-01778, Nov. 24, 2015, Web. Jul. 27, 2016, pp. 1-8.

Declaration of W. Mark Richter in Support of Patent Owner Preliminary Response, Inter Partes Review No. IPR2016-01778, Dec. 27, 2016, pp. 1-8.

Complainants' (Razor USA LLC, Inventist, Inc., and Shane Chen), Documents in Support of Request to commence an investigation, ITC Case No. 337-TA-1000, Exhibit 1010, Mar. 21, 2016, pp. 1-132. [References split in to 6 parts].

Declaration of Dr. Gerald Cook, Exhibit 1008, Inter Partes Review No. IPR2016-01778, Sep. 13, 2016, pp. 1-98.

Complainants' (Razor USA LLC, Inventist, Inc., and Shane Chen) Initial Claim Construction Brief, ITC Case No. 337-TA-1000, Aug. 19, 2016, pp. 1-217.

Respondents' (Hangzhou Chic Intelligent Technology Co., Ltd, Swagway, LLC, Modell's Sporting Goods, Inc., Newegg, Inc., Powerboard a.k.a. Optimum Trading Co., United Integral, Inc. dba Skque Products, Alibaba Group Holding Ltd. and Alibaba.com Ltd., and Jetson Electric Bikes LLC) Opening Claim Construction Brief, ITC Case No. 337-TA-1000, Aug. 19, 2016, pp. 1-229. [References split in to 4 parts].

Claim Construction Brief of the Commission Investigative Staff, ITC Case No. 337-TA-1000, Aug. 29, 2016, pp. 1-26.

Complainants' (Razor USA LLC, Inventist, Inc., and Shane Chen) Rebuttal Claim Construction Brief, ITC Case No. 337-TA-1000, Sep. 2, 2016, pp. 1-24.

Respondents' (Hangzhou Chic Intelligent Technology Co., Ltd, Swagway, LLC, Modell's Sporting Goods, Inc., Newegg, Inc., Powerboard a.k.a. Optimum Trading Co., United Integral, Inc. dba Skque Products, Alibaba Group Holding Ltd. and Alibaba.com Ltd., and Jetson Electric Bikes LLC) Rebuttal Claim Construction Brief, ITC Case No. 337-TA-1000, Sep. 2, 2016, pp. 1-48.

Notice of Institution of Investigation, ITC Case No. 337-TA-1000, May 20, 2016, pp. 1-48.

Patent Owner Preliminary Response, Inter Partes Review No. IPR2016-01778, Dec. 27, 2016, pp. 1-51.

Complainants' (Razor USA LLC, Inventist, Inc., and Shane Chen) Petition for Review, ITC Case No. 337-TA-1000, Jun. 12, 2017, pp. 1-40.

Contingent Petition for Review of Initial Determination by Respondents Swagway, LLC, Modell's Sporting Goods, Inc., and Newegg, Inc., ITC Case No. 337-TA-1000, Jun. 12, 2017, pp. 1-39.

Respondent Hangzhou Chic Intelligent Technology Co., Ltd's Contingent Petition for Review, ITC Case No. 337-TA-1000, Jun. 12, 2017, pp. 1-22.

Petition of the Office of Unfair Import Investigations for Review In-Part of the Initial Determination on Violation, ITC Case No. 337-TA-1000, Jun. 12, 2017, pp. 1-28.

Jetson's Opposition to Petitions Filed by the ITC Attorney and Razor, ITC Case No. 337-TA-1000, Jun. 20, 2017, pp. 1-16.

Complainants' Opposition to Respondents' Contingent Petitions for Review Filed by (1) Hangzhou Chic Intelligent Co., Ltd., and (2) Respondents Swagway, LLC, Modell's Sporting Goods, Inc., and Newegg, Inc., ITC Case No. 337-TA-1000, Jun. 20, 2017, pp. 1-62.

Combined Response of the Office of Unfair Import Investigations to Complainants' Petition for Review and Respondents' Contingent Petitions for Review of the Initial Determination on Violation, ITC Case No. 337-TA-1000, Jun. 20, 2017, pp. 1-48.

Response to Complainants' and Staff's Petitions for Review of Initial Determination by Respondents Swagway, LLC, Modell's Sporting Goods, Inc., Hangzhou Chic Intelligent Technology Co., Ltd., and Newegg.com, Inc., ITC Case No. 337-TA-1000, Jun. 20, 2017, pp. 1-34.

Alibaba's Response to the Petitions for Review, ITC Case No. 337-TA-1000, Jun. 20, 2017, pp. 1-7.

Order 25: Construing the Terms of the Asserted Claims of the Patent at Issue, ITC Case No. 337-TA-1000, Nov. 1, 2016, pp. 1-26.

Consolidated Initial Proposed Claim Constructions, ITC Case No. 337-TA-1000, Jul. 19, 2016, pp. 1-8.

Respondents Powerboard LLC's and Jetson Electric Bikes, LLC's Motion for Summary Determination of Non-Infringement, ITC Case No. 337-TA-1000, Dec. 12, 2016, pp. 1-30.

Respondent Hangzhou Chic Intelligent Technology Co., Ltd.'s Objections and Responses to Complainants' First Set of Contention Interrogatories, ITC Case No. 337-TA-1000, Sep. 9, 2016, pp. 1-208.

Petition for Inter Partes Review of U.S. Pat. No. 8,738,278, Inter Partes Review No. IPR2016-01778, Sep. 13, 2016, pp. 1-73.

Appellants' (Razor USA LLC, Inventist, Inc. and Shane Chen), Non-Confidential Brief, Appeal from ITC Case No. 337-TA-1000,

(56)

**References Cited**

OTHER PUBLICATIONS

U.S. Court of Appeals for the Federal Circuit No. 17-2591, Jan. 8,  
2018, 174 pages. [Divided into 4 Parts].

\* cited by examiner






Fig. 2




Fig 3




Fig 4





Fig 5





**TWO-WHEEL SELF-BALANCING VEHICLE  
WITH INDEPENDENTLY MOVABLE FOOT  
PLACEMENT SECTIONS**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.**

CROSS REFERENCE TO RELATED  
APPLICATIONS

The present application claims the benefit of provisional application No. 61/597,777, filed Feb. 12, 2012, for a Two-Wheeled Self-Balancing Vehicle by the inventor herein.

FIELD OF THE INVENTION

The present invention relates to two-wheel, self-balancing vehicles and, more specifically, to such vehicles with two platform sections or areas that are independently movable with respect to one another and that thereby provide independent control and/or drive of the wheel associated with the given platform section/area.

BACKGROUND OF THE INVENTION

A first group of prior art two-wheel self-balancing vehicles is represented by a product known commonly as the "Segway." This product is disclosed in U.S. Pat. No. 6,302,230, issued to Sramek et al (the '230 patent). While a contribution in the field, the Segway and like devices are disadvantageous in that they are large, heavy and expensive, i.e., too heavy to be carried by a commuter or youth, too expensive for most to buy. Furthermore, turning is achieved through a handle bar structure that ascends from the platform upward toward the chest of a user. This tall steering structure is a trip hazard when a user makes an unplanned exit from the vehicle.

Another group of prior art two-wheel self-balancing vehicles has two platform sections, each associated with a given wheel, that tilt from side-to-side as a user leans left or right. The two platform sections move in a linked or "dependent" manner (for example, through a parallelogram frame, and not independently) and there is a single "vertical" axis for the platforms. When the axis is tilted directly forward or backward, both wheels drive at the same speed (as required for self-balancing). If a user leans to the side (tilts the "vertical" axis sideways), then the outside wheel is driven faster than the inside wheel to effect a turn toward the direction of the tilt.

These devices typically require a multi-component parallelogram structure to coordinate/link movement of the two platform sections and the wheels. Such componentry adds to the weight, bulk, complexity, and potential for mechanical failure of the device. Also, the turning radius is fairly large as one wheel is typically rotating around the other (moving in the same direction though at different speeds).

A need exists for a two-wheel self-balancing vehicle that provides independent wheel control, is light-weight and compact, is easy and safe to use, and that may be made in a cost-effective manner. A need also exists for a two-wheel self-balancing vehicle that is more maneuverable and more

ergonomic (functioning more naturally with the bio-mechanics of a user's legs and body) than prior art devices.

Other prior art includes skateboards that have two platform sections that are movable with respect to one another. Some have a shared shaft about which the two platform sections pivot, while others have a degree of flexibility in the platform. In both of these arrangements, the platform sections are arranged longitudinally, one primarily behind the other in the longitudinal line-of-direction of travel.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a two-wheel, self-balancing vehicle that overcomes the shortcomings of the prior art.

It is another object of the present invention to provide a two-wheel, self-balancing vehicle that has independently movable foot placement sections.

It is also an object of the present invention to provide such a two-wheel, self-balancing vehicle in which the independently movable foot placement sections are used by an operator to assert independent control over the driving of the wheel associated with the respective foot placement section. These and related objects of the present invention are achieved by use of a two-wheel, self-balancing vehicle with independently movable foot placement sections as described herein.

The attainment of the foregoing and related advantages and features of the invention should be more readily apparent to those skilled in the art, after review of the following more detailed description of the invention taken together with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a two-wheel, self-balancing vehicle with independently movable platform sections in accordance with the present invention.

FIG. 2 is a block diagram of components within the vehicle of FIG. 1.

FIG. 3 is a bottom perspective view of another embodiment of a two-wheel, self-balancing vehicle with independently movable platform sections in accordance with the present invention.

FIGS. 4-5 are a top perspective view and a bottom perspective view of another embodiment of a two-wheel, self-balancing vehicle with independently movable platform sections in accordance with the present invention.

DETAILED DESCRIPTION

Referring to FIG. 1, is a perspective view of a two-wheel, self-balancing vehicle **100** with independently movable platform sections in accordance with the present invention is shown.

Vehicle **100** may have a first and a second platform section **110,130**. Each platform section **110,130** may include a housing formed of a bottom housing member **111,131** and a top housing member **112,132**. The top housing members may have a foot placement section or area **113,133** formed integrally therewith or affixed thereon. The foot placement section is preferably of sufficient size to receive the foot of a user and may include a tread or the like for traction and/or comfort.

The housing may be formed of metal, sturdy plastic or other suitable material. The housing members may be molded and incorporate strengthening reinforcements, and



be shaped to receive and “nest” the internal components (discussed below) of the vehicle. The bottom and top housing sections are formed complementarily so that after the internal components are installed, the top housing section is fitted onto the bottom housing section and secured with screws or other fasteners. FIG. 1 illustrates holes 161, through which the fasteners are inserted.

Each platform section includes a wheel 115,135, and each wheel preferably has an axle 116,136 and motorized hub assembly 117,137 (shown in FIG. 2). Motorized hub assemblies are known in the art.

Referring to FIG. 2, a block diagram of components within vehicle 100 in accordance with the invention is shown. The dot-dash line represents a rough outline of the housing members. Each platform section preferably includes a position sensor 120,140, which may be a gyroscopic sensor, for independent measurement of the position of the respective platform section. The sensors are preferably mounted on circuit boards 121,141 that may be attached to the interior of the respective bottom housings. Sensed position information from sensor 120,140 is used to drive the corresponding motor 117,137 and wheel 115,135. The control logic for translating position data to motor drive signals may be centralized or split between the two platform sections. For example, control logic 150 may be electrically connected to sensors 120,140 and to drive motors 117,137, with electrical conduits connecting through the connecting shaft 170 between sensor 140, control logic 150, and drive motor 137.

Alternatively, a separate processor/control logic 151 may be provided in the second platform section 130. Logic 151, in this case, [would be] is [connect] *connected* directly to sensor 140 and drive motor 137 and [generate] *generates* drive signals to motor 137 (and wheel 135) based on data from sensor 140.

Communication between these components is primarily in the direction of data from the sensor and drive signals to the motor. However, communication in the other direction may include start signals ([ie] *i.e.*, to the sensor), status signals ([ie] *i.e.*, from the motor indicating an unsafe condition (e.g., excessive rpm[]), or a motor/drive failure or irregularity). This information, in addition to battery information, etc., could be communicated back to a user via lights or another interface, or communicated wirelessly (e.g., bluetooth) from the vehicle to a hand-held device such as a mobile phone. In addition, if the platform sections have separate and independent control logic 150,151, these processing units may still share information with one another, such as status, safe operation information, etc.

The two platform sections 110,130 are movably coupled to one another. FIG. 2 illustrates a shaft 170 about which they may rotate (or pivot with respect to one another). Brackets 164 and flange brackets 165 may secure the shaft to the platform sections, with the flange brackets preferably configured to prevent or reduce the entry of dirt or moisture within the housings. Shaft 170 may be hollow in part and thereby allowing for the passage of conduits therethrough. Pivoting or rotating shaft arrangements are known in the art, and others may be used without deviating from the present invention as long as the foot placement sections may move independently.

Since the platform sections may rotate or pivot with respect to one another, the left section 110, for example, may tilt forward while the right section tilts backward. This would cause the wheels to be driven in opposite directions, causing a user to spin-in-place or “pirouette” much like a figure skater. Alternatively, the platform wheels could be

tilted in the same direction, but one platform more than the other. This would cause the wheel associated with the more steeply tilted platform to drive faster, in turn causing the vehicle to turn. The sharpness of the turn could be readily adjusted by the user based on the relative tilt of the platform sections.

This leg movement to control turning is a very ergonomic and natural movement, akin to skiing and other gliding/sliding activities.

The rotating shaft 170 may also include a bias mechanism integral with the flange bracket 165 or otherwise configured to return the platform section to an even level in the absence of displacement from a riders weight.

Each platform section 110,130 may also include a platform or “shut-off” sensor 119,139 that detects when a user is standing [of] on the platform. When a user falls off, the absence of the rider is sensed and the control logic, in response, stops driving the wheels such that the vehicle comes to a stop (and does not carry on [rider less] *riderless*). In the absence of such a shut-off sensor, the vehicle would still stop rather soon as the wheels will be driven to a self-balancing position for their respective sections bringing the device to rest.

Referring to FIG. 3, a bottom perspective view of another embodiment of a two-wheel, self-balancing vehicle 200 with independently movable platform sections in accordance with the present invention is shown. Vehicle 200 may include first and second platform section 210,230 that are formed of bottom 211,231 and top 212,232 housing sections, similar to those in vehicle 100 above.

Each platform section 110,130 includes a wheel 215,235 which is respectively driven by a motorized hub 217,237 and an associated position sensor 220,240. Control logic 250 receives the sensed position information and drives the associated wheel toward self-balancing. As discussed above, the control logic 250 may be independent, provided in each platform section, or centralized, provided in one section. Regardless, the driving of each wheel is based on the position sensed by the sensor associated with that wheel.

A pivoting shaft or other arrangement may be used to movably/rotatably join the two platform sections.

Referring to FIGS. 4-5, a top perspective view and a bottom perspective view of another embodiment of a two-wheel, self-balancing vehicle with independently movable platform sections 300 in accordance with the present invention is shown. Vehicle 300 is similar to the other vehicles herein, yet instead of a pivoting or rotating connection between platform sections, the frame or housing is made of a sturdy yet sufficiently flexible material that the two foot placement sections are effectively first and second platform sections that move independently with respect to each other for independent control of wheels 315,335.

Vehicle 300 may include a bottom 311 and a top 312 housing sections. These may be made of a flexible steel or durable flexible plastic or the like. The two sections are preferably configured to receive the internal components. They are preferably complementary in shape and may be secured by fasteners from below. The top housing may include or have attached to it a rubber coating or surface or the like in the foot placement areas 313,333 to increase traction and/or comfort with the foot of a user.

The internal components may include position sensors for both sections 320,340, hub motors 317,337, and control logic 350 for independently driving wheels 315,335 toward a self-balancing position based on position information [sensor] *sensed* by their respective sensors 320,340. These



5

components may be the same or similar to those discussed above for vehicles 100 and 200 (FIGS. 1-3).

While the invention has been described in connection with specific embodiments thereof, it will be understood that it is capable of further modification, and this application is intended to cover any variations, uses, or adaptations of the invention following, in general, the principles of the invention and including such departures from the present disclosure as come within known or customary practice in the art to which the invention pertains and as may be applied to the essential features hereinbefore set forth, and as fall within the scope of the invention and the limits of the appended claims.

The invention claimed is:

1. A two-wheel, self-balancing vehicle device, comprising:

a first foot placement section and a second foot placement section that are coupled to one another and are independently [movable with respect to one another] rotatable along an axis passing through a first wheel and a second wheel;

[a] said first wheel associated with the first foot placement section and [a] said second wheel associated with the second foot placement section, the first and second wheels being spaced apart and substantially parallel to one another;

a first position sensor and a first drive motor configured to drive the first wheel, a second position sensor and a second drive motor configured to drive the second wheel; and

control logic that drives the first wheel toward self-balancing the first foot placement section in response to position data from the first sensor and that drives the second wheel toward self-balancing the second foot placement section in response to position data from the second foot placement section.

[2. The device of claim 1, wherein the first foot placement section and the second foot placement section are rotatably coupled to one another.]

3. The device of claim 1, wherein the first foot placement section and the second foot placement section are positioned substantially linearly between the first and second wheel.

4. The device of claim 1, wherein said first and second foot placement sections are mounted to a frame that is sufficiently flexible that the first and second foot placement platforms can move independently with respect to one another under the weight of a user.

5. The device of claim 1, further comprising:

a first housing section on which the first foot placement section is provided, the first housing section housing the first sensor and first drive motor; and

a second housing section on which the second foot placement section is provided, the second housing section housing the second sensor and second drive motor.

6. The device of claim 5, wherein the control logic include a first control logic controlling the first drive motor located in the first housing section and a second control logic controlling the second drive motor located in the second housing section.

7. The device of claim 5, wherein the first drive wheel extends from the first housing section on an end substantially opposite where the first housing section is coupled to the second housing section, and the second drive wheel extends from the second housing section on an end substantially opposite where the second housing section is coupled to the first housing section.

6

8. The device of claim 1, further comprising a platform sensor provided at at least one of the first and second foot placement sections that detects when a user is standing on that foot placement section.

9. The device of claim 1, further comprising a bias mechanism for returning the two independently movable first and second foot placement sections toward alignment in the absence of a force by a user displacing the two foot placement sections from alignment.

10. A two-wheel self-balancing vehicle device, comprising:

a first foot placement section and a second foot placement section that are coupled to one another and are independently rotatable along an axis passing through a first wheel and a second wheel;

said first wheel associated with the first foot placement section and said second wheel associated with the second foot placement section, the first and second wheels being spaced apart and substantially parallel to one another;

a first position sensor and a first drive motor configured to drive the first wheel a second position sensor and a second drive motor configured to drive the second wheel; and

control logic that drives the first wheel toward self-balancing the first foot placement section in response to position data from the first sensor and that drives the second wheel toward self-balancing the second foot placement section in response to position data from the second sensor.

11. The device of claim 10, wherein the first foot placement section and the second foot placement section are positioned substantially linearly between the first and second wheel.

12. The device of claim 10, wherein said first and second foot placement sections are mounted to a frame that is sufficiently flexible that the first and second foot placement platforms can move independently with respect to one another under the weight of a user.

13. The device of claim 10, further comprising:

a first housing section on which the first foot placement section is provided, the first housing section housing the first sensor and first drive motor; and

a second housing section on which the second foot placement section is provided, the second housing section housing the second sensor and second drive motor.

14. The device of claim 13, wherein the control logic include a first control logic controlling the first drive motor located in the first housing section and a second control logic controlling the second drive motor located in the second housing section.

15. The device of claim 13, wherein the first drive wheel extends from the first housing section on an end substantially opposite where the first housing section is coupled to the second housing section, and the second drive wheel extends from the second housing section on an end substantially opposite where the second housing section is coupled to the first housing section.

16. The device of claim 10, further comprising a platform sensor provided at at least one of the first and second foot placement sections that detects when a user is standing on that foot placement section.

17. The device of claim 10, further comprising a bias mechanism for returning the two independently movable first and second foot placement sections toward alignment in



*the absence of a force by a user displacing the two foot  
placement sections from alignment.*

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : RE46,964 E  
APPLICATION NO. : 15/165654  
DATED : July 24, 2018  
INVENTOR(S) : Chen

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification

At Column 1, under the heading "CROSS REFERENCE TO RELATED APPLICATIONS," at Line 16 (approx.), please replace "The present application," with the following:

--NOTICE: *More than one reissue application has been filed for the reissue of U.S. Patent No. 8,738,278 B2. The reissue applications are U.S. Reissue Patent Application Serial No. 16/000,535, filed on June 5, 2018, and U.S. Reissue Application Serial No. 15/986,713, filed on May 22, 2018, now abandoned, each of which is a continuation reissue application of U.S. Reissue Patent Application Serial No. 15/165,654 (the present application), filed on May 26, 2016, now U.S. Reissue Patent No. RE46,964 E, issued July 24, 2018, which is a reissue application of U.S. Patent Application Serial No. 13/764,781, filed on February 11, 2013, now U.S. Patent No. 8,738,278 B2, issued May 27, 2014, which--*

Signed and Sealed this  
Twenty-third Day of March, 2021



Drew Hirshfeld  
*Performing the Functions and Duties of the  
Under Secretary of Commerce for Intellectual Property and  
Director of the United States Patent and Trademark Office*



US00RE46964C1

(12) **EX PARTE REEXAMINATION CERTIFICATE** (11975th)  
**United States Patent**  
**Chen**

(10) **Number:** **US RE46,964 C1**  
(45) **Certificate Issued:** **Dec. 30, 2021**

(54) **TWO-WHEEL SELF-BALANCING VEHICLE WITH INDEPENDENTLY MOVABLE FOOT PLACEMENT SECTIONS**

(71) Applicant: **Shane Chen**, Camas, WA (US)

(72) Inventor: **Shane Chen**, Camas, WA (US)

(73) Assignee: **Shane Chen**, Camas, WA (US)

**Reexamination Request:**

No. 90/014,765, Jun. 4, 2021

**Reexamination Certificate for:**

Patent No.: **Re. 46,964**  
Issued: **Jul. 24, 2018**  
Appl. No.: **15/165,654**  
Filed: **May 26, 2016**

Certificate of Correction issued Mar. 23, 2021

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **8,738,278**  
Issued: **May 27, 2014**  
Appl. No.: **13/764,781**  
Filed: **Feb. 11, 2013**

(51) **Int. Cl.**  
**B62K 11/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B62K 11/007** (2016.11)

(58) **Field of Classification Search**  
None  
See application file for complete search history.


(56) **References Cited**

To view the complete listing of prior art documents cited during the proceeding for Reexamination Control Number 90/014,765, please refer to the USPTO's public Patent Application Information Retrieval (PAIR) system under the Display References tab.

*Primary Examiner* — Eron J Sorrell

(57) **ABSTRACT**

A two-wheel, self-balancing personal vehicle having independently movable foot placement sections. The foot placement sections have an associated wheel, sensor and motor and are independently self-balancing which gives the user independent control over the movement of each platform section by the magnitude and direction of tilt a user induces in a given platform section. Various embodiments are disclosed including those with a continuous housing, discrete platform sections and/or tapering platform sections.





**EX PARTE  
REEXAMINATION CERTIFICATE**

NO AMENDMENTS HAVE BEEN MADE TO 5  
THE PATENT

AS A RESULT OF REEXAMINATION, IT HAS BEEN  
DETERMINED THAT:

The patentability of claims 1, 3, 5-11 and 13-17 is 10  
confirmed.

Claim 2 was previously cancelled.

Claims 4 and 12 were not reexamined.

\* \* \* \* \*