

### US00RE47422E

## (19) United States

### (12) Reissued Patent

Lowrey et al.

### (10) Patent Number:

US RE47,422 E

### (45) Date of Reissued Patent:

Jun. 4, 2019

# (54) INTERNET-BASED SYSTEM FOR MONITORING VEHICLES

(71) Applicant: VERIZON TELEMATICS INC.,

Atlanta, GA (US)

(72) Inventors: Larkin Hill Lowrey, Seabrook, TX

(US); Matthew Banet, San Diego, CA (US); Bruce Lightner, La Jolla, CA (US); Diego Borrego, San Diego, CA (US); Chuck Myers, La Jolla, CA (US)

(73) Assignee: Verizon Patent and Licensing Inc.,

Basking Ridge, NJ (US)

(21) Appl. No.: 13/944,782

(22) Filed: Jul. 17, 2013

### Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,214,100** 

Issued: Jul. 3, 2012
Appl. No.: 12/783,488
Filed: May 19, 2010

U.S. Applications:

(63) Continuation of application No. 10/614,665, filed on Jul. 7, 2003, now Pat. No. 7,747,365, which is a (Continued)

(51) **Int. Cl.** 

G06F 19/00 (2018.01) G07C 5/00 (2006.01) F02M 25/08 (2006.01)

(52) **U.S. Cl.** 

CPC ...... *G07C 5/008* (2013.01); *G07C 5/006* (2013.01); *F02M 25/0818* (2013.01); *F02M 25/0827* (2013.01); *Y02T 10/84* (2013.01)

### (58) Field of Classification Search

CPC ..... Y02T 10/84; F02M 5/0818; F02M 5/0827 (Continued)

### (56) References Cited

### U.S. PATENT DOCUMENTS

3,748,894 A 7/1973 White et al. 4,258,421 A 3/1981 Juhasz et al. (Continued)

### FOREIGN PATENT DOCUMENTS

CA 2133673 4/1996 CA 2372900 5/2003 (Continued)

### OTHER PUBLICATIONS

RD-422061 A; Anonymous; Jun. 10, 1999; Abstract, Using Internet for vehicle diagnostics-enabling using to operate vehicle personal computer to direct web browser to vehicle diagnostics website . . .


(Continued)

Primary Examiner — Dennis G Bonshock

### (57) ABSTRACT

The invention provides a method for monitoring a vehicle that features the steps of: 1) generating a data packet including vehicle data retrieved from the vehicle using a wireless appliance; 2) transmitting the data packet over an airlink with the wireless appliance so that the data packet passes through a network and to a host computer system; 3) processing the data packet with the host computer system to generate a set of data; and 4) displaying the set of data on a web page hosted on the internet.

### 17 Claims, 7 Drawing Sheets



#### 5,850,209 A Related U.S. Application Data 12/1998 Lemke et al. 5,884,202 A 3/1999 **Arjomand** continuation of application No. 09/804,888, filed on 7/1999 Miller et al. 5,928,292 A 5,941,918 A \* 8/1999 Blosser ..... Mar. 13, 2001, now abandoned, and a continuation-5,957,985 A \* in-part of application No. 11/796,372, filed on Apr. 701/29.2 27, 2007, now Pat. No. 7,904,219, which is a con-5,964,821 A 10/1999 Brunts et al. tinuation-in-part of application No. 10/810,373, filed 5,987,377 A 11/1999 Westerlage et al. 2/2000 Chutorash 6,020,654 A on Mar. 26, 2004, now Pat. No. 7,228,211, which is 5/2000 McMillan et al. 6,064,970 A a continuation-in-part of application No. 10/447,713, 6,088,648 A 7/2000 Shah et al. filed on May 29, 2003, now Pat. No. 6,732,031, which 8/2000 Klarer 6,104,988 A is a continuation of application No. 09/776,100, filed 6,140,969 A 10/2000 Lindenmeier et al. 6,141,611 A 10/2000 Mackey et al. on Feb. 1, 2001, now Pat. No. 6,636,790. 10/2000 Miesterfeld 6,141,710 A 6,144,916 A 11/2000 Wood et al. Provisional application No. 60/222,986, filed on Jul. 11/2000 Caci 6,154,658 A 25, 2000, provisional application No. 60/222,213, 12/2000 Payne et al. 6,167,426 A filed on Aug. 1, 2000, provisional application No. 3/2001 Beckert et al. 6,202,008 B1 60/222,152, filed on Aug. 1, 2000. 6,208,948 B1 3/2001 Klingler et al. 5/2001 Kamiya et al. 6,225,898 B1 Field of Classification Search (58)6,236,933 B1 5/2001 Lang 5/2001 Kennedy et al. 6,240,295 B1 See application file for complete search history. 6,240,365 B1 5/2001 Bunn 6,246,935 B1 6/2001 Buckley 6,263,268 B1\* 7/2001 Nathanson ..... G07C 5/085 **References Cited** (56)340/870.01 8/2001 Harrison et al. 6,278,921 B1 U.S. PATENT DOCUMENTS 9/2001 Harrison et al. 6,285,953 B1 9/2001 Staiger 6,292,718 B2 7/1986 Neely et al. 4,602,127 A 9/2001 Lang et al. 6,295,492 B1 9/1987 McElroy 4,690,475 A 12/2001 Chou et al. 6,330,499 B1 9/1987 Zaleski 4,694,408 A 6,338,152 B1 1/2002 Fera et al. 5/1990 Abe et al. 4,926,330 A 1/2002 Moskowitz et al. 6,339,736 B1 9/1990 Cearley et al. 4,956,777 A 6,339,745 B1 1/2002 Novik 3/1991 Gray et al. 5,003,317 A 2/2002 Flick 6,346,876 B1 6/1991 Wilson 5,026,293 A 6,354,868 B1 3/2002 Korczynski et al. 9/1991 Abe 5,050,080 A 6,356,205 B1 3/2002 Salvo et al. 10/1992 Asano et al. 5,157,610 A 6,356,823 B1 3/2002 Iannotti et al. 6/1993 Mansell et al. 5,223,844 A 6,362,730 B2 3/2002 Razavi et al. 2/1994 Miller et al. 5,289,378 A 6,370,454 B1\* 5,343,906 A 9/1994 Tibbals 340/438 5,431,042 A \* 6,400,701 B2 6/2002 Lin et al. 73/114.71 6,401,528 B1\* 6/2002 Lambert ..... F02M 25/0809 8/1995 Parrillo 5,442,553 A 73/114.39 9/1995 Crane 5,450,321 A 6,405,106 B1 6/2002 Sheth et al. 10/1995 Boen et al. 5,463,567 A 6,408,232 B1 6/2002 Cannon et al. 12/1995 Schmitz 5,473,540 A 8/2002 Schuyler 6,429,773 B1 5,479,479 A 12/1995 Braitberg et al. 8/2002 Larson et al. 6,442,460 B1 2/1996 Welles et al. 5,491,486 A 6,459,988 B1 10/2002 Fan et al. 5/1996 Wortham 5,519,621 A 6,477,452 B2 11/2002 Good 7/1996 Pink et al. 5,532,927 A 6,480,170 B1 11/2002 Langley et al. 7/1996 Joyce 5,537,336 A 11/2002 Nelson 6,487,479 B1 8/1996 Alesio 5,550,551 A 11/2002 Odinak et al. 6,487,494 B2 5,555,498 A 9/1996 Berra et al. 11/2002 Brunemann et al. 6,487,717 B1 5,574,427 A 11/1996 Cavallaro 12/2002 Tennison et al. 6,496,777 B2 12/1996 Doyle 5,586,130 A 6,502,030 B2 12/2002 Hilleary 4/1997 Hapka 5,619,412 A 1/2003 Lawrence et al. 6,505,106 B1 5/1997 Day 5,633,645 A 1/2003 Flick 6,507,786 B2 6/1997 Shah et al. 5,636,122 A 1/2003 Flick 6,512,466 B2 9/1997 Smith et al. 5,671,141 A 2/2003 Flick 6,522,267 B2 5,673,305 A 9/1997 Ross 2/2003 Treyz et al. 6,526,335 B1 10/1997 Skorupski et al. 5,680,328 A 6,526,460 B1 2/2003 Dauner et al. 3/1998 Smith et al. ...... 701/29 5,729,452 A \* 3/2003 Fan et al. 6,529,159 B1 3/1998 Spaur et al. 5,732,074 A 4/2003 Fan 6,552,682 B1 5,737,215 A 4/1998 Schricker et al. 4/2003 Rudick et al. 6,556,889 B2 4/1998 Kobayashi 5,739,761 A 6,556,905 B1 4/2003 Mittelsteadt et al. 5,750,886 A 5/1998 Lambert et al. 6,564,127 B1 5/2003 Bauerle et al. 5,754,965 A 5/1998 Hagenbuch 5/2003 Baird et al. 6,564,128 B2 5,758,300 A 5/1998 Abe 6,580,916 B1 6/2003 Weisshaar et al. 6/1998 Brunts et al. 5,774,828 A 6,594,576 B2 7/2003 Fan et al. 7/1998 Stephen et al. 5,781,101 A 6,594,579 B1 7/2003 Lowrey et al. 7/1998 Mezger et al. 5,781,871 A 8/2003 Moller 6,604,032 B1 5,797,134 A \* 8/1998 McMillan .......... G06Q 30/0283 6,604,033 B1 8/2003 Banet et al. 705/4 8/2003 Lesesky et al. 6,604,038 B1 5,798,647 A 8/1998 Martin et al. 6,609,051 B2 8/2003 Fiechter et al. 5,808,907 A 9/1998 Shetty et al. 8/2003 Smith et al. 6,611,686 B1 9/1998 Doyle 5,815,071 A 8/2003 Harvey et al. 6,611,739 B1 5,828,585 A 10/1998 Welk et al.

6,611,740 B2

8/2003 Lowrey et al.

12/1998 Kaman

5,844,473 A

# US RE47,422 E Page 3

(56)	References Cited		8,214,100 B		Lowrey et al.	
IJ	S PATENT	DOCUMENTS	8,447,439 B 2001/0016789 A		Lowrey et al. Staiger	
0.	.b. IIIIIII	DOCOMENTO	2001/0018628 A		Jenkins et al.	
6,611,755 B	8/2003	Coffee et al.	2001/0033225 A	10/2001	Razavi et al.	
,		Lightner et al 701/33	2001/0034609 A		Dovolis	
		Wilson et al.	2002/0008644 A 2002/0008645 A			
, ,	12/2003		2002/0008043 A 2002/0016655 A			
, ,		Odinak et al. Shuman et al.	2002/0029101 A		Larson et al.	
, ,		McCarthy et al.	2002/0032505 A			
	2/2004	•	2002/0065698 A		Schick et al.	
6,694,234 B		Lockwood et al.	2002/0073170 A 2002/0078458 A		Hoffman et al. Furon et al.	
6,701,233 B 6,718,425 B		Namaky et al. Pajakowski et al.	2002/0099520 A		Falada et al.	
6,732,031 B		Lightner et al.	2002/0118222 A		Fogarty	
6,732,032 B		Banet et al.	2002/0133273 A		Lowrey et al.	
6,738,697 B			2002/0140545 A 2002/0143446 A		Nietupski et al. Rogers et al.	
6,751,452 B 6,751,479 B		Kupczyk et al.	2002/0143440 A			
6,754,485 B		Obradovich et al.	2002/0150050 A		Nathanson	
6,757,262 B		Weisshaar et al.	2002/0171650 A		Prabhakaran	
6,766,233 B		Odinak et al.	2002/0173885 A 2002/0173889 A		_	
, ,		Puranik et al.	2002/01/3889 A 2002/0177476 A			
6,801,841 B	2 10/2004 2 10/2004	Flick et al.	2003/0004623 A		Namaky et al.	
, ,	11/2004		2003/0004624 A	1/2003	Wilson et al.	
	2 12/2004	•	2003/0009270 A			10.1NI 0.1/0.504
, ,		Adachi et al.	2003/0040854 A	2/2003	Rendahl G	701/31.4
0,830,708 B	52 * 12/2004	Tripathi G07C 5/008 340/439	2003/0078722 A	4/2003	Odinak et al.	701/31.7
6,845,307 B	2 1/2005	Rother	2003/0083809 A		Hatano	
6,845,362 B		Furuta et al.	2003/0093199 A		Mavreas	
6,862,524 B		Nagda et al.	2003/0093204 A 2003/0130005 A		Adachi et al. Weisshaar et al.	
6,867,733 B 6,868,386 B		Sandhu et al. Henderson G06Q 30/0283	2003/0130003 A 2003/0130774 A		Tripathi et al.	
0,000,500 D	01 3/2003	340/439	2003/0139179 A		Fuchs et al.	
6,879,894 B	4/2005	Lightner et al.	2003/0147534 A		Ablay et al.	
6,882,313 B		Fan et al.	2003/0182055 A 2003/0231118 A		Curatolo et al.	
6,889,064 B		Baratono et al.	2003/0231118 A 2003/0236596 A		Eisenmann et al.	
6,889,135 B 6,892,131 B		Curatolo et al. Coffee et al.	2004/0023645 A		Olsen et al.	
6,895,444 B		Weisshaar et al.	2004/0039502 A		Wilson et al.	
6,907,330 B		Eisenmann et al.	2004/0039504 A 2004/0044454 A		Coffee et al.	
6,922,566 B		Puranik et al.	2004/0044434 A 2004/0075539 A		Ross et al. Savoie et al.	
6,928,348 B 6,941,202 B		Lightner et al. Wilson et al.	2004/0093134 A		Barber et al.	
6,944,121 B		Weste et al.	2004/0104842 A		Drury et al.	
6,947,760 B		Weisshaar et al.	2004/0196182 A 2005/0131729 A		Unnold Molby et al	
6,947,816 B			2005/0131729 A 2005/0144318 A		Melby et al. Chang	
6,956,501 B 6,957,133 B	10/2005 1 10/2005	Hunt et al.	2006/0116800 A		Obradovich	G01C 21/26
, ,	11/2005					701/31.4
6,973,324 B	2 12/2005	Weisshaar et al.	2007/0069947 A		Banet et al.	
		Lowrey et al.	2008/0027606 A 2008/0319665 A		Heim Berkobin et al.	
7,016,774 B		Roddy et al 701/30	2010/0228429 A		Lowrey et al.	
7,010,774 B		Falada et al.	2011/0153367 A		Amigo	
7,062,375 B			2012/005255	4 0/2012	<b>-</b>	705/4
, ,	7/2006		2012/0053759 A 2012/0259504 A		•	
7,085,710 B	8/2006	Beckert B60R 16/0315 704/201	2012/023930 <del>4</del> A	10/2012	Lowrey et al.	
7,092,803 B	8/2006	Kapolka et al.	FOR	EIGN PATE	NT DOCUMENTS	3
, ,	9/2006	<del>-</del>				
7,155,321 B		Bromley et al.		0816820	1/1998	
7,174,243 B 7,225,065 B		Lightner et al. Hunt et al.		0/040038	7/2000	
7,223,003 B 7,228,211 B		Lowrey et al.	WO 2000	)/079727	12/2000	
7,400,954 B		Sumcad et al.				
7,447,574 B		Washicko et al.	•	OTHER PU	BLICATIONS	
7,477,968 B		Lowrey et al.				
7,480,551 B 7,523,159 B		Lowrey et al. Williams et al.	"#1 Appendix Chart of Asserted Claims U.S. Pat. No. 6,636,790",			
7,532,962 B		Lowrey et al.	6:07-CV-00466-LED, entered, Feb. 11, 2008.			
7,532,963 B	5/2009	Lowrey et al.	"#2 Appendix Chart of Asserted Claims U.S. Pat. No. 6,372,031",			
7,747,365 B		Lowrey et al. Gelvin H04L 67/12	6:07-CV-00466-LED, entered, Feb. 11, 2008.			
7,891,004 B	L/ZUII	701/24	"#3 Appendix Cha	art of Asserted	Claims U.S. Pat. No	o. 6,611,740",
7,904,219 B	3/2011	Lowrey et al.	6:07-CV-00466-LI			

### (56) References Cited

### OTHER PUBLICATIONS

"40 CFR 51", 40 CFR 51, Ch. I (Jul. 1, 2001 Edition), pp. 130-481. "40 CFR 85", 40 CFR 85. Ch. I (Jul. 1, 2001 Edition), 143 pages. "Automotive ISO 9141 Serial Link Driver", Motorola, Inc. Document MC333199/D, 1996, 12 Pages.

"Chipset", Definition of "Chipset," printed from Webopedia, Internet site, Oct. 31, 2002, 3 pages.

"Definition of "Chipset" from Wikipedia, Feb. 23, 2006.", Definition of "Chipset" from Wikipedia, Feb. 23, 2006.

"12C", printed from http://www.nxp.com, Internet site, (associated with www.philipslogic.com), website accessed on Jun. 8, 2006, 3 pages.

"Notice of Disclosure by HTI IP, LLC", of Asserted Claims and Infringement Contentions and Document Production Accompanying Disclosure, Feb. 11, 2008.


"Qualcomm Chipset Solutions", printed from http://www.qualcomm.com, Internet site, website accessed on Jun. 8, 2006, 48 pages.


Di Genova, et al., "Incorporation of Wireless Communications into Vehicle On-Board Diagnostic (OBD) Systems", Report No. SR00-01-03 prepared for California Air Resources Board (Sierra Research, Inc.) Jan. 18, 2000.

Oliver, "Implementing the J1850 Protocol", Intel Corporation, 15 p.p.

Wilson, et al., "Modular system for multiparameter in-line machine fluid analysis", (Technology showcase Apr. 3-6, 2000).

<sup>\*</sup> cited by examiner










Fig. 2










Fig. 5A





# INTERNET-BASED SYSTEM FOR MONITORING VEHICLES

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

# CROSS REFERENCE TO RELATED APPLICATION

This application 1) is a continuation of, and claims  $^{15}$ priority under 35 U.S.C. §120 to, U.S. patent application Ser. No. 10/614,665, now U.S. Pat. No. 7,747,365, entitled 'Internet-based system for monitoring vehicles', which has a filing date of Jul. 7, 2003, and which is a continuation of U.S. patent application Ser. No. 09/804,888, which was filed 20 on Mar. 13, 2001, now abandoned, both of which are incorporated by reference in [its entirety] their entireties herein[. This application also] and; 2) is a continuation-inpart of, and claims priority under 35 U.S.C. §120 to U.S. patent application Ser. No. 11/796,372, now U.S. Pat. No. 25 7,904,219, entitled 'Peripheral Access Devices and Sensors for Use with Vehicle Telematics Devices and Systems', which has a filing date of Apr. 27, 2007[.], which is a continuation-in-part of prior U.S. patent application Ser. No. 10/810,373, filed Mar. 26, 2004, now U.S. Pat. No. 30 tured. 7,228,211, which is (1) a continuation-in-part of prior U.S. patent application Ser. No. 10/431,947, filed May 8, 2003, now issued as U.S. Pat. No. 6,957,133; and (2) a continuation-in-part of prior U.S. patent application Ser. No. 10/447,713, filed May 29, 2003, now issued as U.S. Pat. No. 6,732,031, which is a continuation of prior U.S. patent application Ser. No. 09/776,106, filed Feb. 1, 2001, now issued as U.S. Pat. No. 6,636,790, which claims the benefit of U.S. Provisional Application No. 60/220,986, filed Jul. 25, 2000, U.S. Provisional Application No. 60/222,213, filed Aug. 1, 2000 and U.S. Provisional Application No. 60/222, 152, filed Aug. 1, 2000. The contents of all of the abovelisted applications are incorporated herein by reference in their entirety.

### FIELD OF THE INVENTION

The present invention relates to use of an Internet-based system for monitoring a vehicle's performance.

### BACKGROUND OF THE INVENTION

The Environmental Protection Agency (EPA) requires vehicle manufacturers to install on-board diagnostics (OBD-II) for monitoring light-duty automobiles and trucks beginning with model year 1996. OBD-II systems (e.g., microcontrollers and sensors) monitor the vehicle's electrical and mechanical systems and generate data that are processed by a vehicle's engine control unit (ECU) to detect any malfunction or deterioration in the vehicle's performance. Most 60 ECUs transmit status and diagnostic information over a shared, standardized electronic buss in the vehicle. The buss effectively functions as an on-board computer network with many processors, each of which transmits and receives data. The primary computers in this network are the vehicle's 65 electronic-control module (ECM) and power-control module (PCM). The ECM typically monitors engine functions

2

(e.g., the cruise-control module, spark controller, exhaust/gas recirculator), while the PCM monitors the vehicle's power train (e.g., its engine, transmission, and braking systems). Data available from the ECM and PCM include vehicle speed, fuel level, engine temperature, and intake manifold pressure. In addition, in response to input data, the ECU also generates 5-digit 'diagnostic trouble codes' (DTCs) that indicate a specific problem with the vehicle. The presence of a DTC in the memory of a vehicle's ECU typically results in illumination of the 'Service Engine Soon' light present the dashboard of most vehicles.

Data from the above-mentioned systems are made available through a standardized, serial 16-cavity connector referred to herein as an 'OBD-II connector'. The OBD-II connector typically lies underneath the vehicle's dashboard. When a vehicle is serviced, data from the standardized buss is typically queried using an external engine-diagnostic tool (commonly called a 'scan tool') that connects to the OBD-II connector. The data are then displayed an analyzed with the scan tool, and can then be used to service the vehicle.

Some vehicle manufacturers also include complex electronic systems in their vehicles to access and analyze some of the above-described data. For example, General Motors includes a system called 'On-Star' in some of their high-end vehicles. On-Star collects and transmits data relating to these DTCs through a wireless network. On-Star systems are not connected through the OBD-II connector, but instead are wired directly to the vehicle's electronic system. This wiring process typically takes place when the vehicle is manufactured.

### BRIEF SUMMARY OF THE INVENTION

It is an object of the present invention to provide a wireless, internet-based system for monitoring a vehicle. Specifically, it is an object of the invention to access data from a vehicle, analyze it, and make it available to organizations (e.g. an automotive dealership or service center) over the internet so that the vehicle's performance can be analyzed accurately and in real-time. The data include, for example, DTCs that trigger 'alert messages' that are emailed to a vehicle owner or displayed on a web page on the internet.

In one aspect, the invention provides a method for monitoring a vehicle that features the steps of: 1) generating a data packet that includes data retrieved from the vehicle using a wireless appliance; 2) transmitting the data packet over an airlink with the wireless appliance so that it passes through a network and to a host computer system; 3) processing the data packet with the host computer system to generate a set of data; and 4) displaying the set of data on a web page hosted on the internet.

The 'wireless appliance' used in the above-described method includes electronics that extract data from the vehicle's ECU, and a transmitting component (e.g. a radio or cellular modem) that sends out the data packet over an existing network (e.g., Cingular's Mobitex network). Such a wireless appliance is described in the U.S. patent application Ser. No. 09/776,106, now U.S. Pat. No. 6,636,790, entitled WIRELESS DIAGNOSTIC SYSTEM FOR VEHICLES, and filed Feb. 1, 2001, the contents of which are incorporated herein by reference.

In embodiments, the processing step includes extracting at least one of the following vehicle parameters from the data packet: numerical data, an alphanumeric text message, an active or pending diagnostic trouble code (e.g., a 5-digit code), or a vehicle identification number. These parameters

are then processed with database software (e.g., an Oracle database) to generate a set of data that comprises an alphanumeric text message. The text message, e.g. an alert message, can be displayed on the web page or emailed to a user. The text message can also include a description of the 5 data parameter, such as a written description of the DTC.

In related embodiments, the method includes the step of processing at least one numerical parameter from the numerical data with a mathematical algorithm. This generates an alert message from data other than DTCs. For 10 example, the numerical parameter can be compared or displayed with at least one numerical parameter generated at an earlier point in time (e.g., a previously determined fuel level), or with a predetermined numerical value (e.g., a mileage level corresponding to a recommended service 15 appointment). These values, or a simple analysis of the data, can be included in the alphanumeric text message displayed on the web page or sent out in an email.

In another aspect, the invention features a similar set of steps for processing data from multiple vehicles (e.g., a 20 group of customers) associated with a corporate organization (e.g., a vehicle dealership). Specifically, the invention features the steps of 1) generating a first data packet comprising vehicle data retrieved from a first vehicle in a set of vehicles using a first wireless appliance disposed in the first 25 vehicle; 2) transmitting the first data packet over an airlink with the first wireless appliance so that it passes through a network and to a host computer system; 3) repeating steps 1 and 2 for a second vehicle; 4) processing the first and second data packets with the host computer system to generate first 30 and second sets of data; 5) displaying the first set of data on a first web page hosted on the internet; and 6) displaying the first and second sets of data on a second web page hosted on the internet.

In this embodiment, a single web site includes the first and second web pages. The web site also includes a 'login' web page for entering a user name and a password so that one group of users (e.g. vehicle owners) can log in with and view data from a single vehicle, while another group (e.g. corporate organizations such as vehicle dealerships, vehicle-40 rental organizations, insurance organizations, or fleet organizations) can log in and view data of all the users associated with the group.

In the above-described method, the term "airlink" refers to a standard wireless connection (e.g., a connection used for wireless telephones or pagers) between a transmitter and a receiver. Also in the above-described method, the 'generating' and 'transmitting' steps can be performed at any time and with any frequency, depending on the diagnoses being performed. For a 'real-time' diagnoses of a vehicle's engine performance, for example, the steps may be performed at rapid time or mileage intervals (e.g., several times each minute, or every few miles). Alternatively, other diagnoses (e.g. an emissions or 'smog' check) may require the steps to be performed only once each year or after a large number of miles are driven. Alternatively, the vehicle may be configured to automatically perform these steps at predetermined or random time intervals.

The term 'web page' refers to a single page that is hosted on the internet or world-wide web. A 'web site' typically 60 includes multiple web pages.

The invention has many advantages. In particular, wireless transmission of data from a vehicle, followed by analysis and display of these data using a web site hosted on the internet, makes it possible to diagnose the performance of a 65 vehicle in real-time from virtually any location that has internet access. This ultimately means the problems with the

4

vehicle can be efficiently diagnosed, and in some cases predicted before they actually occur. Moreover, data from the vehicle can be queried and analyzed while the vehicle is actually in use to provide a relatively comprehensive diagnosis that is not possible using a conventional scan tool. An internet-based system for vehicle diagnoses can also be easily updated and made available to a large group of users simply by updating software on the web site. In contrast, a comparable updating process for a series of scan tools can only be accomplished by updating the software on each individual scan tool.

The wireless appliance used to access and transmit the vehicle's data is small, low-cost, and can be easily installed in nearly every vehicle with an OBD-II connector in a matter of minutes. It can also be easily transferred from one vehicle to another, or easily replaced if it malfunctions.

An in-vehicle wireless appliance can also collect data that is not accessible using a scan tool. For example, data that indicates a vehicles performance can be collected while the vehicle is actually driven. Scan tools, in contrast, can only collect data in a vehicle service bay. Service technicians, for example, can analyze DTCs during repair of the vehicle. The system described herein makes also makes data available in real-time, thereby allowing the technicians to order parts and schedule resources for service appointments before the vehicle is actually brought into the dealership.

The resulting data, of course, have many uses for automotive dealerships, vehicle-service organizations, vehicle-renting firms, insurance companies, vehicle owners, organizations that monitor emission performance (e.g., the EPA), manufacturers of vehicles and related parts, survey organizations (e.g., J.D. Power) and vehicle service centers. In general, these data yield information that benefits the consumer, vehicle and parts manufacturers, vehicle service centers, and the environment.

These and other advantages of the invention are described in the following detailed disclosure and in the claims.

### BRIEF DESCRIPTION OF DRAWINGS

The features and advantages of the present invention can be understood by reference to the following detailed description taken with the drawings, in which:

FIG. 1 is a schematic drawing of a website with a login process that renders a series of web pages associated with either a dealer interface or a customer interface;

FIG. 2 is a screen capture of a web page from the web site of FIG. 1 wherein a user enters a login and password;

FIG. 3 is a screen capture of a web page from the web site of FIG. 1 that shows a list of customers corresponding to a single dealership;

FIG. 4 is a screen capture of a web page from the web site of FIG. 1 that shows an alert message, generated by an odometer reading, for a customer's vehicle;

FIG. **5**A is a screen capture of a web page from the web site of FIG. **1** that shows two alerts, each generated by a separate DTC, for a customer's vehicle;

FIG. **5**B is a screen capture of a web page associated with the web page of FIG. **5**A that shows two 5-digit DTCs corresponding to the two alert messages shown in FIG. **5**A;

FIG. 6 is a screen capture of a web page from the web site of FIG. 1 that shows recent diagnostic data for a customer's vehicle; and

FIG. 7 is a screen capture of a web page from the website of FIG. 1 that shows several time-dependent sets of diagnostic data for a customer's vehicle.

# DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows a schematic drawing of a login process 10 for a website 20 that displays diagnostic data for a series of 5 'customer' vehicles associated with a vehicle 'dealership'. Within each vehicle is a wireless appliance that retrieves data from the vehicle's engine computer, and then sends these data, formatted in a data packet, wirelessly through a network. The data eventually are transferred from the network to the website 20 where they are formatted and displayed and processed as described below.

A user 'logs' into the website 20 by entering a username and password that, once entered, are compared to a database associated with the website. The comparison determines if 15 the user is a dealer or a customer. If the user is determined to be a dealer, the website renders a dealer interface 27 that contains, e.g., diagnostic information for each vehicle purchased from the particular dealership. Users viewing the dealer interface 27 do not have access to data corresponding 20 to vehicles sold by other dealerships. If the user is determined to be a customer, the website 20 renders a customer interface 29 that contains diagnostic information for one or more vehicles corresponding to the customer. The customer interface contains diagnostic information for each vehicle 25 corresponding to the customer.

FIG. 2 shows a screen capture from a 'home' web page 40 of an actual website. The web page 40, corresponding to the web page 20 shown in FIG. 1 as www.networkcar.com, is accessed from a conventional web browser (e.g., Netscape 30 Navigator). It renders a dealer/customer login portion 43 that prompts a user for a login and a password. The web page 40 includes a login region 42 where the user enters a login (in this case the user's email address), and a password region 44 where the user enters a corresponding password. The user 35 then clicks the login button 46 to authenticate the login and log the user into the website as either a 'customer', 'dealer', or an invalid user. The authentication process is performed with conventional database software. Here and throughout the application, the term 'clicks' means a computer mouse is 40 used to select or initiate a software-based feature on the web page.

The wireless appliance that provides a diagnostic data to the website is described in more detail in WIRELESS DIAGNOSTIC SYSTEM FOR VEHICLES, filed Feb. 1, 45 2001, the contents of which have been previously incorporated by reference. Each wireless appliance contains logic for retrieving data from the host vehicle and formatting the data in a data packet, and a wireless transmitter that transmits the data packet over an airlink to a wireless network 50 (e.g., Cingular's 'Mobitex' network). Each appliance typically transmits a data packet at either a predetermined time interval (e.g., once each day), or shortly (e.g., within a few seconds) after a DTC is generated. The format of each data packet, along with the data contained therein, is described in 55 the above-mentioned patent application. In general, each data packet contains information of its status, an address describing its destination, an address describing its origin, and a 'payload' that contains diagnostic data from the vehicle. The process for transmitting diagnostic data from a 60 vehicle to a website is described in more detail in the above-referenced patent application.

FIG. 3 is a screen capture of a web page 50 included in the dealer interface indicated in FIG. 1. The host computer system renders this page once the user is determined to be 65 a dealer following the login process. The screen capture features a customer list 52 corresponding to a single deal-

6

ership that includes: customer names 56 for each customer; a vehicle description 58 that includes the vehicle's year, make and model; a unique 17-digit vehicle identification number ('VIN') 60 that functions as the vehicle's serial number; and an 'alert' listing 62 that provides a number of alerts, described in more detail below, for each vehicle.

An alert is generated when data, sent from the vehicle's wireless appliance to the host computer system, indicates either 1) a mechanical/electrical problem with the vehicle; or 2) that a scheduled maintenance is recommended for the vehicle. For example, the customer list 52 includes a data field 54 that lists the user 'Five, Loaner' with an associated 2001 Toyota Corolla. The data field 54 also includes the number '1' in the alert listing 62, indicating the presence of one of a single alert.

FIG. 4 is a screen capture of a web page 60 entitled a 'Vehicle Check Page' that describes in more detail the alert and other data for 'Five, Loaner'. The web page 60 for this user, or any other user in the customer list 52, is accessed by clicking on the highlighted name in the data field **54** shown in the web page 50 of FIG. 3. The web page 60 features a header 61 that lists general information corresponding to this particular user, e.g. name, vehicle description, and VIN. The header 61 also include diagnostic data such as a field 70 showing the vehicle's odometer reading (5229 miles), a time/date stamp 72 indicating the last time the host computer system received data from the vehicle, and an icon and data field 71 indicating the vehicle's emissions performance. In this last case, the green box with a 'checkmark' indicates that the vehicle's emissions are within the levels mandated by the EPA. It is present when the vehicle has no DTCs that are associated with its emissions system.

The web page 60 is separated into four categories describing, respectively, a status of the vehicle's 'emission' system 62, 'transmission/brakes' system 64, 'engine/fuel' system 66, and 'other' systems 68. For this vehicle, the emission 62, transmission/brakes 64, and engine/fuel 66 system categories have no associated alerts. This is indicated by, respectively, messages 62', 64', 66' preceded an icon that features a green box with a checkmark similar to that shown in the data field 71 describing the overview vehicle's emissions status. These icons indicate that no DTCs corresponding to the respective categories were detected. Conversely the 'other' system category 68 includes an alert message 68' that includes a text message field preceded by an icon that features a yellow box with a 'question mark'. The presence of this single alert message **68**' is what generates the '1' listed in the data field 54 in FIG. 3. The alert message 68' is generated in response to an odometer reading (i.e., 5229) miles) transmitted in the most recent data packet sent by the vehicle.

The alert message 68' is first generated when the vehicle's mileage is within 1000 miles of the mileage corresponding to a recommended scheduled maintenance, which in this case is 5000 miles. Thus, an alert in generated and first appears on the web page 60 when the vehicle's odometer reading is 4000 miles or greater. Mileage values corresponding to this and other recommended schedule maintenances are entered into the system in a 'Scheduled Maintenance' section 75 on the same page. The alert message 68' appears on the web page 60 until: 1) the recommended service is performed on the vehicle; or 2) the vehicle's mileage is greater than 1000 miles from the mileage corresponding to a recommended scheduled maintenance (i.e., 6000 miles). In either case, the alert is 'cleared' from the web page 60 and

is stored in a 'History of Alert' section 75 that, when clicked, historically lists all the cleared alerts corresponding to this particular vehicle.

FIGS. 5A and 5B show, respectively, screen captures of web pages 80 and 100 that indicate alert messages 62a', 62b' 5 triggered by the presence of separate emissions-related DTCs within the vehicle. The DTC is sent from the vehicle in the data packet described above. The web pages 80, 100 feature the same general format as shown for FIG. 4, i.e. four categories describing the vehicle's 'emission' system 62, 10 'transmission/brakes' system 64, 'engine/fuel' system 66, and 'other' systems 68. In this case, the transmission/brakes **64**, engine/fuel **66** and other **68** systems have no associated alerts, and thus include messages 64', 66', and 68' preceded an icon that features a green box with a 'checkmark' as 15 before. In contrast, the emissions system **62** includes two alert messages **62**a', **62**b'. Each message includes a brief text message: 'engine may not be processing exhaust gasses efficiently'. The text message is included in a database and associated with each of the 5-digit DTCs. Note that the <sup>20</sup> presence of the alert messages 62a', 62b' means that there is a problem with this vehicle's emission system, and thus the icon in the data field 71 in the page's header 61 is red with an exclamation point.

FIG. **5**B shows a screen capture of a web page **100** that <sup>25</sup> includes more details for the alert messages 62a', 62b' from FIG. 5A. The web page 100 renders when a user clicks on the 'View Emissions System Details' link 85 in the emissions category 62 and includes alert messages 62a", 62b". These messages are essentially more detailed versions of the 30 alert messages 62a', 62b' shown in FIG. 5A. They include the same text description as alert messages 62a', 62b' in addition to a more detailed text description ("Exhaust Gas Recirculation Flow Insufficient Detected" for alert message 62a""; "Exhaust Gas Recirculation Flow Excessive Detected" for alert message 62b"") and the 5-digit DTC (P0401 for alert message 62a"; P0402 for alert message **62b"**). Detailed diagnostic data corresponding to the DTCs is accessed by clicking on the 'To System Diagnostic Measurements' field 90 in FIG. 5B. As shown in FIG. 6, this field 90 renders a web page 120 that lists a detailed data set 40 **122** transmitted from the vehicle-based wireless appliance to the host computer system. The host computer system receives the data set 122 at a time described by a time/date stamp 72 listed in the header 61. The data set 122 includes a data parameter name 125, a corresponding numerical value 45 127, and a description of the units 129 of the numerical value **127**. Some of the numerical values (e.g., the status of the 'MIL light' 131) are dimensionless, i.e. they do not have units. As described above, to generate the numerical values 127 the wireless appliance queries the vehicle's ECU at a set time interval (e.g. every 20 seconds), and transmits a data set **122** at a longer time interval (e.g. every 10 minutes). Thus, the numerical values in the data set can represent 'instantaneous' values that result from a single query to the ECU, or they can represent 'average' values that result from an average from multiple sequential queries.

The data parameters within the set 122 describe a variety of electrical, mechanical, and emissions-related functions in the vehicle. Several of the more significant parameters from the set are listed in Table 1, below:

### TABLE 1

Parameters Monitored from Vehicle

Pending DTCs
Ignition Timing Advance
Calculated Load Value

8

### TABLE 1-continued

Parameters Monitored from Vehicle

Air Flow Rate MAF Sensor Engine RPM Engine Coolant Temperature Intake Air Temperature Absolute Throttle Position Sensor Vehicle Speed Short-Term Fuel Trim Long-Term Fuel Trim MIL Light Status Oxygen Sensor Voltage Oxygen Sensor Location Delta Pressure Feedback EGR Pressure Sensor Evaporative Purge Solenoid Dutycycle Fuel Level Input Sensor Fuel Tank Pressure Voltage Engine Load at the Time of Misfire Engine RPM at the Time of Misfire Throttle Position at the Time of Misfire Vehicle Speed at the Time of Misfire Number of Misfires Transmission Fluid Temperature

PRNDL position (1, 2, 3, 4, 5 = neutral, 6 = reverse)
Number of Completed OBDII Trips
Battery Voltage

The parameters listed in Table 1 were measured from a Ford Crown Victoria. Similar sets of data are available for nearly all vehicles manufactured after 1996. In addition to these, hundreds of other vehicle-specific parameters are also available from the vehicle's ECU.

The data set 122 shown in FIG. 6 represents a current data sent from the vehicle's wireless appliance to the host computer system. Data sets sent at earlier times can also be analyzed individually or in a group to determine the vehicle's performance. These 'historical data', for example, can by used to determine trends in the vehicle's performance. In some cases data analyzed in this manner can be used to predict potential problems with the vehicle before they actually occur.

Referring to FIG. 7, a web page 130 includes a historical data set 132 containing data parameter names 125', units 129' and a series of data sets 127a-127c transmitted at earlier times from the in-vehicle wireless appliance. Each of these data sets is similar to the data set 122 shown in FIG. 6, but is received by the host computer system at an earlier time indicated by a timestamps 140a-140c. For example, the first two data sets 127c, 127b where transmitted with time stamps 140b, 140c of 11:42 and 11:52 on Feb. 12, 2001; the last data set 127a was transmitted the next morning with a time stamp 140a of 6:05. Time-dependent data shown in this manner can be analyzed to determine trends in a vehicle's performance. The trends can then be used to diagnose or predict a problem with the vehicle.

Other embodiments are also within the scope of the invention. In particular, the web pages used to display the data can take many different forms, as can the manner in which the data are displayed. Web pages are typically written in a computer language such as 'HTML' (hypertext mark-up language), and may also contain computer code written in languages such as Java for performing certain functions (e.g., sorting of names). The web pages are also associated with database software (provided by companies such as Oracle) that is used to store and access data. Equivalent versions of these computer languages and software can also be used.

Different web pages may be designed and accessed depending on the end-user. As described above, individual users have access to web pages that only show data for their particular vehicle, while organizations that support a large number of vehicles (e.g. dealerships or distributors) have 5 access to web pages that contain data from a collection of vehicles. These data, for example, can be sorted and analyzed depending on vehicle make, model, odometer reading, and geographic location. The graphical content and functionality of the web pages may vary substantially from what 10 shown in the above-described figures. In addition, web pages may also be formatted using standard wireless access protocols (WAP) so that they can be accessed using wireless devices such as cellular telephones, personal digital assistants (PDAs), and related devices.

The web pages also support a wide range of algorithms that can be used to analyze data once it is extracted from the data packets. For example, the above-mentioned method alert messages are sent out in response to a DTC or when a vehicle approaches a pre-specified odometer reading. Alter- 20 natively, the message could be sent out when a data parameter (e.g. engine coolant temperature) exceeded a predetermined value. In some case, multiple parameters (e.g., engine speed and load) can be analyzed to generate an alert message. In general, an alert message can be sent out after 25 analyzing one or more data parameters using any type of algorithm. These algorithms range from the relatively simple (e.g., determining mileage values for each vehicle in a fleet) to the complex (e.g., predictive engine diagnoses using 'data mining' techniques). Data analysis may be used 30 to characterize an individual vehicle as described above, or a collection of vehicles, and can be used with a single data set or a collection of historical data. Algorithms used to characterize a collection of vehicles can be used, for example, for remote vehicle or parts surveys, to characterize 35 emission performance in specific geographic locations, or to characterize traffic.

Other embodiments of the invention include algorithms for analyzing data to characterize vehicle accidents and driving patterns for insurance purposes; algorithms for 40 determining driving patterns for use-based leasing; and algorithms for recording vehicle use and driving patterns for tax purposes. In general, any algorithm that processes data collected with the above-described method is within the scope of the invention.

Similarly, the temporal or mileage frequency at which data is collected can be adjusted to diagnose specific types of problems. For example, characterization of certain types of vehicle performance indicators, such as emissions, may need to be monitored relatively frequently (e.g., once every 50 few minutes). Other properties, such as mileage and fluid levels, may only need to be monitored every few days, or in some cases just a few times each year.

In other embodiments, additional hardware can be added to the in-vehicle wireless appliance to increase the number of parameters in the transmitted data. For example, hardware for global-positioning systems (GPS) may be added so that the location of the vehicle can be monitored along with its data. Or the radio modem used to transmit the data may employ a terrestrial GPS system, such as that available on modems designed by Qualcomm, Inc. In still other embodiments, the location of the base station that transmits the message can be analyzed to determine the vehicle's approximate location. In addition, the wireless appliance may be interfaced to other sensors deployed in the vehicle to monitor additional data. For example, sensors for measuring tire pressure and temperature may be deployed in the vehicle

**10** 

and interfaced to the appliance so that data relating the tires' performance can be transmitted to the host computer system.

In other embodiments, data processed using the above-described systems can be used for: remote billing/payment of tolls; remote smog and emissions checks; remote payment of parking/valet services; remote control of the vehicle (e.g., in response to theft or traffic/registration violations); and general survey information.

Still other embodiments are within the scope of the following claims.

What is claimed is:

- 1. A method [for monitoring a vehicle with a vehicle computer device located in the vehicle,] comprising:
  - [(a)] acquiring, by a vehicle computer device connected to an engine control unit (ECU) of a vehicle via an OBD or OBD-II connector, vehicle data comprising numerical diagnostic data [or location-based data] associated with the vehicle;
  - [(b)] processing, by the vehicle computer device connected to the ECU of the vehicle via the OBD or OBD-II connector, the vehicle data according to a mathematical algorithm to generate derived diagnostic [or location] information that is at least in part derived from the [acquired] vehicle data, and wherein the derived diagnostic information has a meaning distinct from the [acquired] vehicle data;
  - [(c)] formatting, by the vehicle computer device connected to the ECU of the vehicle via the OBD or OBD-II connector, the derived diagnostic [or location] information for display on an application running on a host computer device, wherein the application can provide an interface for presenting information associated with the vehicle, wherein the interface includes at least one of an icon [and] or a data field associated with derived diagnostic information indicative of [the vehicle's] emissions performance[,] of the vehicle; and
  - [(d)] wirelessly transmitting, by a cellular modem included in the vehicle computer device connected to the ECU of the vehicle via the OBD or OBD-II connector and via an internet, the derived diagnostic information in a communication to the host computer device,
  - the derived diagnostic information for a first diagnostic problem to be diagnosed being monitored and wirelessly transmitted at a first temporal interval or mileage interval set based on the first diagnostic problem to be diagnosed, and
  - the derived diagnostic information for a second diagnostic problem to be diagnosed being monitored and wirelessly transmitted at a second temporal interval or mileage interval set based on the second diagnostic problem to be diagnosed,
    - the first temporal interval or mileage interval being simultaneous with and different than the second temporal interval or mileage interval.
- 2. The method of claim 1, wherein the application includes a browser.
- 3. The method of claim 1, wherein the processing [further] includes extracting information representative of at least one of the following vehicle parameters from the [received] vehicle data: numerical data, an alphanumeric text message, [and] or a vehicle identification number.
- 4. The method of claim 1, wherein the numerical diagnostic data includes at least one of the following numerical parameters: diagnostic trouble codes, vehicle speed, fuel level, fuel pressure, miles per gallon, engine RPM, mileage, oil pressure, oil temperature, tire pressure, tire temperature,

engine coolant temperature, intake-manifold pressure, engine performance tuning parameters, alarm status, accelerometer status, cruise-control status, fuel injector performance, spark-plug timing, [and] or a status of an anti-lock braking system.

- 5. The method of claim 1, wherein the host computer device is one of a cellular telephone, a personal digital assistant (PDA), a wireless smartphone, or a personal computer.
- **6**. A vehicle computer device[, located in a vehicle, 10 configured to perform a method, the method] comprising: *a cellular modem*;
  - a connector that connects to an OBD or OBD-II connector of a vehicle; and

a processor to:

- [(a) acquire] acquire vehicle data comprising numerical diagnostic data [or location-based data] associated with the vehicle via the OBD or OBD-II connector of the vehicle;
- [(b) processing] *process* the vehicle data according to a mathematical algorithm to generate derived diagnostic [or location] information that is at least in part derived from the [acquired] vehicle data, and wherein the derived *diagnostic* information has a meaning distinct from the [acquired] vehicle data; 25
- [(c) formatting] format the derived diagnostic [or location] information for display on an application running on a host computer device, wherein the application can provide an interface for presenting information associated with the vehicle, wherein the 30 interface includes at least one of an icon [and] or a data field associated with derived diagnostic information indicative of [the vehicle's] emissions performance[,] of the vehicle; and
- [(d)] wirelessly [transmitting] transmit, using the cel- 35 a personal computer.] a personal computer.] a personal computer.] transmitting] transmit, using the cel- 35 a personal computer.] a personal computer.] 15. A non-transitor instructions, the instructions, the instructions, the instructions, the instructions.

the derived diagnostic information for a first diagnostic problem to be diagnosed being monitored 40 and wirelessly transmitted at a first temporal interval or mileage interval set based on the first diagnostic problem to be diagnosed, and

the derived diagnostic information for a second diagnostic problem to be diagnosed being moni- 45 tored and wirelessly transmitted at a second temporal interval or mileage interval set based on the second diagnostic problem to be diagnosed, the first temporal interval or mileage interval

the first temporal interval or mileage interval being simultaneous with and different than the 50 second temporal interval or mileage interval.

- 7. The [method] *vehicle computer device* of claim **6**, wherein the application includes a browser.
- 8. The [method] vehicle computer device of claim 6, wherein the processor, when processing the vehicle data, is 55 to:
  - [wherein the processing further includes extracting] extract information representative of at least one of the following vehicle parameters from the [received] vehicle data: numerical data, an alphanumeric text 60 message, [and] or a vehicle identification number.
- 9. The [method] vehicle computer device of claim 6, wherein the numerical diagnostic data includes at least one of the following numerical parameters: diagnostic trouble codes, vehicle speed, fuel level, fuel pressure, miles per 65 gallon, engine RPM, mileage, oil pressure, oil temperature, tire pressure, tire temperature, engine coolant temperature,

**12** 

intake-manifold pressure, engine performance tuning parameters, alarm status, accelerometer status, cruise-control status, fuel injector performance, spark-plug timing, [and] *or* a status of an anti-lock braking system.

10. The [method] vehicle computer device of claim 6, wherein the host computer device is one of a cellular telephone, a personal digital, assistant (PDA), a wireless smartphone, or a personal computer.

[11. A graphical user interface running on a host computer device for displaying derived diagnostic or location information corresponding to a vehicle wherein the derived diagnostic or location information displayed by the graphical user interface includes diagnostic or location information wirelessly transmitted by, a vehicle computer device coupled to the vehicle to acquire diagnostic and location vehicle data generated thereby, and wherein the vehicle computer device processes the diagnostic or location vehicle data according to a mathematical algorithm, and wherein the information comprises at least one of vehicle status reports and vehicle service recommendations to generate the derived information so that it has a meaning distinct from the acquired diagnostic and location vehicle data,

wherein the graphical user interface includes at least one of an icon and data field associated with derived information indicative of the vehicle's emissions.

[12. The graphical user interface of claim 11 wherein the displayed graphical user interface includes a web browser.]

- [13. The graphical user interface of claim 11, wherein the graphical user interface is configured for displaying information formatted according to at least one wireless access protocol (WAP).]
- [14. The graphical user interface of claim 11, wherein the host computer device is one of a cellular telephone, a personal digital assistant (PDA), a wireless smartphone, or a personal computer.]

15. A non-transitory computer-readable medium storing instructions, the instructions comprising:

one or more instructions that, when executed by one or more processors of a vehicle computer device connected to an engine control unit (ECU) of a vehicle via an OBD or OBD-II connector, cause the one or more processors to:

acquire vehicle data comprising numerical diagnostic data associated with the vehicle via the OBD or OBD-II connector of the vehicle;

process the vehicle data according to a mathematical algorithm to generate derived diagnostic information that is at least in part derived from the vehicle data, and wherein the derived diagnostic information has a meaning distinct from the vehicle data;

format the derived diagnostic information for display on an application running on a host computer device, wherein the application can provide an interface for presenting information associated with the vehicle, wherein the interface includes at least one of an icon or a data field associated with derived diagnostic information indicative of emissions performance of the vehicle; and

wirelessly transmit, using a cellular modem included in the vehicle computer device, the derived diagnostic information in a communication via an internet to the host computer device,

the derived diagnostic information for a first diagnostic problem to be diagnosed being monitored and wirelessly transmitted at a first temporal interval or mileage interval set based on the first diagnostic problem to be diagnosed, and

the derived diagnostic information for a second diagnostic problem to be diagnosed being monitored and wirelessly transmitted at a second temporal interval or mileage interval set based on the second diagnostic problem to be diagnosed,

the first temporal interval or mileage interval being simultaneous with and different than the second temporal interval or mileage interval.

16. The non-transitory computer-readable medium of claim 15, wherein the application includes a browser.

17. The non-transitory computer-readable medium of claim 15, wherein the one or more instructions, that cause the one or more processors to process the vehicle data, cause the one or more processors to:

extract information representative of at least one of the 15 following vehicle parameters from the vehicle data: numerical data, an alphanumeric text message, or a vehicle identification number.

18. The non-transitory computer-readable medium of claim 15, wherein the numerical diagnostic data includes at 20 least one of the following numerical parameters: diagnostic trouble codes, vehicle speed, fuel level, fuel pressure, miles per gallon, engine RPM, mileage, oil pressure, oil tempera-

14

ture, tire pressure, tire temperature, engine coolant temperature, intake-manifold pressure, engine performance tuning parameters, alarm status, accelerometer status, cruise-control status, fuel injector performance, spark-plug tinting, or a status of an anti-lock braking system.

19. The non-transitory computer-readable medium of claim 15, wherein the host computer device is one of a cellular telephone, a personal digital, assistant (PDA), a wireless smartphone, or a personal computer.

20. The non-transitory computer-readable medium of claim 15, wherein the first temporal interval or mileage interval is a temporal interval, and

the derived diagnostic information for the first diagnostic problem to be diagnosed is wirelessly transmitted by the cellular modem a plurality of times each minute based on the temporal interval to provide the derived diagnostic information to the host computer device in real-time.

21. The non-transitory computer-readable medium of claim 15, wherein the first temporal interval or mileage interval is a mileage interval.

\* \* \* \*