



US00RE47444E

(19) **United States**
(12) **Reissued Patent**
Oh et al.

(10) **Patent Number:** **US RE47,444 E**
(45) **Date of Reissued Patent:** **Jun. 18, 2019**

(54) **LIGHT EMITTING DEVICE PACKAGE AND BACKLIGHT UNIT COMPRISING THE SAME**

(52) **U.S. Cl.**
CPC *H01L 33/62* (2013.01); *H01L 33/486* (2013.01); *H01L 33/54* (2013.01); *H01L 33/60* (2013.01)

(71) Applicant: **LUMENS CO., LTD.**, Yongin-si, Gyeonggi-do (KR)

(58) **Field of Classification Search**
CPC *H01L 33/10*; *H01L 33/405*; *H01L 33/42*; *H01L 33/44*; *H01L 33/50*; *H01L 33/58*;
(Continued)

(72) Inventors: **Seung Hyun Oh**, Gwangju-si (KR); **Pyoung Gug Kim**, Hwaseong-si (KR); **Seung Hoon Lee**, Yongin-si (KR); **Chun Ki Min**, Yongin-si (KR); **Jung A Lim**, Seoul (KR); **Jun Hyung Lim**, Seoul (KR); **Cheol Hun Jung**, Osan-si (KR); **Bo Hyun Chung**, Seoul (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,573,653 B1 * 6/2003 Ishinaga 313/512
6,700,137 B2 * 3/2004 Horiuchi et al. 257/81
(Continued)

(73) Assignee: **LUMENS CO., LTD.**, Yongin-si (KR)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/147,351**

CN 001630113 A 6/2005
CN 101535366 A 6/2005
(Continued)

(22) Filed: **May 5, 2016**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,142,747**
Issued: **Sep. 22, 2015**
Appl. No.: **14/358,994**
PCT Filed: **Nov. 16, 2012**
PCT No.: **PCT/KR2012/009752**
§ 371 (c)(1),
(2) Date: **May 16, 2014**
PCT Pub. No.: **WO2013/073897**
PCT Pub. Date: **May 23, 2013**

OTHER PUBLICATIONS

Machine English translation of JP 2006128511 A.*
(Continued)

Primary Examiner — Terrence R Till
(74) *Attorney, Agent, or Firm* — Mei & Mark LLP

(30) **Foreign Application Priority Data**


Nov. 17, 2011 (KR) 10-2011-0120496
Sep. 4, 2012 (KR) 10-2012-0097844

(57) **ABSTRACT**

Disclosed is a light emitting element package having excellent heat radiation performance and high luminance, and a backlight unit including the same. The light emitting element package includes a package including a lead frame, a light emitting element provided on the lead frame, and a molded material combined with the lead frame and having an opening for emitting light generated by the light emitting element, and a reflection structure having an opening corresponding to the opening of the molded material, and contacting the molded material.

(51) **Int. Cl.**
H01L 33/48 (2010.01)
H01L 33/62 (2010.01)
(Continued)

15 Claims, 9 Drawing Sheets



(AMENDED)

(51) Int. Cl.		2012/0205693 A1*	8/2012	Ong et al.	257/98
H01L 33/60	(2010.01)	2013/0010495 A1*	1/2013	Moon et al.	362/609
H01L 33/54	(2010.01)	2013/0169149 A1*	7/2013	Sato et al.	313/512
F21V 8/00	(2006.01)	2013/0170208 A1*	7/2013	Kuwaharada et al.	362/243
G02F 1/1335	(2006.01)	2015/0008455 A1*	1/2015	Tozawa et al.	257/88

(58) **Field of Classification Search**
 CPC H01L 33/36; H01L 33/48; H01L 33/60;
 H01L 33/62; H01L 33/486; H01L 25/167
 See application file for complete search history.

(56) **References Cited**
 U.S. PATENT DOCUMENTS

6,791,116	B2*	9/2004	Hirano et al.	257/79
6,897,490	B2*	5/2005	Brunner et al.	257/98
7,518,155	B2*	4/2009	Ishidu et al.	257/98
7,718,456	B2*	5/2010	Maeda et al.	438/40
7,737,463	B2*	6/2010	Lee et al.	257/99
7,830,079	B2*	11/2010	Tamaki et al.	313/498
8,029,152	B2*	10/2011	Sekine et al.	362/84
8,044,412	B2*	10/2011	Murphy et al.	257/81
8,197,097	B2*	6/2012	Ogawa et al.	362/294
8,231,251	B2*	7/2012	Eng et al.	362/346
8,354,745	B2*	1/2013	Lee et al.	257/686
8,664,538	B2*	3/2014	Kim	174/260
2002/0024808	A1*	2/2002	Suehiro et al.	362/245
2002/0085390	A1*	7/2002	Kiyomoto et al.	362/555
2002/0134988	A1*	9/2002	Ishinaga	257/99
2002/0163006	A1*	11/2002	Yoganandan et al.	257/81
2003/0067264	A1*	4/2003	Takekuma	313/501
2004/0061433	A1*	4/2004	Izuno et al.	313/498
2004/0076016	A1*	4/2004	Sato et al.	362/555
2004/0208210	A1*	10/2004	Inoguchi	372/36
2004/0211970	A1*	10/2004	Hayashimoto et al.	257/98
2005/0133808	A1*	6/2005	Uraya et al.	257/99
2005/0133939	A1	6/2005	Chikugawa et al.	
2006/0102917	A1*	5/2006	Oyama et al.	257/99
2006/0138937	A1*	6/2006	Ibbetson	313/502
2006/0152820	A1*	7/2006	Lien et al.	359/726
2006/0157722	A1*	7/2006	Takezawa et al.	H01L 33/60 257/98
2007/0145401	A1*	6/2007	Ikehara	257/98
2008/0023721	A1*	1/2008	Lee et al.	257/99
2008/0037252	A1*	2/2008	Nii et al.	362/267
2008/0054288	A1*	3/2008	Harrah et al.	257/99
2008/0210964	A1	9/2008	Tomioka	
2008/0224161	A1*	9/2008	Takada	257/98
2009/0046456	A1*	2/2009	Urano et al.	362/235
2009/0103005	A1*	4/2009	Nakazato et al.	349/62
2009/0147498	A1*	6/2009	Park	362/84
2009/0201440	A1*	8/2009	Hamada	349/61
2009/0230417	A1*	9/2009	Tsai et al.	257/98
2009/0243458	A1*	10/2009	Lee	313/45
2009/0296367	A1*	12/2009	Sekine et al.	362/84
2009/0303728	A1*	12/2009	Ueji et al.	362/296.01
2010/0002455	A1*	1/2010	Matsuoka et al.	362/382
2010/0072499	A1*	3/2010	Kwon et al.	257/98
2010/0133565	A1*	6/2010	Cho et al.	257/98
2010/0163898	A1*	7/2010	Hung et al.	257/98
2010/0193821	A1*	8/2010	Fukasawa et al.	257/98
2010/0277925	A1	11/2010	Tan et al.	
2010/0314654	A1*	12/2010	Hayashi	257/99
2011/0039978	A1*	2/2011	Kotani et al.	523/218
2011/0049550	A1*	3/2011	Katsuno et al.	257/98
2011/0065241	A1*	3/2011	Lin et al.	438/118
2011/0114979	A1*	5/2011	Jang	257/98
2011/0180832	A1*	7/2011	Kim	257/98
2011/0220926	A1*	9/2011	Kim	257/91
2012/0018772	A1*	1/2012	Nishijima et al.	257/99
2012/0057099	A1*	3/2012	Tanuma et al.	349/62
2012/0153326	A1*	6/2012	Wang et al.	257/98
2012/0161186	A1*	6/2012	Katabe et al.	257/98

FOREIGN PATENT DOCUMENTS

CN	101150164	A	3/2008
CN	101981716	A	2/2011
CN	102163682	A	8/2011
EP	2355194	A2	8/2011
JP	2000-156528		6/2000
JP	2004-288937	A	10/2004
JP	2005-0183531		7/2005
JP	2005-353816		12/2005
JP	2006-054371		2/2006
JP	2006128511	A *	5/2006
JP	2008-078500		9/2006
JP	2006237049	A *	9/2006
JP	2007-134340		5/2007
JP	2007-227480		9/2007
JP	4070208	B2 *	4/2008
JP	2008-186946		8/2008
JP	2008-300544		12/2008
JP	2011-171365		9/2011
JP	2011-204830		10/2011
KR	10-0730076	B1	6/2007
KR	2007-0056230	A	6/2007
KR	2007-0056233	A	6/2007
KR	10-0769718	B1	10/2007
KR	20090032866	A *	4/2009
KR	10-2010-0058978		6/2010
KR	20100058978	A	6/2010
KR	10-2010-0119513		11/2010
KR	1020100119513	A	11/2010
KR	10-2011-0007633		1/2011
KR	1020110007633	A	1/2011
KR	1020110112539	A	10/2011
KR	20110128693	A *	11/2011
TW	201024598	A	7/2010
WO	WO2011/006754		1/2011
WO	WO2011/082876	A1	7/2011

OTHER PUBLICATIONS

Machine English translation of JP 2006237049.*
 Machine English translation of JP 4070208 B2.*
 Machine English translation of KR 20090032866 A.*
 2nd Machine English translation of KR 20090032866 A.*
 Machine English translation of KR 10-2011-0128693.*
 Supplementary European Search Report dated Jul. 15, 2015 in EP 12850417, 8 pgs.
 First Japanese Office Action in JP2014-542249, 2 pgs.
 Second Japanese Office Action in JP2014-542249, 2 pgs.
 Chinese Office Action dated Mar. 16, 2016 in Chinese Application No. 201280067097.7, 15 pgs.
 Chinese Office Action dated Nov. 10, 2016 in Chinese Application No. 201280067097.7, 16 pgs.
 Communication pursuant to Article 94(3) EPC in European Patent Application No. 12850417.2-1551, 5 pgs.
 Office Action dated Jan. 31, 2017 in Japanese Application No. 2016-047503, 3 pgs.
 International Search Report (ISR) of PCT/KR2012/009752, 6 pgs.
 Office Action dated Nov. 7, 2012 in Korean Application No. 10-2011-0120496, 3 pgs.
 Communication from European Patent Office dated Nov. 6, 2018 in EP Application No. 18174472.3, enclosing extended European search report.
 International Search Report mailed Apr. 16, 2013; PCT/KR2012/009752.

* cited by examiner




FIG. 1
(AMENDED)




FIG. 2
(AMENDED)

FIG. 3





FIG. 4






FIG. 5




FIG. 6
(AMENDED)

FIG. 7




FIG. 8




FIG. 9





FIG. 10






FIG. 11




FIG. 12
(AMENDED)




FIG. 13
(AMENDED)




FIG. 14
(AMENDED)

FIG. 1 5




FIG. 1 6





FIG. 17



**LIGHT EMITTING DEVICE PACKAGE AND
BACKLIGHT UNIT COMPRISING THE
SAME**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 9,142,747. Currently, U.S. application Ser. No. 16/168,198, filed Oct. 23, 2018, is another application for reissue of U.S. Pat. No. 9,142,747.

TECHNICAL FIELD

The present invention relates to a light emitting element package and a backlight unit including the same. More particularly, the present invention relates to a light emitting element package having excellent heat radiation performance and high luminance, and a backlight unit including the same.

BACKGROUND ART

In general, a light emitting element is used as a light source of a backlight unit in an electronic device, e.g., display device. A light emitting element may be packaged in various ways before being connected to a backlight module and a backlight unit includes a packaged light emitting element.

The light emitting element of the light emitting element package generates not only light but also a considerable amount of heat.

DETAILED DESCRIPTION OF THE
INVENTION

Technical Problem

However, in the above-described conventional light emitting element package, heat generated by the light emitting element may not be easily discharged to the outside. As a result, a molded material may inflate or the life span of the light emitting element may be shortened.

The present invention has been made in an effort to solve various problems including the above problem, and provides a light emitting element package having excellent heat radiation performance and high luminance, and a backlight unit including the same. However, the scope of the present invention is not limited thereto.

Technical Solution

According to an aspect of the present invention, there is provided a light emitting element package including a lead frame, a light emitting element on the lead frame, a molded material combined with the lead frame and having an opening for emitting light generated by the light emitting element, and a reflection structure having an opening that corresponds to the opening of the molded material, and contacting the molded material.

The reflection structure may include a supporting portion contacting the molded material and provided continuously or discretely along a circumference of the opening of the molded material, and a radial portion contacting the supporting portion and extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.

The molded material may include a supporting portion provided continuously or discretely along a circumference of the opening of the molded material, and the reflection structure may include a radial portion contacting the supporting portion and having a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.

The molded material may include a supporting portion provided continuously or discretely along a circumference of the opening of the molded material, and the reflection structure may have a shape that corresponds to the supporting portion of the molded material and contact the molded material.

Recesses or concave and convex portions may be provided on the molded material, and the reflection structure may be fitted into the recesses or concave and convex portions.

The light emitting element package may further include an adhesive layer provided in at least part of a region between the molded material and the reflection structure to fix the reflection structure onto the molded material.

The adhesive layer may have a first thickness in an area adjacent to the light emitting element and a second thickness in an area away from the light emitting element, and the first thickness may be greater than the second thickness.

The thickness of the adhesive layer may be gradually reduced away from the light emitting element.

The reflection structure may include a radial surface formed in a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.

The radial surface of the reflection structure may form a predetermined angle with a main emission direction of light generated by the light emitting element emits.

The predetermined angle may be equal to or greater than 10° and equal to or less than 20° .

The radial surface of the reflection structure may form a first angle with to a main emission direction of light generated by the light emitting element, from a point where the radial surface contacts the molded material to a first point away from the molded material, and form a second angle with the main emission direction from the first point to a second point further away from the molded material compared to the first point, and the second angle may be greater than the first angle.

The light emitting element package may further include a first resin layer that includes a fluorescent material and be provided in the opening of the molded material to cover the light emitting element.

The light emitting element package may further include a light-transmitting second resin layer that covers the first resin layer and contacts the radial surface.

The light emitting element package may further include a light-transmitting second resin layer provided in the opening of the molded material to cover the light emitting element, and a first resin layer that includes a fluorescent material, covers the second resin layer, and contacts the radial surface.

The reflection structure may comprise metal.

A surface of the supporting portion facing the opening of the molded material may have a radial shape extending

radially relative to a direction along which light generated by the light emitting element emits.

Part of the reflection structure may be inserted into the opening of the molded material, and the other part of the reflection structure, protruding from the opening of the molded material may have a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.

According to another aspect of the present invention, there is provided a light emitting element package including a lead frame, a light emitting element on the lead frame, a molded material combined with the lead frame and having an opening for emitting light generated by the light emitting element, a reflection structure having an opening that corresponds to the opening of the molded material, and contacting the molded material, a supporting portion provided discretely or continuously on the molded material to fix the reflection structure onto the molded material, and an adhesive layer provided in at least part of a region between the molded material and the reflection structure, and having a first thickness in an area adjacent to the light emitting element and a second thickness in an area away from the light emitting element, wherein the first thickness is greater than the second thickness.

According to yet another aspect of the present invention, there is provided a backlight unit including a reflective sheet, a light guide plate on or above the reflective sheet, and a light emitting element package configured to illuminate the light guide plate.

According to yet another aspect of the present invention, there is provided a light emitting element package including a lead frame; a light emitting element on the lead frame; a molded material combined with the lead frame and having an opening for emitting light generated by the light emitting element, the inner surface of the molded material facing with the opening thereof having a first slope line; and a reflection structure having an opening that corresponds to the opening of the molded material and contacting the molded material, the inner surface of the reflection structure facing with the opening thereof having a second slope line, wherein the first slope line and the second slope line from a straight line.

The inner surface of the reflection structure may flush with the inner surface of the molded material along all circumferential direction of the opening of the molded material.

The inner surface of the molded material may have the first slope line in all circumferential direction of the opening of the molded material, and the inner surface of the reflection structure may have the second slope line in all circumferential direction of the opening of the reflection structure.

The light emitting element package may further comprise an adhesive layer provided in at least part of a region between the molded material and the reflection structure to fix the reflection structure onto the molded material, wherein the adhesive layer may be not exposed to the opening of the reflection structure and the opening of the molded material.

The adhesive layer may have a first thickness in an area adjacent to the light emitting element and a second thickness in an area away from the light emitting element, and wherein the first thickness may be greater than the second thickness.

Advantageous Effects

According to an embodiment of the present invention, a light emitting element package having excellent heat radiation performance and high luminance, and a backlight unit

including the same may be provided. However, the scope of the present invention is not limited thereto.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic cross-sectional view of a light emitting element package according to an embodiment of the present invention;

FIG. 2 is a partial schematic perspective view of the light emitting element package of FIG. 1;

FIGS. 3 and 4 are schematic cross-sectional views showing a manufacturing method of a light emitting element package, according to another embodiment of the present invention;

FIGS. 5 and 6 are schematic cross-sectional views showing a manufacturing method of a light emitting element package, according to yet another embodiment of the present invention;

FIGS. 7 and 8 are schematic cross-sectional views showing a manufacturing method of a light emitting element package, according to yet another embodiment of the present invention;

FIG. 9 is a partial schematic perspective view of a light emitting element package according to yet another embodiment of the present invention;

FIG. 10 is a schematic perspective view of a light emitting element package according to yet another embodiment of the present invention;

FIG. 11 is an exploded perspective view of the light emitting element package of FIG. 10;

FIG. 12 is a schematic cross-sectional view taken along line XII-XII of FIG. 10;

FIG. 13 is a schematic cross-sectional view of a light emitting element package according to yet another embodiment of the present invention;

FIG. 14 is a schematic cross-sectional view showing paths of as well as surfaces illuminated by light emitted from the light emitting element package according to embodiments of the present invention;

FIG. 15 is a schematic graph showing a beam angle of light emitted from the light emitting element package according to embodiments of the present invention;

FIG. 16 is a partial schematic perspective view of a light emitting element according to yet another embodiment of the present invention; and

FIG. 17 is a schematic side elevation view of a backlight unit according to an embodiment of the present invention.

BEST MODE

Hereinafter, embodiments of the present invention will be described in detail with reference to the attached drawings. The present invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the concept of the invention to a person having ordinary skill in the art. In the drawings, the sizes of elements may be exaggerated or reduced for convenience of explanation.

In the following description, x, y, and z axes are not limited to three axes on a Cartesian coordinate system, and may be construed in a broad sense to include those axes. For example, the x, y, and z axes may be perpendicular to each other but may also refer to different non-perpendicular directions.

5

FIG. 1 is a schematic cross-sectional view of a light emitting element package according to an embodiment of the present invention, and FIG. 2 is a partial schematic perspective view of the light emitting element package of FIG. 1. The cross-sectional view of FIG. 1 may be understood to be one taken along line I-I of FIG. 2. The light emitting element package according to this embodiment includes a package and a reflection structure 40 as illustrated in FIGS. 1 and 2. The package includes a lead frame 10, a light emitting element 20, and a molded material 30, and the reflection structure 40 includes a supporting portion 41 and a radial portion 42.

The lead frame 10 includes a first lead 11 and a second lead 12. The lead frame 10 may further include another lead(s). For example, the lead frame 10 may include a die pad for mounting the light emitting element 20 to be described below, and first and second leads spaced apart from the die pad.

The light emitting element 20 is provided on the lead frame 10, for example, on the first lead 11 as illustrated in FIGS. 1 and 2. The light emitting element 20 is an element for emitting light by receiving an electrical signal and may be used as a light source for various electronic devices. For example, the light emitting element include a diode of a compound semiconductor, and may be referred to as a light emitting diode (LED). The LED may emit light of various colors depending on materials of the compound semiconductor.

The light emitting element 20 may be electrically connected to the first lead 11 and/or the second lead 12, either by an electrically conductive adhesive member or to through wiring. Referring to FIG. 1, the light emitting element 20 is illustrated to be electrically connected to each of the first and second leads 11 and 12 through wiring. Wiring is not illustrated in FIG. 2.

The molded material 30 may be connected to the lead frame 10 to form an external shape of the whole light emitting element package. The molded material 30 has an opening 30a through which light generated by the light emitting element 20 passes. In FIGS. 1 and 2, the molded material 30 is illustrated to have the opening 30a capable of allowing light generated by the light emitting element 20 to proceed in the positive z direction. *The inner surface of the molded material 30 facing with the opening 30a thereof has a first slope line S_1 . The inner surface of the molded material may have the first slope line S_1 in all circumferential direction of the opening 30a of the molded material 30.*

The molded material 30 may be formed of a resin by, for example, transfer molding. Various modifications are possible and thus the molded material 30 may be formed by injection molding other than transfer molding. The resin for the molded material 30 may include, for example, epoxy.

A first resin layer 51 may be provided within the opening 30a of the molded material 30 such that the light emitting element 20 is covered and protected against, for example, external moisture. A fluorescent material may be mixed into the first resin layer 51 and the opening 30a of the molded material 30 may be completely or partially filled with the first resin layer 51. The opening may be partially filled with the first resin layer 51 mixed with the fluorescent material, and a (transparent) filler having no fluorescent material may be additionally provided to fill the remaining area. When the opening 30a of the molded material 30 is filled with the first resin layer 51, the opening will be filled as high as the top edge of the opening 30a of the molded material 30, that is, the bottom edge of the supporting portion 41 of the reflection

6

structure 40, which will be described below. The first resin layer 51 is not illustrated in FIG. 2.

The reflection structure 40 has an opening 40a that corresponds to the opening 30a of the molded material 30, and contacts the molded material 30. *The inner surface of the reflection structure 40 facing with the opening 40a thereof has a second slope line S_2 . The inner surface of the reflection structure 40 may have the second slope line S_2 in all circumferential direction of the opening 40a of the reflection structure 40. The second slope line S_2 and the first slope line S_1 may form a straight line. Furthermore, the inner surface of the reflection structure 40 facing with the opening 40a thereof may flush with the inner surface of the molded material 30 facing with the opening 30a thereof along all circumferential direction of the opening 30a of the molded material 30.* The reflection structure 40 may be formed of a metallic material having excellent thermal conductivity. Particularly, the reflection structure 40 may include the supporting portion 41 and the radial portion 42.

The supporting portion 41 contacts the molded material 30 and may be continuously provided along the circumference of the opening 30a of the molded material 30. The supporting portion 41 is illustrated to continuously surround the opening 30a of the molded material 30 in FIGS. 1 and 2.

The radial portion 42 is provided to contact the supporting portion 41. The radial portion 42 is illustrated to contact the supporting portion 41 and also contact a top surface of the molded material 30 in a light emitting direction (the positive z direction) in FIGS. 1 and 2, but the present invention is not limited thereto. That is, the radial portion 42 may not contact the molded material 30 but contact the supporting portion 41 only. The radial portion 42 and the supporting portion 41 may be provided as one body.

The radial portion 42 has a radial shape. Particularly, the radial portion 42 may be formed in a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits (the positive z direction). The radial shape of the radial portion 42 may be formed with respect to an axis that passes through the centers of the light emitting element 20 and the opening 30a of the molded material 30 (z axis).

A second resin layer 52 may be further provided. Here, the second resin layer 52 covers the first resin layer 51 and contacts the radial portion 42. The second resin layer 52 contacting the radial portion 42 may be understood to be the second resin layer 52 contacting an internal radial surface of the radial portion 42.

The second resin layer 52 may be formed of a light-transmitting material, e.g., an epoxy or silicone resin. The second resin layer 52 contacts the first resin layer 51 and the radial portion 42 (radiation surface) and thus may prevent the reflection structure 40 from being separated from, for example, the molded material 30. The second resin layer 52 may fill the reflection structure 40 as high as the top edge of the supporting portion 41 as illustrated in FIG. 1. The second resin layer 52 is not illustrated in FIG. 2.

Although the first resin layer 51, into which a fluorescent material is mixed, is provided in the opening 30a of the molded material 30 to cover the light emitting element 20, and the second resin layer 52 is provided to cover the first resin layer 51 and contact the radial portion 42 (radiation surface) in the above description, the relative positions of the first and second resin layers 51 and 52 may be switched. For example, a light-transmitting second resin layer may be provided in the opening 30a of the molded material 30 to cover the light emitting element 20, and a first resin layer,

into which a fluorescent material is mixed, may be provided to cover the second resin layer and contact the radial portion 42 (radiation surface).

Here, since the second resin layer is provided between the light emitting element 20 and the first resin layer into which the fluorescent material is mixed, the distance between the light emitting element 20 and the first resin layer into which the fluorescent material is mixed may be controlled using the second resin layer. If the distance between the light emitting element 20 and the first resin layer into which the fluorescent material is mixed decreases, the color temperature of light ultimately emitted to the outside is lowered. Consequently, the color temperature of light ultimately emitted to the outside may be controlled by adjusting the thickness of the second resin layer.

As described above, the light emitting element 20 generates not only light but also a considerable amount of heat. In a conventional light emitting element package, heat generated by a light emitting element may not be easily discharged to the outside. As a result, a molded material may inflate or the life span of the light emitting element shortened.

The light emitting element package according to the [this] embodiment includes the reflection structure 40, provided near the light emitting element 20 and contacting the molded material 30, and thus heat generated by the light emitting element 20 may be effectively discharged to the outside through the reflection structure 40. In particular, the radial portion 42 of the reflection structure 40 has a radial-shaped structure that is open to the outside of the molded material 30, and thus the heat generated by the light emitting element 20 and absorbed by the reflection structure 40 may be effectively discharged to the outside.

Some of the light generated by the light emitting element 20 proceeds along a direction between the positive z direction and the positive x direction, as well as along the positive z direction. The luminance in a forward direction of the light emitting element package may be greatly increased by having the above described light reflected on the internal surface 42' of the radial portion 42 of the reflection structure and then proceed approximately along the positive z direction. That is, the internal surface 42' of the radial portion 42 of the reflection structure 40 may function as a reflective surface together with a tilted side surface 30' of the opening 30a of the molded material 30.

A reflective portion may be formed only of the internal side surface 30' of the opening 30a of the molded material 30, but there may exist light that proceeds along a direction between the positive z direction and the positive x direction without reaching the internal side surface 30' of the opening 30a of the molded material 30. In the light emitting element package according to the current embodiment, the above described light may also be reflected on the internal surface 42' of the radial portion 42 provided outside the molded material 30 and then proceed approximately along the positive z direction.

The internal surface 42' of the radial portion 42 of the reflection structure 40 may be coated with a reflective material such as silver to improve reflectivity. For convenience, parts other than the internal surface 42' may also be coated.

Mode of the Invention

FIGS. 3 and 4 are schematic cross-sectional views showing a manufacturing method of a light emitting element package, according to another embodiment of the present

invention. Referring to FIG. 3, the package that includes the lead frame 10, the light emitting element 20, and the molded material 30, and the reflection structure 40 that includes the supporting portion 41 and the radial portion 42 are prepared. The package includes the first resin layer 51 that fills the opening 30a of the molded material 30 to cover the light emitting element 20.

After that, the package and the reflection structure 40 are aligned to contact each other as illustrated in FIG. 4, and then the second resin layer 52 is formed on the first resin layer 51, thereby manufacturing the light emitting element package illustrated in FIG. 1. The second resin layer 52 may prevent the reflection structure 40 from being separated from the molded material 30.

One package and one reflection structure 40 are aligned and combined in FIGS. 3 and 4, but the present invention is not limited thereto. For example, a plurality of lead frames 10 of packages may be aligned and connected to each other, a plurality of reflection structures 40 may be aligned and connected to each other, and then the packages and the reflection structures 40 may be combined and cut, thereby simultaneously manufacturing a plurality of light emitting element packages each of which having a reflection structure. This also applies to the following embodiments and modifications thereof.

Meanwhile, as described above, the package that includes the first resin layer 51 filling the opening 30a of the molded material 30 to cover the light emitting element 20 is prepared as illustrated in FIG. 3, the package and the reflection structure 40 are aligned to contact each other as illustrated in FIG. 4, and then the second resin layer 52 is formed on the first resin layer 51, thereby manufacturing the light emitting element package illustrated in FIG. 1. However, the present invention is not limited thereto. For example, a package that includes a light-transmitting second resin layer filling the opening 30a of the molded material 30 to cover the light emitting element 20 may be prepared, the package and the reflection structure 40 may be aligned to contact each other, and then a first resin layer into which a fluorescent material is mixed may be formed on the second resin layer, thereby manufacturing a light emitting element package.

Here, since the second resin layer is provided between the light emitting element 20 and the first resin layer into which the fluorescent material is mixed, the distance between the light emitting element 20 and the first resin layer into which the fluorescent material is mixed may be controlled using the second resin layer. If the distance between the light emitting element 20 and the first resin layer into which the fluorescent material is mixed decreases, the color temperature of light ultimately emitted to the outside is lowered. Consequently, the color temperature of light ultimately emitted to the outside may be controlled by adjusting the thickness of the second resin layer.

FIGS. 5 and 6 are schematic cross-sectional views showing a manufacturing method of a light emitting element package, according to yet another embodiment of the present invention. Referring to FIG. 5, the package that includes the lead frame 10, the light emitting element 20, and the molded material 30, and the reflection structure 40 that includes the supporting portion 41 and the radial portion 42 are prepared. The package does not include the first resin layer 51.

After that, the package and the reflection structure 40 are aligned to contact each other as illustrated in FIG. 6, the first resin layer 51 that fills the opening 30a of the molded material 30 to cover the light emitting element 20 is formed,

and then the second resin layer **52** is formed on the first resin layer **51**, thereby manufacturing the light emitting element package illustrated in FIG. 1. The second resin layer **52** may prevent the reflection structure **40** from being separated from the molded material **30**.

However, unlike this, after the package and the reflection structure **40** are aligned to contact each other as illustrated in FIG. 6, the first resin layer **51**, into which a fluorescent material is mixed, may not only fill the opening **30a** of the molded material **30** to cover the light emitting element **20** but also contact the reflection structure **40**, without a second resin layer being formed. Here, the first resin layer **51** may contact part of the radial portion **42**, or may completely fill the opening of the radial portion **42** lest the internal surface **42'** of the radial portion **42** is exposed.

Alternatively, after the package and the reflection structure **40** are aligned to contact each other as illustrated in FIG. 6, a second resin layer may fill the opening **30a** of the molded material **30** to cover the light emitting element **20**, and then a first resin layer into which a fluorescent material is mixed may be formed on the second resin layer. Here, the second resin layer may not contact the reflection structure **40** and the first resin layer may contact the reflection structure **40**, or the second resin layer may contact the reflection structure **40** and the first resin layer thereon may also contact the reflection structure **40**.

Heretofore, the reflection structure has been illustrated to include a supporting portion and a radial portion, but the present invention is not limited thereto. That is, the supporting portion may be part of a molded material and the reflection structure may include the radial portion only. For example, the supporting portion continuously or discretely disposed along the circumference of an opening of the molded material may be one of the components of the molded material. Furthermore, the reflection structure may include the radial portion contacting the supporting portion of the molded material and formed in a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.

FIGS. 7 and 8 are schematic cross-sectional views showing a manufacturing method of a light emitting element package, according to yet another embodiment of the present invention. In this embodiment, a structure wherein the package and the reflection structure **40** are combined is firstly prepared as illustrated in FIG. 7.

Here, the reflection structure **40** has a shape different from that of the reflection structure according to the preceding embodiments. In the manufacturing process according to this embodiment, part of the reflection structure **40** may be inserted into the opening **30a** of the molded material **30**, and the other part of the reflection structure **40**, protruding from the opening **30a** of the molded material **30**, may be formed in a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element **20** emits. That is, unlike the preceding embodiments, the supporting portion **41** may not be provided.

Particularly, the part of the reflection structure **40**, which is inserted into the opening **30a** of the molded material **30**, may contact an internal surface **30'** of the opening **30a** of the molded material **30**, and may extend to a bottom surface of the opening **30a** of the molded material **30** to contact the bottom surface (the first lead **11** or the second lead **12**) as illustrated in FIGS. 7 and 8. Alternatively, the reflection structure **40** may not extend to the bottom surface of the opening **30a** of the molded material **30** and may cover only

part of the internal surface **30'** of the opening **30a**. Including the above, various modifications of this embodiment are possible.

After the structure wherein the package and the reflection structure **40** are combined is prepared as described above, the first resin layer **51** is formed to cover the light emitting element **20** as illustrated in FIG. 8. A fluorescent material may be mixed into the first resin layer **51**. The first resin layer **51** may be cured and prevent the reflection structure **40** from being separated from the molded material **30**. A light-transmitting second resin layer may be provided on the first resin layer **51**, if necessary.

Unlike the above, after the structure wherein the package and the reflection structure **40** are combined is prepared as illustrated in FIG. 7, the first resin layer **51** into which the fluorescent material is mixed may not only fill the opening of the molded material **30** to cover the light emitting element **20** but also be formed such that a top surface of the first resin layer **51** is higher than that of the molded material **30**, without a second resin layer being formed.

Alternatively, after the structure wherein the package and the reflection structure **40** are combined is prepared as illustrated in FIG. 7, a second resin layer may fill the opening **30a** of the molded material **30** to cover the light emitting element **20**, and then a first resin layer into which a fluorescent material is mixed may be formed on the second resin layer.

The light emitting element package illustrated in FIG. 8 may be understood to be a light emitting element package according to yet another embodiment of the present invention.

Meanwhile, in the light emitting element package illustrated in FIG. 8, since the reflection structure **40** contacts the first and second leads **11** and **12**, the first and second leads **11** and **12** need to be insulated from each other. Accordingly, the reflection structure **40** may have a radial shape and be divided into at least two parts spaced apart from each other. A first part of the reflection structure **40**, which contacts the first lead **11**, and a second part of the reflection structure **40**, which contacts the second lead **12**, may be spaced apart from each other, and have an insulating material filled therebetween.

FIG. 9 is a partial schematic perspective view of a light emitting element package according to yet another embodiment of the present invention. Like the light emitting element package described above with reference to FIG. 1, etc., in the light emitting element package according to this embodiment, the reflection structure **40** includes the supporting portion **41** and a radial portion (not shown).

The difference is that the supporting portion **41** contacts the molded material **30** but is provided not continuously but discretely along the circumference of the opening **30a** of the molded material **30**. That is, the supporting portion **41** has discontinuous parts **41a**. Two discontinuous parts **41a** are illustrated in FIG. 9, but the number of the discontinuous parts **41a** may vary and the width of the discontinuous parts **41a** may be greater than that illustrated in FIG. 9.

Since the supporting portion **41** serves to support the radial portion (not shown), even when the supporting portion **41** has the discontinuous parts **41a**, manufacturing costs may be reduced, without deteriorating heat radiation function and forward direction luminance.

Alternatively, a supporting portion may not be part of the reflection structure **40**. That is, the supporting portion may be part of the molded material **30**, and the reflection structure **40** may have the radial portion only. Even here, the supporting portion, which is part of the molded material **30**,

11

may be provided not continuously but discretely along the circumference of the opening 30a of the molded material 30.

FIG. 10 is a schematic perspective view of a light emitting element package according to yet another embodiment of the present invention, and FIG. 11 is an exploded perspective view of the light emitting element package of FIG. 10. FIG. 12 is a schematic cross-sectional view taken along line XII-XII of FIG. 10.

The light emitting element package according to this embodiment may include a lead frame, a light emitting element 20, a molded material 30, and a reflection structure 40, as illustrated in FIGS. 10 to 12.

The molded material 30 may include a supporting portion 33 provided continuously or discretely along the circumference of the opening 30a. Particularly, the supporting portion 33 may be provided adjacent to the exterior part of the opening 30a along the circumference of the opening 30a. The supporting portion 33 is illustrated to discretely surround the opening 30a of the molded material 30 in FIGS. 10 to 12. However, the supporting portion 33 is not limited thereto and may continuously surround the opening 30a of the molded material 30 as described in the preceding embodiments. If the supporting portion 33 discretely surrounds the opening 30a of the molded material 30 as illustrated in FIGS. 10 to 12, this may be understood to be that recesses or concave and convex portions are formed in the molded material 30.

For example, if the molded material 30 has an almost rectangular parallelepiped shape, the opening 30a may be formed in the center of a top surface of the molded material 30, and the light emitting element 20 may be mounted at the central part of the opening 30a. As illustrated in FIGS. 10 to 12, the supporting portion 33 may extend along the circumference of the opening 30a of the molded material 30 and protrude from corners of the molded material 30 along the positive z direction.

Here, a surface of the supporting portion 33, facing the opening 30a of the molded material 30 may be formed in a radial shape extending radially relative to a direction along which light generated by the light emitting element 20 emits (e.g., the positive z direction). Particularly, the supporting portion 33 may have an internal surface that has a downward inclination with respect to the opening 30a of the molded material 30. This allows the supporting portion 33 to more stably support the reflection structure 40 that will be described below. This also allows the supporting portion 33 to more accurately guide or define a location wherein the reflection structure 40 is combined.

A resin layer [60] 50 may be provided on the light emitting element 20 in the opening 30a of the molded material 30 to cover the light emitting element 20 so as to protect the light emitting element 20 from, for example, external moisture. A fluorescent material may be mixed into the resin layer [60] 50 and the opening 30a of the molded material 30 may be completely or partially filled with the resin layer [60] 50. The opening may be partially filled with the resin layer [60] 50 into which the fluorescent material is mixed, and a (transparent) filler having no fluorescent material may be additionally provided to fill the remaining area. The resin layer [60] 50 or the filler may [be] fill not only the opening 30a of the molded material 30 but also fill the reflection structure 40 to a bottom end or a top end, which will be described below.

The reflection structure 40 has an opening that corresponds to the opening 30a of the molded material 30 and may contact the molded material 30. As described above, if the supporting portion 33 discretely surrounds the opening

12

30a of the molded material 30, that is, if it is understood that recesses or concave and convex portions are formed in the molded material 30, the reflection structure 40 may be fitted into the recesses or concave and convex portions. The reflection structure 40 may include a metal having excellent thermal conductivity. The reflection structure 40 may also include a radial surface 45 formed in a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element 20 emits.

When it comes to the role of the reflection structure 40, the reflection structure 40 may be configured to reflect light emitted by the light emitting element 20 such that the light proceeds approximately along the positive z direction. Particularly, since some of the light generated by the light emitting element 20 proceeds between the positive z direction and the positive y direction, as well as along the positive z direction. The luminance in a forward direction of the light emitting element package may be greatly increased and a beam angle of the light emitted by the light emitting element package may be narrowed by having the above described light reflected on the radial surface 45 of the reflection structure 40 and then proceed approximately along the positive z direction. That is, the radial surface 45 of the reflection structure 40 together with [a] an inclined internal side surface of the opening 30a of the molded material 30 may function as a reflective surface.

A reflective portion may be formed only of the internal side surface of the opening 30a of the molded material 30, but there may exist light that proceeds along a direction between the positive z direction and the positive y direction without reaching the internal side surface of the opening 30a of the molded material 30. In the light emitting element package according to this embodiment, the above described light may also be reflected on the radial surface 45 provided outside the molded material 30 and then proceed approximately along the positive z direction.

The cross-section of the radial surface 45 of the reflection structure 40 may be flat or bent. For example, referring to FIG. 12, the cross-section of the radial surface 45 of the reflection structure 40 may be flat. That is, the radial surface 45 of the reflection structure 40 may form a predetermined angle α with a main emission direction along which light generated by the light emitting element 20 emits. Here, the main emission direction refers to the positive z direction. Here, the predetermined angle α may be equal to or greater than 10° and equal to or less than 20° .

Meanwhile, FIG. 13 is a schematic cross-sectional view of a light emitting element package according to yet another embodiment of the present invention. FIG. 13 is a cross-sectional view of the light emitting element package according to the present invention, taken along a line located similar to the line XII-XII of FIG. 10.

Referring to FIG. 13, the radial surface 45 of the reflection structure 40 may form a first angle α_1 with the positive z direction from a point where the radial surface contacts the molded material 30 to a first point 43 away from the molded material 30, and form a second angle α_2 from the first point 43 to a second point 44 further away from the molded material 30 compared to the first point 43. Here, the second angle α_2 may be greater than the first angle α_1 . Particularly, the first angle α_1 may be about 10° and the second angle α_2 may be about 20° .

Here, the second point 44 may be, for example, an end portion of the reflection structure 40. That is, the first point 43 may be a certain point between two end portions of an internal surface of the reflection structure 40, located along

13

the positive z direction, i.e., between an end portion along a direction toward the molded material 30 (the negative z direction) and an end portion along an emission direction of light (the positive z direction). In addition, each of the first and second points 43 and 44 may be continuously provided along the circumference of the opening 30a of the molded material 30 to form an encircling line.

Since the radial surface 45 is inclined by the predetermined angle α as described above, light emitted from the light emitting element 20 may be radiated onto the radial surface 45. Accordingly, a beam angle of light emitted from the light emitting element package may be narrowed. The radial surface 45 of the reflection structure 40 may be coated with a reflective material such as silver to improve reflectivity. For convenience, portions other than the radial surface 45 may also be coated.

The reflection structure 40 may have a shape that corresponds to the supporting portion 33, thereby contacting the molded material 30. For example, if the supporting portion 33 is continuously provided, the reflection structure 40 may also have a continuous shape that corresponds to the shape of the supporting portion 33. Another example would be that if the supporting portion 33 is discretely provided as illustrated in FIGS. 10 and 11, the reflection structure 40 may also have a discrete shape to be inserted between the supporting portions 33.

FIG. 14 is a schematic cross-sectional view showing paths of light emitted from the light emitting element package according to embodiments of the present invention. Although FIG. 14 schematically illustrates paths of light emitted from the light emitting element package illustrated in FIG. 12, the paths of light may be equally or similarly applied to the light emitting element package illustrated in FIG. 13.

Referring to FIG. 14, light emitted from the light emitting element 20 may directly reach area A of a illuminated surface 70 along a first path 21, reach area B of the illuminated surface 70 after being reflected on the molded material 30 along a second path 22, and reach area C of the illuminated surface 70 after being reflected on the reflection structure 40 along a third path 23.

Here, if the reflection structure 40 and the molded material 30 have the same reflectivity, the luminance of area A may be the highest, the luminance of area B may be the second highest, and the luminance of area C may be the lowest. That is, the luminance is lowered away from an optical axis. In particular, the luminance may be greatly lowered from area B to area C.

However, according to the embodiments of the present invention, the reflection structure 40 may have a higher reflectivity than that of the molded material 30. For example, as described above, the reflection structure 40 may include a metal and thus have a higher reflectivity than that of the molded material 30 that is formed of a resin material. Accordingly, the luminance of light projected onto area C along the third path 23 may increase compared to a conventional way due to the high reflectivity of the reflection structure 40. Therefore, the luminance may not be rapidly reduced but gradually reduced from area A to area C and, particularly, the change in the luminance may be gradual or almost no change may occur from area B to area C. As such, light having an almost uniform luminance may be effectively projected onto the whole illuminated surface 70.

FIG. 15 is a schematic graph showing a beam angle of light emitted from the light emitting element package according to embodiments of the present invention.

14

A conventional light emitting element package has a peak of optical power in an optical axis direction, and emits light in such a manner that the optical power is not rapidly but gradually reduced as an angle with the optical axis is increased. Furthermore, due to a large beam angle, the conventional light emitting element package has a small amount of reduction in optical power even considerably far away from an optical axis, and thus is used for lighting by having an overall luminance of light emitted from a light emitting element package be gradually reduced over a wide range.

According to embodiments of the present invention, however, as shown in FIG. 15, light emitted from the light emitting element 20 may be reflected by the reflection structure 40 and thus the optical power near an optical axis may be almost uniform even away from the optical axis. Furthermore, the luminance of an illuminated area may be increased by narrowing a beam angle. Thus, light emitted from the light emitting element package may have a uniform and high luminance near the optical axis even away from the optical axis. As such, when the light emitting element package is used as a flash for a mobile phone, a camera, etc., light having a high and uniform luminance may be effectively projected onto a whole area to be photographed. That is, the above-described optical lenses are for a flash and may be combined with the light emitting element package to effectively project light having a uniform intensity onto an illuminated area.

FIG. 16 is a partial schematic perspective view of a light emitting element according to yet another embodiment of the present invention. Hereinafter, an adhesive layer 60 will be described with reference to FIGS. 12, 13, and 16. The adhesive layer 60 may be provided at least part of a region between the molded material 30 and the reflection structure 40 to fix the reflection structure 40 onto the molded material 30.

The adhesive layer 60 may be provided between the supporting portion 33 of the molded material 30 and the reflection structure 40 as illustrated in FIG. 12. That is, it would be preferable that an exposed portion of the adhesive layer 60 is minimized and, due to a low reflectivity of light, the adhesive layer 60 may not be exposed between the radiation surface 45 of the reflection structure 40 and the opening 30a of the molded material 30. Accordingly, as illustrated in FIGS. 12 and 13, the adhesive layer 60 may be provided between the supporting portion 33 and the reflection structure 40, and may not be provided between the reflection structure 40 and part of the molded material 30 that is adjacent to the opening 30a. *Therefore, the adhesive layer 60 is not exposed to the opening 40a (refer to FIG. 1) of the reflection structure 40 and the opening 30a of the molded material 30.*

Referring to FIG. 12, the thickness of the adhesive layer 60 may vary according to locations, to maximize adhesive force while minimizing the amount of the adhesive layer. Particularly, a first thickness [51] 61 in an area adjacent to the light emitting element 20 may be greater than a second thickness [52] 62 in an area away from the light emitting element 20. Here, the thickness of the adhesive layer 60 may be gradually reduced away from the light emitting element 20.

Generally, heat is generated from the light emitting element 20 in the light emitting element package and areas adjacent to the light emitting element 20 is greatly influenced by heat generated from the light emitting element 20. Accordingly, the adhesive layer 60 may have a sufficiently large thickness in areas adjacent to the light emitting element

15

20, thereby ensuring a strong adhesion between the molded material 30 and the reflection structure 40, and have a reduced thickness in areas away from the light emitting element 20, thereby reducing the amount of material used to manufacture the light emitting element package and manufacturing costs.

Meanwhile, according to another embodiment of the present invention, a light emitting element package may include a lead frame, a light emitting element 20, a molded material 30, a reflection structure 40, and an adhesive layer 60. The light emitting element package according to this embodiment is the same as or similar to the light emitting element package according to the preceding embodiments. Thus, repeated description thereof will be omitted.

The molded material 30 may be combined with the lead frame and have the opening 30a for emitting light generated by the light emitting element 20. That is, unlike the molded material 30 according to the preceding embodiments, the molded material 30 according to this embodiment may not include the supporting portion 33.

The reflection structure 40 may have an opening that corresponds to the opening 30a of the molded material 30, and contact the molded material 30. The reflection to structure 40 according to this embodiment is the same as or similar to the reflection structure 40 according to the preceding embodiments, but may optionally have a shape that corresponds to the supporting portion 33.

The adhesive layer 60 may be provided at least partly between the molded material 30 and the reflection structure 40 to fix the reflection structure 40 onto the molded material 30. The first thickness [51] 61 of the adhesive layer 60 in areas adjacent to the light emitting element 20 may be greater than the second thickness [52] 62 of the adhesive layer 60 in areas away from the light emitting element 20. The adhesive layer 60 according to this embodiment is the same as or similar to the adhesive layer 60 according to the preceding embodiments, and thus a detailed description thereof will be omitted. The adhesive layer 60 is used to maintain adhesive force.

FIG. 17 is a schematic side elevation view of a backlight unit according to an embodiment of the present invention.

As illustrated in FIG. 17, the backlight unit according to this embodiment includes a frame 110, a reflective sheet 115 on part of the frame 110, a light guide plate 120 on the reflective sheet 115, and a light emitting element package 100 on other part of the frame 110 and configured to illuminate the light guide plate 120. The light emitting element package 100 may be any one of the light emitting element packages according to the preceding embodiments and modifications thereof. The light emitting element package 100 may be connected to a printed circuit board 112.

According to his embodiment, since the light emitting element package 100 included in the backlight unit has improved heat radiation function and forward direction luminance, the whole backlight unit may have improved heat radiation function and improved luminance of emitted light.

Although the light emitting element package 100 is illustrated to be provided on a side surface of the light guide plate 120 in FIG. 17, the present invention is not limited thereto and but applicable to a direct-type backlight unit in which a light guide plate is provided on or above a reflective sheet and a light emitting element package is provided under or below the light guide plate.

While the present invention has been described with reference to embodiments illustrated in the drawings, it will be understood by those of ordinary skill in the art that

16

various changes in form and details may be made without departing from the spirit and scope of the present invention as set forth in the following claims.

INDUSTRIAL APPLICABILITY

The present invention may be used to manufacture a light emitting element package having excellent heat radiation performance and high luminance, and a backlight unit including the same.

The invention claimed is:

1. A light emitting element package, comprising:
 - a lead frame;
 - a light emitting element on the lead frame;
 - a molded material combined with the lead frame and having an opening for emitting light generated by the light emitting element;
 - a reflection structure having an opening that corresponds to the opening of the molded material and contacting the molded material; and
 - an adhesive layer provided in at least part of a region between the molded material and the reflection structure to fix the reflection structure onto the molded material, wherein the adhesive layer has a first thickness in an area adjacent to the light emitting element and a second thickness in an area away from the light emitting element, and wherein the first thickness is greater than the second thickness.
2. The light emitting element package according to claim 1, wherein the reflection structure comprises:
 - a supporting portion contacting the molded material and provided continuously or discretely along a circumference of the opening of the molded material; and
 - a radial portion contacting the supporting portion and extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.
3. The light emitting element package according to claim 1, wherein the molded material comprises a supporting portion provided continuously or discretely along a circumference of the opening of the molded material, and wherein the reflection structure comprises a radial portion contacting the supporting portion and having a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.
4. The light emitting element package according to claim 1, wherein the molded material comprises a supporting portion provided continuously or discretely along a circumference of the opening of the molded material, and wherein the reflection structure has a shape that corresponds to the supporting portion of the molded material, and contacts the molded material.
5. The light emitting element package according to claim 1, wherein recesses or concave and convex portions are provided on the molded material, and wherein the reflection structure is fitted into the recesses or concave and convex portions.
6. The light emitting element package according to claim 1, wherein the thickness of the adhesive layer is gradually reduced away from the light emitting element.
7. A light emitting element package, comprising:
 - a lead frame;
 - a light emitting element on the lead frame;

17

- a molded material combined with the lead frame and having an opening for emitting light generated by the light emitting element; and
 a reflection structure having an opening that corresponds to the opening of the molded material and contacting the molded material,
 wherein the reflection structure comprises a radial surface formed in a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits, and wherein the radial surface of the reflection structure forms a first angle with a main emission direction of light generated by the light emitting element, from a point where the radial surface contacts the molded material to a first point away from the molded material, and forms a second angle with the main emission direction from the first point to a second point further away from the molded material compared to the first point, wherein the second angle is greater than the first angle.
8. The light emitting element package according to claim 7, further comprising a first resin layer that includes a fluorescent material and is provided in the opening of the molded material to cover the light emitting element.
9. The light emitting element package according to claim 8, further comprising a light-transmitting second resin layer that covers the first resin layer and contacts the radial surface.
10. The light emitting element package according to claim 7, further comprising:
 a light-transmitting second resin layer provided in the opening of the molded material to cover the light emitting element; and
 a first resin layer that includes a fluorescent material, covers the second resin layer, and contacts the radial surface.
11. The light emitting element package according to claim 1, wherein the reflection structure comprises metal.

18

12. The light emitting element package according to claim 1, wherein a surface of the supporting portion facing the opening of the molded material has a radial shape extending radially relative to a direction along which light generated by the light emitting element emits.
13. The light emitting element package according to claim 1, wherein part of the reflection structure is inserted into the opening of the molded material, and
 Wherein the other part of the reflection structure, protruding from the opening of the molded material has a radial shape extending radially from the molded material relative to a direction along which light generated by the light emitting element emits.
14. A light emitting element package, comprising:
 a lead frame;
 a light emitting element on the lead frame;
 a molded material combined with the lead frame and having an opening for emitting light generated by the light emitting element;
 a reflection structure having an opening that corresponds to the opening of the molded material, and contacting the molded material;
 a supporting portion provided discretely or continuously on the molded material to fix the reflection structure onto the molded material; and
 an adhesive layer provided in at least part of a region between the molded material and the reflection structure, and having a first thickness in an area adjacent to the light emitting element and a second thickness in an area away from the light emitting element, wherein the first thickness is greater than the second thickness.
15. A backlight unit, comprising:
 a reflective sheet;
 a light guide plate on or above the reflective sheet; and
 a light emitting element package according to claim 1, configured to illuminate the light guide plate.

* * * * *