



US00RE47468E

(19) **United States**
(12) **Reissued Patent**
Fischer et al.

(10) **Patent Number:** **US RE47,468 E**
(45) **Date of Reissued Patent:** ***Jul. 2, 2019**

(54) **TOOTHBRUSH AND PROCESS FOR PRODUCING SUCH A TOOTHBRUSH**

(71) Applicant: **TRISA HOLDING AG**, Triengen (CH)

(72) Inventors: **Franz Fischer**, Triengen (CH); **Reto Strahler**, Adligenswil (CH)

(73) Assignee: **TRISA HOLDING AG**, Triengen (CH)

(*) Notice: This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/460,888**

(22) Filed: **Aug. 15, 2014**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,174,596**
Issued: **Feb. 13, 2007**
Appl. No.: **10/362,590**
PCT Filed: **Dec. 20, 2002**
PCT No.: **PCT/CH02/00717**
§ 371 (c)(1),
(2) Date: **Mar. 17, 2003**
PCT Pub. No.: **WO03/055351**
PCT Pub. Date: **Jul. 10, 2003**

U.S. Applications:

(60) Continuation of application No. 13/815,924, filed on Mar. 18, 2013, now Pat. No. Re. 45,141, which is an
(Continued)

(30) **Foreign Application Priority Data**

Dec. 28, 2001 (DE) 101 64 336

(51) **Int. Cl.**
A46B 7/06 (2006.01)
A46B 9/04 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A46B 9/06** (2013.01); **A46B 3/06** (2013.01); **A46B 7/04** (2013.01); **A46B 15/00** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **A46B 2200/1066**; **A46B 9/04**; **A46B 9/06**; **A46B 15/0081**; **A46B 15/0032**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,022,920 A 4/1912 Anderson
1,125,532 A * 1/1915 Himmel A46B 9/04
15/110

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2003252861 A1 4/2005
CH 169312 8/1934

(Continued)

OTHER PUBLICATIONS

Jul. 25, 2012 Office Action issued in U.S. Appl. No. 13/317,652.

(Continued)



Primary Examiner — Catherine S Williams

(74) *Attorney, Agent, or Firm* — Oliff PLC

(57) **ABSTRACT**

The invention relates to a toothbrush having a handle and a head part, on which bristle filaments and at least one flexible cleaning element are arranged. According to the invention, the at least one flexible cleaning element is arranged on a carrier element which consists of a hard material and is connected to the head part. The invention also relates to a process for producing such a toothbrush.

33 Claims, 12 Drawing Sheets



Related U.S. Application Data

application for the reissue of Pat. No. 7,174,596, and a division of application No. 13/317,652, filed on Oct. 25, 2011, now Pat. No. Re. 44,346, and a division of application No. 12/379,186, filed on Feb. 13, 2009, now Pat. No. Re. 42,985.

(51) **Int. Cl.**

A46D 3/00 (2006.01)
A46B 9/06 (2006.01)
A46B 7/04 (2006.01)
A46B 15/00 (2006.01)
A46D 1/00 (2006.01)
A61C 17/34 (2006.01)
A46B 3/06 (2006.01)
B29L 31/42 (2006.01)

(52) **U.S. Cl.**

CPC *A46B 15/0002* (2013.01); *A46B 15/0032* (2013.01); *A46D 1/00* (2013.01); *A61C 17/349* (2013.01); *A61C 17/3436* (2013.01); *A46B 9/04* (2013.01); *A46B 2200/1026* (2013.01); *A46B 2200/1066* (2013.01); *B29L 2031/425* (2013.01)

(58) **Field of Classification Search**

CPC *A46B 5/0029*; *A46B 3/06*; *A46B 15/0055*; *A46B 9/026*; *A46B 9/025*; *A46B 9/005*; *A61C 17/222*
 USPC 300/21; 15/101, 201, 187-188, 167.1, 15/167.2, 191.1, 192, 193, 207.2; 601/139, 141
 See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

1,142,698 A * 6/1915 Grove et al. A46B 9/005
 119/612
 1,191,556 A * 7/1916 Blake A46B 9/005
 15/117
 1,268,544 A * 6/1918 Cates A46B 15/0002
 15/110
 1,537,726 A 5/1925 Alma
 1,588,785 A 6/1926 Van Sant
 1,598,224 A 8/1926 Van Sant
 1,612,035 A 12/1926 Lorenzo
 1,796,893 A * 3/1931 McVeigh 15/105
 1,908,510 A 5/1933 Dodson
 1,993,763 A 3/1935 Touchstone
 2,042,239 A 5/1936 Planding
 2,129,082 A 9/1938 Byrer A46B 15/00
 15/110
 2,139,245 A 12/1938 Ogden
 2,164,219 A * 6/1939 McGerry 601/141
 2,172,624 A 9/1939 Robert
 2,263,802 A 11/1941 Grusin
 2,266,195 A * 12/1941 Hallock 15/167.1
 2,279,355 A 4/1942 Wilensky
 2,298,156 A 10/1942 Person
 2,476,201 A 7/1949 Ligoure
 2,486,847 A 11/1949 Hokett
 2,488,873 A 11/1949 Maynard
 2,604,649 A 7/1952 Stephenson et al.
 2,614,556 A 10/1952 Staunt
 2,637,870 A 5/1953 Cohen
 2,706,825 A 4/1955 Blakeman
 2,882,544 A 4/1959 Hadidian
 2,935,755 A 5/1960 Leira et al.
 3,082,457 A 3/1963 Lucibello et al.
 3,103,027 A * 9/1963 Birch A46B 15/00
 15/110

3,110,918 A 11/1963 Tate, Jr.
 3,129,449 A 4/1964 Cyzer
 3,177,509 A 4/1965 Cyzer
 3,188,673 A 6/1965 Newman
 3,229,318 A 1/1966 Clemens
 3,230,562 A * 1/1966 Birch A46B 15/00
 15/110
 3,316,576 A 5/1967 Urbush
 3,398,421 A 8/1968 Rashbaum
 3,553,759 A 1/1971 Sober et al.
 4,114,222 A 9/1978 Serediuk
 4,211,217 A 7/1980 Gueret
 4,240,452 A 12/1980 Jean
 4,291,431 A 9/1981 Lewis, Jr.
 4,302,863 A 12/1981 Droeser
 4,429,434 A 2/1984 Sung-shan
 4,543,679 A 10/1985 Rosofsky et al.
 4,545,087 A 10/1985 Nahum
 D282,318 S * 1/1986 Herzfeld D4/104
 4,633,542 A 1/1987 Taravel A46B 7/06
 15/167.1
 4,654,922 A 4/1987 Chen
 4,694,844 A 9/1987 Berl et al.
 4,751,761 A 6/1988 Breitschmid
 4,766,054 A 8/1988 Hirose et al.
 4,776,054 A 10/1988 Rauch
 4,783,874 A 11/1988 Perches et al.
 4,890,349 A 1/1990 Nitzsche
 4,972,542 A 11/1990 Moshos et al.
 4,979,782 A 12/1990 Weihrauch
 5,033,797 A 7/1991 Rueb
 5,120,225 A 6/1992 Amit
 5,159,736 A 11/1992 Newell
 5,184,368 A 2/1993 Holland
 5,186,627 A 2/1993 Amit et al.
 5,228,166 A 7/1993 Gomez
 5,269,038 A 12/1993 Bradley
 5,283,921 A 2/1994 Ng
 5,305,489 A 4/1994 Lage
 5,325,560 A 7/1994 Pavone et al.
 5,357,644 A 10/1994 Theriault
 5,372,501 A 12/1994 Shalvi
 5,398,366 A 3/1995 Bradley
 5,435,032 A 7/1995 McDougall
 5,454,626 A 10/1995 Schiffer et al.
 5,474,366 A * 12/1995 Strutt A46D 3/005
 300/21
 5,483,722 A 1/1996 Scheier et al.
 5,500,975 A 3/1996 Sano
 5,524,312 A 6/1996 Tan et al.
 5,528,786 A 6/1996 Porat et al.
 5,535,474 A 7/1996 Salazar
 5,604,951 A 2/1997 Shipp
 5,628,082 A 5/1997 Moskovich A46B 5/02
 15/110
 5,651,158 A 7/1997 Halm
 5,689,850 A 11/1997 Shekalim
 5,715,011 A * 2/1998 Bramwell H04N 7/0355
 348/465
 5,728,408 A 3/1998 Boucherie
 5,799,353 A 9/1998 Oishi et al.
 5,799,354 A 9/1998 Amir
 5,802,656 A 9/1998 Dawson et al.
 D399,349 S * 10/1998 Barth D4/106
 5,839,148 A 11/1998 Volpenhein
 5,864,915 A 2/1999 Ra
 5,875,510 A 3/1999 Lamond et al.
 5,896,614 A 4/1999 Flewitt A46B 9/005
 15/167.1
 5,926,897 A 7/1999 Volpenhein
 5,930,860 A * 8/1999 Shipp 15/110
 5,946,758 A 9/1999 Hohlbein et al.
 5,964,508 A 10/1999 Maurer
 5,987,688 A * 11/1999 Roberts A46B 3/16
 15/110
 5,991,959 A 11/1999 Raven et al.
 6,044,514 A 4/2000 Kaneda et al.
 D425,306 S 5/2000 Beals et al.
 6,115,870 A 9/2000 Solanki et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,138,316 A 10/2000 Weihrauch
 6,151,745 A 11/2000 Roberts et al.
 6,161,245 A 12/2000 Weihrauch
 6,178,582 B1 1/2001 Halm
 6,219,874 B1 4/2001 van Gelder et al.
 6,290,302 B1 9/2001 Boucherie
 6,290,303 B1 9/2001 Boucherie
 6,311,358 B1* 11/2001 Soetewey A46B 9/06
 15/110
 6,314,606 B1 11/2001 Hohlbein
 6,389,634 B1* 5/2002 Devlin et al. 15/110
 6,523,907 B1 2/2003 Buckner et al.
 6,546,586 B2 4/2003 Cho
 6,553,604 B1* 4/2003 Braun et al. 15/167.1
 6,564,416 B1 5/2003 Claire et al.
 D477,465 S 7/2003 Reilly et al.
 6,681,777 B2 1/2004 Gueret
 6,702,394 B2 3/2004 Boucherie
 6,704,965 B2 3/2004 Ale et al.
 6,764,142 B2 7/2004 Kwon
 6,779,851 B2 8/2004 Bouchiere
 6,826,797 B1* 12/2004 Chenvainu et al. 15/110
 6,886,207 B1 5/2005 Solanki
 6,993,804 B1 2/2006 Braun et al.
 6,996,870 B2 2/2006 Hohlbein
 7,354,112 B2 4/2008 Fischer et al.
 7,418,759 B2 9/2008 Huber et al.
 7,419,225 B2 9/2008 Fischer et al.
 7,503,093 B2 3/2009 Weihrauch
 7,841,041 B2 11/2010 Moskovich et al.
 8,561,247 B2 10/2013 Moskovich et al.
 9,655,435 B2 5/2017 Kraemer et al.
 2001/0024060 A1 9/2001 Boucherie
 2001/0029639 A1 10/2001 Seifert
 2001/0050507 A1 12/2001 Boucherie
 2002/0004964 A1 1/2002 Luchino et al.
 2002/0116778 A1 8/2002 Kwon
 2002/0162183 A1 11/2002 Cho
 2003/0132661 A1 7/2003 Sato et al.
 2004/0070258 A1 4/2004 Kwon
 2004/0074034 A1 4/2004 Russell
 2004/0083569 A1 5/2004 Kweon et al.
 2004/0117934 A1 6/2004 Pfenniger et al.
 2004/0164604 A1 8/2004 Boucherie
 2005/0066464 A1 3/2005 McKay
 2005/0116528 A1 6/2005 Boucherie
 2006/0096053 A1 5/2006 Fischer et al.
 2006/0107478 A1 5/2006 Boucherie
 2007/0170772 A1 7/2007 Kwon et al.
 2008/0148502 A1 6/2008 Fischer et al.
 2008/0224529 A1 9/2008 Kwon et al.
 2008/0238182 A1 10/2008 Fischer et al.
 2008/0271276 A1 11/2008 Garberg et al.
 2009/0013489 A1 1/2009 Binet et al.
 2010/0223745 A1 9/2010 Kraemer et al.
 2010/0223746 A1 9/2010 Mueller
 2011/0138560 A1 6/2011 Vitt et al.

FOREIGN PATENT DOCUMENTS

DE 558 852 9/1932
 DE 1 210 409 9/1961
 DE 1 883 020 11/1963
 DE 1 210 409 2/1966
 DE 1273482 B 7/1968
 DE GM 75 33 143 2/1976
 DE G 82 15 266.7 U1 9/1982
 DE 35 29 953 A1 3/1987
 DE 37 44 630 A1 7/1989
 DE 39 28919 A1 3/1991
 DE 39 28919 A1 7/1991
 DE 4027288 A1 3/1992
 DE 4029610 A1 3/1992
 DE G 94 00 231.2 U1 5/1994

DE 198 17 704 A1 10/1994
 DE 4330171 A1 3/1995
 DE 19542393 A1 5/1997
 DE 196 04 533 A1 8/1997
 DE 19857032 A1 7/1999
 DE 198 18 553 C1 8/1999
 DE 198 17 704 A1 10/1999
 DE 1 983 2436 A1 1/2000
 DE 100 47 699 A1 4/2001
 DE 200 06 311 U1 9/2001
 DE 100 28 530 A1 12/2001
 DE 202004018612 U1 3/2005
 DE 102006026712 A1 12/2007
 EP 0 169 312 A1 1/1986
 EP 0 189 816 A2 8/1986
 EP 0 322 562 A1 7/1989
 EP 0346646 A2 12/1989
 EP 0 405 204 A2 6/1990
 EP 0 405 204 A2 1/1991
 EP 0 471 312 A2 8/1991
 EP 0 471 312 A2 2/1992
 EP 0472857 A1 3/1992
 EP 0 567 672 A1 4/1992
 EP 0 519 677 A1 12/1992
 EP 0 567 672 A1 11/1993
 EP 0 704 179 A1 4/1996
 EP 0 716 821 A1 6/1996
 EP 0 783 850 A2 7/1997
 EP 0 972 464 A1 1/2000
 EP 0 972 465 A1 1/2000
 EP 1234525 A2 8/2002
 EP 1 425 989 A1 6/2004
 EP 1 449 458 A1 8/2004
 EP 1864588 A2 12/2007
 EP 1 894 489 A2 3/2008
 GB 438091 11/1935
 GB 1 537 526 12/1978
 JP A 5-76416 3/1993
 JP A-05-076416 3/1993
 JP A 6-327517 11/1994
 JP H08-214947 A 8/1996
 JP 2000-000118 A 1/2000
 JP 2000342334 A 12/2000
 JP 2001-218623 A 8/2001
 JP A 2002-10832 1/2002
 JP 2002-136341 A 5/2002
 JP 2002-345554 A 12/2002
 JP 2006167027 A 6/2006
 JP 2008-194497 A 8/2008
 KR 10-0403967 B1 6/2002
 SU 1752336 A1 6/1992
 SU 1752336 A1 8/1992
 WO WO 94/22346 10/1994
 WO WO 94/22346 A1 10/1994
 WO WO 96/20654 A1 7/1996
 WO WO 97/14330 4/1997
 WO WO 97/14330 A1 4/1997
 WO WO 98/01055 A1 1/1998
 WO WO 98/43514 10/1998
 WO WO 98/43514 A1 10/1998
 WO WO 99/37181 7/1999
 WO WO 9937181 A1* 7/1999 A46B 9/06
 WO WO 00/21406 A1 4/2000
 WO WO 00/30495 A1 6/2000
 WO WO 00/47083 A1 8/2000
 WO WO 00/53054 A1 9/2000
 WO WO 00/60980 10/2000
 WO WO 00/60980 A2 10/2000
 WO WO 00/64307* 11/2000
 WO WO 00/64307 A1 11/2000
 WO WO 0064307 A1* 11/2000 A46B 9/06
 WO WO 00/74522 A1 12/2000
 WO WO 00/76369* 12/2000
 WO WO 00/76369 A2 12/2000
 WO WO 01/21036 3/2001
 WO WO 01/21036 A1 3/2001
 WO WO 0076369 A3* 6/2001 A46B 9/06
 WO WO 01/87101 A2 11/2001
 WO WO 02/05679 A1 1/2002

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 02/11583	A2	2/2002
WO	WO 02/38004	A1	5/2002
WO	WO 03/043459		5/2003
WO	WO 03/043459	A2	5/2003
WO	2004/037038	A1	5/2004
WO	2004093718	A1	11/2004
WO	2007016802	A1	2/2007
WO	2007043848	A1	4/2007
WO	2009/000903	A1	12/2008

OTHER PUBLICATIONS

Mar. 9, 2012 Office Action issued in U.S. Appl. No. 13/317,652. Boucherie AFT Anchorless Technology Toothbrush, date unknown. Signal Toothbrush, date unknown.

May 27, 2010 Office Action issued in U.S. Appl. No. 12/382,220.

Dec. 13, 2010 Office Action issued in U.S. Appl. No. 12/382,220.

Dec. 5, 2018 Office Action issued in U.S. Appl. No. 14/962,542.

Oct. 16, 2013 Office Action issued in U.S. Appl. No. 13/815,924.

May 20, 2014 Notice of Allowance issued in U.S. Appl. No. 13/815,924.

U.S. Appl. No. 13/317,652, filed Oct. 25, 2011 in the name of Fischer et al.

Mar. 5, 2013 Notice of Allowance issued in U.S. Appl. No. 13/317,652.

U.S. Appl. No. 12/379,186, filed Feb. 13, 2009 in the name of Fischer et al.

Jul. 20, 2011 Notice of Allowance issued in U.S. Appl. No. 12/379,186.

U.S. Appl. No. 11/878,718, filed Jul. 26, 2007 in the name of Huber et al.

May 15, 2008 Office Action issued in U.S. Appl. No. 11/878,718.

Oct. 8, 2008 Notice of Allowance issued in U.S. Appl. No. 11/878,718.

U.S. Appl. No. 11/878,720, filed Jul. 26, 2007 in the name of Huber et al.

Feb. 19, 2008 Office Action issued in U.S. Appl. No. 11/878,718.

Dec. 31, 2008 Office Action issued in U.S. Appl. No. 11/878,718.

Apr. 8, 2009 Notice of Allowance issued in U.S. Appl. No. 11/878,718.

U.S. Appl. No. 12/457,913, filed Jun. 25, 2009 in the name of Huber et al.

Jan. 25, 2010 Office Action issued in U.S. Appl. No. 12/457,913.

Jul. 7, 2010 Office Action issued in U.S. Appl. No. 12/457,913.

Dec. 17, 2010 Office Action issued in U.S. Appl. No. 12/457,913.

May 27, 2011 Notice of Allowance issued in U.S. Appl. No. 12/457,913.

U.S. Appl. No. 13/137,319, filed Aug. 5, 2011 in the name of Huber et al.

Nov. 21, 2011 Office Action issued in U.S. Appl. No. 13/137,319.

Apr. 23, 2012 Office Action issued in U.S. Appl. No. 13/137,319.

Jul. 27, 2012 Notice of Allowance issued in U.S. Appl. No. 13/137,319.

U.S. Appl. No. 10/388,744, filed Mar. 17, 2003 in the name of Pfenniger et al.

Aug. 23, 2004 Office Action issued in U.S. Appl. No. 10/388,744.

Apr. 19, 2005 Office Action issued in U.S. Appl. No. 10/388,744.

Aug. 10, 2005 Notice of Allowance issued in U.S. Appl. No. 10/388,744.

U.S. Appl. No. 11/291,911, filed Dec. 2, 2005 in the name of Pfenniger et al.

Feb. 7, 2006 Office Action issued in U.S. Appl. No. 11/291,911.

Sep. 6, 2006 Notice of Allowance issued in U.S. Appl. No. 11/291,911.

U.S. Appl. No. 11/645,664 filed Dec. 27, 2006 in the name of Pfenniger et al.

Jul. 27, 2007 Office Action issued in U.S. Appl. No. 11/645,664.

Jan. 23, 2008 Office Action issued in U.S. Appl. No. 11/645,664.

Aug. 27, 2008 Office Action issued in U.S. Appl. No. 11/645,664.

Mar. 6, 2009 Notice of Allowance issued in U.S. Appl. No. 11/645,664.

U.S. Appl. No. 12/379,992, filed Mar. 5, 2009 in the name of Pfenniger et al.

Jul. 9, 2009 Office Action issued in U.S. Appl. No. 12/379,992.

Apr. 8, 2010 Notice of Allowance issued in U.S. Appl. No. 12/379,992.

U.S. Appl. No. 12/805,064, filed Jul. 9, 2010 in the name of Pfenniger et al.

Nov. 8, 2010 Office Action issued in U.S. Appl. No. 12/805,064.

Apr. 1, 2011 Notice of Allowance issued in U.S. Appl. No. 12/805,064.

U.S. Appl. No. 13/067,844, filed Jun. 29, 2011 in the name of Pfenniger et al.

Jan. 30, 2012 Office Action issued in U.S. Appl. No. 13/067,844.

Jun. 26, 2012 Office Action issued in U.S. Appl. No. 13/067,844.

Nov. 5, 2012 Office Action issued in U.S. Appl. No. 13/067,844.

Jan. 31, 2013 Notice of Allowance issued in U.S. Appl. No. 13/067,844.

U.S. Appl. No. 13/765,151, filed Feb. 12, 2013 in the name of Pfenniger et al.

U.S. Appl. No. 14/083,896, filed Nov. 19, 2013 in the name of Pfenniger et al.

U.S. Appl. No. 14/962,542, filed Dec. 8, 2015 in the name of Pfenniger et al.

U.S. Appl. No. 12/991,528, filed Dec. 6, 2010 in the name of Loetscher et al.

U.S. Appl. No. 13/952,017, filed Jul. 26, 2013 in the name of Loetscher et al.

Jan. 29, 2013 Office Action issued in U.S. Appl. No. 12/991,528.

Dec. 14, 2012 Office Action issued in U.S. Appl. No. 13/317,652.

Sep. 17, 2010 Office Action issued in Korean Application No. 10-2005-701487.

Aug. 19, 2013 Notice of Allowance issued in U.S. Appl. No. 13/765,151.

Apr. 23, 2013 Office Action issued in U.S. Appl. No. 13/765,151.

Jun. 8, 2015 Office Action issued in U.S. Appl. No. 14/083,896.

Sep. 17, 2015 Notice of Allowance issued in U.S. Appl. No. 14/083,896.

Jun. 25, 2018 Office Action issued in U.S. Appl. No. 14/962,542.

Dec. 1, 2011 International Search Report issued in International Patent Application No. PCT/EP2011/003858.

Feb. 19, 2013 International Preliminary Report on Patentability issued in International Patent Application No. PCT/EP2011/003858.

Jun. 26, 2017 Office Action issued in U.S. Appl. No. 14/715,034.

Nov. 30, 2017 Office Action issued in U.S. Appl. No. 14/715,034.

Aug. 7, 2014 Office Action issued in U.S. Appl. No. 13/816,843.

U.S. Appl. No. 13/816,843, filed Feb. 13, 2013 in the name of Hess et al.

U.S. Appl. No. 14/715,034, filed May 18, 2015 in the name of Hess et al.

Apr. 29, 2014 Office Action issued in U.S. Appl. No. 13/816,843.

Sep. 4, 2017 International Search Report issued in International Patent Application No. PCT/EP2017/058757.

Sep. 4, 2017 Written Opinion of the International Search Authority issued in International Patent Application No. PCT/EP2017/058757.

Feb. 23, 2011 Office Action issued in U.S. Appl. No. 12/379,186.

Aug. 25, 2010 Office Action issued in U.S. Appl. No. 12/379,186.

Jan. 13, 2010 Office Action issued in U.S. Appl. No. 12/379,186.

Mar. 17, 2010 International Search Report issued in Patent Application No. PCT/EP2009/003999.

Dec. 13, 2010 International Preliminary Report on Patentability issued in Patent Application No. PCT/EP2009/003999.

Jul. 2, 2012 Office Action issued in U.S. Appl. No. 12/991,528.

Oct. 2, 2012 Office Action issued in U.S. Appl. No. 12/991,528.

Jun. 5, 2013 Notice of Allowance issued in U.S. Appl. No. 12/991,528.

U.S. Appl. No. 10/362,590, filed Mar. 17, 2003 in the name of Fischer et al.

Jan. 24, 2006 Office Action issued in U.S. Appl. No. 10/362,590.

Jun. 13, 2006 Office Action issued in U.S. Appl. No. 10/362,590.

Oct. 4, 2006 Notice of Allowance issued in U.S. Appl. No. 10/362,590.

U.S. Appl. No. 11/362,069, filed Feb. 27, 2006 in the name of Fischer et al.

Dec. 12, 2006 Office Action issued in U.S. Appl. No. 11/362,069.

Jul. 18, 2007 Office Action issued in U.S. Appl. No. 11/362,069.

(56)

References Cited

OTHER PUBLICATIONS

Dec. 14, 2007 Notice of Allowance issued in U.S. Appl. No. 11/362,069.
U.S. Appl. No. 11/987,506, filed Nov. 30, 2007 in the name of Fischer et al.
May 12, 2008 Office Action issued in U.S. Appl. No. 11/987,506.
Aug. 19, 2008 Notice of Allowance issued in U.S. Appl. No. 11/987,506.
U.S. Appl. No. 11/987,504, filed Nov. 30, 2007 in the name of Fischer et al.
May 14, 2008 Office Action issued in U.S. Appl. No. 11/987,504.
Aug. 21, 2008 Notice of Allowance issued in U.S. Appl. No. 11/987,504.
U.S. Appl. No. 12/068,730, filed Feb. 11, 2008 in the name of Fischer et al.
Jul. 9, 2008 Office Action issued in U.S. Appl. No. 12/068,730.
Dec. 12, 2008 Notice of Allowance issued in U.S. Appl. No. 12/068,730.
U.S. Appl. No. 12/382,220, filed Mar. 11, 2009 in the name of Fischer et al.

Apr. 4, 2011 Notice of Allowance issued in U.S. Appl. No. 12/382,220.
U.S. Appl. No. 16/092,707, filed Oct. 10, 2018 in the name of Strähler et al.
U.S. Appl. No. 16/100,914, filed Aug. 10, 2018 in the name of Hess et al.
May 11, 2018 Notice of Allowance issued in U.S. Appl. No. 14/715,034.
Feb. 26, 2015 Notice of Allowance issued in U.S. Appl. No. 13/816,843.
U.S. Appl. No. 13/815,924, filed Mar. 18, 2013 in the name of Fischer et al.
Dec. 30, 2013 Office Action issued in U.S. Appl. No. 13/952,017.
May 2, 2014 Office Action issued in U.S. Appl. No. 13/952,017.
Jul. 30, 2014 Office Action issued in U.S. Appl. No. 13/952,017.
Nov. 12, 2014 Office Action issued in U.S. Appl. No. 13/952,017.
Mar. 23, 2015 Office Action issued in U.S. Appl. No. 13/952,017.
Jun. 22, 2015 Notice of Allowance issued in U.S. Appl. No. 13/952,017.
Oct. 23, 2018 International Preliminary Report of Patentability issued in International Patent Application No. PCT/EP2017/058757.

* cited by examiner




Fig. 1a




Fig. 1b




Fig. 1c




Fig. 1d




Fig. 2a




Fig. 2b




Fig. 2c




Fig. 2d




Fig. 2e




Fig. 3a




Fig. 3b




Fig. 3d








Fig. 3e






Fig. 5a




Fig. 5b




Fig. 5c




Fig. 5d




Fig. 5e





Fig. 6c

Fig. 6b

Fig. 6d




Fig. 6e








Fig. 6f






Fig.7e




Fig. 8a




Fig. 8b

Fig. 8c




Fig. 8d




Fig. 8e




Fig. 9a




Fig. 9b




Fig. 9c




Fig. 9d




Fig. 9e




Fig. 9f




Fig. 10a Amended




Fig. 10d




Fig. 10b




Fig. 10e




Fig. 10c Amended

Amended




Fig. 10f




Fig. 10h Amended




Fig. 10g




Fig. 10j




Fig. 10i




Fig. 11a




Fig. 11c

**TOOTHBRUSH AND PROCESS FOR
PRODUCING SUCH A TOOTHBRUSH**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

This application is a Reissue Continuation Application of Reissue application Ser. No. 13/815,924, filed Mar. 18, 2013 (now U.S. Pat. No. RE 45,141, issued Sep. 23, 2014), which is a Reissue Divisional of Reissue application Ser. No. 13/317,652, filed Oct. 25, 2011 (now U.S. Pat. No. RE 44,346, issued Jul. 9, 2013), which is a Reissue Divisional of Reissue application Ser. No. 12/379,186, filed Feb. 13, 2009 (now U.S. Pat. No. RE 42,985, issued Dec. 6, 2011), which is a Broadening Reissue of U.S. Pat. No. 7,174,596, issued on Feb. 13, 2007.

The invention relates to a toothbrush and for a process which is intended for producing the same.

Toothbrushes with a conventional bristle arrangement comprising clusters of bristle filaments, e.g. made of a polyamide (PA) or polyester (PBT), and an additional flexible structure are known, for example, from WO 00/64307 and WO 01/21036. The conventional bristles here serve for customary teeth-cleaning purposes, while the flexible structure can perform different functions, e.g. massaging the gums, damping the cleaning movement, removing plaque, polishing the tooth surface, suspending the bristles in an elastic manner and/or sealing non-welded locations. WO 00/64307 discloses a toothbrush with rod-like flexible cleaning elements which are of approximately the same length as the conventional clusters of bristles and are arranged on the periphery of the head part of the toothbrush. In the case of WO 01/21036, elastic cleaning elements are of sheet-like, e.g. undulating, configuration and are arranged within the conventional bristle arrangement. In the case of WO 00/64307, a plurality of the flexible cleaning elements are connected to one another via a material bridge made of the same material. Following the operation of covering the head part of the toothbrush with conventional bristles, the cleaning elements are produced by virtue of the head part being encapsulated by injection molded. The disadvantage here is that the bristle filaments have to be prepared for use, e.g. by virtue of the clusters of bristles being rounded or a predetermined profiling being produced, before the flexible structure is produced. Renewed insertion into the injection mold is then necessary in order to produce the flexible structure. It is possible here for the clusters of bristles to be damaged or contaminated. The elastic-structure shapes which it is possible to produce are limited, inter alia, for demolding reasons.

The object of the invention is to provide a toothbrush, with conventional bristles and a flexible structure, which is straightforward to produce. The intention is also to specify a corresponding production process.

According to the invention, in the case of a toothbrush of the type mentioned in the introduction, at least one flexible structure, e.g. a cleaning element, is arranged on a carrier element which consists of a hard material. This carrier element is connected to the head part. Such a toothbrush has production-related advantages since the additional part, i.e.

the carrier element provided with the flexible structure, can be produced separately and straightforwardly connected to the head part.

The connection between the carrier element and the head part may be produced mechanically by clamping or snap-fitting or riveting, chemically by adhesive bonding, by ultrasonic welding, or thermally by welding or other methods of supplying heat. It is preferred, in terms of production, for the carrier element to consist of the same material as the head part since, in this case, only one hard component need be provided for producing the brush and there is no need to ensure material compatibility. This is advantageous, in particular, for ultrasonic welding.

The arrangement of the flexible structure on a carrier element consisting of a hard material has the following advantages: the additional part may be produced, and prepared for use, separately from the rest of the toothbrush body, comprising the handle and head part, in a straightforward further step, the carrier element is connected to the head part, it being possible to use any of the abovementioned connecting methods and the hard carrier element preferably being formed in adaptation to said head part. The carrier element may be formed, for example, such that, during the later connecting step, it engages around the head part in a clamping manner. On account of the hard carrier element, the additional part is easy to handle and can be gripped considerably more easily than an additional part produced entirely from a flexible material.

The additional part is small in comparison with the rest of the toothbrush. The necessary molds are thus also small and cost-effective. The basic toothbrush body and the bristle covering may be produced using a standard mold even if they are later provided with different additional parts. In order to produce toothbrushes with different additional parts, all that is necessary is to exchange the additional part and/or the corresponding mold therefor, which can be done in a straightforward and cost-effective manner.

A further advantage of producing the additional part and basic body separately is that it is possible to realize any desired shapes of flexible cleaning elements, e.g. even those which cross over the conventional bristles, come into contact therewith or displace the same when the additional part is inserted. The separate production does not pose any problems for the demolding of the flexible structure. It is possible to produce geometries by injection molding which would be extremely difficult to demold if the cleaning element were fitted directly on the bristle-covered head part.

Up until now, the flexible structure, for production-related reasons, has been produced from the same material as any flexible components on the handle part. The invention provides a greater degree of freedom for the material of the structure, with the result that it is possible to use, for example, a different degree of hardness.

A non-releasable connection between the additional part and the head part prevents the additional part from detaching during use and eliminates the risk of swallowing.

The conventional bristles are fastened, for example, directly on the head part, on a bristle plate acting as a further carrier element, or also on the carrier element for the flexible cleaning elements, all variants having advantages. During the operation of fastening the bristles on the head part or on the bristle plate, the flexible structure and the conventional bristles may be prepared independently of one another for later use before the head part and additional part are assembled, with the result that they do not damage or contaminate one another.

Fitting both conventional bristles and the flexible structure on the carrier element has the advantage that any desired spatial arrangement of the two components is possible. A carrier element which is prepared in this way may be connected to different basic toothbrush bodies for finishing purposes, with the result that it is possible to realize a large number of different toothbrushes with only a small number of basic bodies.

The conventional bristles, in both cases, may be prepared for use before or after the flexible structure is fitted. If the two components are provided on the carrier element, it is preferable first of all for the flexible structure, including any cleaning elements, to be integrally formed and then for the carrier element to be covered with bristles, which may be guided, for example, through cutouts in the soft or hard component.

Producing the additional part, i.e. the carrier element with one or more flexible cleaning elements, preferably takes place by two-component or multi-component injection molding. In this case, a non-releasable connection is preferably produced between the components.

The flexible structure is preferably also arranged, e.g. molded, laterally on the carrier element, in which case, in the assembled state, it terminates laterally with the outer contour of the head part or projects beyond the same. It serves, for example, for sealing non-welded locations, for massaging the gums, e.g. by way of molded-on elastic elements which project slightly, or as impact protection during cleaning.

The flexible cleaning element preferably consists of an, in particular, thermoplastic elastomer, e.g. of natural or synthetic rubber. The material used for the basic toothbrush body is preferably used for the carrier element, in particular polypropylene, styrene-acrylonitrile, polyester, acrylonitrile-butadiene-styrene (ABS) or Isoplast®, an engineering thermoplastic polyurethane. The Shore A hardness of the soft component is preferably less than 90 and particularly preferably below 50.

The carrier element is particularly preferably covered with bristles by AFT (Anchor Free Tufting) technology. In this case, first of all, the hard-material carrier plate is produced with the flexible structure, in particular by two-component injection molding. Then, the bristle filaments are guided through cutouts in the carrier plate and/or in the flexible structure and, for fastening on the carrier plate and/or the flexible structure, are welded or adhesively bonded by way of their rear ends, which in the application case are directed toward the brush head. This has the advantage that it is possible to realize largely any desired bristle arrangements, in particular even sheet-like bristle structures. The carrier element is connected to the head part, in particular, by means of ultrasonic welding, e.g. as is described in DE 200 06 311 U.

Since elastomeric material, in particular a thermoplastic elastomer, on account of the pronounced damping of the ultrasonic vibrations, can only be welded ultrasonically to a limited extent, the welding surface between the carrier element and head part is preferably kept at least partially free of the flexible component. For this purpose, the injection point of the soft component is preferably selected to be on the bristle-carrying side of the carrier element, in order that no material bridges from the soft component reduce the size of the welding surface. However, for the case where flexible elements are intended to be arranged in the region of the welding surface, they are preferably positioned to the side of the longitudinal axis of the toothbrush. This likewise produces non-welded locations laterally on the carrier element, while it is possible to weld the longitudinally front and rear

regions between the carrier element and head part. This ensures that the carrier element is held well since the front and rear regions, in particular, and, to a lesser extent, the side regions, are subjected to loading by the cleaning movement and the corresponding leverages. Merely punctiform welding with non-welded locations may also be used specifically, in order that the brush head and carrier element can be moved in relation to one another and a certain level of flexibility of the brush head as a whole is thus achieved.

It is also possible for the flexible structure, in the manner of a sealing lip, to serve for the additional sealing of non-welded locations. As a result, the space between the carrier element and the head part is advantageously sealed against the ingress of water. It is thus not possible for any germs to accumulate in this region, and the brush is more hygienic. In order to achieve a reasonable sealing function, the Shore A hardness of the soft component is preferably less than 50.

Examples for the invention are described hereinbelow and illustrated in the drawings, in which, purely schematically:

FIGS. 1a-d show views of a toothbrush according to the invention in various assembly stages, the additional part being fastened on the head part by riveting;

FIGS. 2a-e show views of a further toothbrush of which the additional part is fastened by riveting;

FIGS. 3a-e show views of a toothbrush of which the additional part is fastened by welding;

FIGS. 4a-e show views of a toothbrush of which the additional part is fastened by means of a snap-fitting connection;

FIGS. 5a-e show views of a further toothbrush of which the additional part is fastened by a snap-fitting connection;

FIGS. 6a-f show views of a toothbrush in the case of which the additional part is fastened in a clamping manner;

FIGS. 7a-e show the production of a toothbrush by AFT;

FIGS. 8a-e show views of a further toothbrush of which the additional part is fastened by a snap-fitting connection;

FIGS. 9a-f show views of a further toothbrush, of which the additional part is fastened on the head part with play;

FIGS. 10a-j show the production of a further toothbrush by AFT; and

FIGS. 11a-c show views of a toothbrush with a lateral surround made of flexible material.

All of the toothbrushes illustrated have a basic body with a head part 1 and a handle part 2, which is only partially illustrated. An additional part 4 with a plurality of flexible cleaning elements 6 of different shapes, which are connected to a carrier element of likewise different shapes, is connected to the head part 1 when the toothbrush is in the finished state. The head part 1, furthermore, is provided directly (FIGS. 1-5) or indirectly (FIG. 6) with clusters 3 of conventional bristle filaments. The materials and arrangements of the clusters of bristles 3 may vary. It is only the special features of the individual exemplary embodiments which are discussed hereinbelow, and elements which correspond to one another are provided with the same designations.

FIGS. 1a and c show a toothbrush of which the head part 1 has already been provided with clusters of bristles 3. The additional part 4 illustrated in FIG. 1b has a sectionally U-shaped carrier element 5 made of a hard material, in particular the same plastic which has been used for producing the head part 1 and/or the entire basic body. Flexible cleaning elements 6, in this case in the form of straight rods, are firmly connected to the carrier element 5. The cleaning elements 6 are inclined slightly out of the vertical, toward one another, and enclose an angle of from 5 to 30° with the vertical. In this way, the elastic cleaning elements 6 come

5

into contact with the conventional clusters of bristles 3 (FIG. 1d) and may even cross over (not illustrated) the latter. Using conventional production processes, such a position can only be realized with high-outlay displacement methods.

The carrier element 5 is adapted in shape to a cutout 9, visible in FIG. 1c, in that region of the head part 1 which is directed away from the clusters of bristles 3. Also located in this region are pins 7, which can be plugged through a hole 8 in the carrier element 5. The pins 7 are cold-formed or hot-formed and thus permanently fixed in the hole 8. FIG. 1d shows a plan view of the finished toothbrush.

For reasons of esthetics or hygiene, the bottom region of the hole 8 or of the head part 1 as a whole may be covered by a protective layer 22 made of soft plastic (cf. FIG. 2d). The boundary regions between the carrier element 5 and the head part 1 are likewise preferably covered by soft plastic. An example of the material used for this purpose is the soft material which is also used for the handle region of the toothbrush. The protective layer is preferably molded on during the production of the handle part by multi-component injection molding. It is also possible, however, for the plastic layer to be integrally formed directly on the carrier element.

A further example of a toothbrush of which the additional part 4 is connected to the head part 1 by riveting is illustrated in FIGS. 2a-e. The additional part, in this case, comprises a plate-like carrier element 5 to which sheet-like flexible cleaning elements 6 are connected in the form of a rosette. The carrier element 5 has a pin 7' by means of which the additional part 4 can be plugged through a correspondingly prepared hole 8' in the front end of the head part and can be fixed by virtue of the pin 7' being deformed. The flexible cleaning elements 6 are located in the region of the tip of the head part 1. The bristle arrangement with individual clusters of bristles 3 follows in the direction of the handle part 2. A protective layer 22 covers the region of the hole 8'.

FIGS. 3a-e show a further example of a toothbrush, which ends up similar to a toothbrush according to FIG. 2. The additional part 4 with a plate-like carrier element 5 and rosette-like flexible cleaning elements 6, in this case, is connected to the head part 1 by welding. For this purpose, the front region of the head part has a plate-like cutout into which the carrier element 5 is permanently introduced, by way of a correspondingly structured underside 5a, by means of ultrasonic welding. FIG. 3d shows a side view of the finished toothbrush, and FIG. 3e shows the plan view of the combined bristle arrangement comprising conventional clusters of bristles 3 and flexible cleaning elements 6.

The additional part 4 of the toothbrush illustrated in FIGS. 4a-e is fastened in the center of the head part 1 by means of snap-fitting. The additional part 4 comprises a rectangular carrier element 5 with wing-like flexible cleaning elements 6 arranged at its corners. Two rod-like cleaning elements 6 are also located on the carrier element 5 (FIGS. 4b and c). As is illustrated in FIG. 4a, the head part 1 has a central hole 8", through which a resiliently configured extension 11 on the carrier element 5 is plugged. The additional part 4 and head part 1 are connected to one another by a snap-fitting connection which, on account of the enlarged cross section at the bottom end 11a of the extension 11, cannot readily be released. The bristle arrangement of the conventional clusters of bristles 3 is configured such that the wing-like cleaning elements 6 are positioned between the conventional clusters of bristles 3, as is illustrated in FIGS. 4a and 4e. The additional part 4 is produced separately and then inserted into the head part 1 with the prepared bristle arrangement. It is thus also possible to realize structures of the flexible cleaning elements 6 which engage through the convention

6

bristle arrangement, such as the diagonally arranged wing-like elements from FIGS. 4b-e or the fanned-out pin-like cleaning elements, oriented in different directions in space, from FIG. 8. For reasons of hygiene or esthetics, the underside of the head part 1 is covered by a layer 22 made of flexible material.

FIGS. 5a-e show a further example of a snap-fitting connection between the additional part 4 and the head part 1 of a toothbrush according to the invention. Within the bristle arrangement made of conventional clusters of bristles 3, the head part 1 has a prepared region 13 for accommodating the additional part 4. This region 13 comprises a depression with a groove 12 running on the border of the latter in each case, perpendicularly to the alignment of the handle 2, said groove 12 providing the head part 1 with a certain level of elasticity or resilient action, as do also the grooves 12' running on the lateral border of the head part. The prepared region 13 is slightly smaller than the basic surface area of the carrier element 5, with the result that the latter can be fitted into the region 13 in a clamping manner. As can be seen from the plan view in FIG. 5e, the additional part has both rod-like cleaning elements and sheet-like cleaning elements arranged transversely to the alignment of the handle 2.

FIGS. 6a-f show a further example of a toothbrush according to the invention, in this case a plug-on toothbrush for an electric teeth-cleaning unit. The conventional clusters of bristles 3 are fastened on a separate bristle plate 18 which, in the assembled state, is connected to the matching head part 1 of the toothbrush or a disc 23 which is fastened in a rotatable or pivotable manner thereon. The flexible cleaning elements 6, which are rod-like in this case, are fastened on a carrier element 5 which is slightly curved in plan view and has a sheet-like extension 16, which is oriented essentially perpendicularly to the alignment of the cleaning elements 6. The additional part 4 can be introduced, by way of said extension 16, into a correspondingly shaped groove 14 in the disc 23. Arranged in the center of the head part 1 and of the groove 14 is a round cutout 15, in which a corresponding mating element 17 on the extension 16 of the additional part 4 engages. The additional part 4 and head part 1 are thus connected to one another in a well-fitting and clamping manner. At its bottom end, the bristle plate 18 has a groove 19 by means of which the bristle plate 18 can be fastened on the disc 23 or the lateral extensions 23 thereof. In the embodiment illustrated, the additional part 4 is moved along by the disc 23. As an alternative, it is possible for the additional part 4 to be fastened directly on the head part 1 and not to rotate as well.

FIGS. 7a-e show an example of the production of a toothbrush by means of AFT technology. FIGS. 7a-c show sectional views of the carrier element 5 in various process stages, to be precise before being provided with flexible cleaning elements 6 and conventional clusters of bristles 3 (FIG. 7a), following the application of the flexible material (FIG. 7b) and following the application of the bristles (FIG. 7c). The outer shape of the carrier element 5 is adapted to the dimensions of a prepared region 13 in the form of a shallow cutout in the head part 1 of the toothbrush. The carrier element 5 has prepared regions 20, into which the flexible cleaning elements 6 are fitted, in particular molded. Furthermore, the carrier element 5 has cutouts 24, which are filled wholly or partially with flexible material 6', see also the detail from FIG. 7e. The carrier element 5 also contains holes 21, through which clusters of bristles 3 are plugged and are fastened on the rear side by virtue of their rear ends 3a being incipiently melted. The elastic material regions 6'

have further holes 21' which likewise serve for accommodating clusters of bristles 3, which are fastened in the same way. The material regions 6' can accommodate one or more clusters of bristles 3. The clusters of bristles 3 anchored in the elastic material 6' are thus anchored or suspended in a particularly elastic manner. Further clusters of bristles 3 are fastened directly on the carrier element 5. The carrier element 5 fitted with clusters of bristles and the flexible structure 6, 6' is then inserted into the prepared region 13.

The edge 30 of the carrier element 5, this edge in the application case being directed towards the base of the cutout 13, is tapered, just as in the example from FIGS. 10 and 11. This tapering edge 30 serves, during ultrasonic welding for connection to the head part 1, as an energy concentrator and a material reservoir for material which is to be liquefied.

The AFT technology manages without anchors or clips for fastening the bristle filaments, which instead are welded directly on the carrier plate. This means that the width of a cluster of bristles is not determined by the anchor, with the result that it is also possible to realize finer structures, in particular also sheet-like bristle arrangements.

It is technically also possible, in the case of AFT, to prepare the bristle filaments for use before they are fitted on the carrier plate. The variant which is realized at present, however, is that where the bristles are only machined once they have been fitted on the carrier plate.

FIGS. 8a-e show a variant of the toothbrush from FIG. 4. The bristle arrangement made of conventional clusters of bristles 3 corresponds to FIG. 4. The additional part 4 has a plurality of pin-like cleaning elements 6 which diverge in the form of a star and engage through the conventional clusters of bristles 3 (FIGS. 8d and e). The fastening mechanism corresponds to FIG. 4. A layer 22 made of flexible material covers the underside of the head and handle parts 1, 2.

FIGS. 9a-f show a further example of a toothbrush according to the invention. The head part 1 has a prepared region 13 for the carrier element 5 of the additional part 4, said region being larger than the carrier element 5 itself. The region 13 is, for example, a hole which passes all the way through the head part 1, see sectional drawings from FIGS. 9b, d and e. The region 13 has two lateral grooves 13a, the shape of which is adapted to the shape of two lateral extensions 5b of the carrier element 5. The latter is inserted into the head part 1 and latches there. The play of the carrier element 5 within the region 13, which allows lateral displacement and/or a pivoting movement about the axis defined by the extensions 5b, results in a particular level of elasticity or resilient action of the additional part 4. The rear side of the head part 1, again, may be covered by a layer of soft material.

FIGS. 10a-j show a further example of a toothbrush produced by means of AFT. FIGS. 10a-c correspond to FIGS. 7a-c and each show the carrier plate 5 in various process stages. FIGS. 10d-f show the same carrier plate 5 in section along line I-I indicated in FIG. 10a. The centrally arranged flexible element 6 is sheet-like or sail-like and is undulating in plan view (FIG. 10h). As is illustrated in FIGS. 10e and f, the flexible structure comprises laterally integrally formed regions 6'' which, in the assembled state (FIG. 10h), bound the toothbrush head 1 laterally and terminate more or less flush with the outer contour of the head part. They serve, for example, as impact protection and/or for additionally massaging the gums. The regions 6'' likewise have holes 21' for accommodating clusters of bristles 3, which are thus suspended in an elastic manner and are particularly compliant during cleaning.

The carrier element 5 provided with conventional bristles 3 and the flexible structure 6, 6', 6'' is inserted into a cutout 13 in the brush head 1. The brush head 1 is illustrated in various views without the carrier element 5 in FIGS. 10g and j and with the carrier element 5 inserted in FIGS. 10h and l. On its lateral border, the brush head 1 or the cutout 13 has lateral openings 25, which are adapted to the lateral flexible regions 6'' previously molded on the carrier element 5.

The carrier element 5 is connected to the brush head 1 by means of ultrasonic welding. The welding surface 26 is indicated by dashed lines. In order to realize the welding, the carrier element has, on its bottom border, a welding border 26' which, during assembly, rests on the base of the cutout 13, the contact surface defining the welding surface 26. The welding border 26' melts under the influence of ultrasound, with the result that the two parts 5 and 1 are connected to one another.

Since elastomeric material can only be welded ultrasonically to a limited extent, the welding surface 26, as far as possible, is kept free of this material, for example as in the case of the toothbrush from FIG. 7 or, with only minimal interruptions, as in the case of the toothbrush from FIG. 10. The aim, in both cases, is to seal the cavity 28 between the carrier element 5 and head part 1 to the full extent, in order to prevent the ingress of water and germs. For this purpose, the injection point of the flexible material is preferably selected to be on the bristle-carrying front side of the carrier element 5, in order that no unnecessary material bridges reduce the size of the welding surface 26. If further flexible elements are provided on the head part 1, in particular on the rear side thereof, they are positioned such that they do not reduce the size of the welding surface 26. For example, these elements and the corresponding injection point are located fully within that region on the rear side of the head part 1 (not illustrated) which is defined by the welding surface 26. The entire contact surface between the head part 1 and carrier element 5 is preferably welded over at least 25%, particularly preferably along the periphery of the head (line 26).

In the example from FIG. 10, the flexible regions 6' interrupt the welding surface 26, with the result that non-welded locations 27 are produced there. These are advantageously arranged on the side of the head part 1, while the longitudinally front and rear regions of the carrier element 5 are firmly welded to the head part 1. This ensures that the carrier element 5 is held securely since the front and rear regions are subjected to an extremely high level of loading by the cleaning movement and corresponding leverages.

The non-welded locations 27 are sealed by the flexible regions 6'' here in the manner of a sealing lip, with the result that only a very small amount of water, if any at all, can penetrate into the cavity 28. For a good sealing function, material with a Shore A hardness of 50 or less is preferably selected. Non-welded locations between the head part and carrier element may also be used specifically, in order to achieve a certain level of flexibility between the two hard components.

FIG. 11 shows various views of a further example of a toothbrush produced by AFT, in this case, with two sail-like flexible cleaning elements 6. The carrier element 5 is fully enclosed, around its periphery, by flexible material 6', which, in the assembled state (plan-view illustration FIG. 11a) fully encloses the outer periphery of the head part 1 on the top side and serves as impact protection. In regions 6'', the soft material serves as a mount for lateral clusters of bristles 3 which are guided through the flexible material 6'.

As can be gathered from FIG. 11c, the hard components (carrier element 5 and head part 1) come into contact with one another along a surface 26 beneath the soft component in the region 6' and can be welded here by means of ultrasound. The welding surface 26 is interrupted by the lateral regions 6", although, as has been described above, a sufficient retaining action is achieved. The cavity 28 beneath the carrier element 5 is sealed by the flexible regions 6" and the locations welded along the surface 26.

The method of welding and sealing the components which has been described above with reference to FIGS. 10 and 11 may also advantageously be used for other toothbrushes.

The invention claimed is:

[1. A toothbrush head, comprising:

a bristle-carrying head part;

bristle filaments and a cutout provided through the head part, the cutout including a bottom opening that is of a larger cross-section than an intermediate section of the cutout; and

a flexible, non-bristle cleaning element arranged on a carrier element, the cleaning element being made of a first material and the carrier element being made of a second, harder material, the carrier element including a base and a resiliently configured extension, the base having a cross-section larger than the intermediate section of the cutout, and the extension having an intermediate portion and a bottom with a cross-section that is larger than the intermediate portion of the extension and the intermediate section of the cutout, the bottom of the extension being resiliently inserted through the intermediate section of the cutout and into the bottom opening to prevent ready release of the carrier element from the head part by a snap-fit connection.]

[2. The toothbrush head according to claim 1, wherein the connection is sufficient to prevent detaching of the carrier element from the head part during use of the toothbrush.]

[3. The toothbrush head according to claim 1, wherein the connection is non-releasable.]

[4. The toothbrush head according to claim 1, wherein play between the carrier element and the head part at the cutout allows movement of the carrier element and the flexible cleaning element during use of the toothbrush.]

[5. The toothbrush head according to claim 1, wherein the flexible cleaning element is arranged to massage gums of the user.]

[6. The toothbrush head according to claim 1, wherein the flexible cleaning element is made from a thermoplastic elastomer.]

[7. The toothbrush head according to claim 1, wherein the flexible cleaning element includes rubber.]

[8. The toothbrush head according to claim 1, wherein the flexible cleaning element has a Shore A hardness of less than 90.]

[9. The toothbrush head according to claim 1, wherein the material of the carrier element is a polypropylene, styrene-acrylonitrile, acrylonitrile-butadiene-styrene, polyurethane or polyester.]

[10. The toothbrush head according to claim 1, wherein the flexible cleaning element and the carrier element are produced by two-component or multi-component injection molding and mated with a non-releasable connection.]

[11. The toothbrush head according to claim 1, wherein the flexible cleaning element is inclined out of the vertical to come into contact with at least one of the bristle filaments.]

[12. The toothbrush head according to claim 1, wherein the flexible cleaning element crosses over at least one of the bristle filaments.]

[13. The toothbrush head according to claim 1, wherein the flexible cleaning element has a rod-like shape.]

[14. The toothbrush head according to claim 1, wherein the carrier element is harder than the flexible cleaning element.]

[15. The toothbrush head according to claim 1, wherein the cutout extends entirely through the head part.]

[16. The toothbrush head according to claim 1, wherein the head part includes a plurality of cutouts and a plurality of flexible cleaning elements and carrier elements.]

[17. The toothbrush head according to claim 1, further comprising a handle connected to the head part.]

[18. A toothbrush head, comprising:

a bristle-carrying head part;

bristle filaments and a cutout provided on the head part;

a flexible, non-bristle cleaning element arranged on a carrier element, the carrier element being of a harder material than that of the flexible cleaning element, the carrier element including an extension that extends into the cutout and is connected to the head part by a not readily releasable snap-fit connection of the carrier element within the cutout; and

play between the carrier element and the head part at the cutout allows pivoting movement of the carrier element about an axis.]

[19. The toothbrush head according to claim 18, wherein the axis is substantially perpendicular to the longitudinal axis of the head part.]

[20. The toothbrush head according to claim 18, wherein the connection is sufficient to prevent detaching of the carrier element from the head part during use of the toothbrush.]

[21. The toothbrush head according to claim 18, wherein the flexible cleaning element is made from a thermoplastic elastomer.]

[22. The toothbrush head according to claim 18, wherein the flexible cleaning element includes rubber.]

[23. The toothbrush head according to claim 18, wherein the flexible cleaning element has a Shore A hardness of less than 90.]

[24. The toothbrush head according to claim 18, wherein the harder material of the carrier element is a polypropylene, styrene-acrylonitrile, acrylonitrile-butadiene-styrene, polyurethane or polyester.]

[25. The toothbrush head according to claim 18, wherein the flexible cleaning element is inclined out of the vertical to come into contact with at least one of the bristle filaments.]

[26. The toothbrush head according to claim 18, wherein the flexible cleaning element has a rod-like shape.]

[27. The toothbrush head according to claim 18, wherein the cutout is provided through the head part and includes an end opening that is of a larger cross-section than an intermediate section of the cutout.]

[28. The toothbrush head according to claim 18, further comprising a handle connected to the head part.]

[29. The toothbrush head according to claim 18, wherein the head is also formed from a material that is harder than the flexible, non-bristle containing cleaning element so that a hard material to hard material snap-fit connection is formed.]

[30. The toothbrush head according to claim 18, wherein the carrier extension is a snap-fitting element, and the snap-fitting element and the carrier form a single-piece body of the harder material.]

11

[31. The toothbrush head according to claim 18, wherein the not-readily releasable snap-fit connection is formed by one of the extension and the head part resiliently deforming.]

[32. The toothbrush head according to claim 18, wherein the cleaning element is non-releasably attached to the carrier element through two component or multi-component injection molding.]

[33. The toothbrush head according to claim 18, wherein the head involves a plurality of cutouts and a plurality of snap-fit carrier elements.]

[34. A process for producing a toothbrush head comprising:

providing a head part with a cutout and with bristle filaments, the cutout having a bottom end opening that is of a larger cross-section than an intermediate section of the cutout;

providing a flexible, non-bristle cleaning element coupled to a carrier element, the cleaning element being made of first material and the carrier being made of a second, harder material;

providing the carrier element with a base having a cross-section larger than the intermediate section of the cutout and an extension having an intermediate portion and a resiliently configured bottom with a cross-section that is larger than the intermediate section of the extension and the intermediate section of the cutout; inserting the bottom of the extension through the intermediate section of the cutout and into the bottom end opening; and

connecting the carrier element to the cutout of the head part in a not-readily releasable snap-fit connection.]

[35. The process as claimed in claim 34, wherein the connecting occurs after the toothbrush head is provided with the bristle filaments.]

[36. The process as claimed in claim 34, wherein the bristle filaments provided on the head part are processed prior to connecting the carrier element to the cutout of the head part.]

[37. The process as claimed in claim 34, wherein the processing includes at least one of rounding, cutting and machining processing operations.]

[38. The process as claimed in claim 34, wherein the flexible cleaning element and the carrier element are produced by two-component or multi-component injection molding.]

[39. The process as claimed in claim 34, further comprising:

providing the toothbrush head part with a handle.]

[40. The process according to claim 34, further comprising inserting the carrier element into the cutout from a bristle bearing front face of the head part.]

[41. A process for producing a toothbrush head of a toothbrush comprising:

providing a head part with a cutout and bristle filaments; providing a non-bristle cleaning element of a first material coupled to a carrier element of a second, harder material, the carrier element being formed with an extension;

inserting the extension into the cutout;

connecting the carrier element to the cutout of the head part by a not readily releasable snap-fit connection of the carrier element within the cutout; and

providing play between the carrier element and the head part at the cutout that allows pivoting movement of the carrier element about axis.]

12

[42. The process as claimed in claim 41, wherein the connecting occurs after the toothbrush head is provided with the bristle filaments.]

[43. The process as claimed in claim 42, wherein the bristle filaments provided on the head part are processed prior to connecting the carrier element to the head part.]

[44. The process as claimed in claim 43, wherein the processing includes at least one of rounding, cutting and machining processing operations.]

[45. The process as claimed in claim 41, wherein the flexible cleaning element and the carrier element are produced by a two-component or multi-component injection molding.]

[46. The process as claimed in claim 45, wherein the flexible cleaning element is produced from a thermoplastic elastomer or rubber and the carrier element is produced from a polypropylene, styrene-acrylonitrile, acrylonitrile-butadiene-styrene, polyurethane or polyester.]

[47. The process as claimed in claim 45, wherein the material of the flexible, non-bristle containing cleaning element and the harder material of the carrier are chosen to be compatible with each other to produce a non-releasable connection in the two component or multi-component injection molding process.]

[48. The process according to claim 41, further comprising:

providing the toothbrush head part with a handle.]

[49. The process according to claim 41, further comprising inserting the carrier element into the cutout from a bristle bearing front face of the head part.]

50. *A brush, comprising: a handle and a head part with bristle filaments and at least one flexible, non-bristle containing cleaning element made from flexible material and arranged on the carrier element,*

wherein the rear ends of the bristle filaments are melted and fixedly connected in cutouts of the carrier element, and

the carrier element being of a harder material than that of the flexible cleaning element and not readily releasably connected to the head part such that the rear side of the carrier element faces the head part, the flexible material of the flexible cleaning element forming a material bond with the carrier element, wherein the carrier element is provided with the at least one flexible cleaning element by means of injection molding.

51. *The brush as claimed in claim 50, wherein the at least one cleaning element is molded into at least one prepared cutout of the carrier element.*

52. *The brush as claimed in claim 50, wherein a region of flexible material is arranged laterally to the carrier element, said region terminating laterally with an outer contour of the head part or projecting beyond the same when the carrier element is connected to the head part.*

53. *The brush as claimed in claim 50, wherein a region of flexible material is arranged between clusters of bristle filaments.*

54. *The brush as claimed in claim 50, wherein contacting locations between the head part and the carrier element are covered with flexible material.*

55. *The brush as claimed in claim 50, wherein the head part is provided with further flexible elements.*

56. *The brush as claimed in claim 55, wherein the further flexible elements are located on a longitudinal rear side of the head part.*

57. *The brush as claimed in claim 56, wherein an injection point of the further flexible elements is located on the longitudinal rear side of the head part.*

58. The brush as claimed in claim 50, wherein a non-releasable connection is provided between the carrier element and the head part.

59. The brush as claimed in claim 50, wherein the carrier element is formed of the same material as the head part.

60. The brush as claimed in claim 50, wherein the flexible material includes natural or synthetic rubber.

61. The brush as claimed in claim 50, wherein the flexible material includes a thermoplastic elastomer.

62. The brush as claimed in claim 50, wherein the flexible material has a Shore A hardness of less than 90.

63. The brush as claimed in claim 50, wherein the non-bristle containing cleaning element comprises sheet-like elements.

64. A brush, comprising: a handle and a head part with bristle filaments and at least one flexible, non-bristle containing cleaning element made from flexible material arranged on a carrier element,

wherein the rear ends of the bristle filaments are connected in cutouts of a carrier element and;

the carrier element being of a harder material than that of the flexible cleaning element and not readily releasably connected to the head part such that the rear side of the carrier element faces the head part; and the at least one cleaning element is molded into at least one prepared cutout of a carrier element, the flexible material of the flexible cleaning element forming a material bond with the carrier element.

65. A brush, comprising: a handle and a head part with bristle filaments and at least one flexible, non-bristle containing cleaning element made from flexible material,

wherein the bristle filaments and cleaning element are fixedly connected in cutouts of a carrier element and; the carrier element being of a harder material than that of the flexible cleaning element and not readily releasably connected to the head part such that the rear side of the carrier element faces the head part, the flexible material of the flexible cleaning element forming a material bond with the carrier element.

66. The brush as claimed in claim 65, wherein the at least one cleaning element is molded into prepared cutouts of the carrier element.

67. The brush as claimed in claim 65, wherein a region of flexible material is arranged laterally to the carrier element, said region terminating laterally with an outer contour of the head part or projecting beyond the same when the carrier element is connected to the head part.

68. The brush as claimed in claim 65, wherein a region of flexible material is arranged between clusters of bristle filaments.

69. The brush as claimed in claim 65, wherein the head part is provided with further flexible elements.

70. The brush as claimed in claim 65, wherein a non-releasable connection is provided between the carrier element and the head part.

71. The brush as claimed in claim 65, wherein the carrier element is formed of the same material as the head part.

72. The brush as claimed in claim 65, wherein the flexible material includes a thermoplastic elastomer.

73. The brush as claimed in claim 65, wherein the flexible material has a Shore A hardness of less than 90.

74. The brush as claimed in claim 65, wherein the non-bristle containing cleaning element comprises sheet-like elements.

75. A process for producing a brush with a handle and a head part with bristle filaments and at least one flexible, non-bristle containing cleaning element made from flexible material arranged on a carrier element, comprising: providing the carrier element having a front side and a rear side and made from a harder material than that of the flexible cleaning element; providing a plurality of bristle filaments connected in cutouts of the carrier element; and connecting the carrier element to the head part in a non-releasable manner such that the rear side of the carrier element faces the head part, wherein the at least one cleaning element is molded into prepared cutouts of the carrier element, the flexible material of the flexible cleaning element forming a material bond with the carrier element.

76. The process as claimed in claim 75, further comprising connecting the carrier element and the head part by clamping, snap-fitting, riveting, adhesive bonding, welding, ultrasonic welding or the supply of heat.

77. The process as claimed in claim 76, further comprising providing the head part with further flexible elements.

78. The process as claimed in claim 77, further comprising locating the further flexible elements on a longitudinal rear side of the head part.

79. The process as claimed in claim 78, further comprising locating the injection point of the further flexible elements on the longitudinal rear side of the head part.

80. The process as claimed in claim 75, comprising producing a non-releasable connection between the flexible cleaning element and the carrier element.

81. The process as claimed in claim 75, further comprising non-releasable connection between the head part and the carrier element at point-like locations and leaving regions therebetween un-connected.

82. The process as claimed in claim 75, wherein the fastening is by melting and forms a bristle melt layer on the rear side of the carrier element.

* * * * *