



US00RE47599E

(19) **United States**
(12) **Reissued Patent**
Dearing et al.

(10) **Patent Number: US RE47,599 E**
(45) **Date of Reissued Patent: *Sep. 10, 2019**

(54) **RF POINT OF SALE AND DELIVERY METHOD AND SYSTEM USING COMMUNICATION WITH REMOTE COMPUTER AND HAVING FEATURES TO READ A LARGE NUMBER OF RF TAGS**

(58) **Field of Classification Search**
CPC G06Q 10/08; G06Q 10/087; G06Q 30/06; G06Q 30/0603; G06F 19/00; G07F 9/026;
(Continued)

(71) Applicant: **Promega Corporation**, Madison, WI (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Michael Dearing**, Spring Green, WI (US); **Gediminas Vidugiris**, Fitchburg, WI (US); **William A. Linton**, Madison, WI (US); **John Linton**, San Carlos, CA (US); **Julia E. Krueger**, Deerfield, WI (US)

3,827,053 A 7/1974 Willie et al. 343/701
3,861,433 A 1/1975 Schier et al. 150/0.5
(Continued)

(73) Assignee: **PROMEGA CORPORATION**, Madison, WI (US)

FOREIGN PATENT DOCUMENTS

AU 2002211769 3/2007
CA 2425189 5/2002
(Continued)

(*) Notice: This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **15/376,597**

Nov. 28, 2008 Official Action in Australian Patent Appln. No. 2006220406.

(22) Filed: **Jun. 14, 2017**

(Continued)

Related U.S. Patent Documents

Primary Examiner — Jalatee Worjloh

Reissue of:

(74) *Attorney, Agent, or Firm* — McAndrews, Held & Malloy, Ltd.

(64) Patent No.: **8,025,228**
Issued: **Sep. 27, 2011**
Appl. No.: **11/980,559**
Filed: **Oct. 31, 2007**

(57) **ABSTRACT**

U.S. Applications:


A method and system for providing point-of-sale and point-of-delivery and/or distribution of products in a restricted access unit near the customer. The method and system utilize products equipped with radio frequency tags and reduce the effects of energy sharing, shadowing, and nulls. In one embodiment, a plurality of RF tagged products are placed within a refrigerator, cabinet, or other micro-warehouse that has a door or opening that can detect access to the micro-warehouse. [In one embodiment, one or more antennas are positioned within the door. Each antenna may have a transmission line of sight and be configured to emit a signal at predefined frequencies. Each antenna generates an electromagnetic field within the micro-warehouse. In one embodiment, the products are positioned in one or more bins, compartments, or similar devices located within the micro-

(63) Continuation of application No. 14/602,694, filed on Jan. 22, 2015, now Pat. No. Re. 46,326, which is an
(Continued)

(51) **Int. Cl.**
G06K 7/10 (2006.01)
G07F 9/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06Q 10/08** (2013.01); **G06K 7/10336** (2013.01); **G06Q 10/087** (2013.01);
(Continued)

(Continued)



warehouse such that at least two of the plurality of products are spaced a distance from each other to reduce energy sharing. The electromagnetic field is moved or altered within the micro-warehouse through the use of reflectors, devices that move the antennas, or other mechanisms.]

15 Claims, 19 Drawing Sheets

Related U.S. Application Data

application for the reissue of Pat. No. 8,025,228, which is a continuation of application No. 10/954,612, filed on Oct. 1, 2004, now Pat. No. 7,661,591, which is a continuation of application No. 10/080,330, filed on Feb. 21, 2002, now abandoned, which is a continuation-in-part of application No. 09/981,219, filed on Oct. 16, 2001, now Pat. No. 7,258,276.

(60) Provisional application No. 60/241,907, filed on Oct. 20, 2000.

(51) **Int. Cl.**
G07G 1/00 (2006.01)
G06Q 10/08 (2012.01)
G06Q 30/06 (2012.01)

(52) **U.S. Cl.**
 CPC **G06Q 30/06** (2013.01); **G06Q 30/0603** (2013.01); **G07F 9/026** (2013.01); **G07G 1/0045** (2013.01); **F25D 2500/06** (2013.01); **F25D 2700/08** (2013.01)

(58) **Field of Classification Search**
 CPC G07G 1/0045; G06K 7/10336; G06K 2017/0067; G06K 2017/0051; F25D 2700/08; F25D 2500/06
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,918,671 A	11/1975	Mizusawa	248/285
4,116,512 A	9/1978	Wiser	312/330.1
4,118,693 A	10/1978	Novikoff	340/572
4,223,830 A	9/1980	Walton	235/380
4,227,037 A	10/1980	Layton	
4,354,613 A	10/1982	Desai et al.	221/4
4,414,690 A	11/1983	Nordholt et al.	455/283
4,496,406 A	1/1985	Dedow	
4,580,041 A	4/1986	Walton	235/380
4,616,694 A	10/1986	Hsieh	165/47
4,636,634 A	1/1987	Harper et al.	250/223 R
4,636,950 A	1/1987	Caswell et al.	364/403
4,639,875 A	1/1987	Abraham et al.	364/479
4,656,463 A	4/1987	Anders et al.	340/572
4,688,026 A	8/1987	Scribner et al.	340/572
4,694,283 A	9/1987	Reeb	340/572
4,746,830 A	5/1988	Holland	310/313 D
4,785,969 A	11/1988	McLaughlin	221/2
4,805,207 A	2/1989	McNutt et al.	
4,837,568 A	6/1989	Snaper	340/825.54
4,847,764 A	7/1989	Halvorson	364/413.02
4,860,918 A	8/1989	Wuyten et al.	
4,862,160 A	8/1989	Ekchian et al.	340/825.54
4,866,661 A	9/1989	de Prins	364/900
4,881,061 A	11/1989	Chambers	340/568
4,961,533 A	10/1990	Teller et al.	177/25.19
5,008,814 A	4/1991	Mathur	364/200
5,014,875 A	5/1991	McLaughlin et al.	221/2
5,019,815 A	5/1991	Lemelson et al.	340/933
5,021,800 A	6/1991	Rilling	343/820

5,030,807 A	7/1991	Landt et al.	235/375
5,036,308 A	7/1991	Fockens	340/572
5,038,023 A	8/1991	Saliga	235/385
5,091,713 A	2/1992	Horne et al.	340/541
5,099,226 A	3/1992	Andrews	340/572
5,103,222 A	4/1992	Hogen Esch et al.	340/825.54
5,117,407 A	5/1992	Vogel	369/30
5,144,314 A	9/1992	Malmberg et al.	342/44
5,155,847 A	10/1992	Kirouac et al.	395/600
5,194,856 A	3/1993	Zijlstra	340/825.35
5,208,599 A	5/1993	Rudduck et al.	342/4
5,214,409 A	5/1993	Beigel	340/572
5,231,844 A	8/1993	Park	62/80
5,240,139 A	8/1993	Chirnomas	221/2
5,260,690 A	11/1993	Mann et al.	340/572
5,266,925 A	11/1993	Vercellotti et al.	340/572
5,285,041 A	2/1994	Wright	219/717
5,287,414 A	2/1994	Foster	382/1
5,294,931 A	3/1994	Meier	342/44
5,327,118 A	7/1994	Drucker et al.	340/572
5,335,509 A	8/1994	Namisniak et al.	62/125
5,365,551 A	11/1994	Snodgrass et al.	375/1
5,389,919 A	2/1995	Warren et al.	340/825.31
5,392,025 A	2/1995	Figh et al.	340/545
5,408,443 A	4/1995	Weinberger	368/10
5,410,315 A	4/1995	Huber	342/42
5,421,009 A	5/1995	Platt	395/600
5,424,858 A	6/1995	Gillotte	359/143
5,431,299 A	7/1995	Brewer et al.	221/2
5,446,447 A	8/1995	Carney et al.	340/572
5,450,070 A	9/1995	Massar et al.	340/825.35
5,460,294 A	10/1995	Williams	221/2
5,471,203 A	11/1995	Sasaki et al.	340/825.31
5,478,990 A	12/1995	Montanari et al.	
5,487,276 A	1/1996	Namisniak et al.	62/125
5,487,764 A	1/1996	Ford, Jr.	44/553
5,489,908 A	2/1996	Orthmann et al.	342/42
5,491,715 A	2/1996	Flaxl	375/344
5,495,961 A	3/1996	Maestre	221/3
5,500,650 A	3/1996	Snodgrass et al.	342/42
5,519,381 A	5/1996	Marsh et al.	340/572
5,520,450 A	5/1996	Colson, Jr. et al.	312/215
5,521,601 A	5/1996	Kandlur et al.	342/44
5,528,222 A	6/1996	Moskowitz et al.	340/572
5,528,232 A	6/1996	Verma et al.	340/825.54
5,530,702 A	6/1996	Palmer et al.	370/85.3
5,537,105 A	7/1996	Marsh et al.	340/825.54
5,539,394 A	7/1996	Cato et al.	340/825.54
5,541,604 A	7/1996	Meier	342/42
5,550,547 A	8/1996	Chan et al.	342/42
5,557,280 A	9/1996	Marsh et al.	342/44
5,564,803 A	10/1996	McDonald et al.	312/215
5,565,858 A	10/1996	Guthrie	
5,573,082 A	11/1996	Conlan et al.	186/44
5,583,819 A	12/1996	Roesner et al.	365/225.7
5,600,121 A	2/1997	Kahn et al.	235/472
5,602,538 A	2/1997	Orthmann et al.	340/825.54
5,606,902 A	3/1997	Hosono et al.	92/88
5,608,298 A	3/1997	Frolov et al.	318/286
5,608,739 A	3/1997	Snodgrass et al.	371/37.1
5,621,199 A	4/1997	Calari et al.	235/375
5,627,517 A	5/1997	Theimer et al.	340/572
5,627,544 A	5/1997	Snodgrass et al.	342/42
5,629,981 A	5/1997	Nerlikar	713/168
5,648,765 A	7/1997	Cresap et al.	340/825.35
5,648,767 A	7/1997	O'Connor et al.	340/928
5,680,459 A	10/1997	Hook et al.	380/23
5,686,902 A	11/1997	Reis et al.	340/825.54
5,689,238 A	11/1997	Cannon, Jr. et al.	340/568
5,699,066 A	12/1997	Marsh et al.	342/44
5,701,252 A	12/1997	Facchin et al.	364/479
5,703,347 A	12/1997	Reddersen et al.	235/472
5,708,423 A	1/1998	Ghaffari et al.	340/825.35
5,711,160 A	1/1998	Namisniak et al.	62/125
5,713,485 A	2/1998	Liff et al.	221/2
RE35,743 E	3/1998	Pearson	221/2
5,726,630 A	3/1998	Marsh et al.	340/572
5,739,765 A	4/1998	Stanfield et al.	
5,742,618 A	4/1998	Lowe	371/36

(56)

References Cited

U.S. PATENT DOCUMENTS

- 5,745,036 A 4/1998 Clare 340/572
5,745,366 A 4/1998 Higham et al. 364/479.12
5,751,221 A 5/1998 Stanfield et al. 340/825.35
5,764,992 A 6/1998 Kullick et al. 395/712
5,765,707 A 6/1998 Kenevan
5,771,003 A 6/1998 Seymour
5,774,053 A 6/1998 Porter 340/568
5,774,059 A 6/1998 Henry et al.
5,774,876 A 6/1998 Woolley et al. 705/28
5,777,561 A 7/1998 Chieu et al. 340/825.54
5,786,763 A 7/1998 Canipe 340/572
5,787,174 A 7/1998 Tuttle 380/23
H1743 H 8/1998 Graves et al. 364/479.06
5,797,515 A 8/1998 Liff et al. 221/2
5,798,693 A 8/1998 Engellenner 340/505
5,798,694 A 8/1998 Reber et al. 340/540
5,801,628 A 9/1998 Maloney 340/568
5,805,455 A 9/1998 Lipps 364/479.01
5,805,456 A 9/1998 Higham et al. 364/479.06
5,805,897 A 9/1998 Gloway 395/712
5,809,230 A 9/1998 Pereira
5,818,348 A 10/1998 Walczak et al. 340/825.54
5,822,692 A 10/1998 Krishan et al. 455/419
5,822,714 A * 10/1998 Cato 702/108
5,825,806 A 10/1998 Tuttle 375/200
5,831,531 A 11/1998 Tuttle 340/572
5,836,618 A 11/1998 Perlman 283/70
5,841,770 A 11/1998 Snodgrass et al. 370/346
5,842,118 A 11/1998 Wood, Jr. 455/101
5,842,976 A 12/1998 Williamson 600/300
5,852,911 A 12/1998 Yuyama et al. 53/168
5,857,152 A 1/1999 Everett 455/406
5,883,582 A 3/1999 Bowers et al. 340/825.54
5,886,634 A 3/1999 Muhme 340/572
5,887,176 A 3/1999 Griffith et al. 395/750
5,889,474 A 3/1999 LaDue 340/825.49
5,892,441 A 4/1999 Woolley et al. 340/539
5,894,266 A 4/1999 Wood, Jr. et al. 340/539
5,902,984 A 5/1999 Planke 235/381
5,902,991 A 5/1999 Kumar 235/492
5,905,653 A 5/1999 Higham et al. 364/479.14
5,906,228 A 5/1999 Keller 141/94
5,909,581 A 6/1999 Park 395/712
5,910,776 A 6/1999 Black 340/825.35
5,912,818 A 6/1999 McGrady et al. 364/479.02
5,923,001 A 7/1999 Morris et al. 177/245
5,923,300 A 7/1999 Mejia 343/788
5,927,540 A 7/1999 Godlewski 221/2
5,929,779 A 7/1999 MacLellan et al. 340/825.54
5,929,801 A 7/1999 Aslanidis et al. 342/44
5,930,145 A 7/1999 Yuyama et al. 364/479.01
5,930,766 A 7/1999 Gibb 705/15
5,936,527 A 8/1999 Isaacman et al. 340/572.1
5,949,335 A 9/1999 Maynard 340/572.1
5,950,630 A 9/1999 Portwood et al. 128/897
5,955,298 A 9/1999 Thomashow et al. 435/69.1
5,955,950 A 9/1999 Gallagher, III et al. ... 340/572.1
5,955,951 A 9/1999 Wischerop et al. 340/572.8
5,959,531 A 9/1999 Gallagher, III et al. ... 340/572.1
5,959,568 A 9/1999 Woolley 342/42
5,960,048 A 9/1999 Haartsen 375/366
5,963,134 A 10/1999 Bowers et al. 340/572.1
5,963,144 A 10/1999 Kruent 340/825.54
5,969,606 A 10/1999 Reber et al. 340/540
5,971,277 A 10/1999 Cragun et al. 235/462.01
5,974,454 A 10/1999 Apfel et al. 709/221
5,977,875 A 11/1999 Lin et al. 340/570
5,979,941 A 11/1999 Mosher, Jr. et al. 283/67
5,986,570 A 11/1999 Black et al. 340/825.54
5,990,794 A 11/1999 Alicot et al. 340/573.1
5,993,046 A 11/1999 McGrady et al. 364/479.01
5,995,019 A 11/1999 Chieu et al. 340/825.54
5,995,898 A 11/1999 Tuttle 701/102
5,999,091 A 12/1999 Wortham 340/431
5,999,741 A 12/1999 May et al. 395/712
5,999,808 A 12/1999 LaDue 455/412
6,002,344 A 12/1999 Bandy et al. 340/825.54
6,003,006 A 12/1999 Colella et al. 705/2
6,006,034 A 12/1999 Heath et al. 395/712
6,009,274 A 12/1999 Fletcher et al. 395/712
6,011,243 A 1/2000 Arnold et al. 291/506
6,011,999 A 1/2000 Holmes 700/231
6,012,041 A 1/2000 Brewer et al. 705/28
6,020,856 A 2/2000 Alicot 343/742
6,021,392 A 2/2000 Lester et al. 705/2
6,023,610 A 2/2000 Wood, Jr. 455/101
6,025,780 A 2/2000 Bowers et al. 340/572.3
6,031,459 A 2/2000 Lake 340/572.8
6,034,603 A 3/2000 Steeves 340/572.1
6,036,099 A 3/2000 Leighton 235/488
6,037,879 A 3/2000 Tuttle 340/825.54
6,039,467 A 3/2000 Holmes 364/479.01
6,040,773 A 3/2000 Vega et al. 334/572.1
6,044,461 A 3/2000 Agha et al. 713/1
6,056,199 A 5/2000 Wiklof et al. 235/462.45
6,057,756 A 5/2000 Engellenner 340/505
6,068,156 A 5/2000 Liff et al. 221/7
6,069,564 A 5/2000 Hatano et al. 340/572.7
6,070,012 A 5/2000 Eitner et al. 395/712
6,070,070 A 5/2000 Ladue 455/419
6,073,547 A * 6/2000 Westbrook, Jr. A47J 39/003
165/48.1
6,075,441 A 6/2000 Maloney 340/568.1
6,088,431 A 7/2000 LaDue 379/114
6,097,306 A 8/2000 Leon et al. 340/825.1
6,107,917 A 8/2000 Carrender et al. 340/505
6,108,588 A 8/2000 McGrady 700/231
6,112,152 A 8/2000 Tuttle 701/115
6,112,502 A 9/2000 Frederick et al. 53/411
6,116,461 A 9/2000 Broadfield et al. 221/98
6,121,583 A 9/2000 Hansen 219/401
6,121,880 A 9/2000 Scott et al. 340/572.5
6,127,928 A 10/2000 Issacman et al. 340/572.1
6,127,981 A 10/2000 Pritchett et al. 343/711
6,131,399 A * 10/2000 Hall 62/127
6,131,812 A 10/2000 Schneider 235/385
6,133,835 A 10/2000 De Leeuw et al. 340/572.5
6,144,848 A 11/2000 Walsh et al. 455/419
6,144,859 A 11/2000 LaDue 455/511
6,147,601 A 11/2000 Sandelman et al. 340/506
6,147,655 A 11/2000 Roesner 343/741
6,147,662 A 11/2000 Grabau et al. 343/895
6,151,536 A 11/2000 Arnold et al. 700/237
6,152,364 A 11/2000 Schoonen et al. 235/375
6,152,365 A 11/2000 Kolls 235/381
6,154,790 A 11/2000 Pruett et al. 710/15
6,160,477 A 12/2000 Sandelman et al. 340/506
6,169,483 B1 1/2001 Ghaffari et al. 340/572.3
6,170,285 B1 1/2001 Huffman et al. 62/448
6,185,198 B1 2/2001 LaDue 370/329
6,202,925 B1 3/2001 Machii et al. 235/380
6,204,764 B1 3/2001 Maloney 340/568.1
6,211,782 B1 4/2001 Sandelman et al. 340/506
6,218,942 B1 4/2001 Vega et al. 340/572.1
6,223,984 B1 5/2001 Renner et al. 235/380
6,229,443 B1 5/2001 Roesner 340/572.1
6,249,227 B1 6/2001 Brady et al. 340/572.1
6,260,049 B1 7/2001 Fitzgerald et al. 707/104
6,265,976 B1 7/2001 Roesner 340/572.4
6,272,394 B1 8/2001 Lipps 700/231
6,285,868 B1 9/2001 LaDue 455/410
6,294,999 B1 9/2001 Yarin et al.
6,296,148 B1 10/2001 Myers et al.
6,305,609 B1 10/2001 Melzer et al. 235/487
6,313,747 B2 11/2001 Imaichi et al. 340/572.5
6,327,576 B1 12/2001 Ogasawara 705/22
6,338,007 B1 1/2002 Broadfield et al. 700/231
6,339,732 B1 1/2002 Phoon et al. 700/237
6,351,215 B2 2/2002 Rodgers et al. 340/572.1
6,356,197 B1 3/2002 Patterson et al. 340/572.1
6,362,737 B1 3/2002 Rodgers et al. 340/572.1
6,375,780 B1 4/2002 Tuttle et al. 156/226
6,380,858 B1 4/2002 Yarin et al.
6,385,505 B1 5/2002 Lipps 700/231

(56)

References Cited

U.S. PATENT DOCUMENTS

6,392,543	B2	5/2002	Maloney	340/568.1	7,276,675	B2 *	10/2007	Faries, Jr.	A61M 5/445 219/413
6,392,544	B1	5/2002	Collins et al.		7,293,705	B2 *	11/2007	Linton et al.	235/385
6,393,339	B1	5/2002	Yeadon	700/237	7,315,247	B2	1/2008	Jung et al.	
6,407,665	B2	6/2002	Maloney	340/568.1	7,389,916	B2	6/2008	Chirnomas	
6,407,669	B1	6/2002	Brown et al.	340/572.1	7,455,225	B1	11/2008	Hadfield et al.	
6,424,260	B2	7/2002	Maloney	340/568.1	7,463,947	B1 *	12/2008	Frederick	G07F 7/06 700/236
6,424,262	B2	7/2002	Garber et al.	340/572.3	8,423,180	B1 *	4/2013	Frederick	G06Q 10/087 700/236
6,427,913	B1	8/2002	Maloney	235/383	2001/0000019	A1	3/2001	Bowers et al.	340/572.1
6,431,438	B1	8/2002	Pires et al.	235/375	2001/0002448	A1	5/2001	Wilson et al.	700/233
6,445,297	B1	9/2002	Nicholson	340/572.7	2001/0011341	A1	8/2001	Hayes, Jr. et al.	712/11
6,451,154	B1	9/2002	Grabau et al.	156/300	2001/0028308	A1	10/2001	De La Huerga	340/573.1
6,462,661	B2	10/2002	Pfeiffer et al.	340/572.8	2001/0034259	A1	10/2001	Luciano et al.	463/16
6,501,435	B1	12/2002	King et al.	343/795	2001/0034613	A1	10/2001	Rubsamen	705/2
6,512,459	B2	1/2003	Benezech et al.		2001/0044731	A1	11/2001	Coffman et al.	705/3
6,512,478	B1	1/2003	Chien	342/357.09	2001/0044804	A1	11/2001	Fitzgerald et al.	707/200
6,517,000	B1	2/2003	McAllister et al.	235/462.01	2001/0045893	A1	11/2001	Swartzel et al.	340/572.1
6,522,645	B1	2/2003	Lee et al.	370/352	2001/0045894	A1	11/2001	Slavin et al.	
6,529,446	B1	3/2003	de la Huerga	368/10	2001/0053980	A1	12/2001	Suliman, Jr. et al.	705/1
6,529,466	B2	3/2003	Saga et al.		2002/0005774	A1	1/2002	Rudolph et al.	
6,532,399	B2	3/2003	Mase		2002/0011967	A1	1/2002	Goff et al.	343/895
6,563,425	B2	5/2003	Nicholson et al.	340/572.7	2002/0013077	A1	1/2002	Lepine et al.	439/191
6,568,596	B1	5/2003	Shaw	235/426.01	2002/0027507	A1	3/2002	Yarin et al.	340/573.1
6,590,498	B2	7/2003	Helms	340/572.7	2002/0038167	A1	3/2002	Chirnomas	700/231
6,595,418	B1	7/2003	Igarashi et al.	235/385	2002/0040968	A1	4/2002	Black et al.	250/393
6,600,420	B2	7/2003	Goff et al.	340/572.4	2002/0041234	A1	4/2002	Kuzma et al.	340/572.8
6,609,047	B1	8/2003	Lipps	700/231	2002/0063622	A1	5/2002	Armstrong et al.	340/10.31
6,639,509	B1	10/2003	Martinez	340/10.4	2002/0113082	A1	8/2002	Leatherman et al.	
6,639,514	B1	10/2003	Müller	340/572.5	2002/0130778	A1	9/2002	Nicholson	
6,640,159	B2	10/2003	Holmes et al.	700/244	2002/0130788	A1	9/2002	Chang	
6,664,895	B2	12/2003	Zhu	340/570	2002/0140966	A1	10/2002	Meade, II et al.	358/1.15
6,677,852	B1	1/2004	Landt	340/10.1	2002/0143320	A1	10/2002	Levin	
6,677,857	B2	1/2004	Bara et al.		2002/0145036	A1	10/2002	Otto	235/383
6,686,830	B1	2/2004	Schirtzer	340/10.2	2002/0145520	A1	10/2002	Maloney	
6,687,609	B2	2/2004	Hsiao et al.		2002/0153411	A1	10/2002	Wan et al.	
6,693,539	B2	2/2004	Bowers et al.	340/572.1	2002/0167397	A1	11/2002	Eroglu et al.	340/10.6
6,700,491	B2	3/2004	Shafer	340/572.7	2002/0180588	A1	12/2002	Erickson et al.	340/10.2
6,707,381	B1	3/2004	Maloney	340/568.1	2002/0183882	A1	12/2002	Dearing et al.	700/115
6,714,121	B1	3/2004	Moore	340/10.3	2002/0190871	A1	12/2002	Stanfield et al.	
6,717,154	B2	4/2004	Black et al.	250/393	2002/0196126	A1	12/2002	Eisenberg et al.	340/10.2
6,758,802	B2	7/2004	Fitzgerald et al.	493/476	2002/0198795	A1	12/2002	Dorenbosch	
6,760,643	B2	7/2004	Lipps	700/231	2003/0006907	A1	1/2003	Lovegreen et al.	340/870.16
6,761,637	B2	7/2004	Weston et al.	463/42	2003/0030539	A1	2/2003	McGarry et al.	
6,768,419	B2	7/2004	Garber et al.	340/572.4	2003/0034390	A1	2/2003	Linton et al.	235/382
6,771,766	B1	8/2004	Shafiee et al.	379/265.09	2003/0052783	A1	3/2003	Sitzman	340/572.7
6,793,127	B2	9/2004	Alsafadi et al.	235/375	2003/0074106	A1	4/2003	Butler	
6,812,824	B1	11/2004	Golding et al.	340/10.1	2003/0117281	A1	6/2003	Srihartho et al.	340/568.1
6,814,254	B2 *	11/2004	Liff	G06F 19/3462 221/7	2003/0171998	A1	9/2003	Pujar et al.	705/26
					2003/0174046	A1	9/2003	Abrams	340/5.92
					2003/0209601	A1	11/2003	Chung	235/385
6,829,520	B1	12/2004	Green		2003/0216969	A1	11/2003	Bauer et al.	705/22
6,830,181	B1	12/2004	Bennett	235/440	2004/0069850	A1	4/2004	De Wilde	235/385
6,836,215	B1	12/2004	Laurash et al.	340/572.1	2004/0100415	A1	5/2004	Veitch et al.	343/850
6,838,989	B1	1/2005	Mays et al.	340/572.1	2004/0124988	A1	7/2004	Leonard et al.	340/612
6,839,604	B2	1/2005	Godfrey et al.	700/116	2004/0205350	A1 *	10/2004	Waterhouse	G06Q 10/08 713/182
6,843,720	B2	1/2005	Luciano et al.		2004/0212542	A1	10/2004	Rahim	
6,859,757	B2	2/2005	Muehl et al.	702/184	2004/0222298	A1	11/2004	Dearing et al.	
6,883,710	B2	4/2005	Chung	235/385	2004/0232230	A1	11/2004	Linton et al.	
6,892,520	B2	5/2005	Rowse et al.	56/377	2004/0232231	A1	11/2004	Linton et al.	
6,892,545	B2	5/2005	Ishikawa et al.	62/126	2004/0263316	A1	12/2004	Dix et al.	340/5.23
6,908,034	B2	6/2005	Alleshouse	235/432	2005/0008376	A1	1/2005	Parry et al.	399/24
6,909,326	B2	6/2005	Jesme	330/251	2005/0009122	A1	1/2005	Whelan et al.	435/7.32
6,970,141	B2	11/2005	Copeland et al.	343/866	2005/0040952	A1	2/2005	Dearing et al.	
6,975,834	B1	12/2005	Forster	455/2.72	2005/0088305	A1	4/2005	Greene et al.	
6,982,640	B2	1/2006	Lindsay et al.	340/540	2005/0113138	A1	5/2005	Mendolia et al.	455/558
6,987,392	B1	1/2006	Hernandez et al.	324/627	2005/0125312	A1	6/2005	Dearing et al.	
6,989,749	B2	1/2006	Mohr	340/572.1	2005/0127177	A1	6/2005	Dearing et al.	
6,989,796	B2	1/2006	Rahim		2005/0194437	A1	9/2005	Dearing et al.	
7,009,515	B2	3/2006	Carrender	340/572.1	2005/0247782	A1	11/2005	Ambartsoumian	235/385
7,020,680	B2 *	3/2006	Defosse	709/201	2006/0006999	A1	1/2006	Walczyk et al.	340/539.27
7,031,803	B2	4/2006	Eneau et al.		2006/0017634	A1	1/2006	Meissner	343/742
7,053,775	B2	5/2006	Moore	340/572.1	2006/0022827	A1	2/2006	Higham	340/572.1
7,181,501	B2	2/2007	Defosse		2006/0081705	A1	4/2006	Linton et al.	
7,250,865	B2	7/2007	Maloney	340/572.1	2006/0190628	A1	8/2006	Linton et al.	
7,258,276	B2	8/2007	Linton et al.		2006/0214864	A1	9/2006	Rahim	
7,268,742	B2	9/2007	Rahim		2006/0244599	A1	11/2006	Taylor et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0289650 A1 12/2006 Taylor et al.
 2007/0069018 A1 3/2007 Dearing et al.
 2007/0108273 A1 5/2007 Harper et al.
 2008/0100527 A1 5/2008 Rahim
 2008/0116269 A1 5/2008 Dearing et al.
 2008/0135613 A1 6/2008 Dearing et al.
 2008/0224875 A1 9/2008 Phillips et al.
 2010/0116885 A1 5/2010 Dearing et al.
 2010/0187307 A1 7/2010 Phillips et al.

FOREIGN PATENT DOCUMENTS

CN 1230270 9/1999
 DE 299 12 346 U1 12/1999
 EP 0 632 288 1/1995
 EP 0 722 590 B1 7/1996
 EP 0726545 8/1996
 EP 1679636 7/2006
 EP 1701296 9/2006
 FR 2786876 6/2000
 GB 232252 A * 10/1925 B01L 3/0282
 GB 2 333 095 A 7/1999
 JP 51-122498 10/1976
 JP 4185397 7/1992
 JP 07-230584 8/1995
 JP H07-302284 11/1995
 JP 10-316210 12/1998
 JP 11-085858 3/1999
 JP 11-130213 5/1999
 JP 11-283123 10/1999
 JP H11-283123 10/1999
 JP 2000-038202 2/2000
 JP 2000-137758 5/2000
 JP 2000-251156 9/2000
 JP 2000-276335 10/2000
 JP 2000-310476 11/2000
 JP 2001-052054 2/2001
 JP 2001-097512 4/2001
 JP 2001-160162 6/2001
 JP 2001-229263 8/2001
 JP 2001-240217 9/2001
 JP 2001-317859 11/2001
 JP 2001-317862 11/2001
 JP 2002-032865 1/2002
 JP 2006-56244 2/2002
 KR 1993-0005285 3/1993
 KR 1996-0002892 Y1 4/1996
 KR 10-0184972 B1 5/1999
 KR 2001-0022226 3/2001
 KR 2001-0022227 3/2001
 KR 2001-0072457 7/2001
 KR 10-0766679 10/2007
 RU 2 161 329 C2 12/2000
 RU 2 168 761 C1 6/2001
 WO WO 95/25423 9/1995
 WO WO 96/12254 4/1996
 WO WO 97/24689 7/1997
 WO WO 97/29729 8/1997
 WO WO 98/26746 6/1998
 WO WO 98/52168 11/1998
 WO WO 99/05659 2/1999
 WO WO 99/05660 2/1999
 WO WO 99/12122 3/1999
 WO WO 99/45493 9/1999
 WO WO 99/45494 9/1999
 WO WO 99/45495 9/1999
 WO WO 99/46940 9/1999
 WO WO 99/49337 9/1999
 WO WO 99/52723 10/1999
 WO WO 99/57837 11/1999
 WO WO 99/60512 11/1999
 WO WO 99/62196 12/1999
 WO WO 99/67735 12/1999
 WO WO 00/03352 1/2000
 WO WO 00/04485 1/2000

WO WO 00/04520 1/2000
 WO WO 00/45324 8/2000
 WO WO 01/55931 A1 8/2001
 WO WO 01/94016 A1 12/2001
 WO WO 01/95243 A2 12/2001
 WO WO 02/01467 A2 1/2002
 WO WO 02/03230 A1 1/2002
 WO WO 02/08939 1/2002
 WO WO 02/19251 3/2002
 WO WO 02/31629 4/2002
 WO WO 02/33511 4/2002
 WO WO 02/35432 A1 5/2002
 WO WO 03/026724 A1 4/2003
 WO WO 03/073201 9/2003
 WO WO 03/073225 A2 9/2003
 WO WO 03/087868 A2 10/2003
 WO WO 2005/013496 2/2005
 WO WO 2007/142645 12/2007
 WO WO 2008/115784 9/2008

OTHER PUBLICATIONS

Declaration of Edward W. Bumham dated May 12, 2003. Oct. 20, 2003 International Search Report.
 Rosen, Cheryl, "The Fast Track," InformationWeek.Com, Jun. 18, 2001.
 Woodyard, Chris, "Chips to Improve Baggage-Check Efficiency," Nov. 27, 2000, USA Today, Gannett Co., Inc.
 Wigglesworth, Zeke, "SFO Installing First-in-U.S. Security System," San Jose Mercury News, Feb. 18, 2001.
 Siedsma, Andrea, "SCS Aims to Make Skies Friendlier for Air Travelers," Feb. 23, 2001.
 Brakeman, Lynne, "RFID Baggage Tracking Solution Helps Keep SFIA Secure," Jul. 1, 2001.
 "Mobil Speedpass Makes Gasoline Purchase Virtually Effortless", Business Wire, Feb. 19, 1997, Copyright 1997 Business Wire, Inc., Business Wire, pp. 1-2.
 "Technical report for RFID systems operating in the 2.45 Ghz ISM band", Jul. 4, 1999, revised Aug. 19, 1999, pp. 1-51.
 "Air Interfaces: Communications and Interfaces: Part B: Parameter Values for 2.45 Ghz Narrow Band RFID Systems", Jun. 1, 1999.
 "Radio Frequency Identification System—13.56 MHz", Feb. 13, 1997, pp. 1-20.
 "Comments on the joint proposal by Gemplus and Checkpoint for a universal wake-up command (at 13.56MHz)", Alain Berthon, Texas Instruments, May 17, 2000, pp. 1-3.
 "Field Re-programmable Item Management Air Interface Standard Proposal for 13,56 MHz," GEMPLUS 13 MHZ Air Interface Proposal, ISO/SC31/WG4/SG3 GEMPLUS NP, Jun. 21, 1999.
 "13.56MHz Air Interface Proposal," Checkpoint systems, Inc. and Microchip Technology, Inc., Aug. 11, 1999.
 "Multiple Frequency Anti-collision Protocol," Inferneon Technologies AG, ISO/8EC JTC 1/SC31 Working Group 4—Radio Frequency Identification for Item Management, Mar. 23, 2000.
 Moore, Bert, "RFID May Yet Prove Its Mettle on Metal," Frontline Solutions, Apr. 2001.
 Senger, Nancy, "Making Airlines Safer With RFID," Business Solutions, Mar. 2000.
 Sharp, Kevin, "This "Killer App" Can Save Lives," ID Systems, Feb. 2000, Inc.
 Binzoni, et al., "SCS Corporation Announces Radio Frequency Identification Installation At A Major Airport.", Oct. 5, 1999.
 Aug. 1, 2003, International Search Report in PCT/US02/40967.
 May 20, 2005 International Preliminary Examination Report in PCT/US03/04653.
 May 3, 2005 Official Action in U.S. Appl. No. 10/209,348.
 Jan. 17, 2005 Canadian Official Action.
 Russian Official Action in Russian Application No. 2004128075 (with English language translation).
 Apr. 13, 2006 Supplementary Partial European Search Report in European Application No. 03713485.
 Feb. 3, 2006 Official Action in U.S. Appl. No. 10/795,386.
 Jul. 14, 2006 Supplementary European Search Report in European Application No. 03713485.5.

(56)

References Cited

OTHER PUBLICATIONS

- Jul. 14, 2005 Official Action in U.S. Appl. No. 10/795,386.
 Jan. 28, 2005 Official Action in U.S. Appl. No. 10/795,386.
 Mar. 21, 2006 Official Action in U.S. Appl. No. 10/209,348.
 Aug. 15, 2006 Canadian Official Action in Canadian Patent Appln. No. 2,425,189.
 Sep. 11, 2006 Australian Written Opinion with Oct. 2, 2006 Singapore communication in Singapore Patent Appln. No. 200403954-1.
 Sep. 20, 2006 Communication in Russian Application No. 2004128075/09(030475) (with English-language translation).
 Dec. 12, 2006 Japanese Official Action in Japanese Patent Appln. No. 2002-538343 (with partial translation).
 Jan. 3, 2007 European Official Action in European Patent Appln. No. 01 919 848.7.
 Feb. 15, 2007 Official Action in Korean Patent Appln. No. 7027537/2006 (with partial translation).
 May 18, 2007 Official Action in Korean Patent Appln. No. 7013101/2004 (with partial translation).
 Jun. 25, 2007 Official Action in Korean Patent Appln. No. 45389/2007 (with partial translation).
 Jun. 25, 2007 Official Action in Korean Patent Appln. No. 45392/2007 (with partial translation).
 Jun. 25, 2007 Official Action in Korean Patent Appln. No. 45394/2007 (with partial translation).
 Jun. 25, 2007 Official Action in Korean Patent Appln. No. 45396/2007 (with partial translation).
 Aug. 6, 2007 Official Action in Korean Patent Appln. No. 45398/2007 (with partial translation).
 Jun. 22, 2007 Official Action in Japanese Patent Appln. No. 2003-571829 (with partial translation).
 Aug. 22, 2007 Official Action in Mexican Patent Appln. No. PA/a/008056 (with partial translation).
 Jul. 27, 2007 Official Action in Australian Patent Appln. No. 2006252255, with attached Oct. 23, 2003 International Preliminary Examination Report.
 Partial Translation of Russian Decision on Grant in Russian Patent Appln. No. 2004128075.
 Sep. 3, 2007 Official Action in Japanese Patent Appln. No. 2002-538343 (with partial translation).
 Sep. 13, 2007 Official Action in European Patent Appln. No. 06 023 373.1.
 Oct. 4, 2007 Official Action in Singapore Patent Appln. No. 200403954-1.
 Nov. 22, 2006 Official Action in U.S. Appl. No. 10/870,946.
 Jan. 27, 2006 Official Action in U.S. Appl. No. 10/870,938.
 Nov. 23, 2004 Official Action in European Patent Appln. No. 01 979 848.7.
 Aug. 8, 2005 Official Action in U.S. Appl. No. 10/870,938.
 Sep. 13, 2004 Supplementary Search Report in European Patent Appln. No. 01 979 848.7.
 Dec. 31, 2008 First Examination Report in Indian Patent Appln. No. 969/KOLNP/2004.
 Mar. 5, 2009 Canadian Official Action in Canadian Patent Appln. No. 2,425,189.
 Feb. 7, 2008 Official Communication in European Patent Appln. No. 03 713 485.5-1238.
 Dec. 14, 2007 Mexican Official Action translation in Mexican Patent Appln. No. PA/a/2004/008056.
 Mar. 6, 2008 Mexican Official Action translation in Mexican Patent Appln. No. PA/a/2004/008056.
 Dec. 24, 2007 Korean Official Action in Korean Patent Appln. No. 45392/2007 (with translation).
 Dec. 27, 2007 Korean Official Action in Korean Patent Appln. No. 45396/2007 (with translation).
 Dec. 24, 2007 Korean Official Action in Korean Patent Appln. No. 45394/2007 (with translation).
 Nov. 13, 2007 Korean Official Action in Korean Patent Appln. No. 7013101/2004 (with translation).
 Dec. 24, 2007 Korean Official Action in Korean Patent Appln. No. 45389/2007 (with translation).
 Feb. 11, 2008 Korean Official Action in Korean Patent Appln. No. 45398/2007 (with translation).
 Feb. 27, 2008 Korean Official Action in Korean Patent Appln. No. 45389/2007 (with translation).
 Apr. 18, 2008 Korean Official Action in Korean Patent Appln. No. 7000578/2008 (with translation).
 Aug. 8, 2008 Mexican Official Action translation in Mexican Patent Appln. No. PA/a/2004/008056.
 Jul. 11, 2008 Japanese Official Action translation in Japanese Patent Appln. No. 2003-571829.
 United States Patent Office Action for U.S. Appl. No. 12/508,758 dated Sep. 21, 2010 (9 pages).
 Chinese Patent Office Action for Application No. 03804323.8 dated Sep. 6, 2010 (12 pages).
 Japanese Patent Office Action for Application No. 2007-326923 dated Sep. 30, 2010 (4 pages).
 Japanese Patent Office Action for Application No. 2007-326923 dated Dec. 24, 2009 (3 pages) English translation only.
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Dec. 24, 2009 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 12/508,758 dated Dec. 30, 2009 (19 pages).
 Chinese Patent Office Action for Application No. 03804323.8 dated Mar. 1, 2010 (11 pages).
 United States Patent Office Notice of Allowance for U.S. Appl. No. 11/559,231 dated May 21, 2010 (5 pages).
 United States Patent Office Notice of Allowance for U.S. Appl. No. 11/381,849 dated Jun. 1, 2010 (14 pages).
 Canadian Patent Office Action for Application No. 2425189 dated May 11, 2010 (3 pages).
 May 22, 2009 Chinese Official Action in Chinese Patent Appln. No. 03804323.8 (with translation).
 Godinez, V., "RFID tracks hospital's devices," *The Dallas Morning News* (Apr. 28, 2007) 3 pages.
 Mobile Aspects, Inc., "Case study: expiration management--for Organization King's Daughters Medical Center," (2007) 1-2.
 Mobile Aspects, Inc., "Hands free through RFID," *File Aspects/Solutions/Hands Free through RFID*, www.mobileaspects.com (2008) 1 page.
 Mobile Aspects, Inc., "iRISite.TM.," *File Aspects/Solutions/IRISite*, www.mobileaspects.com (2008) 1 page.
 Mobile Aspects, Inc., "iRISMed.TM.," *File Aspects/Solutions/IRISMed*, www.mobileaspects.com (2008) 1 page.
 Mobile Aspects, Inc., "iRISupply.TM.," *File Aspects/Solutions/IRISupply*, www.mobileaspects.com (2008) 1 page.
 Mobile Aspects, Inc., "iRISynergy.TM.," *File Aspects/Solutions/IRISynergy*, www.mobileaspects.com (2008) 1 page.
 Mobile Aspects, Inc., "Supporting the needs of the surgical specialty environment automating inventory management with RFID-enabled technology" (2007) 2 pages.
 Multiple Antenna Reader System (MARS), MARS-24 (2007) 2 pages).
 Nalepa, D., "Inventory management and recall capabilities with RFID technology," *Cath Lab Digest*, (2007) 15(3):40-42.
 WinWare, Inc., "Winware releases the Accu-Cab RFID inventory management storage cabinet," Jun. 23, 2006, 1 page.
 WinWare, Inc., CribMaster—AccuCab RFID, RFID Point of Use Dispensing "CribMaster Accu-Cab" brochure, 1 page.
 Australian Patent Office Examination Report for Application No. 2002211769 dated Mar. 31, 2006 (2 pages).
 Australian Patent Office Examination Report for Application No. 2003217534 dated Sep. 7, 2006 (2 pages).
 Canadian Patent Office Action for Application No. 2,474,183 dated Sep. 25, 2009 (3 pages).
 Chinese Patent Office Action for Application No. 03804323.8 dated Dec. 12, 2008 (7 pages), translation only.
 Chinese Patent Office Action for Application No. 03804323.8 dated Sep. 11, 2009 (7 pages).
 European Patent Office Supplementary Partial European Search Report for Application No. 03713485 dated Apr. 13, 2006 (5 pages).

(56)


References Cited


OTHER PUBLICATIONS

International Preliminary Report on Patentability for Application No. PCT/US01/32230 dated Aug. 9, 2002 (4 pages).
 International Search Report for Application No. PCT/US01/32230 dated Dec. 28, 2001 (3 pages).
 International Search Report and Written Opinion for Application No. PCT/US2008/056981 dated Sep. 4, 2008 (9 pages).
 Japanese Patent Office Action for Application No. 2007-061714, translation only (drafted Sep. 9, 2009) 4 pages).
 Korean Patent Office Action for Application No. 7013101/2004 dated Nov. 21, 2006 (6 pages).
 Russian Decision on Grant of Russian Patent Application No. 2004128075, translation (8 pages).
 Russian Patent Office Action for Application No. 2008111640 with response due Oct. 2, 2009 (3 pages) translation only.
 Singapore Patent Office Examination Report for Application No. 200403954-1 dated Jun. 26, 2008 (4 pages).
 United States Patent Office Action for U.S. Appl. No. 09/981,219 dated Apr. 9, 2003 (16 pages).
 United States Patent Office Action for U.S. Appl. No. 10/080,330 dated Jun. 5, 2003 (14 pages).
 United States Patent Office Action for U.S. Appl. No. 10/080,330 dated May 5, 2004 (5 pages).
 United States Patent Office Action for U.S. Appl. No. 10/209,348 dated Oct. 15, 2004 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/795,386 dated Jul. 3, 2006 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/795,386 dated Apr. 13, 2007 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/795,386 dated Dec. 22, 2006 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Dec. 10, 2008 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Jan. 22, 2008 (6 pages).
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Jul. 2, 2008 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Jun. 10, 2009 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Jun. 8, 2006 (11 pages).
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Mar. 14, 2007 (11 pages).
 United States Patent Notice of Allowance for U.S. Appl. No. 10/870,938 dated Aug. 10, 2006 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/870,946 dated May 31, 2006 (11 pages).
 United States Patent Office Action for U.S. Appl. No. 10/870,946 dated May 1, 2007 (13 pages).
 United States Patent Office Action for U.S. Appl. No. 10/870,946 dated Oct. 15, 2007 (14 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Apr. 29, 2008 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Aug. 15, 2006 (10 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Aug. 28, 2009 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Feb. 24, 2006 (6 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Feb. 7, 2007 (9 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Jul. 12, 2007 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Mar. 12, 2009 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Nov. 13, 2007 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/874,264 dated Oct. 2, 2008 (8 pages).

United States Patent Office Action for U.S. Appl. No. 10/953,368 dated Jan. 8, 2008 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/953,369 dated Nov. 17, 2005 (5 pages).
 United States Patent Office Action for U.S. Appl. No. 10/953,369 dated Apr. 17, 2006 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 10/953,369 dated Mar. 29, 2007 (5 pages).
 United States Patent Office Action for U.S. Appl. No. 10/953,390 dated Jun. 1, 2006 (11 pages).
 United States Patent Office Action for U.S. Appl. No. 10/953,390 dated Feb. 14, 2007 (11 pages).
 United States Patent Office Action for U.S. Appl. No. 10/953,390 dated Sep. 5, 2007 (9 pages).
 United States Patent Office Action for U.S. Appl. No. 10/953,390 dated Nov. 15, 2007 (7 pages).
 United States Patent Notice of Allowance for U.S. Appl. No. 10/954,612 dated Mar. 10, 2006 (5 pages).
 United States Patent Notice of Allowance for U.S. Appl. No. 10/954,612 dated Aug. 25, 2006 (5 pages).
 United States Patent Notice of Allowance for U.S. Appl. No. 10/954,612 dated Aug. 14, 2007 (5 pages).
 United States Patent Notice of Allowance for U.S. Appl. No. 10/954,612 dated Oct. 29, 2007 (5 pages).
 United States Patent Office Action for U.S. Appl. No. 10/954,612 dated Dec. 11, 2007 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/954,612 dated Apr. 16, 2008 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/954,612 dated Oct. 20, 2008 (6 pages).
 United States Patent Office Action for U.S. Appl. No. 11/247,253 dated Apr. 15, 2008 (8 pages).
 United States Patent Office Action for U.S. Appl. No. 11/247,253 dated Dec. 31, 2007 (6 pages).
 United States Patent Office Action for U.S. Appl. No. 11/247,253 dated Feb. 7, 2007 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 11/247,253 dated May 24, 2008 (6 pages).
 United States Patent Office Action for U.S. Appl. No. 11/381,849 dated Apr. 23, 2009 (30 pages).
 United States Patent Office Action for U.S. Appl. No. 11/381,849 dated Aug. 4, 2009 (3 pages).
 United States Patent Office Action for U.S. Appl. No. 11/381,849 dated Nov. 28, 2008 (17 pages).
 United States Patent Office Action for U.S. Appl. No. 11/381,849 dated Oct. 19, 2009 (34 pages).
 United States Patent Office Action for U.S. Appl. No. 11/559,231 dated Oct. 19, 2009 (17 pages).
 United States Patent Office Action for U.S. Appl. No. 11/687,272 dated Apr. 17, 2009 (10 pages).
 United States Patent Office Action for U.S. Appl. No. 11/979,124 dated Jun. 18, 2009 (9 pages).
 Written Opinion for International Application No. PCT/US03/04653 dated Nov. 10, 2004 (4 pages).
 European Patent Office Summons to Attend Oral Proceedings for Application No. 01979848.7 dated May 12, 2010 (3 pages).
 United States Patent Office Action for U.S. Appl. No. 12/694,361 dated Aug. 2, 2010 (7 pages).
 United States Patent Office Action for U.S. Appl. No. 10/862,456 dated Jun. 18, 2010 (8 pages).
 European Patent Office Decision to Refuse and Copy of Minutes for Application No. 01979848.7 dated Dec. 1, 2010 (27 pages).
 United States Patent Office Notice of Allowance for U.S. Appl. No. 12/508,758 dated Feb. 4, 2011 (4 pages).
 United States Patent Office Notice of Allowance for U.S. Appl. No. 10/862,456 dated Nov. 19, 2010 (5 pages).
 United States Patent Office Notice of Allowance for U.S. Appl. No. 12/694,361 dated Dec. 30, 2010 (4 pages).
 United States Patent Office Action for U.S. Appl. No. 12/759,510 dated Dec. 27, 2010 (10 pages).

* cited by examiner








Fig. 3





Fig. A






Fig. 6




Fig. 11




Fig. 13






Fig. 12








Fig. 10





Fig. 11






Fig. 15




Fig. 19




Fig. 16




Fig. 17





Fig. 18






Fig. 21




FIG. 2A





Fig. 23



**RF POINT OF SALE AND DELIVERY
METHOD AND SYSTEM USING
COMMUNICATION WITH REMOTE
COMPUTER AND HAVING FEATURES TO
READ A LARGE NUMBER OF RF TAGS**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

RELATED APPLICATIONS

This application is a continuation reissue of application Ser. No. 14/602,694 filed Jan. 22, 2015 which is an application for reissue of U.S. Pat. No. 8,025,228 which issued on Sep. 27, 2011 and was filed on Oct. 31, 2007. U.S. Pat. No. 8,025,228 is a continuation of application Ser. No. 10/954,612 filed Oct. 1, 2004 (now U.S. Pat. No. 7,661,591), which is a continuation of application Ser. No. 10/080,330 filed Feb. 21, 2002 (now abandoned), which is a continuation-in-part of application Ser. No. 09/981,219 filed Oct. 16, 2001, (now U.S. Pat. No. 7,258,276), which claims the benefit of U.S. Provisional Application No. 60/241,907 filed Oct 20, 2000.

Notice: more than one reissue application has been filed for U.S. Pat. No. 8,025,228 which issued on Sep. 27, 2011 and was filed on Oct. 31, 2007. The present application is an application for reissue of U.S. Pat. No. 8,025,228 which issued on Sep. 27, 2011 and was filed on Oct. 31, 2007. The present application is also a continuation reissue application of application Ser. No. 14/602,694 which was filed Jan. 22, 2015. Application Ser. No. 14/602,694 which was filed Jan. 22, 2015 is an application for reissue of U.S. Pat. No. 8,025,228 which issued on Sep. 27, 2011 and was filed on Oct. 31, 2007.

BACKGROUND OF THE INVENTION

The present invention relates to methods and systems for distributing products to customers. More particularly, the invention relates to a system that tracks the use of products using radio frequency (“RF”) tags and provides information to a central computer to enable automated restocking, inventory, tracking, or reordering of the products.

A variety of paper-based, electronic, and Internet ordering systems are available and in use today. In addition, a number of inventory tracking systems, including systems that use bar coding are also in use. Beyond bar codes, it has been proposed that inventory tracking can be accomplished using RF tags. However, commercially acceptable RF systems, particularly systems that are able to track hundreds of items in relatively small areas, have not yet been developed. Furthermore, commercially acceptable integrated systems that allow consumers to order and receive goods at a location proximate to where the goods are used and that also automatically, and with limited human intervention, track usage and initiate reordering are also not available.

SUMMARY OF THE INVENTION

Accordingly, there is a need to improve the distribution and tracking of goods so that consumers experience distribution of goods at a location proximate to where the

consumer will use the goods without requiring paper or computer ordering. There is also a need for a distribution system that is able to track numerous RF tagged items positioned in relatively small areas or volumes.

The invention provides a system and method where a user need only find the product of interest and take that product. As compared to most Internet-based systems and methods, the invention is “clickless.” In other words, the invention requires little or no manual input from users. The invention provides a system for distributing a plurality of products. Each of the products has a radio frequency (“RF”) tag. As used herein, radio frequency means electromagnetic radiation that lies between audible and infrared radiation, including microwave radiation. Each tag is encoded with a unique identifying code. In one embodiment, the system is accessed by individuals possessing a radio frequency user badge with an identifying code. Alternatively, the system could rely on magnetic swipe cards, password systems, biometric devices (such as a retinal scanner, thumb or finger print reader, voice identification unit, or the like), bar code cards, or other systems for limiting access to authorized individuals.

The system includes one or more cabinets, refrigerators, similar storage units, (generically referred to as “micro-warehouses”) or even secured rooms that are stocked with the RF tagged products and accessed by individuals through one of the mechanisms described above. In one embodiment, each micro-warehouse defines an RF cavity, has a door that may be equipped with a lock (such as an electric-actuated lock), an antenna or antenna array mounted on or in the micro-warehouse, a client controller (or similar programmable device) coupled to the lock and the antenna, a badge or key reader, and an output or user-feedback device such as a light, audio device, or display. Using a signal from the badge or key reader, the client controller checks the identity of the individual accessing the micro-warehouse, such as by reading the code of the user badge. The user feedback device is then activated to indicate whether the individual attempting to access the micro-warehouse is authorized to access the unit. If the code or other identifier matches stored records of authorized users, the client controller opens the door and the user may remove desired products from the micro-warehouse. Once the user closes the door (and in some embodiments, the door is locked), the client controller performs a scan of the products remaining in the micro-warehouse to determine the identity of each of the products. The client controller then generates a message including the identity of each of the products or other message related to the products taken. That message or a second message based on the first is sent to a server. The server tracks product and user information automatically, that is, without relying on user input. The server also generates orders for products taken from the micro-warehouse by the user. The server can be programmed to automatically place those orders. This eliminates the need for the customer to re-order consumed items.

Alternatively, the system can operate like a vending machine, but with the product exit chamber, the area behind a door through which a user reaches for the product after it has fallen from its storage area, arranged as the RF cavity. Tags on products that fall into the pick up area can be read before or as the user picks them up.

Each user badge may also include billing information and form-of-payment information in addition to having identification information. As should be apparent, billing information could take the form of the entity to be billed, which may or may not be the individual associated with the tag.

Form-of-payment information may include account information, credit card information, or the like.

In one embodiment, an array of antennas is positioned within the door of each MW. Each antenna may have a transmission line of sight and be configured to emit a signal at one or more predefined frequencies. The antenna array generates an electromagnetic field within the MW. The products are positioned in one or more bins, compartments, or similar devices located within the MW. Preferably, the electromagnetic field is altered within the cavity defined by the micro-warehouse through the use of reflectors or devices that move the antennas within the array. In one embodiment, material that is reflective to RF signals is placed near the door/cabinet gap to prevent the escape of RF energy. This helps reduce accidental reading of tags outside the MW but near the gap, and exposure of people and things outside the MW to RF radiation.

In one preferred embodiment, tagged products are positioned such that each tag on each product is organized in an orderly fashion such that 1) the likelihood of a tag being shadowed by an RF absorbing substance within the cavity is reduced, 2) the likelihood of one tag sharing energy with another due to too close proximity is reduced, and 3) the orientation of the tags located in the fringe RF areas, and in the nulls of the cavity, increases the RF cross-section and energy absorbency of each such tag. Some of the above three desirable characteristics may be achieved by placing the tags such that they are generally orthogonal to the transmission line of sight (as opposed to being positioned generally parallel) of at least one antenna within the array. In addition, at least two of the plurality of products may be spaced a distance from each other such that energy sharing is reduced. ("Energy sharing" is a phenomenon where one or more tags positioned in close proximity share energy from an electromagnetic wave traveling through the volume such that one or more of the tags fails to receive sufficient energy to be energized and, therefore, fail to emit an identifying signal.) In one form of the invention, the distance is based on the wavelength of the signal(s) from the antenna array and is a fraction thereof. In one preferred embodiment, the distance is about 3 to about 6 cm.

It is also preferable that each tag have the ability to cloak itself for a predetermined amount of time. The amount of time may be in a range that is based on the maximum number of tags in the micro-warehouse and the temperature of the tags. In one embodiment, this time is about 1-5 seconds when the tagged products are stored at a temperature of -20° C. However, the amount of time is variable and depends on the temperature inside the MW, the tag type, the tag transmission algorithm, and the existence or not of a wake or decloak function. The cloaking time is selected to allow de-cloaking such that another scan can be done within an algorithmically acceptable time period.

A controller (often referred to as a "client controller") is coupled to the antenna array and is operable to control the antenna array such that a series of scans or runs are performed. In a preferred embodiment, the controller is operable to perform a baseline run, an inventory run, and a background run. The controller generates messages indicative of changes in the presence of tagged items within the micro-warehouse and stores those messages in a queue or buffer. The controller also calculates an integrity value, compares that value to a predetermined integrity value, and reports the comparison in the message.

As is apparent from the above, it is an advantage of the present invention to provide a method and system of inventorying and distributing products. Other features and advan-

tages of the present invention will become apparent by consideration of the detailed description and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a schematic illustration of a system embodying the invention.

FIG. 2 is a schematic diagram of servers and a client device used in the system shown in FIG. 1.

FIG. 3 is a schematic illustration of fulfillment, inventory, and other information flow among components in the system shown in FIG. 1.

FIG. 4 is a schematic illustration of a system embodying the invention.

FIG. 5 is a schematic illustration of information flow among components of the system shown in FIG. 4.

FIG. 6 is a perspective view of an exemplary micro-warehouse in the form of a freezer.

FIG. 7 is a cross-sectional view of the door of the micro-warehouse shown in FIG. 6.

FIG. 8 is a cross-sectional view of a door of a micro-warehouse configured according to another embodiment of the invention.

FIG. 9 is a perspective, partially phantom view of a chest capable of holding multiple drawers suitable for use in the micro-warehouse of FIG. 6 and a drawer.

FIG. 10 is a schematic diagram of a control system used in a micro-warehouse.

FIG. 11 is a diagram of an exemplary embodiment of the control system shown in FIG. 10.

FIG. 12 is a schematic diagram of electromagnetic fields within a micro-warehouse.

FIG. 13 is a perspective view of an exemplary packaged product illustrating possible locations for RF tags on the product.

FIG. 14 is a flowchart of software used in one embodiment of the invention.

FIG. 15 is a flowchart of software of one embodiment of the invention.

FIG. 16 is a flowchart of software of one embodiment of the invention.

FIG. 17 is a flowchart of software of one embodiment of the invention.

FIG. 18 is a flowchart of software of one embodiment of the invention.

FIG. 19 is a flowchart of software of one embodiment of the invention.

FIG. 20 is a flowchart of software of one embodiment of the invention.

FIG. 21 is a graph of product tag read times versus the number of tagged products in a micro-warehouse.

FIG. 22 is a flowchart of software of one embodiment of the invention.

FIG. 23 is a flowchart of software of one embodiment of the invention.

FIG. 24 is a flowchart of software of one embodiment of the invention.

DETAILED DESCRIPTION

Before embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of the construction and the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is

capable of still other embodiments and of being practiced or being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

FIG. 1 illustrates an exemplary system **25** embodying the invention. The system **25** includes two servers (maintenance and commerce) **26** and **27** that create and maintain user lists, perform inventory, account, ordering functions, and monitoring functions, such as micro-warehouse status, monitoring temperature, and other faults. Servers **26** and **27** may communicate with a client (and, more particularly, a computer or similar device such as the controller in a micro-warehouse (“MW”) discussed below) using standard protocols such as TCP/IP, UDP, or other protocols over a network **28**. The network **28** may be the Internet, a telephone network, a wireless network, power line carrier (“PLC”) network, or other type of network and combinations thereof. In the embodiment shown, servers **26** and **27** include standard hardware and operating system software (not shown). Running on top of the hardware and operating system software is a MW enterprise application **29**. The MW enterprise application **29** accesses a profile database **30** that includes a registration module **31**, an order history module **32**, an account set-up module **33**, and a stock request module **34**. Each of the modules **31-34** is maintained for each client coupled to the server **27**. The modules may be configured with web content designed to be accessible by a system administrator using protocols for the World Wide Web section of the Internet.

As best seen by reference to FIG. 2, the MW enterprise application **29** performs numerous functions. Broadly, the MW enterprise application **29** controls the administration of the radio frequency identification (“RFID”) badges or other user badges or keys (discussed below), manages communication sessions with clients connected to the server **27**, maintains an inventory of products for each client connected to the servers **26** and **27**, checks inventory of MWs, and in some embodiments, other MWs local to the specific MW of interest, before ordering a product, manages security of communications, provides system administration functionality, and monitors and maintains the health of clients connected to the servers.

The registration module **31** (FIG. 1) provides part of the inventory functionality of the server **27** by providing access to information regarding the location of clients connected to the server **27**. In one embodiment of the invention, the clients take the form of MWs. The registration module also provides access to information regarding sales persons assigned to a particular MW and the identification, location, and similar information for each MW. The registration module **31** may access a MW database **34A**.

The order history module **32** provides a history of orders for each MW **36** and product preferences for each MW **36**. The account set-up module provides administrative screens for payment authorization, user information, and similar information. The stock request module **34** controls inventory replenishment based on usage and on specific customer requests and similar information.

The server **27** also accesses a commerce engine **35** that uses information received from a client (or MW) to generate orders that are delivered to a fulfillment infrastructure (not shown). The fulfillment infrastructure produces products to be distributed using the system and method of the invention. The information may be used by a manufacturing infrastructure and marketing, customer relation management (“CRM”), billing, and other systems and functions (all not

shown). For example, the invention may be used in the distribution of life science research products such as enzymes, assays, cloning vectors, competent cells, and the like. (Of course, a wide variety of non-biological products could be distributed using the invention.) The information provided by the server **27** is used in the manufacturing infrastructure to ensure proper production of products according to the demand for such products. As noted above, the server **27** may be coupled to a plurality of clients or MWs. An exemplary client in the form of the MW **36** is shown in FIG. 1. While only one client is shown, the number of clients connected to the server **27** is limited only by the server’s internal capacity and the capacity of the network **28**.

The MW **36** may take the form of a refrigerated cabinet, a freezer, or other storage container. A secured storeroom, similar location, or other defined area could also be outfitted with a client controller and other components, as described herein, and be used to store products. In the embodiment shown, the MW **36** includes a door **37**. While it is preferred, it is not required that the MW **36** have a door. Devices (such as light curtains) that sense when access to the interior of the MW is being attempted may also be used. As noted, in another embodiment, the system may utilize a defined area to enclose the tagged products rather than a cabinet. The defined area uses an access point (not shown) to serve as its entryway. The products within the area are fitted with identification tags and specifically positioned in the area to be read by a RF inventory interrogator (such as a controller **45** and antenna array (discussed below)). Product scans begin when a sensor (such as, e.g., a proximity sensor) senses a user passing through the access point. The access point is controlled by a processor, such as the client controller **45**, and is able to control doors, portals, alarms, or other mechanisms to restrict access to the area and products.

As shown, the MW **36** may also include an electric actuated lock **39**, a proximity sensor **40**, and a user feedback or, more generally, an output device that may take the form of an audio device or light **41**. Other output devices such as a voice synthesis device, a display screen, and the like may also be used. The MW **36** is configured with an antenna array **43**. The antenna array **43** is coupled to the client controller **45**. In one embodiment, the invention may include an antenna array with six vertically or circularly polarized antennas. The antenna array **43** is a RF receive and transmit system that communicates with transponder devices or tags (discussed in greater detail below). In one embodiment, each tag is a passive tag and powered by energy from the antenna array **43**.

The MW **36** may include a specialized badge or card reader **47** (generically a “key reader”) in the form of a magnetic card swipe device, an antenna, a fingerprint reader, or similar device. The reader **47** is coupled to the client controller **45** via a communication link **49**. The MW **36** may also include internal and ambient temperature sensors **55** and **56**. The temperature sensors **55** and **56** are coupled to the client controller **45** to provide temperature information to the client controller. Additional information may be provided to the client controller through optional input devices. The location of the MW **36** may be monitored by a global positioning system (GPS) device (not shown) plus inertial frame recognition for fine measurement and for interpolation between GPS satellite acquisitions. Motion and shock of transport may be monitored with an accelerometer (not shown). The voltage, current, and other characteristics of electrical supply lines may be monitored and provided to the client controller **45** by a power-line-monitoring device (also not shown). The on/off duty cycle of the current supplied to

the refrigeration compressor can be used, with the internal and ambient temperatures, to indicate the relative health of the compressor. Additional input devices, such as cameras, microphones, sensors, etc., could be coupled to the client controller to monitor environmental and other conditions.

A smartcard reader (not shown) may also be coupled to the controller **45**. A smartcard, in addition to identifying the customer for admittance purposes, can contain a preloaded monetary equivalent that can be debited at the time of door closure for any products taken during the door open session.

The client controller **45** includes software to carry out several functions that are discussed in greater detail below. If desired, the client controller **45** may be a consumer grade device, such as a Palm Pilot® personal digital assistant, Packet PC device, or a personal computer, modified according to the teachings herein. Depending on the hardware used, the client controller **45** may be configured with a graphical user interface (“GUT”) to facilitate interaction between the system **25** and its users.

The client controller **45** includes software (discussed below) which may interrogate the RF tagged products within the MW **36**. The interrogation process involves sending signals from antennas and receiving signals from passive, transponder RFID tags. Preferably, interrogation is accomplished in such a way as to eliminate or reduce interference problems that are typically associated with reading RF signals from multiple devices. The system **25** could also be implemented with active tags (not shown), although presently available active tags need to be improved so as to perform in the temperatures that the embodiments of a system for distribution of life science research products are expected to operate within and at roughly the same cost and power consumption.

In one embodiment of the system **25**, one or more RFID access badges **75** (FIGS. **1** and **3**) are generated. Preferably, the RFID badges **75**, as well as the other RFID tags (discussed below) are passive transponder tags. Preferably, the RFID badges **75** are encoded with unique identifying information from the account set-up module **33** based on digital signatures. In addition, it is preferred that the digital signatures encoded on the RFID badges **75** used by restocking services provide one-time access to a specific MW, and thereafter expire, and be disposable. One-time access badges may be set to expire after a certain amount of time or at a set time. However, the badges **75** may also take a form that can be enabled again for one-time access at the next restocking event. The RFID access badges may be fixed on a carton of products **80** (FIG. **3**). Alternatively, they may be delivered separately to the facility where the MW of interest is located. Alternatively, they may be the badges of field personnel or designated on-site authorized support personnel.

As best seen by reference to FIG. **3**, the carton of products **80** includes a plurality of individual products **90** each with an identification tag **95**. Each identification tag **95** may be structurally the same as an RFID badge **75**, but coded with different information and configured such that the digital signature on tag **95** will generally not expire. In one form of the invention, each tag **95** has a 16-bit group identification code and a 32-bit item identification code. The 16-bit group identification code may be programmed with information such as the manufacturer or distribution channel of the product. The latter allows routing of the transaction involving a product to the proper enterprise system. The 32-bit item identification code is used to provide descriptive information regarding the product such as serial number, product

type, date, lot number, and similar information, or a unique ID, which corresponds to such information in a database on a server.

Once all the products **90** have been fitted with unique RFID tags **95**, the products may be shipped in the carton **80** to a designated MW such as the MW **36**. The carton **80** is packed according to a fulfillment request that is based on either an initial order from a customer (not shown) or MW specific business rules followed by the server **27**. The carton **80** may be fitted with RFID access badge **75** or the RFID access badge **75** may be shipped separately to the location of the MW of interest. If fitted with an RFID access badge **75**, the carton **80** may be shipped by a delivery service contracted to deliver the package to the MW **36**. Once the carton is delivered, the recipient or user may use the RFID access badge **75** to open the door **37** of the MW **36** by passing RFID access badge **75** in front of the reader **47**. Client controller **45** reads the digital signature of the RFID access badge **75** and confirms reading of the code by actuating a user feedback device such as a voice synthesis module or the light **41**. Since, the server **27** provides a locally based user list to the client controller **45**, the client controller **45** oversees authentication of the digital code read from the RFID access badge **75**. Client controller **45** checks the authenticity of the read code by matching the code to the user list. Client controller **45** may then optionally read the temperature sensors **55** and **56** and transmit temperature information to the server **26**. If used, the temperature sensors **55** and **56** are preferably read on a periodic basis, with the temperature information being transmitted to the server **26** each time the temperature is read. Client controller **45** can also be programmed to transmit temperature data if the internal temperature falls beneath or above a predetermined range. In many instances, it will be important to ensure that the temperature of the MW is within an appropriate range to store the products **90**. If the temperature of the MW **36** is within an appropriate range, and the user is authenticated, the client controller **45** then actuates the lock **39** to open the door **37** (of course, the MW need not be equipped with the lock **39**). If the temperature of the MW **36** is not within an appropriate range, then access to the MW **36** may be prevented by maintaining the lock **39** in a closed state. This allows a refrigeration unit (not shown) associated with the MW **36** to cool the interior space of the MW **36** to a desired temperature before ambient air is allowed into the MW **36** by opening of the door. This also provides for product **90** integrity during a power failure.

Once the door **37** opens (which may be sensed by the proximity sensor **40**), or access to the interior of the MW **36** is gained, a communication session between the MW **36** and server **27**, which may be segmented based on appropriate events to optimize user response and network usage, begins. Having full access to the MW **36**, the employee of a carrier or logistic service (such as UPS, Airborne Express, etc.) who delivered the carton **80** now proceeds to place the individual items **90** into the MW **36**. Once the carton of products **80** is empty, the delivery employee then closes the door **37**, and removes the carton, if necessary. The proximity sensor **40** senses the closing of the door **37**. The client controller **45** senses the status of the sensor. Preferably, the lock **39** (if used) resets automatically after being unlocked for a predetermined time, for example five (5) seconds. The user has that predetermined time to open the door. Power to the antenna array **43** is disabled once the door **37** opens. When the door **37** closes or access is prohibited, a scan of the products **90** placed within the MW **36** is performed. Upon completing the scan, the client controller **45** sends a change-

in-inventory message 100 to the commerce server 27. To ensure integrity of the inventory change billed to the customer, the client controller 45 employs an integrity algorithm when the MW 36 is scanned. The algorithm is based on statistical information, historical information, and other factors including RF algorithms and delay data.

As will be explained further below, it was found, for one embodiment, that to accurately determine the number of tagged items in a MW 36 (i.e., to provide acceptable integrity in the system), it is best to scan the tagged items multiple times. Further, in the embodiment where the MW takes the form of a freezer, refrigerator, or other cabinet, achieving integrity generally requires choosing a superset of tagged items from all scans as well as noting the set that represents the majority set (over 50%) of the scans, the number of scans in non-cloaked mode (which may be an empirical number, found to be ten for the MW 36 illustrated in FIG. 6), and the number of scans in the cloaked mode (which for the same embodiment was empirically found to be three). To achieve greater system integrity (which in one embodiment is no more than one error in five-thousand tagged items), information from scans or interrogations is held on the server 27 for a predetermined amount of time (e.g., twenty-four hours). During this time, and while the subject MW is not being accessed by a customer, the controller 45 performs background inventory checks. The background inventory checks are used to increase the inventory sample population data set to statistically significant levels whose cross section corresponds to the 1 in 5000 level. Preferably, any anomalies found are sent to the server 27 where they are used to modify information held on the server 27.

The MW 36 may be accessed by a customer at the MW location using a separate RFID badge 75 (or other identifying badge or key) shipped directly to that customer. Alternatively, and as noted above, the reader 47 may be configured as a smartcard, a magnetic card swipe device, a barcode device, a fingerprint reader, or some similar device that controls access to the MW 36. Regardless of its exact configuration, the reader preferably reads the badge or key, compares the ID information contained in the key with the list of authorized users stored in the client controller 45, and if the user's key matches one of those authorized, the client controller 45 acknowledges authorization by generating an output such as by lighting the light 41. The list of authorized users is sent to the client controller 45 and updated as needed by the server 26. The server 26 may be configured with the capability to authenticate a user's key as well. Once authentication takes place, the client controller 45 then opens the door 37 allowing the customer or user to access the interior of the MW 36. The customer then removes one or more products 90 from the interior of the MW 36 and then closes the door 37. Once the door is closed, client controller 45 scans the products 90 in the MW 36 and sends an inventory message identifying the missing or added products 90 to the server 27. The server 27 compares the previous inventory prior to opening to the current inventory. From the comparison, the server 27 determines the missing or added items in the MW 36. The inventory information is then communicated to the commerce engine 35, which preferably stores the information for future use for both marketing and inventory functions. Receipts for the used products can then be sent via electronic mail or printed and shipped via regular mail to the customer at the MW location. Invoicing can also occur using other electronic and nonelectronic communication mechanisms.

The inventory message can be used for other purposes as well. For example, the inventory message includes information regarding individual products 90. Therefore, the amount of time a particular product 90 spends in any MW 36 may be recorded by the server, as well as the product's temperature history. If time is recorded, it is also possible to compare the amount of time any particular product 90 spends in a MW 36 to a shelf life or acceptable usable life for that product. Temperature history can also be stored and compared to other data. If the shelf life is passed, then an expiration message, such as a pick list, may be generated and sent to the MW 36 or an electronic mail address of a user of the system to inform the user that certain products should be removed from the MW 36 and not used. Temperature history and time sent by the MW 36 to the server 27 may also be used to calculate a "storage-degree-day" value to for each product 90 in the MW 36. This value may, in turn, be used to make an activity projection and expiry threshold for the subject products 90. The administrator of the MW 36 may then use this information to remove expired products from the MW 36.

In yet another implementation, the inventory message may be used to determine the type of products 90 in the MW 36. If any of the products present within the MW 36 are subject to a recall by the manufacturer, the MW 36 may be placed in a "lock down" condition, whereby access to the MW 36 is denied until an administrator or other authorized individual removes the recalled product or otherwise addresses the situation. In addition to its use to protect against the use of recalled products, the lock down feature is useful for controlling the distribution of potentially spoiled or degraded products and other products where exacting product specifications and quality controls are desired, such as pharmaceutical products and controlled substances.

FIGS. 4 and 5 illustrate additional features of the system 25. As shown in FIG. 4, the system 25 may be implemented such that the MW 36 communicates with a telephone system or similar access point 105 through a wireless communication link 107. The access point 105 may be connected to a network service provider such as an Internet service provider ("ISP") 110. The service provider 110 may provide a connection to the network 28 (which is shown as the Internet in FIG. 4). FIG. 5 provides additional details concerning the exemplary fulfillment infrastructure noted above. Servers 26 and 27 may be configured in a cluster 112 with a middleware server 114, which in one form of the invention takes the form of an extensible markup language ("XML") middleware server 114. The cluster 112 is protected by a firewall 116 and communicates with an enterprise computer 118 (such as a mainframe) which may run various enterprise resource planning ("ERP"), CRM, manufacturing, and other business process programs. The enterprise computer 118 communicates with an enterprise database 120, which is also accessible by the server 27. It should be understood that the cluster 112 may consist of any number of hardware or software servers and that the exact configuration may be modified depending on how the invention is implemented. In general, it is possible to combine functionality on one server or to separate out operations and functionality on multiple servers beyond those shown and described herein.

In the embodiment shown, information received from tagged items 90 within each MW 36 is sent to the web cluster 112, particularly the server 27, in an XML format. The XML formatted messages are transferred from the server 27 to the middleware server 114, which hosts XML middleware 120 (FIG. 5) such as Biz Talk® software. The

XML software **120** communicates with other software/systems such as ERP system **124**, web ordering system **126**, an RFID badge, key, or passkey administration system **128**, and a MW administration system **130**. The ERP system **124** may be configured to assign RF tags **95** to selected products or lots of products; assign identities to each MW **36**; handle inventory planning; handle re-supplying of MWs; and handle sales orders. The web ordering system **126** may be configured to process customer order inquiries; inventory inquiries; passkey updates; and purchase order updates.

FIG. **6** illustrates an exemplary micro-warehouse in the form of a freezer **230**. In the embodiment of the invention described and illustrated, components are tuned to work efficiently in a micro-warehouse having a volume of about five cubic feet (about 142 liters) and that can hold hundreds of RF tagged items. However, other embodiments are possible, including, for example, a 21 cu. ft. (about 425 liters) freezer and a 15 cu. ft. (about 595 liters) room temperature hospital supply cabinet. The freezer **230** includes a housing **232** with an opening **234** and an interior **235**. A door **236** is attached to the housing **232** such that the door **236** can be closed to occlude the opening **234** and opened to provide access to the interior **235** of the freezer **232**. A number of shelves **238** are positioned within the interior **235**. Each shelf **238** may hold one or more cabinets **240**. Each cabinet **240** may include one or more drawers **242**. Each drawer **242** may hold multiple packaged products (discussed below). Products, particularly larger products, may also be positioned within a bin **244**. The package dimensions of larger products often create a desirable separation of tags (which, as discussed below, reduces energy sharing).

The freezer **232** can be constructed using a standard freezer modified and equipped as described herein. For example, the door **236** may be constructed from a door provided with a standard freezer. Insulation in the standard door is removed or otherwise formed or positioned and various components needed to scan RF tags on products stored within freezer **230** (e.g., in the drawers **242** in the cabinets **240**) are added. The freezer **230** may be equipped with a strip (not shown) of RF reflective material positioned around the perimeter of opening **234** to prevent or reduce the escape or leakage of RF energy.

As best seen by reference to FIGS. **6** and **7**, the door **236** includes a front panel **250**, which in one embodiment has curved sides such that a cavity or depression **252** is formed by the panel **250**. Insulation **254** is positioned within the depression **252**. Near the center of the panel **250** the insulation **254** is hollowed out or otherwise formed or positioned such that a controller **256** (discussed further below) may be positioned within the door **236**. A second portion of the insulation **254**, near one corner of the panel **250**, is also hollowed out or otherwise formed or positioned such that a badge or key reader **258** or similar device may be positioned within the door **236**. The insulation **254**, the controller **256**, and the key reader **258** are maintained within the depression **252** by a mounting plate **260**. Preferably, the mounting plate **260** is made from metal. The mounting plate **260** supports an array of antennas **261**. In one preferred embodiment, the array of antennas **261** includes antenna **262**, antenna **263**, antenna **264**, antenna **265**, antenna **266**, and antenna **267**. (FIG. **6**). Although six antennas are shown, the number and positioning of the antennas within the door **236** is dependent on a variety of factors, such as antenna gain, beam shape and directionality, transmitted power, RF cavity geometry, reactivity and reflectivity, convenience of location, distance from transmitter, cost, antenna-antenna interference, effective use of antenna beam volume, prevention of RF energy escape

from cavity, antenna size and shape, antenna-tag orientation, antenna multiplexing pattern, and other factors. Thus, the invention is not limited to the array shown and other arrays could be used and may be more suitable for different micro-warehouses. The array of antennas **261** can also either singly, or in some combination, be rotated through a small arc by using one or more actuators or similar devices to shift the beam interference pattern or electromagnetic field in the RF cavity, for example, to mitigate any RF nulls or shadows. The antennas may also be activated at different times and patterns to shift the beam interference pattern or alter the electromagnetic field within the RF cavity.

The presence of shelves **238**, cabinets **240**, drawers **242**, products, and tags may affect the electromagnetic field within the freezer **230**. While most of the items just mentioned are preferably made from substantially RF transparent material, they nevertheless can block or diminish the strength of RF signals. Furthermore, the tags on the products and the products themselves are not made from RF transparent material and they may block or otherwise interfere with other tags receiving RF signals. These phenomena can be variously known as shadowing. The effects of shadowing may be reduced by positioning tagged products in the cabinets **240** and drawers **242**, bin **244**, or in other compartments, receptacles, or devices that can help provide separation.

The waves from each antenna and reflections off of the interior surfaces of the freezer **230** interact to create an electromagnetic field with many nulls (areas where waves combine to cancel each other such that there is insufficient energy to energize passive RF tags). The effects of nulls may be reduced by moving the field within the interior of the freezer **230** at a speed and with a pattern such that any nulls generated change position over time. Alternatively, this can also be done by changing the geometry of one or more reflective surfaces in the RF cavity, such as with an acute sawtooth pattern, or by adjusting the power to minimize internal reflected power, or by selection or variation of antenna power and frequency. In some cases, more than one of these alternatives is used. Preferably, reflectors such as the reflector **670** (FIG. **12**) are used. (As shown, the reflector **670** is positioned at the rear of the freezer **230**, but other placements within the freezer are also possible.) However, actuators, pivots, and other devices could be used to move the antennas **262-267** to generate many different interference patterns and alter the position of nulls in the interior **235** such that no tag is positioned at or within a null for any significant length of time. For example, as shown in FIG. **8** the antennas **262-267** could be mounted on pivots **269** and coupled to small, electrically or pneumatically powered actuators **270** located within the cavity **252** and mounted on the mounting plate **260**. Antennas suitable for use in at least some embodiments of the invention include Huber & Suhner model 2400/70/9/0/CP antennas, which are available from commercial sources. Preferably, the antennas **262-267** are protected by a RF-transparent radome **272**. The radome **272** also helps position the antennas **262-267** at desired locations along the door **236**. As will be discussed in greater detail below, the controller **256** sends and receives signals from the antennas **262-267**. Signals transmitted by the antennas **262-267** are used to excite passive RF transponder tags **270** (FIG. **13**) attached to products **272** (FIG. **13**) stored within the freezer **230** or applicable MW. In preferred embodiments, the products are in the drawers **242** of the cabinets **240** or bins (when larger products are stored). Signals generated by the transponder tags **270** are received by the antennas **262-267** and processed by the controller **256**.

Before discussing embodiments of the invention in greater detail, some premises of their design, particularly the designs shown in FIGS. 6 and higher, need to be addressed. First, for those embodiments implemented in a micro-warehouse, RF cavity considerations are important. Second, the particular embodiments described are designed to be compliant with Part 15 of the regulations issued by the United States Federal Communications Commission ("FCC"). Part 15 of the FCC regulations places limitations on antenna powers and frequencies that may be used in systems, such as the current one, where RF tags are scanned. In order to meet the requirements of Part 15 as well as the requirements of scanning numerous tags within a relatively small volume (or RF cavity), an antenna frequency in the GHz range (or microwave range) was chosen. In particular, the inventors discovered that a frequency of about 2.45 GHz was best suited for the applications discussed herein. Nevertheless, alternative embodiments of the invention could be configured to operate at different power ratings and frequencies (for example, MHz embodiments), as would be apparent to one of ordinary skill in the art after reviewing the designs and teachings set forth herein.

FIG. 9 illustrates an exemplary cabinet 240 used in the freezer 230. The cabinet 240 includes a top 280, a bottom 282, a rear 284, and sides 286 and 288. In the embodiment shown, the cabinet 240 includes four bays 290. Each bay 290 is configured to accept a drawer 242. Each drawer includes a pull knob 300 or similar device and a plurality of angled separators 302. The angled separators 302 define a plurality of slots 304 in which packaged products 270 with RF transponder tags 272 may be positioned. The separators 302 are configured to position products within the interior 235 of the freezer 230 such that tags 272 on the products 270 contained within any one drawer 242 are maintained at a minimum separation distance and, in one embodiment, in a generally orthogonal position with respect to the transmission line of sight of the antennas located most proximate to the subject drawer 242. Orthogonal positioning is not necessary, however. The purposes of spacing tagged products include reducing energy sharing among and between proximate tags such that each tag on each product within the freezer 230 is energized at its requisite level, which for one embodiment is a minimum of about 0.23 mW/cm². In the embodiment shown, the distance between the separators 302 may be based upon the frequency of the signals from the antennas 262-267. In particular, spacing corresponding to a fraction of, and in one preferred embodiment, approximately 1/2 of the wavelength of the 2.45 GHz excitation signal (approximately 3 to 6 cm) has been found to reduce energy sharing among the tags. Preferably, the smallest possible spacing is used and shorter separation distances than those specified have been found to be adequate in some circumstances, particularly where other parameters such as frequency, antenna power, and others are different from the particular examples provided herein.

Instead of drawers and cabinets, bins or similar items with separators could be placed directly on the shelves or surfaces within the freezer 230. In addition, in some applications, the impact of energy sharing may be reduced through the selection of frequency, RF power, and transponder design (mainly size) such that products can be placed in a random or haphazard manner within the freezer 230.

FIG. 10 schematically illustrates one exemplary embodiment of the architecture of the controller 256. The controller 256 includes a central processing unit or processor 400 that receives time signals (e.g., time of day) from a real-time clock 402. In one embodiment, the real-time clock is syn-

chronized periodically to a standard time reference, S such as the atomic standard clock at the National Institute of Standards ("NIST"), connected to the real time clock 402 through the network 28. Synchronization of the real-time clock 402 helps ensure accuracy in time stamping the transactions (e.g., taking and placing tagged products in the freezer 230) controlled by the controller 256. The processor 400 receives inputs from an optional biometric device 404, a badge or key reader or similar device 408, and the antennas 262-267. The antennas 262-267 receive information from the tagged products 270 within the freezer 230. The tags 272 on the products 270 produce identifying signals in response to being excited by signals transmitted from the antennas 262-267. The processor 400 sends signals to the antennas 262-267 through a controller 412. The controller 412 provides a command signal to a multiplexer 413, which addresses each antenna 262-267. One controller suitable for use as the controller 412 is an SCS 511 scanner with 100 398 multiplexer available from Single Chip Systems ("SCS") Corporation, San Diego, Calif. The interrogation operation (energization of and then reading of signals emitted by the tags) performed by the controller 412 and antenna array 261 will be discussed in further detail below.

The processor 400 reads and writes data to a memory 414. The processor 400 also controls a display 416, which is used to communicate with users of the freezer 230. The display 416 may be a simple lighted logo display which when lit indicates authorization of access to the freezer 230 and when unlit or lit in another color indicates denial of access to the freezer 230. A proximity sensor, e.g., the sensor 420, may be positioned on the door 236 or around the opening 234 to provide information to the processor 400 regarding whether the door 236 is opened or closed or the area comprising the MW has been accessed. Information relevant to operation of the freezer 230 and protection of the products therein, such as temperature, power status, and the like (sometimes referred to as "operational status," "heartbeat," or "health" information), is received over one or more input lines represented by communication link 422 from temperature, power, and positioning sensors, which are represented by the box 424. Communication between the processor 400 and the servers 26 and 27 (or server cluster 112) may be accomplished using a variety of technologies and hardware. FIG. 10 illustrates a wireless system 425 that is connected to an access port 430 via a communication link 432. 802.11b wireless links, available from many vendors, are suitable for use in the invention. In one preferred embodiment, wireless links from Aerocomm are used. The access port 430 may take the form of a modem or network interface device which may, in turn, be connected to an appropriate and compatible communication link such as a landline 434, wireless network 436, local area network 438, or the like. The access port 430 ultimately connects to a communication link or network (such as the network 28) that is linked to the server cluster 112.

FIG. 11 illustrates one implementation of the processor 400 shown in FIG. 10. The implementation includes an example of the processor 400 in the form of a M16C/80 chip from Mitsubishi. As would be apparent to those of ordinary skill in the art, a variety of other chips could be used. The processor 400 receives a clock signal from an oscillator 600, power from a supply circuit 601, and time signals from the real-time clock 402. Software instructions used by the processor 400 are stored on a non-volatile memory (such as EEPROM) 602. The memory 602 may be implemented using a 512 kB Flash memory integrated circuit 603 and a 512 kB SRAM integrated circuit 604.

Operational status (“health”) and related information of the relevant MW is received from a MW temperature sensor **605** and an ambient temperature sensor **606**. A battery monitor **608** monitors power supplied to the processor **400**. A current switch **609** is used to monitor the on/off duty cycle of the current supplied to the refrigeration compressor (not shown) in the freezer **230**. Information from the switch **609** as well as information from the internal and ambient temperature sensors **605** and **606** can be used to determine the relative health of the compressor.

The processor **400** is connected to a power failure/lockdown circuit **610**. The power failure lockdown circuit **610** is coupled to the supply circuit **601** and works in conjunction with an alarm circuit **612**. If power is cut off to the processor **400**, the power failure lockdown circuit **610** causes the alarm circuit **612** to generate an audio signal in order to alert users to the power failure condition. In addition, the lockdown/powerfail circuit locks the lock **613** (FIG. 10) on the freezer **230** in order to prevent additional access to the freezer. This action protects against inventory theft and assists in maintaining the internal temperature of the freezer (which is important to protecting products therein) by maintaining the integrity of the insulated volume of air within the freezer.

In the embodiment shown in FIG. 11, two mechanical switches, a door switch or sensor **614** and a key switch **615**, are used. The sensor **614** is equivalent to the sensor **420** and provides an indication of whether the door **236** is open or closed (or whether ingress or egress to a controlled or restricted access area has occurred as detected by some other sensor). The key switch **615** provides a mechanical mechanism for rebooting the processor **400** (a “hard” reboot). In addition, when turned to an off or disarm position (not shown) the key switch **615** provides an input to the processor **400** that causes the processor **400** to shut off. With the processor **400** shut off, the freezer **230** may be operated, if desired, as a normal freezer without any access restriction or inventory monitoring. As should be apparent, it is preferred that distribution of the key or keys compatible with the key switch **615** be limited to service or other authorized personnel.

The processor **400** sends control signals to an electromagnetic lock (if used) on line **617**, which is coupled to an electromagnetic actuator **619** in the lock **613**. Information regarding the stability of the freezer **230** is provided by an accelerometer **621**. The accelerometer **621** can detect vibration or other motion caused by a variety of situations such as improper positioning of the freezer **230** or an attempt to tamper or otherwise obtain access to the freezer **230** by breaking the door **236** or lock **613** (if used).

The processor **400** may control an output light such as a logo light **624**, which may be used to display the brand name of the manufacturer of the products placed within the applicable MW **36**. The processor **400** may also provide output indicative of granting or denying access to the freezer **230** to a user through green LED **626** and red LED **628**. Audio output, such as processor failure or similar status information, is delivered to an audio circuit **630**. The processor **400** also receives inputs from an implementation of a badge or key reader in the form of reader **636**. A reader suitable for use in the invention is a Visonics Key Reader, available from Visonics Inc.

Communication between the processor **400** and other devices such as the server cluster **112** may be accomplished using a dual universal asynchronous receive transmit (“UART”) integrated circuit **638**. For example, the circuit **638** may communicate with the wireless system **425**. The

circuit **638** may also communicate with a GPS system (not shown) through an interface circuit **640**. Communication between the processor **400** and the controller **412** occurs through two lines **642** and **644**. The controller **400** may also communicate to a maintenance computer through a connector interface circuit **650**.

FIG. 12 illustrates a simplified field model of the electromagnetic field within the freezer **230**. Each antenna in the array **261** has a line of sight or bore sight represented by a straight line emanating from the respective antenna **262-267**. Electromagnetic waves having a frequency of about 2.45 GHz travel outward from each antenna **262-267** into the space defined by the walls of the freezer **230** (i.e., the RF cavity). The energy of the waves diminishes. The model shown includes two lines indicating where energy of the waves is at about -20 dB and at about -20 dB level.

FIG. 13 illustrates an exemplary packaged item in the form of product **270** that may be stored in the freezer **230**. In the embodiment shown, the product **270** includes one or more vials **702** containing a biological assay. The product **270** also includes packaging that includes a pouch **704** and a periphery **706**. The vials **702** are positioned within the pouch **704**. Each product **270** also includes one tag **272**, preferably a passive RF tag. FIG. 13 illustrates multiple possible locations for the tag **272** on the periphery **706** (shown in phantom) and the pouch **704**. The tag **272** may be a folded-dipole, read-only tag, but other tags having other antenna geometries, such as bowtie, may be suitable in some embodiments. Read-only tags suitable for use in at least some of the embodiments discussed and illustrated are available from SCS Corporation. As noted, in at least one embodiment it is preferred that each product **270** be placed in one of the drawers **242** so that it is generally orthogonal to the transmission line of sight of those antennas **262-267** that are adjacent to the subject drawer **242**. It is also preferable that the tag **272** be positioned on a portion of the packaging such that it will not be bent when placed within one of the drawers **242**. Placement of the tag **272** on the pouch **704** provides a location that is less subject to bending than positions on the periphery **706**. Alternatively, a rigid tag substrate or a rigid cover label may be used to prevent bending.

Having described much of the mechanical and hardware aspects of embodiments of the invention, additional details of the software will be further described. As noted above, in general, the controller **256** activates the antenna array **261**. The antennas **262-267** emit signals that energize the tags **272** on the products within the freezer **230**. Each tag **272** emits an identifying signal. The identifying signals from the tags **272** are received by the antennas **262-267** and delivered to the controller **256**.

As may be apparent, the energization of multiple tags in a relatively small, defined volume (e.g., the RF cavity defined by the interior walls of the freezer **230**) causes the tags **272** to simultaneously or nearly simultaneously emit identifying signals. The signals interfere with each other such that identifying any individual signal from any one specific tag **272** is difficult, and in some cases nearly impossible. In order to read numerous tags **272**, a “cloaking” system can be used. In general, cloaking refers to shutting down or otherwise disabling transmission of the tag once it has been energized and identified by an interrogator (for example, controller **256**). While cloaking is generally known, the inventors developed the specific use of the cloaking techniques described herein, including the speci-

fications for minimum and maximum cloak time, and the cloak time distribution, with respect to RF cavity temperature.

The controller **256** executes inventory control software. In the embodiment described, the software carries out six basic steps. First, the controller **256** is initialized. Second, a baseline scan is performed. Third, access to the freezer **230** or relevant micro-warehouse is controlled based upon sensing the presence of and determining the validity of a user passkey using the badge or key reader **258** or similar device. Fourth, the operational status or health of the micro-warehouse is checked. Fifth, the inventory level of products is checked after a user has accessed the micro-warehouse (as sensed, for example, by closing of the freezer door **236**). Lastly, information gathered by the controller **256** is communicated to the server cluster **112**.

A more specific definition of the procedures performed by the inventory control software is set out in Table 1.

TABLE 1

Scan	A single request for a list of inventory identifiers ("Inventory IDs") (i.e., identifying codes stored in the tags) with no duplicates. The scan continues until: (a) a specified time limit has been reached, (b) a specified rate of IDs per second is exceeded, or (c) a specified limit of interval time between tag reads has been reached. There are two modes of execution, 1. cloaked, and 2. uncloaked.
Run	A series of one or more Scans continued either until (a) a specified number of Scans has been reached, (b) a specified time limit has been reached, (c) a specified integrity level has been reached, or (d) an event (such as an RF power failure) has occurred which terminates a scan, Each of (a)-(d) is a mode of execution, and one or more modes can be requested. A run is terminated on the first occurrence of a mode. Each Scan is separated by a specified time interval.
Inventory ID	A 6-byte, binary hexadecimal string, unique to 2^{44} values. The Inventory CD identifies a tagged product in a micro-warehouse.
Integrity Level	A percentage expressed as "0.90."
Inventory List	A single list of all Inventory IDs present in a micro-warehouse
ReadTime	The amount of time elapsed from the start of a Scan to the last tag being read. This time may also be a set and includes the time elapsed to the reading of each of any number of tags.
ReadTemp	The temperature of any one tag as reported by the tag during a Scan (assumes that system is implemented using tags that are capable of reporting their temperature).
ScanTime	Time limit for one Scan
ScanInterval	Time between tag ReadTimes in one Scan
NumScans	Number of Scans to perform in a Run
ScanWaitTime	Time to wait between Scans for de-cloaking
ReadRate	Rate of tags read per second during one Scan

As noted in Table 1, the read time (or for the specific embodiment discussed, "ReadTime") of a scan is the elapsed time from the start of a scan to the reading of any or all of the tags in the field generated by the antennas. The read time can be collected in either the non-cloaked or cloaked mode. The read time (which can also be a set of read times) can be sent to the server cluster **112** as part of each transaction that results from a scan. The read time can be used as a composite indicator of several operating parameters, such as

temperature, product tag position in the RF cavity, RF interference in the cavity, etc. For instance, a gradual lengthening of the read time(s) for all tags in a RF cavity can correspond to an increase in interior temperature. It is possible to quantify a temperature change from the shift in a tag versus read time curve (such as the curve **725** shown in FIG. **21**). As another instance, the shape of the curve of tag versus read time for the last few tags that were read can be used as an indicator of an RF anomaly in the RF cavity that is preventing the tags from getting enough power to respond. In this case, the normally linear curve becomes exponential for the last few tags. Operating parameters read from other sensors in the RF cavity, such as the temperature sensor, can be used with the read time curve to predict the condition that resulted in the change in the read time curve.

In one embodiment, the inventory control software includes three classes of runs: a base line run, an inventory run; and a background run. Definitions for Methods corresponding to these runs are set out in Table 2.

TABLE 2

Method	Function
Baseline Run Output: IntegLvl, ReadTime, ReadTemp Input: (NumScans, RunTime, IntegLvl, ScanInterval, ScanWaitTime, ScanTime, ReadRate)	A run in cloaked or uncloaked mode to establish the starting inventory list.
Inventory Run Output: (PlusInventoryList, MinusInventoryList, IntegLvl, ReadTime, ReadTemp) Input: (NumScans, RunTime, IntegLvl, ScanInterval, ScanWaitTime, ScanTime, ReadRate)	A run or runs in uncloaked (or cloaked) mode to determine a new inventory list. Uses master inventory list established at baseline, and returns the change in inventory between the master inventory list and the new inventory list as plus delta inventory and minus delta inventory.
Background Run Output: (PlusInventoryList, MinusInventoryList, IntegLvl, ReadTime, ReadTemp) Input: (NumScans, RunTime, IntegLvl, ScanInterval, ScanWaitTime, ScanTime, ReadRate)	A continuous series of scans in cloaked or uncloaked mode until a termination event occurs, such as a user presenting a badge or key to request entry.
Reveal Inventory Output: (MasterInventoryList)	

Classes of Runs

Baseline Run

A run in cloaked mode to establish the starting inventory list. If IntegrityLevel is not specified, the actual read integrity level is returned, that is, the number of times the majority scan list occurs. Creates the first master inventory list, consisting of the superset of all inventory IDs read throughout the baseline scans. The read integrity is returned even when an input integrity level has been set.

Inventory Run

A run or runs in uncloaked (or cloaked) mode to determine changes to the inventory list. Uses the superset of all inventory run scans as the new list of inventory. Uses master inventory list (from baseline and/or background) or most recent temporary master inventory list, whichever is more recent, and returns change in inventory between master inventory list and new inventory list, as plus delta inventory and minus delta inventory. Creates new temporary master inventory list.

Background Run

A continuous series of scans in cloaked mode until a termination event occurs. Uses a superset of all scans as the inventory list. Creates new master inventory list.

Reveal Inventory

No scans. Returns most recent master inventory list.

One useful feature of the embodiments described herein is that the manner in which the controller 256 controls the antenna array 261 may be adjusted. The adjustment may be accomplished by modifying certain software parameters, including those noted in Tables 1 and 2 (such as integrity level, read time, run time, wait time, scan interval, etc.) as circumstances change (for example, changes in temperature, tag type, RF cavity, etc.). As explained in additional detail below, these changes can be performed remotely by sending the changed parameters to the controller 256 from the server cluster 112.

An overview of the operations performed by the inventory control software is set out in FIG. 14. At step 750, the controller 256 is reset via a hard reset by, for example, turning the key switch 615 to an arm position (not shown). At step 752, the controller checks the server cluster 112 to see if a new version of the controller software is available. If a new version is available, that version is downloaded and loaded into the memory 602 and a soft reset is performed, as shown at step 754. Once any necessary software updates have been performed, the controller 256 loads required parameters, reloads saved transactions, and reloads any master inventory information, if it exists, as shown at step 756. At step 758, the controller 256 checks its status. At step 760, the controller 256 determines whether a lockdown condition exists. If a lockdown condition exists, the controller sets a flag or similar device to indicate the presence of a lockdown condition (as shown at step 762) and continues to check for the presence of a lockdown condition (as shown by loop 764).

Once it is determined that a lockdown condition does not exist, the controller 256 performs a baseline run, queues (or places in a buffer) the inventory master value, and sets the lockdown flag to "off," as shown at step 766. The controller 256 then executes a control idle loop (step 768) or, more broadly, a main processing loop. In the embodiment illustrated, the control idle loop includes five basic operations: a check diagnostic command operation (step 770), a poll user pass operation (step 772), a poll status operation (step 774), an update saved status operation (step 776), and a check alarm conditions operation (step 778). These steps are discussed in greater detail below. In summary, during these operations, the controller 256 determines whether the user has an authorized key and whether any alarm or other conditions are present. If any of the alarm or status conditions meet the requirements of a lockdown situation (as determined at step 780), the lockdown flag is set to "on" (step 782), information obtained about the inventory in and status of the MW 36 is sent to the server cluster 112 (step 784, background communication) and the control idle loop is executed again (as shown by loop 786).

If a lockdown condition does not exist, the controller 256 determines whether a user has accessed the MW (step 788) as determined, for example, by the controller 256 sensing an opening and closing of the door 236. If a user has accessed the MW, an inventory run is requested and the information from the run is queued in a transaction buffer, as shown in block 792. The information gathered from the inventory run is then sent to the server cluster 112 (as shown at step 784). The controller 256 continues to execute the software until reset.

FIGS. 15 through 21 provide additional information regarding the operations (or routines) discussed above with respect to FIG. 14.

As shown in FIG. 15, when the controller 256 executes the control idle loop, it determines whether any diagnostic commands need to be processed (step 793). If commands are unprocessed, the controller 256 processes those commands (step 794) and then returns to the control idle loop (step 768).

As shown in FIG. 16, after processing any diagnostic commands, the controller 256 checks the validity of any key or pass presented by a user. If the key is invalid, appropriate feedback is provided by, for example, lighting the red LED 628 (step 796). The controller then returns to the control idle loop. If the key is valid, the controller checks for the existence of a lockdown condition (step 798). If a lockdown condition exists, the controller denies access to the MW and returns to the control idle loop. If a lockdown condition does not exist, access is permitted and appropriate feedback provided by, for example, lighting the green LED 626 (step 799).

FIG. 17 illustrates the operations performed during a poll status operation (step 774). The controller 256 retrieves information from the various sensors (temperature, power, etc.) and returns to the control idle loop (step 768). As shown in FIG. 18, updating saved status information involves assigning the information retrieved during polling (step 774) to variables or registers holding prior status information.

As shown in FIG. 19, checking alarm conditions (step 778) involves comparing or otherwise evaluating the status information and other information, for example, shelf life, to predetermined thresholds (step 800). In the event any information exceeds or fails to meet the predetermined thresholds, as the case may be, an alarm transaction is queued (step 802). Then control is returned to the control idle loop (step 768).

FIG. 20 illustrates the functions performed by controller 256 when it executes RF inventory operations. As shown at steps 804-806, the controller 256 first determines whether the scanning operation to be performed is a baseline run or scan, an inventory run, or a background run. The type of run to be performed is passed from the control idle loop to the RF inventory module. Depending on the type of run requested, the appropriate parameters are loaded, as shown at steps 807-810. Once the parameters are loaded, an appropriate scan is performed, as shown at step 812. If the results of the scan are higher than a predetermined integrity level, a union set based on the results is formed as shown at steps 814 and 816. If the results do not meet the predetermined integrity level, additional scans are performed until the integrity level is met or exceeded, as shown by loop 818. If the type of run or scan performed was an inventory run (step 819), changes between the inventory run and previously stored information (in the example shown, the inventory master) are determined, as shown at step 820. Control is then returned to the control idle loop, as shown at step 822.

The number of scans to be used in any run is variable and is set to ensure a predetermined integrity, which, in the ideal case, is 100% integrity of recorded inventory. In one embodiment of the invention, a plurality of scans is performed such that the specified integrity level is achieved based on experimental data. A superset or union of all the scan sets is then formed. For example, in order to achieve an integrity level of 50%, the number of identical scans must be the majority set. In one embodiment, experiments have shown that the number of scans, in non-cloaked mode, should be about ten and in cloaked mode, about three.

Additionally, an order (a product removal or purchase transaction), based on inventory recorded before door opening and after door closure, can be aged or buffered, that is, held for processing, either in the controller or at the server, for some time until further transactions are recorded. If the additional scans from these further transactions reveal a product recorded as taken in the previous transaction, the erroneous transaction can be corrected before billing a customer. While it is possible for the system to miss a tagged item during a scan, testing of embodiments of the invention has not resulted in a situation where a scan indicated the presence of items not physically present in the relevant MW. In any case, anomalies in recorded inventory that are picked up in later scans can be used to correct the billing information. In actual use it is believed, and limited tests have shown, that this type of correction will be seldomly required. Further, the baseline run and the background run are not necessary in all applications, and can be selected to be used on any particular MW at the time of manufacture, field installation, or service interval.

The tags 272 may be equipped with the ability to report their temperature during a scan. A function of the temperature information obtained from the tags 272 can be used to adjust the scan and scan wait times (defined in Table 1 as Scan and Scan Wait) to adjust for cloak time changes due to temperature in order to ensure inventory integrity during any run. All of the instances mentioned in the above paragraph refer to read time in cloaked mode.

Once the controller 256 has scanned the tagged products in the MW 36 or freezer 230, a message containing information regarding the scan is sent to the server cluster 112. As shown in FIG. 22, in the particular embodiment shown, the message takes the form of a background communication (step 784). The controller 256 checks, at step 850, whether a communication session or transaction between the controller 256 and the cluster 112 has already been started. If a transaction or communication has not been started, the controller 256 checks to see whether there is any information to send to the cluster 112, at step 852. If there is information to send, the controller 256 creates a connection to the server cluster 112, as shown at step 854.

If no transactions are being processed or queued, the controller 256 determines whether it should synchronize the real-time clock 402 with a standard time reference (step 855). For example, if a certain amount of time has passed since the last synchronization has occurred, the real time clock 402 is synchronized again to compensate for any variations that might have occurred since the last synchronization. If no synchronization is needed, the background communication module is exited and control is returned to the control idle loop. If synchronization is required, the clock is updated (as shown at steps 856 and 857).

If a transaction has been started or a transaction is queued, the controller 256 processes the next transaction or message to be communicated to the cluster 112 (as shown at step 860). Processing of the next transaction includes sending inventory, status, alarm, heartbeat, and passkey information to the server cluster 112. Once these transactions have been processed, the controller 256 processes input transactions for transmission to the server cluster 112 (step 862). Information such as updated passkey information, updated parameters, resets, lockdown information, software updates, status requests, and passkey lists are sent to the server cluster 112.

FIGS. 23 and 24 illustrate operations performed by the controller 256 upon the occurrence of key switch and interrupt events. As noted above, a transition of the key

switch 615 from an arm position to a disarm position causes the controller to reboot or reset itself (as shown in steps 875 and 877 in FIG. 23). If a transition from the arm position to the disarm position occurs, the controller 256 initiates a shutdown sequence and saves information in the transaction queue (as shown at steps 879 and 881).

Various events cause the controller 256 to perform certain functions. For the embodiment described, the condition of a power failure causes a power fail transaction to be queued (steps 890 and 892 in FIG. 24). The need to input or output information on a serial port causes the controller to place the input information in an I/O buffer (steps 894 and 896). Operational status (or health or heartbeat) checks are carried out at predefined times. If the time for a status check has occurred, a status check is performed and the information obtained during the check is queued for transmission to the server cluster 112 (steps 900 and 902). If the door switch or sensor is toggled, the time of day and temperature of the MW 36 are recorded (steps 904 and 906). If the current sensor senses a toggling of the AC current, the toggle is recorded (steps 908 and 910). Finally, if the controller must provide user feedback (such as providing an indication of the validity of a passkey), the user feedback is provided and appropriate feedback flags are toggled (steps 912 and 914).

As can be seen from the above, the present invention provides an RF inventory and distribution system with features to diminish the effects of energy sharing, nulls, shadowing, and other effects that degrade integrity in recording inventory changes.

Various features and advantages of the invention are set forth in the following claims.

What is claimed is:

[1. An RFID cabinet for monitoring items having an RFID tag, the cabinet comprising: a cabinet comprising a back, a first side, a second side, a third side, a bottom and at least one locking door; an RFID detector for monitoring each item placed within the cabinet and for identifying the data embedded on an RFID tag located on items placed within the cabinet; and a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the locking door, wherein the computer is configured to receive an input that identifies a user, and wherein the computer is configured to at a plurality of times record data read from the RFID tags by the RFID detector.]

[2. The RFID cabinet of claim 1, wherein the cabinet is manufactured of a material so that an RFID field produced by the RFID detector is within the interior of the RFID cabinet.]

[3. The RFID cabinet of claim 1, wherein the RFID detector scans each item placed within the cabinet, such that the RFID cabinet may determine if an item is removed from the interior of the RFID cabinet.]

[4. The RFID cabinet of claim 1, wherein the computer has a connection chosen from a group comprising Internet and wireless.]

[5. The RFID cabinet of claim 1, wherein the input that identifies a user is chosen from a group comprising a password, an RFID badge, voice recognition, a mag card, or biometrics.]

[6. The RFID cabinet of claim 1, wherein the RFID detecting device is coupled to a network, through the computer, wherein a database provides inventory of each of the items placed within the cabinet.]

[7. The RFID cabinet of claim 6, wherein an inventory control module software enables the RFID detecting device to scan items in the cabinet and to generate a message regarding items taken.]

23

[8. The RFID cabinet of claim 1, wherein the means for accessing the RFID cabinet comprises an RFID badge, wherein the locking door of the RFID cabinet unlocks in response to the RFID badge coming into proximity.]

[9. The RFID cabinet of claim 1, wherein there is a strong enough field within the cabinet such that all items can be read using the RFID detector.]

[10. A method for removing items having an RFID tag from an RFID cabinet, the method comprising: providing a cabinet having an RFID detector for monitoring each item placed within the cabinet and for identifying the data embedded on an RFID tag located on each item placed within the cabinet and a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the locking door; reading an input that identifies a user; receiving the input that identifies a user at the computer; unlocking the door to the RFID cabinet if the user is allowed access; and at a plurality of times scanning all the items in the RFID cabinet to determine if any items have been removed by the user.]

[11. The method of claim 10, further comprising disabling the RFID detector when the door to the RFID cabinet is open.]

[12. A method for scanning items having an RFID tag in an RFID cabinet, the method comprising: providing a cabinet having an RFID detector for monitoring each item placed within the cabinet and for identifying the data embedded on an RFID tag located on each item placed within the cabinet and a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the locking door, and wherein the computer is configured to receive an input that identifies a user allows access to the RFID cabinet; reading the RFID tag associated with an item using an RFID field from the RFID detector; and recording the resulting information in a database.]

[13. The method of claim 12, further comprising sounding an alert if certain conditions programmed within the memory of the computer are satisfied.]

[14. An RFID cabinet for monitoring items having an RFID tag, the cabinet comprising: a cabinet comprising a back, a first side, a second side, a top, a bottom and at least one locking front door; an RFID detector for monitoring each item placed within the cabinet and for identifying the data embedded on an RFID tag located on items placed within the cabinet, the RFID detector located within the interior of the RFID cabinet; and a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the locking front door, wherein the computer is configured to receive an input that identifies a user, and wherein the computer is configured to periodically record data read from the RFID tags by the RFID detector.]

[15. The RFID cabinet of claim 14, wherein the cabinet is manufactured of a material that confines an RFID field produced by the RFID detector within the interior of the RFID cabinet.]

[16. The RFID cabinet of claim 14, wherein the RFID detector scans each item placed within the cabinet in a time period, such that the RFID cabinet may determine if an item is removed from the interior of the RFID cabinet.]

[17. The RFID cabinet of claim 16, wherein the time period is a predetermined amount of time.]

[18. The RFID cabinet of claim 14, wherein the computer has a connection chosen from a group comprising Internet and wireless.]

24

[19. The RFID cabinet of claim 14, wherein the input that identifies a user is chosen from a group comprising a password, an RFID badge, a bar code, voice recognition, a mag card, or biometrics.]

[20. The RFID cabinet of claim 14, wherein the RFID detecting device is coupled to a network, through the computer, wherein a database provides inventory of each of the items placed within the cabinet.]

[21. The RFID cabinet of claim 20, wherein an inventory control module software enables the RFID detecting device to scan items in the cabinet and to generate a message regarding items taken.]

[22. The RFID cabinet of claim 14, wherein the means for accessing the RFID cabinet comprises an RFID badge, wherein the locking front door of the RFID cabinet unlocks in response to the RFID badge coming into proximity.]

[23. The RFID cabinet of claim 14, wherein the material provides a shield sufficient to allow a strong enough field within the cabinet such that all items can be read using the RFID detector.]

[24. A method for removing items having an RFID tag from an RFID cabinet, the method comprising: providing a cabinet having an RFID detector for monitoring each item placed within the cabinet and for identifying the data embedded on an RFID tag located on each item placed within the cabinet, the RFID detector located within the interior of the RFID cabinet and a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the locking front door; reading an input that identifies a user; receiving the input that identifies a user at the computer; unlocking the door to the RFID cabinet if the user is allowed access; and at least periodically scanning all the items in the RFID cabinet to determine if any items have been removed by the user.]

[25. The method of claim 24, further comprising disabling the RFID detector when the door to the RFID cabinet is open.]

[26. A method for scanning items having an RFID tag in an RFID cabinet, the method comprising: providing a cabinet having an RFID detector monitoring each item placed within the cabinet and for identifying the data embedded on an RFID tag located on each item placed within the cabinet, the RFID detector located within the interior of the RFID cabinet and a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the locking front door, and wherein the computer is configured to receive an input that identifies a user allows access to the RFID cabinet; reading the RFID tag associated with an item using an RFID field from the RFID detector; and recording the resulting information in a database.]

[27. The method of claim 26, further comprising sounding an alert if certain conditions programmed within the memory of the computer are satisfied.]

28. *A radio frequency identification (RFID) cabinet for monitoring items having an RFID tag, the RFID cabinet comprising:*

a back, a first side, a second side, a third side, a bottom and at least one lockable door;

an RFID detector for monitoring each item placed within the cabinet and for reading data embedded on an RFID tag located on the items placed within the cabinet; and a computer coupled to the RFID cabinet,

wherein the computer is configured to control unlocking and locking of the lockable door,

wherein the computer is configured to receive an input that identifies a user, and

25

wherein the computer is configured to at more than one time scan the cabinet and record data read from the RFID tags by the RFID detector.

29. The RFID cabinet of claim 28, wherein the RFID detector is configured to scan any item placed within the cabinet, such that the RFID cabinet may determine if an item is removed from the interior of the RFID cabinet.

30. The RFID cabinet of claim 28, wherein the computer has a connection chosen from a group comprising Internet and wireless.

31. The RFID cabinet of claim 28, wherein a RFID detecting device is coupled to a network, through the computer, wherein a database provides inventory of each of the items placed within the cabinet.

32. The RFID cabinet of claim 31, wherein an inventory control module software is configured to enable the RFID detecting device to scan items in the cabinet and to generate a message regarding items taken.

33. The RFID cabinet of claim 28, wherein the RFID detector is configured to scan any item placed within the cabinet, such that the RFID cabinet may determine if an item is added from the interior of the RFID cabinet.

34. The RFID cabinet of claim 28, wherein the RFID detector is configured to scan each item placed within the cabinet, such that the RFID cabinet may determine an amount of time an item has been in the interior of the RFID cabinet.

35. The RFID cabinet of claim 28, wherein the RFID detector is configured to scan each item placed within the cabinet, such that the RFID cabinet may determine a temperature history for an item while in the interior of the RFID cabinet.

36. The RFID cabinet of claim 28, wherein the RFID detector is configured to scan each item placed within the cabinet, such that the RFID cabinet may determine an expiration time for an item in the RFID cabinet.

37. The RFID cabinet of claim 30, wherein the computer communicates with an enterprise computer.

38. The RFID cabinet of claim 35 wherein an enterprise computer is configured to run enterprise resource planning ("ERP"), customer relation management ("CRM"), manufacturing, and/or other business process programs.

39. The RFID cabinet of claim 28, wherein the cabinet is a refrigerator.

26

40. The RFID cabinet of claim 28, wherein the cabinet is a freezer.

41. A method for removing items having an radio frequency identification (RFID) tag from an RFID cabinet, the method comprising:

providing

a cabinet having an RFID detector for monitoring each item placed within the cabinet and for reading data embedded on an RFID tag located on each item placed within the cabinet and

a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the lockable door;

reading an input that identifies a user;

receiving the input that identifies a user at the computer;

unlocking the door to the RFID cabinet if the user is allowed access; and

at more than one time scanning all the items in the RFID cabinet to determine if any items have been removed by the user;

wherein the scanning corresponds to closing of the lockable door.

42. A method for scanning items having an radio frequency identification (RFID) tag in an RFID cabinet, the method comprising:

providing

a cabinet having an RFID detector for monitoring each item placed within the cabinet and for reading data embedded on an RFID tag located on each item placed within the cabinet and

a computer coupled to the RFID cabinet, wherein the computer controls unlocking and locking of the lockable door, and wherein the computer is configured to receive an input that identifies a user allowed access to the RFID cabinet;

reading the RFID tag associated with an item using an RFID field from the RFID detector; and

recording the resulting information in a database

wherein said information is selected from identity of items removed from the RFID cabinet, identity of items added to the RFID cabinet, amount of time an item has been in the interior of the RFID cabinet, a temperature history of an item while in the interior of the RFID cabinet and expiration of an item in the RFID cabinet.

* * * * *