



US00RE47675E

(19) **United States**
(12) **Reissued Patent**
Bouma et al.

(10) **Patent Number:** **US RE47,675 E**
(45) **Date of Reissued Patent:** **Oct. 29, 2019**

(54) **PROCESS AND APPARATUS FOR A WAVELENGTH TUNING SOURCE**

(58) **Field of Classification Search**
CPC . H01S 3/10; H01S 3/105; H01S 3/109; H01S 5/141

(71) Applicant: **The General Hospital Corporation,**
Boston, MA (US)

(Continued)

(72) Inventors: **Brett Eugene Bouma,** Quincy, MA (US); **Seok-Hyun Yun,** Cambridge, MA (US); **Wang-Yuhl Oh,** Cambridge, MA (US); **Johannes Fitzgerald De Boer,** Amstelveen (NL); **Guillermo J. Tearney,** Cambridge, MA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,339,754 A 1/1944 Brace
3,090,753 A 5/1963 Matuszak et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1550203 12/2004
DE 4105221 9/1991

(Continued)

(73) Assignee: **The General Hospital Corporation,**
Boston, MA (US)

(21) Appl. No.: **15/151,789**

(22) Filed: **May 11, 2016**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,995,627**
Issued: **Aug. 9, 2011**
Appl. No.: **12/627,918**
Filed: **Nov. 30, 2009**

U.S. Applications:

(62) Division of application No. 11/867,953, filed on Apr. 11, 2008, now Pat. No. 7,724,786, which is a division
(Continued)

(51) **Int. Cl.**
H01S 3/10 (2006.01)
G01J 3/10 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G01J 3/10** (2013.01); **A61B 5/0059** (2013.01); **A61B 5/0066** (2013.01);
(Continued)

OTHER PUBLICATIONS

Silva K et al. "Extended range, rapid scanning optical delay line for biomedical interferometric imaging", Electronics Letters, IEE Stevenage, GB, vol. 35 No. 17 (1999).

(Continued)


Primary Examiner — James A Menefee

(74) *Attorney, Agent, or Firm* — Quarles & Brady LLP

(57) **ABSTRACT**

An apparatus and source arrangement for filtering an electromagnetic radiation can be provided which may include at least one spectral separating arrangement configured to physically separate one or more components of the electromagnetic radiation based on a frequency of the electromagnetic radiation. The apparatus and source arrangement may also have at least one continuously rotating optical arrangement which is configured to receive at least one signal that is associated with the one or more components. Further, the apparatus and source arrangement can include at least one beam selecting arrangement configured to receive the signal.

31 Claims, 16 Drawing Sheets



Related U.S. Application Data				
	of application No. 10/861,179, filed on Jun. 4, 2004, now Pat. No. 7,519,096.		4,928,005 A	5/1990 Lefevre et al.
			4,940,328 A	7/1990 Hartman
			4,965,441 A	10/1990 Picard
			4,965,599 A	10/1990 Roddy et al.
			4,966,589 A	10/1990 Kaufman
(60)	Provisional application No. 60/476,600, filed on Jun. 6, 2003, provisional application No. 60/514,769, filed on Oct. 27, 2003.		4,984,888 A	1/1991 Tobias et al.
			4,993,834 A	2/1991 Carlhoff et al.
			4,998,972 A	3/1991 Chin et al.
			5,039,193 A	8/1991 Snow et al.
			5,040,889 A	8/1991 Keane
(51)	Int. Cl.		5,045,936 A	9/1991 Lobb et al.
	G01B 9/02 (2006.01)		5,046,501 A	9/1991 Crilly
	G01J 3/12 (2006.01)		5,065,331 A	11/1991 Vachon et al.
	G01N 21/47 (2006.01)		5,085,496 A	2/1992 Yoshida et al.
	G02B 27/48 (2006.01)		5,120,953 A	6/1992 Harris
	A61B 5/00 (2006.01)		5,121,983 A	6/1992 Lee
	G01J 9/02 (2006.01)		5,127,730 A	7/1992 Brelje et al.
	H01S 3/08 (2006.01)		5,197,470 A	3/1993 Helfer et al.
	H01S 3/105 (2006.01)		5,202,745 A	4/1993 Sorin et al.
	H01S 5/14 (2006.01)		5,202,931 A	4/1993 Bacus
	H01S 5/40 (2006.01)		5,208,651 A	5/1993 Buican
(52)	U.S. Cl.		5,212,667 A	5/1993 Tomlinson, Jr. et al.
	CPC G01B 9/02004 (2013.01); G01B 9/02091 (2013.01); G01J 3/12 (2013.01); G01N 21/4795 (2013.01); G02B 27/48 (2013.01); G01J 9/0215 (2013.01); H01S 3/08009 (2013.01); H01S 3/08063 (2013.01); H01S 3/105 (2013.01); H01S 5/141 (2013.01); H01S 5/146 (2013.01); H01S 5/4087 (2013.01)		5,214,538 A	5/1993 Lobb
			5,217,456 A	6/1993 Narciso, Jr.
			5,228,001 A	7/1993 Birge et al.
			5,241,364 A	8/1993 Kimura
			5,248,876 A	9/1993 Kerstens et al.
			5,250,186 A	10/1993 Dollinger et al.
			5,251,009 A	10/1993 Bruno
			5,262,644 A	11/1993 Maguire
			5,275,594 A	1/1994 Baker
			5,281,811 A	1/1994 Lewis
			5,283,795 A	2/1994 Fink
(58)	Field of Classification Search		5,291,885 A	3/1994 Taniji et al.
	USPC 372/20		5,293,872 A	3/1994 Alfano et al.
	See application file for complete search history.		5,293,873 A	3/1994 Fang
			5,302,025 A	4/1994 Kleinerman
(56)	References Cited		5,304,173 A	4/1994 Kittrell et al.
	U.S. PATENT DOCUMENTS		5,304,810 A	4/1994 Amos
			5,305,759 A	4/1994 Kaneko et al.
	3,601,480 A	8/1971 Randall	5,317,389 A	5/1994 Hochberg et al.
	3,856,000 A	12/1974 Chikama	5,318,024 A	6/1994 Kittrell et al.
	3,872,407 A	3/1975 Hughes	5,321,501 A	6/1994 Swanson et al.
	3,941,121 A	3/1976 Olinger	5,348,003 A	9/1994 Caro
	3,973,219 A	8/1976 Tang et al.	5,353,790 A	10/1994 Jacques et al.
	3,983,507 A	9/1976 Tang et al.	5,383,467 A	1/1995 Auer et al.
	4,030,827 A	6/1977 Delhay et al.	5,394,235 A	2/1995 Takeuchi et al.
	4,030,831 A	6/1977 Gowrinathan	5,404,415 A	4/1995 Mori et al.
	4,140,364 A	2/1979 Yamashita et al.	5,411,016 A	5/1995 Kume et al.
	4,141,362 A	2/1979 Wurster	5,419,323 A	5/1995 Kittrell et al.
	4,224,929 A	9/1980 Furihata	5,424,827 A	6/1995 Horwitz et al.
	4,295,738 A	10/1981 Meltz et al.	5,439,000 A	8/1995 Gunderson et al.
	4,300,816 A	11/1981 Snitzer et al.	5,441,053 A	8/1995 Lodder et al.
	4,303,300 A	12/1981 Pressiat et al.	5,450,203 A	9/1995 Penkethman
	4,428,643 A	1/1984 Kay	5,454,807 A	10/1995 Lennox et al.
	4,479,499 A	10/1984 Alfano	5,459,325 A	10/1995 Hueton et al.
	4,533,247 A	8/1985 Epworth	5,459,570 A	10/1995 Swanson et al.
	4,585,349 A	4/1986 Gross et al.	5,465,147 A	11/1995 Swanson
	4,601,036 A	7/1986 Faxvog et al.	5,483,058 A *	1/1996 Leviton G01D 5/38 250/231.13
	4,607,622 A	8/1986 Fritch et al.	5,486,701 A	1/1996 Norton et al.
	4,631,498 A	12/1986 Cutler	5,491,524 A	2/1996 Hellmuth et al.
	4,639,999 A	2/1987 Daniele	5,491,552 A	2/1996 Kittrell
	4,650,327 A	3/1987 Ogi	5,522,004 A	5/1996 Djupsjobacka et al.
	4,734,578 A	3/1988 Horikawa	5,526,338 A	6/1996 Hasman et al.
	4,744,656 A	5/1988 Moran et al.	5,555,087 A	9/1996 Miyagawa et al.
	4,751,706 A	6/1988 Rohde et al.	5,562,100 A	10/1996 Kittrell et al.
	4,763,977 A	8/1988 Kawasaki et al.	5,565,983 A	10/1996 Barnard et al.
	4,770,492 A	9/1988 Levin et al.	5,565,986 A	10/1996 Knüttel
	4,827,907 A	5/1989 Tashiro	5,566,267 A	10/1996 Neuberger
	4,834,111 A	5/1989 Khanna et al.	5,577,058 A *	11/1996 Kafka G02F 1/39 359/328
	4,868,834 A	9/1989 Fox et al. H01S 3/117 372/102	5,583,342 A	12/1996 Ichie
			5,590,660 A	1/1997 MacAulay et al.
			5,600,486 A	2/1997 Gal et al.
			5,601,087 A	2/1997 Richards-Kortum et al.
			5,621,830 A	4/1997 Lucey et al.
			5,623,336 A	4/1997 Raab
			5,635,830 A	6/1997 Itoh

(56)

References Cited

U.S. PATENT DOCUMENTS

5,649,924 A	7/1997	Everett et al.	6,107,048 A	8/2000	Goldenring et al.
5,697,373 A	12/1997	Gunderson et al.	6,111,645 A	8/2000	Tearney et al.
5,698,397 A	12/1997	Zarling et al.	6,117,128 A	9/2000	Gregory
5,710,630 A	1/1998	Essenpreis et al.	6,120,516 A	9/2000	Selmon et al.
5,716,324 A	2/1998	Toida	6,134,003 A	10/2000	Tearney et al.
5,719,399 A	2/1998	Alfano et al.	6,134,010 A	10/2000	Zavislan
5,730,731 A	3/1998	Mollenauer et al.	6,134,033 A	10/2000	Bergano et al.
5,735,276 A	4/1998	Lemelson	6,141,577 A	10/2000	Rolland et al.
5,740,808 A	4/1998	Panescu et al.	6,151,522 A	11/2000	Alfano et al.
5,748,318 A	5/1998	Maris et al.	6,159,445 A	12/2000	Klaveness et al.
5,748,598 A	5/1998	Swanson et al.	6,160,826 A	12/2000	Swanson et al.
5,752,518 A	5/1998	McGee et al.	6,161,031 A	12/2000	Hochman et al.
5,771,252 A *	6/1998	Lang H01S 5/141 372/102	6,166,373 A	12/2000	Mao
5,784,352 A	7/1998	Swanson et al.	6,174,291 B1	1/2001	McMahon et al.
5,785,651 A	7/1998	Kuhn et al.	6,175,669 B1	1/2001	Colston et al.
5,795,295 A	8/1998	Hellmuth et al.	6,185,271 B1	2/2001	Kinsinger
5,801,826 A	9/1998	Williams	6,191,862 B1	2/2001	Swanson et al.
5,801,831 A	9/1998	Sargoytchev et al.	6,193,676 B1	2/2001	Winston et al.
5,803,082 A	9/1998	Stapleton et al.	6,198,956 B1	3/2001	Dunne
5,807,261 A	9/1998	Benaron et al.	6,201,989 B1	3/2001	Whitehead et al.
5,810,719 A	9/1998	Toida	6,208,415 B1	3/2001	De Boer et al.
5,817,144 A	10/1998	Gregory	6,208,887 B1	3/2001	Clarke
5,836,877 A	11/1998	Zavislan	6,245,026 B1	6/2001	Campbell et al.
5,840,023 A	11/1998	Oraevsky et al.	6,249,349 B1	6/2001	Lauer
5,840,075 A	11/1998	Mueller et al.	6,249,381 B1	6/2001	Suganuma
5,842,995 A	12/1998	Mahadevan-Jansen et al.	6,249,630 B1	6/2001	Stock et al.
5,843,000 A	12/1998	Nishioka et al.	6,263,234 B1	7/2001	Engelhardt et al.
5,843,052 A	12/1998	Benja-Athon	6,264,610 B1	7/2001	Zhu
5,847,827 A	12/1998	Fercher	6,272,376 B1	8/2001	Marcu et al.
5,862,273 A	1/1999	Pelletier	6,274,871 B1	8/2001	Dukor et al.
5,865,754 A	2/1999	Sevick-Muraca et al.	6,282,011 B1	8/2001	Tearney et al.
5,867,268 A	2/1999	Gelikonov et al.	6,282,213 B1 *	8/2001	Gutin H01S 5/141 372/20
5,871,449 A	2/1999	Brown	6,297,018 B1	10/2001	French et al.
5,872,879 A	2/1999	Hamm	6,301,048 B1	10/2001	Cao et al.
5,877,856 A	3/1999	Fercher	6,308,092 B1	10/2001	Hoyns
5,887,009 A	3/1999	Mandella et al.	6,324,419 B1	11/2001	Guzelsu et al.
5,892,583 A	4/1999	Li	6,341,036 B1	1/2002	Tearney et al.
5,910,839 A	6/1999	Erskine	6,353,693 B1	3/2002	Kano et al.
5,912,764 A	6/1999	Togino	6,359,692 B1	3/2002	Groot
5,920,373 A	7/1999	Bille	6,374,128 B1	4/2002	Toida et al.
5,920,390 A	7/1999	Farahi et al.	6,377,349 B1	4/2002	Fercher
5,921,926 A	7/1999	Rolland et al.	6,384,915 B1	5/2002	Everett et al.
5,926,592 A	7/1999	Harris et al.	6,393,312 B1	5/2002	Hoyns
5,949,929 A	9/1999	Hamm	6,394,964 B1	5/2002	Sievert, Jr. et al.
5,951,482 A	9/1999	Winston et al.	6,396,941 B1	5/2002	Bacus et al.
5,955,737 A	9/1999	Hallidy et al.	6,421,164 B2	7/2002	Tearney et al.
5,956,355 A	9/1999	Swanson et al.	6,437,867 B2	8/2002	Zeylikovich et al.
5,968,064 A	10/1999	Selmon et al.	6,441,892 B2	8/2002	Xiao
5,975,697 A	11/1999	Podoleanu et al.	6,441,959 B1	8/2002	Yang et al.
5,983,125 A	11/1999	Alfano et al.	6,445,485 B1	9/2002	Frigo et al.
5,987,346 A	11/1999	Benaron et al.	6,445,939 B1	9/2002	Swanson et al.
5,991,697 A	11/1999	Nelson et al.	6,445,944 B1	9/2002	Ostrovsky
5,994,690 A	11/1999	Kulkarni et al.	6,459,487 B1	10/2002	Chen et al.
5,995,223 A	11/1999	Power	6,463,313 B1	10/2002	Winston et al.
6,002,480 A	12/1999	Izatt et al.	6,469,846 B2	10/2002	Ebizuka et al.
6,004,314 A	12/1999	Wei et al.	6,475,159 B1	11/2002	Casscells et al.
6,006,128 A	12/1999	Izatt et al.	6,475,210 B1	11/2002	Phelps et al.
6,007,996 A	12/1999	McNamara et al.	6,477,403 B1	11/2002	Eguchi et al.
6,010,449 A	1/2000	Selmon et al.	6,485,413 B1	11/2002	Boppart et al.
6,014,214 A	1/2000	Li	6,485,482 B1	11/2002	Belef
6,016,197 A	1/2000	Krivoshlykov	6,501,551 B1	12/2002	Tearney et al.
6,020,963 A	2/2000	DiMarzio	6,501,878 B2	12/2002	Hughes et al.
6,025,956 A	2/2000	Nagano et al.	6,516,014 B1 *	2/2003	Sellin et al. 372/32
6,033,721 A	3/2000	Nassuphis	6,517,532 B1	2/2003	Altshuler et al.
6,037,579 A	3/2000	Chan et al.	6,538,817 B1	3/2003	Farmer et al.
6,044,288 A	3/2000	Wake et al.	6,540,391 B2	4/2003	Lanzetta et al.
6,045,511 A	4/2000	Ott et al.	6,549,801 B1	4/2003	Chen et al.
6,048,742 A	4/2000	Weyburne et al.	6,552,796 B2	4/2003	Magnin et al.
6,053,613 A	4/2000	Wei et al.	6,556,305 B1	4/2003	Aziz et al.
6,069,698 A	5/2000	Ozawa et al.	6,556,853 B1	4/2003	Cabib et al.
6,078,047 A *	6/2000	Mittleman et al. 250/338.1	6,558,324 B1	5/2003	Von Behren et al.
6,091,496 A	7/2000	Hill	6,564,087 B1	5/2003	Pitris et al.
6,091,984 A	7/2000	Perelman et al.	6,564,089 B2	5/2003	Izatt et al.
6,094,274 A	7/2000	Yokoi	6,567,585 B2	5/2003	Harris
			6,593,101 B2	7/2003	Richards-Kortum et al.
			6,611,833 B1	8/2003	Johnson
			6,615,071 B1	9/2003	Casscells, III et al.
			6,622,732 B2	9/2003	Constantz

(56)

References Cited

U.S. PATENT DOCUMENTS

6,654,127 B2	11/2003	Everett et al.	2002/0016533 A1	2/2002	Marchitto et al.
6,657,730 B2	12/2003	Pfau et al.	2002/0024015 A1	2/2002	Hoffmann et al.
6,658,278 B2	12/2003	Gruhl	2002/0048025 A1	4/2002	Takaoka
6,680,780 B1	1/2004	Fee	2002/0048026 A1	4/2002	Isshiki et al.
6,685,885 B2	2/2004	Nolte et al.	2002/0052547 A1	5/2002	Toida
6,687,007 B1	2/2004	Meigs	2002/0057431 A1	5/2002	Fateley et al.
6,687,010 B1	2/2004	Horii et al.	2002/0064341 A1	5/2002	Fauver et al.
6,687,036 B2	2/2004	Riza	2002/0076152 A1	6/2002	Hughes et al.
6,692,430 B2	2/2004	Adler	2002/0085209 A1	7/2002	Mittleman et al.
6,701,181 B2	3/2004	Tang et al.	2002/0086347 A1	7/2002	Johnson et al.
6,721,094 B1	4/2004	Sinclair et al.	2002/0091322 A1	7/2002	Chaiken et al.
6,738,144 B1	5/2004	Dogariu	2002/0093662 A1	7/2002	Chen et al.
6,741,355 B2	5/2004	Drabarek	2002/0109851 A1	8/2002	Deck
6,757,467 B1	6/2004	Rogers	2002/0122182 A1	9/2002	Everett et al.
6,790,175 B1	9/2004	Furusawa et al.	2002/0122246 A1	9/2002	Tearney et al.
6,806,963 B1	10/2004	Wälti et al.	2002/0140942 A1	10/2002	Fee et al.
6,816,743 B2	11/2004	Moreno et al.	2002/0158211 A1	10/2002	Gillispie
6,831,781 B2	12/2004	Tearney et al.	2002/0161357 A1	10/2002	Rox et al.
6,839,496 B1	1/2005	Mills et al.	2002/0163622 A1	11/2002	Magnin et al.
6,882,432 B2	4/2005	Deck	2002/0168158 A1	11/2002	Furusawa et al.
6,900,899 B2	5/2005	Nevis	2002/0172485 A1	11/2002	Keaton et al.
6,903,820 B2	6/2005	Wang	2002/0183623 A1	12/2002	Tang et al.
6,909,105 B1	6/2005	Heintzmann et al.	2002/0188204 A1	12/2002	McNamara et al.
6,949,072 B2	9/2005	Furnish et al.	2002/0196446 A1	12/2002	Roth et al.
6,961,123 B1	11/2005	Wang et al.	2002/0198457 A1	12/2002	Tearney et al.
6,980,299 B1	12/2005	de Boer	2003/0001071 A1	1/2003	Mandella et al.
6,996,549 B2	2/2006	Zhang et al.	2003/0013973 A1	1/2003	Georgakoudi et al.
7,006,231 B2	2/2006	Ostrovsky et al.	2003/0023153 A1	1/2003	Izatt et al.
7,006,232 B2	2/2006	Rollins et al.	2003/0026735 A1	2/2003	Nolte et al.
7,019,838 B2	3/2006	Izatt et al.	2003/0028114 A1	2/2003	Casscells, III et al.
7,027,633 B2	4/2006	Foran et al.	2003/0030816 A1	2/2003	Eom et al.
7,061,622 B2	6/2006	Rollins et al.	2003/0043381 A1	3/2003	Fercher
7,072,047 B2	7/2006	Westphal et al.	2003/0053673 A1	3/2003	Dewaele et al.
7,075,658 B2	7/2006	Izatt et al.	2003/0067607 A1	4/2003	Wolleschensky et al.
7,099,358 B1	8/2006	Chong H01S 5/141 372/100	2003/0082105 A1	5/2003	Fischman et al.
7,113,288 B2	9/2006	Fercher	2003/0097048 A1	5/2003	Ryan et al.
7,113,625 B2	9/2006	Watson et al.	2003/0108911 A1	6/2003	Klimant et al.
7,130,320 B2	10/2006	Tobiason et al.	2003/0120137 A1	6/2003	Pawluczyk
7,139,598 B2	11/2006	Hull et al.	2003/0135101 A1	7/2003	Webler
7,142,835 B2	11/2006	Paulus	2003/0137669 A1	7/2003	Rollins et al.
7,148,970 B2	12/2006	De Boer	2003/0164952 A1	9/2003	Deichmann et al.
7,177,027 B2	2/2007	Hirasawa et al.	2003/0165263 A1	9/2003	Hamer et al.
7,190,464 B2	3/2007	Alphonse	2003/0171691 A1	9/2003	Casscells, III et al.
7,230,708 B2	6/2007	Lapotko et al.	2003/0174327 A1*	9/2003	Tayebati G01J 9/00 356/328
7,231,243 B2	6/2007	Tearney et al.	2003/0174339 A1	9/2003	Feldchtein et al.
7,236,637 B2	6/2007	Sirohey et al.	2003/0199769 A1	10/2003	Podoleanu et al.
7,242,480 B2	7/2007	Alphonse	2003/0216719 A1	11/2003	Debenedictis et al.
7,267,494 B2	9/2007	Deng et al.	2003/0220749 A1	11/2003	Chen et al.
7,272,252 B2	9/2007	De La Torre-Bueno et al.	2003/0236443 A1	12/2003	Cespedes et al.
7,304,798 B2	12/2007	Izumi et al.	2004/0002650 A1	1/2004	Mandrusov et al.
7,330,270 B2	2/2008	O'Hara et al.	2004/0039298 A1	2/2004	Abreu
7,336,366 B2	2/2008	Choma et al.	2004/0054268 A1	3/2004	Esenaliev et al.
7,342,659 B2	3/2008	Horn et al.	2004/0072200 A1	4/2004	Rigler et al.
7,355,716 B2	4/2008	de Boer et al.	2004/0075841 A1	4/2004	Van Neste et al.
7,355,721 B2	4/2008	Quadling et al.	2004/0076940 A1	4/2004	Alexander et al.
7,359,062 B2	4/2008	Chen et al.	2004/0077949 A1	4/2004	Blofgett et al.
7,366,376 B2	4/2008	Shishkov et al.	2004/0085540 A1	5/2004	Lapotko et al.
7,382,809 B2	6/2008	Chong et al.	2004/0086245 A1	5/2004	Farroni et al.
7,391,520 B2	6/2008	Zhou et al.	2004/0100631 A1	5/2004	Bashkansky et al.
7,458,683 B2	12/2008	Chernyak et al.	2004/0100681 A1	5/2004	Bjarklev et al.
7,530,948 B2	5/2009	Seibel et al.	2004/0110206 A1	6/2004	Wong et al.
7,539,530 B2	5/2009	Caplan et al.	2004/0126048 A1	7/2004	Dave et al.
7,609,391 B2	10/2009	Betzig	2004/0126120 A1	7/2004	Cohen et al.
7,630,083 B2	12/2009	de Boer et al.	2004/0133191 A1	7/2004	Momiuchi et al.
7,643,152 B2	1/2010	de Boer et al.	2004/0150829 A1	8/2004	Koch et al.
7,643,153 B2	1/2010	de Boer et al.	2004/0150830 A1	8/2004	Chan
7,646,905 B2	1/2010	Guittet et al.	2004/0152989 A1	8/2004	Puttappa et al.
7,649,160 B2	1/2010	Colomb et al.	2004/0165184 A1	8/2004	Mizuno
7,664,300 B2	2/2010	Lange et al.	2004/0166593 A1	8/2004	Nolte et al.
7,733,497 B2	6/2010	Yun et al.	2004/0189999 A1	9/2004	De Groot et al.
7,782,464 B2	8/2010	Mujat et al.	2004/0212808 A1	10/2004	Okawa et al.
7,805,034 B2	9/2010	Kato et al.	2004/0239938 A1	12/2004	Izatt
2001/0036002 A1	11/2001	Tearney et al.	2004/0246490 A1	12/2004	Wang
2001/0047137 A1	11/2001	Moreno et al.	2004/0246583 A1	12/2004	Mueller et al.
			2004/0254474 A1	12/2004	Seibel et al.
			2004/0263843 A1	12/2004	Knopp et al.
			2005/0018133 A1	1/2005	Huang et al.
			2005/0018201 A1	1/2005	De Boer

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0035296	A1	2/2005	Kojima et al.
2005/0036150	A1	2/2005	Izatt et al.
2005/0046837	A1	3/2005	Izumi et al.
2005/0057680	A1	3/2005	Agan
2005/0057756	A1	3/2005	Fang-Yen et al.
2005/0059894	A1	3/2005	Zeng et al.
2005/0065421	A1	3/2005	Burckhardt et al.
2005/0075547	A1	4/2005	Wang
2005/0083534	A1	4/2005	Riza et al.
2005/0119567	A1	6/2005	Choi
2005/0128488	A1	6/2005	Yelin et al.
2005/0165303	A1	7/2005	Kleen et al.
2005/0171438	A1	8/2005	Chen et al.
2005/0190372	A1	9/2005	Dogariu et al.
2005/0254061	A1	11/2005	Alphonse et al.
2006/0033923	A1	2/2006	Hirasawa et al.
2006/0093276	A1	5/2006	Bouma et al.
2006/0103850	A1	5/2006	Alphonse et al.
2006/0146339	A1	7/2006	Fujita
2006/0155193	A1	7/2006	Leonardi et al.
2006/0164639	A1	7/2006	Horn et al.
2006/0171503	A1	8/2006	O'Hara et al.
2006/0184048	A1	8/2006	Saadat et al.
2006/0193352	A1	8/2006	Chong et al.
2006/0244973	A1	11/2006	Yun et al.
2006/0256348	A1*	11/2006	Toida A61B 5/0066 356/511
2007/0019208	A1	1/2007	Toida et al.
2007/0038040	A1	2/2007	Cense et al.
2007/0070496	A1	3/2007	Gweon et al.
2007/0076217	A1	4/2007	Baker et al.
2007/0086013	A1	4/2007	De Lega et al.
2007/0086017	A1	4/2007	Buckland et al.
2007/0091317	A1	4/2007	Freischlad et al.
2007/0133002	A1	6/2007	Wax et al.
2007/0188855	A1	8/2007	Shishkov et al.
2007/0223006	A1	9/2007	Tearney et al.
2007/0236700	A1	10/2007	Yun et al.
2007/0258094	A1	11/2007	Izatt et al.
2007/0291277	A1	12/2007	Everett et al.
2008/0002197	A1	1/2008	Sun et al.
2008/0007734	A1	1/2008	Park et al.
2008/0049220	A1	2/2008	Izzia et al.
2008/0094613	A1	4/2008	de Boer et al.
2008/0094637	A1	4/2008	de Boer et al.
2008/0097225	A1	4/2008	Tearney et al.
2008/0097709	A1	4/2008	de Boer et al.
2008/0100837	A1	5/2008	de Boer et al.
2008/0152353	A1	6/2008	de Boer et al.
2008/0154090	A1	6/2008	Hashimshony
2008/0204762	A1	8/2008	Izatt et al.
2008/0265130	A1	10/2008	Colomb et al.
2008/0308730	A1	12/2008	Vizi et al.
2009/0011948	A1	1/2009	Unlu et al.
2009/0196477	A1	8/2009	Cense et al.
2009/0273777	A1	11/2009	Yun et al.
2009/0290156	A1	11/2009	Popescu et al.
2010/0086251	A1	4/2010	Xu et al.
2010/0094576	A1	4/2010	de Boer et al.
2010/0150467	A1	6/2010	Zhao et al.

FOREIGN PATENT DOCUMENTS

DE	4309056	9/1994
DE	19542955	5/1997
DE	10351319	6/2005
EP	0110201	6/1984
EP	0251062	1/1988
EP	0617286	2/1994
EP	0590268	4/1994
EP	0728440	8/1996
EP	0933096	8/1999
EP	1324051	7/2003
EP	1426799	6/2004

FR	2738343	8/1995
GB	1257778	12/1971
GB	2030313	4/1980
GB	2209221	5/1989
GB	2298054	8/1996
JP	6073405	4/1985
JP	20040056907	2/1992
JP	4135550	5/1992
JP	4135551	5/1992
JP	5509417	11/1993
JP	2002214127	7/2002
JP	20030035659	2/2003
JP	2007271761	10/2007
WO	7900841	10/1975
WO	9201966	2/1992
WO	9216865	10/1992
WO	9219930	11/1992
WO	9303672	3/1993
WO	9533971	12/1995
WO	9628212	9/1996
WO	9732182	8/1997
WO	9800057	1/1998
WO	9801074	1/1998
WO	9814132	4/1998
WO	9835203	8/1998
WO	9838907	9/1998
WO	9846123	10/1998
WO	9848838	11/1998
WO	9848846	11/1998
WO	9905487	2/1999
WO	9944089	2/1999
WO	9944089	9/1999
WO	9957507	11/1999
WO	0058766	10/2000
WO	0101111	1/2001
WO	0108579	2/2001
WO	0127679	4/2001
WO	0138820	5/2001
WO	0142735	6/2001
WO	03020119	3/2002
WO	0236015	5/2002
WO	0237075	5/2002
WO	0238040	5/2002
WO	02053050	7/2002
WO	02054027	7/2002
WO	02084263	10/2002
WO	03046495	6/2003
WO	03046636	6/2003
WO	03052478	6/2003
WO	03062802	7/2003
WO	03105678	12/2003
WO	2004034869	4/2004
WO	2004057266	7/2004
WO	2004066824	8/2004
WO	2004088361	10/2004
WO	2004105598	12/2004
WO	2005000115	1/2005
WO	2005047813	5/2005
WO	2005054780	6/2005
WO	2005082225	9/2005
WO	20050082225	9/2005
WO	2006004743	1/2006
WO	2006014392	2/2006
WO	2006038876	4/2006
WO	2006039091	4/2006
WO	2006059109	6/2006
WO	2006124860	11/2006
WO	2006130797	12/2006
WO	2007028531	3/2007
WO	2007038787	4/2007
WO	2007083138	7/2007
WO	2007084995	7/2007

OTHER PUBLICATIONS

European Search Report for European Patent Application No. 10183497.6 dated Oct. 8, 2013.
 European Search Report for European Patent Application No. 10183412.5 dated Sep. 10, 2013.

(56)

References Cited

OTHER PUBLICATIONS

- European Search Report for European Patent Application No. 101834758.0 dated Oct. 31, 2012.
- European Search Report for European Patent Application No. 10183326.7 dated Dec. 27, 2010.
- European Search Report for European Patent Application No. 15191701.0 dated Mar. 9, 2016.
- S. H. Yun et al., "High-speed wavelength-swept semiconductor laser with a polygon-scanner-based wavelength filter" *Opt Letters*, vol. 28, No. 20 (2003).
- Sanders S T.: "Wavelength-Agile Fiber Laser Using Group-Velocity . . . Broadband Absorption Spectroscopy", *Applied Physics B: Lasers and Optics*, vol. B75, No. 6-07, (2002).
- Xiaoke Wan et al "Linearly chirped erbium-doped fiber laser" *IEEE Photonics Technology Letters*, vol. 15, No. 2, (2003).
- Fujimoto et al., "High Resolution in Vivo Intra-Arterial Imaging with Optical Coherence Tomography," *Official Journal of the British Cardiac Society*, vol. 82, pp. 128-133 Heart, 1999.
- D. Huang et al., "Optical Coherence Tomography," *Science*, vol. 254, pp. 1178-1181, Nov. 1991.
- Teamey et al., "High-Speed Phase—and Group Delay Scanning with a Grating Based Phase Control Delay Line," *Optics Letters*, vol. 22, pp. 1811-1813, Dec. 1997.
- Rollins, et al., "In Vivo Video Rate Optical Coherence Tomography," *Optics Express*, vol. 3, pp. 219-229, Sep. 1998.
- Saxer, et al., High Speed Fiber-Based Polarization-Sensitive Optical Coherence Tomography of in Vivo Human Skin, *Optical Society of America*, vol. 25, pp. 1355-1357, Sep. 2000.
- Oscar Eduardo Martinez, "3000 Times Grating Compress or with Positive Group Velocity Dispersion," *IEEE*, vol. QE-23, pp. 59-64, Jan. 1987.
- Kulkarni, et al., "Image Enhancement in Optical Coherence Tomography Using Deconvolution," *Electronics Letters*, vol. 33, pp. 1365-1367, Jul. 1997.
- Bashkansky, et al., "Signal Processing for Improving Field Cross-Correlation Function in Optical Coherence Tomography," *Optics & Photonics News*, vol. 9, pp. 8137-8138, May 1998.
- Yung et al., "Phase-Domain Processing of Optical Coherence Tomography Images," *Journal of Biomedical Optics*, vol. 4, pp. 125-136, Jan. 1999.
- Tearney, et al., "In Vivo Endoscopic Optical Biopsy with Optical Coherence Tomography," *Science*, vol. 276, Jun. 1997.
- W. Drexler et al., "In Vivo Ultrahigh-Resolution Optical Coherence Tomography," *Optics Letters* vol. 24, pp. 1221-1223, Sep. 1999.
- Nicuser V. Iftimia et al., (2005) "A Portable, Low Coherence Interferometry Based Instrument for Fine Needle Aspiration Biopsy Guidance," Accepted to Review of Scientific Instruments, published May 23, 2005.
- Abbas, G.L., V.W.S. Chan et al., "Local-Oscillator Excess-Noise Suppression for Homodyne and Heterodyne-Detection," *Optics Letters*, vol. 8, pp. 419-421, Aug. 1983 issue.
- Agrawal, G.P., "Population Pulsations and Nondegenerate 4-Wave Mixing in Semiconductor-Lasers and Amplifiers," *Journal Of Rhe Optical Society Of America B-Optical Physics*, vol. 5, pp. 147-159, Jan. 1998.
- Andretzky, P. et al., "Optical Coherence Tomography by Spectral Radar: Improvement of Signal-to-Noise Ratio," *The International Society for Optical Engineering*, USA, vol. 3915, 2000.
- Ballif, J. et al., "Rapid and Scalable Scans at 21 m/s in optical Low-Coherence Reflectometry," *Optics Letters*, vol. 22, pp. 757-759, Jun. 1997.
- Barfuss H. et al., "Modified Optical Frequency-Domain Reflectometry with High Spatial-Resolution for Components of Integrated Optic Systems," *Journal of Lightwave Technology*, vol. 7, pp. 3-10, Jan. 1989.
- Beaud, P. et al., "Optical Reflectometry with Micrometer Resolution for the Investigation of Integrated Optical-Devices," *Lee Journal of Quantum Electronics*, vol. 25, pp. 755-759, Apr. 1989.
- Bouma, Brett et al., "Power-Efficient Nonreciprocal Interferometer and Linear-Scanning Fiber-Optic Catheter for Optical Coherence Tomography," *Optics Letters*, vol. 24, pp. 531-533, Apr. 1999.
- Brinkmeyer, E. et al., "Efficient Algorithm for Non-Equidistant Interpolation of Sampled Data," *Electronics Letters*, vol. 28, p. 693, Mar. 1992.
- Brinkmeyer, E. et al., "High-Resolution OCDR in Dispersive Wave-Guides," *Electronics Letters*, vol. 26, pp. 413-414, Mar. 1990.
- Chinn, S.R. et al., "Optical Coherence Tomography Using a Frequency-Tunable Optical Source," *Optics Letters*, vol. 22, pp. 340-342, Mar. 1997.
- Danielson, B.L. et al., "Absolute Optical Ranging Using Low Coherence Interferometry," *Applied Optics*, vol. 30, p. 2975, Jul. 1991.
- Dorrer, C. et al., "Spectral Resolution and Sampling Issues in Fourier-Transform Spectral Interferometry," *Journal of the Optical Society of America B-Optical Physics*, vol. 17, pp. 1795-1802, Oct. 2000.
- Dudley, J.M. et al., "Cross-Correlation Frequency Resolved Optical Gating Analysis of Broadband Continuum Generation in Photonic Crystal Fiber: Simulations and Experiments," *Optics Express*, vol. 10, p. 1215, Oct. 2002.
- Eickhoff, W. et al., "Optical Frequency-Domain Reflectometry in Single-Mode Fiber," *Applied Physics Letters*, vol. 39, pp. 693-695, 1981.
- Fercher, Adolf "Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 1, pp. 157-173, Apr. 1996.
- Ferreira, L.A. et al., "Polarization-Insensitive Fiberoptic White-Light Interferometry," *Optics Communications*, vol. 114, pp. 386-392, Feb. 1995.
- Fujii, Yohji, "High-Isolation Polarization-Independent Optical Circulator", *Journal of Lightwave Technology*, vol. 9, pp. 1239-1243, Oct. 1991.
- Glance, B., "Polarization Independent Coherent Optical Receiver," *Journal of Lightwave Technology*, vol. LT-5, p. 274, Feb. 1987.
- Glombitza, U., "Coherent Frequency-Domain Reflectometry for Characterization of Single-Mode Integrated-Optical Wave-Guides," *Journal of Lightwave Technology*, vol. 11, pp. 1377-1384, Aug. 1993.
- Golubovic, B. et al., "Optical Frequency-Domain Reflectometry Using Rapid Wavelength Tuning of a Cr⁴⁺:Forsterite Laser," *Optics Letters*, vol. 11, pp. 1704-1706, Nov. 1997.
- Haberland, U. H. P. et al., "Chirp Coherence Optical Tomography of Layered Scattering Media," *Journal of Biomedical Optics*, vol. 3, pp. 259-266, Jul. 1998.
- Hammer, Daniel X. et al., "Spectrally Resolved White-Light Interferometry for Measurement of Ocular Dispersion," *Journal of the Optical Society of America A-Optics Image Science and Vision*, vol. 16, pp. 2092-2102, Sep. 1999.
- Harvey, K. C. et al., "External-Cavity Diode-Laser Using a Grazing-Incidence Diffraction Grating," *Optics Letters*, vol. 16, pp. 910-912, Jun. 1991.
- Hausler, Gerd et al., "'Coherence Radar' and 'Spectral Radar' New Tools for Dermatological Diagnosis," *Journal of Biomedical Optics*, vol. 3, pp. 21-31, Jan. 1998.
- Hee, Michael R. et al., "Polarization-Sensitive Low-Coherence Reflectometer for Birefringence Characterization and Ranging," *Journal of the Optical Society of America B (Optical Physics)*, vol. 9, p. 903-908, Jun. 1992.
- Hotate Kazuo et al., "Optical Coherence Domain Reflectometry by Synthesis of Coherence Function," *Journal of Lightwave Technology*, vol. 11; pp. 1701-1710, Oct. 1993.
- Inoue, Kyo et al., "Nearly Degenerate 4-Wave-Mixing in a Traveling-Wave Semiconductor-Laser Amplifier," *Applied Physics Letters*, vol. 51, pp. 1051-1053, 1987.
- Ivanov, A. P. et al., "New Method for High-Range Resolution Measurements of Light Scattering in Optically Dense Inhomogeneous Media," *Optics Letters*, vol. 1, pp. 226-228, Dec. 1977.
- Ivanov, A. P. et al., "Interferometric Study of the Spatial Structure of a Light-Scattering Medium," *Journal of Applied Spectroscopy*, vol. 28, pp. 518-525, 1978.

(56)

References Cited

OTHER PUBLICATIONS

- Kazovsky, L. G. et al., "Heterodyne Detection Through Rain, Snow, and Turbid Media: Effective Receiver Size at Optical Through Millimeter Wavelengths," *Applied Optics*, vol. 22, pp. 706-710, Mar. 1983.
- Kersey, A. D. et al., "Adaptive Polarization Diversity Receiver Configuration for Coherent Optical Fiber Communications," *Electronics Letters*, vol. 25, pp. 275-277, Feb. 1989.
- Kohlhaas, Andreas et al., "High-Resolution OADR for Testing Integrated-Optical Waveguides: Dispersion-Corrupted Experimental Data Corrected by a Numerical Algorithm," *Journal of Lightwave Technology*, vol. 9, pp. 1493-1502, Nov. 1991.
- Larkin, Kieran G., "Efficient Nonlinear Algorithm for Envelope Detection in White Light Interferometry," *Journal of the Optical Society of America A-Optics Image Science and Vision*, vol. 13, pp. 832-843, Apr. 1996.
- Leitgeb, R. et al., "Spectral measurement of Absorption by Spectroscopic Frequency-Domain Optical Coherence Tomography," *Optics Letters*, vol. 25, pp. 820-822, Jun. 2000.
- Lexer, F. et al., "Wavelength-Tuning Interferometry of Intraocular Distances," *Applied Optics*, vol. 36, pp. 6548-6553, Sep. 1997.
- Mitsui, Takahisa, "Dynamic Range of Optical Reflectometry with Spectral Interferometry," *Japanese Journal of Applied Physics Part 1-Regular Papers Short Notes & Review Papers*, vol. 38, pp. 6133-6137, 1999.
- Naganuma, Kazunori et al., "Group-Delay Measurement Using the Fourier-Transform of an Interferometric Cross-Correlation Generated by White Light," *Optics Letters*, vol. 15, pp. 393-395, Apr. 1990.
- Okoshi, Takanori, "Polarization-State Control Schemes for Heterodyne or Homodyne Optical Fiber Communications," *Journal of Lightwave Technology*, vol. LT-3, pp. 1232-1237, Dec. 1995.
- Passy, R. et al., "Experimental and Theoretical Investigations of Coherent OFDR with Semiconductor-Laser Sources," *Journal of Lightwave Technology*, vol. 12, pp. 1622-1630, Sep. 1994.
- Podoleanu, Adrian G., "Unbalanced Versus Balanced Operation in an Optical Coherence Tomography System," *Applied Optics*, vol. 39, pp. 173-182, Jan. 2000.
- Price, J. H. V. et al., "Tunable, Femtosecond Pulse Source Operating in the Range 1.06-1.33 μm Based on an Yb³⁺-doped Holey Fiber Amplifier," *Journal of the Optical Society of America B-Optical Physics*, vol. 19, pp. 1286-1294, Jun. 2002.
- Schmitt, J. M. et al., "Measurement of Optical-Properties of Biological By Low-Tissues Coherence Reflectometry," *Applied Optics*, vol. 32, pp. 6032-6042, Oct. 1993.
- Silberberg, Y. et al., "Passive-Mode Locking of a Semiconductor Diode-Laser," *Optics Letters*, vol. 9, pp. 507-509, Nov. 1984.
- Smith, L. Montgomery et al., "Absolute Displacement Measurements Using Modulation of the Spectrum of White-Light in a Michelson Interferometer," *Applied Optics*, vol. 28, pp. 3339-3342, Aug. 1989.
- Sonnenschein, C. M. et al., "Signal-To-Noise Relationships for Coaxial Systems that Heterodyne Backscatter from Atmosphere," *Applied Optics*, vol. 10, pp. 1600-1604, Jul. 1971.
- Sorin, W. V. et al., "Measurement of Rayleigh Backscattering at 1.55 μm with 32 μm Spatial Resolution," *IEEE Photonics Technology Letters*, vol. 4, pp. 374-376, Apr. 1992.
- Sorin, W. V. et al., "A Simple Intensity Noise-Reduction Technique for Optical Low-Coherence Reflectometry," *IEEE Photonics Technology Letters*, vol. 4, pp. 1404-1406, Dec. 1992.
- Swanson, E. A. et al., "High-Speed Optical Coherence Domain Reflectometry," *Optics Letters*, vol. 17, pp. 151-153, Jan. 1992.
- Takada, K. et al., "High-Resolution OFDR with Incorporated Fiber optic Frequency Encoder," *IEEE Photonics Technology Letters*, vol. 4, pp. 1069-1072, Sep. 1992.
- Takada, Kazumasa et al., "Narrow-Band light Source with Acoustooptic Tunable Filter for Optical Low-Coherence Reflectometry," *IEEE Photonics Technology Letters*, vol. 8, pp. 658-660, May 1996.
- Takada, Kazumasa et al., "New Measurement System for Fault Location in Optical Wave-Guide Devices Based on an Interometric-Technique," *Applied Optics*, vol. 26, pp. 1603-1606, May 1987.
- Tateda, Mitsuhiro et al., "Interferometric Method for Chromatic Dispersion Measurement in a Single-Mode Optical Fiber," *IEEE Journal of Quantum Electronics*, vol. 17, pp. 404-407, Mar. 1981.
- Toide, M. et al., "Two-Dimensional Coherent Detection Imaging in Multiple Scattering Media Based the Directional Resolution Capability of the Optical Heterodyne Method," *Applied Physics B (Photophysics and Laser Chemistry)*, vol. B52, pp. 391-394, 1991.
- Trutna, W. R. et al., "Continuously Tuned External-Cavity Semiconductor-Laser," *Journal of Lightwave Technology*, vol. 11, pp. 1279-1286, Aug. 1993.
- Uttam, Deepak et al., "Precision Time Domain Reflectometry in Optical Fiber Systems Using a Frequency Modulated Continuous Wave Ranging Technique," *Journal of Lightwave Technology*, vol. 3, pp. 971-977, Oct. 1985.
- Von Der Weid, J. P. et al., "On the Characterization of Optical Fiber Network Components with Optical Frequency Domain Reflectometry," *Journal of Lightwave Technology*, vol. 15, pp. 1131-1141, Jul. 1997.
- Wysocki, P.F. et al., "Broad-Spectrum, Wavelength-Swept, Erbium-Doped Fiber Laser at 1.55- μm ," *Optics Letters*, vol. 15, pp. 879-881, Aug. 1990.
- Youngquist, Robert C. et al., "Optical Coherence-Domain Reflectometry—A New Optical Evaluation Technique," *Optics Letters*, vol. 12, pp. 158-160, Mar. 1987.
- Yun, S. H. et al., "Wavelength-Swept Fiber Laser with Frequency Shifted Feedback and Resonantly Swept Intra-Cavity Acoustooptic Tunable Filter," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 3, pp. 1087-1096, Aug. 1997.
- Yun, S. H. et al., "Interrogation of Fiber Grating Sensor Arrays with a Wavelength-Swept Fiber Laser," *Optics Optics*, vol. 23, pp. 843-845, Jun. 1998.
- Yung, K. M., "Phase-Domain Processing of Optical Coherence Tomography Images," *Journal of Biomedical Optics*, vol. 4, pp. 125-136, Jan. 1999.
- Zhou, Xiao-Qun et al., "Extended-Range FMCW Reflectometry Using an optical Loop with a Frequency Shifter," *IEEE Photonics Technology Letters*, vol. 8, pp. 248-250, Feb. 1996.
- Zorabedian, Paul et al., "Tuning Fidelity of Acoustooptically Controlled External Cavity Semiconductor-Lasers," *Journal of Lightwave Technology*, vol. 13, pp. 62-66, Jan. 1995.
- Victor S. Y. Lin et al., "A Porous Silicon-Based Optical Interferometric Biosensor," *Science Magazine*, vol. 278, pp. 840-843, Oct. 31, 1997.
- De Boer, Johannes F. et al., "Review of Polarization Sensitive Optical Coherence Tomography and Stokes Vector Determination," *Journal of Biomedical Optics*, vol. 7, No. 3, Jul. 2002, pp. 359-371.
- Jiao, Shuliang et al., "Depth-Resolved Two-Dimensional Stokes Vectors of Backscattered Light and Mueller Matrices of Biological Tissue Measured with Optical Coherence Tomography," *Applied Optics*, vol. 39, No. 34, Dec. 1, 2000, pp. 6318-6324.
- Park, B. Hyle et al., "In Vivo Burn Depth Determination by High-Speed Fiber-Based Polarization Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 6, No. 4, Oct. 2001, pp. 474-479.
- Roth, Jonathan E. et al., "Simplified Method for Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 26, No. 14, Jul. 15, 2001, pp. 1069-1071.
- Hitzenberger, Christopher K. et al., "Measurement and Imaging of Birefringence and Optic Axis Orientation by Phase Resolved Polarization Sensitive Optical Coherence Tomography," *Optics Express*, vol. 9, No. 13, Dec. 17, 2001, pp. 780-790.
- Wang, Xuedong et al., (2001) "Propagation of Polarized Light in Birefringent Turbid Media: Time-Resolved Simulations," *Optical Imaging Laboratory*, Biomedical Engineering Program, Texas A&M University, Aug. 27, 2001, pp. 254-259.
- Wong, Brian J.F. et al., "Optical Coherence Tomography of the Rat Cochlea," *Journal of Biomedical Optics*, vol. 5, No. 4, Oct. 2000, pp. 367-370.
- Yao, Gang et al., "Propagation of Polarized Light in Turbid Media: Simulated Animation Sequences," *Optics Express*, vol. 7, No. 5, Aug. 28, 2000, pp. 198-203.

(56)

References Cited

OTHER PUBLICATIONS

- Wang, Xiao-Jun et al., "Characterization of Dentin and Enamel by Use of Optical Coherence Tomography," *Applied Optics*, vol. 38, No. 10, Apr. 1, 1999, pp. 2092-2096.
- De Boer, Johannes F. et al., "Detelination of the Depth-Resolved Stokes Parameters of Light Backscattered from Turbid Media by use of Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 24, No. 5, Mar. 1, 1999, pp. 300-302.
- Ducros, Mathieu G. et al., "Polarization Sensitive Optical Coherence Tomography of the Rabbit Eye," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 5, No. 4, Jul./Aug. 1999, pp. 1159-1167.
- Groner, Warren et al., "Orthogonal Polarization Spectral Imaging: A New the Method for Study of Microcirculation," *Nature Medicine Inc.*, vol. 5 No. 10, Oct. 1999, pp. 1209-1213.
- De Boer, Johannes F. et al., "Polarization Effects in Optical Coherence Tomography of Various Viological Tissues," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 5, No. 4, Jul./Aug. 1999, pp. 1200-1204.
- Yao, Gang et al., "Two-Dimensional Depth-Resolved Mueller Matrix Characterization of Biological Tissue by Optical Coherence Tomography," *Optics Letters*, Apr. 15, 1999, vol. 24, No. 8, pp. 537-539.
- Lu, Shih-Yau et al., "Homogeneous and Inhomogeneous Jones Matrices," *J. Opt. Soc. Am. A.*, vol. 11, No. 2, Feb. 1994, pp. 766-773.
- Bickel, S. William et al., "Stokes Vectors, Mueller Matrices, and Polarized Scattered Light," *Am. J. Phys.*, vol. 53, No. 5, May 1985 pp. 468-478.
- Brehonnet, F. Le Roy et al., "Optical Media and Target Characterization by Mueller Matrix Decomposition," *J. Phys. D: Appl. Phys.* 29, 1996, pp. 34-38.
- Cameron, Brent D. et al., "Measurement and Calculation of the Two-Dimensional Backscattering Mueller Matrix of a Turbid Medium," *Optics Letters*, vol. 23, No. 7, Apr. 1, 1998, pp. 485-487.
- De Boer, Johannes F. et al., "Two-Dimensional Birefringence Imaging in Biological Tissue by Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 22, No. 12, Jun. 15, 1997, pp. 934-936.
- De Boer, Johannes F. et al., "Imaging Thermally Damaged Tissue by Polarization Sensitive Optical Coherence Tomography," *Optics Express*, vol. 3, No. 6, Sep. 14, 1998, pp. 212-218.
- Everett, M.J. et al., "Birefringence Characterization of Biological Tissue by Use of Optical Coherence Tomography," *Optics Letters*, vol. 23, No. 3, Feb. 1, 1998, pp. 228-230.
- Hee, Michael R. et al., "Polarization-Sensitive Low-Coherence Reflectometer for Birefringence Characterization and Ranging," *J. Opt. Soc. Am. B.*, vol. 9, No. 6, Jun. 1992, pp. 903-908.
- Barakat, Richard, "Statistics of the Stokes Parameters," *J. Opt. Soc. Am. B.*, vol. 4, No. 7, Jul. 1987, pp. 1256-1263.
- Schmitt, J.M. et al., "Cross-Polarized Backscatter in Optical Coherence Tomography of Biological Tissue," *Optics Letters*, vol. 23, No. 13, Jul. 1, 1998, pp. 1060-1062.
- Schoenenberger, Klaus, et al., "Mapping of Birefringence and Thermal Damage in Tissue by use of Polarization-Sensitive Optical Coherence Tomography," *Applied Optics*, vol. 37, No. 25, Sep. 1, 1998, pp. 6026-6036.
- Pierce, Mark C. et al., "Simultaneous Intensity, Birefringence, and Flow Measurements with High-Speed Fiber-Based Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 17, Sep. 1, 2002, pp. 1534-1536.
- De Boer, Johannes F. et al., "Review of Polarization Sensitive Optical Coherence Tomography and Stokes Vector Determination," *Journal of Biomedical Optics*, Jul. 2002, vol. 7, No. 3, pp. 359-371.
- Fried, Daniel et al., "Imaging Caries Lesions and Lesion Progression with Polarization Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 7, No. 4, Oct. 2002, pp. 618-627.
- Jiao, Shuliang et al., "Two-Dimensional Depth-Resolved Mueller Matrix of Biological Tissue Measured with Double-Beam Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 2, Jan. 15, 2002, pp. 101-103.
- Jiao, Shuliang et al., "Jones-Matrix Imaging of Biological Tissues with Quadruple-Channel Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 7, No. 3, Jul. 2002, pp. 350-358.
- Kuranov, R.V. et al., "Complementary Use of Cross-Polarization and Standard OCT for Differential Diagnosis of Pathological Tissues," *Optics Express*, vol. 10, No. 15, Jul. 29, 2002, pp. 707-713.
- Cense, Barry et al., "In Vivo Depth-Resolved Birefringence Measurements Optical of the Human Optics Retinal Nerve Fiber Layer by Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 18, Sep. 15, 2002, pp. 1610-1612.
- Ren, Hongwu et al., "Phase-Resolved Functional Optical Coherence Tomography: Simultaneous Imaging of In Situ Tissue Structure, Blood Flow Velocity, Standard Deviation, Birefringence, and Stokes Vectors in Human Skin," *Optics Letters*, vol. 27, No. 19, Oct. 1, 2002, pp. 1702-1704.
- Tripathi, Renu et al., "Spectral Shaping for Non-Gaussian Source Spectra in Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 6, Mar. 15, 2002, pp. 406-408.
- Yasuno, Y. et al., "Birefringence Imaging of Human Skin by Polarization-Sensitive Spectral Interferometric Optical Coherence Tomography," *Optics Letters*, vol. 27, No. 20, Oct. 15, 2002 pp. 1803-1805.
- White, Brian R. et al., "In Vivo Dynamic Human Retinal Blood Flow Imaging Using Ultra-High-Speed Spectral Domain Optical Doppler Tomography," *Optics Express*, vol. 11, No. 25, Dec. 15, 2003, pp. 3490-3497.
- De Boer, Johannes F. et al., "Improved Signal-to-Noise Ratio in Spectral-Domain Compared with Time-Domain Optical Coherence Tomography," *Optics Letters*, vol. 28, No. 21, Nov. 1, 2003, pp. 2067-2069.
- Jiao, Shuliang et al., "Optical-Fiber-Based Mueller Optical Coherence Tomography," *Optics Letters*, vol. 28, No. 14, Jul. 15, 2003, pp. 1206-1208.
- Jiao, Shuliang et al., "Contrast Mechanisms in Polarization-Sensitive Mueller-Matrix Optical Coherence Tomography and Application in Burn Imaging," *Applied Optics*, vol. 42, No. 25, Sep. 1, 2003, pp. 5191-5197.
- Moreau, Julien et al., "Full-Field Birefringence Imaging by Thermal-Light Polarization-Sensitive Optical Coherence Tomography. I. Theory," *Applied Optics*, vol. 42, No. 19, Jul. 1, 2003, pp. 3800-3810.
- Moreau, Julien et al., "Full-Field Birefringence Imaging by Thermal-Light Polarization-Sensitive Optical Coherence Tomography. II. Instrument and Results," *Applied Optics*, vol. 42, No. 19, Jul. 1, 2003, pp. 3811-3818.
- Morgan, Stephen P. et al., "Surface-Reflection Elimination in Polarization Imaging of Superficial Tissue," *Optics Letters*, vol. 28, No. 2, Jan. 15, 2003, pp. 114-116.
- Oh, Jung-Taek et al., "Polarization-Sensitive Optical Coherence Tomography for Photoelasticity Testing of Glass/Epoxy Composites," *Optics Express*, vol. 11, No. 14, Jul. 14, 2003, pp. 1669-1676.
- Park, B. Hyle et al., "Real-Time Multi-Functional Optical Coherence Tomography," *Optics Express*, vol. 11, No. 7, Apr. 7, 2003, pp. 782-793.
- Shribak, Michael et al., "Techniques for Fast and Sensitive Measurements of Two-Dimensional Birefringence Distributions," *Applied Optics*, vol. 42, No. 16, Jun. 1, 2003, pp. 3009-3017.
- Somervell, A.R.D. et al., "Direct Measurement of Fringe Amplitude and Phase Using a Heterodyne Interferometer Operating in Broadband Light," *Elsevier, Optics Communications*, Oct. 2003.
- Stifter, D. et al., "Polarisation-Sensitive Optical Coherence Tomography for Material Characterisation and Strain-Field Mapping," *Applied Physics A 76, Materials Science & Processing*, Jan. 2003, pp. 947-951.
- Davé, Digant P. et al., "Polarization-Maintaining Fiber-Based Optical Low-Coherence Reflectometer for Characterization and Ranging of Birefringence," *Optics Letters*, vol. 28, No. 19, Oct. 1, 2003, pp. 1775-1777.
- Yang, Ying et al., "Observations of Birefringence in Tissues from Optic-Fibre-Based Optical Coherence Tomography," *Measurement Science and Technology*, Nov. 2002, pp. 41-46.
- Yun, S.H. et al., "High-Speed Optical Frequency-Domain Imaging," *Optics Express*, vol. 11, No. 22, Nov. 3, 2003, pp. 2953-2963.

(56)

References Cited

OTHER PUBLICATIONS

- Yun, S.H. et al., "High-Speed Spectral-Domain Optical Coherence Tomography at 1.3 μm Wavelength," *Optics Express*, vol. 11, No. 26, Dec. 29, 2003, pp. 3598-3604.
- Zhang, Jun et al., "Determination of Birefringence and Absolute Optic Axis Orientation Using Polarization-Sensitive Optical Coherence Tomography with PM Fibers," *Optics Express*, vol. 11, No. 24, Dec. 1, 2003, pp. 3262-3270.
- Pircher, Michael et al., "Three Dimensional Polarization Sensitive OCT of Human Skin In Vivo," 2004, *Optical Society of America*.
- Götzinger, Erich et al., "Measurement and Imaging of Birefringent Properties of the Human Cornea with Phase-Resolved, Polarization-Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 1, Jan./Feb. 2004, pp. 94-102.
- Guo, Shuguang et al., "Depth-Resolved Birefringence and Differential Optical Axis Orientation Measurements with Finer-based Polarization-Sensitive Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 17, Sep. 1, 2004, pp. 2025-2027.
- Huang, Xiang-Run et al., "Variation of Peripapillary Retinal Nerve Fiber Layer Birefringence in Normal Human Subjects," *Investigative Ophthalmology & Visual Science*, vol. 45, No. 9, Sep. 2004, pp. 3073-3080.
- Matcher, Stephen J. et al., "The Collagen Structure of Bovine Intervertebral Disc Studied Using Polarization-Sensitive Optical Coherence Tomography," *Physics in Medicine and Biology*, 2004, pp. 1295-1306.
- Nassif, Nader et al., "In Vivo Human Retinal Imaging by Ultrahigh-Speed Spectral Domain Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 5, Mar. 1, 2004, pp. 480-482.
- Nassif, N. A. et al., "In Vivo High-Resolution Video-Rate Spectral-Domain Optical Coherence Tomography of the Human Retina and Optic Nerve," *Optics Express*, vol. 12, No. 3, Feb. 9, 2004, pp. 367-376.
- Park, B. Hyle et al., "Comment on Optical-Fiber-Based Mueller Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 24, Dec. 15, 2004, pp. 2873-2874.
- Park, B. Hyle et al., "Jones Matrix Analysis for a Polarization-Sensitive Optical Coherence Tomography System Using Fiber-Optic Components," *Optics Letters*, vol. 29, No. 21, Nov. 1, 2004, pp. 2512-2514.
- Pierce, Mark C. et al., "Collagen Denaturation can be Quantified in Burned Human Skin Using Polarization-Sensitive Optical Coherence Tomography," *Elsevier, Burns*, 2004, pp. 511-517.
- Pierce, Mark C. et al., "Advances in Optical Coherence Tomography Imaging for Dermatology," *The Society for Investigative Dermatology, Inc.* 2004, pp. for 458-463.
- Pierce, Mark C. et al., "Birefringence Measurements in Human Skin Using Polarization-Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 2, Mar./Apr. 2004, pp. 287-291.
- Cense, Barry et al., "In Vivo Birefringence and Thickness Measurements of the Human Retinal Nerve Fiber Layer Using Polarization-Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 1, Jan./Feb. 2004, pp. 121-125.
- Pircher, Michael et al., "Imaging Of Polarization Properties of Human Retina in Vivo with Phase Resolved Transversal PS-OCT," *Optics Express*, vol. 12, No. 24, Nov. 29, 2004 pp. 5940-5951.
- Pircher, Michael et al., "Transversal Phase Resolved Polarization Sensitive Optical Coherence Tomography," *Physics in Medicine & Biology*, 2004, pp. 1257-1263.
- Srinivas, Shyam M. et al., "Determination of Burn Depth by Polarization-Sensitive Optical Coherence Tomography," *Journal of Biomedical Optics*, vol. 9, No. 1, Jan./Feb. 2004, pp. 207-212.
- Strasswimmer, John et al., "Polarization-Sensitive Optical Coherence Tomography of Invasive Basal Cell Carcinoma," *Journal of Biomedical Optics*, vol. 9, No. 2, Mar./Apr. 2004, pp. 292-298.
- Todorovič, Miloš et al., "Determination of Local Polarization Properties of Biological Samples in the Presence of Diattenuation by use of Mueller Optical Coherence Tomography," *Optics Letters*, vol. 29, No. 20, Oct. 15, 2004, pp. 2402-2404.
- Yasuno, Yoshiaki et al., "Polarization-Sensitive Complex Fourier Domain Optical Coherence Tomography for Jones Matrix Imaging of Biological Samples," *Applied Physics Letters*, vol. 85, No. 15, Oct. 11, 2004, pp. 3023-3025.
- Acioli, L. H., M. Ulman, et al. (1991). "Femtosecond Temporal Encoding in Barium-Titanate." *Optics Letters* 16(24): 1984-1986.
- Aigouy, L., A. Lahrech, et al. (1999). "Polarization effects in apertureless scanning near-field optical microscopy: an experimental study." *Optics Letters* 24(4): 187-189.
- Akiba, M., K. P. Chan, et al. (2003). "Full-field optical coherence by two-dimensional heterodyne detection with a pair of CCD cameras." *Optics Letters* 28(10): 816-818.
- Akkin, T., D. P. Dave, et al. (2004). "Detection of neural activity using phase-sensitive optical low-coherence reflectometry." *Optics Express* 12(11): 2377-2386.
- Akkin, T., D. P. Dave, et al. (2003). "Surface analysis using phase sensitive optical low coherence reflectometry." *Lasers in Surgery and Medicine*: 4-4.
- Akkin, T., D. P. Dave, et al. (2003). "Imaging tissue response to electrical and photothermal stimulation with nanometer sensitivity." *Lasers in Surgery and Medicine* 33(4): 219-225.
- Akkin, T., T. E. Milner, et al. (2002). "Phase-sensitive measurement of birefringence change as an indication of neural functionality and diseases." *Lasers in Surgery and Medicine*: 6-6.
- Andretzky, P., Lindner, M.W., Herrmann, J.M., Schultz, A., Konzog, M., Kiesewetter, F., Haeusler, G. (1999). "Optical coherence tomography by 'spectral radar': Dynamic range estimation and in vivo measurements of skin." *Proceedings of SPIE—The International Society for Optical Engineering* 3567: pp. 78-87.
- Antcliff, R. J., T. J. Iffytche, et al. (2000). "Optical coherence tomography of melanocytoma." *American Journal of Ophthalmology* 130(6): 845-7.
- Antcliff, R. J., M. R. Stanford, et al. (2000). "Comparison between optical coherence tomography and fundus fluorescein angiography for the detection of cystoid macular edema in patients with uveitis." *Ophthalmology* 107(3): 593-9.
- Anvari, B., T. E. Milner, et al. (1995) "Selective Cooling of Biological Tissues—Application for Thermally Mediated Therapeutic Procedures." *Physics in Medicine and Biology* 40(2):241-252.
- Anvari, B., B. S. Tanenbaum, et al. (1995). "A Theoretical-Study of the Thermal Response of Skin to Cryogen Spray Cooling and Pulsed-Laser Irradiation—Implications for Treatment of Port-Wine Stain Birthmarks." *Physics in Medicine and Biology* 40(9): 1451-1465.
- Arend, O., M. Ruffer, et al. (2000). "Macular circulation in patients with diabetes mellitus with and without arterial hypertension." *British Journal of Ophthalmology* 84(12): 1392-1396.
- Arimoto, H. and Y. Ohtsuka (1997). "Measurements of the complex degree of spectral coherence by use of a wave-front-folded interferometer." *Optics Letters* 22 (13): 958-960.
- Azzolini, C., F. Patelli, et al. (2001). "Correlation between optical coherence tomography data and biomicroscopic interpretation of idiopathic macular hole." *American Journal of Ophthalmology* 132(3): 348-55.
- Baba, T., K. Ohno-Matsui, et al. (2002). "Optical coherence tomography of choroidal neovascularization in high myopia." *Acta Ophthalmologica Scandinavica* 80(1): 82-7.
- Bail, M. A. H., Gerd; Herrmann, Juergen M.; Lindner, Michael W.; Ringler, R. (1996). "Optical coherence tomography with the "spectral radar": fast optical analysis in volume scatterers by short-coherence interferometry." *Proc. SPIE*, 2925: p. 298-303.
- Baney, D. M. and W. V. Sorin (1993). "Extended-Range Optical Low-Coherence Reflectometry Using a Recirculating Delay Technique." *Ieee Photonics Technology Letters* 5(9): 1109-1112.
- Baney, D. M., B. Szafraniec, et al. (2002). "Coherent optical spectrum analyzer." *Ieee Photonics Technology Letters* 14(3): 355-357.
- Barakat, R. (1981). "Bilinear Constraints between Elements of the 4by4 Mueller-Jones Transfer-Matrix of Polarization Theory." *Optics Communications* 38(3): 159-161.
- Barakat, R. (1993). "Analytic Proofs of the Arago-Fresnel Laws for the Interference of Polarized-Light." *Journal of the Optical Society of America a-Optics Image Science and Vision* 10(1): 180-185.

(56)

References Cited

OTHER PUBLICATIONS

- Barbastathis, G. and D. J. Brady (1999). "Multidimensional tomographic imaging using volume holography." *Proceedings of the IEEE* 87(12): 2098-2120.
- Bardal, S., A. Kamal, et al. (1992). "Photoinduced Birefringence in Optical Fibers—a Comparative-Study of Low-Birefringence and High-Birefringence -Fibers." *Optics Letters* 17(6): 411-413.
- Barsky, S. H., S. Rosen, et al. (1980). "Nature and Evolution of Port Wine Stains—Computer-Assisted Study." *Journal of Investigative Dermatology* 74(3): 154-157.
- Barton, J. K., J. A. Izatt, et al. (1999). "Three-dimensional reconstruction of blood vessels from in vivo color Doppler optical coherence tomography images." *Dermatology* 198(4): 355-361.
- Barton, J. K., A. Rollins, et al. (2001). "Photothermal coagulation of blood vessels: a comparison of high-speed optical coherence tomography and numerical modelling." *Physics in Medicine and Biology* 46.
- Barton, J. K., A. J. Welch, et al. (1998). "Investigating pulsed dye laser-blood vessel interaction with color Doppler optical coherence tomography." *Optics Express* 3.
- Bashkansky, M., M. D. Duncan, et al. (1997). "Subsurface defect detection in ceramics by high-speed high-resolution optical coherent tomography." *Optics Letters* 22 (1): 61-63.
- Bashkansky, M. and J. Reintjes (2000). "Statistics and reduction of speckle in optical coherence tomography." *Optics Letters* 25(8): 545-547.
- Baumgartner, A., S. Dichtl, et al. (2000). "Polarization-sensitive optical coherence tomography of dental structures." *Caries Research* 34(1): 59-69.
- Baumgartner, A., C. K. Hitzenberger, et al. (2000). "Resolution-improved dual-beam and standard optical coherence tomography: a comparison." *Graefes Archive for Clinical and Experimental Ophthalmology* 238(5): 385-392.
- Baumgartner, A., C. K. Hitzenberger, et al. (1998). "Signal and resolution enhancements in dual beam optical coherence tomography of the human eye." *Journal of Biomedical Optics* 3(1): 45-54.
- Beaurepaire, E., P. Gleyzes, et al. (1998). *Optical coherence microscopy for the in-depth study of biological structures: System based on a parallel detection scheme*, Proceedings of SPIE—The International Society for Optical Engineering.
- Beaurepaire, E., L. Moreaux, et al. (1999). "Combined scanning optical coherence and two-photon-excited fluorescence microscopy." *Optics Letters* 24(14): 969-971.
- Bechara, F. G., T. Gambichler, et al. (2004). "Histomorphologic correlation with routine histology and optical coherence tomography." *Skin Research and Technology* 10 (3): 169-173.
- Bechmann, M., M. J. Thiel, et al. (2000). "Central corneal thickness determined with optical coherence tomography in various types of glaucoma. [see comments]." *British Journal of Ophthalmology* 84(11): 1233-7.
- Bek, T. and M. Kandi (2000). "Quantitative anomaloscopy and optical coherence tomography scanning in central serous chorioretinopathy." *Acta Ophthalmologica Scandinavica* 78(6): 632-7.
- Benoit, A. M., K. Naoun, et al. (2001). "Linear dichroism of the retinal nerve fiber layer expressed with Mueller matrices." *Applied Optics* 40(4): 565-569.
- Bicout, D., C. Brosseau, et al. (1994). "Depolarization of Multiply Scattered Waves by Spherical Diffusers—Influence of the Size Parameter." *Physical Review E* 49(2): 1767-1770.
- Blanchot, L., M. Lebec, et al. (1997). *Low-coherence in depth microscopy for biological tissues imaging: Design of a real time control system*. Proceedings of SPIE—The International Society for Optical Engineering.
- Blumenthal, E. Z. and R. N. Weinreb (2001). "Assessment of the retinal nerve fiber layer in clinical trials of glaucoma neuroprotection. [Review] [36 refs]." *Survey of Ophthalmology* 45(Suppl 3): S305-12; discussion S332-4.
- Blumenthal, E. Z., J. M. Williams, et al. (2000). "Reproducibility of nerve fiber layer thickness measurements by use of optical coherence tomography." *Ophthalmology* 107(12): 2278-82.
- Boppart, S. A., B. E. Bouma, et al. (1996). "Imaging developing neural morphology using optical coherence tomography." *Journal of Neuroscience Methods* 70.
- Boppart, S. A., B. E. Bouma, et al. (1997). "Forward-imaging instruments for optical coherence tomography." *Optics Letters* 22.
- Boppart, S. A., B. E. Bouma, et al. (1998). "Intraoperative assessment of microsurgery with three-dimensional optical coherence tomography." *Radiology* 208: 81-86.
- Boppart, S. A., J. Herrmann, et al. (1999). "High-resolution optical coherence tomography-guided laser ablation of surgical tissue." *Journal of Surgical Research* 82(2): 275-84.
- Bouma, B. E. and J. G. Fujimoto (1996). "Compact Kerr-lens mode-locked resonators." *Optics Letters* 21. 134-136.
- Bouma, B. E., L. E. Nelson, et al. (1998). "Optical coherence tomographic imaging of human tissue at 1.55 μm and 1.81 μm using Er and Tm-doped fiber sources." *Journal of Biomedical Optics* 3. 76-79.
- Bouma, B. E., M. Ramaswamy-Paye, et al. (1997). "Compact resonator designs for mode-locked solid-state lasers." *Applied Physics B (Lasers and Optics)* B65. 213-220.
- Bouma, B. E. and G. J. Tearney (2002). "Clinical imaging with optical coherence tomography." *Academic Radiology* 9(8): 942-953.
- Bouma, B. E., G. J. Tearney, et al. (1996). "Self-phase-modulated Kerr-lens mode-locked Cr:forsterite laser source for optical coherence tomography." *Optics Letters* 21(22): 1839.
- Bouma, B. E., G. J. Tearney, et al. (2000). "High-resolution imaging of the human esophagus and stomach in vivo using optical coherence tomography." *Gastrointestinal Endoscopy* 51(4): 467-474.
- Bouma, B. E., G. J. Tearney, et al. (2003). "Evaluation of intracoronary stenting by intravascular optical coherence tomography." *Heart* 89(3): 317-320.
- Bourquin, S., V. Monterosso, et al. (2000). "Video-rate optical low-coherence reflectometry based on a linear smart detector array." *Optics Letters* 25(2): 102-104.
- Bourquin, S., P. Seitz, et al. (2001). "Optical coherence tomography based on a two-dimensional smart detector array." *Optics Letters* 26(8): 512-514.
- Bouzid, A., M. A. G. Abushagur, et al. (1995). "Fiber-optic four-detector polarimeter." *Optics Communications* 118(3-4): 329-334.
- Bowd, C., R. N. Weinreb, et al. (2000). "The retinal nerve fiber layer thickness in ocular hypertensive, normal, and glaucomatous eyes with optical coherence tomography." *Archives of Ophthalmology* 118(1): 22-6.
- Bowd, C., L. M. Zangwill, et al. (2001). "Detecting early glaucoma by assessment of retinal nerve fiber layer thickness and visual function." *Investigative Ophthalmology & Visual Science* 42(9): 1993-2003.
- Bowd, C., L. M. Zangwill, et al. (2002). "Imaging of the optic disc and retinal nerve fiber layer: the effects of age, optic disc area, refractive error, and gender." *Journal of the Optical Society of America, A, Optics, Image Science, & Vision* 19(1): 197-207.
- Brand, S., J. M. Ponomeros, et al. (2000). "Optical coherence tomography in the gastrointestinal tract." *Endoscopy* 32(10): 796-803.
- Brezinski, M. E. and J. G. Fujimoto (1999). "Optical coherence tomography: high-resolution imaging in nontransparent tissue." *IEEE Journal of Selected Topics in Quantum Electronics* 5(4): 1185-1192.
- Brezinski, M. E., G. J. Tearney, et al. (1996). "Imaging of coronary artery microstructure (in vitro) with optical coherence tomography." *American Journal of Cardiology* 77 (1): 92-93.
- Brezinski, M. E., G. J. Tearney, et al. (1996). "Optical coherence tomography for optical biopsy—Properties and demonstration of vascular pathology." *Circulation* 93(6): 1206-1213.
- Brezinski, M. E., G. J. Tearney, et al. (1997). "Assessing atherosclerotic plaque morphology: Comparison of optical coherence tomography and high frequency intravascular ultrasound." *Heart* 77(5): 397-403.

(56)

References Cited

OTHER PUBLICATIONS

- Brink, H. B. K. and G. J. Vanblokkland (1988). "Birefringence of the Human Foveal Area Assessed In vivo with Mueller-Matrix Ellipsometry." *Journal of the Optical Society of America a-Optics Image Science and Vision* 5(1):49-57.
- Brosseau, C. and D. Bicout (1994). "Entropy Production in Multiple-Scattering of Light by a Spatially Random Medium." *Physical Review E* 50(6): 4997-5005.
- Burgoyne, C. F., D. E. Mercante, et al (2002). "Change detection in regional and volumetric disc parameters using longitudinal confocal scanning laser tomography." *Ophthalmology* 109(3): 455-66.
- Candido, R. and T. J. Allen (2002). "Haemodynamics in microvascular complications in type 1 diabetes." *Diabetes-Metabolism Research and Reviews* 18(4): 286-304.
- Cense, B., T. C. Chen, et al. (2004). "Thickness and birefringence of healthy retinal nerve fiberlayer tissue measured with polarization-sensitive optical coherence tomography." *Investigative Ophthalmology & Visual Science* 45(8): 2606-2612.
- Cense, B., N. Nassif, et al. (2004). "Ultrahigh-Resolution High-Speed Retinal Imaging Using Spectral-Domain Optical Coherence Tomography." *Optics Express* 12(11): 2435-2447.
- Chance, B., J. S. Leigh, et al. (1988). "Comparison of Time-Resolved and Time-Unresolved Measurements of Deoxyhemoglobin in Brain." *Proceedings of the National Academy of Sciences of the United States of America* 85(14): 4971-4975.
- Chang, E. P., D. A. Keedy, et al. (1974). "Ultrastructures of Rabbit Corneal Stroma--Mapping of Optical and Morphological Anisotropies." *Biochimica Et Biophysica Acta* 343(3): 615-626.
- Chartier, T., A. Hideur, et al. (2001). "Measurement of the elliptical birefringence of single-mode optical fibers." *Applied Optics* 40(30): 5343-5353.
- Chauhan, B. C., J. W. Blanchard, et al. (2000). "Technique for Detecting Serial Topographic Changes in the Optic Disc and Peripapillary Retina Using Scanning Laser Tomograph." *Invest Ophthalmol Vis Sci* 41: 775-782.
- Chen, Z. P., T. E. Milner, et al. (1997). "Optical Doppler tomographic imaging of fluid flow velocity in highly scattering media." *Optics Letters* 22(1): 64-66.
- Chen, Z. P., T. E. Milner, et al. (1997). "Noninvasive imaging of in vivo blood flow velocity using optical Doppler tomography." *Optics Letters* 22(14): 1119-1121.
- Chen, Z. P., Y. H. Zhao, et al. (1999). "Optical Doppler tomography." *Ieee Journal of Selected Topics in Quantum Electronics* 5(4): 1134-1142.
- Cheong, W. F., S. A. Prael, et al. (1990). "A Review of the Optical-Properties of Biological Tissues." *Ieee Journal of Quantum Electronics* 26(12): 2166-2185.
- Chernikov, S. V., Y. Zhu, et al. (1997). "Supercontinuum self-Q-switched ytterbium fiber laser." *Optics Letters* 22(5): 298-300.
- Cho, S. H., B. E. Bouma, et al. (1999). "Low-repetition-rate high-peak-power Kerr-lens mode-locked Ti:A1/sub 2/0/sub 3/ laser with a multiple-pass cavity." *Optics Letters* 24(6): 417-419.
- Choma, M. A., M. V. Sarunic, et al. (2003). "Sensitivity advantage of swept source and Fourier domain optical coherence tomography." *Optics Express* 11(18): 2183-2189.
- Choma, M. A., C. H. Yang, et al. (2003). "Instantaneous quadrature low-coherence interferometry with 3x3 fiber-optic couplers." *Optics Letters* 28(22): 2162-2164.
- Choplin, N. T. And D. C. Lundy (2001). "The sensitivity and specificity of scanning laser polarimetry in the detection of glaucoma in a clinical setting." *Ophthalmology* 108 (5): 899-904.
- Christens Barry, W. A., W. J. Green, et al. (1996). "Spatial mapping of polarized light transmission in the central rabbit cornea." *Experimental Eye Research* 62(6): 651-662.
- Chvapil, M., D. P. Speer, et al. (1984). "Identification of the depth of burn injury by collagen stainability." *Plastic & Reconstructive Surgery* 73(3): 438-41.
- Cioffi, G. A. (2001). "Three common assumptions about ocular blood flow and glaucoma." *Survey of Ophthalmology* 45: S325-S331.
- Coleman, A. L. (1999). "Glaucoma." *Lancet* 354(9192): 1803-10.
- Collaborative Normal-Tension Glaucoma Study Group (1998). "Comparison of Glaucomatous Progression Between Untreated Patients With Normal Tension Glaucoma and Patients with Therapeutically Reduced Intraocular Pressures." *Am J Ophthalmol* 126: 487-97.
- Collaborative Normal-Tension Glaucoma Study Group (1998). "The effectiveness of intraocular pressure reduction in the treatment of normal-tension glaucoma." *Am J Ophthalmol* 126: 498-505.
- Collaborative Normal-Tension Glaucoma Study Group (2001). "Natural History of Normal-Tension Glaucoma." *Ophthalmology* 108: 247-253.
- Colston, B. W., M. J. Everett, et al. (1998). "Imaging of hard- and soft-tissue structure in the oral cavity by optical coherence tomography." *Applied Optics* 37(16): 3582-3585.
- Colston, B. W., U. S. Sathyam, et al. (1998). "Dental OCT." *Optics Express* 3(6): 230-238.
- Congdon, N. G., D. S. Friedman, et al. (2003). "Important causes of visual impairment in the world today." *Jama-Journal of the American Medical Association* 290(15): 2057-2060.
- Cregan, R. F., B. J. Mangan, et al. (1999). "Single-mode photonic band gap guidance of light in air." *Science* 285(5433): 1537-1539.
- DalMolin, M., A. Galtarossa, et al. (1997). "Experimental investigation of linear polarization in high-birefringence single-mode fibers." *Applied Optics* 36(12): 2526-2528.
- Danielson, B. L. and C. D. Whittenberg (1987). "Guided-Wave Reflectometry with Micrometer Resolution." *Applied Optics* 26(14): 2836-2842.
- Dave, D. P. and T. E. Milner (2000). "Doppler-angle measurement in highly scattering media." *Optics Letters* 25(20): 1523-1525.
- de Boer, J. F., T. E. Milner, et al. (1998). *Two dimensional birefringence imaging in biological tissue using phase and polarization sensitive optical coherence tomography*. Trends in Optics and Photonics (TOPS): Advances in Optical Imaging and Photon Migration, Orlando, USA, Optical Society of America, Washington, DC 1998.
- de Boer, J. F., C. E. Saxer, et al. (2001). "Stable carrier generation and phase-resolved digital data processing in optical coherence tomography." *Applied Optics* 40(31): 5787-5790.
- Degroot, P. and L. Deck (1993). "3-Dimensional Imaging by Sub-Nyquist Sampling of White-Light Interferograms." *Optics Letters* 18(17): 1462-1464.
- Denk, W., J. H. Strickler, et al. (1990). "2-Photon Laser Scanning Fluorescence Microscopy." *Science* 248(4951): 73-76.
- Descour, M. R., A. H. O. Karkkainen, et al. (2002). "Toward the development of miniaturized Imaging systems for detection of pre-cancer." *Ieee Journal of Quantum Electronics* 38(2): 122-130.
- Dettwiller, L. (1997). "Polarization state interference: A general investigation." *Pure and Applied Optics* 6(1): 41-53.
- DiCarlo, C. D., W. P. Roach, et al. (1999). "Comparison of optical coherence tomography imaging of cataracts with histopathology." *Journal of Biomedical Optics* 4.
- Ding, Z., Y. Zhao, et al. (2002). "Real-time phase-resolved optical coherence tomography and optical Doppler tomography." *Optics Express* 10(5): 236-245.
- Dobrin, P. B. (1996). "Effect of histologic preparation on the cross-sectional area of arterial rings." *Journal of Surgical Research* 61(2): 413-5.
- Donohue, D. J., B. J. Stoyanov, et al. (1995). "Numerical Modeling of the Corneas Lamellar Structure and Birefringence Properties." *Journal of the Optical Society of America a-Optics Image Science and Vision* 12(7): 1425-1438.
- Doornbos, R. M. P., R. Lang, et al. (1999). "The determination of in vivo human tissue optical properties and absolute chromophore concentrations using spatially resolved steady-state diffuse reflectance spectroscopy." *Physics in Medicine and Biology* 44(4): 967-981.
- Drexler, W., A. Baumgartner, et al. (1997). "Biometric investigation of changes in the anterior eye segment during accommodation." *Vision Research* 37(19): 2789-2800.
- Drexler, W., A. Baumgartner, et al. (1997). "Submicrometer precision biometry of the anterior segment of the human eye." *Investigative Ophthalmology & Visual Science* 38(7): 1304-1313.

(56)

References Cited

OTHER PUBLICATIONS

- Drexler, W., A. Baumgartner, et al. (1998). "Dual beam optical coherence tomography: signal identification for ophthalmologic diagnosis." *Journal of Biomedical Optics* 3 (1): 55-65.
- Drexler, W., O. Findl, et al. (1998). "Partial coherence interferometry: A novel approach to biometry in cataract surgery." *American Journal of Ophthalmology* 126(4): 524-534.
- Drexler, W., O. Findl, et al. (1997). "Clinical feasibility of dual beam optical coherence topography and tomography for ophthalmologic diagnosis." *Investigative Ophthalmology & Visual Science* 38(4): 1038-1038.
- Drexler, W., C. K. Hitzenberger, et al. (1998). "Investigation of dispersion effects in ocular media by multiple wavelength partial coherence interferometry." *Experimental Eye Research* 66(1): 25-33.
- Drexler, W., C. K. Hitzenberger, et al. (1996). "(Sub)micrometer precision biometry of the human eye by optical coherence tomography and topography." *Investigative Ophthalmology & Visual Science* 37(3): 4374-4374.
- Drexler, W., C. K. Hitzenberger, et al. (1995). "Measurement of the Thickness of Fundus Layers by Partial Coherence Tomography." *Optical Engineering* 34(3): 701-710.
- Drexler, W., U. Morgner, et al. (2001). "Ultrahigh-resolution ophthalmic optical coherence tomography." *Nature Medicine* 7(4): 502-507.
- Drexler, W., U. Morgner, et al. (2001). "Ultrahigh-resolution ophthalmic optical coherence tomography. [erratum appears in Nat Med 2001 May;7(5):636.]" *Nature Medicine* 7(4): 502-7.
- Drexler, W., H. Sattmann, et al. (2003). "Enhanced visualization of macular pathology with the use of ultrahigh-resolution optical coherence tomography." *Archives of Ophthalmology* 121(5): 695-706.
- Drexler, W., D. Stamper, et al. (2001). "Correlation of collagen organization with polarization sensitive imaging of in vitro cartilage: implications for osteoarthritis." *Journal of Rheumatology* 28(6): 1311-8.
- Droog, E. J., W. Steenbergen, et al. (2001). "Measurement of depth of burns by laser Doppler perfusion imaging." *Burns* 27(6): 561-8.
- Dubois, A., K. Grieve, et al. (2004). "Ultrahigh-resolution full-field optical coherence tomography." *Applied Optics* 43(14): 2874-2883.
- Dubois, A., L. Vabre, et al. (2002). "High-resolution full-field optical coherence tomography with a Linnik microscope." *Applied Optics* 41(4): 805-812.
- Ducros, M., M. Laubscher, et al. (2002). "Parallel optical coherence tomography in scattering samples using a two-dimensional smart-pixel detector array." *Optics Communications* 202(1-3): 29-35.
- Ducros, M. G., J. D. Marsack, et al. (2001). "Primate retina imaging with polarization-sensitive optical coherence tomography." *Journal of the Optical Society of America a-Optics Image Science and Vision* 18(12): 2945-2956.
- Duncan, A., J. H. Meek, et al. (1995). "Optical Pathlength Measurements on Adult Head, Calf and Forearm and the Head of the Newborn-Infant Using Phase-Resolved Optical Spectroscopy." *Physics in Medicine and Biology* 40(2): 295-304.
- Eigensee, A., G. Haeusler, et al. (1996). "New method of short-coherence interferometry in human skin (in vivo) and in solid volume scatterers." *Proceedings of SPIE—The International Society for Optical Engineering* 2925: 169-178.
- Eisenbeiss, W., J. Marotz, et al. (1999). "Reflection-optical multispectral imaging method for objective determination of burn depth." *Burns* 25(8): 697-704.
- Elbaum, M., M. King, et al. (1972). "Wavelength-Diversity Technique for Reduction of Speckle Size." *Journal of the Optical Society of America* 62(5): 732-&.
- Ervin, J. C., H. G. Lemij, et al. (2002). "Clinician change detection viewing longitudinal stereophotographs compared to confocal scanning laser tomography in the LSU Experimental Glaucoma (LEG) Study." *Ophthalmology* 109(3): 467-81.
- Essenpreis, M., C. E. Elwell, et al. (1993). "Spectral Dependence of Temporal Point Spread Functions in Human Tissues." *Applied Optics* 32(4): 418-425.
- Eun, H. C. (1995). "Evaluation of skin blood flow by laser Doppler flowmetry. [Review] [151 refs]." *Clinics in Dermatology* 13(4): 337-47.
- Evans, J. A., J. M. Ponerros, et al. (2004). "Application of a histopathologic scoring system to optical coherence tomography (OCT) images to identify high-grade dysplasia in Barrett's esophagus." *Gastroenterology* 126(4): A51-A51.
- Feldchtein, F. I., G. V. Gelikonov, et al. (1998). "In vivo OCT imaging of hard and soft tissue of the oral cavity." *Optics Express* 3(6): 239-250.
- Feldchtein, F. I., G. V. Gelikonov, et al. (1998). "Endoscopic applications of optical coherence tomography." *Optics Express* 3(6): 257-270.
- Fercher, A. F., W. Drexler, et al. (1997). "Optical ocular tomography." *Neuro-Ophthalmology* 18(2): 39-49.
- Fercher, A. F., W. Drexler, et al. (1994). *Measurement of optical distances by optical spectrum modulation*. Proceedings of SPIE—The International Society for Optical Engineering.
- Fercher, A. F., W. Drexler, et al. (2003). "Optical coherence tomography—principles and applications." *Reports on Progress in Physics* 66(2): 239-303.
- Fercher, A. F., C. Hitzenberger, et al. (1991). "Measurement of Intraocular Optical Distances Using Partially Coherent Laser-Light." *Journal of Modern Optics* 38(7): 1327-1333.
- Fercher, A. F., C. K. Hitzenberger, et al. (1996). *Ocular partial coherence interferometry*. Proceedings of SPIE—The International Society for Optical Engineering.
- Fercher, A. F., C. K. Hitzenberger, et al. (1993). "In-Vivo Optical Coherence Tomography." *American Journal of Ophthalmology* 116(1): 113-115.
- Fercher, A. F., C. K. Hitzenberger, et al. (1994). *In-vivo dual-beam optical coherence tomography*. Proceedings of SPIE—The International Society for Optical Engineering.
- Fercher, A. F., C. K. Hitzenberger, et al. (1995). "Measurement of Intraocular Distances by Backscattering Spectral Interferometry." *Optics Communications* 117(1-2): 43-48.
- Fercher, A. F., C. K. Hitzenberger, et al. (2000). "A thermal light source technique for optical coherence tomography." *Optics Communications* 185(1-3): 57-64.
- Fercher, A. F., C. K. Hitzenberger, et al. (2001). "Numerical dispersion compensation for Partial Coherence Coherence Interferometry and Optical Coherence Tomography." *Optics Express* 9(12): 610-615.
- Fercher, A. F., C. K. Hitzenberger, et al. (2002). "Dispersion compensation for optical coherence tomography depth-scan signals by a numerical technique." *Optics Communications* 204(1-6): 67-74.
- Fercher, A. F., H. C. Li, et al. (1993). "Slit Lamp Laser-Doppler Interferometer." *Lasers in Surgery and Medicine* 13(4): 447-452.
- Fercher, A. F., K. Mengedoh, et al. (1988). "Eye-Length Measurement by Interferometry with Partially Coherent-Light." *Optics Letters* 13(3): 186-188.
- Ferro, P., M. Haelterman, et al. (1991). "All-Optical Polarization Switch with Long Low-Birefringence Fiber." *Electronics Letters* 27(16): 1407-1408.
- Fetterman, M. R., D. Goswami, et al. (1998). "Ultrafast pulse shaping: amplification and characterization." *Optics Express* 3(10): 366-375.
- Findl, O., W. Drexler, et al. (2001). "Improved prediction of intraocular lens power using partial coherence interferometry." *Journal of Cataract and Refractive Surgery* 27 (6): 861-867.
- Fork, R. L., C. H. B. Cruz, et al. (1987). "Compression of Optical Pulses to 6 Femtoseconds by Using Cubic Phase Compensation." *Optics Letters* 12(7): 483-485.
- Foschini, G. J. and C. D. Poole (1991). "Statistical-Theory of Polarization Dispersion in Single-Mode Fibers." *Journal of Light-wave Technology* 9(11): 1439-1456.
- Francia, C., F. Bruyere, et al. (1998). "PMD second-order effects on pulse propagation in single-mode optical fibers." *Ieee Photonics Technology Letters* 10(12): 1739-1741.
- Fried, D., R. E. Glana, et al. (1995). "Nature of Light-Scattering in Dental Enamel and Dentin at Visible and near-Infrared Wavelengths." *Applied Optics* 34(7): 1278-1285.

(56)

References Cited

OTHER PUBLICATIONS

- Fujimoto, J. G., M. E. Brezinski, et al. (1995). "Optical Biopsy and Imaging Using Optical Coherence Tomography." *Nature Medicine* 1(9): 970-972.
- Fukasawa, A. and H. Iijima (2002). "Optical coherence tomography of choroidal osteoma." *American Journal of Ophthalmology* 133(3): 419-21.
- Fymat, A. L. (1981). "High-Resolution Interferometric Spectrophotopolarimetry." *Optical Engineering* 20(1): 25-30.
- Galtarossa, A., L. Palmieri, et al. (2000). "Statistical characterization of fiber random birefringence." *Optics Letters* 25(18): 1322-1324.
- Galtarossa, A., L. Palmieri, et al. (2000). "Measurements of beat length and perturbation length in long single-mode fibers." *Optics Letters* 25(6): 384-386.
- Gandjbakhche, A. H., P. Mills, et al. (1994). "Light-Scattering Technique for the Study of Orientation and Deformation of Red-Blood-Cells in a Concentrated Suspension." *Applied Optics* 33(6): 1070-1078.
- Garcia, N. and M. Nieto-Vesperinas (2002). "Left-handed materials do not make a perfect lens." *Physical Review Letters* 88(20).
- Gelikonov, V. M., G. V. Gelikonov, et al. (1995). "Coherent Optical Tomography of Microscopic Inhomogeneities in Biological Tissues." *Jetp Letters* 61(2): 158-162.
- George, N. and A. Jain (1973). "Speckle Reduction Using Multiple Tones of Illumination." *Applied Optics* 12(6): 1202-1212.
- Gibson, G. N., R. Klank, et al. (1996). "Electro-optically cavity-dumped ultrashort-pulse Ti:sapphire oscillator." *Optics Letters* 21(14): 1055.
- Gil, J. J. (2000). "Characteristic properties of Mueller matrices." *Journal of the Optical Society of America a-Optics Image Science and Vision* 17(2): 328-334.
- Gil, J. J. and E. Bernabeu (1987). "Obtainment of the Polarizing and Retardation Parameters of a Nondepolarizing Optical-System from the Polar Decomposition of Its Mueller Matrix." *Optik* 76(2): 67-71.
- Gladkova, N. D., G. A. Petrova, et al. (2000). "In vivo optical coherence tomography imaging of human skin: norm and pathology." *Skin Research and Technology* 6 (1): 6-16.
- Glaessl, A., A. G. Schreyer, et al. (2001). "Laser surgical planning with magnetic resonance imaging-based 3-dimensional reconstructions for intralésional Nd : YAG laser therapy of a venous malformation of the neck." *Archives of Dermatology* 137(10): 1331-1335.
- Gloesmann, M., B. Hermann, et al. (2003). "Histologic correlation of pig retina radial stratification with ultrahigh-resolution optical coherence tomography." *Investigative Ophthalmology & Visual Science* 44(4): 1696-1703.
- Goldberg, L. and D. Mehuys (1994). "High-Power Superluminescent Diode Source." *Electronics Letters* 30(20): 1682-1684.
- Goldsmith, J. A., Y. Li, et al. (2005). "Anterior chamber width measurement by high speed optical coherence tomography." *Ophthalmology* 112(2): 238-244.
- Goldstein, L. E., J. A. Muffat, et al. (2003). "Cytosolic beta-amyloid deposition and supranuclear cataracts in lenses from people with Alzheimer's disease." *Lancet* 361(9365): 1258-1265.
- Golubovic, B., B. E. Bouma, et al. (1996). "Thin crystal, room-temperature Cr/sup 4 +/forstefite laser using near-infrared pumping." *Optics Letters* 21(24): 1993-1995.
- Gonzalez, S. and Z. Tannous (2002). "Real-time, in vivo confocal reflectance microscopy of basal cell carcinoma." *Journal of the American Academy of Dermatology* 47(6): 869-874.
- Gordon, M. O. and M. A. Kass (1999). "The Ocular Hypertension Treatment Study: design and baseline description of the participants." *Archives of Ophthalmology* 117(5): 573-83.
- Grayson, T. P., J. R. Torgerson, et al. (1994). "Observation of a Nonlocal Pancharatnam Phase-Shift in the Process of Induced Coherence without Induced Emission." *Physical Review A* 49(1): 626-628.
- Greaney, M. J., D. C. Hoffman, et al. (2002). "Comparison of optic nerve imaging methods to distinguish normal eyes from those with glaucoma." *Investigative Ophthalmology & Visual Science* 43(1): 140-5.
- Greenfield, D. S., H. Bagga, et al. (2003). "Macular thickness changes in glaucomatous optic neuropathy detected using optical coherence tomography." *Archives of Ophthalmology* 121(1): 41-46.
- Greenfield, D. S., R. W. Knighton, et al. (2000). "Effect of corneal polarization axis on assessment of retinal nerve fiber layer thickness by scanning laser polarimetry." *American Journal of Ophthalmology* 129(6): 715-722.
- Griffin, R. A., D. D. Sampson, et al. (1995). "Coherence Coding for Photonic Code-Division Multiple-Access Networks." *Journal of Lightwave Technology* 13(9): 1826-1837.
- Guedes, V., J. S. Schuman, et al. (2003). "Optical coherence tomography measurement of macular and nerve fiber layer thickness in normal and glaucomatous human eyes." *Ophthalmology* 110(1): 177-189.
- Gueugniaud, P. Y., H. Carsin, et al. (2000). "Current advances in the initial management of major thermal burns. [Review] [76 refs]." *Intensive Care Medicine* 26(7): 848-56.
- Guido, S. and R. T. Tranquillo (1993). "A Methodology for the Systematic and Quantitative Study of Cell Contact Guidance in Oriented Collagen Gels—Correlation of Fibroblast Orientation and Gel Birefringence." *Journal of Cell Science* 105: 317-331.
- Gurses-Ozden, R., H. Ishikawa, et al. (1999). "Increasing sampling density improves reproducibility of optical coherence tomography measurements." *Journal of Glaucoma* 8(4): 238-41.
- Guzzi, R. (1998). "Scattering Theory from Homogeneous and Coated Spheres." 1-11.
- Haberland, U. B., Vladimir; Schmitt, Hans J. (1996). "Optical coherent tomography of scattering media using electrically tunable near-infrared semiconductor laser." *Applied Optics Draft Copy*.
- Haberland, U. R., Walter; Blazek, Vladimir; Schmitt, Hans J. (1995). "Investigation of highly laser scattering media using near-infrared continuous wave tunable semiconductor laser." *Proc. SPIE*, 2389: 503-512.
- Hale, G. M. and M. R. Query (1973). "Optical-Constants of Water 200-Nm to 200-Mum Wavelength Region." *Applied Optics* 12(3): 555-563.
- Hammer, D. X., R. D. Ferguson, et al. (2002). "Image stabilization for scanning laser ophthalmoscopy." *Optics Express* 10(26): 1542.
- Hara, T., Y. Ooi, et al. (1989). "Transfer Characteristics of the Microchannel Spatial Light-Modulator." *Applied Optics* 28(22): 4781-4786.
- Harland, C. C., S. G. Kale, et al. (2000). "Differentiation of common benign pigmented skin lesions from melanoma by high-resolution ultrasound." *British Journal of Dermatology* 143(2): 281-289.
- Hartl, I., X. D. Li, et al. (2001). "Ultrahigh-resolution optical coherence tomography using continuum generation in an air-silica microstructure optical fiber." *Optics Letters* 26(9): 608-610.
- Hassenstein, A., A. A. Bialasiewicz, et al. (2000). "Optical coherence tomography in uveitis patients." *American Journal of Ophthalmology* 130(5): 669-70.
- Hattenhauer, M. G., D. H. Johnson, et al. (1998). "The probability of blindness from open-angle glaucoma. [see comments]." *Ophthalmology* 105(11): 2099-104.
- Hausler, G., J. M. Herrmann, et al. (1996). "Observation of light propagation in volume scatterers with 10(11)-fold slow motion." *Optics Letters* 21(14): 1087-1089.
- Hazebroek, H. F. and A. A. Holscher (1973). "Interferometric Ellipsometry." *Journal of Physics E-Scientific Instruments* 6(9): 822-826.
- Hazebroek, H. F. and W. M. Visser (1983). "Automated Laser Interferometric Ellipsometry and Precision Reflectometry." *Journal of Physics E-Scientific Instruments* 16(7): 654-661.
- He, Z. Y., N. Mukohzaka, et al. (1997). "Selective image extraction by synthesis of the coherence function using two-dimensional optical lock-in amplifier with microchannel spatial light modulator." *Ieee Photonics Technology Letters* 9(4): 514-516.
- Hee, M. R., J. A. Izatt, et al. (1993). "Femtosecond Transillumination Optical Coherence Tomography." *Optics Letters* 18(12): 950-952.

(56)

References Cited

OTHER PUBLICATIONS

- Hee, M. R., J. A. Izatt, et al. (1995). "Optical coherence tomography of the human retina." *Archives of Ophthalmology* 113(3): 325-32.
- Hee, M. R., C. A. Puliafito, et al. (1998). "Topography of diabetic edema with optical macular coherence tomography." *Ophthalmology* 105(2): 360-70.
- Hee, M. R., C. A. Puliafito, et al. (1995). "Quantitative assessment of macular edema with optical coherence tomography." *Archives of Ophthalmology* 113(8): 1019-29.
- Hellmuth, T. and M. Welle (1998). "Simultaneous measurement of dispersion, spectrum, and distance with a fourier transform spectrometer." *Journal of Biomedical Optics* 3(1): 7-11.
- Hemenger, R. P. (1989). "Birefringence of a medium of tenuous parallel cylinders." *Applied Optics* 28(18): 4030-4034.
- Henry, M. (1981). "Fresnel-Arago Laws for Interference in Polarized-Light—Demonstration Experiment." *American Journal of Physics* 49(7): 690-691.
- Herz, P. R., Y. Chen, et al. (2004). "Micromotor endoscope catheter for in vivo, ultrahigh-resolution optical coherence tomography." *Optics Letters* 29(19): 2261-2263.
- Hirakawa, H., H. Iijima, et al. (1999). "Optical coherence tomography of cystoid macular edema associated with retinitis pigmentosa." *American Journal of Ophthalmology* 128(2): 185-91.
- Hitzenberger, C. K., A. Baumgartner, et al. (1994). "Interferometric Measurement of Corneal Thickness with Micrometer Precision." *American Journal of Ophthalmology* 118(4): 468-476.
- Hitzenberger, C. K., A. Baumgartner, et al. (1999). "Dispersion effects in partial coherence interferometry: Implications for intraocular ranging." *Journal of Biomedical Optics* 4(1): 144-151.
- Hitzenberger, C. K., A. Baumgartner, et al. (1998). "Dispersion induced multiple signal peak splitting in partial coherence interferometry." *Optics Communications* 154 (4): 179-185.
- Hitzenberger, C. K., M. Danner, et al. (1999). "Measurement of the spatial coherence of superluminescent diodes." *Journal of Modern Optics* 46(12): 1763-1774.
- Hitzenberger, C. K. and A. F. Fercher (1999). "Differential phase contrast in optical coherence tomography." *Optics Letters* 24(9): 622-624.
- Hitzenberger, C. K., M. Sticker, et al. (2001). "Differential phase measurements in low-coherence interferometry without 2 pi ambiguity." *Optics Letters* 26(23): 1864-1866.
- Hoeling, B. M., A. D. Fernandez, et al. (2000). "An optical coherence microscope for 3-dimensional imaging in developmental biology." *Optics Express* 6(7): 136-146.
- Hoerauf, H., C. Scholz, et al. (2002). "Transscleral optical coherence tomography: a new imaging method for the anterior segment of the eye." *Archives of Ophthalmology* 120(6): 816-9.
- Hoffmann, K., M. Happe, et al. (1998). "Optical coherence tomography (OCT) in dermatology." *Journal of Investigative Dermatology* 110(4): 583-583.
- Hoh, S. T., D. S. Greenfield, et al. (2000). "Optical coherence tomography and scanning laser polarimetry in normal, ocular hypertensive, and glaucomatous eyes." *American Journal of Ophthalmology* 129(2): 129-35.
- Hohenleutner, U., M. Hilbert, et al. (1995). "Epidermal Damage and Limited Coagulation Depth with the Flashlamp-Pumped Pulsed Dye-Laser—a Histochemical-Study." *Journal of Investigative Dermatology* 104(5): 798-802.
- Holland, A. J. A., H. C. O. Martin, et al. (2002). "Laser Doppler imaging prediction of burn wound outcome in children." *Burns* 28(1): 11-17.
- Hotate, K. and T. Okugawa (1994). "Optical Information-Processing by Synthesis of the Coherence Function." *Journal of Lightwave Technology* 12(7): 1247-1255.
- Hourdakis, C. J. and A. Perris (1995). "A Monte-Carlo Estimation of Tissue Optical-Properties for Use in Laser Dosimetry." *Physics in Medicine and Biology* 40(3): 351-364.
- Hu, Z., F. Li, et al. (2000). "Wavelength-tunable narrow-linewidth semiconductor fiber-ring laser." *IEEE Photonics Technology Letters* 12(8): 977-979.
- Huang, F., W. Yang, et al. (2001). "Quadrature spectral interferometric detection and pulse shaping." *Optics Letters* 26(6): 382-384.
- Huang, X. R. and R. W. Knighton (2002). "Linear birefringence of the retinal nerve fiber layer measured in vitro with a multispectral imaging micropolarimeter." *Journal of Biomedical Optics* 7(2): 199-204.
- Huber, R., M. Wojtkowski, et al. (2005). "Amplified, frequency swept lasers for frequency domain reflectometry and OCT imaging: design and scaling principles." *Optics Express* 13(9): 3513-3528.
- Hunter, D. G., J. C. Sandruck, et al. (1999). "Mathematical modeling of retinal birefringence scanning." *Journal of the Optical Society of America a-Optics Image Science and Vision* 16(9): 2103-2111.
- Hurwitz, H. H. and R. C. Jones (1941). "A new calculus for the treatment of optical systems II. Proof of three general equivalence theorems." *Journal of the Optical Society of America* 31(7): 493-499.
- Huttner, B., C. De Barros, et al. (1999). "Polarization-induced pulse spreading in birefringent optical fibers with zero differential group delay." *Optics Letters* 24(6): 370-372.
- Huttner, B., B. Gisin, et al. (1999). "Distributed PMD measurement with a polarization-OTDR in optical fibers." *Journal of Lightwave Technology* 17(10): 1843-1848.
- Huttner, B., J. Reecht, et al. (1998). "Local birefringence measurements in single-mode fibers with coherent optical frequency-domain reflectometry." *Ieee Photonics Technology Letters* 10(10): 1458-1460.
- Hyde, S. C. W., N. P. Barry, et al. (1995). "Sub-100-Mu-M Depth-Resolved Holographic Imaging through Scattering Media in the near-Infrared." *Optics Letters* 20(22): 2330-2332.
- Hyde, S. C. W., N. P. Barry, et al. (1995). "Depth-Resolved Holographic Imaging through Scattering Media by Photorefractive." *Optics Letters* 20(11): 1331-1333.
- Iftimia, N. V., B. E. Bouma, et al. (2004). "Adaptive ranging for optical coherence tomography." *Optics Express* 12(17): 4025-4034.
- Iida, T., N. Hagimura, et al. (2000). "Evaluation of central serous chorioretinopathy with optical coherence tomography." *American Journal of Ophthalmology* 129(1): 16-20.
- Imai, M., H. Iijima, et al. (2001). "Optical coherence tomography of tractional macular elevations in eyes with proliferative diabetic retinopathy. [republished in Am J Ophthalmol. Sep. 2001;132(3):458-61 ; 11530091.]" *American Journal of Ophthalmology* 132(1): 81-4.
- Indebetouw, G. and P. Klysubun (2000). "Imaging through scattering media with depth resolution by use of low-coherence gating in spatiotemporal digital holography." *Optics Letters* 25(4): 212-214.
- Ip, M. S., B. J. Baker, et al. (2002). "Anatomical outcomes of surgery for idiopathic macular hole as determined by optical coherence tomography." *Archives of Ophthalmology* 120(1): 29-35.
- Ismail, R., V. Tanner, et al. (2002). "Optical coherence tomography imaging of severe commotio retinae and associated macular hole." *British Journal of Ophthalmology* 86(4): 473-4.
- Izatt, J. A., M. R. Hee, et al. (1994). "Optical Coherence Microscopy in Scattering Media." *Optics Letters* 19(8): 590-592.
- Izatt, J. A., M. R. Hee, et al. (1994). "Micrometer-scale resolution imaging of the anterior eye in vivo with optical coherence tomography." *Archives of Ophthalmology* 112 (12): 1584-9.
- Izatt, J. A., M. D. Kulkarni, et al. (1997). "In vivo bidirectional color Doppler flow imaging of picoliter blood volumes using optical coherence tomography." *Optics Letters* 22(18): 1439-1441.
- Izatt, J. A., M. D. Kulkarni, et al. (1996). "Optical coherence tomography and microscopy in gastrointestinal tissues." *IEEE Journal of Selected Topics in Quantum Electronics* 2(4): 1017.
- Jacques, S. L., J. S. Nelson, et al. (1993). "Pulsed Photothermal Radiometry of Port-Wine-Stain Lesions." *Applied Optics* 32(13): 2439-2446.
- Jacques, S. L., J. R. Roman, et al. (2000). "Imaging superficial tissues with polarized light." *Lasers in Surgery and Medicine* 26(2): 119-129.
- Jang, I. K., B. E. Bouma, et al. (2002). "Visualization of coronary atherosclerotic plaques in patients using optical coherence tomography: Comparison with intravascular ultrasound." *Journal of the American College of Cardiology* 39(4): 604-609.

(56)

References Cited

OTHER PUBLICATIONS

- Jang, I. K., B. D. MacNeill, et al. (2002). "In-vivo characterization of coronary plaques in patients with ST elevation acute myocardial infarction using optical coherence tomography (OCT)." *Circulation* 106(19): 698-698 3440 Suppl. S.
- Jang, I. K., G. J. Tearney, et al. (2000). "Comparison of optical coherence tomography and intravascular ultrasound for detection of coronary plaques with large lipid-core in living patients." *Circulation* 102(18): 509-509.
- Jeng, J. C., A. Bridgeman, et al. (2003). "Laser Doppler imaging determines need for excision and grafting in advance of clinical judgment: a prospective blinded trial." *Burns* 29(7): 665-670.
- Jesser, C. A., S. A. Boppart, et al. (1999). "High resolution imaging of transitional cell carcinoma with optical coherence tomography: feasibility for the evaluation of bladder pathology." *British Journal of Radiology* 72: 1170-1176.
- Johnson, C. A., J. L. Keltner, et al. (2002). "Baseline visual field characteristics in the ocular hypertension treatment study." *Ophthalmology* 109(3): 432-7.
- Jones, R. C. (1941). "A new calculus for the treatment of optical systems III. The Sohncke theory of optical activity." *Journal of the Optical Society of America* 31(7): 500-503.
- Jones, R. C. (1941). "A new calculus for the treatment of optical systems I. Description and discussion of the calculus." *Journal of the Optical Society of America* 31(7): 488-493.
- Jones, R. C. (1942). "A new calculus for the treatment of optical systems. IV." *Journal of the Optical Society of America* 32(8): 486-493.
- Jones, R. C. (1947). "A New Calculus for the Treatment of Optical Systems .6. Experimental Determination of the Matrix." *Journal of the Optical Society of America* 37(2): 110-112.
- Jones, R. C. (1947). "A New Calculus for the Treatment of Optical Systems .5. A More General Formulation, and Description of Another Calculus." *Journal of the Optical Society of America* 37(2): 107-110.
- Jones, R. C. (1948). "A New Calculus for the Treatment of Optical Systems .7. Properties of the N-Matrices." *Journal of the Optical Society of America* 38(8): 671-685.
- Jones, R. C. (1956). "New Calculus for the Treatment of Optical Systems .8. Electromagnetic Theory." *Journal of the Optical Society of America* 46(2): 126-131.
- Jopson, R. M., L. E. Nelson, et al. (1999). "Measurement of second-order polarization-mode dispersion vectors in optical fibers." *Ieee Photonics Technology Letters* 11(9): 1153-1155.
- Jost, B. M., A. V. Sergienko, et al. (1998). "Spatial correlations of spontaneously down-converted photon pairs detected with a single-photon-sensitive CCD camera." *Optics Express* 3(2): 81-88.
- Kaplan, B., E. Compain, et al. (2000). "Phase-modulated Mueller ellipsometry characterization of scattering by latex sphere suspensions." *Applied Optics* 39(4): 629-636.
- Kass, M. A., D. K. Heuer, et al. (2002). "The Ocular Hypertension Treatment Study: a randomized trial determines that topical ocular hypotensive medication delays or prevents the onset of primary open-angle glaucoma." *Archives of Ophthalmology* 120(6): 701-13; discussion 829-30.
- Kasuga, Y., J. Arai, et al. (2000). "Optical coherence tomography to confirm early closure of macular holes." *American Journal of Ophthalmology* 130(5): 675-6.
- Kaufman, T., S. N. Lusthaus, et al. (1990). "Deep Partial Skin Thickness Burns—a Reproducible Animal-Model to Study Burn Wound-Healing." *Burns* 16(1): 13-16.
- Kemp, N. J., J. Park, et al. (2005). "High-sensitivity determination of birefringence in turbid media with enhanced polarization-sensitive optical coherence tomography." *Journal of the Optical Society of America a-Optics Image Science and Vision* 22(3): 552-560.
- Kerrigan-Baumrind, L. A., H. A. Quigley, et al. (2000). "Number of ganglion cells in glaucoma eyes compared with threshold visual field tests in the same persons." *Investigative Ophthalmology & Visual Science* 41(3): 741-8.
- Kesen, M. R., G. L. Spaeth, et al. (2002). "The Heidelberg Retina Tomograph vs clinical impression in the diagnosis of glaucoma." *American Journal of Ophthalmology* 133(5): 613-6.
- Kienle, A. and R. Hibst (1995). "A New Optimal Wavelength for Treatment of Port-Wine Stains." *Physics in Medicine and Biology* 40(10): 1559-1576.
- Kienle, A., L. Lilge, et al. (1996). "Spatially resolved absolute diffuse reflectance measurements for noninvasive determination of the optical scattering and absorption coefficients of biological tissue." *Applied Optics* 35(13): 2304-2314.
- Kim, B. Y. and S. S. Choi (1981). "Analysis and Measurement of Birefringence in Single-Mode Fibers Using the Backscattering Method." *Optics Letters* 6(11): 578-580.
- Kimel, S., L. O. Svaasand, et al. (1994). "Differential Vascular-Response to Laser Photothermolysis." *Journal of Investigative Dermatology* 103(5): 693-700.
- Kloppenber, F. W. H., G. Beerthuis, et al. (2001). "Perfusion of burn wounds assessed by Laser Doppler Imaging is related to burn depth and healing time." *Burns* 27(4): 359-363.
- Knighton, R. W. and X. R. Huang (2002). "Analytical methods for scanning laser polarimetry." *Optics Express* 10(21): 1179-1189.
- Knighton, R. W., X. R. Huang, et al. (2002). "Analytical model of scanning laser polarimetry for retinal nerve fiber layer assessment." *Investigative Ophthalmology & Visual Science* 43(2): 383-392.
- Knuttel, A. R. S., Joseph M.: Shay, M.; Knutson, Jay R. (1994). "Stationary low-coherence light imaging and spectroscopy using a CCD camera." *Proc. SPIE*, vol. 2135: p. 239-250.
- Knuttel, A. and M. Boehlau-Godau (2000). "Spatially confined and temporally resolved refractive index and scattering evaluation in human skin performed with optical coherence tomography." *Journal of Biomedical Optics* 5(1): 83-92.
- Knuttel, A. and J. M. Schmitt (1993). "Stationary Depth-Profiling Reflectometer Based on Low-Coherence Interferometry." *Optics Communications* 102(3-4): 193-198.
- Knuttel, A., J. M. Schmitt, et al. (1994). "Low-Coherence Reflectometry for Stationary Lateral and Depth Profiling with Acoustooptic Deflectors and a Ccd Camera." *Optics Letters* 19(4): 302-304.
- Kobayashi, M., H. Hanafusa, et al. (1991). "Polarization-Independent Interferometric Optical-Time-Domain Reflectometer." *Journal of Lightwave Technology* 9(5): 623-628.
- Kolios, M. C., M. D. Sherar, et al. (1995). "Large Blood-Vessel Cooling in Heated Tissues—A Numerical Study." *Physics in Medicine and Biology* 40(4): 477-494.
- Koozekanani, D., K. Boyer, et al. (2001). "Retinal thickness measurements from optical coherence tomography using a Markov boundary model." *Ieee Transactions on Medical Imaging* 20(9): 900-916.
- Kop, R. H. J. and R. Sprik (1995). "Phase-sensitive interferometry with ultrashort optical pulses." *Review of Scientific Instruments* 66(12): 5459-5463.
- Kramer, R. Z., J. Bella, et al. (1999). "Sequence dependent conformational variations of collagen triple-helical structure." *Nature Structural Biology* 6(5): 454-7.
- Kulkarni, M. D., T. G. van Leeuwen, et al. (1998). "Velocity-estimation accuracy and frame-rate limitations in color Doppler optical coherence tomography." *Optics Letters* 23(13): 1057-1059.
- Kwon, Y. H., C. S. Kim, et al. (2001). "Rate of visual field loss and long-term visual outcome in primary open-angle glaucoma." *American Journal of Ophthalmology* 132(1): 47-56.
- Kwong, K. F., D. Yankelevich, et al. (1993). "400-Hz Mechanical Scanning Optical Delay-Line." *Optics Letters* 18(7): 558-560.
- Landers, J., I. Goldberg, et al. (2002). "Analysis of risk factors that may be associated with progression from ocular hypertension to primary open angle glaucoma." *Clin Experiment. Ophthalmology* 30(4): 242-7.
- Laszlo, A. and A. Venetianer (1998). Heat resistance in mammalian cells: Lessons and challenges. *Stress of Life*. 851: 169-178.
- Laszlo, A. and A. Venetianer (1998). "Heat resistance in mammalian cells: lessons and challenges. [Review] [52 refs]." *Annals of the New York Academy of Sciences* 851: 169-78.
- Laufer, J., R. Simpson, et al. (1998). "Effect of temperature on the optical properties of ex vivo human dermis and subdermis." *Physics in Medicine and Biology* 43(9): 2479-2489.

(56)

References Cited

OTHER PUBLICATIONS

- Lederer, D. E., J. S. Schuman, et al. (2003). "Analysis of macular volume in normal and glaucomatous eyes using optical coherence tomography." *American Journal of Ophthalmology* 135(6): 838-843.
- Lee, P. P., Z. W. Feldman, et al. (2003). "Longitudinal prevalence of major eye diseases." *Archives of Ophthalmology* 121(9): 1303-1310.
- Lehrer, M. S., T. T. Sun, et al. (1998). "Strategies of epithelial repair: modulation of stem cell and transit amplifying cell proliferation." *Journal of Cell Science* 111(Pt 19): 2867-75.
- Leibowitz, H. M., D. E. Krueger, et al. (1980). "The Framingham Eye Study monograph: An ophthalmological and epidemiological study of cataract, glaucoma, diabetic retinopathy, macular degeneration, and visual acuity in a general population of 2631 adults, 1973-1975." *Survey of Ophthalmology* 24(Suppl): 335-610.
- Leitgeb, R., C. K. Hitzenberger, et al. (2003). "Performance of fourier domain vs. time domain optical coherence tomography." *Optics Express* 11(8): 889-894.
- Leitgeb, R., L. F. Schmetterer, et al. (2002). "Flow velocity measurements by frequency domain short coherence interferometry." *Proc. SPIE* 4619: 16-21.
- Leitgeb, R. A., W. Drexler, et al. (2004). "Ultrahigh resolution Fourier domain optical coherence tomography." *Optics Express* 12(10): 2156-2165.
- Leitgeb, R. A., C. K. Hitzenberger, et al. (2003). "Phase-shifting algorithm to achieve high-speed long-depth-range probing by frequency-domain optical coherence tomography." *Optics Letters* 28(22): 2201-2203.
- Leitgeb, R. A., L. Schmetterer, et al. (2003). "Real-time assessment of retinal blood flow with ultrafast acquisition by color Doppler Fourier domain optical coherence tomography." *Optics Express* 11(23): 3116-3121.
- Leitgeb, R. A., L. Schmetterer, et al. (2004). "Real-time measurement of in vitro flow by Fourier-domain color Doppler optical coherence tomography." *Optics Letters* 29 (2): 171-173.
- LeRoyBrehonnet, F. and B. LeJeune (1997). "Utilization of Mueller matrix formalism to obtain optical targets depolarization and polarization properties." *Progress in Quantum Electronics* 21(2): 109-151.
- Leske, M. C., A. M. Connell, et al. (1995). "Risk factors for open-angle glaucoma. The Barbados Eye Study. [see comments]." *Archives of Ophthalmology* 113(7): 918-24.
- Leske, M. C., A. M. Connell, et al. (2001). "Incidence of open-angle glaucoma: the Barbados Eye Studies. The Barbados Eye Studies Group. [see comments]." *Archives of Ophthalmology* 119(1): 89-95.
- Leske, M. C., A. Heijl, et al. (1999). "Early Manifest Glaucoma Trial. Design and Baseline Data." *Ophthalmology* 106(11): 2144-2153.
- Lewis, S. E., J. R. DeBoer, et al. (2005). "Sensitive, selective, and analytical improvements to a porous silicon gas sensor." *Sensors and Actuators B: Chemical* 110(1): 54-65.
- Lexer, F., C. K. Hitzenberger, et al. (1999). "Dynamic coherent focus OCT with depth-independent transversal resolution." *Journal of Modern Optics* 46(3): 541-553.
- Li, X., C. Chudoba, et al. (2000). "Imaging needle for optical coherence tomography." *Optics Letters* 25: 1520-1522.
- Li, X., T. H. Ko, et al. (2001). "Intraluminal fiber-optic Doppler imaging catheter for structural and functional optical coherence tomography." *Optics Letters* 26: 1906-1908.
- Liddington, M. I. and P. G. Shakespeare (1996). "Timing of the thermographic assessment of burns." *Burns* 22(1): 26-8.
- Lindmo, T., D. J. Smithies, et al. (1998). "Accuracy and noise in optical Doppler tomography studied by Monte Carlo simulation." *Physics in Medicine and Biology* 43(10): 3045-3064.
- Liu, J., X. Chen, et al. (1999). "New thermal wave aspects on burn evaluation of skin subjected to instantaneous heating." *IEEE Transactions on Biomedical Engineering* 46(4): 420-8.
- Luke, D. G., R. McBride, et al. (1995). "Polarization mode dispersion minimization in fiber-wound piezoelectric cylinders." *Optics Letters* 20(24): 2550-2552.
- MacNeill, B. D., I. K. Jang, et al. (2004). "Focal and multi-focal plaque distributions in patients with macrophage acute and stable presentations of coronary artery disease." *Journal of the American College of Cardiology* 44(5): 972-979.
- Mahgerefteh, D. and C. R. Menyuk (1999). "Effect of first-order PMD compensation on the statistics of pulse broadening in a fiber with randomly varying birefringence." *Ieee Technology Letters* 11(3): 340-342.
- Maitland, D. J. and J. T. Walsh, Jr. (1997). "Quantitative measurements of linear birefringence during heating of native collagen." *Lasers in Surgery & Medicine* 20 (3): 310-8.
- Majaron, B., S. M. Srinivas, et al. (2000). "Deep coagulation of dermal collagen with repetitive Er : YAG laser irradiation." *Lasers in Surgery and Medicine* 26(2): 215-222.
- Mansuripur, M. (1991). "Effects of High-Numerical-Aperture Focusing on the State of Polarization in Optical and Magneto-optic Data-Storage Systems." *Applied Optics* 30(22): 3154-3162.
- Marshall, G. W., S. J. Marshall, et al. (1997). "The dentin substrate: structure and properties related to bonding." *Journal of Dentistry* 25(6): 441-458.
- Martin, P. (1997). "Wound healing—Aiming for perfect skin regeneration." *Science* 276 (5309): 75-81.
- Martinez, O. E. (1987). "3000 Times Grating Compressor with Positive Group-Velocity Dispersion—Application to Fiber Compensation in 1.3-1.6 μm Region." *Ieee Journal of Quantum Electronics* 23(1): 59-64.
- Martinez, O. E., J. P. Gordon, et al. (1984). "Negative Group-Velocity Dispersion Using Refraction." *Journal of the Optical Society of America a-Optics Image Science and Vision* 1(10): 1003-1006.
- McKinney, J. D., M. A. Webster, et al. (2000). "Characterization and imaging in optically scattering media by use of laser speckle and a variable-coherence source." *Optics Letters* 25(1): 4-6.
- Miglior, S., M. Casula, et al. (2001). "Clinical ability of Heidelberg retinal tomograph examination to detect glaucomatous visual field changes." *Ophthalmology* 108 (9): 1621-7.
- Milner, T. E., D. M. Goodman, et al. (1996). "Imaging laser heated subsurface chromophores in biological materials: Determination of lateral physical dimensions." *Physics in Medicine and Biology* 41(1): 31-44.
- Milner, T. E., D. M. Goodman, et al. (1995). "Depth Profiling of Laser-Heated Chromophores in Biological Tissues by Pulsed Photothermal Radiometry." *Journal of the Optical Society of America a-Optics Image Science and Vision* 12 (7): 1479-1488.
- Milner, T. E., D. J. Smithies, et al. (1996). "Depth determination of chromophores in human skin by pulsed photothermal radiometry." *Applied Optics* 35(19): 3379-3385.
- Mishchenko, M. I. and J. W. Hovenier (1995). "Depolarization of Light Backscattered by Randomly Oriented Nonspherical Particles." *Optics Letters* 20(12): 1356-&.
- Mistlberger, A., J. M. Liebmann, et al. (1999). "Heidelberg retina tomography and optical coherence tomography in normal, ocular-hypertensive, and glaucomatous eyes." *Ophthalmology* 106(10): 2027-32.
- Mitsui, T. (1999). "High-speed detection of ballistic photons propagating through suspensions using spectral interferometry." *Japanese Journal of Applied Physics Part 1-Regular Papers Short Notes & Review Papers* 38(5A): 2978-2982.
- Molteno, A. C., N. J. Bosma, et al. (1999). "Otago glaucoma surgery outcome study: long-term results of trabeculectomy—1976 to 1995." *Ophthalmology* 106(9): 1742-50.
- Morgner, U., W. Drexler, et al. (2000). "Spectroscopic optical coherence tomography." *Optics Letters* 25(2): 111-113.
- Morgner, U., F. X. Kartner, et al. (1999). "Sub-two-cycle pulses from a Kerr-lens mode-locked Ti : sapphire laser (vol. 24, p. 411, 1999)." *Optics Letters* 24(13): 920-920.
- Mourant, J. R., A. H. Hielscher, et al. (1998). "Evidence of intrinsic differences in the light scattering properties of tumorigenic and nontumorigenic cells." *Cancer Cytopathology* 84(6): 366-374.

(56)

References Cited

OTHER PUBLICATIONS

- Muller, M., J. Squier, et al. (1998). "Dispersion pre-compensation of 15 femtosecond optical pulses for high-numerical-aperture objectives." *Journal of Microscopy-Oxford* 191: 141-150.
- Muscat, S., N. McKay, et al. (2002). "Repeatability and reproducibility of corneal thickness measurements by optical coherence tomography." *Investigative Ophthalmology & Visual Science* 43(6): 1791-5.
- Musch, D. C., P. R. Lichter, et al. (1999). "The Collaborative Initial Glaucoma Treatment Study, Study Design, MethodsR, and Baseline Characteristics of Enrolled Patients." *Ophthalmology* 106: 653-662.
- Neerken, S., Lucassen, G.W., Bisschop, M.A., Lenderink, E., Nuijs, T.A.M. (2004). "Characterization of age-related effects in human skin: A comparative study that applies confocal laser scanning microscopy and optical coherence tomography." *Journal of Biomedical Optics* 9(2):274-281.
- Nelson, J. S., K. M. Kelly, et al. (2001). "Imaging blood flow in human port-wine in situ and in real time using optical Doppler tomography." *Archives of Dermatology* 137(6): 741-744.
- Newson, T. P., F. Farahi, et al. (1988). "Combined Interferometric and Polarimetric Fiber Optic Temperature Sensor with a Short Coherence Length Source." *Optics Communications* 68(3): 161-165.
- November, L. J. (1993). "Recovery of the Matrix Operators in the Similarity and Congruency Transformations—Applications in Polarimetry." *Journal of the Optical Society of America a-Optics Image Science and Vision* 10(4): 719-739.
- Oh, W. Y., S. H. Yun, et al. (2005). "Wide tuning range wavelength-swept laser with two semiconductor optical amplifiers." *Ieee Photonics Technology Letters* 17(3): 678-680.
- Oka, K. and T. Kato (1999). "Spectroscopic polarimetry with a channeled spectrum." *Optics Letters* 24(21): 1475-1477.
- Okugawa, T. and K. Rotate (1996). "Real-time coherence optical image processing by synthesis of the function using real-time holography." *Ieee Photonics Technology Letters* 8(2): 257-259.
- Oshima, M., R. Tofii, et al. (2001). "Finite element simulation of blood flow in the cerebral artery." *Computer Methods in Applied Mechanics and Engineering* 191 (6-7): 661-671.
- Pan, Y. T., H. K. Xie, et al. (2001). "Endoscopic optical coherence tomography based on a microelectromechanical mirror." *Optics Letters* 26(24): 1966-1968.
- Parisi, V., G. Manni, et al. (2001). "Correlation between optical coherence tomography, pattern electroretinogram, and visual evoked potentials in open-angle glaucoma patients." *Ophthalmology* 108(5): 905-12.
- Park, B. H., M. C. Pierce, et al. (2005). "Real-time fiber-based multi-functional spectral-domain optical coherence tomography at 1.3 μm ." *Optics Express* 13(11): 3931-3944.
- Park, D. H., J. W. Hwang, et al. (1998). "Use of laser Doppler flowmetry for estimation of the depth of burns." *Plastic and Reconstructive Surgery* 101(6): 1516-1523.
- Pendry, J. B., A. J. Holden, et al. (1999). "Magnetism from conductors and enhanced nonlinear phenomena." *Ieee Transactions on Microwave Theory and Techniques* 47(11): 2075-2084.
- Penninckx, D. and V. Morenas (1999). "Jones matrix of polarization mode dispersion." *Optics Letters* 24(13): 875-877.
- Pierce, M. C., M. Shishkov, et al. (2005). "Effects of sample arm motion in endoscopic polarization-sensitive optical coherence tomography." *Optics Express* 13(15):5739-5749.
- Pircher, M., E. Gotzinger, et al. (2003). "Measurement and imaging of water concentration in human cornea with differential absorption optical coherence tomography." *Optics Express* 11(18): 2190-2197.
- Pircher, M., E. Gotzinger, et al. (2003). "Speckle reduction in optical coherence tomography by frequency compounding." *Journal of Biomedical Optics* 8(3): 565-569.
- Podoleanu, A. G., G. M. Dobre, et al. (1998). "En-face coherence imaging using galvanometer scanner modulation." *Optics Letters* 23(3): 147-149.
- Podoleanu, A. G. and D. A. Jackson (1999). "Noise analysis of a combined optical coherence tomograph and a confocal scanning ophthalmoscope." *Applied Optics* 38(10): 2116-2127.
- Podoleanu, A. G., J. A. Rogers, et al. (2000). "Three dimensional OCT images from retina and skin." *Optics Express* 7(9): 292-298.
- Podoleanu, A. G., M. Seeger, et al. (1998). "Transversal and longitudinal images from the retina of the living eye using low coherence reflectometry." *Journal of Biomedical Optics* 3(1): 12-20.
- Poole, C. D. (1988). "Statistical Treatment of Polarization Dispersion in Single-Mode Fiber." *Optics Letters* 13(8): 687-689.
- Povazay, B., K. Bizheva, et al. (2002). "Submicrometer axial resolution optical coherence tomography." *Optics Letters* 27(20): 1800-1802.
- Qi, B., A. P. Himmer, et al. (2004). "Dynamic focus control in high-speed optical coherence tomography based on a microelectromechanical mirror." *Optics Communications* 232 (1-6): 123-128.
- Radhakrishnan, S., A. M. Rollins, et al. (2001). "Real-time optical coherence tomography of the anterior segment at 1310 nm." *Archives of Ophthalmology* 119(8): 1179-1185.
- Rogers, A. J. (1981). "Polarization-Optical Time Domain Reflectometry—A Technique for the Measurement of Field Distributions." *Applied Optics* 20(6): 1060-1074.
- Rollins, A. M. And J. A. Izatt (1999). "Optimal interferometer designs for optical coherence tomography." *Optics Letters* 24(21): 1484-1486.
- Rollins, A. M., R. Ung-arunyawee, et al. (1999). "Real-time in vivo imaging of human gastrointestinal ultrastructure by use of endoscopic optical coherence tomography with a novel efficient interferometer design." *Optics Letters* 24(19): 1358-1360.
- Rollins, A. M., S. Yazdanfar, et al. (2002). "Real-time in vivo colors Doppler optical coherence tomography." *Journal of Biomedical Optics* 7(1): 123-129.
- Rollins, A. M., S. Yazdanfar, et al. (2000). "Imaging of human retinal hemodynamics using color Doppler optical coherence tomography." *Investigative Ophthalmology & Visual Science* 41(4): S548-S548.
- Sandoz, P. (1997). "Wavelet transform as a processing tool in white-light interferometry." *Optics Letters* 22 (14): 1065-1067.
- Sankaran, V., M. J. Everett, et al. (1999). "Comparison of polarized-light propagation in biological tissue and phantoms." *Optics Letters* 24(15): 1044-1046.
- Sankaran, V., J. T. Walsh, et al. (2000). "Polarized light propagation through tissue phanto, ehms containing densely packed scatterers." *Optics Letters* 25(4): 239-241.
- Sarunic, M. V., M. A. Choma, et al. (2005). "Instantaneous complex conjugate resolved spectral domain and swept-source OCT using 3x3 fiber couplers." *Optics Express* 13(3): 957-967.
- Sathyam, U. S., B. W. Colston, et al. (1999). "Evaluation of optical coherence quantitation of analytes in turbid media by use of two wavelengths." *Applied Optics* 38(10): 2097-2104.
- Schmitt, J. M. (1997). "Array detection for speckle reduction in optical coherence microscopy." *Physics in Medicine and Biology* 42(7): 1427-1439.
- Schmitt, J. M. (1999). "Optical coherence tomography (OCT): A review." *Ieee Journal of Selected Topics in Quantum Electronics* 5(4): 1205-1215.
- Schmitt, J. M. and A. Knüttel (1997). "Model of optical coherence tomography of heterogeneous tissue." *Journal of the Optical Society of America a-Optics Image Science and Vision* 14(6): 1231-1242.
- Schmitt, J. M., S. L. Lee, et al. (1997). "An optical coherence microscope with enhanced resolving power in thick tissue." *Optics Communications* 142(4-6): 203-207.
- Schmitt, J. M., S. H. Xiang, et al. (1998). "Differential absorption imaging with optical coherence tomography." *Journal of the Optical Society of America a-Optics Image Science and Vision* 15(9): 2288-2296.
- Schmitt, J. M., S. H. Xiang, et al. (1999). "Speckle in optical coherence tomography." *Journal of Biomedical Optics* 4(1): 95-105.
- Schmitt, J. M., M. J. Yadlowsky, et al. (1995). "Subsurface Imaging of Living Skin with Optical Coherence Microscopy." *Dermatology* 191(2): 93-98.

(56)

References Cited

OTHER PUBLICATIONS

- Shi, H., J. Finlay, et al. (1997). "Multiwavelength 10-GHz picosecond pulse generation from a single-stripe semiconductor diode laser." *Ieee Photonics Technology Letters* 9(11): 1439-1441.
- Shi, H., I. Nitta, et al. (1999). "Demonstration of phase correlation in multiwavelength mode-locked semiconductor diode lasers." *Optics Letters* 24(4): 238-240.
- Simon, R. (1982). "The Connection between Mueller and Jones Matrices of Polarization Optics." *Optics Communications* 42(5): 293-297.
- Smith, P. J. M., (2000) "Variable-Focus Microlenses as a Potential Technology for Endoscopy." *SPIE* (vol. 3919), USA pp. 187-192.
- Smithies, D. J., T. Lindmo, et al. (1998). "Signal attenuation and localization in optical coherence tomography studied by Monte Carlo simulation." *Physics in Medicine and Biology* 43(10): 3025-3044.
- Sorin, W. V. and D. F. Gray (1992). "Simultaneous Thickness and Group Index Measurement Using Optical Low-Coherence Reflectometry." *Ieee Photonics Technology Letters* 4(1): 105-107.
- Sticker, M., C. K. Hitzenger, et al. (2001). "Quantitative differential phase measurement and imaging in transparent and turbid media by optical coherence tomography." *Optics Letters* 26(8): 518-520.
- Sticker, M., M. Pircher, et al. (2002). "En face imaging of single cell layers by differential phase-contrast optical coherence microscopy." *Optics Letters* 27(13): 1126-1128.
- Stoller, P., B. M. Kim, et al. (2002). "Polarization-dependent optical second-harmonic imaging of a rat-tail tendon." *Journal of Biomedical Optics* 7(2): 205-214.
- Sun, C. S. (2003). "Multiplexing of fiber-optic acoustic sensors in a Michelson interferometer configuration." *Optics Letters* 28(12): 1001-1003.
- Swanson, E. A., J. A. Izatt, et al. (1993). "In-Vivo Retinal Imaging by Optical Coherence Tomography." *Optics Letters* 18(21): 1864-1866.
- Takada, K., A. Himeno, et al. (1991). "Phase-Noise and Shot-Noise Limited Operations of Low Coherence Optical-Time Domain Reflectometry." *Applied Physics Letters* 59(20): 2483-2485.
- Takenaka, H. (1973). "Unified Formalism for Polarization Optics by Using Group-Theory I (Theory)." *Japanese Journal of Applied Physics* 12(2): 226-231.
- Tanno, N., T. Ichimura, et al. (1994). "Optical Multimode Frequency-Domain Reflectometer." *Optics Letters* 19(8): 587-589.
- Targowski, P., M. Wojtkowski, et al. (2004). "Complex spectral OCT in human eye imaging in vivo." *Optics Communications* 229(1-6): 79-84.
- Tearney, G. J., S. A. Boppart, et al. (1996). "Scanning single-mode fiber optic catheter-endoscope for optical coherence tomography (vol. 21, p. 543, 1996)." *Optics Letters* 21(12): 912-912.
- Tearney, G. J., B. E. Bouma, et al. (1996). "Rapid acquisition of in vivo biological images by use of optical coherence tomography." *Optics Letters* 21(17): 1408-1410.
- Tearney, G. J., B. E. Bouma, et al. (1997). "In vivo endoscopic optical biopsy with optical coherence tomography." *Science* 276(5321): 2037-2039.
- Tearney, G. J., M. E. Brezinski, et al. (1996). "Catheter-based optical imaging of a human coronary artery." *Circulation* 94(11): 3013-3013.
- Tearney, G. J., M. E. Brezinski, et al. (1997). "In vivo endoscopic optical biopsy with optical coherence tomography." *Science* 276(5321): 2037-9.
- Tearney, G. J., M. E. Brezinski, et al. (1997). "Optical biopsy in human gastrointestinal tissue using optical coherence tomography." *American Journal of Gastroenterology* 92(10): 1800-1804.
- Tearney, G. J., M. E. Brezinski, et al. (1995). "Determination of the refractive index of highly scattering human tissue by optical coherence tomography." *Optics Letters* 20(21): 2258-2260.
- Tearney, G. J., I. K. Jang, et al. (2000). "Porcine coronary imaging in vivo by optical coherence tomography." *Acta Cardiologica* 55(4): 233-237.
- Tearney, G. J., R. H. Webb, et al. (1998). "Spectrally encoded confocal microscopy." *Optics Letters* 23(15): 1152-1154.
- Tearney, G. J., H. Yabushita, et al. (2003). "Quantification of macrophage content in atherosclerotic plaques by optical coherence tomography." *Circulation* 107(1): 113-119.
- Tower, T. T. and R. T. Tranquillo (2001). "Alignment maps of tissues: I. Microscopic elliptical polarimetry." *Biophysical Journal* 81(5): 2954-2963.
- Tower, T. T. and R. T. Tranquillo (2001). "Alignment maps of tissues: II. Fast harmonic analysis for imaging." *Biophysical Journal* 81(5): 2964-2971.
- Troy, T. L. and S. N. Thennadil (2001). "Optical properties of human skin in the near infrared wavelength range of 1000 to 2200 nm." *Journal of Biomedical Optics* 6 (2): 167-176.
- Vabre, L., A. Dubois, et al. (2002). "Thermal-light full-field optical coherence tomography." *Optics Letters* 27(7): 530-532.
- Vakhtin, A. B., D. J. Kane, et al. (2003). "Common-path interferometer for frequency-domain optical coherence tomography." *Applied Optics* 42(34): 6953-6958.
- Vakhtin, A. B., K. A. Peterson, et al. (2003). "Differential spectral interferometry: an imaging technique for biomedical applications." *Optics Letters* 28(15): 1332-1334.
- Vakoc, B. J., S. H. Yun, et al. (2005). "Phase-resolved optical frequency domain imaging." *Optics Express* 13(14): 5483-5493.
- van Leeuwen, T. G., M. D. Kulkarni, et al. (1999). "High-flow-velocity and shear-rate imaging by use of color Doppler optical coherence tomography." *Optics Letters* 24(22): 1584-1586.
- Vansteenkiste, N., P. Vignolo, et al. (1993). "Optical Reversibility Theorems for Polarization—Application to Remote-Control of Polarization." *Journal of the Optical Society of America a-Optics Image Science and Vision* 10(10): 2240-2245.
- Vargas, O., E. K. Chan, et al. (1999). "Use of an agent to reduce scattering in skin." *Lasers in Surgery and Medicine* 24(2): 133-141.
- Wang, R. K. (1999). "Resolution improved optical coherence-gated tomography for imaging through biological tissues." *Journal of Modern Optics* 46(13): 1905-1912.
- Wang, X. J., T. E. Milner, et al. (1997). "Measurement of fluid-flow-velocity profile in turbid media by the use of optical Doppler tomography." *Applied Optics* 36(1): 144-149.
- Wang, X. J., T. E. Milner, et al. (1995). "Characterization of Fluid-Flow Velocity by Optical Doppler Tomography." *Optics Letters* 20(11): 1337-1339.
- Wang, Y. M., J. S. Nelson, et al. (2003). "Optimal wavelength for ultrahigh-resolution optical coherence tomography." *Optics Express* 11(12): 1411-1417.
- Wang, Y. M., Y. H. Zhao, et al. (2003). "Ultrahigh-resolution optical coherence tomography by broadband continuum generation from a photonic crystal fiber." *Optics Letters* 28(3): 182-184.
- Watkins, L. R., S. M. Tan, et al. (1999). "Determination of interferometer phase distributions by use of wavelets." *Optics Letters* 24(13): 905-907.
- Wetzel, J. (2001). "Optical coherence tomography in dermatology: a review." *Skin Research and Technology* 7(1): 1-9.
- Wentworth, R. H. (1989). "Theoretical Noise Performance of Coherence-Multiplexed Interferometric Sensors." *Journal of Lightwave Technology* 7(6): 941-956.
- Westphal, V., A. M. Rollins, et al. (2002). "Correction of geometric and refractive image distortions in optical coherence tomography applying Fermat's principle." *Optics Express* 10(9): 397-404.
- Westphal, V., S. Yazdanfar, et al. (2002). "Real-time, high velocity-resolution color Doppler optical coherence tomography." *Optics Letters* 27(1): 34-36.
- Williams, P. A. (1999). "Rotating-wave-plate Stokes polarimeter for differential group delay measurements of polarization-mode dispersion." *Applied Optics* 38(31): 6508-6515.
- Wojtkowski, M., T. Bajraszewski, et al. (2003). "Real-time in vivo imaging by high-speed spectral optical coherence tomography." *Optics Letters* 28(19): 1745-1747.
- Wojtkowski, M., A. Kowalczyk, et al. (2002). "Full range complex spectral optical coherence tomography technique in eye imaging." *Optics Letters* 27(16): 1415-1417.

(56)

References Cited

OTHER PUBLICATIONS

- Wojtkowski, M., R. Leitgeb, et al. (2002). "In vivo human retinal imaging by Fourier domain optical coherence tomography." *Journal of Biomedical Optics* 7(3): 457-463.
- Wojtkowski, M., R. Leitgeb, et al. (2002). "Fourier domain OCT imaging of the human eye in vivo." *Proc. SPIE* 4619: 230-236.
- Wojtkowski, M., V. J. Srinivasan, et al. (2004). "Ultra-high-resolution, high-speed, Fourier domain optical coherence tomography and methods for dispersion compensation." *Optics Express* 12(11): 2404-2422.
- Wong, B. J. F., Y. H. Zhao, et al. (2004). "Imaging the internal structure of the rat cochlea using optical coherence tomography at 0.827 μm and 1.3 μm ." *Otolaryngology-Head and Neck Surgery* 130(3): 334-338.
- Yabushita, H. B., et al. (2002) "Measurement of Thin Fibrous Caps in Atherosclerotic Plaques by Optical Coherence Tomography." American Heart Association, Inc, *Circulation* 2002;106;1640.
- Yang, C., A. Wax, et al. (2001). "Phase-dispersion optical tomography." *Optics Letters* 26(10): 686-688.
- Yang, C., A. Wax, et al. (2001). "Phase-referenced interferometer with subwavelength and subhertz sensitivity applied to the study of cell membrane dynamics." *Optics Letters* 26(16): 1271-1273.
- Yang, C. H., A. Wax, et al. (2001). "Phase-dispersion optical tomography." *Optics Letters* 26(10): 686-688.
- Yang, C. H., A. Wax, et al. (2000). "Interferometric phase-dispersion microscopy." *Optics Letters* 25(20): 1526-1528.
- Yang, V. X. D., M. L. Gordon, et al. (2002). "Improved phase-resolved optical Doppler tomography using the Kasai velocity estimator and histogram segmentation." *Optics Communications* 208(4-6): 209-214.
- Yang, V. X. D., M. L. Gordon, et al. (2003). "High speed, wide velocity dynamic range Doppler optical coherence tomography (Part I): System design, signal processing, and performance" *Optics Express* 11(7): 794-809.
- Yang, V. X. D., M. L. Gordon, et al. (2003). "High speed, wide velocity dynamic range Doppler optical coherence tomography (Part II): Imaging in vivo cardiac dynamics of *Xenopus laevis*." *Optics Express* 11(14): 1650-1658.
- Yang, V. X. D., M. L. Gordon, et al. (2003). "High speed, wide velocity dynamic range Doppler optical coherence tomography (Part III): in vivo endoscopic imaging of blood flow in the rat and human gastrointestinal tracts." *Optics Express* 11(19): 2416-2424.
- Yang, V. X. D., B. Qi, et al. (2003). "In vivo feasibility of endoscopic catheter-based Doppler optical coherence tomography." *Gastroenterology* 124(4): A49-A50.
- Yao, G. And L. H. V. Wang (2000). "Theoretical and experimental studies of ultrasound-modulated optical tomography in biological tissue." *Applied Optics* 39(4): 659-664.
- Yazdanfar, S. and J. A. Izatt (2002). "Self-referenced Doppler optical coherence tomography." *Optics Letters* 27(23): 2085-2087.
- Yazdanfar, S., M. D. Kulkarni, et al. (1997). "High resolution imaging of in vivo cardiac dynamics using color Doppler optical coherence tomography." *Optics Express* 1 (13) : 424-431.
- Yazdanfar, S., A. M. Rollins, et al. (2000). "Imaging and velocimetry of the human retinal circulation with color Doppler optical coherence tomography." *Optics Letters* 25(19): 1448-1450.
- Yazdanfar, S., A. M. Rollins, et al. (2000). "Noninvasive imaging and velocimetry of human retinal blood flow using color Doppler optical coherence tomography." *Investigative Ophthalmology & Visual Science* 41(4): S548-S548.
- Yazdanfar, S., A. M. Rollins, et al. (2003). "In vivo imaging of human retinal flow dynamics by color Doppler optical coherence tomography." *Archives of Ophthalmology* 121(2): 235-239.
- Yazdanfar, S., C. H. Yang, et al. (2005). "Frequency estimation precision in Doppler optical coherence tomography using the Cramer-Rao lower bound." *Optics Express* 13(2): 410-416.
- Yun, S. H., C. Boudoux, et al. (2004). "Extended-cavity semiconductor wavelength-swept laser for biomedical imaging." *Ieee Photonics Technology Letters* 16(1): 293-295.
- Yun, S. H., C. Boudoux, et al. (2003). "High-speed wavelength-swept semiconductor laser with a polygon-scanner-based wavelength filter." *Optics Letters* 28(20): 1981-1983.
- Yun, S. H., G. J. Tearney, et al. (2004). "Pulsed-source and swept-source spectral-domain optical coherence tomography with reduced motion artifacts." *Optics Express* 12(23): 5614-5624.
- Yun, S. H., G. J. Tearney, et al. (2004). "Removing the depth-degeneracy in optical frequency domain imaging with frequency shifting." *Optics Express* 12(20): 4822-4828.
- Yun, S. H., G. J. Tearney, et al. (2004). "Motion artifacts in optical coherence tomography with frequency-domain ranging." *Optics Express* 12(13): 2977-2998.
- Zhang, J., J. S. Nelson, et al. (2005). "Removal of a mirror image and enhancement of the signal-to-noise ratio in Fourier-domain optical coherence tomography using an electro-optic phase modulator." *Optics Letters* 30(2): 147-149.
- Zhang, Y., M. Sato, et al. (2001). "Numerical investigations of optimal synthesis of several low coherence sources for resolution improvement." *Optics Communications* 192(3-6): 183-192.
- Zhang, Y., M. Sato, et al. (2001). "Resolution improvement in optical coherence tomography by optimal synthesis of light-emitting diodes." *Optics Letters* 26(4): 205-207.
- Zhao, Y., Z. Chen, et al. (2002). "Real-time phase-resolved functional optical coherence tomography by use of optical Hilbert transformation." *Optics Letters* 27(2): 98-100.
- Zhao, Y. H., Z. P. Chen, et al. (2000). "Doppler standard deviation imaging for clinical monitoring of in vivo human skin blood flow." *Optics Letters* 25(18): 1358-1360.
- Zhao, Y. H., Z. P. Chen, et al. (2000). "Phase-resolved optical coherence tomography and optical Doppler tomography for imaging blood flow in human skin with fast scanning speed and high velocity sensitivity." *Optics Letters* 25(2): 114-116.
- Zhou, D., P. R. Prucnal, et al. (1998). "A widely tunable narrow linewidth emiconductor fiber ring laser." *Ieee Photonics Technology Letters* 10(6): 781-783.
- Zuluaga, A. F. and R. Richards-Kortum (1999). "Spatially resolved spectral interferometry for determination of subsurface structure." *Optics Letters* 24(8): 519-521.
- Zvyagin, A. V., J. B. FitzGerald, et al. (2000). "Real-time detection technique for Doppler optical coherence tomography." *Optics Letters* 25(22): 1645-1647.
- Marc Nikles et al., "Brillouin gain spectrum characterization in single-mode optical fibers", *Journal of Lightwave Technology* 1997, 15 (10): 1842-1851.
- Tsuyoshi Sonehara et al., "Forced Brillouin Spectroscopy Using Frequency-Tunable Continuous-Wave Lasers", *Physical Review Letters* 1995, 75 (23): 4234-4237.
- Hajime Tanaka et al., "New Method of Superheterodyne Light Beating Spectroscopy for Brillouin-Scattering Using Frequency-Tunable Lasers", *Physical Review Letters* 1995, 74 (9): 1609-1612.
- Webb RH et al. "Confocal Scanning Laser Ophthalmoscope", *Applied Optics* 1987, 26 (8): 1492-1499.
- Andreas Zumbusch et al. "Three-dimensional vibrational imaging by coherent anti-Stokes Raman scattering", *Physical Review Letters* 1999, 82 (20): 4142-4145.
- Katrin Kneipp et al., "Single molecule detection using surface-enhanced Raman scattering (SERS)", *Physical Review Letters* 1997, 78 (9): 1667-1670.
- K.J. Koski et al., "Brillouin imaging" *Applied Physics Letters* 87, 2005.
- Boas et al., "Diffusing temporal light correlation for burn diagnosis", *SPIE*, 1999, 2979:468-477.
- David J. Briers, "Speckle fluctuations and biomedical optics: implications and applications", *Optical Engineering*, 1993, 32(2):277-283.
- Clark et al., "Tracking Speckle Patterns with Optical Correlation", *SPIE*, 1992, 1772:77-87.
- Facchini et al., "An endoscopic system for DSPI", *Optik*, 1993, 95(1):27-30.
- Hrabovsky, M., "Theory of speckle displacement and decorrelation: application in mechanics", *SPIE*, 1998, 3479:345-354.

(56)

References Cited

OTHER PUBLICATIONS

- Sean J. Kirkpatrick et al., "Micromechanical behavior of cortical bone as inferred from laser speckle data", *Journal of Biomedical Materials Research*, 1998, 39(3):373-379.
- Sean J. Kirkpatrick et al., "Laser speckle microstrain measurements in vascular tissue", *SPIE*, 1999, 3598:121-129.
- Loree et al., "Mechanical Properties of Model Atherosclerotic Lesion Lipid Pools", *Arteriosclerosis and Thrombosis*, 1994, 14(2):230-234.
- Podbielska, H. "Interferometric Methods and Biomedical Research", *SPIE*, 1999, 2732:134-141.
- Richards-Kortum et al., "Spectral diagnosis of atherosclerosis using an optical fiber laser catheter", *American Heart Journal*, 1989, 118(2):381-391.
- Ruth, B. "blood flow determination by the laser speckle method", *Int J Microcirc: Clin Exp*, 1990.
- Shapo et al., "Intravascular strain imaging: Experiments on an Inhomogeneous Phantom", *IEEE Ultrasonics Symposium* 1996, 2:1177-1180.
- Shapo et al., "Ultrasonic displacement and strain imaging of coronary arteries with a catheter array", *IEEE Ultrasonics Symposium* 1995, 2:1511-1514.
- Thompson et al., "Imaging in scattering media by use of laser speckle", *Opt. Soc. Am. A.*, 1997, 14(9):2269-2277.
- Thompson et al., "Diffusive media characterization with laser speckle", *Applied Optics*, 1997, 36(16):3726-3734.
- Tuchin, Valery V., "Coherent Optical Techniques for the Analysis of Tissue Structure and Dynamics," *Journal of Biomedical Optics*, 1999, 4(1):106-124.
- M. Wussling et al., "Laser diffraction and speckling studies in skeletal and heart muscle", *Biomed, Biochim, Acta*, 1986, 45(1/2):S 23- S27.
- T. Yoshimura et al., "Statistical properties of dynamic speckles", *J. Opt. Soc. Am A*. 1986, 3(7):1032-1054.
- Zimnyakov et al., "Spatial speckle correlometry in applications to tissue structure monitoring", *Applied Optics* 1997, 36(22): 5594-5607.
- Zimnyakov et al., "A study of statistical properties of partially developed speckle fields as applied to the diagnosis of structural changes in human skin", *Optics and Spectroscopy*, 1994, 76(5): 747-753.
- Zimnyakov et al., "Speckle patterns polarization analysis as an approach to turbid tissue structure monitoring", *SPIE* 1999, 2981:172-180.
- Ramasamy Manoharan et al., "Biochemical analysis and mapping of atherosclerotic human artery using FT-IR microspectroscopy", *Atherosclerosis*, May 1993, 181-1930.
- N. V. Salunke et al., "Biomechanics of Atherosclerotic Plaque" *Critical Reviews™ in Biomedical Engineering* 1997, 25(3):243-285.
- D. Fu et al., "Non-invasive quantitative reconstruction of tissue elasticity using an iterative forward approach", *Phys. Med. Biol.* 2000 (45): 1495-1509.
- S.B. Adams Jr. et al., "The use of polarization sensitive optical coherence tomography and elastography to assess connective tissue", *Optical Soc. of American Washington* 2002, p. 3.
- International Search Report for International Patent application No. PCT/US2005/039740 published Feb. 21, 2006.
- International Written Opinion for International Patent application No. PCT/US2005/039740 published Feb. 21, 2006.
- International Search Report for International Patent application No. PCT/US2005/030294 published Aug. 22, 2006.
- International Written Opinion for International Patent application No. PCT/US2005/043951 published Apr. 6, 2006.
- International Search Report for International Patent application No. PCT/US2005/043951 published Apr. 6, 2006.
- Erdelyi et al. "Generation of diffraction-free beams for applications in optical microlithography", *J. Vac. Sci. Technol. B* 15 (12), Mar./Apr. 1997, pp. 287-292.
- International Search Report for International Patent application No. PCT/US2005/023664 published Oct. 12, 2005.
- International Written Opinion for International Patent application No. PCT/US2005/023664 published Oct. 12, 2005.
- Tearney et al., "Spectrally encoded miniature endoscopy" *Optical Society of America; Optical Letters* vol. 27, No. 6, Mar. 15, 2002; pp. 412-414.
- Yelin et al., "Double-clad Fiber for Endoscopy" *Optical Society of America; Optical Letters* vol. 29, No. 20, Oct. 16, 2005; pp. 2408-2410.
- International Search Report for International Patent application No. PCT/US2001/049704 published Dec. 10, 2002.
- International Search Report for International Patent application No. PCT/US2004/039454 published May 11, 2005.
- International Written Opinion for International Patent application No. PCT/US2004/039454 published May 11, 2005.
- PCT International Preliminary Report on Patentability for International Application No. PCT/US2004/038404 dated Jun. 2, 2006.
- Notice of Reasons for Rejection and English translation for Japanese Patent Application No. 2002-538830 dated May 12, 2008.
- Office Action dated Aug. 24, 2006 for U.S. Appl. No. 10/137,749.
- Barry Cense et al., "Spectral-domain polarization-sensitive optical coherence tomography at 850nm", *Coherence Domain Optical Methods and Optical Coherence Tomography in Biomedicine IX*, 2005, pp. 159-162.
- A. Ymeti et al., "Integration of microfluidics with a four-channel integrated optical Young interferometer immunosensor", *Biosensors and Bioelectronics*, Elsevier Science Publishers, 2005, pp. 1417-1421.
- PCT International Search Report for Application No. PCT/US2006/018865 filed May 5, 2006.
- International Written Opinion for International Patent application No. PCT/US2006/018865 filed May 5, 2006.
- John M. Ponerros, "Diagnosis of Barrett's esophagus using optical coherence tomography", *Gastrointestinal Endoscopy clinics of North America*, 14 (2004) pp. 573-588.
- P.F. Escobar et al., "Diagnostic efficacy of optical coherence tomography in the management of preinvasive and invasive cancer of uterine cervix and vulva", *Int. Journal of Gynecological Cancer* 2004, 14, pp. 470-474.
- Ko T et al., "Ultrahigh resolution in vivo versus ex vivo OCT imaging and tissue preservation", *Conference on Lasers and electro-optics*, 2001, pp. 252-253.
- Paul M. Ripley et al., "A comparison of Artificial Intelligence techniques for spectral classification in the diagnosis of human pathologies based upon optical biopsy", *Journal of Optical Society of America*, 2000, pp. 217-219.
- Wolfgang Drexler et al., "Ultrahigh-resolution optical coherence tomography", *Journal of Biomedical Optics Spie USA*, 2004, pp. 47-74.
- PCT International Search Report for Application No. PCT/US2006/016677 filed Apr. 28, 2006.
- International Written Opinion for International Patent application No. PCT/US2006/016677 filed Apr. 28, 2006.
- Office Action dated Nov. 13, 2006 for U.S. Appl. No. 10/501,268.
- Office Action dated Nov. 20, 2006 for U.S. Appl. No. 09/709,162.
- PCT International Search Report and Written Opinion for Application No. PCT/US2004/023585 filed Jul. 23, 2004.
- Office Action dated Dec. 6, 2006 for U.S. Appl. No. 10/997,789.
- Elliott, K. H. "The use of commercial CCD cameras as linear detectors in the physics undergraduate teaching laboratory", *European Journal of Physics*, 1998, pp. 107-117.
- Lauer, V. "New approach to optical diffraction tomography yielding a vector equation of diffraction tomography and a novel tomographic microscope", *Journal of Microscopy* vol. 205, Issue 2, 2002, pp. 165-176.
- Yu, P. et al. "Imaging of tumor necroses using full-frame optical coherence imaging", *Proceedings of SPIE* vol. 4956, 2003, pp. 34-41.
- Zhao, Y. et al. "Three-dimensional reconstruction of in vivo blood vessels in human skin using phase-resolved optical Doppler tomography", *IEEE Journal of Selected Topics in Quantum Electronics* 7.6 (2001): 931-935.

(56)

References Cited

OTHER PUBLICATIONS

- Office Action dated Dec. 18, 2006 for U.S. Appl. No. 10/501,276.
- Devesa, Susan S. et al. (1998) "Changing Patterns in the Incidence of Esophageal and Gastric Carcinoma in the United States." *American Cancer Society* vol. 83, No. 10 pp. 2049-2053.
- Barr, H et al. (2005) "Endoscopic Therapy for Barrett's Oesophagus" *Gut* vol. 54:875-884.
- Johnston, Mark H.(2005) "Technology Insight: Ablative Techniques for Barrett's Esophagus—Current and Emerging Trends" www.Nature.com/clinicalpractice/gasthep.
- Falk, Gary W. et al. (1997) "Surveillance of Patients with Barrett's Esophagus for Dysplasia and Cancer with Balloon Cytology" *Gastroenterology* vol. 112, pp. 1787-1797.
- Sepchler, Stuart Jon. (1997) "Barrett's Esophagus: Should We Brush off this Balloning Problem?" *Gastroenterology* vol. 112, pp. 2138-2152.
- Froehly, J. et al. (2003) "Multiplexed 3D Imaging Using Wavelength Encoded Spectral Interferometry: A Proof of Principle" *Optics Communications* vol. 222, pp. 127-136.
- Kubba A.K. et al. (1999) "Role of p53 Assessment in Management of Barrett's Esophagus" *Digestive Disease and Sciences* vol. 44, No. 4, pp. 659-667.
- Reid, Brian J. (2001) "p53 and Neoplastic Progression in Barrett's Esophagus" *The American Journal of Gastroenterology* vol. 96, No 5, pp. 1321-1323.
- Sharma, P. et al.(2003) "Magnification Chromoendoscopy for the Detection of Intestinal Metaplasia and Dysplasia in Barrett's Oesophagus" *Gut* vol. 52, pp. 24-27.
- Kuipers E.J et al. (2005) "Diagnostic and Therapeutic Endoscopy" *Journal of Surgical Oncology* vol. 92, pp. 203-209.
- Georgakoudi, Irene et al. (2001) "Fluorescence, Reflectance, and Light-Scattering Spectroscopy for Evaluating Dysplasia in Patients with Barrett's Esophagus" *Gastroenterology* vol. 120, pp. 1620-1629.
- Adrain, Alyn L. et al. (1997) "High-Resolution Endoluminal Sonography is a Sensitive Modality for the Identification of Barrett's Meaplasia" *Gastrointestinal Endoscopy* vol. 46, No. 2, pp. 147-151.
- Canto, Marcia Irene et al (1999) "Vital Staining and Barrett's Esophagus" *Gastrointestinal Endoscopy* vol. 49, No. 3, part 2, pp. 12-16.
- Evans, John A. et al. (2006) "Optical Coherence Tomography to Identify Intramucosal Carcinoma and High-Grade Dysplasia in Barrett's Esophagus" *Clinical Gastroenterology and Hepatology* vol. 4, pp. 38-3.
- Poneros, John M. et al. (2001) "Diagnosis of Specialized Intestinal Metaplasia by Optical Coherence Tomography" *Gastroenterology* vol. 120, pp. 7-12.
- Ho, W. Y. et al. (2005) "115 KHz Tuning Repetition Rate Ultrahigh-Speed Wavelength-Swept Semiconductor Laser" *Optics Letters* col. 30, No. 23, pp. 3159-3161.
- Brown, Stanley B. et al. (2004) "The Present and Future Role of Photodynamic Therapy in Cancer Treatment" *The Lancet Oncology* vol. 5, pp. 497-508.
- Boogert, Jolanda Van Den et al. (1999) "Endoscopic Ablation Therapy for Barrett's Esophagus with High-Grade Dysplasia: A Review" *The American Journal of Gastroenterology* vol. 94, No. 5, pp. 1153-1160.
- Sampliner, Richard E. et al. (1996) "Reversal of Barrett's Esophagus with Acid Suppression and Multipolar Electrocoagulation: Preliminary Results" *Gastrointestinal Endoscopy* vol. 44, No. 5, pp. 532-535.
- Sampliner, Richard E. (2004) "Endoscopic Ablative Therapy for Barrett's Esophagus: Current Status" *Gastrointestinal Endoscopy* vol. 59, No. 1, pp. 66-69.
- Soetikno, Roy M. et al. (2003) "Endoscopic Mucosal resection" *Gastrointestinal Endoscopy* vol. 57, No. 4, pp. 567-579.
- Ganz, Robert A. et al. (2004) "Complete Ablation of Esophageal Epithelium with a Balloon-based Bipolar Electrode: A Phased Evaluation in the Porcine and in the Human Esophagus" *Gastrointestinal Endoscopy* vol. 60, No. 6, pp. 1002-1010.
- Pfefer, Jorje at al. (2006) "Performance of the Aer-O-Scope, a Pneumatic, Self Propelling, Self Navigating Colonoscope in Animal Experiments" *Gastrointestinal Endoscopy* vol. 63, No. 5, pp. AB223.
- Overholt, Bergein F. et al. (1999) "Photodynamic Therapy for Barrett's Esophagus: Follow-Up in 100 Patients" *Gastrointestinal Endoscopy* vol. 49, No. 1, pp. 1-7.
- Vogel, Alfred et al. (2003) "Mechanisms of Pulsed Laser Ablation of Biological Tissues" *American Chemical Society* vol. 103, pp. 577-644.
- McKenzie, A. L. (1990) "Physics of Thermal Processes in Laser-Tissue Interaction" *Phys. Med.Biol* vol. 35, No. 9, pp. 1175-1209.
- Anderson, R. Rox et al. (1983) "Selective Photothermolysis" Precise Microsurgery by Selective Absorption of Pulsed Radiation *Science* vol. 220, No. 4596, pp. 524-527.
- Jacques, Steven L. (1993) "Role of Tissue Optics and Pulse Duration on Tissue Effects During High-Power Laser Irradiation" *Applied Optics* vol. 32, No. 13, pp. 2447-2454.
- Nahen, Kester et al. (1999) "Investigations on Acosustic On-Line Monitoring of IR Laser Ablation of burned Skin" *Lasers in Surgery and Medicine* vol. 25, pp. 69-78.
- Jerath, Maya R. et al. (1993) "Calibrated Real-Time Control of Lesion Size Based on Reflectance Images" *Applied Optics* vol. 32, No. 7, pp. 1200-1209.
- Jerath, Maya R. et al (1992) "Dynamic Optical Property Changes: Implications for Reflectance Feedback Control of Photocoagulation" *Journal of Photochemical, Photobiology. B: Biol* vol. 16, pp. 113-126.
- Deckelbaum, Lawrence I. (1994) "Coronary Laser Angioplasty" *Lasers in Surgery and Medicine* vol. 14, pp. 101-110.
- Kim, B.M. et al. (1998) "Optical Feedback Signal for Ultrashort Laser Pulse Ablation of Tissue" *Applied Surface Science* vol. 127-129, pp. 857-862.
- Brinkman, Ralf et al. (1996) "Analysis of Cavitation Dynamics During Pulsed Laser Tissue Ablation by Optical On-Line Monitoring" *IEEE Journal of Selected Topics in Quantum Electronics* vol. 2, No. 4, pp. 826-835.
- Whelan, W.M. et al. (2005) "A novel Strategy for Monitoring Laser Thermal Therapy Based on Changes in Optothermal Properties of Heated Tissues" *International Journal of Thermophysics* vol. 26., No. 1, pp. 233-241.
- Thomsen, Sharon et al. (1990) "Microscopic Correlates of Macroscopic Optical Property Changes During Thermal Coagulation of Myocardium" *SPIE* vol. 1202, pp. 2-11.
- Khan, Misban Huzaira et al. (2005) "Intradermally Focused Infrared Laser Pulses: Thermal Effects at Defined Tissue Depths" *Lasers in Surgery and Medicine* vol. 36, pp. 270-280.
- Neumann, R.A. et al. (1991) "Enzyme Histochemical Analysis of Cell Viability After Argon Laser-Induced Coagulation Necrosis of the Skin" *Journal of the American Academy of Dermatology* vol. 25, No. 6, pp. 991-998.
- Nadkarni, Seemantini K. et al (2005) "Charaterization of Atherosclerotic Plaques by Laser Speckle Imaging" *Circulation* vol. 112, pp. 885-892.
- Zimnyakov, Dmitry A. et al (2002) "Speckle-Contrast Monitoring of Tissue Thermal Modification" *Applied Optics* vol. 41, No. 28, pp. 5989-5996.
- Morelli, J.G., et al (1986) "Tunable Dye Laser (577 nm) Treatment of Port Wine Stains" *Lasers in Surgery and Medicine* vol. 6, pp. 94-99.
- French, P.M.W. et al. (1993) "Continuous-wave Mode-Locked Cr⁴⁺: YAG Laser" *Optics Letters* vol. 18, No. 1, pp. 39-41.
- Sennaroglu, Alphan at al. (1995) "Efficient Continuous-Wave Chromium-Doped Yag Laser" *Journal of Optical Society of America* vol. 12, No. 5, pp. 930-937.
- Bouma, B et al. (1994) "Hybrid Mode Locking of a Flash-Lamp-Pumped Ti: Al₂O₃ Laser" *Optics Letters* vol. 19, No. 22, pp. 1858-1860.
- Bouma, B et al. (1995) "High Resolution Optical Coherence Tomography Imaging Using a Mode-Locked Ti: Al₂O₃ Laser Source" *Optics Letters* vol. 20, No. 13, pp. 1486-1488.
- Fernandez, Cabrera Delia et al. "Automated detection of retinal layer structures on optical coherence tomography images", *Optics Express* vol. 13, No. 25, Oct. 4, 2005, pp. 10200-10216.

(56)

References Cited

OTHER PUBLICATIONS

- Ishikawa, Hiroshi et al. "Macular Segmentation with optical coherence tomography", *Investigative Ophthalmology & Visual Science*, vol. 46, No. 6, Jun. 2005, pp. 2012-2017.
- Hariri, Lida P. et al. "Endoscopic Optical Coherence Tomography and Laser-Induced Fluorescence Spectroscopy in a Murine Colon Cancer Model", *Laser in Surgery and Medicine*, vol. 38, 2006, pp. 305-313.
- PCT International Search Report and Written Opinion for Application No. PCT/US2006/031905 dated May 3, 2007.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060481 dated May 23, 2007.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060717 dated May 24, 2007.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060319 dated Jun. 6, 2007.
- D. Yelin et al., "Three-dimensional imaging using spectral encoding heterodyne interferometry", *Optics Letters*, Jul. 15, 2005, vol. 30, No. 14, pp. 1794-1796.
- Akiba, Masahiro et al. "En-face optical coherence imaging for three-dimensional microscopy", *SPIE*, 2002, pp. 8-15.
- Office Action dated Aug. 10, 2007 for U.S. Appl. No. 10/997,789.
- Office Action dated Feb. 2, 2007 for U.S. Appl. No. 11/174,425.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060657 dated Aug. 13, 2007.
- Lewis, Neil E. et al., (2006) "Applications of Fourier Transform Infrared Imaging Microscopy in Neurotoxicity", *Annals New York Academy of Sciences*, Dec. 17, 2006, vol. 820, pp. 234-246.
- Joo, Chulmin et al., Spectral-domain optical coherence phase microscopy for quantitative phase-contrast imaging, *Optics Letters*, Aug. 15, 2005, vol. 30, No. 16, pp. 2131-2133.
- Guo, Bujin et al., "Laser-based mid-infrared reflectance imaging of biological tissues", *Optics Express*, Jan. 12, 2004, vol. 12, No. 1, pp. 208-219.
- Office Action dated Mar. 28, 2007 for U.S. Appl. No. 11/241,907.
- Office Action dated May 23, 2007 for U.S. Appl. No. 10/406,751.
- Office Action dated May 23, 2007 for U.S. Appl. No. 10/551,735.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/061815 dated Aug. 2, 2007.
- Sir Randall, John et al., "Brillouin scattering in systems of biological significance", *Phil. Trans. R. Soc. Lond. A* 293, 1979, pp. 341-348.
- Takagi, Yasunari, "Application of a microscope to Brillouin scattering spectroscopy", *Review of Scientific Instruments*, No. 12, Dec. 1992, pp. 5552-5555.
- Lees, S. et al., "Studies of Compact Hard Tissues and Collagen by Means of Brillouin Light Scattering", *Connective Tissue Research*, 1990, vol. 24, pp. 187-205.
- Berovic, N. "Observation of Brillouin scattering from single muscle fibers", *European Biophysics Journal*, 1989, vol. 17, pp. 69-74.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/062465 dated Aug. 8, 2007.
- Pyhtila John W. et al., "Rapid, depth-resolved light scattering measurements using Fourier domain, angle-resolved low coherence interferometry", *Optics Society of America*, 2004.
- Pyhtila John W. et al., "Determining nuclear morphology using an improved angle-resolved low coherence interferometry system", *Optics Express*, Dec. 15, 2003, vol. 11, No. 25, pp. 3473-3484.
- Desjardins A.E., et al., "Speckle reduction in OCT using massively-parallel detection and frequency-domain ranging", *Optics Express*, May 15, 2006, vol. 14, No. 11, pp. 4736-4745.
- Nadkarni, Seemantini K., et al., "Measurement of fibrous cap thickness in atherosclerotic plaques by spatiotemporal analysis of laser speckle images", *Journal of Biomedical Optics*, vol. 11 Marsh/Apr. 2006, pp. 021006-1-8.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/066017 dated Aug. 30, 2007.
- Yamanari M. et al., "Polarization sensitive Fourier domain optical coherence tomography with continuous polarization modulation", *Proc. of SPIE*, vol. 6079, 2006.
- Zhang Jun et al., "Full range polarization-sensitive Fourier domain optical coherence tomography", *Optics Express*, Nov. 29, 2004, vol. 12, No. 24, pp. 6033-6039.
- European Patent Office Search report for Application No. 01991092.6-2305 dated Jan. 12, 2006.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/060670 dated Sep. 21, 2007.
- J. M. Schmitt et al., (1999) "Speckle in Optical Coherence Tomography: An Overview", *SPIE* vol. 3726, pp. 450-461.
- Office Action dated Oct. 11, 2007 for U.S. Appl. No. 11/534,095.
- Office Action dated Oct. 9, 2007 for U.S. Appl. No. 09/709,162.
- Notice of Allowance dated Oct. 3, 2007 for U.S. Appl. No. 11/225,840.
- Siavash Yazdanfar et al., "In Vivo imaging in blood flow in human retinal vessels using color Doppler optical coherence tomography", *SPIE*, 1999 vol. 3598, pp. 177-184.
- Office Action dated Oct. 30, 2007 for U.S. Appl. No. 11/670,069.
- Tang C. L. et al., "Wide-band electro-optical tuning of semiconductor lasers", *Applied Physics Letters*, vol. 30, No. 2, Jan. 15, 1977, pp. 113-116.
- Tang C. L. et al., "Transient effects in wavelength-modulated dye lasers", *Applied Physics Letters*, vol. 26, No. 9, May 1, 1975, pp. 534-537.
- Telle M. John, et al., "Very rapid tuning of cw dye laser", *Applied Physics Letters*, vol. 26, No. 10, May 15, 1975, pp. 572-574.
- Telle M. John, et al., "New method for electro-optical tuning of tunable lasers", *Applied Physics Letters*, vol. 24, No. 2, Jan. 15, 1974, pp. 85-87.
- Schmitt M. Joseph et al. "OCT elastography: imaging microscopic deformation and strain of tissue", *Optics Express*, vol. 3, No. 6, Sep. 14, 1998, pp. 199-211.
- M. Gualini Muddassir et al., "Recent Advancements of Optical Interferometry Applied to Medicine", *IEEE Transactions on Medical Imaging*, vol. 23, No. 2, Feb. 2004, pp. 205-212.
- Maurice L. Roch et al. "Noninvasive Vascular Elastography: Theoretical Framework", *IEEE Transactions on Medical Imaging*, vol. 23, No. 2, Feb. 2004, pp. 164-180.
- Kirkpatrick J. Sean et al. "Optical Assessment of Tissue Mechanical Properties", *Proceedings of the SPIE—The International Society for Optical Engineering SPIE—vol. 4001, 2000, pp. 92-101.*
- Lisauskas B. Jennifer et al., "Investigation of Plaque Biomechanics from Intravascular Ultrasound Images using Finite Element Modeling", *Proceedings of the 19th International Conference—IEEE* Oct. 30-Nov. 2, 1997, pp. 887-888.
- Parker K. J. et al., "Techniques for Elastic Imaging: A Review", *IEEE Engineering in Medicine and Biology*, Nov./Dec. 1996, pp. 52-59.
- European Patent Office Search Report dated Nov. 20, 2007 for European Application No. 05791226.3.
- Dubois Arnaud et al., "Ultra-high-resolution OCT using white-light interference microscopy", *Proceedings of SPIE*, 2003, vol. 4956, pp. 14-21.
- Office Action dated Jan. 3, 2008 for U.S. Appl. No. 10/997,789.
- Office Action dated Dec. 21, 2007 for U.S. Appl. No. 11/264,655.
- Office Action dated Dec. 18, 2007 for U.S. Appl. No. 11/288,994.
- Office Action dated Jan. 10, 2008 for U.S. Appl. No. 11/435,228.
- Office Action dated Jan. 10, 2008 for U.S. Appl. No. 11/410,937.
- Office Action dated Jan. 11, 2008 for U.S. Appl. No. 11/445,990.
- Office Action dated Feb. 4, 2008 for U.S. Appl. No. 10/861,179.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/061463 dated Jan. 23, 2008.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/061481 dated Mar. 17, 2008.
- PCT International Search Report and Written Opinion for Application No. PCT/US2007/078254 dated Mar. 28, 2008.
- Sadhvani, Ajay et al., "Determination of Teflon thickness with laser speckle I. Potential for burn depth diagnosis", *Optical Society of America*, 1996, vol. 35, No. 28, pp. 5727-5735.
- C.J. Stewart et al., "A comparison of two laser-based methods for determination of burn scar perfusion: Laser Doppler versus laser speckle imaging", *Elsevier Ltd.*, 2005, vol. 31, pp. 744-752.
- G. J. Tearney et al., "Atherosclerotic plaque characterization by spatial and temporal speckle pattern analysis", *CLEO 2001*, vol. 56, pp. 307-307.

(56)

References Cited

OTHER PUBLICATIONS

PCT International Search Report for Application No. PCT/US2007/068233 dated Feb. 21, 2008.

PCT International Search Report for Application No. PCT/US2007/060787 dated Mar. 18, 2008.

Statement under Article 19 and Reply to PCT Written Opinion for PCT International Application No. PCT/US2005/043951 dated Jun. 6, 2006.

PCT International Preliminary Report on Patentability for Application No. PCT/US2005/043951 dated Jun. 7, 2007.

Liptak David C. et al., (2007) "On the Development of a Confocal Rayleigh-Brillouin Microscope" *American Institute of Physics* vol. 78, 016106.

Office Action mailed Oct. 1, 2008 for U.S. Appl. No. 11/955,986. Invitation of Pay Additional Fees mailed Aug. 7, 2008 for International Application No. PCT/US2008/062354.

Invitation of Pay Additional Fees mailed Jul. 20, 2008 for International Application No. PCT/US2007/081982.

International Search Report and Written Opinion mailed Mar. 7, 2006 for PCT/US2005/035711.

International Search Report and Written Opinion mailed Jul. 18, 2008 for PCT/US2008/057533.

Aizu, Y et al. (1991) "Bio-Speckle Phenomena and Their Application to the Evaluation of Blood Flow" *Optics and Laser Technology*, vol. 23, No. 4, Aug. 1, 1991.

Richards G.J. et al. (1997) "Laser Speckle Contrast Analysis (LASCA): A Technique for Measuring Capillary Blood Flow Using the First Order Statistics of Laser Speckle Patterns" Apr. 2, 1997.

Gonick, Maria M., et al (2002) "Visualization of Blood Microcirculation Parameters in Human Tissues by Time Integrated Dynamic Speckles Analysis" vol. 972, No. 1, Oct. 1, 2002.

International Search Report and Written Opinion mailed Jul. 4, 2008 for PCT/US2008/051432.

Jonathan, Enock (2005) "Dual Reference Arm Low-Coherence Interferometer-Based Reflectometer for Optical Coherence Tomography (OCT) Application" *Optics Communications* vol. 252.

Motaghian Nezam, S.M.R. (2007) "increased Ranging Depth in optical Frequency Domain Imaging by Frequency Encoding" *Optics Letters*, vol. 32, No. 19, Oct. 1, 2007.

Office Action dated Jun. 30, 2008 for U.S. Appl. No. 11/670,058.

Office Action dated Jul. 7, 2008 for U.S. Appl. No. 10/551,735.

Australian Examiner's Report mailed May 27, 2008 for Australian patent application No. 2003210669.

Notice of Allowance mailed Jun. 4, 2008 for U.S. Appl. No. 11/174,425.

European communication dated May 15, 2008 for European patent application No. 05819917.5.

International Search Report and Written Opinion mailed Jun. 10, 2008 for PCT/US2008/051335.

Oh, W.Y. et al (2006) "Ultrahigh-Speed Optical Frequency Domain Imaging and Application to laser Ablation Monitoring" *Applied Physics Letters*, vol. 88.

Office Action dated Aug. 21, 2008 for U.S. Appl. No. 11/505,700.

Sticker, Markus (2002) En Face Imaging of Single Cell layers by Differential Phase-Contrast Optical Coherence Microscopy) *Optics Letters*, col. 27, No. 13, Jul. 1, 2002.

International Search Report and Written Opinion dated Jul. 17, 2008 for International Application No. PCT/US2008/057450.

International Search Report and Written Opinion dated Aug. 11, 2008 for International Application No. PCT/US2008/058703.

US National Library of Medicine (NLM), Bethesda, MD, US; Oct. 2007, "Abstracts of the 19th Annual Symposium of Transcatheter Cardiovascular Therapeutics, Oct. 20-25, 2007, Washington, DC, USA."

International Search Report and Written Opinion dated May 26, 2008 for International Application No. PCT/US2008/051404.

Office Action dated Aug. 25, 2008 for U.S. Appl. No. 11/264,655.

Office Action dated Sep. 11, 2008 for U.S. Appl. No. 11/624,334.

Office Action dated Aug. 21, 2008 for U.S. Appl. No. 11/956,079.

Gelikono, V. M. et al. Oct. 1, 2004 "Two-Wavelength Optical Coherence Tomography" *Radio physics and Quantum Electronics*, Kluwer Academic Publishers-Consultants. vol. 47, No. 10-1.

International Search Report and Written Opinion for PCT/US2007/081982 dated Oct. 19, 2007.

Database Compendex Engineering Information, Inc., New York, NY, US; Mar. 5, 2007, Yelin, Dvir et al: "Spectral-Domain Spectrally-Encoded Endoscopy".

Database Biosis Biosciences Information Service, Philadelphia, PA, US; Oct. 2006, Yelin D. et al: "Three-Dimensional Miniature Endoscopy".

International Search Report and Written Opinion mailed Mar. 14, 2005 for PCT/US2004/018045.

Notification of the international Preliminary Report on Patentability mailed Oct. 21, 2005.

Shim M.G. et al., "Study of Fiber-Optic Probes for in vivo Medical Raman Spectroscopy" *Applied Spectroscopy*. vol. 53, No. 6, Jun. 1999.

Bingid U. et al., "Fibre-Optic Laser-Assisted Infrared Tumour Diagnostics (FLAIR); Infrared Tumour Diagnostics" *Journal of Physics D. Applied Physics*, vol. 38, No. 15, Aug. 7, 2005.

Jun Zhang et al. "Full Range Polarization-Sensitive Fourier Domain Optical Coherence Tomography" *Optics Express*, vol. 12, No. 24. Nov. 29, 2004.

Yonghua et al., "Real-Time Phase-Resolved Functional Optical Hilbert Transformation" *Optics Letters*, vol. 27, No. 2, Jan. 15, 2002.

Siavash et al., "Self-Referenced Doppler Optical Coherence Tomography" *Optics Letters*, vol. 27, No. 23, Dec. 1, 2002.

International Search Report and Written Opinion dated Dec. 20, 2004 for PCT/US04/10152.

Notification Concerning Transmittal of International Preliminary Report on Patentability dated Oct. 13, 2005 for PCT/US04/10152.

International Search Report and Written Opinion dated Mar. 23, 2006 for PCT/US2005/042408.

International Preliminary Report on Patentability dated Jun. 7, 2007 for PCT/US2005/042408.

International Search Report and Written Opinion dated Feb. 28, 2007 for International Application No. PCT/US2006/038277.

International Search Report and Written Opinion dated Jan. 30, 2009 for International Application No. PCT/US2008/081834.

Fox, J.A. et al; "A New Galvanometric Scanner for Rapid tuning of CO₂ Lasers" *New York, IEEE, US* vol. Apr. 7, 1991.

Motaghian Nezam, S.M. et al: "High-speed Wavelength-Swept Semiconductor laser using a Diffraction Grating and a Polygon Scanner in Littro Configuration" *Optical Fiber Communication and the National Fiber Optic Engineers Conference* Mar. 29, 2007.

International Search Report and Written Opinion dated Feb. 2, 2009 for International Application No. PCT/US2008/071786.

Bilenca A et al: "The Role of Amplitude and phase in Fluorescence Coherence Imaging: From Wide Field to Nanometer Depth Profiling", *Optics IEEE*, May 5, 2007.

Inoue, Yusuke et al: "Variable Phase-Contrast Fluorescence Spectrometry for Fluorescently Strained Cells", *Applied Physics Letters*, Sep. 18, 2006.

Bernet, S et al: "Quantitative Imaging of Complex Samples by Spiral Phase Contrast Microscopy", *Optics Express*, May 9, 2006.

International Search Report and Written Opinion dated Jan. 15, 2009 for International Application No. PCT/US2008/074863.

Office Action dated Feb. 17, 2009 for U.S. Appl. No. 11/211,483.

Notice of Reasons for Rejection mailed Dec. 2, 2008 for Japanese patent application No. 2000-533782.

International Search Report and Written Opinion dated Feb. 24, 2009 for PCT/US2008/076447.

European Official Action dated Dec. 2, 2008 for EP 07718117.0.

Barfuss et al (1989) "Modified Optical Frequency Domain Reflectometry with High spatial Resolution for Components of integrated optic Systems", *Journal of Lightwave Technology*, IEEE vol. 7., No. 1.

Yun et al., (2004) "Removing the Depth-Degeneracy in Optical Frequency Domain Imaging with Frequency Shifting", *Optics Express*, vol. 12, No. 20.

International Search Report and Written Opinion dated Jun. 10, 2009 for PCT/US08/075456.

(56)

References Cited

OTHER PUBLICATIONS

European Search Report issued May 5, 2009 for European Application No. 01991471.2.

Motz, J.T. et al: "Spectral-and Frequency-Encoded Fluorescence Imaging" *Optics Letters*, OSA, Optical Society of America, Washington, DC, US, vol. 30, No. 20, Oct. 15, 2005, pp. 2760-2762.

Japanese Notice of Reasons for Rejection dated Jul. 14, 2009 for Japanese Patent application No. 2006-503161.

Office Action dated Aug. 18, 2009 for U.S. Appl. No. 12/277,178.

Office Action dated Aug. 13, 2009 for U.S. Appl. No. 10/136,813.

Office Action dated Aug. 6, 2009 for U.S. Appl. No. 11/624,455.

Office Action dated May 15, 2009 for U.S. Appl. No. 11/537,123.

Office Action dated Apr. 17, 2009 for U.S. Appl. No. 11/537,343.

Office Action dated Apr. 15, 2009 for U.S. Appl. No. 12/205,775.

Office Action dated Dec. 9, 2008 for U.S. Appl. No. 09/709,162.

Office Action dated Dec. 23, 2008 for U.S. Appl. No. 11/780,261.

Office Action dated Jan. 9, 2010 for U.S. Appl. No. 11/624,455.

Office Action dated Feb. 18, 2009 for U.S. Appl. No. 11/285,301.

Beddow et al, (May 2002) "Improved Performance Interferometer Designs for Optical Coherence Tomography", *IEEE Optical Fiber Sensors Conference*, pp. 527-530.

Yaqoob et al., (Jun. 2002) "High-Speed Wavelength-Multiplexed Fiber-Optic Sensors for Biomedicine," *Sensors Proceedings of the IEEE*, pp. 325-330.

Office Action dated Feb. 18, 2009 for U.S. Appl. No. 11/697,012.

Zhang et al, (Sep. 2004), "Fourier Domain Functional Optical Coherence Tomography", *Saratov Fall Meeting 2004*, pp. 8-14.

Office Action dated Feb. 23, 2009 for U.S. Appl. No. 11/956,129.

Office Action dated Mar. 16, 2009 for U.S. Appl. No. 11/621,694.

Office Action dated Oct. 1, 2009 for U.S. Appl. No. 11/677,278.

Office Action dated Oct. 6, 2009 for U.S. Appl. No. 12/015,642.

Lin, Stollen et al., (077) "A CW Tunable Near-infrared (1.085-1.175- μ m) Raman Oscillator," *Optics Letters*, vol. 1, 96.

Summons to attend Oral Proceedings dated Oct. 9, 2009 for European patent application No. 06813365.1.

Office Action dated Dec. 15, 2009 for U.S. Appl. No. 11/549,397.

Haggitt et al., "Barrett's Esophagus Correlation Between Mucin Histochemistry, Flow Cytometry, and Histological Diagnosis for Predicting Increased Cancer Risk," *Apr. 1988, American Journal of Pathology*, vol. 131, No. 1, pp. 53-61.

R.H. Hardwick et al., (1995) "c-erbB-2 Overexpression in the Dysplasia/Carcinoma Sequence of Barrett's Oesophagus," *Journal of Clinical Pathology*, vol. 48, No. 2, pp. 129-132.

W. Polkowski et al, (1998) Clinical Decision making in Barrett's Oesophagus can be supported by Computerized Immunoquantitation and Morphometry of Features Associated with Proliferation and Differentiation, *Journal of pathology*, vol. 184, pp. 161-168.

J.R. Turner et al., MN Antigen Expression in Normal Preneoplastic, and Neoplastic Esophagus: A Clinicopathological Study of a New Cancer-Associated Biomarker, Jun. 1997, *Human Pathology*, vol. 28, No. 6, pp. 740-744.

D.J. Bowery et al., (1999) "Patterns of Gastritis in Patients with Gastro-Oesophageal Reflux Disease," *Gut*, vol. 45, pp. 798-803.

O'Reih et al., (2000) "Expression of Oestrogen and Progesterone Receptors in Low-Grade Endometrial Stromal Sarcomas," *British Journal of Cancer*, vol. 82, No. 5, pp. 1030-1034.

M.I. Canto et al., (1999) "Vital Staining and Barrett's Esophagus," *Gastrointestinal Endoscopy*, vol. 49, No. 3, Part 2, pp. S12-S16.

S. Jackle et al., (2000) "In Vivo Endoscopic Optical Coherence Tomography of the Human Gastrointestinal Tract-Toward Optical Biopsy," *Endoscopy*, vol. 32, No. 10, pp. 743-749.

E. Montgomery et al., "Reproducibility of the Diagnosis of Dysplasia in Barrett Esophagus: A Reaffirmation," *Apr. 2001, Human Pathology*, vol. 32, No. 4, pp. 368-378.

H. Geddert et al., "Expression of Cyclin B1 in the Metaplasia-Dysphasia—Carcinoma Sequence of Barrett Esophagus," *Jan. 2002, Cancer*, vol. 94, No. 1, pp. 212-218.

P. Pfau et al., (2003) "Criteria for the Diagnosis of Dysphasia by Endoscopic Optical Coherence Tomography," *Gastrointestinal Endoscopy*, vol. 58, No. 2, pp. 196-2002.

R. Kiesslich et al., (2004) "Confocal Laser Endoscopy for Diagnosing Intraepithelial Neoplasias and Colorectal Cancer in Vivo," *Gastroenterology*, vol. 127, No. 3, pp. 706-713.

X. Qi et al., (2004) "Computer Aided Diagnosis of Dysphasia in Barrett's Esophagus Using Endoscopic Optical Coherence Tomography," *SPIE, Coherence Domain Optical Methods and Optical Coherence Tomography in Biomedicine VIII. Proc. of Conference on.*, vol. 5316, pp. 33-40.

Seltzer et al., (1991) "160 nm Continuous Tuning of a MQW Laser in an External Cavity Across the Entire 1.3 μ m Communications Window," *Electronics Letters*, vol. 27, pp. 95-96.

Office Action dated Jan. 25, 2010 for U.S. Appl. No. 11/537,048.

International Search Report dated Jan. 27, 2010 for PCT/US2009/050553.

International Search Report dated Jan. 27, 2010 for PCT/US2009/047988.

International Search Report dated Feb. 23, 2010 for U.S. Appl. No. 11/445,131.

Office Action dated Mar. 18, 2010 of U.S. Appl. No. 11/844,454.

Office Action dated Apr. 8, 2010 of U.S. Appl. No. 11/414,564.

Japanese Office Action dated Apr. 13, 2010 for Japanese Patent application No. 2007-515029.

International Search Report dated May 27, 2010 for PCT/US2009/063420.

Office Action dated May 28, 2010 for U.S. Appl. No. 12/015,642.

Office Action dated Jun. 2, 2010 for U.S. Appl. No. 12/112,205.

Office Action dated Jul. 7, 2010 for U.S. Appl. No. 11/624,277.

Montag Ethan D., "Parts of the Eye" online textbook for JIMG 774: Vision & Psychophysics, download on Jun. 23, 2010 from <http://www.cissit.edu/people/faculty/montag/vandplite/pages/chap...8/ch8p3.html>.

Office Action dated Jul. 16, 2010 for U.S. Appl. No. 11/445,990.

Office Action dated Jul. 20, 2010 for U.S. Appl. No. 11/625,135.

Office Action dated Aug. 5, 2010 for U.S. Appl. No. 11/623,852.

Chinese office action dated Aug. 4, 2010 for CN 200780005949.9.

Chinese office action dated Aug. 4, 2010 for CN 200780016266.3.

Zhang et al., "Full Range Polarization-Sensitive Fourier Domain Optical Coherence Tomography" *Optics Express*, Nov. 20, 2004, vol. 12, No. 24.

Office Action dated Aug. 27, 2010 for U.S. Appl. No. 11/569,790.

Office Action dated Aug. 31, 2010 for U.S. Appl. No. 11/677,278.

Office Action dated Sep. 3, 2010 for U.S. Appl. No. 12/139,314.

Yong Zhao et al: "Virtual Data Grid Middleware Services for Data-Intensive Science", *Concurrency and Computation: Practice and Experience*, Wiley, London, GB, Jan. 1, 2000, pp. 1-7, pp. 1532-0626.

Swan et al., "Toward Nanometer-Scale Resolution in Fluorescence Microscopy using Spectral Self-Interference" *IEEE Journal. Selected Topics in Quantum Electronics* 9 (2) 2003, pp. 294-300.

Moiseev et al., "Spectral Self-Interference Fluorescence Microscopy", *J. Appl. Phys.* 96 (9) 2004, pp. 5311-5315.

Hendrik Verschueren, "Interference Reflection Microscopy in Cell Biology", *J. Cell Sci.* 75, 1985, pp. 289-301.

Park et al., "Diffraction Phase and Fluorescence Microscopy", *Opt. Expr.* 14 (18) 2006, pp. 8263-8268.

Swan et al. "High Resolution Spectral Self-Interference Fluorescence Microscopy", *Proc. SPIE* 4621, 2002, pp. 77-85.

Sanchez et al., "Near-Field Fluorescence Microscopy Based on Two-Photon Excitation with Metal Tips", *Phys. Rev. Lett.* 82 (20) 1999, pp. 4014-4017.

Wojtkowski, Maciej, Ph.D. "Three-Dimensional Retinal Imaging with High-Speed Ultrahigh-Resolution Optical Coherence Tomography" *Ophthalmology*, Oct. 2005, 112(10): 1734-1746.

Vaughan, J.M. et al., "Brillouin Scattering, Density and Elastic Properties of the Lens and Cornea of the Eye", *Nature*, vol. 284, Apr. 3, 1980, pp. 489-491.

Hess, S.T. et al. "Ultra-high Resolution Imaging by Fluorescence Photoactivation Localization Microscopy" *Biophysical Journal* vol. 91, Dec. 2006, 4258-4272.

(56)

References Cited

OTHER PUBLICATIONS

Fernandez-Suarez, M. et al., "Fluorescent Probes for Super-Resolution Imaging in Living Cells" Nature Reviews Molecular Cell Biology vol. 9, Dec. 2008.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 1G




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B

PROCESS AND APPARATUS FOR A WAVELENGTH TUNING SOURCE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a divisional of U.S. patent application Ser. No. 11/867,953 filed Apr. 11, 2008, now U.S. Pat. No. 7,724,786 which is a divisional of U.S. patent application Ser. No. 10/861,179 filed Jun. 4, 2004, which issued as U.S. Pat. No. 7,519,096 on Apr. 14, 2009. This application also claims priority from U.S. patent application Ser. No. 60/476,600 filed on Jun. 6, 2003, and U.S. patent application Ser. No. 60/514,769 filed on Oct. 27, 2003, the entire disclosure of which is incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

The invention was made with the U.S. Government support under Grant Number DAMD17-99-2-9001 awarded by the U.S. Department of the Army and Grant Number BES-0086789 awarded by the National Science Foundation. Thus, the U.S. Government has certain rights in the invention.

FIELD OF THE INVENTION

The present invention relates generally to optical systems and more particularly to an optical wavelength filter system for wavelength tuning.

BACKGROUND OF THE INVENTION

Considerable effort has been devoted for developing rapidly and widely tunable wavelength laser sources for optical reflectometry, biomedical imaging, sensor interrogation, and tests and measurements. A narrow line width, wide-range and rapid tuning have been obtained by the use of an intra-cavity narrow band wavelength scanning filter. Mode-hopping-free, single-frequency operation has been demonstrated in an extended-cavity semiconductor laser by using a diffraction grating filter design. Obtaining single-frequency laser operation and ensuring mode-hop-free tuning, however, may use a complicated mechanical apparatus and limit the maximum tuning speed. One of the fastest tuning speeds demonstrated so far has been limited less than 100 nm/s. In certain applications such as biomedical imaging, multiple-longitudinal mode operation, corresponding to an instantaneous line width as large or great than 10 GHz, may be sufficient. Such width may provide a ranging depth of a few millimeters in tissues in optical coherence tomography and a micrometer-level transverse resolution in spectrally-encoded confocal microscopy.

A line width on the order of 10 GHz is readily achievable with the use of an intra-cavity tuning element (such as an acousto-optic filter, Fabry-Perot filter, and galvanometer-driven diffraction grating filter). However, the sweep fre-

quency previously demonstrated has been less than 1 kHz limited by finite tuning speeds of the filters. Higher-speed tuning with a repetition rate greater than 15 kHz may be needed for video-rate (>30 frames/s), high-resolution optical imaging in biomedical applications.

Accordingly, there is a need to overcome the above-described deficiencies.

SUMMARY OF THE INVENTION

According to the exemplary concepts of the present invention, an optical wavelength filter may be provided that can be tuned with a repetition rate of greater than 15 kHz over a wide spectral range. In addition, a wavelength tuning source comprising such optical filter in combination with a laser gain medium may be provided. The tuning source may be useful in video-rate optical imaging applications, such as the optical coherence tomography and spectrally encoded confocal microscope.

In general, the optical filter according to one exemplary embodiment of the present invention may include a diffraction grating, a rotating polygon scanner, and a telescope. Such optical filter can be operated at a tuning speed more than an order of magnitude higher than the conventional filters. The wavelength tunable light source may be implemented by employing the filter, e.g., in combination with a laser gain medium. The filter and gain medium may further, be incorporated into a laser cavity. For example, a laser can emit a narrow band spectrum with its center wavelength being swept over a broad wavelength range at a high repetition rate.

In one exemplary embodiment of the present invention, an apparatus is provided which includes an arrangement for emitting an electromagnetic radiation that has a spectrum whose mean frequency changes substantially continuously over time. Such radiation is may be associated with a tuning speed that is greater than 100 terahertz per millisecond. The mean frequency can change repeatedly at a repetition rate that is greater than 5 kilohertz or over a range greater than 10 terahertz. The spectrum may have a tuning range covering a portion of the visible, near-infrared or infrared wavelengths. Exemplary spectra may be centered at approximately at 850 nm, 1300 nm or 1700 nm wavelengths. Further, the spectrum may have an instantaneous line width that is smaller than 100 gigahertz. The apparatus may also include a laser cavity with a roundtrip length shorter than 5 m. The apparatus may also have a polygon scanner arrangement which may be adapted to receive at least a portion of the emitted electromagnetic radiation and reflect or deflect the portion to a further location. In addition, a beam separating arrangement can be provided which selectively receives components of the electromagnetic radiation.

According to another exemplary embodiment of the present invention the apparatus for filtering an electromagnetic radiation can include at least one spectral separating arrangement configured to physically separate one or more components of the electromagnetic radiation based on a frequency of the electromagnetic radiation. The apparatus may also have at least one continuously rotating optical arrangement that is configured to receive the physically separated components and selectively direct individual components to a beam selecting arrangement.

In one exemplary variation of the present invention, the spectral separating arrangement includes a diffraction grating, a prism, a grism, an acousto-optic beam deflector, a virtual phased array, and/or an arrayed waveguide grating. The continuously rotating optical arrangement may be a

5 polygon mirror, a diffractive element, a substantially opaque disk having an array of substantially transparent regions, and/or a substantially transparent disk having an array of substantially reflective regions. The spectral separating arrangement may also include a holographic grating mounted on a substrate comprising a continuously rotating optical arrangement.

In another exemplary variation of the present invention the beam selecting arrangement may be an optical fiber, an optical waveguide, a pinhole aperture, a combination of a lens with an optical fiber, waveguide or pinhole, and/or a spatial filter. The beam selecting arrangement can include a plurality of beam selecting elements, and the electromagnetic radiation which is transmitted by the plurality of beam selecting elements may be combined. The signal may be reflected multiple times from the continuously rotating optical arrangement before being received by the selecting arrangement.

According to yet another exemplary embodiment of the present invention the apparatus for filtering an electromagnetic radiation may include at least one spectral separating arrangement configured to angularly separate one or more components of the electromagnetic radiation based on a frequency of the electromagnetic radiation. Such arrangement can also include at least one angularly deflecting optical arrangement that includes a pivot point, and that is configured to receive the components of the electromagnetic radiation and selectively direct the components to a beam selecting arrangement. Further, the arrangement can include at least one optical imaging arrangement configured to receive the components of the electromagnetic radiation and generate an image of one or more dispersive elements associated with the components. The position of the pivot point of the angularly deflecting optical arrangement may be provided in proximity to a real or virtual image of at least one of the dispersive elements.

In one exemplary variant of the present invention, a deflection point of the angularly deflecting optical element may substantially overlap with a real image of at least one of the dispersive elements. At least one reflector which is configured to receive at least one signal from the at least one angularly deflecting optical arrangement may also be provided. One or more of the dispersive elements may be a diffraction grating, a prism, a grism, an acousto-optic beam deflector, a virtual phased array, and/or an arrayed waveguide grating. The angularly deflecting optical element may be a polygon mirror scanner, a galvanometer mirror scanner, or a piezo-electric mirror scanner.

According to still another exemplary embodiment of the present invention, an apparatus is provided for filtering an electromagnetic radiation. The apparatus includes at least one dispersive arrangement configured to angularly separate components of the electromagnetic radiation based on a frequency of the electromagnetic radiation, and generate frequency-separated components. The apparatus may also include at least one angularly deflecting optical element having a pivot point of an angular deflection. The pivot point can substantially overlap a location where substantially all of the frequency-separated components overlap.

In another exemplary embodiment of the present invention, at least one spectral separating arrangement can be provided that is configured to physically separate one or more components of the electromagnetic radiation based on a frequency of the electromagnetic radiation. In addition, at least one continuously rotating optical arrangement may be included which is configured to receive at least one signal that is associated with the one or more components. At least

one beam selecting arrangement may also be configured to receive the signal. The emitter can be a laser gain medium, a semiconductor optical amplifier, a laser diode, a superluminescent diode, a doped optical fiber, a doped laser crystal, a doped laser glass, and/or a laser dye.

In still another exemplary embodiment of the present invention, a source arrangement can provide an electromagnetic radiation. The source includes at least one emitter of the electromagnetic radiation, at least one spectral separating arrangement configured to angularly separate one or more components of the electromagnetic radiation based on a frequency of the electromagnetic radiation, as well as at least one angularly deflecting optical arrangement that includes a pivot point, and configured to receive the components of the electromagnetic radiation to generate at least one signal associated with the one or more components. In addition, the source arrangement can include at least one beam selecting arrangement adapted to receive the signal, and selectively generate at least one selected signal, and at least one optical imaging arrangement configured to receive the selected signal, and generate an image of one or more dispersive elements associated with the one or more components. In a variation of the present invention, more than one laser gain medium providing electromagnetic radiation and at least one spectral separating arrangement configured to physically separate one or more components of the electromagnetic radiation based on a frequency of the electromagnetic radiation can be provided. In this variation, the selected components of electromagnetic radiation from each laser gain medium are synchronized, and can be used separately or combined.

In one further exemplary embodiment of the present invention, a high-speed tuning of an extended-cavity semiconductor laser may be provided. The laser resonator may include a unidirectional fiber-optic ring, a semiconductor optical amplifier as the gain medium, and a scanning filter based on a polygon scanner. Variable tuning rates of up to 1,150 nm/ms (15.7 kHz repetition frequency) can be obtained over a 70 nm wavelength span centered at 1.32 μm . Such tuning rate can be more than an order of magnitude faster than is conventionally known, and may be facilitated in part by self-frequency shifting in the semiconductor optical amplifier. The instantaneous line width of the source may be <0.1 nm for 9-mW cw output power, and a low spontaneous-emission background of 80 dB can be obtained.

Other features and advantages of the present invention will become apparent upon reading the following detailed description of embodiments of the invention, when taken in conjunction with the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Further objects, features and advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying figures showing illustrative embodiments of the invention, in which:

FIG. 1A is a block diagram of a first exemplary embodiment of an optical wavelength filter according to the present invention;

FIG. 1B is a block diagram of a second exemplary embodiment of the optical wavelength filter according to the present invention;

FIG. 1C is a block diagram of a third exemplary embodiment of the optical wavelength filter according to the present invention;

5

FIG. 1D is a block diagram of a fourth exemplary embodiment of the optical wavelength filter according to the present invention;

FIG. 1E is a block diagram of a fifth exemplary embodiment of the optical wavelength filter according to the present invention;

FIG. 1F is a block diagram of a sixth exemplary embodiment of the optical wavelength filter according to the present invention;

FIG. 1G is a block diagram of a seventh exemplary embodiment of the optical wavelength filter according to the present invention;

FIG. 2 is a graph of exemplary characteristics of the optical wavelength filter according to the present invention;

FIG. 3 is an exemplary embodiment of the wavelength tuning laser source according to the present invention;

FIG. 4A is a graph of exemplary first output characteristics (laser spectrum vs. wavelength) of the laser source according to the present invention;

FIG. 4B is a graph of exemplary second output characteristics (output power vs. time) of the laser source according to the present invention;

FIG. 5 is a graph of exemplary output power provided as a function of sweep speed according to the present invention;

FIG. 6 is an exemplary embodiment of a free-space extended-cavity semiconductor tunable laser arrangement according to the present invention;

FIG. 7 is an illustration of a seventh exemplary embodiment of the optical wavelength filter according to the present invention;

FIG. 8 is a schematic diagram of an exemplary embodiment of a spectrally-encoded confocal microscope that utilizes the tunable laser source according to the present invention;

FIG. 9 is a schematic diagram of an exemplary embodiment of a frequency-domain optical coherence tomography arrangement that utilizes the tunable laser source according to the present invention;

FIG. 10A is a top view of an eighth exemplary embodiment of the wavelength filter according to the present invention; and

FIG. 10B is a perspective plan view of the wavelength filter shown in FIG. 10A.

DETAILED DESCRIPTION

FIG. 1A shows a block diagram of a first exemplary embodiment of an optical wavelength filter **1** in accordance the present invention. In this first exemplary embodiment, the optical wavelength filter **1** can be used in a variety of different applications, general examples of which are described below. In this example, the filter **1** may be coupled to one or more applications **3** via a light source **2**. It should be understood that in certain exemplary applications, the filter **1** can be used with or connected to an application (e.g., one or more of the applications **3**) via a device other than a light source (e.g. a passive or active optical element). In the first exemplary embodiment shown in FIG. 1A, a broad spectrum light source and/or controller **2** (hereinafter referred to as "light controller"), may be coupled to a wavelength dispersing element **4**. The light controller **2** can be further coupled to one or more of the applications **3** that are adapted to perform one or more tasks with or for, including but not limited to, optical imaging processes and optical imaging systems, laser machining processes and systems, photolithography and photolithographic systems,

6

laser topography systems, telecommunications processes and systems, etc. The wavelength dispersing element **4** can be coupled to a lens system **6**, which is further coupled to a beam deflection device **8**.

The light controller **2** can be one or more of various systems and/or arrangements that are configured to transmit a beam of light having a broad frequency (f) spectrum. In one exemplary embodiment, the beam of light may be a collimated beam of light. The beam of light can include a plurality of wavelengths $\lambda \dots \lambda_n$, within the visible light spectrum (e.g., red, blue, green). Similarly, the beam of light provided by the light controller **2** can also include a plurality of wavelengths $\lambda \dots \lambda_n$ that may be defined outside of the visible spectrum (e.g., ultraviolet, near infrared or infrared).

In one exemplary embodiment of the present invention, the light controller **2** can include a unidirectional light transmission ring, which shall be described in further detail below in connection with FIG. **3** which shows an exemplary embodiment of a wavelength tuning laser source. Further, in another exemplary embodiment of the present invention, the light controller **2** can include a linear resonator system, which shall be described in further detail below in connection with FIG. **6**.

The wavelength dispersing element **4** of the optical wavelength filter **1** can include one or more elements that are specifically adapted to receive the beam of light from the light controller **2**, and to conventionally separate the beam of light into a plurality of wavelengths of light having a number of directions. The wavelength dispersing element **4** is further operative to direct portions of light having different wavelengths in equal angular directions or displacements with respect to an optical axis **38**. In one exemplary embodiment of the present invention, the wavelength dispersing element **4** can include a light dispersion element, which may include but not limited to, a reflection grating, a transmission grating, a prism, a diffraction grating, an acousto-optic diffraction cell or combinations of one or more of these elements.

The lens system **6** of the optical wavelength filter **1** can include one or more optical elements adapted to receive the separated wavelengths of light from the wavelength dispersing element. Light at each wavelength propagates along a path which is at an angle with respect to the optical axis **38**. The angle is determined by the wavelength dispersing element **4**. Furthermore, the lens system **6** is adapted to direct or steer and/or focus the wavelengths of light to a predetermined position located on a beam deflection device **8**.

The beam deflection device **8** can be controlled to receive and selectively redirect one or more discrete wavelengths of light back along the optical axis **38** through the lens system **6** to the wavelength dispersing element **4** and back to the light controller **2**. Thereafter, the light controller **2** can selectively direct the received discrete wavelengths of light to any one or more of the applications. The beam deflecting device **8** can be provided in many different ways. For example, the beam deflecting device **8** can be provided from elements including, but not limited to, a polygonal mirror, a planar mirror disposed on a rotating shaft, a mirror disposed on a galvanometer, or an acousto-optic modulator.

FIG. 1B shows a schematic diagram of a second exemplary embodiment of the optical wavelength filter **1'**. The exemplary optical wavelength filter **1'** can be configured as a reflection-type filter which may have substantially identical input and output ports. An input/output optical fiber **10** and a collimating lens **12** can provide an input from a light controller **2'** (which may be substantially similar to the light

controller 2 described above with reference to FIG. 1A) to the optical wavelength filter 1'. The optical wavelength filter 1' includes a diffraction grating 16, optical telescoping elements 6' (hereinafter referred to as "telescope 6'" and may possibly be similar to the lens system 6 of FIG. 1A), and a polygon mirror scanner 24. The telescope 6' can include two lenses, e.g., first and second lenses 20, 22 with 4-f configuration.

In the second exemplary embodiment of the optical wavelength filter 1' shown in FIG. 1B, the telescope 6' includes the first and second lenses 20, 22, which are each substantially centered along the optical axis 38. The first lens 20 may be located at a first distance from the wavelength dispersing element 4' (e.g., diffraction grating 16), which can approximately be equal to the focal length F1 of the first lens 20. The second lens 22 may be located at a second distance from the first lens 20, which can be approximately equal to the sum of the focal length F1 of the first lens 20 and the focal length F2 of the second lens 22. Using such arrangement, the first lens 20 can receive one or more collimated discrete wavelengths of light from the wavelength dispersing element 4', and can effectively perform a Fourier Transform on each one of the collimated one or more discrete wavelengths of light to provide one or more approximately equal converging beams that are projected onto an image plane IP.

The image plane IP is preferably located between the first lens 20 and the second lens 22 and at a predetermined distance from the first lens 20. According to one exemplary variation of the present invention, such predetermined distance may be defined by the focal length F1 of the first lens 20. After such one or more converging beams are propagated through the image plane IP, these one or more converging beams form equal or corresponding one or more diverging beams that are received by the second lens 22. The second lens 22 is adapted to receive the diverging beams and provide approximately an equal number of collimated beams having predetermined angular displacements with respect to the optical axis 38. Thus, the second lens 22 can direct or steer the collimated beams to predefined portions of the beam deflection device 8'.

The telescope 6' according to the second exemplary embodiment of the present invention is operative to provide one or more features as described above, as well as to convert a diverging angular dispersion from the grating into converging angular dispersion after the second lens 22. Such result may be advantageous for a proper operation of the filter. In addition, the telescope 6' may provide adjustable parameters which control the tuning range and linewidth and reduce the beam size at the polygon mirror to avoid beam clipping. As is illustrated in the exemplary embodiment of FIG. 1B, a beam deflection device 6' (e.g., which may include a polygon mirror or arrangement 24) is adapted to preferably reflect back only the spectral component within a narrow passband as a function of the angle of the front minor facet of the polygon arrangement 24 with respect to the optic axis 38. The reflected narrow band light is diffracted and received by the optical fiber 10. The orientation of the incident beam 30 with respect to the optic axis and a rotation direction 40 of the polygon arrangement 24 can be used to determine the direction of wavelength tuning, e.g., a wavelength up (positive) scan or a wavelength down (negative) scan. The exemplary arrangement shown in FIG. 1B can generate a positive wavelength sweep. It should be understood that although the polygon arrangement 24 is shown in FIG. 1B as having twelve facets, polygon arrangements which have fewer than twelve facets or greater than twelve

facets can also be used. While generally not considering practical mechanical limits, based upon conventional manufacturing techniques, a particular number of facets of the polygon arrangement 24 to use in any application may depend on a desired scanning rate and a scanning range for a particular application.

Furthermore, the size of the polygon arrangement 24 may be selected based on preferences of a particular application, and preferably taking into account certain factors including, but not limited to, manufacturability and weight of the polygon arrangement 24. It should also be understood that lenses 20, 22 that have different focal lengths may be provided. For example, the lenses 20, 22 should be selected to provide a focal point at approximately the center point 24a of the polygon arrangement 24.

In one exemplary embodiment, a Gaussian beam 30 can be utilized with a broad optical spectrum incident to the grating from the fiber collimator 12. The well-known grating equation is expressed as $\lambda = p \cdot (\sin \alpha + \sin \beta)$ where λ is the optical wavelength, p is the grating pitch, and α and β are the incident and diffracted angles of the beam with respect to the normal axis 42 of the grating, respectively. The center wavelength of tuning range of the filter may be defined by $\lambda_0 = p \cdot (\sin \alpha + \sin \beta_0)$ where β_0 is the angle between the optic axis 38 of the telescope and the grating normal axis. FWHM bandwidth of the filter is defined by $(\delta\lambda)_{FWHM}/\lambda_0 = A \cdot (p/m) \cos \alpha / W$, where $A = \sqrt{4 \ln 2} / \pi$ for double pass, m is the diffraction order, and W is $1/e^2$ -width of the Gaussian beam at the fiber collimator.

Tuning range of the filter may be limited by the finite numerical aperture of the first lens 20. The acceptance angle of the first lens 20 without beam clipping may be defined by $\Delta\beta = (D_1 - W \cos \beta_0 / \cos \alpha) / F_1$, where D_1 and F_1 are the diameter and focal length of the first lens 20. Such formulation relates to the filter tuning range via $\Delta\lambda = p \cos \beta_0 \cdot \Delta\beta$. One of exemplary design parameters of the filter, originated from the multiple facet nature of the polygon mirror, is the free spectral range, which is described in the following. A spectral component after propagating through the first lens 20 and the second lens 22 may have a beam propagation axis at an angle β' with respect to the optic axis 38, e.g., $\beta' = -(\beta - \beta_0) \cdot (F_1 / F_2)$, where F_1 and F_2 are the focal lengths of the first lens 20 and the second lens 22, respectively. The polygon arrangement 24 may have a facet-to-facet polar angle given by $\theta = 2\pi / N \approx L / R$, where L is the facet width, R is the radius of the polygon and N is the number of facets. If the range of β' of incident spectrum is greater than the facet angle, i.e. $\Delta\beta' = \Delta\beta \cdot (F_1 / F_2) > \theta$, the polygon arrangement 24 can retro-reflect more than one spectral component at a given time. The spacing of the multiple spectral components simultaneously reflected, or the free spectral range, can be defined as $(\Delta\lambda)_{FSR} = p \cos \beta_0 (F_1 / F_2) \cdot \theta$. In an exemplary intra-cavity scanning filter application, the free spectral range of the filter should exceed the spectral range of the gain medium in order to avoid multiple frequency bands (in the case of an inhomogeneously broadened gain medium) or limited tuning range (in the case of a homogeneously broadened gain medium).

The duty cycle of laser tuning by the filter can be, for example, 100% with no excess loss caused by beam clipping if two preferable conditions are met as follows:

$$W < \frac{\cos \alpha F_1}{\cos \beta F_2} L \quad \text{and} \quad W < \frac{\cos \alpha}{\cos \beta_0} (F_2 - S) \cdot \theta$$

The first equation may be derived from a condition that the beam width after the second lens **22** should be smaller than the facet width. The second equation can be derived from that the two beams at the lowest **32** and highest wavelengths **34** of the tuning range, respectively, which should not overlap each other at the polygon arrangement **24**. S in equation (1) denotes the distance between the second lens **22** and the front mirror of the polygon arrangement **24**.

It is possible to select the optical components with the following parameters: $W=2.4$ mm, $p=1/1200$ mm, $\alpha=1.2$ rad, $\beta_0=0.71$ rad, $m=1$, $D_1=D_2=25$ mm, $F_1=100$ mm, $F_2=45$ mm, $N=24$, $R=25$ mm, $L=6.54$, $S=5$ mm, $\theta=0.26$ rad, $\lambda_0=1320$ nm. From the parameters, the theoretical FWHM bandwidth, tuning range and free spectral range of the filter could be calculated: $(\Delta\lambda)_{FWHM}=0.09$ nm, $\Delta\lambda=126$ nm and $(\Delta\lambda)_{FSR}=74$ nm. Both conditions in equation (1) may be satisfied with particular margins.

FIG. **1C** shows a diagram of a third exemplary embodiment of the wavelength tunable filter arrangement for doubling the tuning speed with the same polygon rotation speed according to the present invention. In this exemplary embodiment, the mirror surface of the polygon arrangement **24** is placed substantially a distance F_2 from lens **22**, and the beam of light is reflected with a non-zero angle (rather than directly being reflected back to the telescope from the polygon arrangement's **24** mirror facet). The sweep angle of the reflected light from the polygon arrangement **24** is double the polygon arrangement's **24** rotation angle. When the incident angle difference **90** between λ_1 and λ_N with respect to the polygon arrangement **24** is approximately the same as the facet-to-facet angle **92** of the polygon, e.g., angle θ , the sweep angle **94** of the reflected light is 2θ for a rotation of the angle θ of the polygon arrangement **24**. By placing two reflectors **100**, **102**, which preferably direct the reflected beam of light from the polygon arrangement **24** back to the polygon arrangement **24**, and to the telescope (e.g., similar to the telescope **6'** of FIG. **1B**), with the angle θ between each other, twice wavelength scans from λ_1 to λ_N are achieved for the polygon rotation of the one facet-to-facet angle θ .

In FIG. **1D** which shows a fourth exemplary embodiment of the present invention, the incident angle **90** difference between λ_1 and λ_N to the polygon arrangement **24** is smaller than polygon facet-to facet angle **92**, e.g., ϕ ($=\theta/K$, where $K>1$). This can be achieved by reducing the grating pitch and increasing the F_2/F_1 ratio. In this exemplary embodiment, the filter tuning speed may be increased by factor of $2K$ without increasing either the rotation speed of the polygon arrangement **24** or the number of facets of the polygon arrangement **24**.

The filter tuning speed can be further increased by having the beam of light reflected multiple times by the polygon arrangement **24**. A fifth exemplary embodiment of the present invention, depicted in FIG. **1E**, is an arrangement for increasing the tuning speed by factor of $4K$, where K is the ratio of angle **92** to angle **90** ($K=\theta/\phi$). The beam of light is reflected twice (e.g., four times round trip) by the polygon arrangement **24**, so that the sweep angle **94** of the reflected light becomes angle 4θ , and the tuning speed becomes $4K$ times faster. Such reflection can also be assisted with the reflection of surfaces **100**, **102**, **104**, **106** and **108**. This exemplary embodiment of the filter arrangement can be used to broaden the free spectral range ("FSR") of the filter. For example, if one of the final reflectors **102** in the embodiment shown in FIG. **1E** is removed, the FSR of the filter may become twice broader. It is likely that there is no tuning

speed enhancement in such case. Similarly, it is possible to retain only one final reflector **100** in FIG. **1E**. The FSR in this embodiment can become four times broader.

FIG. **1F** shows a sixth exemplary embodiment of the present invention which provides a polygon tuning filter accommodating two light inputs and outputs. For example, in order to support two or more inputs and outputs of this filter, two or more sets of optical arrangements, each respective set including an input/output fiber **10**, **10'**, a collimating lens **12**, **12'**, a diffraction grating **16**, **16'**, and a telescope, may share the same polygon arrangement **24**. Because the scanning mirror of the polygon arrangement **24** is structurally isotropic about the rotation axis, certain optical arrangements that can deliver the beams of light to the polygon arrangement **24** can be accommodated from any directions. Since both sets of optical arrangement in the embodiment of FIG. **1F** utilize the same polygon scanner, their respective scanning optical transmission spectra are synchronized. It should be understood that the exemplary embodiment of FIG. **1F** can be extended to include multiple (greater than 2) optical arrangements each having its own input and output optical channel.

One exemplary application of the above-described polygon tuning filter according to the sixth embodiment of the present invention may be a wide band wavelength scanning light source. In FIG. **1G** which shows a seventh exemplary embodiment of the present invention, a first broadband light source **60** provides a light signal which may have a wavelength λ_1 to λ_i , and a second broadband light source **600** provides another light signal having a wavelength λ_{i-j} to λ_N . When the two optical arrangements supporting the wavelengths λ_1 to λ_i and the wavelengths λ_{i-j} to λ_N , respectively, are synchronized to output approximately the same wavelength at the same instance, such exemplary arrangement may become a wide band wavelength scanning light source with linear scan rate from λ_1 to λ_N . Since the FSR of the polygon scanning filter can be adjusted to be 200 nm or wider without any optical performance degradation, two or more broadband light sources with different center wavelengths can be combined with this filter to provide linear scanning light source over 200 nm tuning bandwidth. It should be understood that the embodiment of FIG. **1G** can be extended to include multiple (e.g., greater than 2) optical arrangements and multiple (e.g., greater than 2) broadband light sources.

The exemplary embodiment illustrated in FIG. **1G** can also be configured so that the wavelength tuning bands of each optical arrangement and broadband light source are discontinuous. In such a configuration, the tuning bands can be swept in a continuous or discontinuous sequential manner or be swept simultaneously.

FIG. **2** shows an exemplary graph of measured characteristics of the filter according to an exemplary embodiment of the present invention. The normalized reflection spectrum of the filter, e.g., a curve **48**, may be measured by using broadband amplifier spontaneous emission light from a semiconductor optical amplifier (SOA) and an optical spectrum analyzer. The optical spectrum analyzer can obtain or record a normalized throughput (reflected) spectrum in peak-hold mode while the polygon arrangement **24** spins at its maximum speed of 15.7 kHz. The measured tuning range may be 90 nm which is substantially smaller than the theoretical value of 126 nm. It is possible to have a discrepancy which may be due to an aberration of the telescope **6'**, primarily field curvature, associated with relatively large angular divergence of the beam from the grating. Such aberration can be corrected using optimized lens designs

well known in the art. A curve **46** shown in FIG. **2** illustrates the throughput spectrum when the polygon arrangement is static at a particular position. The observed free spectral range is 73.5 nm, in agreement with a theoretical calculation. The FWHM bandwidth of curve **46** was measured to be 0.12 nm. The discrepancy between the measured FWHM and the theoretical limit of 0.09 nm is reasonable considering the aberration and imperfection of the optical elements.

FIG. **3** shows an exemplary embodiment of the wavelength tuning laser source according to the present invention. For example, the polygon-based filter can be incorporated into an extended-cavity semiconductor laser via a Faraday circulator **50**. Intra-cavity elements may be connected by single-mode optical fibers **10**. The gain medium may be a semiconductor optical amplifier **52** (e.g., SOA, Philips, CQF 882/e). Laser output **72** may be obtained via the 90% port of a fiber-optic fused coupler **70**. Two polarization controllers **64**, **62** can be used to align the polarization states of the intra-cavity light to the axes of maximum efficiency of the grating **16**, and of the maximum gain of the SOA **50**. A current source **54** may provide an injection current to the SOA **50**. The polygon arrangement **24** may be driven and controlled by a motor driver **97**. To generate a sync signal useful for potential applications, approximately 5% of the laser output may be directed to a photodetector **82** through a variable wavelength filter **80** with bandwidth of 0.12 nm. In this exemplary implementation, the center wavelength of the filter was fixed at 1290 nm. The detector signal can generate short pulses when the output wavelength of the laser is swept through the narrow passband of the fixed-wavelength filter. The timing of the sync pulse may be controlled by changing the center wavelength of the filter.

FIG. **4A** shows a graph of exemplary first output characteristics (laser spectrum vs. wavelength) of the laser source according to the present invention, and FIG. **4B** is a graph of exemplary second output characteristics (output power vs. time) of the laser source according to the present invention. Turning to FIG. **4A**, curve **110** represents the output spectrum of the laser measured by the optical spectrum analyzer in peak-hold mode, e.g., when the polygon arrangement spins at 15.7 kHz. The edge-to-edge sweep range was observed to be from 1282 nm to 1355 nm, equal to the free-spectral range of the filter. The Gaussian-like profile of the measured spectrum, rather than a square profile, can be mainly due to the polarization-dependent cavity loss caused by polarization sensitivity of the filter and the birefringence in the cavity. It may be preferable to adjust the polarization controllers to obtain the maximum sweep range and output power. In FIG. **4B**, curve **114** is the output of the exemplary laser in the time domain. The upper trace **112** is the sync signal which may be obtained through the fixed-wavelength filter. The amplitude of power variation from facet to facet was less than 3.5%. The peak and average output power was 9 mW and 6 mW, respectively. The y-axis scale of the curve **110** of FIG. **4A** can be calibrated from the time-domain measurement, because the optical spectrum analyzer records a time-averaged spectrum due to the laser tuning speed being much faster than the sweep speed of the spectrum analyzer.

A frequency downshift in the optical spectrum of the intra-cavity laser light may arise as the light passes through the SOA gain medium, as a result of an intraband four-wave mixing phenomenon. In the presence of the frequency downshift, greater output power can be generated by operating the wavelength scanning filter in the positive wavelength sweep direction. FIG. **5** shows an exemplary illustration of a normalized peak power of the laser output

measured as a function of the tuning speed. The negative tuning speed can be obtained by flipping the position of the collimator and the orientation of the grating with respect to the optic axis **38** of the exemplary embodiment of the arrangement according to the present invention. It is preferable to make the physical parameters of the filter identical in both tuning directions. The result shows that the combined action of self-frequency shift and positive tuning allows higher output to be obtained and enables the laser to be operated at higher tuning speed as is demonstrated in the curve **120**. Therefore, the positive wavelength scan may be the preferable operation. The output power can be decreased with an increasing tuning speed. A short cavity length may be desired to reduce the sensitivity of the output power to the tuning speed. In such case, a free-space laser cavity may be preferred.

An exemplary embodiment of a free-space extended-cavity semiconductor tunable laser arrangement according to the present invention is depicted in FIG. **6**. A semiconductor waveguide **162** made on a substrate chip **160** can be coupled to the polygon scanning filter via a collimating lens **180**. The front facet **164** thereof may be anti-reflection coated, and the output facet **166** may be cleaved or preferably coated with dielectrics to have an optimal reflectivity. The laser output **190** may be obtained through the output coupling lens **182**. The sync output may be taken by using a lens **140**, a pinhole **142**, and a photodetector **144** positioned on the 0-th order diffraction path for the light which is on retro-reflection from the polygon scanner **24**. The photodetector **144** can generate a short pulse when the focus of the optical beam of a particular wavelength sweeps through the pinhole **142**. Other types of gain medium include but are not limited to rare-earth-ion doped fiber, Ti:Al₂O₃, and Cr³⁺:forsterite. The first and second lenses **20**, **22** can be preferably achromats with low aberration particularly in field curvature and coma. The collimating lenses **180**, **182** are preferably aspheric lenses.

FIG. **7** shows another exemplary embodiment of the wavelength tunable filter which includes an input collimating lens **12**, diffraction grating **16**, focusing lens **200**, and a spinning disk **210**, as shown in FIG. **7**. The diffraction grating **16** preferably has a concave curvature that has a focal length and may thus eliminate the need for the use of the focusing lens **200**. The diffraction grating may be replaced by other angular dispersive elements such as a prism. Preferably more than one reflector **212** can be deposited on the surface of the spinning disk **210**. Preferably, the reflectors **212** may include multiple narrow stripes periodically and radially patterned. The material for the reflectors is preferably gold. The disk **210** can be made of a lightweight plastic or silicon substrate. Instead of the reflectors deposited on the top surface of the disk, the disk can have a series of through holes followed by a single reflector attached to the back surface of the disk or supported independently from the disk. Incident from the optical fiber **10**, the optical beams of different wavelengths are illuminated on the surface of the disk into a line after being diffracted by the grating **16** and focused by the lens **200**. The beam that hits the reflectors of the spinning disk may be retro-reflected and received by the optical fiber **10**. For example, a mirror **202** may be used to facilitate the access of the beam onto the disk.

The distance from the lens **200** to the reflectors of the disk **210** may be approximately equal to the focal length, F , of the lens **200**. The tuning range of the filter may be given by $\Delta\lambda = p \cos \beta_0 (D/F)$, where D denotes the distance between

the stripes. The width of the strip, w , can preferably be substantially equal to the beam spot size, w_s , at the surface of the disk:

$$w_s = W \frac{\cos\beta_0}{\cos\alpha} \cdot \frac{F/z}{\sqrt{1+f/z^2}},$$

where $z = \pi w_s^2 / 2$. Such formulation may lead to a FWHM filter bandwidth given by $(\delta\lambda)_{FWHM} / \lambda_0 = A \cdot (p/m) \cos\alpha / W$ where $A = \sqrt{4 \ln 2} / \pi$. For $w > w_s$, the filter bandwidth may become greater, and for $w < w_s$, the efficiency (reflectivity) of the filter can be decreased by beam clipping. The orientation of the incident beam **30** with respect to the optic axis of the lens **200** and the spinning direction **220** may determine the sense of wavelength tuning. The positive wavelength scan may be preferable, which is the case of the exemplary embodiment shown in FIG. 7.

Two exemplary applications of the exemplary embodiments of the present invention are described as follows. FIG. 8 shows a block diagram of an exemplary embodiment of the spectrally encoded confocal microscope ("SECM") that uses the aforementioned tunable laser source **300**. The basic principle of SECM has been described in detail in U.S. Pat. No. 6,341,036, the disclosure of which is incorporated herein by reference in its entirety. An exemplary probe **310** includes a transmission grating **312** provided between two silicon prisms **314**, **316**, a collimator **318**, and a microscope objective lens **320**. The probe is equipped with a micro actuator **322** to scan the beam onto a different location of the sample **330**. The actuator **322** may be driven by an actuator driver **324** at substantially slower speed than the tuning speed of the laser source. The probe motion is preferably rotary or translational and is synchronized to the sync output of the laser source. In one example, the wavelength sweep frequency may be 15.7 kHz, and the probe scan frequency can be 30 Hz, which allows 30 frames of image to be obtained in 1 second. The objective lens **320** has a high numerical aperture to provide a transverse resolution of an order of micrometers and a confocal parameter of a few micrometers. The focus of the optical beam may be continuously scanned in time over the sample **330** by the swept output wavelength of the optical source and the scanning motion of the probe. The optical power returned from the sample is proportional to the reflectivity of the sample within a small section where the beam was focused down to a narrow waist at a given time. Two dimensional en-face image of the sample is constructed by a signal processor **344**. The detector **340** is preferably an avalanche photodiode ("APD") followed by a transimpedance amplifier **342**. The reflected power may be received through a Faraday circulator **350** or a fiber-optic coupler.

Another exemplary application of the exemplary embodiments of the present invention is for optical coherence tomography ("OCT") the details of which are described in U.S. Pat. No. 5,956,355, the disclosure of which is incorporated herein by reference in its entirety. In one exemplary configuration, depicted in FIG. 9, an output of a tunable source **300** may be directed to a sample **330** through a fiber-optic coupler **410**. An objective lens **412** in the probe may typically provide a focus near the surface or within the sample **330**. The reference mirror **420** can be placed in a reference arm **120** at a position where an optical path length between two arms of the Michelson interferometer is substantially matched. Alternatively, the reference path can be

configured in a transmissive, non-reflective configuration. The detector **430** may be a PIN photodiode followed by a transimpedance amplifier **432** with finite frequency bandwidth. The detector may preferably incorporate polarization diverse and dual balanced detection. The detector signal can be processed in the processor **434** through a fast Fourier transform to construct the depth image of the sample. The probe may be scanned by an actuator **414** and an actuator driver **416** to allow a 3-dimensional image of the sample to be obtained.

FIGS. 10A and 10B show a top and perspective view of another exemplary embodiment of the wavelength tunable filter according to the present invention. An angularly deflecting optical element **700** of this exemplary embodiment can be a rotating polygon arrangement **24** where the facets of the polygon are on the inner diameter of a hollow cylinder. A dispersing element **702** such as a diffraction grating can be placed at the center of the polygon arrangement **24**. Light can be delivered to the grating through an optical fiber and collimated onto the grating so that each frequency component of the light is diffracted through a different angle (Θ). Only one narrow range of frequencies may be substantially orthogonal to one facet of the polygon arrangement **24**, and therefore such frequency range may be reflected back to the diffraction grating and collected by the optical fiber **704/706**. When the cylinder rotates, a surface normal direction for the illuminated polygon arrangement's facet may align with a new narrow frequency range. By rotating the cylinder, frequency tuning can thereby be achieved. When the cylinder rotation angle becomes large, an adjacent facet of the polygon arrangement **24** can become aligned with the light diffracted from the grating and the filter will repeat another frequency tuning cycle. The free spectral range and finesse can be controlled by appropriate choice of the polygon diameter, number of facets, collimated beam diameter and diffraction grating groove density.

The foregoing merely illustrates the principles of the invention. Various modifications and alterations to the described embodiments will be apparent to those skilled in the art in view of the teachings herein. For example, the invention described herein is usable with the exemplary methods, systems and apparatus described in U.S. Patent Application No. 60/514,769. It will thus be appreciated that those skilled in the art will be able to devise numerous systems, arrangements and methods which, although not explicitly shown or described herein, embody the principles of the invention and are thus within the spirit and scope of the present invention.

What is claimed is:

1. An apparatus comprising:

[an arrangement] a light source configured to emit an electromagnetic radiation [that has], the light source including a cavity, a filter, and a gain medium which cause a spectrum [whose] of the electromagnetic radiation to have a mean frequency that changes (i) at an absolute rate that is greater than about 100 terahertz per millisecond, and (ii) over a range that is greater than about 10 terahertz.

2. The apparatus according to claim 1, wherein the mean frequency changes repeatedly at a repetition rate that is greater than 5 kilohertz.

3. The apparatus according to claim 2, wherein the spectrum has a tuning range whose center is approximately centered at 1300 nm.

4. The apparatus according to claim 2, wherein the spectrum has a tuning range whose center is approximately centered at 850 nm.

15

5. The apparatus according to claim 2, wherein the spectrum has a tuning range whose center is approximately centered at 1700 nm.

6. The apparatus according to claim 2, wherein the spectrum has an instantaneous line width that is smaller than 100 gigahertz.

7. The apparatus according to claim 1, *the filter* further comprising a polygon arrangement which is adapted to receive at least one signal that is associated with the emitted electromagnetic radiation, and at least one of reflect and deflect the at least one signal to a further location.

8. The apparatus according to claim 1, *the light source* further comprising a laser resonating system forming an optical circuit and configured to control a spatial mode of the electromagnetic radiation.

9. The apparatus according to claim 8, wherein the [arrangement] *light source* causes the electromagnetic radiation to propagate substantially unidirectionally within at least one portion of the *laser resonating [arrangement] system*.

10. The apparatus according to claim 9, further comprising an optical circulator which is configured to control a direction of propagation of the electromagnetic radiation within the *laser resonating [arrangement] system*.

11. The apparatus according to claim 8, [further comprising an optical filtering system] *the filter* being configured to at least one of transmit or reflect at least one portion of the electromagnetic radiation based on a frequency of the electromagnetic radiation, and wherein the at least one portion has a full-width-at-half-maximum frequency distribution which is less than about 100 GHz.

12. *The apparatus of claim 1, wherein the filter comprises a movable mirror.*

13. *An apparatus comprising:*

a light source arrangement configured to emit an electromagnetic radiation, the light source arrangement including a cavity and a gain medium; and

a filter integrated with the light source arrangement, wherein the light source arrangement and the filter in combination produce an output that has a spectrum whose mean frequency changes (i) at an absolute rate that is greater than about 100 terahertz per millisecond, and (ii) over a range that is greater than about 10 terahertz.

14. *The apparatus according to claim 13, the filter further comprising a polygon arrangement which is adapted to receive at least one signal that is associated with the emitted electromagnetic radiation, and at least one of reflect and deflect the at least one signal to a further location.*

15. *The apparatus according to claim 13, the light source further comprising a laser resonating system forming an optical circuit and configured to control a spatial mode of the electromagnetic radiation.*

16. *The apparatus according to claim 13, wherein the mean frequency changes repeatedly at a repetition rate that is greater than 5 kilohertz.*

17. *An apparatus comprising:*

a light source arrangement configured to emit an electromagnetic radiation, the light source arrangement including a cavity and a gain medium; and

a filter combined with the light source arrangement, wherein the combination of the light source arrangement and the filter produce an output that has a spectrum whose mean frequency changes (i) at an absolute rate that is greater than about 100 terahertz per millisecond, and (ii) over a range that is greater than about 10 terahertz.

16

18. *The apparatus according to claim 17, the filter further comprising a polygon arrangement which is adapted to receive at least one signal that is associated with the emitted electromagnetic radiation, and at least one of reflect and deflect the at least one signal to a further location.*

19. *The apparatus according to claim 17, the light source further comprising a laser resonating system forming an optical circuit and configured to control a spatial mode of the electromagnetic radiation.*

20. *The apparatus according to claim 17, wherein the mean frequency changes repeatedly at a repetition rate that is greater than 5 kilohertz.*

21. *An apparatus comprising:*

a light source arrangement configured to emit an electromagnetic radiation; and

a filter coupled to the light source arrangement, wherein the light source arrangement and the filter in combination produce an output that has a spectrum whose mean frequency changes (i) at an absolute rate that is greater than about 100 terahertz per millisecond, and (ii) over a range that is greater than about 10 terahertz.

22. *The apparatus according to claim 21, the filter further comprising a polygon arrangement which is adapted to receive at least one signal that is associated with the emitted electromagnetic radiation, and at least one of reflect and deflect the at least one signal to a further location.*

23. *The apparatus according to claim 21, the light source further comprising a laser resonating system forming an optical circuit and configured to control a spatial mode of the electromagnetic radiation.*

24. *The apparatus according to claim 21, wherein the mean frequency changes repeatedly at a repetition rate that is greater than 5 kilohertz.*

25. *An apparatus comprising:*

a light source configured to emit an electromagnetic radiation, the light source including a cavity, a filter including a movable reflector, and a gain medium which cause a spectrum of the electromagnetic radiation to have a mean frequency that changes (i) at an absolute rate that is greater than about 100 terahertz per millisecond, and (ii) over a range that is greater than about 10 terahertz.

26. *The apparatus according to claim 25, wherein the movable reflector comprises a movable mirror.*

27. *The apparatus according to claim 26, wherein the filter is tuned by varying a resonator length using the movable mirror.*

28. *The apparatus according to claim 25, the light source further comprising a laser resonating system forming an optical circuit and configured to control a spatial mode of the electromagnetic radiation.*

29. *The apparatus according to claim 28, wherein the light source causes the electromagnetic radiation to propagate substantially unidirectionally within at least one portion of the laser resonating system.*

30. *The apparatus according to claim 29, further comprising an optical circulator which is configured to control a direction of propagation of the electromagnetic radiation within the laser resonating system.*

31. *The apparatus according to claim 28, the filter being configured to at least one of transmit or reflect at least one portion of the electromagnetic radiation based on a frequency of the electromagnetic radiation, and wherein the at*

least one portion has a full-width-at-half-maximum frequency distribution which is less than about 100 GHz.

* * * * *