



US00RE47725E

(19) **United States**
(12) **Reissued Patent**
Li et al.

(10) **Patent Number:** **US RE47,725 E**
(45) **Date of Reissued Patent:** ***Nov. 12, 2019**

(54) **DISPLAY APPARATUS AND LIQUID CRYSTAL DISPLAY DEVICE**

(58) **Field of Classification Search**
CPC G02F 1/133504; G02F 1/133528; G02F 2201/305; G02B 5/18; G02B 5/1819
(Continued)

(71) Applicant: **CHENG MEI MATERIALS TECHNOLOGY CORPORATION**, Tainan (TW)

(56) **References Cited**

(72) Inventors: **Wang-Yang Li**, Tainan (TW); **Ting-I Wu**, Kaohsiung (TW)

U.S. PATENT DOCUMENTS

(73) Assignee: **CHENG MEI MATERIALS TECHNOLOGY CORPORATION**, Tainan (TW)

5,945,967 A 8/1999 Rallison et al.
5,990,997 A * 11/1999 Jones G02F 1/133632 349/118

(Continued)

(*) Notice: This patent is subject to a terminal disclaimer.

CN 101772726 A 7/2010
EP 0 567 995 11/1993

(Continued)

(21) Appl. No.: **15/248,018**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Aug. 26, 2016**

EP Office Action dated Mar. 6, 2017 in EP application (No. 12162388.8-1914).

(Continued)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,817,208**
Issued: **Aug. 26, 2014**
Appl. No.: **13/433,703**
Filed: **Mar. 29, 2012**

Primary Examiner — Norca L. Torres Velazquez
(74) *Attorney, Agent, or Firm* — McClure, Qualey & Rodack, LLP

(30) **Foreign Application Priority Data**

Mar. 31, 2011 (TW) 100111497
Mar. 12, 2012 (TW) 101108364


(57) **ABSTRACT**

(51) **Int. Cl.**
G02F 1/1335 (2006.01)
G02B 5/18 (2006.01)
G02B 5/02 (2006.01)

A display apparatus and a liquid crystal display device are provided. The display apparatus comprises a display device for displaying an image and a diffractive optical element. The diffractive optical element comprises pixel unit regions. Each of the pixel unit regions has a long pixel side and a short pixel side adjacent to each other. The diffractive optical element is disposed on a light emitting side of the display device and comprises first grating regions and second grating regions. The first grating regions have a first diffraction grating. The second grating regions have a second diffraction grating. An azimuth angle of the first diffraction grating is different from an azimuth angle of the second diffraction grating.

(52) **U.S. Cl.**
CPC **G02F 1/133504** (2013.01); **G02B 5/1819** (2013.01); **G02B 5/1823** (2013.01);
(Continued)

65 Claims, 35 Drawing Sheets



US RE47,725 E

(52) **U.S. Cl.**
 CPC *G02B 5/0252* (2013.01); *G02B 5/0263*
 (2013.01); *G02F 2001/133562* (2013.01);
G02F 2201/305 (2013.01)

(58) **Field of Classification Search**
 USPC 349/57, 112, 201
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,067,137	A	5/2000	Ohnishi et al.	
6,483,612	B2	11/2002	Walker	
8,269,932	B2	9/2012	Fu et al.	
8,405,804	B2	3/2013	Watanabe et al.	
9,036,117	B2	5/2015	Li et al.	
2003/0098933	A1*	5/2003	Suzuki et al.	349/30
2007/0058151	A1*	3/2007	Eurlings <i>G02B 5/1819</i>	
				355/71
2009/0027606	A1*	1/2009	Nakanishi <i>G02B 5/1819</i>	349/143
2009/0046367	A1*	2/2009	Kim et al. <i>G02F 1/133553</i>	
				359/566
2009/0116125	A1*	5/2009	Kolesnychenko et al. ...	359/735
2009/0195742	A1*	8/2009	Fu et al.	349/128
2009/0213311	A1*	8/2009	Hisakado et al.	349/117
2010/0085642	A1*	4/2010	Drinkwater <i>G02B 5/1819</i>	359/567
2010/0134733	A1	6/2010	Watanabe et al.	
2010/0219412	A1*	9/2010	Lee <i>G02B 5/1819</i>	257/59
2010/0309098	A1*	12/2010	Kurashima et al.	345/32
2012/0033153	A1	2/2012	Wu et al.	

FOREIGN PATENT DOCUMENTS

EP	0760490	A2	3/1997
JP	H09152602	A	6/1997
JP	2000089216		3/2000

JP	2000266914	A	9/2000
JP	2005-070632		3/2005
JP	2006091702		4/2006
JP	2006091702		9/2006
KR	1020090017885		2/2009
KR	1020100017962	A	2/2010
TW	201239475	A1	10/2012
WO	WO 96/22590		7/1996
WO	0206858	A2	1/2002
WO	WO 02/06858		1/2002

OTHER PUBLICATIONS

KIPO Office Action dated Jul. 19, 2017 in Korean application (No. 10-2012-0033284).
 KIPO Office Action dated Jul. 19, 2017 in Korean application (No. 10-2012-0033782).
 Office Action dated Sep. 4, 2014, issued in U.S. Appl. No. 13/435,323, dated Sep. 4, 2014.
 European Search Report dated Jan. 27, 2015, issued in application No. EP 12 162 231.0.
 Chinese language Office Action dated Jun. 3, 2015, issued in application No. TW 102114268.
 Chinese Office Action dated Aug. 11, 2015, issued in application No. CN 201210089934.8.
 Japanese language office action dated Oct. 6, 2015, issued in application No. JP 2012-078485 (with translation).
 Japanese language office action dated May 31, 2016, issued in application No. JP 2012-078485 (with translation).
 CN Office Action dated Apr. 11, 2019 in Chinese application (No. 201710011325.3).
 European Search Report dated Aug. 13, 2012.
 English language translation of abstract of JP 2005-070632 (published Mar. 17, 2005).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 53




FIG. 52




FIG. 55




FIG. 54




FIG. 57




FIG. 56




FIG. 59




FIG. 58




FIG. 60

DISPLAY APPARATUS AND LIQUID CRYSTAL DISPLAY DEVICE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

This application claims the benefits of Taiwan application Serial No. 100111497, filed Mar. 31, 2011, and 101108364, filed Mar. 12, 2012, the subject matters of which are incorporated herein by reference

BACKGROUND

1. Technical Field

The disclosure relates in general to a display apparatus and more particularly to a display apparatus having a diffractive optical element.

2. Description of the Related Art

Currently, an image display device mainly comprises a liquid crystal display device, a plasma display device, an OLED display device and an electronic paper display device, etc. The liquid crystal display device is a non-self-luminous display device, and thus usually needs a backlight source for generating light that entering the liquid crystal display panel with a uniform plane profile through an optical film such as a diffusion film, a brightener film, etc, for displaying an image.

J.P. patent application number 2003-302954, entitled "SPATIAL OPTICAL MODULATOR, AND PROJECTOR", has disclosed a projector having a projection image of high contrast, at low cost and with a simple construction. An spatial optical modulator having a pair of counter substrate and a TFT substrate and a liquid crystal interposed between the counter substrate and the TFT substrate and modulating incident light from the counter substrate side according to an image signal to emit the modulated light from the TFT substrate side has a wedge prism deflecting incident light to the light emission side of the TFT substrate.

EP. patent publication number 0567995A1, entitled "Image display apparatus", has disclosed an image display apparatus includes an image display device such as, a liquid crystal display panel having a plurality of dot-shaped picture elements arranged in a two-dimensional pattern, and a diffraction grating disposed on an optical path through which imagewise rays of light emerging front the device travel.

U.S. Pat. No. 6,483,612, entitled "Projection screen apparatus including holographic optical element", has disclosed a screen apparatus includes a holographic optical element and a diffuser. In operation, the holographic optical element receives image light from an image engine or projector and redirects the image light to the diffuser for scattering. The holographic optical element can be designed to substantially collimate, converge, or diverge the image light.

A twisted nematic (TN) or a super twisted nematic (STN) liquid crystal display device are types of the display devices usually used. Although this kind of the liquid crystal display device has advantage in price, the viewing angle of which is smaller than that of a ordinary wide viewing angle liquid crystal display device, such as a multi-domain vertical alignment (MVA) liquid crystal display device, an in-plane

switching (IPS) liquid crystal display device, a fringe field switching (FFS) liquid crystal display device, etc.

The viewing angle means an angle range in which the display device can display an image quality of which is in a standard range. For example, for a general desktop liquid crystal display device, the main viewing angle is a front view. Therefore, for designers, the display device is designed according to the front view mainly since the optical effect would be affect due to the arrangement of the liquid crystal molecule. Therefore, an observer would find images of different colors and brightness with different oblique s to the liquid crystal display device. At the same time, the image difference increases as the viewing angle increases. Among the liquid crystal display devices usually used, the TN liquid crystal display device has the worst condition. For a TN liquid crystal display device without using any compensating element for viewing angle, usually, an image observed from the side viewing angle of the liquid crystal display device has problems such as serious contrast decreasing (to lower than 10), gray level reversion degrees, etc.

Therefore, a display apparatus for improving image quality problems such as contrast, gray level reversion, etc is need.

SUMMARY

A display apparatus is provided. The display apparatus comprises a liquid crystal display, a first polarizer, a second polarizer and a diffractive optical element. The liquid crystal display device comprises a backlight module and a liquid crystal panel. The liquid crystal panel comprises a first substrate, a second substrate and a liquid crystal layer. The liquid crystal layer is disposed between the first substrate and the second substrate. The first polarizer is disposed on the first substrate. The second polarizer is disposed between the second substrate and the backlight module. Polarizing directions of the first polarizer and the second polarizer have different azimuth angles. The diffractive optical element is disposed on a light emitting side of the first polarizer and has a first diffraction grating and a second diffraction grating. Grating directions of the first diffraction grating and the second diffraction grating have different azimuth angles.

A display apparatus is provided. The display apparatus comprises a liquid crystal display device for displaying an image and a diffractive optical element. The liquid crystal display device comprises a backlight module and a liquid crystal panel. The liquid crystal panel is disposed on the backlight module and comprises a first substrate, a first alignment film, a second substrate, a second alignment film, and a liquid crystal layer. The first alignment film is disposed on the first substrate. The second alignment film is disposed on the second substrate. Aligning directions of the first alignment film and the second alignment film have different azimuth angles. The liquid crystal layer is disposed between the first alignment film and the second alignment film. The diffractive optical element is disposed on a light emitting side of the liquid crystal display device and comprises a first diffraction grating and a second diffraction grating. An azimuth angle of a grating direction of the first diffraction grating is different from an azimuth angle of a grating direction of the second diffraction grating.

A liquid crystal display device for displaying an image is provided. The liquid crystal display device comprises a liquid crystal panel and a diffractive optical element. The liquid crystal panel comprises a first substrate, a second substrate and a liquid crystal layer. The liquid crystal layer is disposed between the first substrate and the second

substrate. The liquid crystal layer comprises liquid crystal molecules. At least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction. At least one of the liquid crystal molecules adjacent to the second substrate has a second liquid crystal tilt direction. An azimuth angle of the first liquid crystal tilt direction is different from an azimuth angle of the second liquid crystal tilt direction. The diffractive optical element is disposed on a light emitting side of the liquid crystal panel and comprises a first diffraction grating and a second diffraction grating. An azimuth angle of a grating direction of the first diffraction grating is different from an azimuth angle of a grating direction of the second diffraction grating.

A display apparatus is provided. The display apparatus comprises a display device for displaying an image and a diffractive optical element. The diffractive optical element comprises pixel unit regions. Each of the pixel unit regions has a long pixel side and a short pixel side adjacent to each other. The diffractive optical element is disposed on a light emitting side of the display device and comprises first grating regions and second grating regions. The first grating regions have a first diffraction grating. The second grating regions have a second diffraction grating. An azimuth angle of the first diffraction grating is different from an azimuth angle of the second diffraction grating.

The above and other aspects of the disclosure will become better understood with regard to the following detailed description of the non-limiting embodiment(s). The following description is made with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a three dimensional diagram of the display apparatus according to one embodiment of the present invention.

FIGS. 2-11 and 20-32 illustrate the diffractive optical elements in embodiments.

FIGS. 12-19 illustrate the grating regions of the diffractive optical elements in embodiments.

FIG. 33 illustrates a cross-section view of the display apparatus in one embodiment.

FIG. 34 illustrates a three dimensional diagram of the alignment film and the liquid crystal layer of the display device.

FIG. 35 illustrates the liquid crystal tilt azimuth angle of the liquid crystal molecule of the liquid crystal layer.

FIGS. 36-41 illustrate relations between the diffractive optical element and the polarizing direction of the polarizer.

FIG. 42 illustrates the influence of the diffractive optical element having the diffraction gratings of two kinds of the azimuth angles to the contrast.

FIG. 43 illustrates gamma curves of the display apparatus without using the diffractive optical element (comparative example) from the front view (zenith angle of 0 degree) and the side viewing angles (zenith angles of 45 degrees and 60 degrees).

FIG. 44 illustrates gamma curves of the display apparatus with using the diffractive optical element from the front view (zenith angle of 0 degree) and the side viewing angles (zenith angles of 45 degrees and 60 degrees).

FIG. 45 illustrates the influence of the diffractive optical element having the diffraction gratings of three kinds of the azimuth angles to the contrast and the brightness white state.

FIG. 46 illustrates the influence of the diffractive optical element having the diffraction gratings of three kinds of the azimuth angles to the contrast and the brightness black state.

FIG. 47 illustrates gamma curves of the display apparatus without using the diffractive optical element (comparative example) from the front view (zenith angle of 0 degree) and the side viewing angles (zenith angles of 45 degrees and 60 degrees).

FIG. 48 illustrates gamma curves of the display apparatus with using the diffractive optical element from the front view (zenith angle of 0 degree) and the side viewing angles (zenith angles of 45 degrees and 60 degrees).

FIGS. 49-51 illustrate the relations between the diffractive optical element and the pixel of the display device.

FIGS. 52-59 illustrate the arrangements of the grating region and the pixel unit region.

FIG. 60 illustrates the relation curves between the contrast and the brightness in the white state of the display apparatus and the gap distance between the grating regions of the diffractive optical element.

DETAILED DESCRIPTION

FIG. 1 illustrates a three dimensional diagram of a display apparatus according to one embodiment of the present invention. FIGS. 2-11 and 20-32 illustrate diffractive optical elements in embodiments. FIGS. 12-19 illustrate grating regions of the diffractive optical elements in embodiments. FIG. 33 illustrates a cross-section view of the display apparatus in one embodiment. FIG. 34 illustrates a three dimensional diagram of an alignment film and a liquid crystal layer in the display device. FIG. 35 illustrates a liquid crystal tilt azimuth angle of a liquid crystal molecule of the liquid crystal layer. FIGS. 36-41 illustrate relations between the diffractive optical element and the polarizing direction of the polarizer. FIG. 42 shows a relation between a contrast of the display device and the diffractive optical element having the diffraction grating having two kinds of azimuth angles. FIG. 43 illustrates gamma curves of the display apparatus without using the diffractive optical element (comparative examples) from the front view (zenith angle: 0 degree) and the side viewing angle (zenith angle: 45 degrees and 60 degrees). FIG. 44 illustrates gamma curves of the display apparatus with using the diffractive optical element from the front view (zenith angle: 0 degree) and from the side viewing angle (zenith angle: 45 degrees and 60 degrees). FIG. 45 shows a relation among the diffractive optical element having diffraction gratings of three kinds of azimuth angles, the contrast and the brightness in the white state of the display device. FIG. 46 shows a relation among the diffractive optical element having the diffraction gratings of three kinds of the azimuth angles, the contrast and the brightness in the black state of the display device. FIG. 47 illustrates gamma curves of the display apparatus without using the diffractive optical element (comparative example) from the front view (zenith angle: 0 degree) and from the side viewing angle (zenith angle: 45 degrees and 60 degrees). FIG. 48 illustrates gamma curves of the display apparatus with using the diffractive optical element from the front view (zenith angle: 0 degree) and from the side viewing angle (zenith angle: 45 degrees and 60 degrees). FIGS. 49-51 illustrate relations between the diffractive optical element and the pixel of the display device. FIGS. 52-59 illustrate arrangements of the grating region and a pixel unit region. FIG. 60 illustrates a relation among the contrast, the brightness in the white state, and the gap distance between the grating regions of the diffractive optical element of the display apparatus.

Referring to FIG. 1, the diffractive optical element 2 is disposed on a light emitting side of the display device 10 for

displaying an image. The display device **10** may be a liquid crystal display device, a plasma display device, an OLED display device and an electronic paper display device, or other kinds of the display device for displaying an image. The display device **10** may be incorporated with other elements, such as a touch element for forming a touch panel. The diffractive optical element **2** may be used with other elements, such as an anti-reflection film or a touch panel, and disposed on a light emitting side of the display device **10** for displaying an image. The liquid crystal display device may be a vertical aligned/multi-domain vertical aligned liquid crystal display device, a twisted nematic (TN) liquid crystal display device, a super twisted nematic (STN) liquid crystal display device, or an optically compensated bend (OCB) liquid crystal display device or color sequential liquid crystal display (i.e. a liquid crystal display without color filter). The diffractive optical element **2** may be a film having a grating, such as a phase grating, for diffracting a light emitted from the display device **10**. An observation angle to the liquid crystal display device is presented by a zenith angle θ and an azimuth angle ψ in spherical coordinate. The azimuth angle ψ indicates an included angle on the X-Y plane from the X-axis. The zenith angle θ indicates an included angle from the Z-axis perpendicular to the X-Y plane. The positive included angle represents a counter-clockwise-direction included angle, and the negative included angle represents a clock-wise-direction included angle.

Referring to FIG. 2, in embodiments, the diffractive optical element **32** comprises the grating region **43** and the grating region **53** separated from each other. An “ordinary region (or non-grating region)” besides the grating region **43** and the grating region **53** of the diffractive optical element **32** is a region that generates a low-degree diffraction effect. In particular, the grating region **43** and the grating region **53** can generate a high-degree effect diffraction effect of a intensity ratio of the total zero order diffraction light (the light having an emitting direction same with an incident direction) to the total non-zero order diffraction light (the light having an emitting direction different from an incident direction) lower than 100:1 to a light passing through the grating region **43** and the grating region **53** with a specific direction. The “ordinary region (or non-grating region)” generates the low-degree effect diffraction effect of a intensity ratio of the total zero order diffraction light (the light having an emitting direction same with an incident direction) to the total non-zero order diffraction light (the light having an emitting direction different from an incident direction) higher than 100:1 to a light passing through the “ordinary region (or non-grating region)”, so as to increase penetration quantity of the light. Alternatively, the “ordinary region (or non-grating region)” passes through no light almost. That is, a light-opaque region can have the similar effect with the “ordinary region (or non-grating region). The grating regions **43** and the grating regions **53** are arranged in rows. The grating regions **43** and the grating regions **53** arranged in alternation constitute columns. The grating region **43** and the grating region **53** respectively have the diffraction grating **44** and the diffraction grating **54**. The diffraction grating **44** and the diffraction grating **54** respectively have constant period and uniform directions (azimuth angles). The connecting lines of the wave crests (or wave troughs) of the diffraction grating **44** having a substantially constant gap distance between the connecting lines. The connecting lines of the wave crests (or wave troughs) of the diffraction grating **54** having a substantially constant gap distance between the connecting lines.

In embodiments, the direction of the diffraction grating is the direction of the connecting line of the wave crests (or the wave troughs) of the diffraction grating structure. In embodiments, the direction of the diffraction grating of the grating region is indicated by a solid line. An included angle between the direction of the diffraction grating and the X-axis is the azimuth angle τ of the diffraction grating. In one embodiment, the period of the diffraction grating represents a gap distance between the wave crests (or a gap distance between the wave troughs). For example, the period **D1** of the diffraction grating **44** is $1\ \mu\text{m}$, indicating that the gap distance between the wave crests of the diffraction grating structure of the grating region **43** is $1\ \mu\text{m}$. The period **D2** of the diffraction grating **54** may be $1\ \mu\text{m}$. The direction of the diffraction grating **44** is different from the direction of the diffraction grating **54**. The direction of the diffraction grating **44** may be perpendicular to the direction of the diffraction grating **54**. In this case, for example, the azimuth angle τ_1 of the diffraction grating **44** is 90 degrees. The azimuth angle of the diffraction grating **54** is 0 degree. The grating region **43** and the grating region **53** may have spherical shapes respectively having a diameter **K1** and a diameter **K2**, such as $28\ \mu\text{m}$ - $29\ \mu\text{m}$. A refractive index of a material of the diffraction grating may be about 1.49. A height between the wave crest and the wave trough of the diffraction grating structure is about $0.4\ \mu\text{m}$. For example, the refractive index of the material, the gap distance between the wave crests, or the height between the wave crest and the wave trough of the diffraction grating structure are designed properly, for generating a high-degree effect diffraction effect of a intensity ratio of the total zero order diffraction light (the light having an emitting direction same with an incident direction) to the total non-zero order diffraction light (the light having an emitting direction different from an incident direction) by a deflection angle bigger than 15 degrees) lower than 100:1 to a light passing through the diffraction grating structure with a specific direction. The non-grating region is designed properly for generating the low-degree effect diffraction effect of an intensity ratio of the total zero order diffraction light (the light having an emitting direction same with an incident direction) to the total non-zero order diffraction light (the light having an emitting direction different from an incident direction) by a deflection angle bigger than 15 degrees) higher than 100:1 to a light passing through the non-grating region. The design method for the non-grating region is not described in detail herein.

In other embodiments, the single grating region may have diffraction gratings having the same azimuth angle and various periods. For example, the single grating region has diffraction gratings having two kinds of the gap distances between connecting lines of wave crests (or wave troughs), substantially $1\ \mu\text{m}$ and $0.5\ \mu\text{m}$. An area of the grating region may occupy 17.5%~94% of an area of the diffractive optical element.

Referring to FIG. 2, in a line constituted by the grating region **43** and the grating region **53** arranged in alternation, the closest gap distance between the grating region **43** and the grating region **53** may be constant or varied according to actual demands. For example, the closest gap distances **S1**, **S2** of the grating regions **43** and the grating regions **53** may be $1\ \mu\text{m}$ - $15\ \mu\text{m}$, such as $1\ \mu\text{m}$, $9\ \mu\text{m}$, or $15\ \mu\text{m}$ both. In other embodiments, the gap distance **S1** is $9\ \mu\text{m}$, and the gap distance **S2** is $15\ \mu\text{m}$. In another embodiment, the closest gap distance between the grating region **43** and the grating region **53** may be 0 or negative that is the grating region **43** and the grating region **53** have an overlapping area therebetween.

Referring to FIG. 2, for example, in a line constituted by the grating regions 43 or in a line constituted by the grating regions 53, the closest gap distance between the grating regions 43 or the closest gap distance between the grating regions 53 may be adjusted to be constant or varied according to actual demands. In one embodiment, the closest gap distance S4 between the grating regions 43 and the closest gap distance S5 between the grating regions 53 are respectively 1 μm -15 μm , such as 1 μm and 13 μm . In another embodiment, the closest gap distance S4 between the grating regions 43 and the closest gap distance S5 between the grating regions 53 may be 0 or negative that is the grating region 43 and the grating region 53 have an overlapping area therebetween.

In one embodiment, the azimuth angle the first kind of the diffraction grating of the diffractive optical element is 0 ± 60 degrees, that is the angle is in a range of bigger than and equal to -60 degrees, smaller than and equal to $+60$ degrees, and equal to 0 degree, and the similar concept is not described repeatedly hereafter. The azimuth angle the first kind of the diffraction grating of the diffractive optical element is 0 ± 20 degrees preferably. In addition, the azimuth angle the second kind of the diffraction grating of the diffractive optical element is 90 ± 60 degrees, preferably 90 ± 20 degrees. In another embodiment, the azimuth angle of the diffraction grating of the first kind is ± 45 degrees, ± 20 degrees, preferably $\pm 45\pm 10$ degrees, and the azimuth angle of the diffraction grating of the second kind is 135 ± 20 degrees, preferably 135 ± 10 degrees. In yet another embodiment, the azimuth angle of the diffraction grating of the first kind is -45 ± 20 degrees, preferably -45 ± 10 degrees, and the azimuth angle of the diffraction grating of the second kind is 45 ± 20 degrees, preferably 45 ± 10 degrees. An area of the grating region of the first kind may occupy 17.5%~38.5% of an area of the diffractive optical element, and an area of the grating region of the second kind may occupy 17.5%~38.5% of the area of the diffractive optical element. The diffractive optical element 62 in FIG. 3 is different from the diffractive optical element 32 in FIG. 2 in that the diffractive optical element 62 has a grating region 73 having a diffraction grating 74 of a constant azimuth angle.

The diffractive optical element 82 in FIG. 4 is different from the diffractive optical element 32 in FIG. 2 in that the diffractive optical element 82 comprises grating regions 93, 103 and 113 respectively having diffraction gratings 94, 104 and 114 of different azimuth angles. For example, the azimuth angle $\tau 2$ of the diffraction grating 94 is 135 degrees, the azimuth angle of the diffraction grating 104 is 0 degree, and the azimuth angle $\tau 3$ of the diffraction grating 114 is 45 degrees.

In one embodiment, the azimuth angles of the diffraction gratings of the first kind, the second kind and the third kind of the diffractive optical element are respectively 90 ± 15 degrees, 135 ± 15 degrees and 45 ± 15 degrees. In another embodiment, the azimuth angles of the diffraction gratings of the first kind, the second kind and the third kind are respectively 15 ± 10 degrees, 60 ± 10 degrees and -30 ± 10 degrees. In yet another embodiment, the azimuth angle of the diffraction grating of the first kind is 0 ± 40 degrees, preferably 0 ± 20 degrees, the azimuth angle of the diffraction grating of the second kind is 45 ± 40 degrees, preferably 45 ± 20 degrees, and the azimuth angle of the diffraction grating of the third kind is 135 ± 40 degrees, preferably 135 ± 10 degrees. An area of the grating region of the first kind may occupy 17.5%~38.5% of an area of the diffractive optical element. An area of the grating region of the second kind may occupy 17.5%~38.5% of an area of the diffractive

optical element. In addition, an area of the grating region of the third kind may occupy 7.5%~38.5% of an area of the diffractive optical element.

The diffractive optical element 122 in FIG. 5 is different from the diffractive optical element 32 in FIG. 2 in that the grating regions 133 and the grating regions 143 are respectively arranged in rows, and the grating regions 133 and the grating regions 143 are arranged in alternation in rows vertically.

The diffractive optical element 142 in FIG. 6 is different from the diffractive optical element 132 in FIG. 5 in that a horizontal (X direction) period C1 between the grating regions 145 is different from the horizontal period C2 between the grating regions 146. In one embodiment, the period C1 is 30 μm , and the period C2 is 48 μm . In addition, the vertical (Y direction) cycle space C3 between the grating region 145 and the grating region 146 is 41 μm . The cycle space also means an appearing cycle between the grating regions respectively having different grating directions.

The diffractive optical element 152 in FIG. 7 is different from the diffractive optical element 32 in FIG. 2 in that all the grating regions 163 and the grating regions 173 are arranged in alternation.

The diffractive optical element 182 in FIG. 8 is different from the diffractive optical element 32 in FIG. 2 in that the diffraction grating 194 of the grating region 193 and the diffraction grating 204 of the grating region 203 have azimuth angles other than 0 degree and 90 degrees. For example, the azimuth angle $\tau 4$ of the diffraction grating 194 is 45 degrees. The azimuth angle $\tau 5$ of the diffraction grating 204 is 135 degrees.

The diffractive optical element 183 in FIG. 9 is different from the diffractive optical element 182 in FIG. 8 in that the horizontal (X direction) period C4 between the grating regions 185 is different from the horizontal period C5 between the grating regions 186. In one embodiment, the period C4 is 30 μm , and the period C5 is 48 μm . In addition, the vertical (Y direction) cycle space C6 between the grating region 185 and the grating region 186 is 41 μm .

In one embodiment, the diffractive optical element may have grating regions of more than three kinds of diffraction grating directions.

Referring to FIG. 10, for example, the diffractive optical element 202 has the grating region 205, the grating region 206 and the grating region 207. The azimuth angle of the diffraction grating 208 of the grating region 205 is 135 degrees. The azimuth angle of the diffraction grating 209 of the grating region 206 is 0 degree. The azimuth angle of the diffraction grating 210 of the grating region 207 is 90 degrees. In embodiments, the grating regions 205 having a higher amount (or density) are arranged into one row, and the grating regions 206 and the grating regions 207 having a lower amount (or density) are arranged in alternation into another row, so as to utilizing arrangement space of the diffractive optical element 202 properly. In a case of the TN panel using the diffractive optical element 202, the grating region 205 is mainly used for compensating up and down gray level reversion direction, and the grating region 206 and the grating region 207 are mainly used for compensating 45 degrees and -45 degrees direction. That is, the diffractive optical element 202 is used by rotating 45 degrees ($+45$ degrees) counter-clockwise. In one embodiment, the horizontal (X direction) period C7 between the grating regions 205 is different from the horizontal (X direction) period C8 between the grating region 206 and the grating region 207. For example, the period C7 is 36 μm , and the period C8 is 32 μm . In another embodiment, the vertical (Y) cycle space

C9 between the grating region 205 and the grating region 207 (or the grating region 206) is 36 μm .

Referring to FIG. 11, for example, the azimuth angle of the diffraction grating 174 of the diffractive optical element 192 is 0 degree. The azimuth angle τ_6 of the diffraction grating 184 is 45 degrees. The azimuth angle τ_7 of the diffraction grating 214 is 90 degrees. In addition, the azimuth angle τ_8 of the diffraction grating 234 is 135 degrees. In another embodiment, in the diffractive optical element having the diffraction gratings of more than three kinds of the azimuth angles, the grating regions having different azimuth angles may be arranged in alternation.

In one embodiment, the diffraction grating direction of the single grating region is not limited to only one direction. The single grating region may have the diffraction grating of various azimuth angles. In addition, the grating region is not limited to the spherical shape as shown in FIGS. 2-11. For example, in embodiments, the single grating region having four kinds of the diffraction grating directions may comprise square shapes (FIG. 12), rectangle shapes (FIG. 13) or other quadrilateral shapes. For example, the single grating region having three kinds of the diffraction grating directions may comprise regular triangle shapes (FIG. 14), isosceles triangle shapes (FIG. 15), non-isosceles triangle shapes (FIG. 16). For example, the single grating region having multiple kinds of the diffraction grating directions may comprise regular pentagon shapes (FIG. 17) or other regular pentagon shapes; or regular octagon shapes (FIG. 18) or other octagon shapes; or spherical shapes (FIG. 19) or other curved shapes; or other suitable shapes. In addition, the effect from the grating of polygon shape can also be obtained a combination of the gratings of different directions, and therefore the present disclosure is not limited to the grating of polygon shape.

In some embodiments, the diffractive optical element 212 comprises the grating region 223 as shown in FIG. 20. Referring to FIG. 20, in one embodiment, the period T of the grating region 223 is 124 μm . A width W of the grating region 223 is 116 μm -118 μm . The period N of the diffraction gratings 224 is 1 μm . The gap distance M between the diffraction gratings 224 is 6 μm -8 μm . In another embodiment, the gap distance between the grating regions 223 may be 0 or negative. The negative gap distance means the adjacent grating regions 223 have an overlapping region therebetween.

Referring to FIG. 21, the diffractive optical element 232 may also comprise the diffraction grating 244, the diffraction grating 254. The diffractive optical element 232 may also be regarded as a result of the grating region having the diffraction grating 244 and the grating region having the diffraction grating 254 overlapped with each other. In one embodiment, the diffractive optical element 262 comprises the grating region 273 and the grating region 283 as shown in FIG. 22.

Referring to FIG. 23, the diffractive optical element 263 comprises the grating region 264 and the grating region 265. The azimuth angle of the diffraction grating 267 of the grating region 264 is 45 degrees. The azimuth angles of the diffraction grating 268 and the diffraction grating 269 of the grating region 265 are 90 degrees and 0 degree, respectively. In one embodiment, the width W1 of the grating region 264 measured along the azimuth angle of 135 degrees and the width W2 of the grating region 265 measured along the azimuth angle of 135 degrees are 20 μm , respectively. The gap distances C10 or C11 of the grating region 264 and the grating region 265 along the azimuth angle of 135 degrees are 60 μm .

Referring to FIG. 24, the diffractive optical element 271 comprises the grating region 272 and the grating region 274.

The azimuth angle of the diffraction grating 275 of the grating region 272 is 45 degrees. The azimuth angle of the diffraction grating 276 of the grating region 274 is 135 degrees. In one embodiment, the horizontal (X direction) width W3 of the grating region 272 and the horizontal (X direction) width W4 of the grating region 274 are 20 μm , respectively. The horizontal (X direction) gap distance between the grating region 272 and the grating region 274 is 36 μm .

Referring to FIG. 25, the diffractive optical element 277 comprises the grating region 278, the grating region 279 and the grating region 280. The azimuth angle of the diffraction grating 281 of the grating region 278 is 90 degrees. The azimuth angle of the diffraction grating 282 of the grating region 279 is 45 degrees. The azimuth angle of the diffraction grating 284 of the grating region 280 is 135 degrees. In one embodiment, the horizontal (X direction) width W5 of the grating region 278, the horizontal (X direction) width W6 of the grating region 279 and the horizontal (X direction) width W7 of the grating region 280 are all 28 μm . The horizontal (X direction) cycle space C12 between the adjacent grating region 278 and grating region 279 is 60 μm . The horizontal (X direction) cycle space C13 between the adjacent grating region 278 and grating region 280 is 60 μm .

Referring to FIG. 26, in one embodiment, for example, the horizontal (X direction) width W8 of the grating region 286 is 22 μm . The horizontal (X direction) width W9 of the grating region 287 and the horizontal (X direction) width W11 of the grating region 289 are 18 μm , respectively. The horizontal (X direction) width W10 of the grating region 288 is 14 μm . The closest distance S12 between the grating region 286 and the grating region 287 is 25 μm . The closest distance S13 between the grating region 286 and the grating region 289 is 15 μm . In other embodiments, the element may be constituted by overlapping two diffractive optical elements 277 as shown in FIG. 25.

Referring to FIG. 27, the diffractive optical element 290 comprises the grating region 291, the grating region 293 and the grating region 294. In one embodiment, the horizontal (X direction) width W12 of the grating region 291, the horizontal (X direction) width W13 of the grating region 293, and the horizontal (X direction) width W14 of the grating region 294 are 28 μm , respectively. The closest distance S14 between the adjacent grating regions 291 is 5 μm .

The diffractive optical element 292 may also comprise the grating region 303 and the grating region 313 as shown in FIG. 28.

The grating regions of the diffractive optical element are not limited to order arrangement, and can be adjusted into disorder arrangement according to actual demands. Referring to FIG. 29, for example, the diffractive optical element 322 may also comprise the grating region 333, the grating region 343, the grating region 353, the grating region 363 and the grating region 373 disorderly.

In embodiments, the many diffractive optical elements can be overlapped for using according to actual demands. The diffractive optical elements of different levels may be arranged by overlapping the grating regions having the same pattern, i.e. the same shape or the same diffraction grating, of different levels with each other, or by overlapping the grating regions having different patterns, i.e. different shapes or diffraction gratings of different characteristics. Referring to FIG. 2, for example, in a case of overlapping one diffractive optical element 32 with another diffractive optical element 32, the grating region 53 of the one diffractive optical element 32 is overlapped with the grating region 43

of the another diffractive optical element **32**, and the grating region **43** of the one diffractive optical element **32** is overlapped with the grating region **53** of the another diffractive optical element **32**. For example, after a laser light source is emitted to a single-layer diffractive optical element **32** as shown in FIG. 2, diffraction lights of two directions such as 0/180 degrees or 90/270 degrees are formed. Conversely, after the laser light source is emitted to a stacked structure constituted by multi-layer diffractive optical elements, not only the transmission light having the diffraction directions as formed by the single-layer diffractive optical element, but also transmission lights having other diffraction directions such as oblique directions. Cause of this is from the additional the cycle structure for the oblique direction. In addition, it is presumed that diffraction light emitted from the grating region adjacent to a light source and generated from a light emitted into and the perpendicular to grating region adjacent to the light source is further diffracted by the grating region away from the light source. Therefore, besides the diffraction lights of two directions such as 0/180 degrees or 90/270 degrees are generated by the single-layer diffractive optical element, additional diffraction lights of other oblique directions such as 45 degrees, 135 degrees, 225 degrees, or 315 degrees or a bisector angle of the azimuth angles of two diffraction gratings are formed.

In embodiments, the slacked structure constituted by the diffractive optical elements of various layers may be constituted by overlapping the grating regions of the same pattern according to actual demands. Referring to FIG. 2, in one embodiment, for example, one diffractive optical element **32** is overlapped with another diffractive optical element **32**. The grating region **43** of the one diffractive optical element **32** is overlapped with the grating region **43** of the another diffractive optical element **32**. The grating region **53** of the one diffractive optical element **32** is overlapped with the grating region **53** of another diffractive optical element **32**. It can increase diffraction effect.

Referring to FIG. 30, the diffractive optical element **334** may be constituted by overlapping two diffractive optical elements. For example, one of the two diffractive optical elements has the grating region **335A** and the grating region **335B**, and the other of the two diffractive optical elements has the grating region **336**. The azimuth angle of the diffraction grating **337A** of the grating region **335A** and the diffraction grating **337B** of the grating region **335B** are both 135 degrees. The azimuth angle of the diffraction grating **338** of the grating region **336** is 45 degrees. The horizontal (X direction) period **C14** between the grating regions **335A** of the first raw and the third raw is 36 μm . The horizontal (X direction) period **C15** between the grating regions **336** of the second raw and the fourth raw is 41 μm . In addition, the horizontal (X direction) period **C25** between the grating regions **335B** is 41 μm . The vertical (Y direction) period **C26** between the grating regions **335A** is 72 μm . The vertical (Y direction) cycle space **C16** between the grating region **335A** and the grating region **336** is 36 μm .

Referring to FIG. 31, the diffractive optical element **339** may be constituted by overlapping two diffractive optical elements. For example, one of the two diffractive optical elements has the grating region **340A** and the grating region **340B**, and the other of the two diffractive optical elements has the grating region **341**. The azimuth angle of the diffraction grating **342A** of the grating region **340A** and the diffraction grating **342B** of the grating region **340B** are both 0 degrees. The azimuth angle of the diffraction grating **334** of the grating region **341** is 90 degrees. The horizontal (X direction) period **C17** between the grating regions **340A** of

the first raw and the third raw is 36 μm . The horizontal (X direction) period **C18** between the grating regions **341** of the second raw and the fourth raw is 41 μm . In addition, the horizontal (X direction) period **C27** between the grating regions **340B** is 41 μm . The vertical (Y direction) period **C28** between the grating regions **340A** is 72 μm . The vertical (Y direction) cycle space **C19** between the grating region **340A** and the grating region **341** is 36 μm .

Referring to FIG. 32, the diffractive optical element **345** comprises the grating region **346**, the grating region **347** and the grating region **348**. In one embodiment, the horizontal (X direction) period **C20** between the grating regions **346** is 26 μm . The horizontal (X direction) period **C21** between the grating regions **347** is 48 μm . The horizontal (X direction) period **C22** between the grating regions **348** is 26 μm . The vertical (Y direction) of the cycle space **C23** between the grating region **346** and the grating region **347** is 41 μm . The vertical (Y direction) of the cycle space **C24** between the grating region **347** and the grating region **348** is 41 μm .

In embodiments, the diffractive optical element is adjusted according to condition and effect for the display device.

Referring to FIG. 33, in embodiments, the display device **410** is a liquid crystal display device. The display device **410** comprises a backlight module **411**, a liquid crystal panel **427**, the polarizer **415** and the polarizer **425**. The liquid crystal panel **427** is disposed on the backlight module **411**. For example, the liquid crystal panel **427** comprises a thin film transistor substrate **416**, a liquid crystal layer **418**, a color filter substrate **421**, the alignment film **417** and the alignment film **419**. The alignment film **419** may be disposed on the color filter substrate **421**. The alignment film **417** may be disposed on the thin film transistor substrate **416**. The liquid crystal layer **418** may be disposed between the alignment film **417** and the alignment film **419**. The polarizer **415** may be disposed between the thin film transistor substrate **416** and the backlight module **411** (on the light entering side of the liquid crystal panel **427**). The polarizer **425** may be disposed on the color filter substrate **421** (the light emitting side of the liquid crystal panel **427**). The diffractive optical element **402** may be disposed on the light emitting side of the polarizer **425**. The diffractive optical element **402** is disposed by placing the wave crest structure facing the polarizer **425** or opposite to the polarizer **425**. The diffractive optical element **425** may be used by stacking with other elements having different functions, such as an anti-reflection film, a scratch-resistant film, etc.

In some embodiments, the display device **410** is a twisted nematic (TN) liquid crystal display device. In this case, referring to FIG. 34, the azimuth angle of the aligning direction **426** of the alignment film **417** is arranged not parallel to the azimuth angle of the aligning direction **436** of the alignment film **419**. The liquid crystal molecules **428** in the liquid crystal layer **418** are aligned by the alignment film **417** and the alignment film **419**, and thus the liquid crystal molecules **428a** (i.e. top layer liquid crystal molecule) adjacent to the alignment film **419** (i.e. top layer alignment film adjacent to the color filter substrate **421** in FIG. 33) and the liquid crystal molecule **428b** (i.e. bottom layer liquid crystal molecule) adjacent to the alignment film **417** (i.e. bottom layer alignment film adjacent to the thin film transistor substrate **416** in FIG. 33) are aligned into a twisted structure and to have pretilt angles. One end of the liquid crystal molecule having the pretilt angle away from the alignment film is referred to as a head end, and the other end of the liquid crystal molecule is referred to as a tail end. For example, the alignment film **419** is used for aligning the top

layer liquid crystal molecules **428a** to have the pretilt angle. For example, the alignment film **417** is used for aligning the bottom layer liquid crystal molecules **428b** to have the pretilt angle. The alignment film **417** and the alignment film **419** are arranged to the aligning directions of which not parallel to each other for aligning the liquid crystal molecules **428** therebetween to twist continuously into a twisted structure. In the twisted structure, the twist angle of the liquid crystal molecules **428** may be defined as an angle twist continuously from the head end of the bottom layer liquid crystal molecule **428b**, through the middle layer liquid crystal molecule, to the tail end of the top layer liquid crystal molecule **428a**.

Moreover, for conventional the twisted nematic (TN) liquid crystal display device, an optical characteristic of a viewing angle, ranged from the head end of the bottom layer liquid crystal molecule **428b** twisted continuously, through the middle layer liquid crystal molecules, to the tail end of the liquid crystal molecules **428a**, is not good and thus is usually defined as a look-down angle direction for a viewer. The above region for poor viewing angle can also be defined as some viewing angle directions for a viewer.

The azimuth angle of the liquid crystal molecule tilted relative to the substrate is defined as the tilt azimuth angle. For example, as the liquid crystal molecule is aligned or driven to have a specific included angle with the substrate, the tilted liquid crystal has the azimuth angle relative to the horizontal plane of the substrate. In other words, the included angle between the projection direction of the head end of the liquid crystal molecule on the horizontal plane of the substrate and the X-axis of the substrate is defined as liquid crystal tilt azimuth angle. For the liquid crystal display device is a multi-domain vertical aligned liquid crystal display device, it can be understood that various liquid crystal tilt azimuth angles can be generated at the same time.

In some embodiments, the diffractive optical element is designed according to the condition of the liquid crystal molecules **428** of the display device **410** (FIG. **34**). Referring to FIG. **35**, for example, the liquid crystal molecules **428a** has the liquid crystal tilt azimuth angle **Q1**, such as 45 degrees. The liquid crystal molecule **428b** has the liquid crystal tilt azimuth angle **Q2**, such as 315 degrees. In this case, the diffractive optical element having the diffraction gratings having the azimuth angles of 0 degree and 90 degrees may be used. In addition, the density (i.e. area percentage of grating occupying the diffractive optical element) of the diffraction grating having the grating direction having the azimuth angle of 0 degree is bigger than or equal to the density of the diffraction grating having the azimuth angle of 90 degrees. For example, diffractive optical element **32** as shown in FIG. **2** may be used. In other embodiments, the diffractive optical element having diffraction gratings having azimuth angles of 0 degree, 45 degrees and 135 degrees may be used. In addition, the density of the diffraction grating having the azimuth angle of 0 degree is bigger than or equal to the density of the diffraction gratings having the azimuth angles of 45 degrees and 135 degrees, respectively. For example, the diffractive optical element **82** as shown in FIG. **4** may be used. In one embodiment, the included angle between the grating direction of the first kind of the diffraction grating of the diffractive optical element and the tilt direction of the top layer liquid crystal molecule is 90 ± 10 degrees or 0 ± 10 degrees. The included angle between the grating direction of the second kind of the diffraction grating of the diffractive optical element and the

tilt direction of the top layer liquid crystal molecule is 180 ± 10 degrees or 90 ± 10 degrees.

In one embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 0 ± 20 degrees, preferably 0 ± 10 degrees, and the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is -90 ± 20 degrees, preferably -90 ± 10 degrees. In another embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 90 ± 20 degrees, preferably 90 ± 10 degrees, and the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 0 ± 20 degrees, preferably 0 ± 10 degrees. In yet another embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 45 ± 60 degrees, preferably 45 ± 20 degrees and more preferably 45 ± 10 degrees, and the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is -45 ± 60 degrees, preferably -45 ± 20 degrees and more preferably -45 ± 10 degrees.

In one embodiment, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 45 ± 20 degrees, preferably 45 ± 10 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 0 ± 20 degrees, preferably 0 ± 10 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 90 ± 20 degrees, preferably 90 ± 10 degrees. In another embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is -45 ± 15 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 90 ± 15 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 0 ± 15 degrees. In one embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 30 ± 10 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive

optical element to the tilt direction of the top layer liquid crystal molecule is -15 ± 10 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 75 ± 10 degrees. In one embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle between from grating direction of the first kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 45 ± 20 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 0 ± 20 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 90 ± 20 degrees.

In some embodiments, the diffractive optical element may be designed according to the alignment film **417**, the alignment film **419** of the display device **410** (FIG. **33**). For example, in one embodiment, the azimuth angle of the aligning direction of the alignment film **419** is 45 degrees, and the azimuth angle of the aligning direction of the alignment film **417** is -45 degrees. In this case, the diffractive optical element having the diffraction gratings having the grating directions having the azimuth angles of 0 degree and 90 degrees may be used. In addition, in some embodiments, the density of the diffraction grating having the grating direction having the azimuth angle of 0 degree is bigger than or equal to the density of the diffraction grating having the grating direction having the azimuth angle of 90 degree. For example, the diffractive optical element **32** in FIG. **2** may be used. In other embodiments, the diffractive optical element having the diffraction gratings having the grating directions having the azimuth angles of 0 degree, 45 degrees and 135 degrees may be used. In addition, the density of the diffraction grating having the grating direction having the azimuth angle of 0 degree is bigger than or equal to the densities of the diffraction gratings having the grating directions having the azimuth angles of 45 degrees and 135 degrees, respectively. For example, the diffractive optical element **82** in FIG. **4** may be used.

In one embodiment, as the included angle between the aligning directions of the upper alignment film and the lower alignment film is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 45 ± 60 degrees, preferably 45 ± 20 degrees and more preferably 45 ± 10 degrees, and the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is -45 ± 60 degrees, preferably -45 ± 20 degrees and more preferably -45 ± 10 degrees. In another embodiment, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 0 ± 20 degrees, preferably 0 ± 110 degrees, and the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is -90 ± 20 degrees, preferably -90 ± 10 degrees. In one embodiment, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is $+90\pm 20$ degrees, preferably $+90\pm 10$ degrees, and the

included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 0 ± 20 degrees, preferably 0 ± 10 degrees.

In one embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is -45 ± 15 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 90 ± 15 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 0 ± 15 degrees. In another embodiment, as the included angle between the tilt directions of the top layer and the bottom layer liquid crystal molecules is 90 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 30 ± 10 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is -15 ± 10 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 75 ± 10 degrees. In one embodiment, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 45 ± 20 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 0 ± 20 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the aligning direction of the top layer alignment film is 90 ± 20 degrees.

In some embodiments, the diffractive optical element is designed according to the arrangement of the polarizer.

Referring to FIG. **36**, for example, the azimuth angle $\psi 1$ of the polarizing direction **445** of the polarizer, such as the polarizer **425** in FIG. **33**, on the light emitting side is 135 degrees, that is the azimuth angle of the transmission axis of the polarizer **425** is 135 degrees, or the azimuth angle of the absorption axis of the polarizer **425** is 45 degrees. The azimuth angle $\psi 2$ of the polarizing direction **455** of the polarizer, such as the polarizer **415** in FIG. **33**, adjacent to the backlight module is 45 degrees, that is the azimuth angle of the transmission axis of the polarizer is 45 degrees, or the azimuth angle of the absorption axis is 135 degrees. The diffractive optical element **462**, similar to the diffractive optical element **32** in FIG. **2**, has the grating region **473** and the grating region **483**, respectively having the diffraction grating **474** having the grating direction having the azimuth angle of 0 degree and the diffraction grating **484** having the grating direction having the azimuth angle of 90 degrees. The density of the diffraction grating **473** is bigger than or equal to the density of the diffraction grating **483**. In this case, the azimuth angle of the long axis direction of the row constituted by the grating regions **473** and the azimuth angle of the long axis direction of the row constituted by the grating regions **483** are 0 degree. The azimuth angle of the

long axis direction of the column constituted by the grating regions **473** and the grating region **483** arranged in alternating fashion is 90 degrees.

The embodiment as shown in FIG. **37** is different from the embodiment as shown in FIG. **36** in that the grating regions **493**, similar with the grating region **473** in FIG. **36**, and the grating region **503**, similar with the grating region **483** in FIG. **36** are arranged in alternation. In this case, the azimuth angle of the long axis direction **496** of the row constituted by the grating regions **493** and the azimuth angle of the long axis direction **497** of the row constituted by the grating regions **503** are 0 degree. The azimuth angle of the long axis direction of the column constituted by the grating regions **493** and the grating region **503** arranged in alternating fashion is 60 degrees. The embodiment as shown in FIG. **38** is different from the embodiment as shown in FIG. **36** in that the grating regions **513**, similar with the grating region **473** in FIG. **36**, and the grating region **523**, similar with the grating region **483** in FIG. **36** are arranged in alternation. In this case, the azimuth angle of the long axis direction of the row constituted by the grating regions **513** and the grating regions **523** arranged in alternation is 0 degree. The azimuth angle of the long axis direction of the column constituted by the grating regions **513** and the grating regions **523** arranged in alternation is 90 degrees.

Referring to FIG. **39**, the azimuth angle ψ_3 of the polarizing direction **505** of the polarizer, such as the polarizer **425** in FIG. **33**, on the light emitting side is 135 degrees, that is the azimuth angle of the transmission axis of the polarizer **425** is 135 degrees, or the azimuth angle of the absorption axis of the polarizer **425** is 45 degrees. The azimuth angle ψ_4 of the polarizing direction **515** of the polarizer, such as the polarizer **415** in FIG. **33**, adjacent to the backlight module is 45 degrees, that is the azimuth angle of the transmission axis of the polarizer **455** is 45 degrees, or the azimuth angle of the absorption axis of the polarizer **455** is 135 degrees. The diffractive optical element **522**, similar with the diffractive optical element **82** in FIG. **4**, has the grating region **533**, the grating region **543** and the grating region **553**, for example, respectively having the diffraction grating **534** having the grating direction having the azimuth angle of 135 degrees, the diffraction grating **544** having the grating direction having the azimuth angle of 0 degree, and the diffraction grating **554** having the grating direction having the azimuth angle of 45 degrees. In one embodiment, especially for the TN liquid crystal display device, the density of the diffraction grating **544** is gibber than or equal to the density of the diffraction grating **534** and the density of the diffraction grating **554** respectively.

Referring to FIG. **40**, the azimuth angle ψ_5 of the polarizing direction **545** of the polarizer, such as the polarizer **425** in FIG. **33**, on the light emitting side is 135 degrees, that is the azimuth angle of the transmission axis of the polarizer **425** is 135 degrees, or the azimuth angle of the absorption axis of the polarizer **425** is 45 degrees. The azimuth angle ψ_6 of the polarizing direction **555** of the polarizer, such as the polarizer **415** in FIG. **33**, adjacent to the backlight module is 45 degrees, that is the azimuth angle of the transmission axis of the polarizer **455** is 45 degrees, or the azimuth angle of the absorption axis of the polarizer **455** is 135 degrees. The diffractive optical element **562**, similar with the diffractive optical element **182** in FIG. **8**, has the grating region **573** and the grating region **583**, respectively having the diffraction grating **574** having the grating direction having the azimuth angle of 135 degrees and the diffraction grating **584** having the grating direction having the azimuth angle of 45 degrees.

Referring to FIG. **41**, the azimuth angle ψ_7 of the polarizing direction **605** of the polarizer, such as the polarizer **425** in FIG. **33**, on the light emitting side is 135 degrees. The azimuth angle ψ_8 of the polarizing direction **615** of the polarizer, such as the polarizer **415** in FIG. **33**, adjacent to the backlight module is 45 degrees. The diffractive optical element **622** for using is similar with the diffractive optical element **292** in FIG. **28**, and has the grating region **603** and the grating region **613**, respectively having the diffraction grating **604** having various grating directions and the diffraction grating **614** having the grating direction having the azimuth angle of 90 degrees.

In one embodiment, the included angle between the azimuth angles of the grating direction of the first kind of the diffraction grating of the diffractive optical element and the polarizing direction of the polarizer on the light emitting side is 135 ± 20 degrees, and the included angle between the azimuth angles of the grating direction of the second kind of the diffraction grating of the diffractive optical element and the polarizing direction of the polarizer on the light emitting side is 45 ± 20 degrees. In another embodiment, as the included angle between the polarizing direction of the polarizer on the light emitting side and the polarizing direction of the polarizer on the light entering side is 90 degrees and the azimuth angle of the polarizing direction of the polarizer on the light entering side is 135 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 90 ± 20 degrees, preferably 90 ± 10 degrees, and the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 0 ± 20 degrees, preferably 0 ± 10 degrees. In another embodiment, as the included angle between the polarizing direction of the polarizer on the light emitting side and the polarizing direction of the polarizer on the light entering side is 90 degrees and the azimuth angle of the polarizing direction of the polarizer on the light entering side is 135 degrees, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 180 ± 20 degrees, preferably 180 ± 10 degrees, and the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 90 ± 20 degrees, preferably 90 ± 10 degrees. In one embodiment, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 45 ± 15 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 0 ± 15 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 90 ± 15 degrees. In another embodiment, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 20 ± 10 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 75 ± 10 degrees, and the included angle from the grating direction of the third kind of the diffraction grating

of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 165 ± 10 degrees. In one embodiment, the included angle from the grating direction of the first kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 135 ± 20 degrees, the included angle from the grating direction of the second kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 90 ± 20 degrees, and the included angle from the grating direction of the third kind of the diffraction grating of the diffractive optical element to the polarizing direction of the polarizer on the light emitting side is 180 ± 20 degrees.

In one embodiment, one experiment uses the Konica Minolta CS-2000 to measure the N101L6-L07 type liquid crystal display device having the diffractive optical element **212** ($T=124\ \mu\text{m}$, $W=117\ \mu\text{m}$, $N=1\ \mu\text{m}$, $M=7\ \mu\text{m}$) as shown in FIG. **20**. The white state and the black state of the liquid crystal display device are measured for every 5 degrees of counter-clockwise rotating of the diffractive optical element **212**. In addition, the contrast value (white state (255 gray levels) brightness/black state (0 gray level) brightness) and the normalization brightness of each gray level (brightness of each gray level/white state (255 gray levels) brightness) are calculated. Data are shown in table 1. The display device without using the diffractive optical element is one comparative example. Effect of adjusting the angle of the diffraction grating for the normalization brightness of the display device for the specific gray level is shown in table 2. The measuring method for the characteristics as shown in table 2 is adjusting the angle of the diffraction grating, and measuring the difference between the normalization brightness of the display device at the zenith angle of 0° and the brightness of the display device at the zenith angles of 45° or 60° , in the specific gray levels (224 gray levels, 232 gray levels). Each unit for the gray level reversion is 8 gray levels. The gray level reversion is happened as the difference between the next one unit of the gray level and the previous one unit of the gray level is negative. The normalization difference is the difference between the conditions in which

the diffraction grating has the azimuth angle of 0 degrees and the diffraction grating has the azimuth angle of other rotating angles.

TABLE 1

	azimuth angle of diffraction grating	Central contrast
	-85	734
	-80	761
	-75	786
	-70	827
	-65	864
	-60	879
	-55	882
	-50	873
	-45	845
	-40	827
	-35	781
	-30	736
	-25	687
	-20	662
	-15	653
	-10	653
	-5	660
	0	681
	5	762
	10	764
	15	790
	20	809
	25	828
	30	856
	35	865
	40	885
	45	896
	50	905
	55	915
	60	906
	65	889
	70	857
	75	812
	80	764
	85	734
	90	722

TABLE 2

azimuth angle of diffraction grating	gray level for level reversion	Normalization brightness difference	normalization difference at θ of 45°	Normalization brightness difference	normalization difference at θ of 60°
		between θ of 45° and 0° (gray level 224)		between θ of 60° and 0° (gray level 232)	
comparative example	64~152	56.4%	—	58.9%	—
0	non	18.9%	100%	11.8%	100%
10	non	21.9%	116%	16.6%	140%
20	non	24.0%	127%	20.0%	169%
30	non	28.8%	153%	25.8%	218%
40	non	35.8%	190%	34.5%	292%
45	non	40.3%	214%	39.3%	333%
50	non	43.3%	229%	41.3%	350%
60	non	47.3%	251%	44.6%	378%

The side viewing angle can be much improved due to the high density of 94%. However, since the single grating direction is used, the result is much affected by the rotating angle.

The contrast of the display apparatus is affected by adjusting the included angle between the diffraction grating direction and the polarizing direction of the polarizer.

In another embodiment, one experiment uses the Konica Minolta CS-2000 to measure the N101L6-L07 type liquid crystal display device (pixel of which is 800*600, 126 PPI and the long side of the pixel of which is 203.2 μm , and the short side of the pixel of which is 67.73 μm) having the diffractive optical element 462 (S1=9 μm , S2=15 μm , S4=S5=13 μm , D1=D2=1 μm , K1=K2=28 μm) as shown in FIG. 36. Referring to FIG. 2, in other embodiments, the display apparatus (S1=9 μm , S2=15 μm , S3=9 μm , D1=D2=1 μm , S4=S5=41 μm , K1=K2=28 μm) may be used. The white state and the black state of the liquid crystal display device are measured for every 5 degrees of counter-clockwise rotating of the diffractive optical element 462. In addition, the contrast value (white state (255 gray levels) brightness/black state (0 gray levels) brightness) and the normalization brightness of each gray level (brightness of each gray level/white state (255 gray levels) brightness) are calculated. The influence of the diffraction grating angle to the contrast is shown in table 3 and FIG. 42. The display device without using the diffractive optical element is one comparative example. Effect of adjusting the angle of the diffraction grating to the normalization brightness of the display device for the specific gray level is shown in table 4, FIG. 43 and FIG. 44.

TABLE 3

azimuth angle of diffraction grating 474	Central contrast
-85	776
-80	763
-75	777
-70	802
-65	829
-60	863
-55	894
-50	913
-45	923
-40	916
-35	898
-30	867
-25	837
-20	814
-15	786
-10	772
-5	757
0	757
5	743
10	748
15	767
20	790
25	822
30	844
35	880
40	900
45	916
50	916
55	907
60	890
65	853
70	828
75	804
80	786
85	776
90	770

In FIG. 42 and table 3, 0 degree indicates that the azimuth angle of the diffraction grating 474 of the grating region 473 is 0 degree, and the azimuth angle of the diffraction grating 484 of the grating region 483 is 90 degrees, as shown in the arrangement condition in FIG. 36. In FIG. 42 and table 3, +5 degrees indicates that the azimuth angle of the diffraction grating 474 of the grating region 473 is +5 degree, and the azimuth angle of the diffraction grating 484 of the grating region 483 is +95 degrees. The azimuth angle ψ_1 of the polarizing direction 445 of the polarizer on the light emitting side is fixed at 135 degrees, and thus the included angle from the polarizing direction of the polarizer on the light emitting side to the grating direction of the diffraction grating 484 is -130 degrees (or +50 degrees) and the included angle from the polarizing direction of the polarizer on the light emitting side to the grating direction of the diffraction grating 474 is -40 degrees (or +140 degrees). The angle of the counter-clockwise direction has a positive value, the angle of the clock-wise direction has a negative value, and so forth.

From table 3, it is found, for decreasing the influence to the contrast, the desired condition is that the azimuth angle of the diffraction grating 474 is about +45 degrees and the azimuth angle of the diffraction grating 484 is 135 degrees. For maintaining the influence to the contrast lower than 90%, the desired condition is that the azimuth angle of the diffraction grating 474 is 45 \pm 20 degrees and the azimuth angle of the diffraction grating 484 is 135 \pm 20 degrees. For making the influence to the contrast lower than 95%, the desired condition is that the azimuth angle of the diffraction grating 474 is 45 \pm 10 degrees and the azimuth angle of the diffraction grating 484 is 135 \pm 10 degrees. As the included angle between the tilt directions of the top layer liquid crystal molecule and the bottom layer liquid crystal molecule is 90 degrees, the desired condition is that the included angle from the grating direction of the diffraction grating 474 of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is 0 \pm 20 degrees, preferably 0 \pm 10 degrees, and the included angle from the grating direction of the diffraction grating 484 of the diffractive optical element to the tilt direction of the top layer liquid crystal molecule is -90 \pm 20 degrees, preferably -90 \pm 10 degrees. In addition, included angle from the grating direction of the diffraction grating 474 to the aligning direction of the first (top layer) alignment film, such as the alignment film 419 in FIG. 34, is 0 \pm 10 degrees, and the included angle from the grating direction of the diffraction grating 484 to the aligning direction of the first alignment film is -90 \pm 10 degrees. As the included angle between the polarizing direction of the polarizer of the light emitting side and the polarizing direction of the polarizer of the light entering side is 90 degrees, and the azimuth angle of the polarizing direction of the polarizer of the light emitting side is 135 degrees, the included angle from the grating direction of the diffraction grating 474 to the polarizing direction of the polarizer of the light emitting side is 90 \pm 10 degrees, and the included angle from the grating direction of the diffraction grating 484 to the polarizing direction of the polarizer of the light emitting side is 0 \pm 10 degrees.

From table 3, it is also found, for decreasing the influence to the contrast, the desired condition is that the azimuth angle of the diffraction grating 474 is about -45 degrees and the azimuth angle of the diffraction grating 484 is 45 degrees. For maintaining the influence to the contrast lower than 90%, the desired condition is that the azimuth angle of the diffraction grating 474 is -45 \pm 20 degrees and the azimuth angle of the diffraction grating 484 is 45 \pm 20 degrees. For making the influence to the contrast lower than 95%, the

desired condition is that the azimuth angle of the diffraction grating **474** is -45 ± 10 degrees and the azimuth angle of the diffraction grating **484** is 45 ± 10 degrees. In this embodiment, the included angle from the grating direction of the diffraction grating **474** to the tilt direction of the top layer liquid crystal molecule, such as the top layer liquid crystal molecule **428a** in FIG. **34** is 90 ± 10 degrees and the included angle from the grating direction of the diffraction grating **484** to the tilt direction of the top layer liquid crystal molecule is 0 ± 10 degrees. The included angle from the grating direction of the diffraction grating **474** to the aligning direction of the top layer alignment film is $+90\pm 10$ degrees, and the included angle from the grating direction of the diffraction grating **484** to the aligning direction of the top layer alignment film is 0 ± 10 degrees. As the included angle between the polarizing direction of the polarizer of the light emitting side and the polarizing direction of the polarizer of the light entering side is 90 degrees, and the azimuth angle of the polarizing direction of the polarizer of the light emitting side is 135 degrees, the included angle from the polarizing direction of the polarizer of the light emitting side to the grating direction of the diffraction grating **474** is 180 ± 10 degrees, and the included angle from the polarizing direction of the polarizer of the light emitting side to the grating direction of the diffraction grating **484** is 90 ± 10 degrees.

462 from 0 degree increases, the difference value between the normalization brightness values at 224 gray level of $\theta=45$ and $\theta=0$ increases. The difference value has the maximum (53.2%) as the deviation reaches about 30~40 degrees, which is smaller than comparative example (58.9%). The difference value gets smaller than the maximum value after the deviation of about 40 degrees.

In comparative example, at an observation angle of $(\theta, \psi)=(60, 270)$, the difference value between the normalization brightness at the zenith angle $\theta=60$ and the normalization brightness at the zenith angle $\theta=0$ has the maximum value (58.92%) at the 232 gray level. With increase of the deviation of the azimuth angle of the diffraction grating **474** of the diffractive optical element **462** from 0 degree increases, the difference value between the normalization brightness values at 232 gray level of $\theta=60$ and $\theta=0$ increases. The difference value has the maximum (50.0%) as the deviation reaches about 45 degrees, which is smaller than comparative example (58.9%). By comparing table 2 with table 3, it is found that the influence from rotating the diffractive optical element **462** is smaller than the influence from rotating the diffractive optical element **212**.

As a whole, even effect of the diffractive optical element **462** deviated about 40~45 degrees is poor, it is still better than that of comparative example. Therefore, the diffractive optical element **462** can be used in a deviation range of 0~60 degrees.

TABLE 4

azimuth angle of diffraction grating 474	gray level for gray level reversion	Normalization brightness difference		Normalization brightness difference	
		between θ of 45° and 0° (gray level 224)	normalization difference at θ of 45°	between θ of 60° and 0° (gray level 232)	normalization difference at θ of 60°
comparative example	64~152	56.4%	—	58.9%	—
0	non	41.3%	100.00%	26.8%	100.00%
10	non	42.9%	103.79%	28.5%	106.40%
20	non	43.8%	105.98%	31.1%	116.26%
30	non	53.2%	128.77%	49.1%	183.48%
40	non	53.2%	128.77%	49.1%	183.48%
45	non	45.1%	109.14%	50.0%	186.76%
50	non	44.9%	108.64%	48.7%	182.08%
60	non	42.9%	103.85%	45.3%	169.28%

The measuring method for the characteristics as shown in table 4 is adjusting the angle of the diffraction grating, and measuring the difference between the normalization brightness of the display device at the zenith angle of 0° and the brightness of the display device at the zenith angles of 45° or 60° , in the specific gray levels (224 gray level, 232 gray level). Each unit for the gray level reversion is 8 gray levels. The gray level reversion is happened as the difference between the next one unit of the gray level and the previous one unit of the gray level is negative. The normalization difference is the difference between the conditions in which the diffraction grating has the azimuth angle of 0 degree and the diffraction grating has the azimuth angle of other rotating angles.

In comparative example, at an observation angle of $(\theta, \Omega)=(45, 270)$, the difference value between the normalization brightness at the zenith angle $\theta=45$ and the normalization brightness at the zenith angle $\theta=0$ has the maximum value (56.41%) at the 224 gray level. Therefore, the observation at the zenith angle $\theta=45$ is based on the 224 gray level. With increase of the deviation of the azimuth angle of the diffraction grating **474** of the diffractive optical element

In this embodiment, for improving the gray level reversion, the azimuth angle of the diffraction grating **474** is set at 0 ± 60 degrees, and the azimuth angle of the diffraction grating **484** is set at 90 ± 60 degrees. For further improving the look-down angle characteristic, the azimuth angle of the diffraction grating **474** is set at 0 ± 20 degrees and the azimuth angle of the diffraction grating **484** is set at 90 ± 20 degrees. The included angle from the grating direction of the diffraction grating **474** to the polarizing direction of the polarizer of the light emitting side is 135 ± 20 degrees, and the included angle from the grating direction of the diffraction grating **484** to the polarizing direction of the polarizer of the light emitting side is 45 ± 20 degrees. The included angle from the grating direction of the diffraction grating **474** to the tilt direction of the top layer liquid crystal molecule is 45 ± 10 degrees, and the included angle from the grating direction of the diffraction grating **484** to the tilt direction of the top layer liquid crystal molecule is -45 ± 10 degrees. The included angle from the grating direction of the diffraction grating **474** to the aligning direction of the top layer alignment film is 45 ± 10 degrees, and the included angle from the grating direction of the diffraction grating **484** the aligning direction of the top layer alignment film is -45 ± 10 degrees.

In yet another embodiment, one experiment uses the Konica Minolta CS-2000 to measure the N101L6-L07 type liquid crystal display device having the diffractive optical element **522** ($S_6=1\ \mu\text{m}$, $S_7=1\ \mu\text{m}$, $S_8=1\ \mu\text{m}$, $D_3=D_4=D_5=1\ \mu\text{m}$, $S_9=S_{10}=S_{11}=1\ \mu\text{m}$, $K_3=K_4=K_5=28\ \mu\text{m}$) as shown in FIG. **39**. The white state and the black state of the liquid crystal display device are measured for every 5 degrees of counter-clockwise rotating of the diffractive optical element **522**. In addition, the contrast value (white state (255 gray levels) brightness/black state (0 gray levels) brightness) and the normalization brightness of each gray level (brightness of each gray level/white state (255 gray levels) brightness) are calculated. Experiment results are shown in FIG. **45** and FIG. **46**. In FIG. **45** and FIG. **46**, 0 degree indicates that the azimuth angle of the diffraction grating **534** of the grating region **533** is 135 degrees, the azimuth angle of the diffraction grating **544** of the grating region **543** is 0 degree, and the azimuth angle of the diffraction grating **554** of the grating region **553** is 45 degrees. 24.4% of the area of the diffractive optical element **522** is occupied by the area of the grating region **533**. 24.4% of the area of the diffractive optical element **522** is occupied by the area of the grating region **543**. In addition, 24.4% of the area of the diffractive optical element **522** is occupied by the area of the grating region **553**. +5 degrees indicates that the azimuth angle of the diffraction grating **534** of the grating region **533** is 140 degrees, the azimuth angle of the diffraction grating **544** of the grating region **543** is 5 degrees, and the azimuth angle of the diffraction grating **554** of the grating region **553** is 50 degrees. The azimuth angle ψ_3 of the polarizing direction **505** of the polarizer of the light emitting side is fixed at 135, and thus the included angle from the grating direction of the diffraction grating **534** to the polarizing direction of the polarizer of the light emitting side is -5 degrees (or +175 degrees), the included angle from the grating direction of the diffraction grating **544** to the polarizing direction **505** of the polarizer of the light emitting side is -50 degrees (or 130 degrees), and the included angle from the grating direction of the diffraction grating **554** to the polarizing direction **505** of the polarizer of the light emitting side is -90 degrees (or +85 degrees). The angle of the counter-clockwise direction has a positive value, the angle of the clock-wise direction has a negative value, and so forth. The influence of the diffraction grating angle to the contrast for the display device is shown in table 5, FIG. **45** and FIG. **46**. The display device without using the diffractive optical element is one comparative example. Effect of adjusting the angle of the diffraction grating to the normalization brightness of the display device for the specific gray level is shown in table 6, FIG. **47** and FIG. **48**.

TABLE 5

azimuth angle of diffraction grating 544	Central contrast
-85	654
-80	651
-75	630
-70	611
-65	594
-60	587
-55	581
-50	582
-45	583
-40	584
-35	585
-30	586

TABLE 5-continued

	azimuth angle of diffraction grating 544	Central contrast
5	-25	582
	-20	591
	-15	592
	-10	602
	-5	604
10	0	612
	5	630
	10	634
	15	634
	20	633
	25	628
	30	617
15	35	613
	40	608
	45	604
	50	596
	55	598
20	60	607
	65	617
	70	624
	75	638
	80	642
	85	645
25	90	659

Referring to table 5, from experimental results, it is found that the influence for the contrast is low as the azimuth angle of the diffraction grating **534** is 45 ± 15 degrees, the azimuth angle of the diffraction grating **544** is 90 ± 15 degrees, and the azimuth angle of the diffraction grating **554** is 135 ± 15 degrees. In this embodiment, as the included angle between the polarizing direction **505** of the polarizer of the light emitting side and the polarizing direction **515** of the polarizer of the light entering side is 90 degrees and the azimuth angle ψ_3 of the polarizing direction **505** of the polarizer of the light entering side is 135 degrees, the included angle from the polarizing direction **505** of the polarizer of the light emitting side to the grating direction of the diffraction grating **534** is 90 ± 15 degrees, the included angle from the grating direction of the diffraction grating **544** to the polarizing direction **505** of the polarizer of the light emitting side is 45 ± 15 degrees, and the included angle from the grating direction of the diffraction grating **554** to the polarizing direction **505** of the polarizer of the light emitting side is 0 ± 15 degrees. The included angle from the grating direction of the diffraction grating **544** to the tilt direction of the top layer liquid crystal molecule is -45 ± 15 degrees, the included angle from the grating direction of the diffraction grating **554** to the tilt direction of the top layer liquid crystal molecule is -90 ± 15 degrees, and the included angle from the grating direction of the diffraction grating **534** to the tilt direction of the top layer liquid crystal molecule is 0 ± 15 degrees. The included angle from the grating direction of the diffraction grating **544** to the aligning direction of the top layer alignment film is -45 ± 15 degrees, the included angle from the grating direction of the diffraction grating **554** to the aligning direction of the top layer alignment film is -90 ± 15 degrees, and the included angle from the grating direction of the diffraction grating **534** to the aligning direction of the top layer alignment film is 0 ± 15 degrees.

In one embodiment, the influence for the contrast is low as the azimuth angle of the diffraction grating **534** is -30 ± 10 degrees, the azimuth angle of the diffraction grating **544** is 15 ± 10 degrees, and the azimuth angle of the diffraction grating **554** is 60 ± 10 degrees. As the included angle between the polarizing direction **505** of the polarizer of the light

emitting side and the polarizing direction **515** of the polarizer of the light entering side is 90 degrees and the azimuth angle ψ_3 of the polarizing direction **505** of the polarizer of the light entering side is 135 degrees, the included angle from the grating direction of the diffraction grating **534** to the polarizing direction **505** of the polarizer of the light emitting side is 165 ± 10 degrees, the included angle from the grating direction of the diffraction grating **544** to the polarizing direction **505** of the polarizer of the light emitting side is 120 ± 10 degrees, and the included angle from the grating direction of the diffraction grating **554** to the polarizing direction **505** of the polarizer of the light emitting side is 75 ± 10 degrees. The included angle from the grating direction of the diffraction grating **544** to the tilt direction of the top layer liquid crystal molecule is 30 ± 10 degrees, the included angle from the grating direction of the diffraction grating **554** to the tilt direction of the top layer liquid crystal molecule is -15 ± 10 degrees, and the included angle from the grating direction of the diffraction grating **534** to the tilt direction of the top layer liquid crystal molecule is 75 ± 10 degrees. The included angle from the grating direction of the diffraction grating **544** to the aligning direction of the top layer alignment film is 30 ± 10 degrees, the included angle from the grating direction of the diffraction grating **554** to the aligning direction of the top layer alignment film is -15 ± 10 degrees, and the included angle from the grating direction of the diffraction grating **534** to the aligning direction of the top layer alignment film is 75 ± 10 degrees.

brightness at the zenith angle $\theta=0$ has the maximum value (58.92%) at the 232 gray level. At the observation angle of $(\theta,\psi)=(60,270)$, with increase of the deviation of the azimuth angle of the diffraction grating **544** of the diffractive optical element **522** from 0 degree increases, the difference value between the normalization brightness values at 232 gray level of $\theta=60$ and $\theta=0$ increases. The difference value has the maximum (39.71%) as the deviation reaches about 50 degrees, which is smaller than comparative example (58.9%). The difference value gets smaller than the maximum value after the deviation of about 50 degrees.

As a whole, even effect of the diffractive optical element **522** deviated about 60 degrees is poor, it is still better than that of comparative example. Therefore, the diffractive optical element **522** can be used in a deviation range of 0~60 degrees. In this embodiment, for improving the gray level reversion, the azimuth angle of the diffraction grating **534** is set at 135 ± 40 degrees, the azimuth angle of the diffraction grating **544** is set at 0 ± 40 degrees, and the azimuth angle of the diffraction grating **554** is set at 45 ± 40 degrees. For further improving the look-down angle characteristic, the azimuth angle of the diffraction grating **534** is set at 135 ± 20 degrees, the azimuth angle of the diffraction grating **544** is set at 0 ± 20 degrees, and the azimuth angle of the diffraction grating **554** is set at 45 ± 20 degrees. The included angle from the grating direction of the diffraction grating **534** to the polarizing direction of the polarizer of the light emitting side is 180 ± 20 degrees, the included angle from the grating

TABLE 6

azimuth angle of diffraction grating 544	$\theta = 45^\circ$ range for gray level reversion	Normalization brightness difference		Normalization brightness difference	
		between θ of 45° and 0° (gray level 224)	normalization difference at θ of 45°	between θ of 60° and 0° (gray level 232)	normalization difference at θ of 60°
comparative example	64~152	56.4%	—	58.9%	—
0	Non	37.68%	100.00%	31.49%	100.00%
10	Non	35.98%	95.50%	29.46%	93.57%
20	Non	37.44%	99.36%	33.52%	106.47%
30	Non	40.10%	106.43%	32.97%	104.69%
40	Non	41.50%	110.13%	34.47%	109.47%
45	Non	43.46%	115.34%	34.69%	100.65%
50	Non	41.85%	111.08%	39.71%	126.11%
60	Non	43.58%	115.68%	36.88%	117.12%

Referring to table 6, in comparative example, at an observation angle of $(\theta,\psi)=(45,270)$, the difference value between the normalization brightness at the zenith angle $\theta=45$ and the normalization brightness at the zenith angle $\theta=0$ has the maximum value (56.41%) at the 224 gray level. Therefore, the observation at the zenith angle $\theta=45$ is based on the 224 gray level. With increase of the deviation of the azimuth angle of the diffraction grating **544** of the diffractive optical element **522** from 0 degree increases, the difference value between the normalization brightness values at 224 gray level of $\theta=45$ and $\theta=0$ increases. The difference value has the maximum (43.58%) as the deviation reaches about 60 degrees, which is smaller than comparative example (56.4%). By comparing table 6 with table 1, it is found that the influence from rotating the diffractive optical element **522** is smaller than the influence from rotating the diffractive optical element **212**.

In comparative example, at an observation angle of $(\theta,\psi)=(60,270)$, the difference value between the normalization brightness at the zenith angle $\theta=60$ and the normalization

direction of the diffraction grating **544** to the polarizing direction of the polarizer of the light emitting side is 135 ± 20 degrees, and the included angle from the grating direction of the diffraction grating **554** to the polarizing direction of the polarizer of the light emitting side is 90 ± 20 degrees. In this embodiment, the included angle from the grating direction of the diffraction grating **544** to the tilt direction of the top layer liquid crystal molecule (such as the liquid crystal molecule **428a** in FIG. 34) is 45 ± 20 degrees, the included angle from the grating direction of the diffraction grating **554** to the tilt direction of the top layer liquid crystal molecule is 0 ± 20 degrees, and the included angle from the grating direction of the diffraction grating **534** to the tilt direction of the top layer liquid crystal molecule is 90 ± 20 degrees. The included angle from the grating direction of the diffraction grating **544** to the aligning direction of the top layer alignment film is 45 ± 20 degrees, the included angle from the grating direction of the diffraction grating **554** to the aligning direction of the top layer alignment film is 0 ± 20 degrees, and the included angle from the grating direction of

the diffraction grating 534 to the aligning direction of the top layer alignment film is 90 ± 20 degrees.

In some embodiments, the diffractive optical element is designed according to condition of the display device.

Referring to FIG. 49, the display device has a pixel 630. The pixel 630 comprises a pixel unit region 637, a pixel unit region 638 and a pixel unit region 639. For example, each of the pixel unit region 637, the pixel unit region 638 and the pixel unit region 639 has a long pixel side 647 and a short pixel side 648 adjacent to each other. The pixel unit region 637, the pixel unit region 638 and the pixel unit region 639 may be a red pixel unit region, a green pixel unit region, and a blue pixel unit region, respectively. In other embodiments, the pixel unit region may be not limited to three regions, and may be constituted by various colors. Generally, the length J of the short pixel side 648 is one-third as big as the length L of the long pixel side 647. In some embodiments, the pixel 630 may be for the single color for forming a black-and-white display device, and in this case, each of the pixel unit regions may have the pixel sides having equal lengths (not shown).

Referring to FIG. 49, in this embodiment, the long axis direction of the row constituted by the grating regions 653 and the long axis direction of the row constituted by the grating regions 663 are both substantially parallel to the direction of the short pixel side 648. The long axis direction of the column constituted by the grating regions 653 and the grating regions 663 arranged in alternation is substantially parallel to the direction of the long pixel side 647. In addition, in the row constituted by the grating regions 653, the period P_x between the grating region 653 is smaller than or equal to the length J of the short pixel side 648. In the row constituted by the grating regions 663, the period G_x of the grating regions 663 is also smaller than or equal to the length J of the short pixel side 648. Therefore, light for each of the pixel can get effect from at least one grating region 653 and at least one grating region 663. In some embodiments, in condition of fixing the grating structure unit and the grating density in the specific single pixel unit, the period P_x of the grating region 653 or the period G_x of the grating region 663 is not necessary to be smaller than or equal to the length J of the short pixel side 648, and thus can be bigger than the length J. For example, in the display device having the red, green and blue pixel unit regions arranged along the short pixel side cyclically, for the red pixel unit regions, the red pixels in one column have gratings, and the left (right) most next red pixels in column have no gratings or have gratings of other kinds of arrangement.

Referring to FIG. 49, in some embodiments, in the column constituted by the grating regions 653 and the grating regions 663, the period P_y of the grating regions 653 is smaller than or equal to the length L of the long pixel side 647. In the column constituted by the grating regions 663, the period G_y of the grating regions 663 is also smaller than or equal to the length L of the long pixel side 647. Therefore, light for each of the pixel can get effect from at least one grating region 653 and at least one grating region 663. In some embodiments, in condition of fixing the grating structure unit and the grating density in the specific single pixel unit, the period P_y of the grating region 653 or the period G_y of the grating region 663 is not necessary to be smaller than or equal to the length L of the short pixel side 647, and thus can be bigger than the length L. For example, along the long pixel side, one row has gratings, and the left (right) most next row has no gratings or has gratings of other kinds of arrangement.

The embodiment shown in FIG. 50 is different from the embodiment shown in FIG. 49 in that the long axis of the line constituted by the grating regions 673 and the grating regions 683 is not parallel to the short pixel side 668 and the long pixel side 667. In embodiments, the included angle g between the long axis of the line constituted by the grating regions 673 and the grating regions 683 arranged in alternation and the short pixel side 668 is bigger than 0 degree and smaller than 90 degrees. In addition, the grating axes of the grating region 673 and the grating region 683 follow the included angle g . In the period of the line constituted by the grating regions 673 and the grating regions 683 arranged in alternation, the period F between the grating region 673 and the grating region 683 is smaller than or equal to $J/\cos(g)$. J indicates the length of the short pixel side 668. The long axis of the line constituted by the grating regions 673 and the short pixel side 668 has the included angle $90-g$ therebetween. The long axis of the line constituted by the grating regions 683 and the short pixel side 668 has the included angle $90-g$ therebetween. In the line constituted by the grating regions 673 and the line constituted by the grating regions 683, the period V between the grating regions 673 and the period Y between the grating regions 683 are respectively smaller than or equal to $J/\cos(90-g)$. This structure arrangement can be used for resolving moiré issue, or adjusting the main diffraction direction of the diffractive element relative to the direction of the display device without changing the exiting whole arrangement.

Referring to FIG. 50, the compensate direction shifts by the angle g as the grating axes of the grating region 673 and the grating region 683 is shifted by the angle g with the whole arrangement. In this case, for maintaining the main diffraction direction as not rotating the angle g , the grating region 673 and the grating region 683 may be made without changing the grating axis directions of which as shown in FIG. 51.

The arrangement of the grating region can be adjusted according to actual demands. Referring to FIG. 52 and FIG. 53, for example, the grating region is arranged according to the corresponding pixel unit region. For example, the grating regions in the pixel unit region of the same color or the same structure, such as the single unit having three red, green and blue pixels or the single unit having multiple red, green and blue pixels, have the same arrangement method. Optionally, the grating regions in the pixel unit region of different colors or different structures, such as the single unit having three red, green and blue pixels or the single unit having multiple red, green and blue pixels, have different arrangement methods. For example, for the front view, the chromatic color of the white gray level is blue. For compensating chromatic difference of the white gray level from the front view (observation angle of $\theta=0$) of the display device, the grating density in the blue pixel unit region may be higher than the grating density in the red and green pixel unit region. In one embodiment as shown in FIG. 54, the pixel unit regions of the same color is designed to have the lines constituted by the same grating region. In addition, the location of the lines arranged in the pixels may be changed. As such, the optical moiré issue that would happen easily in the grating of the period structure can be avoided. In FIG. 55, the included angle between the line constituted by the grating regions and the pixel side may be adjusted properly, such as the same included angle g_1 in this embodiment. Referring to FIG. 56, in this embodiment, the lines constituted by the grating regions corresponding to the upper pixels and the pixel side have the same included angle g_2 therebetween. The lines constituted by the grating regions

corresponding to the lower upper pixels and the pixel side have various included angles g_3 , g_4 , g_5 , g_6 therebetween. Every pixel has the grating regions of substantially the same area by the method. Referring to FIG. 57, the lines constituted by the grating regions and the pixel side may have different included angles therebetween. Referring to FIG. 58, in this embodiment, the lines constituted by the grating regions corresponding to the upper pixels and the pixel side have the same included angle g_8 therebetween. The lines constituted by the grating regions corresponding to the lower pixels and the pixel side have the same included angle g_9 therebetween. The included angle g_8 and the included angle g_9 are respectively smaller than or bigger than 90 degrees. The embodiment shown in FIG. 59 may be a variation of the embodiment shown in FIG. 54. The embodiment shown in FIG. 59 is different from the embodiment shown in FIG. 54 in that, in FIG. 59, some grating regions are deviated from the long axis of the line. The deviation degree is limited to a range in the period between the lines, so that the pixels of the same characteristic, such as the same color or the same LC mode, etc. respectively have the grating region of the same area equally. The RGB pixel of each group has the grating arrangement of the grating regions having the periods $\wedge 1, \dots \wedge n$ therebetween. In some embodiments, the RGB pixels of different groups adjacent to each other may be designed to have different grating arrangements. The design can be adjusted as long as the period between the RGB pixels and the cycle structure of the grating can be reconstituted.

The line constituted by the grating regions and the pixel side may be designed to have different included angles therebetween for decreasing the moiré issue.

In embodiments, one experiment uses the Konica Minolta CS-2000 to measure the N101L6-L07 type liquid crystal display device having the diffractive optical element 462 ($S_1=9 \mu\text{m}$, $S_2=15 \mu\text{m}$, $S_3=9 \mu\text{m}$, $D_1=D_2=1 \mu\text{m}$, $K_1=K_2=28 \mu\text{m}$, referring to FIG. 2) as shown in FIG. 36. The white state and the black state of the 8"TN panel are measured. In addition, the contrast values of the 8"TN panel are calculated. In this embodiment, the condition of fixing $S_5=13 \mu\text{m}$ and adjusting the period between the grating regions, such as the gap distance=20 ($S_4=-8$), 23 ($S_4=-5$), 26 ($S_4=-2$), 29 ($S_4=1$), 32 ($S_4=4$), 35 ($S_4=7$), 38 ($S_4=10$), 41 ($S_4=13$), 44 μm ($S_4=16$), between the centers of the circles is used. The experiment results are shown in table 7.

TABLE 7

Period of grating	white state	black state	contrast	Area of first grating	Area of second grating
20	126	0.24	533	38.5%	18.8%
23	111	0.24	455	33.5%	18.8%
26	116	0.25	475	29.6%	18.8%
29	138	0.23	592	26.5%	18.8%
32	146	0.23	632	24.1%	18.8%
35	172	0.22	785	22.0%	18.8%
38	165	0.22	742	20.3%	18.8%
41	184	0.22	843	18.8%	18.8%
44	202	0.21	975	17.5%	18.8%

The ratio of the area of the grating region to the area of the diffractive optical element can be obtained by calculating. For example, in one embodiment, it is found that as the gap distance between the grating regions is 26 μm -41 μm , the contrast (equal to the brightness in the white state/the brightness in the black state) or the brightness in the white state of the display apparatus (comprising the TN type liquid

crystal display device) would change with the change of the gap distance between the grating regions with a linear relation roughly, as shown in FIG. 60. In the condition of $S_5+K_2=S_4+K_1=41 \mu\text{m}$, since the diffraction efficiency shows a substantial symmetrical result and thus can be used as a standard, the structure variation can be supposed correspondingly for increasing or decreasing the diffraction efficiency roughly. From the result shown in FIG. 60, it is obtained from calculations that as the gap distance between the grating regions (having the structure as shown in FIG. 2 is changed by 1 μm , the diffraction efficiency of the display apparatus would change by about 2.33%, that is, the normalization brightness would change by 2.3%. Therefore, for increasing/decreasing the whole oblique diffraction effect, the gap distance between the grating regions can be increase or decreased from 41 μm linearly. Similarly, the contrast may be driven out from the similar method. For example, for increasing the whole oblique diffraction effect (or decreasing the normalization brightness) by 10%, the gap distance between the grating regions should be creased from 41 μm by 2.1 μm . For example, for increasing the oblique diffraction by 10%, the gap distance between the grating regions should be 38.9 μm . For increasing the oblique diffraction by 20%, the gap distance between the grating regions should be 36.7 μm , and so forth. On the contrary, for increasing the normalization brightness (or decreasing the oblique diffraction effect) by 10%, the gap distance between the grating regions should be increased by 2.1 μm from 41 μm . For example, for increasing the normalization brightness by 10%, the gap distance between the grating regions should be 43.1 μm . For increasing the normalization brightness by 20%, the gap distance between the grating regions should be 45.3 μm , and so forth.

While the disclosure has been described by way of example and in terms of the exemplary embodiment(s), it is to be understood that the disclosure is not limited thereto. On the contrary, it is intended to cover various modifications and similar arrangements and procedures, and the scope of the appended claims therefore should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements and procedures.

What is claimed is:

1. A display apparatus, comprising:

a [liquid crystal] display device [comprising:];

[a backlight module; and

a liquid crystal panel comprising a first substrate, a second substrate and a liquid crystal layer, wherein the liquid crystal layer is disposed between the first substrate and the second substrate;]

a [first] polarizer disposed on the [first substrate] display device and having a polarizing direction;

[a second polarizer disposed between the second substrate and the backlight module, wherein polarizing directions of the first polarizer and the second polarizer have different azimuth angles;] and

a diffractive optical element disposed on a light emitting side of the [first] polarizer and having a first diffraction grating and a second diffraction grating, wherein grating directions of the first diffraction grating and the second diffraction grating have different azimuth angles, an included angle from the grating direction of the first diffraction grating to the polarizing direction of the [first] polarizer is 0 ± 20 degrees, and an included angle from the grating direction of the second diffraction grating to the polarizing direction of the [first] polarizer is 90 ± 20 degrees.

2. The display apparatus according to claim 1, wherein an included angle from the grating direction of the first diffraction grating to the polarizing direction of the [first] polarizer is 0 ± 15 degrees, an included angle from the grating direction of the second diffraction grating to the polarizing direction of the [first] polarizer is 90 ± 15 degrees.

[3. The display apparatus according to claim 1, wherein an included angle from the grating direction of the first diffraction grating to the polarizing direction of the first polarizer is 0 ± 10 degrees, an included angle from the grating direction of the second diffraction grating to the polarizing direction of the first polarizer is 90 ± 10 degrees.]

4. The display apparatus according to claim 1, wherein the diffractive optical element further comprises a third diffraction grating, wherein an azimuth angle of the third diffraction grating is different from the azimuth angles of the first diffraction grating and the second diffraction grating.

[5. The display apparatus according to claim 4, wherein an included angle from the grating direction of the third diffraction grating to the polarizing direction of the first polarizer is 135 ± 20 degrees.]

[6. The display apparatus according to claim 4, wherein an included angle from the grating direction of the third diffraction grating to the polarizing direction of the first polarizer is 135 ± 15 degrees.]

[7. The display apparatus according to claim 4, wherein an included angle from the grating direction of the first diffraction grating to the polarizing direction of the first polarizer is 0 ± 15 degrees, an included angle from the grating direction of the second diffraction grating to the polarizing direction of the first polarizer is 90 ± 15 degrees, an included angle from the grating direction of the third diffraction grating to the polarizing direction of the first polarizer is 135 ± 15 degrees.]

[8. The display apparatus according to claim 1, wherein an included angle between the polarizing direction of the first polarizer and the polarizing direction of the second polarizer is 90 degrees.]

[9. The display apparatus according to claim 1, wherein the azimuth angle of the polarizing direction of the first polarizer measured from a horizontal axis is 135 degrees.]

10. A display apparatus, comprising:

a liquid crystal display device for displaying an image and comprising:

a backlight module; and

a liquid crystal panel disposed on the backlight module and comprising:

a first substrate;

a first alignment film disposed on the first substrate;

a second substrate;

a second alignment film disposed on the second substrate, wherein aligning directions of the first alignment film and the second alignment film have different azimuth

angles; and

a liquid crystal layer disposed between the first alignment film and the second alignment film; and

a diffractive optical element disposed on a light emitting side of the liquid crystal display device and comprising

a first diffraction grating and a second diffraction grating, wherein an azimuth angle of a grating direction of the first diffraction grating is different from an azimuth angle of a grating direction of the second diffraction grating, an included angle from the grating direction of the first diffraction grating to the aligning direction of the first alignment film is 90 ± 20 degrees, an included

angle from the grating direction of the second diffraction grating to the aligning direction of the first alignment film is 0 ± 20 degrees.

11. The display apparatus according to claim 10, wherein an included angle from the grating direction of the first diffraction grating to the aligning direction of the first alignment film is 90 ± 15 degrees, an included angle from the grating direction of the second diffraction grating to the aligning direction of the first alignment film is 0 ± 15 degrees.

[12. The display apparatus according to claim 10, wherein an included angle from the grating direction of the first diffraction grating to the aligning direction of the first alignment film is 90 ± 10 degrees, an included angle from the grating direction of the second diffraction grating to the aligning direction of the first alignment film is 0 ± 10 degrees.]

13. The display apparatus according to claim 10, wherein the diffractive optical element further comprises a third diffraction grating, an azimuth angle of the third diffraction grating is different from the azimuth angles of the first diffraction grating and the second diffraction grating.

14. The display apparatus according to claim 13, wherein an included angle from the grating direction of the third diffraction grating to the aligning direction of the first alignment film is 45 ± 20 degrees.

[15. The display apparatus according to claim 13, wherein an included angle from the grating direction of the third diffraction grating to the aligning direction of the first alignment film is 45 ± 15 degrees.]

[16. The display apparatus according to claim 13, wherein an included angle from the grating direction of the first diffraction grating to the aligning direction of the first alignment film is 90 ± 10 degrees, an included angle from the grating direction of the second diffraction grating to the aligning direction of the first alignment film is 0 ± 10 degrees, an included angle from the grating direction of the third diffraction grating to the aligning direction of the first alignment film is 45 ± 10 degrees.]

[17. The display apparatus according to claim 10, wherein an included angle between the aligning direction of the first alignment film and the aligning direction of the second alignment film is 90 degrees.]

18. A liquid crystal display device for displaying an image, comprising:

a liquid crystal panel comprising:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein the liquid crystal layer comprises liquid crystal molecules, at least one of

the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, at least one

of the liquid crystal molecules adjacent to the second substrate has a second liquid crystal tilt direction, an

azimuth angle of the first liquid crystal tilt direction is different from an azimuth angle of the second liquid

crystal tilt direction; and

a diffractive optical element disposed on a light emitting side of the liquid crystal panel and comprising a first

diffraction grating and a second diffraction grating, wherein an azimuth angle of a grating direction of the

first diffraction grating is different from an azimuth angle of a grating direction of the second diffraction

grating, an included angle from the grating direction of the first diffraction grating to the first liquid crystal tilt

direction is 90 ± 20 degrees, an included angle from the

35

grating direction of the second diffraction grating to the first liquid crystal tilt direction is 0 ± 20 degrees.

19. The display apparatus according to claim 18, wherein an included angle from the grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 15 degrees, an included angle from the grating direction of the second diffraction grating to the first liquid crystal tilt direction is 0 ± 15 degrees.

[20. The display apparatus according to claim 18, wherein an included angle from the grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 10 degrees, an included angle from the grating direction of the second diffraction grating to the first liquid crystal tilt direction is 0 ± 10 degrees.]

21. The display apparatus according to claim 18, wherein the diffractive optical element further comprises a third diffraction grating, an azimuth angle of the third diffraction grating is different from the azimuth angles of the first diffraction grating and the second diffraction grating.

22. The display apparatus according to claim 21, wherein included angle from the grating direction of the third diffraction grating to the first liquid crystal tilt direction is 45 ± 20 degrees.

[23. The display apparatus according to claim 21, wherein an included angle from the grating direction of the third diffraction grating to the first liquid crystal tilt direction is 45 ± 15 degrees.]

[24. The display apparatus according to claim 21, wherein an included angle from the grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 10 degrees, an included angle from the grating direction of the second diffraction grating to the first liquid crystal tilt direction is 0 ± 10 degrees, an included angle from the grating direction of the third diffraction grating to the first liquid crystal tilt direction is 45 ± 10 degrees.]

25. The display apparatus according to claim 18, wherein an included angle between the first liquid crystal tilt direction and the second liquid crystal tilt direction is 90 degrees.

[26. The display apparatus according to claim 10, wherein the azimuth angle of the aligning direction of the first alignment film measured from a horizontal axis is 45 degrees.]

27. The display apparatus according to claim 18, wherein the azimuth angle of the first liquid crystal tilt direction measured from a horizontal axis is 45 degrees.

28. A display apparatus, comprising:

a display device for displaying an image; and
a diffractive optical element disposed on a light emitting side of the display device and having a first diffraction grating and a second diffraction grating, wherein grating directions of the first diffraction grating and the second diffraction grating have different azimuth angles, and the first diffraction grating and the second diffraction grating generate an intensity ratio of a total zero order diffraction light to a total non-zero order diffraction light lower than 100.

29. The display apparatus according to claim 28, wherein an area of the first grating regions occupies 17.5%~94% of an area of the diffractive optical element.

30. The display apparatus according to claim 28, wherein the display device further comprises pixel unit regions, each of the pixel unit regions has a long pixel side and a short pixel side adjacent to each other, and

a long axis direction of a line constituted by the first grating regions and a long axis direction of a line constituted by the second grating regions are substantially parallel to a direction of the short pixel side,

36

a long axis direction of a line constituted by the first grating regions and the second grating regions arranged in alternation is substantially parallel to a direction of the long pixel side.

31. The display apparatus according to claim 28, wherein the display device further comprises pixel unit regions, each of the pixel unit regions has a long pixel side and a short pixel side adjacent to each other, and

in a line constituted by the first grating regions, a period of the first grating regions is smaller than or equal to a length of the short pixel side,

in a line constituted by the second grating regions, a period of the second grating regions is smaller than or equal to a length of the short pixel side.

32. The display apparatus according to claim 28, wherein the display device further comprises pixel unit regions, each of the pixel unit regions has a long pixel side and a short pixel side adjacent to each other, and

in a line constituted by the first grating regions, a period of the first grating regions is smaller than or equal to a length of the long pixel side,

in a line constituted by the second grating regions, a period of the second grating regions is smaller than or equal to a length of the long pixel side.

33. The display apparatus according to claim 28, wherein the display device further comprises pixel unit regions, each of the pixel unit regions has a long pixel side and a short pixel side adjacent to each other, and

a long axis of a line constituted by the first grating regions and the second grating regions arranged in alternation and the short pixel side have an included angle θ therebetween, wherein the included angle θ is bigger than 0 degree and smaller than 90 degrees, in the line constituted by the first grating regions and the second grating regions arranged in alternation, a period between the first grating regions and the second grating regions is equal to or smaller than $J/\cos(\theta)$, wherein J is a length of the short pixel side;

a long axis of a line constituted by the first grating regions and a long axis of a line constituted by the second grating region respectively have included angles $90-\theta$ with the short pixel side, in the line constituted by the first grating regions and the line constituted by the second grating region, a period between the first grating regions and the second grating regions is equal to or smaller than $J/\cos(90-\theta)$.

34. A display apparatus, comprising:

a display device for displaying an image; and
a diffractive optical element disposed on a light emitting side of the display device, comprising:

a first diffraction grating, which generates an intensity ratio of a total zero order diffraction light to the light having an emitting direction different from an incident direction by a deflection angle bigger than 15 degrees lower than 100.

35. The display apparatus according to claim 34, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 0 ± 20 degrees.

36. The display apparatus according to claim 34, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from

37

a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 135 ± 20 degrees.

37. The display apparatus according to claim 34, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 45 ± 20 degrees.

38. The display apparatus according to claim 34, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 90 ± 20 degrees.

39. The display apparatus according to claim 34, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from a first grating direction of the first diffraction grating to a aligning direction of the alignment film is 45 ± 20 degrees.

40. The display apparatus according to claim 34, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from a first grating direction of the first diffraction grating to a aligning direction of the alignment film is 90 ± 20 degrees.

41. The display apparatus according to claim 34, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from a first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 45 ± 20 degrees.

42. The display apparatus according to claim 34, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from a first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 20 degrees.

43. The display apparatus according to claim 34, wherein the diffractive optical element further comprises:

a second diffraction grating, wherein a first grating direction of the first diffraction grating and a second grating direction of the second diffraction grating are different.

38

44. The display apparatus according to claim 43, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 0 ± 20 degrees.

45. The display apparatus according to claim 43, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 135 ± 20 degrees.

46. The display apparatus according to claim 43, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 45 ± 20 degrees.

47. The display apparatus according to claim 43, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 90 ± 20 degrees.

48. The display apparatus according to claim 43, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from the first grating direction of the first diffraction grating to a aligning direction of the alignment film is 45 ± 20 degrees.

49. The display apparatus according to claim 43, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from the first grating direction of the first diffraction grating to a aligning direction of the alignment film is 90 ± 20 degrees.

50. The display apparatus according to claim 43, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from the first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 45 ± 20 degrees.

51. The display apparatus according to claim 43, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the

39

liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from the first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 20 degrees.

52. The display apparatus according to claim 43, wherein the diffractive optical element further comprises:

a third diffraction grating, wherein the first grating direction of the first diffraction grating, the second grating direction of the second diffraction grating and a third grating direction of the third diffraction grating are different.

53. The display apparatus according to claim 52, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 0 ± 20 degrees.

54. The display apparatus according to claim 52, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 135 ± 20 degrees.

55. The display apparatus according to claim 52, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 45 ± 20 degrees.

56. The display apparatus according to claim 52, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from the first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 90 ± 20 degrees.

57. The display apparatus according to claim 52, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from the first grating direction of the first diffraction grating to a aligning direction of the alignment film is 45 ± 20 degrees.

58. The display apparatus according to claim 52, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from the first grating direction of the first diffraction grating to a aligning direction of the alignment film is 90 ± 20 degrees.

59. The display apparatus according to claim 52, wherein the display device comprises:

a first substrate;

a second substrate; and

40

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from the first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 45 ± 20 degrees.

60. The display apparatus according to claim 52, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from the first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 20 degrees.

61. A display apparatus, comprising:

a display device for displaying an image; and

an optical film disposed on a light emitting side of the display device, wherein the optical film is a stacked structure comprised by:

a first diffractive optical element, comprising a first diffraction grating, wherein the first diffraction grating generates an intensity ratio of a total zero order diffraction light to the light having an emitting direction different from an incident direction by a deflection angle bigger than 15 degrees lower than 100; and

a second diffractive optical element, comprising a second diffraction grating.

[62. The density apparatus according to claim 61, wherein the first diffraction grating generates an intensity ratio of a total zero order diffraction light to the light having an emitting direction different from an incident direction by a deflection angle bigger than 15 degrees lower than 100.]

63. The display apparatus according to claim 61, further comprising:

a polarizer disposed between the display device and the optical film, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 0 ± 20 degrees.

64. The display apparatus according to claim 61, further comprising:

a polarizer disposed between the display device and the optical film, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 135 ± 20 degrees.

65. The display apparatus according to claim 61, further comprising:

a polarizer disposed between the display device and the optical film, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 45 ± 20 degrees.

66. The display apparatus according to claim 61, further comprising:

a polarizer disposed between the display device and the optical film, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 90 ± 20 degrees.

67. The display apparatus according to claim 61, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from a first grating direction of the first diffraction grating to a aligning direction of the alignment film is 45 ± 20 degrees.

68. The display apparatus according to claim 61, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from a first grating direction of the first diffraction grating to a aligning direction of the alignment film is 90 ± 20 degrees.

69. The display apparatus according to claim 61, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from a first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 45 ± 20 degrees.

70. The display apparatus according to claim 61, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from a first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 20 degrees.

71. The display apparatus according to claim 61, wherein the first diffraction grating and the second diffraction grating are overlapping.

72. A display apparatus, comprising:

a display device for displaying an image; and

a diffractive optical element disposed on a light emitting side of the display device, comprising:

a first diffraction grating; and

a second diffraction grating, wherein the first diffraction grating generates an intensity ratio of a total zero order diffraction light to the light having an emitting direction different from an incident direction by a deflection angle bigger than 15 degrees lower than 100 and the first diffraction grating and the second diffraction grating are overlapping.

73. The display apparatus according to claim 72, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 0 ± 20 degrees.

74. The display apparatus according to claim 72, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 135 ± 20 degrees.

75. The display apparatus according to claim 72, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 45 ± 20 degrees.

76. The display apparatus according to claim 72, further comprising:

a polarizer disposed between the display device and the diffractive optical element, and an included angle from a first grating direction of the first diffraction grating to a polarizing direction of the polarizer is 90 ± 20 degrees.

77. The display apparatus according to claim 72, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from a first grating direction of the first diffraction grating to a aligning direction of the alignment film is 45 ± 20 degrees.

78. The display apparatus according to claim 72, wherein the display device comprises:

a first substrate;

a second substrate;

a liquid crystal layer disposed between the first substrate and the second substrate; and

an alignment film disposed between the first substrate and the liquid crystal layer, wherein an included angle from a first grating direction of the first diffraction grating to a aligning direction of the alignment film is 90 ± 20 degrees.

79. The display apparatus according to claim 72, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from a first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 45 ± 20 degrees.

80. The display apparatus according to claim 72, wherein the display device comprises:

a first substrate;

a second substrate; and

a liquid crystal layer disposed between the first substrate and the second substrate, wherein at least one of the liquid crystal molecules adjacent to the first substrate has a first liquid crystal tilt direction, and an included angle from a first grating direction of the first diffraction grating to the first liquid crystal tilt direction is 90 ± 20 degrees.