



US00RE47738E

(19) **United States**
(12) **Reissued Patent**
Cooper

(10) **Patent Number: US RE47,738 E**
(45) **Date of Reissued Patent: Nov. 26, 2019**

(54) **JOINT FOR USE IN AIRCRAFT CONSTRUCTION**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **Airbus Operations Limited**, Bristol (GB)

DE 704327 3/1941
GB 1022131 3/1966

(Continued)

(72) Inventor: **Paul Anthony Cooper**, Bristol (GB)

OTHER PUBLICATIONS

(73) Assignee: **AIRBUS OPERATIONS LIMITED**, Bristol (GB)

English language machine translation of DE 704327, 3 pgs (retrieved from http://translationportal.epo.org/emtp/translate/?ACTION=description-retrieval&COUNTRY=DE&ENGINE=google&FORMAT=docdb&KIND=C&LOCALE=en_EP&NUMBER=704327&OPS=ops.epo.org/3.2&SRCLANG=de&TRGLANG=en).*

(21) Appl. No.: **13/886,454**

(22) Filed: **May 3, 2013**

(Continued)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,909,290**
Issued: **Mar. 22, 2011**
Appl. No.: **12/097,328**
PCT Filed: **Nov. 28, 2006**
PCT No.: **PCT/GB2006/004439**
§ 371 (c)(1),
(2) Date: **Jun. 13, 2008**
PCT Pub. No.: **WO2007/071905**
PCT Pub. Date: **Jun. 28, 2007**

Primary Examiner — Robert M Fetsuga

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(30) **Foreign Application Priority Data**

Dec. 20, 2005 (GB) 0525896.7

(51) **Int. Cl.**
B64C 1/12 (2006.01)
B64C 3/26 (2006.01)

(52) **U.S. Cl.**
CPC . **B64C 3/26** (2013.01); **B64C 1/12** (2013.01)

(58) **Field of Classification Search**
CPC B64C 3/26; B64C 1/12
See application file for complete search history.

(57) **ABSTRACT**

A joint for use in aircraft construction, for example a wing, comprises: a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface; and a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end. The first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap. The exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap. The first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface.


(56) **References Cited**

U.S. PATENT DOCUMENTS

4,507,011 A * 3/1985 Brown 403/404
4,888,451 A 12/1989 Toni et al.

(Continued)

35 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,803,406 A * 9/1998 Kolodziej et al. 244/171.7
6,375,120 B1 * 4/2002 Wolnek 244/123.8
7,021,856 B2 * 4/2006 Assler et al. 403/408.1
7,296,656 B2 * 11/2007 Sanicki et al. 181/210
2004/0070260 A1 * 4/2004 Chung et al. 301/59
2005/0213278 A1 9/2005 Hawley
2006/0032982 A1 * 2/2006 Stephens 244/131
2006/0251496 A1 * 11/2006 Wood et al. 411/507
2008/0164376 A1 * 7/2008 Kato et al. 244/132
2010/0006702 A1 * 1/2010 Fogarty et al. 244/131
2010/0065688 A1 * 3/2010 Wood 244/131
2010/0077690 A1 * 4/2010 Durand 52/578

FOREIGN PATENT DOCUMENTS

JP 63-240494 10/1988
WO 82/00313 A1 2/1982

OTHER PUBLICATIONS

GB Search Report for GB0525896.7 dated Apr. 5, 2006. ISR for
PCT/GB2006/004439 dated Mar. 16, 2007.

* cited by examiner

Fig. 1
(Prior art)




Fig. 2
(Prior art)




Fig. 3
(Prior art)




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13





Fig. 14



JOINT FOR USE IN AIRCRAFT CONSTRUCTION

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

RELATED APPLICATIONS

The present application is a *Reissue of U.S. Pat. No. 7,909,290 B2*, which is based on International Application Number PCT/GB2006/004439 filed Nov. 28, 2006, and claims priority from British Application Number 0525896.7 filed Dec. 20, 2005, the disclosures of which are hereby incorporated by reference herein in their entirety.

FIELD OF THE INVENTION

The present invention relates to an improved joint arrangement suitable for use in aircraft construction. More particularly, although not exclusively, the present invention relates to an improved cover skin joint construction which is particularly suitable for joining aircraft components which have dissimilar physical properties. Even more particularly, although not exclusively, the present invention relates to an improved butt-strap and wing-skin cover joint for use in an aircraft wing for joining composites and metals.

BACKGROUND ART

Aircraft components including items such as wing skins and other panels are increasingly being made from composite materials, for example laminates. Direct attachment of leading and trailing edge structures, such as leading and trailing edge panels, to the wing skin is often impractical when using laminates. Pre-moulded precision-fit joints, known as joggles, are difficult to manufacture in thick laminates, would increase overhang size and may adversely affect the mechanical properties of the laminate. Furthermore, it is difficult to provide effective panel attachment through thick laminates.

It is known to fasten the leading and trailing edge panels of a wing to the wing skin using butt-straps located along the joint between the leading and trailing edges panels and the wing skin. These butt-straps secure the panels in place and ensure that the leading and trailing edges of the panels are properly aligned with the corresponding trailing and leading edges of the wing skin.

Conventionally, a metallic butt-strap **10** is used as shown in cross-section in FIG. 1. The butt-strap is attached to the inner mould line (IML) face of the wing skin that generally faces towards the interior of the wing. Prior art butt-strap **10** has a stepped, z-shaped profile, with a short vertical portion **10a** joining two horizontal plate portions **10b,c**. In this example, plate **10b** fits over a portion of the IML face of cover **20** of the aircraft's wing skin such that the leading edge of cover **20** butts up against vertical portion **10a**. This is bolted in place with bolt **30** that is countersunk into cover **20** on its outer-mould-line (OML) face.

Plate **10c** is attached to the structure that is to be fixed to the leading edge of the cover. For example a "D"-nose leading edge skin **40** is shown attached to a wing cover leading edge **50** (FIG. 2). In order to reduce erosion of the

composite skin **20** by airflow **60**, the "D"-nose skin **40** is usually chosen to be sufficiently thick to overhang the leading edge **50** of cover **20**. However, it is found that aerodynamic erosion still occurs and the increased thickness also increases drag. Aerodynamic erosion is often exacerbated when composite materials are used.

The prior-art butt-strap is also vulnerable to bird strike and similar collisions. FIG. 3 shows schematically how an impact on the leading-edge structure (not shown) attached by butt-strap **10** can lead to catastrophic forces on bolt **30**.

The present invention seeks to ameliorate at least some of the abovementioned problems.

DISCLOSURE OF THE INVENTION

In a first aspect, the invention provides a joint for use in aircraft construction comprising:

- (i) a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface;
- (ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface.

The continuous exterior surface may correspond to a continuous curved or planar surface. The continuous exterior surface may be smooth or substantially smooth.

In a preferred embodiment, the thickness of the first portion of the butt-strap at the junction is non-zero but preferably small compared to the thickness of the cover skin. Where the thickness of the first portion of the butt-strap is non-zero, the first portion of the butt-strap is located so that a substantially continuous exterior surface is formed at said junction. The first portion of the butt-strap may be located so that, adjacent to the junction, the exterior surface of the skin is substantially coplanar with the exterior surface of the first portion of the butt-strap. The first portion of the butt-strap may be located so that, adjacent to the junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a curved substantially continuous exterior surface.

The joint may include filler or a filler plate located in the recess formed by the distal end or edge of the first portion and the exterior surface of the cover skin adjacent the junction. The first portion of the butt-strap tapers towards its distal end, and may give the first portion a wedge-shaped profile. The tapering portion may form an angle of about 3° at its distal portion. The skin may be of substantially the same thickness in the proximal portion and in the distal portion and the distal portion may be offset from the proximal portion at an angle that orients the exterior-facing surface of the distal portion so that it is complementary to the tapering first portion of the butt-strap.

The first portion of the butt-strap may be connected to the skin by a fastener, for example a bolt, including a tapered washer or a tapered collar.

3

The butt-strap may comprise a second portion for connection to an aircraft structure such as a leading-edge or trailing-edge structure.

The cover skin may be made of a composite material. The butt-strap may be metallic.

The wing may further comprise a filler plate arranged to fill a space between the aircraft structure and the second portion of the butt-strap. The plate may be wedge-shaped.

The distal portion of the skin may be truncated at the upper or lower surface of its distal end. The truncated region may be of a shape complementary to the shape of a third portion of the butt-strap, the third portion being between the first portion and the second portion. The truncated region may act to retain the skin against the butt-strap.

The proximal portion and the distal portion of the second surface of the skin may meet to form a step region. A distal end of the butt-strap may be retained by the step region.

A plurality of said butt-straps may be spliced together by connection to an aircraft structure such as a leading- or trailing-edge structure. Alternatively, each butt strap may extend continuously under said structure.

The butt-strap may comprise a portion that extends into a pylon region of the wing. The distal portion of the skin may extend over the pylon portion of the butt-strap.

In a further aspect, the invention provides an aerodynamic surface, such as a wing, fin or horizontal stabilizer or the like, incorporating a joint as hereinbefore defined.

The exterior-facing surface of the distal portion of the skin may have been formed in a first region of the wing's leading or trailing edge by moulding and in a second region of the wing's leading or trailing edge by machining. The moulded region of the distal portion may run parallel to spars of the wing. The machined region may be located at an undercarriage rib of the wing.

The skin may comprise conductive foil and there may be electrical continuity between the butt-strap and said foil.

It may be that cut edges of the leading edge of the skin are protected, at least partially by the butt-strap, so that they are not exposed to the air stream in flight.

In an alternative embodiment, the second portion of the butt-strap may have the same form as the first portion of the butt-strap as hereinbefore defined and function in a similar manner as said first portion.

In a second aspect, the invention provides a method of manufacturing a joint for use in aircraft construction comprising forming a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface, forming a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end wherein the method further comprises connecting the first portion of the butt-strap to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface.

The exterior-facing surface of the distal portion of the skin may be formed by moulding. The moulding may be carried out using a tool, shaped to form the exterior surface of the proximal portion, including an add-on to form the exterior-surface of the distal portion of the skin. The moulding may

4

be carried out using a tool shaped to form both the exterior surface of the proximal portion and the exterior-facing surface of the distal portion of the skin.

The exterior-facing surface of the distal portion of the skin may be formed by machining. The exterior-facing surface of the distal portion of the skin may be formed by moulding in a first region of the aircraft component, such as a wing, and by machining in a second region.

The butt-strap and skin may be bonded together prior to being joined by a fastener.

A third aspect of the invention provides an aircraft constructed using one or more joints as hereinbefore defined.

It will be appreciated that aspects of the present invention described in relation to the method of the present invention are equally applicable to the apparatus of the present invention and vice versa.

BRIEF DESCRIPTION OF THE DRAWINGS

Certain illustrative embodiments of the invention will now be described in detail, by way of example only, with reference to the accompanying schematic drawings, in which:

FIG. 1 is a cross-sectional view in an inboard direction of a prior-art butt-strap attached to the leading edge of the skin of an aircraft wing;

FIG. 2 shows the arrangement of FIG. 1 further including a portion of D-nose skin;

FIG. 3 is an illustration of the effects of bird strike on the arrangement of FIG. 1;

FIG. 4 is a cross-sectional view in an inboard/outboard direction of a butt-strap according to an embodiment of the present invention attached to the leading edge of the skin of an aircraft wing;

FIG. 5 shows installation of the butt-strap of FIG. 4 at a leading- or trailing-edge fitting;

FIG. 6 shows a detail of the butt-strap and cover of FIG. 5;

FIG. 7 shows another detail of the butt-strap and spar of FIG. 5;

FIG. 8 is a cross-sectional view in an aft direction of the butt-strap of FIG. 5, through AA;

FIG. 9 is a cross-sectional view in an inboard direction of an installation of the butt-strap of FIG. 4 at a pylon grow-out;

FIG. 10 shows an aircraft wing, in which areas to receive the butt-strap of FIG. 4 are marked according to the method used to profile those areas;

FIG. 11 shows three configuration options (a) to (c) for a skin tool for moulding the wing-skin;

FIG. 12 shows blending of the butt-strap of FIG. 4 into the wing skin;

FIG. 13 is an illustration of the effects of bird strike on the arrangement of FIG. 4; and

FIG. 14 shows lighting protection arrangements for the butt-strap of FIG. 4.

DETAILED DESCRIPTION

Referring to FIG. 4, an embodiment of a butt-strap 100 is shown in profile and is seen to be in the form of a mildly stepped, z-shaped profile, with a short vertical portion 100a joining two horizontal plate portions 100b,c. According to this embodiment, plate 100b has a wedge-shaped profile, tapering from its thickest point near the vertical portion 100a to a thin, distal end. In a preferred variant, the thickness of the first portion at the junction formed by the exterior surface

of the cover skin at the exterior surface of the butt-strap (i.e.; the distal end) is zero. When the joint is created, this would form an essentially perfect planar seam joining the cover and the butt-strap. However, in practice, most practical embodiments will have a small, but non-zero thickness at the distal end of the first portion such as shown in FIG. 4. According to this particular embodiment, the interior, tapering surface forms an angle of about 3° with the exterior face of plate **100b**.

Butt-strap **100** is bolted in place on the OML of cover **200** with bolt **30**, which is countersunk into tapered plate **100b** on its exterior face. Cover **200** comprises a proximal portion **207**, which forms most of the wing skin and a distal, angled portion **205**. The exterior-facing surface of distal portion **205** recedes at an angle of 3° from the exterior surface of the proximal portion of cover **200**. In that way, the exterior-facing surface of distal portion **205**, in this example at its leading edge, is of a shape complementary to the shape of the interior, tapering surface of butt-strap plate **100b**. The exterior surface of the proximal portion **207** of cover **200** and the exterior surface of plate **100b** thus form a substantially continuous surface of the wing. This ideally forms a continuous planar exterior surface.

The butt-strap **100** may be extruded or machined from aluminium plate, depending on the complexity of the skin contour it needs to match. Internally, where there are no fittings, the fastener collars sit on tapered washers or have collars **35** that accommodate the 3° angle (as shown in FIG. 4).

The butt-strap **100** in this example is used (FIG. 5) to secure a leading edge fitting **70** to cover **200**. Throughout the wing, where leading edge/trailing edge (LE/TE) fittings are present, tapered aluminium plates **90** are installed, to level off the angle of the taper **205** of cover **200**, provide adjustment to accommodate the various interface tolerances, to act as spreader plates for the fittings **70**, and to act as electrical bonding straps.

Leading edge fitting **70** butts up against spar **80** and the distal end of cover portion **205**, which it overlaps by approximately the length of the butt-strap **100**. Because of the angled portion **205** of cover **200**, there is a wedge-shaped gap between fitting **70** and cover **200**. This is filled in with tapered plate **90**, through which bolt **30** also passes.

The butt-straps **100** and internal plates **90** are bonded onto the cover **200** prior to the installation of fastener **30**. Use of a paste adhesive/shim material such as Hysol EA934 allows for the setting of the various dimensions of the construction. A combination of fore/aft movement of the taper and the use of liquid shim provides sufficient freedom of adjustment to achieve the correct dimensional fit-up.

The fit of the LE/TE fittings **70** themselves is dependent on the girth tolerance for spar **80** and the angular relationship between the spar web and the pads on the covers **200**. As such tolerance management is demanding and may require shimming/fettling of these components on assembly, as is done on prior-art metal wings.

The distal end of the angled portion **205** of cover **200** may also be truncated at its lower edge (FIG. 6), forming a more steeply tapered surface **208** that butts up against a corresponding sloped surface **108** on vertical portion **100a** of butt-strap **100**. The leading edge of the skin portion **205** is thus retained in place against butt-strap **100**.

The arrangement of spar **80** and cover **200** is shown in more detail in FIG. 7. Heel line **120** is the line at which the plane coincident with the outer mould line of the angled portion **205** of cover **200**, if extended sufficiently, would meet the outer surface of the rest of cover **200**. Heel line **120**

is in line with the leading edge of spar **80**. That extended plane is not the true outer surface of cover **200**. Rather, the angled portion of cover **200** stops short of the non-angled portion, which is itself extended beyond heel line **120**, thus forming step **130**, which acts to constrain aft-ward movement of the distal end of portion **100b**.

Leading edge fitting **70** is used to splice sections of butt-strap **100** together (FIG. 8). In an alternative embodiment, (not shown) butt-strap **100** runs continuously under fitting **70**.

All regions that would otherwise have aluminium in contact with the cover **200** or spar **80** are faced with glass cloth to inhibit corrosion.

At a pylon "grow-out" (FIG. 9), the angled distal portion of cover **200'** does not form the ultimate distal end of cover **200'**, but rather leads into a further distal portion that is parallel to (but displaced from) the rest of the non-angled cover **200'**. Cover **200'** thus extends over plate **100c** of butt-strap **100** at pylon grow-out regions of the wing.

The (reflex-) angled portion **205** of cover **200** is moulded into the cover in some regions **270** of, for example, the aircraft wing **250** and machined in other regions **260** (FIG. 10). The butt-strap **100** runs parallel to the front and rear spars of wing **250** for most of the wing's length (dashed line in FIG. 10). At the undercarriage rib it deviates and follows the (shark's fin) contour of the skin in that area **260** (solid line in FIG. 12). At the front spar pylon area **275**, however, the strap **100** continues parallel to the front spar (FIGS. 9 and 10). The strap **100** can either be extended forward as illustrated in FIG. 9 or a separate section can be added forward, effectively to extend the leading edge panel land. In both cases this extra material acts as a spreader plate or reinforcement for the pylon fitting.

The angle to be moulded at the cover edges requires early definition, especially if the skin tool itself is to be manufactured to this profile. As discussed above, the angle is moulded parallel to the front or rear spars (with the exception of the outboard section **260** of the "sharks fin"). Thus only a small amount of detail definition is required to establish the location of the start (heel line **110**) of the 3° angle. The heel line **110** is positioned close to the centre of the chord to provide maximum flexibility to fastener and part edge changes later in the design (albeit possibly at a small weight penalty).

It will be apparent from the above discussion that use of an external butt-strap has implications for the cover **200's** outer mould line. Moulding the cover to accept the butt-strap is preferable from an engineering standpoint. The feature can be accommodated into the tooling in two principal ways: (1) by machining the tool **180** so that it incorporates the additional taper (FIGS. 11c); and (2) by adding separate tapered features **170** to the tool, for example by bolting them on post completion of the main tool **160** (FIG. 11a & b).

Machining the tool is preferable from a cost cure cycle perspective but has the disadvantage of requiring definition very early on in the manufacturing programme. The major drawback of using additional "bolt-on" components is the adverse effect that has on the thermal properties of the tool, which must be accounted for in tool design and component cure cycle.

As an alternative to moulding the taper profile into the cover **200**, a third option is to machine the angle post-cure. That may be the preferred approach where moulding of the feature is difficult or impractical, for example in regions difficult to tape lay or where component wrinkling is expected. Generally, the cover **200** is likely to be particularly thick (for example, thicker than 20 mm) in such areas and so

machining the taper and exposing fibres is likely to be of little structural consequence. Further, it is envisaged that any delamination that does occur will be restrained by bolts **30** at the butt-strap **100**, spar **80** and LE/TE fittings **70**. It is envisaged that tooling of the 3° additional taper will be acceptable for most areas **270** of the outer part of the wing **250**, as the angle is shallow and there are no other adjacent tooling complexities. At the gear rib **260**, however, the feature follows the contour of the “sharks fin” and tape-laying difficulties and ply wrinkling could be experienced in this region, so post-cure machining of the cover is used in these regions **260**, with transition regions to blend the machined profile back into the moulded profile.

The external butt-strap arrangement produces, in some embodiments an extra gap/step between strap **100** and cover **200** on the aerodynamic surface (FIG. **12**). The butt-strap **100** is set onto the skin as part of the skin assembly. As previously described, the strap **100** is bonded/shimmed into place using a suitable adhesive **230** to ensure compliance with the OML **240** as the primary datum. Additionally the taper of the strap **100** can be used to gain adjustment by moving the component fore and aft over the skin. If that results in a foul with the resin edge on the skin, the butt-strap **100** can be fettled to fit. As can be seen in FIG. **12** the skin moulding process will leave a resin edge **210** that together with the butt-strap **100** will provide a distinct “channel” to retain any aero filler **220** required to complete the transition.

The external butt-strap approach of the invention provides the benefit of erosion protection of the composite cover **200** by ensuring that there are no cut edges of the cover **200** exposed to the air stream, an important consideration at the leading edge, rather, the cut edge of the cover **200** is inside the wing, shielded by butt-strap **100**. In contrast, the internal butt-strap arrangement of the prior art (FIG. **2**) results in the composite cover **200** having an exposed edge **50** which is susceptible to aerodynamic erosion.

Because butt-strap **100** sits outside the angled portion of cover **200**, bird-strike resistance is also improved (FIG. **13**). The force resulting from an impact on plate **100b** or **100c** will be passed in a large part directly into cover **200**, without putting bolt **30** into excessive tension (c.f. FIG. **3**).

The butt-strap arrangement also forms part of the aircraft’s lightning protection scheme by providing conducting paths for current resulting from a lightning strike (FIG. **14**). There are four distinct conducting paths for the current: at each butt-strap location on the upper and lower, leading and trailing edges. Each conducting path, whilst separate from the others, forms a continuous path in which the current can flow, with electrical continuity between the butt-strap sections **100** and to the bronze mesh/foil **280** in the cover **200** itself.

Continuity between butt-strap sections **100** can be achieved by the arrangement of FIG. **8**. Established joining techniques should ensure good electrical bonding

Connection to bronze mesh/foil **280** is achieved in this example via a conducting sleeve **290** around bolt **30** (FIG. **14(b)**). Attempting to link the butt-strap **100** directly to the mesh/foil **290** is not appropriate due to the potential for corrosion. Alternative arrangements include connecting butt-strap **100** to mesh/foil **280** via bolts **30**, either at the bolt’s head (FIG. **14(a)**) or at a region along its length (FIG. **14(c)**).

Whilst the present invention has been described and illustrated with reference to particular embodiments, it will be appreciated by those of ordinary skill in the art that the invention lends itself to many different variations not spe-

cifically illustrated herein. Some examples of such variations and alternatives have been described above.

Where in the foregoing description, integers or elements are mentioned which have known, obvious or foreseeable equivalents, then such equivalents are herein incorporated as if individually set forth. Reference should be made to the claims for determining the true scope of the present invention, which should be construed so as to encompass any such equivalents. It will also be appreciated by the reader that integers or features of the invention that are described as preferable, advantageous, convenient or the like are optional and do not limit the scope of the independent claims.

The invention claimed is:

[1. A joint for use in aircraft construction comprising:

- (i) a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface;
- (ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface.]

2. A joint as claimed in claim **[1]** **9**, wherein the thickness of the first portion of the butt-strap at the junction is small compared to the thickness of the cover skin.

3. A joint as claimed in claim **2**, wherein the thickness of the distal end of the first portion of the butt-strap is substantially zero.

4. A joint as claimed in claim **[1]** **9**, wherein the first portion of the butt-strap is located so that, adjacent to the junction, the exterior surface of the skin is substantially coplanar with the exterior surface of the first portion of the butt-strap.

[5. A joint as claimed in claim **1**, wherein the first portion of the butt-strap is located so that, adjacent to the junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a curved substantially continuous exterior surface.]

6. A joint [as claimed in claim **1**] for use in aircraft construction comprising:

- (i) a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface;
- (ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface, wherein the joint

9

includes filler [or a filler plate] located in a [recess] channel formed by the distal end of the first portion of the butt-strap and the exterior surface of the cover skin adjacent the junction.

7. A joint as claimed in claim [1] 9, wherein the first portion is wedge-shaped.

8. A joint as claimed in claim [1] 9, wherein the tapering portion forms an angle of approximately 3° at its distal portion.

9. A joint [as claimed in claim 1] for use in aircraft construction comprising:

(i) a cover skin having an interior surface, an exterior surface and a distal portion said distal portion having an exterior-facing surface;

(ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface, wherein the skin is of substantially the same thickness in the proximal portion and in the distal portion and the distal portion is offset from the proximal portion at an angle that orients the exterior-facing surface of the distal portion so that it is complementary to the tapering first portion of the butt-strap.

10. A joint as claimed in claim [1] 9, wherein the first portion of the butt-strap is connected to the skin by a fastener.

[11. A joint as claimed in claim 1, wherein the butt-strap comprises a second portion for connection to an aircraft structure.]

12. A joint as claimed in claim [1] 9, wherein the butt-strap comprises a second portion for connection to an aircraft structure, and wherein the aircraft structures include a leading-or trailing-edge structure.

13. A joint as claimed in claim [1] 9, wherein the cover skin is made of a composite material.

14. A joint as claimed in claim [1] 9, wherein the butt-strap is made of a metallic material.

[15. A joint as claimed in claim 1, further comprising a filler plate arranged to fill a space between the aircraft structure and the second portion of the butt-strap.]

[16. A joint as claimed in claim 15 wherein the plate is wedge-shaped.]

17. A joint as claimed in claim [1] 9, wherein the distal portion of the skin is truncated at the upper or lower surface of its distal end.

18. A joint as claimed in claim 17 wherein the truncated region has a shape complementary to the shape of a third portion of the butt-strap, the third portion being between the first portion and the second portion.

19. A joint as claimed in claim 17, wherein the truncated region acts to retain the skin against the butt-strap.

20. A joint as claimed in claim [1] 9, wherein the cover skin further comprises a proximal portion and wherein the proximal portion and the distal portion of the [second] exterior surface of the skin meet to form a step region.

21. A joint as claimed in claim 20 wherein the step region retains a distal end of the butt-strap.

10

22. A joint as claimed in claim [1] 9, wherein a plurality of said butt-straps is spliced together by connection to an aircraft structure.

23. A joint as claimed in claim [1] 9, wherein the butt-strap comprises a portion that extends into a pylon region of the wing.

[24. An aircraft structure, aerodynamic surface, wing, fin or horizontal stabilizer, incorporating a joint as claimed in claim 1.]

[25. A wing incorporating a joint as claimed in claim 1, wherein the exterior-facing surface of the distal portion of the skin is formed in a first region of the wing's leading or trailing edge by moulding and in a second region of the wing's leading or trailing edge by machining.]

[26. A wing as claimed in claim 25 wherein the moulded region of the distal portion runs parallel to spars of the wing.]

[27. A wing as claimed in claim 25, wherein the machined region is located at an undercarriage rib of the wing.]

28. A joint as claimed in claim [1] 9, wherein the butt-strap comprises a second portion for connection to an aircraft structure, and wherein the second portion of the butt-strap has the same form as the first portion and functions in a similar manner to said first portion.

[29. A method of manufacturing a joint for use in aircraft construction comprising forming a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface, forming a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end wherein the method further comprises connecting the first portion of the butt-strap to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface.]

[30. A method as claimed in claim 29 wherein the exterior-facing surface of the distal portion of the skin is formed by moulding.]

[31. An aircraft constructed using one or more joints as claimed in claim 1.]

32. A joint as claimed in claim 10, wherein said fastener is a bolt including a tapered washer.

33. A joint as claimed in claim 10, wherein said fastener is a bolt including a tapered collar.

34. A method of manufacturing the joint as claimed in claim 6, the method comprising: forming a cover skin having an interior surface, an exterior surface and a distal portion said distal portion having an exterior-facing surface, forming a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end wherein the method further comprises connecting the first portion of the butt-strap to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the

exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface.

35. A method of manufacturing the joint as claimed in claim 9, the method comprising: forming a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface, forming a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end wherein the method further comprises connecting the first portion of the butt-strap to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface.

36. An aircraft wing, an aircraft fin, or an aircraft horizontal stabilizer, incorporating a joint comprising:

(i) a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface;

(ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface, wherein the joint includes filler located in a channel formed by the distal end of the first portion and the exterior surface of the cover skin adjacent the junction.

37. An aircraft wing, an aircraft fin, or an aircraft horizontal stabilizer, incorporating a joint comprising:

(i) a cover skin having an interior surface, an exterior surface and a distal portion said distal portion having an exterior-facing surface;

(ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface, wherein the skin is of substantially the same thickness in the proximal portion and in the distal portion and the distal portion is offset from the proximal portion at an angle that orients the exterior-facing surface of the distal portion so that it is complementary to the tapering first portion of the butt-strap.

38. A wing incorporating a joint as claimed in claim 6, wherein the exterior-facing surface of the distal portion of the skin is formed in a first region of a wing's leading or trailing edge by molding and in a second region of the wing's leading or trailing edge by machining.

39. A wing incorporating a joint as claimed in claim 9, wherein the exterior-facing surface of the distal portion of the skin is formed in a first region of a wing's leading or trailing edge by molding and in a second region of the wing's leading or trailing edge by machining.

40. An aircraft constructed using one or more joints each comprising:

(i) a cover skin having an interior surface, an exterior surface and a distal portion, said distal portion having an exterior-facing surface;

(ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that, at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface, wherein the joint includes filler located in a channel formed by the distal end of the first portion and the exterior surface of the cover skin adjacent the junction.

41. An aircraft constructed using one or more joints each comprising:

(i) a cover skin having an interior surface, an exterior surface and a distal portion said distal portion having an exterior-facing surface;

(ii) a butt-strap having a first portion for connection to the skin, said first portion having an interior surface, an exterior surface and a distal end;

wherein the first portion of the butt-strap is connected to the distal portion of the skin such that a junction is formed between the exterior surface of the skin and the exterior surface of the first portion of the butt-strap and wherein the exterior-facing surface of the distal portion of the skin is of a shape complementary to the shape of the interior surface of the first portion of the butt-strap and wherein the first portion of the butt-strap tapers towards its distal end such that at said junction, the exterior surface of the skin and the exterior surface of the first portion of the butt-strap form a substantially continuous exterior surface, wherein the skin is of substantially the same thickness in the proximal portion and in the distal portion and the distal portion is offset from the proximal portion at an angle that orients the exterior-facing surface of the distal portion so that it is complementary to the tapering first portion of the butt-strap.

42. A wing as claimed in claim 38 wherein the moulded region of the distal portion runs parallel to spars of the wing.

43. A wing as claimed in claim 39 wherein the moulded region of the distal portion runs parallel to spars of the wing.

44. A wing as claimed in claim 38, wherein the machined region is located at an undercarriage rib of the wing.

45. A wing as claimed in claim 39, wherein the machined region is located at an undercarriage rib of the wing.

46. A method as claimed in claim 34 wherein the exterior-facing surface of the distal portion of the skin is formed by moulding.

47. A method as claimed in claim 35 wherein the exterior-facing surface of the distal portion of the skin is formed by 5 moulding.

* * * * *