



US00RE47811E

(19) **United States**
(12) **Reissued Patent**
Sullivan et al.

(10) **Patent Number: US RE47,811 E**
(45) **Date of Reissued Patent: Jan. 14, 2020**

(54) **KNOTLESS SUTURE ANCHORS AND METHODS OF TISSUE REPAIR**

(71) Applicant: **Arthrex, Inc.**, Naples, FL (US)
(72) Inventors: **Derek C. Sullivan**, Naples, FL (US);
Thomas Dooney, Jr., Naples, FL (US);
Allen E. Holowecky, Naples, FL (US);
Paul C. Brady, Knoxville, TN (US);
Benjamin G. Domb, Chicago, IL (US)

(73) Assignee: **Arthrex, Inc.**, Naples, FL (US)

(21) Appl. No.: **15/978,852**

(22) Filed: **May 14, 2018**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,737,292**
Issued: **Aug. 22, 2017**
Appl. No.: **13/916,104**
Filed: **Jun. 12, 2013**

U.S. Applications:

(60) Provisional application No. 61/663,029, filed on Jun. 22, 2012.

(51) **Int. Cl.**
A61B 17/04 (2006.01)
A61B 17/88 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 17/0401** (2013.01); **A61B 17/0469**
(2013.01); **A61B 17/0482** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **A61B 17/0401**
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,176,316 A 4/1965 Bodell
4,187,558 A 2/1980 Dahlen et al.
(Continued)

FOREIGN PATENT DOCUMENTS

DE 299 10 202 U1 9/1999
DE 201 01 791 U1 6/2001
(Continued)

OTHER PUBLICATIONS


MaxFire MarXmen Meniscal Repair Surgical Technique, BIOMET Sports Medicine, Mar. 2009.
(Continued)

Primary Examiner — Cary E Wehner
(74) *Attorney, Agent, or Firm* — Blank Rome LLP

(57) **ABSTRACT**

Systems and methods for soft tissue to bone repairs employing tensionable knotless anchors, without knot tying. The tensionable knotless anchors may be used by themselves or in combination with additional constructs (which may have a similar or different configuration, i.e., modified according to the specific repair) and with the flexible strands provided through tissue, around tissue, or through and around tissue to be repaired or fixated. The tensionable knotless anchors may be used to achieve simple stitch repairs, mattress stitch repairs or interlocked looped mattress repairs, among others. The tensionable knotless anchors may be also provided in a daisy chain configuration, i.e., with the suture from one anchor passed through the eyelet/loop of the shuttle/pull device of another anchor and repeated in a pattern.

20 Claims, 33 Drawing Sheets



US RE47,811 E

(52)	U.S. Cl. CPC <i>A61B 17/0485</i> (2013.01); <i>A61B 17/8875</i> (2013.01); <i>A61B 2017/044</i> (2013.01); <i>A61B</i> <i>2017/0409</i> (2013.01); <i>A61B 2017/0414</i> (2013.01); <i>A61B 2017/0427</i> (2013.01); <i>A61B</i> <i>2017/0458</i> (2013.01); <i>A61B 2017/0459</i> (2013.01); <i>A61B 2017/0496</i> (2013.01)	2003/0114929 A1 2004/0015171 A1 2004/0059415 A1 2004/0073306 A1 2004/0243235 A1 2004/0267360 A1 2005/0004670 A1 2005/0033363 A1*	6/2003 Knudsen et al. 1/2004 Bojarski et al. 3/2004 Schmieding 4/2004 Eichhorn et al. 12/2004 Goh et al. 12/2004 Huber 1/2005 Gebhardt et al. 2/2005 Bojarski A61B 17/0401 606/228
(58)	Field of Classification Search USPC 606/232 See application file for complete search history.	2005/0065533 A1 2005/0070906 A1 2005/0137704 A1 2005/0149187 A1 2005/0171603 A1 2005/0203623 A1 2005/0261766 A1 2006/0004364 A1 2006/0067971 A1 2006/0095130 A1 2006/0106423 A1*	3/2005 Magen et al. 3/2005 Clark et al. 6/2005 Steenlage 7/2005 Clark et al. 8/2005 Justin et al. 9/2005 Steiner et al. 11/2005 Chervitz et al. 1/2006 Green et al. 3/2006 Story et al. 5/2006 Caborn et al. 5/2006 Weisel A61B 17/0401 606/232
(56)	References Cited U.S. PATENT DOCUMENTS 4,301,551 A 11/1981 Dore et al. 4,400,833 A 8/1983 Kurland 4,776,851 A 10/1988 Bruchman et al. 4,790,850 A 12/1988 Dunn et al. 4,792,336 A 12/1988 Hlavacek et al. 4,851,005 A 7/1989 Hunt et al. 4,863,471 A 9/1989 Mansat 4,917,700 A 4/1990 Aikins 4,932,972 A 6/1990 Dunn et al. 5,024,669 A 6/1991 Peterson et al. 5,026,398 A 6/1991 May et al. 5,129,902 A 7/1992 Goble et al. 5,171,274 A 12/1992 Fluckiger et al. 5,211,647 A 5/1993 Schmieding 5,217,495 A 6/1993 Kaplan et al. 5,263,984 A 11/1993 Li et al. 5,266,075 A 11/1993 Clark et al. 5,306,301 A 4/1994 Graf et al. 5,320,626 A 6/1994 Schmieding 5,397,357 A 3/1995 Schmieding et al. 5,562,669 A 10/1996 McGuire 5,562,683 A * 10/1996 Chan A61B 17/0469 289/17 5,575,819 A 11/1996 Amis 5,628,756 A 5/1997 Barker, Jr. et al. 5,643,266 A 7/1997 Li 5,645,588 A 7/1997 Graf et al. 5,658,313 A * 8/1997 Thal A61B 17/0401 24/357 5,931,869 A 8/1999 Boucher et al. 5,961,520 A 10/1999 Beck, Jr. et al. 5,964,764 A 10/1999 West, Jr. et al. 6,056,752 A 5/2000 Roger 6,099,530 A 8/2000 Simonian et al. 6,099,568 A 8/2000 Simonian et al. 6,110,207 A 8/2000 Eichhorn et al. 6,159,234 A 12/2000 Bonutti et al. 6,193,754 B1 2/2001 Seedhom 6,203,572 B1 3/2001 Johnson et al. 6,283,996 B1 9/2001 Chervitz et al. 6,296,659 B1 10/2001 Foerster 6,325,804 B1 12/2001 Wenstrom, Jr. et al. 6,517,578 B2 2/2003 Hein 6,533,802 B2 3/2003 Bojarski et al. 7,097,654 B1 8/2006 Freedland 7,494,506 B2 2/2009 Brulez et al. 7,686,838 B2 3/2010 Wolf et al. 7,749,250 B2 7/2010 Stone et al. 7,776,039 B2 8/2010 Bernstein et al. 7,819,898 B2 10/2010 Stone et al. 7,828,855 B2 11/2010 Ellis et al. 7,875,057 B2 1/2011 Cook et al. 7,905,903 B2 3/2011 Stone et al. 7,914,539 B2 3/2011 Stone et al. 8,109,965 B2 2/2012 Stone et al. 8,118,836 B2 2/2012 Denham et al. 8,162,997 B2 4/2012 Struhl 8,206,446 B1 6/2012 Montgomery 8,231,654 B2 7/2012 Kaiser et al. 2001/0041938 A1 11/2001 Hein 2002/0161439 A1 10/2002 Strobel et al.	2006/0122608 A1* 2006/0142769 A1 2006/0161159 A1* 2006/0265064 A1 2007/0021839 A1 2007/0083236 A1 2007/0118217 A1 2007/0162123 A1 2007/0162125 A1 2007/0179531 A1 2007/0225805 A1 2007/0239209 A1 2007/0239275 A1 2007/0250163 A1 2007/0270857 A1 2008/0046009 A1 2008/0065114 A1* 2008/0177302 A1 2008/0188935 A1 2008/0188936 A1 2008/0208252 A1 2008/0215150 A1 2008/0228271 A1 2008/0234819 A1 2008/0243248 A1 2008/0255613 A1* 2008/0275553 A1 2008/0275554 A1 2008/0300683 A1 2008/0312689 A1 2009/0018654 A1 2009/0030516 A1 2009/0054982 A1 2009/0062854 A1 2009/0082805 A1* 2009/0187244 A1 2009/0216326 A1 2009/0228017 A1 2009/0234451 A1 2009/0265003 A1 2009/0275950 A1 2009/0306776 A1 2009/0306784 A1 2009/0312776 A1 2010/0049258 A1 2010/0049319 A1 2010/0063541 A1* 2010/0100182 A1 2010/0145384 A1 2010/0145448 A1 2010/0211075 A1	6/2006 Fallin A61B 17/0401 606/232 6/2006 Collette 7/2006 Dreyfuss A61B 17/0401 606/232 11/2006 Re et al. 1/2007 Lowe 4/2007 Sikora et al. 5/2007 Brulez et al. 7/2007 Whittaker et al. 7/2007 LeBeau et al. 8/2007 Thornes 9/2007 Schmieding 10/2007 Fallman 10/2007 Willobee 10/2007 Cassani 11/2007 Lombardo et al. 2/2008 Albertorio et al. 3/2008 Stone A61B 17/0401 606/139 7/2008 Shurnas 8/2008 Saylor et al. 8/2008 Ball et al. 8/2008 Holmes 9/2008 Koob et al. 9/2008 Stone et al. 9/2008 Schmieding et al. 10/2008 Stone et al. 10/2008 Kaiser A61B 17/0401 606/232 11/2008 Wolf et al. 11/2008 Iannarone et al. 12/2008 Altman et al. 12/2008 Denham et al. 1/2009 Schmieding et al. 1/2009 Imbert 2/2009 Cimino 3/2009 Kaiser et al. 3/2009 Kaiser A61B 17/0401 606/228 7/2009 Dross 8/2009 Hirpara et al. 9/2009 Collins 9/2009 Manderson 10/2009 Re et al. 11/2009 Sterrett et al. 12/2009 Murray 12/2009 Blum 12/2009 Kaiser et al. 2/2010 Dougherty 2/2010 Dougherty 3/2010 Brunelle A61B 17/0401 606/232 4/2010 Barnes et al. 6/2010 Stone et al. 6/2010 Montes De Oca Balderas et al. 8/2010 Stone

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0211173 A1 8/2010 Bardos et al.
 2010/0249930 A1 9/2010 Myers
 2010/0256677 A1 10/2010 Albertorio et al.
 2010/0268273 A1 10/2010 Albertorio et al.
 2010/0268275 A1 10/2010 Stone et al.
 2010/0274355 A1 10/2010 McGuire et al.
 2010/0274356 A1 10/2010 Fening et al.
 2010/0292792 A1 11/2010 Stone et al.
 2010/0305709 A1 12/2010 Metzger et al.
 2010/0312341 A1 12/2010 Kaiser et al.
 2010/0318188 A1 12/2010 Linares
 2010/0324676 A1 12/2010 Albertorio et al.
 2010/0331975 A1 12/2010 Nissan et al.
 2011/0040380 A1 2/2011 Schmieding et al.
 2011/0046734 A1 2/2011 Tobis et al.
 2011/0054609 A1 3/2011 Cook et al.
 2011/0087284 A1 4/2011 Stone et al.
 2011/0098727 A1 4/2011 Kaiser et al.
 2011/0112640 A1 5/2011 Amis et al.
 2011/0112641 A1 5/2011 Justin et al.
 2011/0118838 A1 5/2011 Delli-Santi et al.
 2011/0137416 A1 6/2011 Myers
 2011/0184227 A1 7/2011 Altman et al.
 2011/0196432 A1 8/2011 Griffis, III
 2011/0196490 A1 8/2011 Gadikota et al.
 2011/0208239 A1* 8/2011 Stone A61B 17/0469
 606/228
 2011/0218625 A1 9/2011 Berelsman et al.
 2011/0238179 A1 9/2011 Laurencin et al.
 2011/0270278 A1 11/2011 Overes et al.
 2011/0276137 A1 11/2011 Seedhom et al.
 2011/0288635 A1 11/2011 Miller et al.
 2011/0301707 A1 12/2011 Buskirk et al.

2011/0301708 A1 12/2011 Stone et al.
 2012/0046746 A1 2/2012 Konicek
 2012/0046747 A1 2/2012 Justin et al.
 2012/0053630 A1 3/2012 Denham et al.
 2012/0065732 A1 3/2012 Roller et al.
 2012/0089143 A1 4/2012 Martin et al.
 2012/0109299 A1 5/2012 Li et al.
 2012/0123474 A1 5/2012 Zajac et al.
 2012/0123541 A1 5/2012 Albertorio et al.
 2012/0150297 A1 6/2012 Denham et al.
 2012/0165938 A1 6/2012 Denham et al.
 2012/0197271 A1 8/2012 Astorino et al.
 2012/0296345 A1 11/2012 Wack et al.
 2013/0023928 A1 1/2013 Dreyfuss
 2013/0023929 A1 1/2013 Sullivan et al.
 2013/0165972 A1 6/2013 Sullivan
 2014/0052179 A1* 2/2014 Dreyfuss A61B 17/0401
 606/232
 2016/0287243 A1* 10/2016 Benedict A61B 17/0401
 2019/0029667 A1* 1/2019 Hester A61B 17/0401

FOREIGN PATENT DOCUMENTS

EP 0 440 991 A1 8/1991
 EP 1 108 401 A1 6/2001
 EP 1 707 127 A1 10/2006
 WO WO-2007/002561 A1 1/2007
 WO WO-2008/091690 A1 7/2008

OTHER PUBLICATIONS

ToggleLoc Femoral Fixation for ACL Reconstruction, BIOMET Sports Medicine, 2008.

* cited by examiner




FIG. 3




FIG. 2




FIG. 1




FIG. 5




FIG. 4




FIG. 7




FIG. 9




FIG. 6




FIG. 8




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

FIG. 16

FIG. 17




FIG. 18




FIG. 19




FIG. 21

FIG. 20




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26

FIG. 27

FIG. 28

FIG. 29




FIG. 30

FIG. 31

FIG. 32




FIG. 33




FIG. 35




FIG. 34




FIG. 37




FIG. 36




FIG. 39









FIG. 38








FIG. 50





FIG. 51






FIG. 53

FIG. 52




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 62

FIG. 61

FIG. 60




FIG. 63




FIG. 64




FIG. 65




FIG. 66








FIG. 67






FIG. 73




FIG. 75




FIG. 72




FIG. 74




FIG. 76 FIG. 77 FIG. 78




FIG. 79 FIG. 80 FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86




FIG. 87




FIG. 88




FIG. 89




FIG. 90




FIG. 91




FIG. 92




FIG. 93




FIG. 94




FIG. 95





FIG. 98

FIG. 97

FIG. 96

FIG. 99




FIG. 100




FIG. 101




FIG. 102




FIG. 103

KNOTLESS SUTURE ANCHORS AND METHODS OF TISSUE REPAIR

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 61/663,029 filed Jun. 22, 2012, the disclosure of which is incorporated by reference in its entirety herein.

FIELD OF THE INVENTION

The present invention relates to surgical devices and, in particular, to knotless suture constructs and associated methods of tissue repairs.

BACKGROUND OF THE INVENTION

When soft tissue such as a ligament or a tendon becomes detached from a bone, surgery is usually required to reattach or reconstruct the tissue. Often, a tissue graft is attached to the bone to facilitate regrowth and permanent attachment. Techniques and devices that have been developed generally involve tying the soft tissue with suture to an anchor or a hole provided in the bone tissue. Knotless suture anchors, such as the two piece Arthrex PushLock® anchor, disclosed in U.S. Pat. No. 7,329,272, have been developed to facilitate tissue fixation to bone.

There is a need for knotless suture anchor constructs with improved design that allow tensioning of the tissue after implantation of the suture anchors. Also needed are improved technologies for knotless fixation of soft tissue with easier suture management and increased tensioning of the tissue.

SUMMARY OF THE INVENTION

The present invention fulfills the above needs and objectives by providing knotless, tensionable suture anchors and methods of tissue repair employing one or more of such knotless, tensionable suture anchors. The suture anchors of the present invention allow for tensioning after insertion in bone (to allow attached tissue to be brought proximate to bone) and do not require tying of any knots.

Other features and advantages of the present invention will become apparent from the following description of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1-14 illustrate subsequent steps of a method of tissue repair (simple stitch of soft tissue) using a tensionable knotless anchor according to an exemplary embodiment of the present invention.

FIGS. 15-17 illustrate subsequent steps of a method of tissue repair (tendon repair) using a tensionable knotless anchor according to an exemplary embodiment of the present invention.

FIGS. 18-21 illustrate subsequent steps of a method of tissue repair (hip labral repair) using multiple tensionable knotless anchors according to an exemplary embodiment of the present invention.

FIGS. 22-25 illustrate subsequent steps of a method of tissue repair (hip capsular repair) using multiple tensionable knotless anchors according to an exemplary embodiment of the present invention.

FIGS. 26-32 illustrate subsequent steps of a method of tissue repair (simple stitch repair) using a tensionable knotless anchor according to an exemplary embodiment of the present invention.

FIGS. 33-39 illustrate subsequent steps of a method of tissue repair (hip labral repair) using multiple tensionable knotless anchors according to an exemplary embodiment of the present invention.

FIGS. 40-48 illustrate subsequent steps of a method of tissue repair (mattress stitch repair) using a tensionable knotless anchor according to an exemplary embodiment of the present invention.

FIGS. 49-51 illustrate subsequent steps of a method of tissue repair (hip gluteus medius repair) using a tensionable knotless anchor according to an exemplary embodiment of the present invention.

FIGS. 52 and 53 illustrate subsequent steps of a method of tissue repair (modified anchor rotator cuff repair) using a modified tensionable knotless anchor according to an exemplary embodiment of the present invention.

FIGS. 54-59 illustrate subsequent steps of a method of tissue repair (simple stitch with tied mattress repair) using multiple interconnected tensionable knotless anchors according to an exemplary embodiment of the present invention.

FIGS. 60-71 illustrate subsequent steps of a method of tissue repair (interlocked looped mattress over two anchors repair) using multiple interconnected tensionable knotless anchors (with interlocked loops) according to an exemplary embodiment of the present invention.

FIGS. 72-75 illustrate subsequent steps of a method of tissue repair (two or more anchors in daisy chain) using multiple interconnected tensionable knotless anchors according to an exemplary embodiment of the present invention.

FIGS. 76-95 illustrate subsequent steps of a method of tissue repair (double row rotator cuff or Achilles tendon repair using daisy chain) using multiple interconnected tensionable knotless anchors according to an exemplary embodiment of the present invention.

FIGS. 96-99 illustrate subsequent steps of a method of tissue repair (simple two anchor mattress repair) using two different tensionable knotless anchors together (the anchors having different configurations) according to an exemplary embodiment of the present invention.

FIGS. 100 and 101 illustrate a tissue repair (rotator cuff repair using two anchors for medial row and two different anchors for lateral row) using two different-style tensionable knotless anchors together according to an exemplary embodiment of the present invention.

FIGS. 102 and 103 illustrate a side view and a cross-sectional view, respectively, of a tensionable knotless anchor employed in the exemplary methods of tissue repair and fixation according to the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

The present invention provides surgical constructs, systems and techniques for knotless soft tissue repair and

fixation, such as fixation of soft tissue (ligament, tendon, graft, etc.) to bone. The knotless anchor constructs may be employed for any soft tissue repair including labral, rotator cuff, Achilles tendon, biceps and hip repairs, among many others.

The knotless suture constructs of the present invention use a mechanism similar to that of knotless SutureTak® but provide improvements in the design of the anchor constructs (for example, an anchor with two separate flexible strands or an anchor without a flexible strand but with one or more suture shuttle devices) as well as in the suture management and tensioning.

The surgical constructs and systems detailed below comprise fixation devices (tensionable knotless anchors) having various configurations that are inserted into bone with a flexible strand (for example, a suture) provided within the fixation device and optionally a shuttle/pull device (a suture passing instrument) attached to the flexible strand. The flexible strand and the shuttle/pull device attached to it allow the formation of a splice within the body of the anchor and during the tissue repair procedure to finalize the construct. The shuttle/pull device is provided within the strand (inside of the strand) and forms the splice subsequent to the insertion of the fixation device within the bone (and subsequent to attachment to soft tissue to be repaired or fixated) to allow formation of the final fixation device with a knotless self-locking mechanism that allows the user (for example, the surgeon) to control the tension of the strand on the soft tissue to be attached to bone.

Details of the formation of an exemplary knotless suture anchor employed in the embodiments of the present invention and with the splice-forming mechanism detailed above are set forth in U.S. Patent Application Publication No. 2013/0096611, entitled "Tensionable Knotless Anchors with Splice and Methods of Tissue Repair" and U.S. application Ser. No. 13/709,138 filed Dec. 10, 2012, entitled "Tensionable Knotless Anchor Systems and Methods of Tissue Repair," the disclosures of both of which are incorporated in their entirety herewith.

The present invention also provides methods of soft tissue repair which do not require tying of knots and allow adjustment of both the tension of the suture and the location of the tissue with respect to the bone. In the exemplary methods detailed below with reference to FIGS. 1-101, the tensionable knotless anchors may be used by themselves or in combination with additional constructs (which may have a similar or different configuration, i.e., modified according to the specific repair) and with the flexible strand provided through tissue, around tissue, or through and around tissue to be repaired or fixated. The tensionable taintless anchors may be used to achieve simple stitch repairs, mattress stitch repairs or interlocked looped mattress repairs, among others. The tensionable knotless anchors may be also provided in a daisy chain configuration, i.e., with the suture from one anchor passed through the eyelet/loop of the shuttle/pull device of another anchor and repeated in a pattern (to allow the formation of a splice within each anchor with a shuttle/pull device of another anchor).

The methods and constructs of the present invention will be detailed below with reference to an exemplary knotless suture anchor 50, 50a-50d (or anchors having a configuration similar to it such as anchors 150, 250). Details of an anchor similar to knotless suture anchor 50 are set forth in U.S. Application Publication No. 2013/0096611, entitled "Tensionable Knotless Anchors with Splice and Methods of Tissue Repair" (the disclosure of which is incorporated in its entirety herewith), but are also provided in this application

(for ease of understanding of the embodiments below), and with reference to FIGS. 102 and 103.

The tensionable knotless anchor 50 shown in FIGS. 102 and 103 has an anchor body 11 provided with a longitudinal axis 11a, a proximal end 13 and a distal end 12, and a plurality of ribs 15 extending circumferentially around it. Openings/channels 16 and 17 allow threading suture(s) and/or suture passing device(s) around post 20, as detailed below. Cannulation 11b extends along the body 11 to allow passage of flexible strands and of suture passing devices, as detailed below. Cylindrical portion 14 is provided at the proximal end 13 of the anchor 50 and contains a socket 19 (FIG. 103) configured to securely engage a tip of a driver. Openings/channels 16, 17 are positioned opposite to each other relative to the post 20 and also symmetrically located relative to the post 20, to allow flexible strand 30 (suture 30) and shuttle/pull device 40 (suture passing instrument 40 or shuttle 40) provided with eyelet or loop 44 to pass and slide through.

Tensionable knotless anchor 50 is loaded with tensionable construct 99 formed of suture 30 attached to the shuttle/pull device 40. To assembly anchor 50, suture 30, which is typically braided or multi-filament, is preloaded onto the anchor by tying static knot 39, which prevents suture 30 from passing through distal blind hole 12a. The suture may also be preloaded by insert molding or by any other means known in the art. Suture 30 passes around post 20, which is large enough to allow suture 30 to take gradual turns instead of sharp turns. Suture 30 then passes through cannulation 11b and proximal blind hole 13a. Tensionable knotless anchor 50 is loaded onto a driver (not shown in FIGS. 102 and 103), and suture 30 is tied to the driver (for example, wrapped around a cleft of the driver) to fasten tensionable knotless anchor 50 securely to the driver.

Prior to the fastening of the anchor 50 to the driver, suture passing device 40 (for example, a FiberLink™ or a nitinol loop) is threaded through suture 30 (i.e., attached to the suture 30 through splice region 38), as shown in FIG. 103. Suture passing device 40 includes an eyelet/loop 44 for passing suture and, optionally, a pull-ring (not shown). Suture passing device 40 passes through an aperture of suture 30, located either proximal or distal to distal blind hole 12a. It then exits an aperture of suture 30, within the tensionable knotless anchor 50, traverses around post 20, and through proximal blind hole 13a. Tensionable knotless anchor 50 loaded with tensionable construct 99 (formed of suture 30 attached to the suture passing device 40) is then secured into bone (for example, into a hole/socket/tunnel formed in the bone) by using the driver. Suture 30 is then passed through or around the tissue which is to be reattached to bone. Suture 30 is subsequently passed through eyelet/loop 44 of the suture passing device 40. Suture passing device 40 is then pulled, thereby pulling suture 30 towards tensionable knotless anchor 50 so that it doubles on itself inside the body of the tensionable knotless anchor. The suture passing device 40 has also been further pulled through the splice region 38 of suture 30, to form a splice within the strand 30 and within the body of the anchor 50.

Anchor 50 may be a screw-in anchor or a push-in style anchor. Anchor 50 may be formed of metal, biocompatible plastic such as PEEK or a bioabsorbable PLLA material. Socket 19 at the [distal] proximal end 13 of the anchor 50 is configured to securely engage a tip of a driver, as detailed below. The socket of the anchor 50 may have any shape adapted to receive a driver tip for tapping or screw-in style anchors. Tensionable knotless anchor 50 may be made of one or more pieces, or may be provided as an integrated

device. As detailed below, the tensionable knotless anchor **50** may be modified to carry more than one suture/shuttle construct (i.e., more than a flexible strand **30** and a shuttle/pull device **40**), or may be modified to carry no suture but only one or more shuttle/pull devices, etc.

Reference is now made to FIGS. **1-101** which illustrate various suture anchor constructs and methods of attaching soft tissue to other tissue such as bone with such constructs. For simplicity, the suture anchor constructs have been grouped into three categories A-C, or three Embodiments A-C, set forth below.

Embodiment A—Single Anchor Constructs

The following description is a summary of the various methods of using the knotless anchor:

FIGS. **1-14**

1) Simple Stitch Using Single Anchor to Attach Tissue for all Soft Tissue Repairs

- a. Insert anchor **50** into bone **90** using driver **95**, remove driver **95** exposing suture **30** and suture shuttle **40** (with wire loop **44**) (FIGS. **1-4**)
 - i. Can pre-drill bone hole **91** or tap
 - ii. Can go through tissue **80** or under it directly into bone **90**
- b. Pass suture **30** through tissue **80** using suture passing instrument **35** (FIGS. **5** and **6**)
- c. Feed suture **30** through loop **44** of suture shuttle **40** (FIG. **7**)
- d. Pull end of suture shuttle **40** to pull suture **30** through itself and the body of anchor **50** and create splice within the body of the anchor **50** (FIGS. **8-11**)
- e. Pull suture **30** until desired tension and tissue position is reached (FIGS. **12-14**)
- f. Cut suture **30** when repair is complete

FIGS. **15-17**

Technique for Tendon Repair

- a. Whipstitch suture tape **31** (for example, FiberTape® **31**) on tendon **80**
- b. Create loop **31a** at end of tendon **80** with FiberTape® **31**
- c. Pass end of suture **30** from knotless anchor **50** through loop **31a** at end of tendon **80**
- d. Feed through loop **44** of suture shuttle **40** and complete steps d-f

FIGS. **18-21**

Technique for Hip Labral Reconstruction Using Multiple Knotless Anchors **50a**, **50b** (similar to knotless anchor **50**)

- a. Insert Anchor **1** (anchor **50a**) into bone at first edge **82a** of segmental labral loss **82** of labrum **80** (FIG. **18**)
- b. Insert Anchor **2** (anchor **50b**) into bone **90** at second edge **82b** of segmental labral loss **82** of labrum **80** (FIG. **18**)
- c. Pass suture **30a** from Anchor **1** (anchor **50a**) through first end of labral graft **88** (FIG. **18**)
- d. Pass suture **30b** from Anchor **2** (anchor **50b**) through second end of labral graft **88** (FIG. **18**)
- e. Feed end of suture **30a** from Anchor **1** (anchor **50a**) back through cannula **70** and through the loop **44a** of suture shuttle **40a** of Anchor **1** (anchor **50a**) (FIG. **18**)
- f. Continue to pass end of suture **30a** through the accessory portal (FIG. **19**)
- g. Apply tension to end of suture through the accessory portal to parachute graft **88** into placement (FIGS. **19** and **20**)
- h. Feed end of suture **30b** from Anchor **2** (anchor **50b**) through loop **44b** of suture shuttle **40b** and up through

accessory portal; apply tension through accessory portal in the direction of arrow A (FIG. **19**) to “parachute” graft **88** into the joint

- i. Apply tension to end of suture to complete placement of graft **88** (FIG. **20**)
- j. Tension both ends of suture **30a**, **30b** to desired tension; tension posterior anchor **50b** for completing anterior and posterior fixation (FIG. **20**)
- k. Cut suture ends when repair completed (FIG. **21**)
- l. Place additional anchors as needed (for example, anchors **50c**, **50d**) between the ends of the graft **88** to achieve fixation of the middle segment and complete graft fixation (FIG. **21**)

FIGS. **22-25**

Technique for Hip Capsular Repair or Plication

- a. Place anchors **50a**, **50b**, **50c**, **50d** in bone **90** along tear; once anchors **50a**, **50b**, **50c**, **50d** are placed, the sutures **30a**, **30b**, **30c**, **30d** are passed through capsule **80** with a suture passing instrument (such as Bird Beak or Lasso suture passer) (FIG. **22** shows only three anchors)
- b. Using a suture passing instrument (not shown), pass suture **30a**, **30b**, **30c** from each anchor **50a**, **50b**, **50c** through capsule **80** (FIG. **22**)
- c. Feed each end of suture **30a**, **30b**, **30c**, **30d** through suture shuttle **44a**, **44b**, **44c**, **44d** of respective anchor **50a**, **50b**, **50c**, **50d**
- d. Sequentially tension from medial to lateral each suture **30a**, **30b**, **30c**, **30d** to the desired tension; sutures are shuttled through anchors and sequentially tensioned medial to lateral (FIG. **24**)
- e. Cut suture ends when repair complete (FIG. **25**)

FIGS. **26-32**

2) Simple Stitch—Single Anchor with Pass Suture Around Tissue and Attached to Bone

- a. Insert anchor **50** into bone **90** using driver, remove driver exposing suture **30** and suture shuttle **40** with wire loop **44** (of the shuttle/pull device **40**) (FIG. **26**)
 - i. Can pre-drill bone hole or tap
- b. Pass suture **30** around tissue **80** using a suture passing instrument (FIG. **27**)
- c. Feed suture **30** through loop **44** of suture shuttle **40** (FIG. **27**)
- d. Pull end of suture shuttle **40** to pull suture **30** through itself and the anchor body (FIGS. **28-30**)
- e. Pull suture **30** until desired tension and tissue position is reached (FIG. **31**)
- f. Cut suture **30** when repair is complete (FIG. **32**)

FIGS. **33-39**

Technique for Hip Labral Repair (looped stitch)

- a. Drill all anchor holes **91a**, **91b**, **91c**, **91d** with drill **93** into hip **90** through Mid-Anterior Portal (MA) or Distal Anterior Accessory Portal (DAAP) or may drill one hole at a time (FIGS. **33** and **34**); can use a 2-portal technique (antero-lateral portal (AL) and mid-anterior portal (MA)) or a 3-portal technique (antero-lateral portal (AL), distal-anterior accessory portal (DAAP) and anterior portal (A))
- b. Place first anchor **50a** (FIG. **35**), pass suture **30a** behind labrum **80** (FIG. **36**), retrieve suture **30a** on front side of labrum **80** using suture passing instrument (FIG. **37**)
- c. Feed end of suture **30a** through loop **44a** of suture shuttle **40a** on anchor **50a** (FIG. **37**)
- d. Pull end of shuttle **40a** (nitinol shuttle) to pass suture **30a** through itself and anchor **50a** and form splice within the anchor (FIG. **37**)
- e. Place each subsequent anchor **50b**, **50c**, **50d**, pass sutures **30b**, **30c**, **30d** same as steps b-d

- f. Can store suture tails through a portal (for example, anterior portal) or outside of cannula (FIG. 38)
- g. Tension sutures to achieve desired placement and tension of labrum 80 (FIG. 39)

FIGS. 40-48

3) Mattress Stitch-Using Single Anchor to Attach Tissue

- a. Insert anchor 50 into bone 90 using driver, remove driver exposing suture 30 and suture passing construct 44 (wire loop 44 of shuttle 40) (FIG. 40)

- i. Can pre-drill bone hole or tap
- ii. Can go under tissue directly into bone

- b. Using suture passing instrument, pass suture 30 up through the tissue 80 and back down through the tissue 80 (FIGS. 41-43)

- c. Feed suture 30 through the suture shuttle 44 (FIG. 44)

- d. Pull end of suture shuttle 44 to pull suture through itself and through the anchor body (FIGS. 45 and 46)

- e. Continue to pull suture 30 until the tissue 80 is in desired position and tension (FIG. 47)

- f. Cut suture 30 when repair is complete (FIG. 48)

FIGS. 49-51

Technique for Hip Gluteus Medius Repair-Trans-tendinous

- a. Create longitudinal incision 84 in tendon 80, allows access to deep-sided tear 84a (FIG. 49)

- b. Place anchor 50 through incision 84 (FIG. 50)

- c. Pass anchor suture shuttle 40 with loop/eyelet 44 through anterior side 80a of tendon 80 (FIG. 50)

- d. Pass suture 30 through posterior side 80b of tendon 80 (FIG. 50)

- e. Feed end of suture 30 through loop 44 of suture shuttle 40 (FIG. 51)

- f. Pull suture shuttle 40 to pass suture 30 through itself and the anchor body to complete horizontal mattress

- g. Tension suture end in direction of arrow A until desired tension (FIG. 51)

- h. Cut end of suture 30 when repair completed

- i. May use additional anchors depending on the size of the tear

FIGS. 52 and 53

4) Modified Anchor Rotator Cuff Repair

- a. Anchor 150 is modified to have 2 sutures 30a, 30b loaded each with a suture shuttle 40a, 40b (with eyelets 44a, 44b) within a single anchor body; anchor 150 is similar in part to anchor 50 (a knotless SutureTak anchor) except for the fact that the post is optional and the anchor contains two or more sutures and suture shuttling devices (suture/nitinol constructs)

- b. Anchor 150 has no post, sutures 30a, 30b are knotted at base of anchor 150 in knot 39 (FIG. 52); FIG. 52 shows an exemplary modified anchor 150 which is provided with no post but with two suture/nitinol loop constructs built within the anchor

- c. Suture shuttle is inserted through a portion of the suture so both ends of shuttle extend from top of anchor as well as one end of suture

- d. Insert Anchor 150 into bone 90 (a single anchor 150 can be used to hold the rotator cuff 80 together)

- e. Using suture passer instrument, pass suture A (suture 30a) up through tissue 80 on one side of tear 84a (FIG. 53)

- f. Feed suture A (suture 30a) through loop 44a of suture shuttle 40a

- g. Pull suture shuttle 40a, pulling suture A (suture 30a) through itself and anchor body to create a splice within the anchor body

- h. Using suture passer instrument, pass suture B (suture 30b) up through tissue 80 on opposite side of tear 84a

- i. Feed suture B (suture 30b) through loop 44b of suture shuttle 40b

- j. Pull suture shuttle 40b, pulling suture B (suture 30b) through itself and anchor body to create a second splice within the anchor body

- k. Tension ends of suture A and B (sutures 30a and 30b) until desired tension is reached

- l. Suture ends 30a, 30b may be cut when repair is complete (FIG. 53)

Embodiment B—Multiple Interconnected Knotless Anchor Constructs

Methods of Using Multiple Knotless Anchors to Create a Construct

FIGS. 54-59

1) Simple Stitch with Tied Mattress

- a. Insert Anchor 1 (50a) into bone 90 using driver, remove driver exposing suture 30a and suture passing construct 40a with wire loop 44a

- i. Can pre-drill bone hole or tap
- ii. Can go through tissue or under it directly into bone

- b. Using suture passing instrument, pass suture 30a through or around the tissue 80

- c. Feed suture 30a through the loop 44a of suture shuttle 40a

- d. Pull end of suture shuttle 40a to pull suture 30a through itself and through the anchor body to form inside splice (these are the same steps as Embodiment A1 steps a-d)

- e. Pass the suture 30a back up through the tissue 80

- f. Continue to pull suture 30a until the tissue is in desired position and tension

- g. Insert Anchor 2 (50b) into desired position in bone 90, repeat steps b-f with suture 30b from Anchor 2 (50b)

- h. Using suture passing instrument, pass suture 30b up through tissue 80 (FIG. 54)

- i. Feed suture 30b through loop 44b of suture shuttle 40b (FIG. 55)

- j. Pull end of suture shuttle 40b to pull suture 30b through itself and the anchor body to form another inside splice (FIG. 56)

- k. Pass the suture 30b back up through the tissue 80 using suture passing instrument 35 (FIG. 57)

- l. Pull ends of both sutures 30a, 30b until desired tension and tissue position is reached (FIG. 58)

- m. Tie the suture limbs 30a, 30b of the two anchors 50a, 50b together in knot 39 to complete the mattress stitch (FIG. 59)

- n. Cut the sutures 30a, 30b when repair is complete (FIG. 59)

FIGS. 60-71

2) Interlocked Looped Mattress Over Two Anchors

- a. Insert Anchor 1 (50a) into bone 90 using driver, remove driver exposing suture 30a and suture passing construct 40a with wire loop 44a

- i. Can pre-drill bone hole or tap
- ii. Can go under tissue directly into bone

- b. Using suture passing instrument 35, pass suture 30a up through the tissue 80 and back down through the tissue 80 (FIGS. 60 and 61)

- c. Feed suture 30a through the loop 44a of suture shuttle 40a (FIG. 62)

- d. Pull end of suture shuttle 40a to pull suture 30a through itself and through the anchor body to form splice within the anchor body

- e. Continue to pull suture, leaving slack in loop **32a** above the tissue **80** to pass the second suture **30b** through it (FIG. **63**)
- f. Insert Anchor **2** (**50b**), remove driver, pass suture **30b** from Anchor **2** (**50b**) up through tissue **80** using suture passing instrument **35** (FIG. **64**)
- g. Pass suture **30b** through the suture loop **32a** of Anchor **1** (**50a**) (FIG. **65**)
- h. Pass suture **30b** back down through the tissue **80** (FIG. **66**)
- i. Feed end of suture **30b** through loop **44b** of the suture shuttle **40b** of Anchor **2** (**50b**) (FIG. **67**)
- j. Pull end of suture shuttle **40b** to pull suture **30b** through itself and body of Anchor **2** (**50b**) to form another splice and leaving two interlocked loops **32a**, **32b** above the tissue **80** (FIG. **68**)
- k. Pull the two sutures **30a**, **30b** to the desired tension to complete the mattress stitch (FIGS. **69** and **70**)
- l. Cut the sutures **30a**, **30b** when the repair is complete (FIG. **71**, also showing top view of the inserted anchors **50a**, **50b**)

FIGS. **72-75**

3) Two or More Anchors in Daisy Chain

- a. Insert Anchor I (**50a**), insert Anchor II (**50b**), insert Anchor III (**50c**) all in bone **90**, remove drivers (FIG. **72**)
- b. Using suture passing instrument, pass suture **30a** of Anchor I (**50a**) up through the tissue **80**
- c. Feed the suture I (**30a**) through loop **44b** of the suture shuttle **40b** of Anchor II (**50b**)
- d. Pass suture II (**30b**) of Anchor II (**50b**) up through tissue **80**, feed through loop **44c** of suture shuttle **40c** of Anchor III (**50c**)
- e. Pass the suture III (**30c**) up through tissue **80**, feed through loop **44a** of suture shuttle **40a** of Anchor I (**50a**)
- f. Pull suture shuttles **40a**, **40b**, **40c** and respective sutures **30a**, **30b**, **30c** through body of Anchors **50a**, **50b**, **50c** (FIG. **74**) to form respective splices within each of these anchors
- g. Tighten sutures **30a**, **30b**, **30c** until desired tension (FIG. **75**)
- h. Cut all sutures **30a**, **30b**, **30c** when repair completed
- i. Option: can be repeated with any number of anchors, in any order

FIGS. **76-95**

4) Double Row Rotator Cuff or Achilles Tendon Repair Using Daisy Chain

- a. Drill holes **91a**, **91b**, **91c**, **91d** for all 4 anchors **50a**, **50b**, **50c**, **50d**, two anchors under tissue **80** and two anchors on outside edge of tissue **80** (FIGS. **76** and **77**)
- b. Place Anchor I (**50a**) and Anchor III (**50c**), using suture passing instrument pass suture **30a** and suture shuttle **40a** with loop **44a** from Anchor I (**50a**) up through tissue **80** (FIG. **78**)
- c. Feed end of suture I (**30a**) through loop **44c** of suture shuttle **40c** of Anchor III (**50c**) and shuttle suture through Anchor III (**50c**) (FIGS. **79** and **80**)
- d. Pull end of suture I (**30a**) until desired tension reached and insert Anchor II (**50b**) (FIG. **81**)
- e. Pass suture II (**30b**) and suture shuttle **40b** with loop **44b** up through tissue (FIGS. **82** and **83**)
- f. Feed end of suture III (**30c**) through loop **44b** of suture shuttle **40b** of Anchor II (**50b**) and shuttle suture III (**30c**) through Anchor II (**50b**) (FIG. **84**)
- g. Pull end of suture III (**30c**) until desired tension reached (FIG. **85**)

- h. Insert Anchor IV (**50d**) with suture **30d** and shuttle loop **44d** (FIG. **86**)
- i. Feed end of suture II (**30b**) through loop **44d** of suture shuttle **40d** of Anchor IV (**50d**) (FIG. **87**)
- j. Shuttle suture II (**30b**) through Anchor IV (**50d**) (FIG. **88**)
- k. Pull end of suture II (**30b**) until desired tension reached (FIG. **89**)
- l. Feed end of suture IV (**30d**) through loop **44a** of suture shuttle **40a** of Anchor I (**50a**) (FIG. **90**)
- m. Shuttle suture IV (**30d**) through Anchor I (**50a**) (FIG. **91**)
- n. Pull end of suture IV (**30d**) until desired tension reached (FIGS. **92** and **93**)
- o. Pull ends of sutures I, II, III, and IV (**30a**, **30b**, **30c**, **30d**) to complete repair (FIG. **94**)
- p. Cut ends of sutures **30a**, **30b**, **30c**, **30d** (FIG. **95**)

Embodiment C—Multiple Anchor Constructs Using 2 Different Types of Knotless Anchors

Method of Using 2 Different Style Knotless Anchors Together

FIGS. **96-99**

1) Two Anchor Mattress with Suture Shuttle (Anchor **1** is Anchor **50a**, Anchor **2** is a Modified Anchor **250** in that it has No Suture, Only Suture Shuttle **40b** with Loop **44b**)

- a. Insert Anchor **1** (**50a**) into bone **90** through or under tissue **80** and remove driver exposing suture **30a** and loop **44a** of suture shuttle **40a**
- b. Insert Anchor **2** (**250**) into bone **90** and remove driver exposing suture shuttle **40b** with loop **44b** (FIG. **96**)
- c. Using suture passing instrument, pass the suture **30a** from Anchor **1** (**50a**) up through the tissue **80**
- d. Using suture passing instrument, pass suture through tissue near site of Anchor **2** (**250**)
 - i. Optional: pass suture shuttle **40b** of Anchor **2** (**250**) through tissue **80** near Anchor **2** (**250**)
- e. Feed suture **30a** through the loop **44b** of suture shuttle **40b** of Anchor **2** (**250**) (FIG. **97**)
- f. Pull end of suture shuttle **40b** to pass suture **30a** through the body of Anchor **2** (**250**) and form splice within the anchor body
 - i. If used Optional d.i. step, then using shuttle **40b**, pull suture **30a** down through tissue **80**, through Anchor **2** (**250**) body and back up through tissue **80**, skip to step h

- g. Pass the suture **30a** up through the tissue **80** near Anchor **2** (**250**)
- h. Pass the suture **30a** down through the tissue **80** near Anchor **1** (**50a**)
- i. Feed the suture **30a** through the loop **44a** of suture shuttle **40a** of Anchor **1** (**50a**) (FIG. **98**)
- j. Pull end **40a** of the suture shuttle to pass suture **30a** through itself and body of Anchor **1** (**50a**) and form splice within the anchor body (FIG. **99**)
- k. Pull the suture **30a** until the desired placement of the tissue **80** and tension is reached
- l. Cut suture **30a** to complete the repair (FIG. **99**)

FIGS. **100** and **101**

Options: Rotator Cuff Repair Using Two Anchor **2** (**250**) for Medial Row and Two Anchor **1** (**50a**) for the Lateral Row or Anchor **1** (**50a**) for Medial Row and Anchor **2** (**250**) for Lateral Row (FIG. **100**)

FIG. **101**

2) Modified Knotless Anchors in Double Row Construct

- a. Anchor **1** is modified to accommodate 2 sutures (**1A** & **1B**) and 2 suture shuttles; anchor **1** is similar to anchor **150** of FIG. **52**

11

- b. Anchor **2 (350)** is modified to accommodate 2 suture shuttles (**2A & 2B**) without any suture
- c. Insert Anchor **1** into bone for the lateral row
- d. Insert two Anchor **2 (350)** into bone for the medial row
- e. Using suture passing instrument pass suture **1A** from Anchor **1** through tissue near Anchor **2**
- f. Feed suture **1A** through suture shuttle **2A** of Anchor **2**
- g. Pull suture **1A** through body of Anchor **2** and back up through tissue
- h. Feed suture **1A** through suture shuttle **1A** of Anchor **1**
- i. Pull suture shuttle **1A** and suture **1A** through itself and the body of Anchor **1**
- j. Pull until desired tension and tissue position obtained
- k. Using suture passing instrument, pass suture **1B** from Anchor **1** through tissue near 2^{nd} Anchor **2**
- l. Feed suture **1B** through suture shuttle **2A** of 2^{nd} Anchor **2**
- m. Pull suture **1B** through body of 2^{nd} Anchor **2** and back up through tissue
- n. Feed suture **1B** through suture shuttle of Anchor **1**
- o. Pull suture shuttle and suture **1B** through itself and body of Anchor **1**
- p. Pull suture **1B** until desired tension and tissue position obtained
- q. Insert 2^{nd} Anchor **1** into bone for the lateral row
- r. Using suture passing instrument pass suture **1A** of 2^{nd} Anchor **1** through tissue near Anchor **2**
- s. Feed suture **1A** through suture shuttle **2B** of Anchor **2**
- t. Pull suture **1A** through body of Anchor **2** and back up through tissue **20**
- u. Feed suture **1A** through suture shuttle **1A** of 2^{nd} Anchor **1**
- v. Pull suture shuttle **1A** and suture **1A** through itself and body of 2^{nd} Anchor **1**
- w. Pull until desired tension and tissue position obtained
- x. Using suture passing instrument, pass suture **1B** from 2^{nd} Anchor **1** through tissue near 2^{nd} Anchor **2**
- y. Feed suture **1B** through suture shuttle **2B** of 2^{nd} Anchor **2**
- z. Pull suture **1B** through body of 2^{nd} Anchor **2** and up through tissue
- aa. Feed suture **1B** through suture shuttle of 2^{nd} Anchor **1**
- bb. Pull suture shuttle and suture **1B** through itself and body of 2^{nd} Anchor **1**
- cc. Pull suture **1B** until desired tension and tissue position is obtained
- dd. Cut all suture ends when repair is complete

Options: Any Suture can be Loaded Through Any Anchor as Long as All Splices are Tightened.

The knotless suture constructs and systems of the present invention are used in conjunction with any knotless fixation devices which can allow a flexible strand and attached suture passing device to form a splice within the body of the fixation device. The fixation devices may be any of swivel and/or screw-in suture anchors and/or push-in suture anchors (such as an Arthrex SwiveLock® anchor, disclosed in U.S. Patent Application Publication No. 2008/0004659 or a PushLock® anchor, as disclosed in U.S. Pat. No. 7,329, 272). The fixation devices may be also any anchors, implants or screws (such as interference screws or tenodesis screws) so or any fixation element that allows attachment/fixation of the knotless suture construct to bone. The fixation devices/implants may have various sizes (various diameters and/or lengths) and may be formed of biocompatible materials such as PEEK, biocomposite materials, metals and/or metal alloys, or combination of such materials, among others.

12

The flexible strand **30** may be a high-strength suture, such as an ultrahigh molecular weight polyethylene (UHMWPE) suture which is the preferred material as this material allows easy splicing. Alternatively, the high strength suture may be a FiberWire® suture, which is disclosed and claimed in U.S. Pat. No. 6,716,234, the entire disclosure of which is incorporated herein by reference. FiberWire® suture is formed of an advanced, high-strength fiber material, namely ultrahigh molecular weight polyethylene (UHMWPE), sold under the tradenames Spectra (Honeywell) and Dyneema (DSM), braided with at least one other fiber, natural or synthetic, to form lengths of suture material. The preferred FiberWire® suture includes a core within a hollow braided construct, the core being a twisted yarn of UHMWPE. Typically the suture will be UHMWPE suture without a core to permit ease of splicing. The shuttle/pull device may be a shuttle/pull suture device such as a FiberLink™ or a Nitinol loop.

The strands may also be formed of a stiff material, or combination of stiff and flexible materials, depending on the intended application. The strands may be also formed of suture tape or a combination of suture and tape, a stiff material, or combination of stiff and flexible materials, depending on the intended application. The strands may be also coated and/or provided in different colors. The knotless anchors of the present invention can be used with any type of flexible material or suture that forms a splice and a loop.

The knotless suture constructs also include sutures that are spliced—at least in part—in a manner similar to an Arthrex ACL TightRope®, such as disclosed in U.S. Patent Application Publication Nos. 2010/0256677 and 2010/0268273, the disclosures of which are incorporated by reference herein.

While the present invention is described herein with reference to illustrative embodiments for particular applications, it should be understood that the invention is not limited thereto. Those having ordinary skill in the art and access to the teachings provided herein will recognize additional modifications, applications, embodiments and substitution of equivalents all fall within the scope of the invention. Accordingly, the invention is to be limited not by the specific disclosure herein, but only by the appended claims.

What is claimed is:

1. A method of tissue repair, comprising the steps of: installing at least one fixation device in bone, the fixation device comprising a body, a flexible strand extending through the body and a shuttling device threaded to the flexible strand within the fixation device through a splice region thereof, the flexible strand and the shuttling device being pre-loaded on the fixation device such that the entirety of the splice region of the flexible strand is located within the fixation device; passing the flexible strand through or around tissue to be fixated; pulling on the shuttling device to allow the flexible strand to form a splice through itself within the fixation device, and provide tensioning of the tissue to be fixated relative to the bone; and forming, with the flexible strand and the shuttling device, a knotless closed loop having an adjustable perimeter, after the steps of installing the fixation device in bone and passing the flexible strand through or around the tissue.

2. The method of claim 1, comprising the step of installing two or more fixation devices in the bone and passing a flexible strand from at least one of the two or more fixation devices around the tissue.

13

3. The method of claim 1, comprising the step of installing two or more fixation devices in the bone and passing a flexible strand from at least one of the two or more fixation devices through the tissue.

4. The method of claim 3, further comprising the step of forming a mattress stitch by passing a flexible strand from each of the plurality of fixation devices back and forth through the tissue.

5. The method of claim 3, further comprising the step of forming two knotless closed loops each having an adjustable perimeter.

6. The method of claim 5, wherein the two knotless closed loops are interlocked with each other.

7. The method of claim 1, wherein the tissue is soft tissue.

8. The method of claim 1, wherein the tissue is tendon, labrum, Achilles tendon, rotator cuff, biceps or capsular tissue.

9. The method of claim 1, further comprising the step of adjusting the length of the knotless closed loop to approximate tissue to bone.

10. The method of claim 1, further comprising the steps of:

installing the at least one fixation device into a hole in the bone; and

passing the flexible strand around or through the tissue to be fixated, and then through an eyelet of the shuttling device.

11. The method of claim 1, wherein the fixation device is an anchor with a post and a pair of openings symmetrically positioned relative to the post, the pair of openings extending in a direction about transversal to the longitudinal axis of the body, the pair of openings being configured to allow the flexible strand and attached shuttling device to be passed through the body of the fixation device and around the post.

12. The method of claim 1, wherein the flexible strand is a suture formed of ultrahigh molecular weight polyethylene and wherein the shuttling device is a suture passing instrument.

13. The method of claim 1, wherein the shuttling device is configured to be pulled out of the body of the fixation device.

14. A method of tissue repair, comprising the steps of: installing a plurality of fixation devices into bone, each of the fixation devices including a flexible construct extending through the fixation device, the flexible construct comprising a flexible strand and a corresponding shuttling device threaded to the flexible strand within the fixation device through a splice region thereof the flexible construct being pre-loaded on the fixation device such that the entirety of the splice region of the flexible strand is located within the fixation device; passing each of the flexible strands around or through tissue to be fixated, and then through an eyelet of the shuttling devices; and pulling on each of the shuttling devices to allow each of the flexible strands to form a splice through itself within the fixation device, and provide tensioning of the tissue to be fixated relative to the bone.

15. The method of claim 14, comprising the step of passing each of the flexible strands around or through tissue to be fixated, and then through its corresponding eyelet of the shuttling/pulling device.

16. The method of claim 14, comprising the step of passing each of the flexible strands around or through tissue to be fixated, and then through an eyelet of one of the corresponding shuttling devices of an adjacent fixation device.

17. The method of claim 16, wherein each of the flexible strands is passed through tissue to be fixated, and then

14

through an eyelet of one of any other of the corresponding shuttling devices of any of the other fixation device of the plurality of fixation devices.

18. The method of claim 14, comprising the steps of:

installing a first, a second and a third fixation devices into bone, each of the first, second and third fixation devices including a flexible construct extending through each of the first, second and third fixation devices, the flexible construct comprising a flexible strand and a corresponding shuttling device attached to the flexible strand;

passing each of the flexible strands around or through tissue to be fixated;

passing the flexible strand of the first fixation device through an eyelet of the shuttling device of the second fixation device, passing the flexible strand of the second fixation device through an eyelet of the shuttling/pulling device of the third fixation device, and passing the flexible strand of the third fixation device through an eyelet of the shuttling/pulling device of the first fixation device; and

pulling on each of the shuttling devices to allow each of the flexible strands to form a splice through itself and within the fixation device, and provide tensioning of the tissue to be fixated relative to the bone.

19. The method of claim 18, wherein at least one of the first, second and third fixation devices is a knotless anchor.

20. A method of attaching tissue to bone using an anchor assembly including a driver and an anchor, the anchor comprising: an anchor body having a distal end, a proximal end, a longitudinal axis, and two surgical constructs pre-loaded within the anchor body, each of the two surgical constructs [consisting of] including a suture and a suture passing instrument attached to the suture, *the anchor being pre-loaded with two sutures, with the sutures passed around a post of the anchor and extending within a cannulation of the anchor, the sutures being secured by a knot at a most distal end of the anchor, the anchor, pre-loaded with sutures, being secured to a driver with the sutures tied to the driver, two suture passing instruments being threaded through the sutures, each of the suture passing instruments being attached to one of the sutures;* the method comprising the steps of:

[providing an anchor pre-loaded with two sutures by passing the sutures around a post of the anchor and extending the sutures within a cannulation of the anchor, the sutures being secured by a knot at a most distal end of the anchor;

securing the anchor pre-loaded with the sutures to a driver by tying the sutures to the driver;

threading two suture passing instruments through the sutures, each of the suture passing instruments being attached to one of the sutures;]

installing the anchor, pre-loaded with the sutures and with the attached suture passing instruments, into the bone using the driver;

removing the driver;

passing the sutures around or through tissue to be fixated; threading each of the sutures through a closed loop of each of their respective suture passing instruments;

pulling each of the suture passing instruments to allow each of the sutures to pass through itself, within the anchor body, and to form a splice in each of the sutures; and

15

removing the suture passing instruments and pulling on
the sutures to approximate tissue to bone.

* * * * *

16