



US00RE48144E

(19) **United States**
(12) **Reissued Patent**
Faulkner et al.

(10) **Patent Number: US RE48,144 E**
(45) **Date of Reissued Patent: Aug. 4, 2020**

(54) **SPLICE PROTECTOR FOR FIBER OPTIC RIBBONS**

(58) **Field of Classification Search**
CPC G02B 6/2258; G02B 6/448
See application file for complete search history.

(71) Applicant: **Corning Optical Communications LLC**, Hickory, NC (US)

(56) **References Cited**

(72) Inventors: **Michael Todd Faulkner**, Granite Falls, NC (US); **Lars Kristian Nielsen**, Hickory, NC (US)

U.S. PATENT DOCUMENTS

4,475,935 A 10/1984 Tanaka et al. 65/3.41
4,784,458 A 11/1988 Horowitz et al. 350/96.21
5,022,735 A 6/1991 Dahlgren 350/96.21

(Continued)

(73) Assignee: **Corning Optical Communications LLC**, Charlotte, NC (US)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/990,661**

DE 4343944 A1 6/1995 G02B 6/44
GB 2324622 10/1998 G02B 6/255

(22) Filed: **May 27, 2018**

(Continued)

Related U.S. Patent Documents

OTHER PUBLICATIONS

Reissue of:

(64) Patent No.: **9,360,624**
Issued: **Jun. 7, 2016**
Appl. No.: **14/206,392**
Filed: **Mar. 12, 2014**

International Preliminary Report on Patentability for PCT/US2013/033477, dated Oct. 2, 2014, 7 pages.

(Continued)

U.S. Applications:

(63) Continuation of application No. PCT/US2013/033477, filed on Mar. 22, 2013, which is a continuation of application No. 13/491,086, filed on Jun. 7, 2012, now Pat. No. 8,702,326.

(60) Provisional application No. 61/614,839, filed on Mar. 23, 2012.

(51) **Int. Cl.**
G02B 6/255 (2006.01)
G02B 6/44 (2006.01)


Primary Examiner — Deandra M Hughes
(74) *Attorney, Agent, or Firm* — Kapil U. Banakar

(52) **U.S. Cl.**
CPC **G02B 6/2558** (2013.01); **G02B 6/4495** (2013.01); **G02B 6/448** (2013.01)

(57) **ABSTRACT**

A fiber optic cable assembly includes first and second fiber optic ribbons and a splice protector. The ribbons are spliced together such that the corresponding spliced fibers at the splice have a common lengthwise axis, widthwise axis orthogonal to the lengthwise axis, and thickness axis orthogonal to the lengthwise and widthwise axes. The splice protector supports the ribbons that are spliced to one another at the splice. The splice protector may include or even consist essentially of an adhesive that provides a flexible support for the splice. The splice protector may be at least half as flexible when cured over the splice as the first and second ribbons in bending about the widthwise axis.

44 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,157,751 A 10/1992 Maas et al. 385/99
 5,257,337 A 10/1993 Grigsby et al. 385/99
 5,416,873 A * 5/1995 Huebscher G02B 6/2558
 385/95
 5,731,051 A 3/1998 Fahey et al. G02B 6/2558
 138/118.1
 6,265,476 B1 7/2001 Krongauz et al. .. C08F 290/067
 385/123
 6,915,043 B2 7/2005 Rio et al. 385/37
 7,251,411 B1 7/2007 Lu et al. 385/147
 7,289,714 B1 10/2007 Wells G02B 6/4475
 385/100
 7,349,605 B2 3/2008 Noonan et al. 385/100
 7,424,189 B2 9/2008 Lu et al. 385/100
 7,454,106 B2 11/2008 Cobb, III et al. 385/100
 7,480,436 B2 1/2009 Wells et al. 385/134
 7,489,843 B2 2/2009 Carlson et al. ... B29C 45/14549
 264/1.28
 7,556,441 B2 * 7/2009 Furuyama G02B 6/255
 385/137
 7,840,109 B2 11/2010 Lu et al. 385/114
 7,941,021 B2 5/2011 Cody et al. 385/100
 8,333,519 B2 12/2012 Marcouiller et al.
 G02B 6/2558
 385/135
 8,702,326 B2 * 4/2014 Faulkner G02B 6/2557
 385/95
 9,052,459 B2 * 6/2015 Compton G02B 6/2558
 9,360,624 B2 6/2016 Faulkner et al.
 2002/0000192 A1 1/2002 Kojima et al. 118/620
 2002/0179683 A1 * 12/2002 Carrier G02B 6/3833
 228/133
 2002/0187432 A1 * 12/2002 Dawes C09D 4/06
 430/321
 2003/0091293 A1 * 5/2003 Murata G02B 6/2558
 385/70
 2005/0207712 A1 * 9/2005 Saito G02B 6/3803
 385/95
 2009/0022457 A1 * 1/2009 de Jong G02B 6/3846
 385/96
 2009/0297099 A1 * 12/2009 Benjamin G02B 6/25
 385/32

2010/0247044 A1 9/2010 Noddings et al. ... G02B 6/2558
 385/99
 2012/0134629 A1 5/2012 Lu et al. 385/77
 2012/0243838 A1 * 9/2012 Sato G02B 6/2558
 385/96
 2013/0074303 A1 * 3/2013 Durrant G02B 6/2558
 29/402.14
 2013/0251317 A1 * 9/2013 Faulkner G02B 6/2557
 385/96
 2013/0251319 A1 * 9/2013 Compton G02B 6/2558
 385/99
 2014/0286615 A1 9/2014 Faulkner et al.
 2018/0329156 A1 * 11/2018 Flaig G02B 6/3861

FOREIGN PATENT DOCUMENTS

GB 2324622 A 10/1998
 JP 3-2304 U 1/1991 G02B 6/255
 JP H032304 U 1/1991
 WO 0212934 A1 2/2002

OTHER PUBLICATIONS

Author Unknown, "Flexible Micro Series: Fusion Splice Protection Sleeve," Product Description, Product # FSS-SC40, Retrieved on May 27, 2014 from www.splicetechnologies.com/FlexibleMicroSeries.php, Splice Technologies, Inc., 1 page.
 Non-Final Office Action for U.S. Appl. No. 14/206,392, dated Sep. 29, 2015, 9 pages.
 Notice of Allowance for U.S. Appl. No. 14/206,392, dated Feb. 8, 2016, 8 pages.
 Notice of Allowance for U.S. Appl. No. 13/491,086, dated Feb. 20, 2014, 8 pages.
 Non-Final Office Action for U.S. Appl. No. 13/491,086, dated Dec. 27, 2013, 8 pages.
 Patent Cooperation Treaty, International Search Report and Written Opinion for International Application No. PCT/US2013/033477; Jun. 19, 2013—9 pages.
 Splice Technologies, Inc., "Flexible Micro Series Fusion Splice Protection Sleeve," 2014—1 page; Retrieved on May 27, 2014 from <http://www.splicetechnologies.com/FlexibleMicroSeries.php>.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 5






FIG. 8 (NEW)

SPLICE PROTECTOR FOR FIBER OPTIC RIBBONS

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

RELATED APPLICATION

This is a continuation of International Application No. PCT/US2013/033477 filed Mar. 22, 2013, which claims the benefit of priority of U.S. application Ser. No. 13/491,086 filed Jun. 7, 2012 and U.S. application Ser. No. 61/614,839 filed on Mar. 23, 2012, the content of each of which is relied upon and incorporated herein by reference in its entirety.

BACKGROUND

Aspects of the present disclosure relate generally to splice protectors for optical fiber splicing such as splicing of fiber optic ribbons, where the splice protector surrounds and supports the splice to provide structural reinforcement to the area of the splice.

Splice protectors may be bulky and rigid, interfering with the ability to wind a spliced fiber optic ribbon on a reel or spool, or the ability to place the spliced ribbon in a narrow cavity, such as the cavity of a furcation tube or fiber optic distribution cable. A need exists for a splice protector that may be applied to a splice of spliced optical fibers optic in a time- and space-efficient manner, while allowing the spliced fibers at the splice to actively flex and bend, as may facilitate placement of the spliced fibers in an actively handled fiber optic assembly.

SUMMARY

One embodiment relates to a fiber optic cable assembly, which includes first and second fiber optic ribbons and a splice protector. The ribbons are spliced together such that the ribbons at the splice have a common lengthwise axis, widthwise axis orthogonal to the lengthwise axis, and thickness axis orthogonal to the lengthwise and widthwise axes. The splice protector supports the ribbons that are spliced to one another at the splice. The splice protector may include or even consist essentially of an adhesive that provides a flexible support for the splice. The splice protector may be at least half as flexible when cured over the splice as the first and second ribbons in bending about the widthwise axis.

Additional features and advantages are set forth in the Detailed Description that follows, and in part will be readily apparent to those skilled in the art from the description or recognized by practicing the embodiments as described in the written description and claims hereof, as well as the appended drawings. It is to be understood that both the foregoing general description and the following Detailed Description are merely exemplary, and are intended to provide an overview or framework to understand the nature and character of the claims.

BRIEF DESCRIPTION OF THE FIGURES

The accompanying Figures are included to provide a further understanding, and are incorporated in and constitute

a part of this specification. The drawings illustrate one or more embodiments, and together with the Detailed Description serve to explain principles and operations of the various embodiments. As such, the disclosure will become more fully understood from the following Detailed Description, taken in conjunction with the accompanying Figures, in which:

FIG. 1 is a schematic view of a splice protector according to an exemplary embodiment.

FIG. 2 is a digital image of a splice between two fiber optic ribbons.

FIG. 3 is a digital image of liquid UV-curable adhesive being inserted over the splice of FIG. 2, surrounded by a translucent mold according to an exemplary embodiment.

FIG. 4 is a digital image of UV-curing of the adhesive of FIG. 3 according to an exemplary embodiment.

FIG. 5 is a digital image of the splice protector of FIGS. 4, following the curing, flexing about a mandrel according to an exemplary embodiment.

FIG. 6 is a digital image of the splice protector of FIGS. 4 flexing about the mandrel of FIG. 5 with the mold removed according to an exemplary embodiment.

FIG. 7 is another digital image of the splice protector of FIGS. 6 flexing according to an exemplary embodiment.

FIG. 8 is a schematic view of a splice protector devoid of a substrate according to an exemplary embodiment.

DETAILED DESCRIPTION

Before turning to the following Detailed Description and Figures, which illustrate exemplary embodiments in detail, it should be understood that the present inventive and innovative technology is not limited to the details or methodology set forth in the Detailed Description or illustrated in the Figures. For example, as will be understood by those of ordinary skill in the art, features and attributes associated with embodiments shown in one of the Figures or described in the text relating to one of the embodiments may well be applied to other embodiments shown in another of the Figures or described elsewhere in the text.

Referring to FIG. 1, a fiber optic **110** assembly includes first and second fiber optic ribbons **112**, **114** (side view), each including a plurality of optical fibers (see, e.g., fibers **216** as shown in FIG. 2), such as at least 2, at least 6, or at least 12 optical fibers. According to an exemplary embodiment, the optical fibers of the ribbons **112**, **114** are coupled to the other optical fibers of the respective ribbons **112**, **114** in a substantially flat arrangement (e.g., planar) where the optical fibers are aligned side-by-side with one another to form the ribbons **112**, **114**.

According to an exemplary embodiment, the optical fibers of the first ribbon **112** are fusion spliced with the optical fibers of the second ribbon **114** such that the spliced ribbons **112**, **114** at the splice **116** have a common lengthwise axis L, widthwise axis W orthogonal to the lengthwise axis L, and thickness axis T orthogonal to the lengthwise and widthwise axes, L, W. A splice protector **118** supports the optical fibers of the first and second fiber optic ribbons **112**, **114** that are spliced to one another at the splice **116**. According to an exemplary embodiment, the splice protector **[116]** **118** includes an ultra-violet light (UV-) curable adhesive **120** that provides a flexible support for the splice **116**. The UV-curable adhesive **120** encapsulates the spliced optical fibers of the first and second ribbons **112**, **114** and also provides tensile strength to the splice **116**.

In some embodiments, the splice protector **118** is at least half as flexible as either of the first and second ribbons **112**,

114 in bending about the widthwise axis **W** (e.g., at least 60%, at least 75%), where flexibility or stiffness corresponds to the stiffness coefficient (i.e., force applied over resulting displacement) of the respective element. For example, flexibility may be observed with the moment required to bend the splice protector **118** about the widthwise axis **W** and an equal length of one of the ribbons **112**, **114** in a cantilever arrangement by a vertical deflection of the free end that is ten percent of the length. In some such embodiments, the splice protector **118** is at least as flexible as the first and second ribbons **112**, **114** in bending about the widthwise axis **W**.

Flexibility allows the splice protector **118** and splice **116** to bend and move with the spliced ribbons **112**, **114** around curved surfaces, such as a spool or reel for a corresponding fiber optic cable or assembly that includes the spliced ribbons **112**, **114**. Without sufficient flexibility, the splice protector **118** may pin or otherwise load the optical fibers of the ribbons **112**, **114**, particularly at the lengthwise ends of the splice protector **118**, possibly leading to attenuation and/or damaging the optical fibers. Accordingly, sufficient flexibility of the splice protector **118** may reduce stress concentrations, facilitating improved performance of the optical fibers of the splice **116**.

Various types of commercially-available UV-curable adhesives are contemplated for use with splice protectors, some of which have undergone testing by the Applicants. Examples of UV-curable adhesives for the splice protector **118** include commercially-available UV-curable adhesives manufactured by PENN COLOR and commercially-available UV-curable adhesives manufactured by LOCTITE. More specifically, the PENN COLOR UV-curable adhesives contemplated for use with splice protectors include material numbers are 706, RP54, 518, and RS81 and the LOCTITE UV-curable adhesives contemplated for use with splice protectors include LOCTITE® 3974™ LIGHT CURE and LOCTITE® 3106™ LIGHT CURE.

According to an exemplary embodiment, the cured UV-curable adhesive **120** of the splice protector **118** has a low-profile, such as having a thickness in the thickness axis **T** that is less than 2 mm (e.g., less than 1 mm, less than 0.75 mm, less than 0.5 mm) thicker than either the first or second fiber optic ribbons **112**, **114** in the thickness axis **T**. Furthermore, in some embodiments the cured UV-curable adhesive **120** has a narrow-profile, having a width in the width axis **W** that is less than 2 mm (e.g., less than 1 mm, less than 0.75 mm, less than 0.5 mm) wider than either the first or second fiber optic ribbons **112**, **114** in the width axis **W**.

According to one example, a twelve-fiber fiber optic ribbon **112**, **114** has a width of about 3.1 mm and thickness of about 0.3 mm. A corresponding twelve-fiber UV-curable adhesive splice mold **122** (e.g., Teflon) has a length of 30 mm, a width of 3.9 mm, and a thickness of 1.25 mm, without including a substrate in addition to the mold **122**. In such an example, the splice mold **122** defines the exterior of the splice protector **118**. In another example, a functional UV-curable adhesive splice protector **118** for the twelve-fiber ribbons **112**, **114** has a length of 27 mm, a width as small as 3.3 mm, and a thickness as thin as 0.6 mm, not including a substrate in addition to the mold **122**.

A narrow and low-profile UV-curable adhesive splice protector **118** allows the splice **116** to be inserted into a correspondingly narrow structure, such as a furcation tube, back into the jacket of a distribution cable, an overmold, or another narrow supporting structure. The narrow structure surrounding the splice **116** then allows for translation of the associated fiber optic assembly within correspondingly nar-

row ducts or other confined spaces, which may improve installation of the associated fiber optic assembly in a data center or elsewhere.

In some embodiments, the splice protector **118** of the fiber optic assembly includes a substrate **124** to provide extra strength to the splice **116**. The substrate **124** may be integrated or integral with the mold **122**, or may be a separate body in addition to the mold **122**. Put another way, the mold **122** may serve as the substrate in addition to being the mold **122**. In some embodiments, the splice protector **118** includes a translucent, flexible substrate **124**.

In other embodiments, the substrate **124** is a thin polymeric material, such as Teflon, placed interior to the mold **122**, between the mold **122** and the optical fiber. In some embodiments, the splice protector is a thin, flexible glass sheet (e.g., sheet of WILLOW™ glass manufactured by CORNING INCORPORATED). In some such embodiments, the thin, flexible glass sheet is less than 0.25 mm thick, such as about 0.15 mm thick, and therefore does not greatly increase the profile of the splice protector **118**. The sheet may or may not be flat.

In other embodiments, the splice protector **118** does not include a substrate **124**. The cured UV-curable adhesive **120** provides sufficient tensile strength for the splice **116**. As such, in some embodiments, the splice protector **118** is formed entirely from (e.g., consists of) UV-curable adhesive. Omission of the substrate **124** significantly reduces the materials required for protecting the splice **116**, saving costs associated with the substrate **124** as well as manufacturing time to prepare the substrate **124**. Furthermore, using only UV-curable adhesive **120** for the splice protector **118** provides increased reliability for the performance of the splice protector **118** by removing variability associated with interactions between different materials in the splice protector **118** and the specific fracture mechanics of the materials and corresponding interface.

In contemplated embodiments, the splice protector **118** includes a matrix or binding agent other than a UV-curable adhesive, such as an epoxy or other type of adhesive, thermoplastic, tape, or other material that may still provide the flexibility and profile characteristics disclosed herein. However, such materials may not be as quick to cure, as uniform, as efficient to apply, or as flexible as UV-curable adhesive. In at least some contemplated embodiments, a flexible substrate **124**, such as a flexible glass substrate, is used to support a splice **116** and is bound to the splice **116** with a heat shrink, such that UV-curable adhesive is not included.

Applicants note that methods and structures disclosed herein may not perform in the same way for single-fibers as with fiber optic ribbons. The ribbon profile allows for a greater volume of adhesive to be used without greatly increasing the profile of the splice protector about the splice, as disclosed herein. Single fibers may require a greater ratio of adhesive to achieve sufficient support for protection of the splice, which may decrease the flexibility of the spliced area and/or increase the profile of the splice protector. However, in contemplated embodiments, a UV-curable adhesive or other adhesive, with molds and substrates as disclosed herein, may be used to support the splice of single-fibers.

Referring now to FIGS. 2-7, a method of manufacturing a fiber optic assembly **210** includes a step of splicing first and second fiber optic ribbons **212**, **214**, as shown in FIG. 2. As discussed above with regard to the embodiment of FIG. 1, the first and second fiber optic ribbons **212**, **214** each include a plurality of optical fibers **216** coupled in a substantially flat arrangement where the optical fibers **216** are

aligned side-by-side with one another. The step of splicing includes fusion splicing the optical fibers **216** of the first ribbon **212** with the optical fibers **216** of the second ribbon **214** such that the spliced ribbons **212**, **214** at the splice **218** (e.g., multi-fiber fusion splice) have common lengthwise, widthwise, and thickness axes (see FIG. 1). During manufacturing, the ribbon fibers **212**, **214** may be placed into a fixture that holds the fibers straight, as shown in FIG. 2.

Referring now to FIG. 3, the method of manufacturing a fiber optic assembly **210** includes a step of coupling (e.g., contacting) a substrate **220** (e.g., Teflon mold) with the first and second fiber optic ribbons **212**, **214**, where the substrate **220** is translucent and able to communicate ultra-violet light. In some embodiments, the substrate **220** includes a flattened sleeve that slides over one the first and second ribbons **212**, **214** prior to the splicing step, and then slides over the splice **218** following the splicing step. In other contemplated embodiments, an substrate, such as a sheet is used with or in place of the substrate **220**.

According to an exemplary embodiment, the method further includes applying a liquid, UV-curable adhesive around the splice **218** and supported by the substrate **220**. In some embodiments, the method includes inserting a needle **222** coupled to a syringe **224** or other pump that supplies the liquid UV-curable adhesive to the splice **218**. The liquid UV-curable adhesive then fills space around the splice **218**. For example, a Teflon mold cavity is centered over the splice **218** and injected with UV adhesive material. In some embodiments, a heat shrinkable tube surrounds the splice **218**.

Referring to FIG. 4, the method of manufacturing a fiber optic assembly **210** includes directing light from an ultra-violet light source **230** at the UV-curable adhesive **232** through the substrate **220** to cure the UV-curable adhesive **232**. The ultra-violet light may reach the UV-curable adhesive prior to and/or following transmission through the substrate **220**. A mirror or other reflector may be positioned below the splice **218** to reflect the ultra-violet light back toward the underside of the splice **218**. The splice **218** may also be flipped during curing. For example, the UV material may be cured for approximately 30 sec on each side of the splice.

According to an exemplary embodiment, the UV-curable adhesive **232** encapsulates the splice **218** and, at least in part, forms a splice protector **226**. As shown in FIG. 5, the splice protector formed with the mold **220** and UV-curable adhesive **232** is flexible and may readily bend over a 1.25-inch mandrel **228** without damaging the splice **218** or splice protector **226**.

According to an exemplary embodiment, the method may further include a step of peeling the substrate **220** off of the cured UV-curable adhesive **232**, such that the splice protector **226** then does not include the substrate **220**. Instead, the splice protector **226**, as shown in FIGS. 6-7, consists of UV-curable adhesive **232** encapsulating the spliced optical fibers **216**. Removing the substrate may improve the flexibility of the splice protector **226**. Referring to FIGS. 6-7, the splice protector **226** without the substrate or mold after UV adhesive curing, readily bends over the 1.25-inch mandrel **228**. Furthermore, the bend radius is not limited to 1.25 inches, as shown in FIG. 7.

FIG. 8 shows a fiber optic assembly **310** including a splice protector **318** substantially identical to the splice protector **118** shown in FIG. 1, except the splice protector **318** is devoid of a substrate. The fiber optic assembly **310** includes first and second fiber optic ribbons **312**, **314** each including a plurality of optical fibers. The optical fibers of the first

ribbon **312** are fusion spliced with the optical fibers of the second ribbon **314** at a splice **316**, such that the spliced ribbons **312**, **314** at the splice **316** have a common lengthwise axis L , a widthwise axis W orthogonal to the lengthwise axis L , and a thickness axis T orthogonal to both the lengthwise axis L and the widthwise axis W . A splice protector **318** supports the optical fibers of the first and second fiber optic ribbons **312**, **314**. According to certain embodiments, the splice protector **318** includes an adhesive (e.g., UV-curable adhesive) **320** that encapsulates the spliced optical fibers of the first and second ribbons **312**, **314** and also provides tensile strength to the splice **316**.

According to an exemplary embodiment, the flexible splice protectors disclosed herein may be used with different fiber optic assemblies, including FlexNAP™ manufactured by CORNING CABLE SYSTEMS LLC, or more-generally in assemblies that operate in tight areas where bending is expected or uncontrolled. The low-profile and flexible design of the splice protectors allow an operator to insert a protected splice back inside a distribution cable, as if it were part of the internal structure of the cable. For example, embodiments disclosed herein allow for placement of the protected splice within the cavity of an RPX® distribution cable manufactured by CORNING CABLE SYSTEMS LLC.

According to an exemplary embodiment, the protected splice is also able to flex within the RPX distribution cable when operators install the cable around sheave wheels and the like. For example, sheave wheel testing at 600-lbs load with temperatures of -30° C. and 40° C., as per GR-3122 testing standards, have shown the protected splice to survive at these extremes. As such, embodiments disclosed herein enable a low-profile FlexNAP design using an RPX distribution cable, allowing FlexNAP to fit in smaller ducts, and thereby reducing costs to the customer. By way of example, dimensions and structural details of fiber optic cables and tether assemblies similar to FlexNAP and RPX ribbon cable are disclosed in International Application PCT/US06/29716 filed Jul. 27, 2006, which is incorporated by reference herein in its entirety.

The construction and arrangements of the splice protector, as shown in the various exemplary embodiments, are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes, and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter described herein. For example, UV adhesive could be substituted with other materials that are flexible, as well as the Teflon substrate/mold. Some elements shown as integrally formed may be constructed of multiple parts or elements, the position of elements may be reversed or otherwise varied, and the nature or number of discrete elements or positions may be altered or varied. The order or sequence of any process, logical algorithm, or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes and omissions may also be made in the design, operating conditions and arrangement of the various exemplary embodiments without departing from the scope of the present inventive and innovative technology.

What is claimed is:

1. A fiber optic assembly, comprising:
 - first and second fiber optic ribbons, each comprising a plurality of optical fibers coupled in an arrangement

7

- where the optical fibers are aligned side-by-side with one another, wherein the optical fibers of the first ribbon are spliced with the optical fibers of the second ribbon such that the spliced ribbons at the splice have a common lengthwise axis, widthwise axis orthogonal to the lengthwise axis, and thickness axis orthogonal to the lengthwise and widthwise axes; and
- a splice protector supporting the optical fibers of the first and second fiber optic ribbons that are spliced to one another at the splice, wherein the splice protector comprises an adhesive that provides a flexible support for the splice, *wherein the splice protector and the splice are bendable around curved surfaces about the widthwise axis, and* wherein the splice protector is at least [half] 60% as flexible when cured over the splice as the first and second ribbons in bending about the widthwise axis[, and wherein the splice protector is at least 60% as flexible as the first and second ribbons in bending about the widthwise axis] *at the splice.*
2. The fiber optic assembly of claim 1, wherein the splice protector has a low-profile, having a thickness in the thickness axis that is less than 1 mm thicker than either the first or second fiber optic ribbons in the thickness axis.
3. The fiber optic assembly of claim 2, wherein the splice protector has a narrow-profile, having a width in the [width] widthwise axis that is less [that] than 1 mm wider than either the first or second fiber optic ribbons in the [width] widthwise axis.
4. The fiber optic assembly of claim 1, wherein the splice protector is at least as flexible as the first and second ribbons in bending about the widthwise axis.
5. The fiber optic assembly of claim 1, wherein the splice protector does not include a substrate.
6. The fiber optic assembly of claim 1, wherein the splice protector consists of UV-curable adhesive.
7. A fiber optic assembly, comprising:
 first and second fiber optic ribbons, each comprising a plurality of optical fibers coupled in an arrangement where the optical fibers are aligned side-by-side with one another, wherein the optical fibers of the first ribbon are spliced with the optical fibers of the second ribbon such that the spliced ribbons at the splice have a common lengthwise axis, widthwise axis orthogonal to the lengthwise axis, and thickness axis orthogonal to the lengthwise and widthwise axes; and
 a splice protector supporting the optical fibers of the first and second fiber optic ribbons that are spliced to one another at the splice, wherein the splice protector comprises an ultra-violet light (UV-) curable adhesive facilitating a controlled profile for the splice protector; wherein the splice protector has a low-profile, having a thickness in the thickness axis that is less than [1] 0.75 mm thicker than either the first or second fiber optic ribbons in the thickness axis; [and]
 wherein the splice protector has a narrow-profile, having a width in the [width] widthwise axis that is less [that] than 1 mm wider than either the first or second fiber optic ribbons in the [width] widthwise axis[, and wherein the thickness of the splice protector is less than 0.75 mm thicker than either the first or second fiber optic ribbons in the thickness axis]; and
wherein the splice protector and the splice are bendable around curved surfaces about the widthwise axis.
8. The fiber optic assembly of claim 7, wherein the thickness of the splice protector is less than 0.5 mm thicker than either the first or second fiber optic ribbons in the thickness axis.

8

9. The fiber optic assembly of claim 7, wherein the width of the splice protector is less [that] than 0.75 mm wider than either the first or second fiber optic ribbons in the [width] widthwise axis.
10. The fiber optic assembly of claim 7, wherein the width of the splice protector is less [that] than 0.5 mm wider than either the first or second fiber optic ribbons in the [width] widthwise axis.
11. The fiber optic assembly of claim 7, wherein the splice protector does not include a substrate.
12. The fiber optic assembly of claim 11, wherein the splice protector consists of UV-curable adhesive.
13. A fiber optic assembly, comprising:
 first and second fiber optic ribbons, each comprising a plurality of optical fibers coupled in an arrangement where the optical fibers are aligned side-by-side with one another, wherein the optical fibers of the first ribbon are spliced with the optical fibers of the second ribbon such that the spliced ribbons at the splice have a common lengthwise axis, widthwise axis orthogonal to the lengthwise axis, and thickness axis orthogonal to the lengthwise and widthwise axes; and
 a splice protector supporting the optical fibers of the first and second fiber optic ribbons that are spliced to one another at the splice,
 wherein the splice protector consists essentially of an adhesive that provides a flexible support for the splice, *wherein the splice protector and the splice are bendable around curved surfaces about the widthwise axis, and*
 wherein the splice protector is at least 60% as flexible as the first and second ribbons in bending about the widthwise axis *at the splice.*
14. The fiber optic assembly of claim 13, wherein the splice protector consists of the adhesive.
15. The fiber optic assembly of claim 14, wherein the adhesive is an ultra-violet light (UV-) curable adhesive.
16. The fiber optic assembly of claim 13, wherein the splice protector has a low-profile, having a thickness in the thickness axis that is less than 1 mm thicker than either the first or second [optical fibers] *fiber optic ribbons* in the thickness axis.
17. The fiber optic assembly of claim 13, wherein the splice protector has a narrow-profile, having a width in the [width] widthwise axis that is less [that] than 1 mm wider than either the first or second [optical fibers] *fiber optic ribbons* in the [width] widthwise axis.
18. *The fiber optic assembly of claim 1, further comprising:*
a fiber optic cable comprising the first and second fiber optic ribbons, wherein the fiber optic cable includes a jacket surrounding the splice protector.
19. *The fiber optic assembly of claim 7, further comprising:*
a fiber optic cable comprising the first and second fiber optic ribbons, wherein the fiber optic cable includes a jacket surrounding the splice protector.
20. A fiber optic assembly, comprising:
 first and second fiber optic ribbons, each comprising a plurality of optical fibers coupled in an arrangement where the optical fibers are aligned side-by-side with one another, wherein the plurality of optical fibers of the first fiber optic ribbon are joined to the plurality of optical fibers of the second fiber optic ribbon by a fusion splice such that the spliced first and second fiber optic ribbons have a common lengthwise axis in a region of the fusion splice, a common widthwise axis

orthogonal to the lengthwise axis at the fusion splice, and a common thickness axis orthogonal to the lengthwise and widthwise axes at the fusion splice; and

a splice protector comprising a solid thermoplastic material encapsulating the fusion splice and providing a flexible support for the pluralities of optical fibers of the first and second fiber optic ribbons at the fusion splice, wherein the splice protector and the fusion splice are bendable around curved surfaces about the widthwise axis, and wherein the splice protector comprises at least one of the following features (i) to (iii):

(i) the splice protector has a low-profile, having a thickness along the thickness axis that is less than 0.75 mm thicker than either the first fiber optic ribbon or the second fiber optic ribbon along the thickness axis;

(ii) the splice protector has a narrow-profile, having a width along the widthwise axis that is less than 1 mm thicker than either the first fiber optic ribbon or the second fiber optic ribbon along the widthwise axis; or

(iii) the splice protector is bendable to conform to a surface of a 1.25 inch mandrel.

21. The fiber optic assembly of claim 20, wherein the splice protector has a low-profile, having a thickness along the thickness axis that is less than 0.75 mm thicker than either the first fiber optic ribbon or the second fiber optic ribbon along the thickness axis.

22. The fiber optic assembly of claim 20, wherein the splice protector has a narrow-profile, having a width along the widthwise axis that is less than 1 mm thicker than either the first fiber optic ribbon or the second fiber optic ribbon along the widthwise axis.

23. The fiber optic assembly of claim 20, wherein the splice protector is bendable to conform to a surface of a 1.25 inch mandrel.

24. The fiber optic assembly of claim 20, wherein the splice protector is at least 60% as flexible as the first and second fiber optic ribbons in bending about the widthwise axis.

25. The fiber optic assembly of claim 20, wherein the splice protector is devoid of a substrate configured to provide extra strength to the fusion splice.

26. The fiber optic assembly of claim 20, comprising at least one of the following features (a) or (b): (a) the splice protector has a thickness along the thickness axis that is less than 0.5 mm thicker than either the first fiber optic ribbon or the second fiber optic ribbon along the thickness axis, or (b) the splice protector has a width along the widthwise axis that is less than 0.5 mm wider than either the first fiber optic ribbon or the second fiber optic ribbon along the widthwise axis.

27. The fiber optic assembly of claim 20, wherein the splice protector is devoid of a heat shrinkable tube surrounding at least a portion of the fusion splice.

28. A fiber optic assembly, comprising:

first and second fiber optic ribbons each comprising a plurality of optical fibers coupled in an arrangement where the optical fibers are aligned side-by-side with one another, wherein the optical fibers of the first ribbon are spliced with the optical fibers of the second ribbon by a fusion splice such that the spliced ribbons at a region of the fusion splice have a common lengthwise axis, have a common widthwise axis orthogonal to the lengthwise axis, and are substantially arranged in a common plane; and

a splice protector consisting essentially of a solid thermoplastic material encapsulating and providing a flexible support for the first and second fiber optic ribbons at the fusion splice;

wherein the splice protector and the fusion splice are bendable around curved surfaces about the widthwise axis, and

wherein the splice protector is devoid of a substrate defining a cavity containing the solid thermoplastic material.

29. The fiber optic assembly of claim 28, wherein the splice protector is further devoid of any substrate configured to provide extra strength to the fiber optic assembly at the fusion splice.

30. The fiber optic assembly of claim 28, wherein the splice protector is devoid of a heat shrinkable tube surrounding at least a portion of the fusion splice.

31. The fiber optic assembly of claim 28, wherein the splice protector has a width along the widthwise axis that is less than 1 mm wider than either the first fiber optic ribbon or the second fiber optic ribbon along the widthwise axis.

32. The fiber optic assembly of claim 28, wherein the splice protector has a width along the widthwise axis that is at least 0.5 mm greater than either the first fiber optic ribbon or the second fiber optic ribbon along the widthwise axis.

33. The fiber optic assembly of claim 28, further comprising:

a fiber optic cable comprising the first and second fiber optic ribbons, wherein the fiber optic cable includes a jacket surrounding the splice protector.

34. The fiber optic assembly of claim 28, wherein: the plurality of optical fibers of the first fiber optic ribbon includes fiber optic segments extending from a ribbonized portion of the first fiber optic ribbon;

the plurality of optical fibers of the second fiber optic ribbon includes fiber optic segments extending from a ribbonized portion of the second fiber optic ribbon; and the thermoplastic material of the splice protector encapsulates an end of the ribbonized portion of the first fiber optic ribbon and an end of the ribbonized portion of the second fiber optic ribbon.

35. The fiber optic assembly of claim 28, wherein: the first and second fiber optic ribbons have a common thickness axis orthogonal to the lengthwise and widthwise axes at the fusion splice; and

the splice protector has a low-profile, having a thickness in the thickness axis that is less than 0.75 mm thicker than either the first or second fiber optic ribbons in the thickness axis.

36. The fiber optic assembly of claim 28, wherein the splice protector has a narrow-profile, having a width in the widthwise axis that is less than 1 mm wider than either the first or second fiber optic ribbons in the widthwise axis.

37. The fiber optic assembly of claim 36, wherein: the first and second fiber optic ribbons have a common thickness axis orthogonal to the lengthwise and widthwise axes at the fusion splice; and

the splice protector has a low-profile, having a thickness in the thickness axis that is less than 0.75 mm thicker than either the first or second fiber optic ribbons in the thickness axis.

38. A fiber optic assembly, comprising:

first and second fiber optic ribbons each comprising a plurality of optical fibers coupled in an arrangement where the optical fibers are aligned side-by-side with one another, wherein the optical fibers of the first ribbon are spliced with the optical fibers of the second

11

ribbon by a fusion splice such that the spliced ribbons at a region of the fusion splice have a common lengthwise axis and have a common widthwise axis orthogonal to the lengthwise axis; and

a splice protector consisting essentially of a solid thermoplastic material encapsulating and providing a flexible support for the first and second fiber optic ribbons at the fusion splice;

wherein the splice protector and the fusion splice are bendable to conform to a surface of a 1.25 inch mandrel; and

wherein the splice protector is devoid of a substrate defining a cavity containing the solid thermoplastic material.

39. The fiber optic assembly of claim 38, wherein the splice protector is further devoid of any substrate configured to provide extra strength to the fiber optic assembly at the fusion splice.

40. The fiber optic assembly of claim 38, wherein the splice protector is devoid of a heat shrinkable tube surrounding at least a portion of the fusion splice.

*41. The fiber optic assembly of claim 38, wherein:
the plurality of optical fibers of the first fiber optic ribbon includes fiber optic segments extending from a ribbonized portion of the first fiber optic ribbon;*

12

the plurality of optical fibers of the second fiber optic ribbon includes fiber optic segments extending from a ribbonized portion of the second fiber optic ribbon; and the thermoplastic material of the splice protector encapsulates an end of the ribbonized portion of the first fiber optic ribbon and an end of the ribbonized portion of the second fiber optic ribbon.

42. The fiber optic assembly of claim 38, further comprising:

10 a fiber optic cable comprising the first and second fiber optic ribbons, wherein the fiber optic cable includes a jacket surrounding the splice protector.

43. The fiber optic assembly of claim 38, wherein the splice protector has a maximum dimension along the widthwise axis that is less than 1 mm greater than a maximum dimension of either the first fiber optic ribbon or the second fiber optic ribbon along the widthwise axis.

44. The fiber optic assembly of claim 38, wherein the splice protector has a maximum dimension along the widthwise axis that is at least 0.5 mm greater than a maximum dimension of either the first fiber optic ribbon or the second fiber optic ribbon along the widthwise axis.

* * * * *