



US00RE48154E

(19) **United States**
(12) **Reissued Patent**
McClure

(10) **Patent Number:** **US RE48,154 E**
(45) **Date of Reissued Patent:** **Aug. 11, 2020**

(54) **SYSTEM AND METHOD FOR INTEGRATING AUTOMATIC ELECTRICAL STEERING WITH GNSS GUIDANCE**

(71) Applicant: **AGJUNCTION LLC**, Hiawatha, KS (US)

(72) Inventor: **John A. McClure**, Scottsdale, AZ (US)

(73) Assignee: **AGJUNCTION LLC**, Scottsdale, AZ (US)

(21) Appl. No.: **15/211,865**

(22) Filed: **Jul. 15, 2016**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,781,685**
Issued: **Jul. 15, 2014**
Appl. No.: **13/944,767**
Filed: **Jul. 17, 2013**

U.S. Applications:

(60) Provisional application No. 61/672,621, filed on Jul. 17, 2012.

(51) **Int. Cl.**
G05D 1/02 (2020.01)
B62D 5/04 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G05D 1/0278** (2013.01); **A01B 69/008** (2013.01); **B62D 1/286** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC . B62D 1/286; B62D 1/02; B62D 3/00; B62D 3/04; B62D 3/10; B62D 5/04;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

515,286 A 2/1894 Dyer
2,400,868 A 12/1944 Le Tourneau
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2002325645 B2 3/2003
AU 2002325645 9/2007
(Continued)

OTHER PUBLICATIONS

Trimble Navigation Limited, "AgGPS EZ-Steer Sales Brochure", <http://www.trimble.com/Agriculture/>, last accessed 2011, (last updated Mar. 2010).


(Continued)

Primary Examiner — Samuel G Rimell
(74) *Attorney, Agent, or Firm* — Schwabe Williamson & Wyatt

(57) **ABSTRACT**

A guidance and vehicle control system for automatically steering a vehicle, such as an agricultural vehicle or a tractor, through a field. The system includes a GNSS receiver and antenna for determining the vehicle's instantaneous position, a guidance CPU, and an automatic steering subsystem integrated with the vehicle's electrical power system. The automatic steering subsystem can be interfaced with the steering column of the vehicle, and mechanically activates the steering column, thereby steering the vehicle according to instructions received from the CPU based upon the vehicle's position and a predetermined path. An interrupt element, such as a wheel movement sensor or a slip gear, may be interfaced with the automatic steering subsystem to allow for manual steering override of the automatic steering control.

11 Claims, 4 Drawing Sheets



US RE48,154 E

(51)	Int. Cl.		6,198,992 B1	3/2001	Winslow	
	B62D 1/28	(2006.01)	6,199,000 B1	3/2001	Keller et al.	
	A01B 69/04	(2006.01)	6,212,453 B1	4/2001	Kawagoe et al.	
	G01S 19/14	(2010.01)	6,233,511 B1	5/2001	Berger et al.	
(52)	U.S. Cl.		6,236,916 B1	5/2001	Staub et al.	
	CPC	B62D 5/046 (2013.01); G01S 19/14 (2013.01); G05D 1/027 (2013.01); G05D 2201/0201 (2013.01)	6,257,357 B1	7/2001	Teal et al.	
			6,275,357 B1	8/2001	Teal et al.	
			6,314,348 B1	11/2001	Winslow	
(58)	Field of Classification Search		6,336,066 B1	1/2002	Pellenc et al.	
	CPC	B62D 5/0409 ; B62D 5/0421 ; B62D 5/092 ; B62D 6/00 ; B62D 5/046 ; A01B 69/008 ; A01B 69/007 ; A01D 41/1278 ; G05D 1/0278 ; G05D 1/021 ; G05D 1/027 ; G05D 2201/0201 ; G01S 19/14	6,377,889 B1	4/2002	Soest	
			6,389,345 B2	5/2002	Phelps	
			6,397,147 B1	5/2002	Whitehead	
			6,397,569 B1 *	6/2002	Homburg	A01B 69/007 56/10.2 F
			6,424,054 B1	7/2002	Onnen et al.	
			6,431,576 B1	8/2002	Viaud et al.	
			6,434,462 B1	8/2002	Bevly et al.	
			6,445,983 B1	9/2002	Dickson et al.	
	See application file for complete search history.		6,463,374 B1	10/2002	Keller et al.	
			6,469,663 B1	10/2002	Whitehead et al.	
			6,484,827 B2	11/2002	Teal et al.	
(56)	References Cited		6,501,442 B2	12/2002	Nichols	
	U.S. PATENT DOCUMENTS		6,539,303 B2	3/2003	McClure et al.	
			6,553,299 B1	4/2003	Keller et al.	
			6,553,311 B2	4/2003	Lange et al.	
			6,577,952 B2	6/2003	Geier et al.	
			6,581,717 B1 *	6/2003	Sørensen	B62D 5/09 180/401
			6,622,091 B2	9/2003	Perlmutter et al.	
			6,631,916 B1	10/2003	Miller	
			6,643,576 B1	11/2003	O Connor et al.	
			6,688,403 B2	2/2004	Bernhardt et al.	
			6,703,973 B1	3/2004	Nichols	
			6,711,501 B2	3/2004	McClure et al.	
			6,789,014 B1	9/2004	Rekow et al.	
			6,804,587 B1	10/2004	O Connor et al.	
			6,819,780 B2	11/2004	Benson et al.	
			6,865,465 B2	3/2005	McClure	
			6,876,920 B1	4/2005	Mailer	
			6,923,288 B2	8/2005	Szabela	
			6,932,184 B2	8/2005	Wittmeijer	
			7,020,555 B1	3/2006	Janky et al.	
			7,065,440 B2	6/2006	Aral	
			7,142,956 B2 *	11/2006	Heiniger et al.	701/23
			7,162,348 B2	1/2007	McClure et al.	
			7,191,061 B2 *	3/2007	McKay	A01B 69/008 701/23
			7,225,060 B2	5/2007	O'Connor et al.	
			7,277,792 B2	10/2007	Overschie	
			7,290,633 B2	11/2007	Kasten et al.	
			7,349,779 B2	3/2008	Nelson	B62D 1/02 701/41
			7,363,132 B2	4/2008	Lange et al.	
			7,383,114 B1	6/2008	Lange et al.	
			7,383,916 B2	6/2008	Genz	
			7,400,957 B2	7/2008	Hofer et al.	
			7,437,230 B2	10/2008	McClure et al.	
			7,460,942 B2	12/2008	Mailer	
			7,477,973 B2	1/2009	Brewer et al.	
			7,574,290 B2	8/2009	Gibson et al.	
			7,578,361 B2	8/2009	Thacher	
			7,588,088 B2	9/2009	Zachman	
			7,648,002 B2	1/2010	Easton et al.	
			7,648,004 B1	1/2010	Larouche et al.	
			7,689,354 B2	3/2010	Heiniger et al.	
			7,762,135 B2	7/2010	Hertzman et al.	
			7,764,365 B2	7/2010	Nichols et al.	
			7,838,808 B1	11/2010	Ake	
			7,860,628 B2	12/2010	Lange	
			7,913,800 B2	3/2011	Graeve et al.	
			7,917,654 B2	3/2011	Toivonen	
			7,941,759 B2	5/2011	Kreissl et al.	
			7,970,519 B2	6/2011	Green	
			8,004,397 B2	8/2011	Forrest et al.	
			8,081,987 B2	12/2011	Manson et al.	
			8,112,201 B2	2/2012	Aral	
			8,116,977 B2	2/2012	Aral et al.	
			8,140,223 B2	3/2012	Whitehead et al.	
			8,190,337 B2	5/2012	McClure	

(56)

References Cited

U.S. PATENT DOCUMENTS

8,239,083 B2 * 8/2012 Durkos G05D 1/0219
700/245

8,265,826 B2 9/2012 Feller et al.

8,437,901 B2 5/2013 Anderson

8,583,315 B2 * 11/2013 Whitehead et al. 701/31.4

8,594,879 B2 * 11/2013 Roberge et al. 701/23

8,634,993 B2 * 1/2014 McClure et al. 701/50

8,639,416 B2 * 1/2014 Jones et al. 701/41

8,649,930 B2 2/2014 Reeve et al.

8,892,308 B2 * 11/2014 Davis B62D 1/28
701/41

2002/0072850 A1 6/2002 McClure et al.

2003/0187560 A1 10/2003 Keller et al.

2004/0186644 A1 9/2004 McClure et al.

2004/0210357 A1 10/2004 McKay et al.

2006/0167600 A1 7/2006 Nelson, Jr. et al.

2008/0195268 A1 8/2008 Sapilewski et al.

2009/0099730 A1 * 4/2009 McClure et al. 701/41

2009/0121932 A1 5/2009 Whitehead et al.

2009/0164067 A1 * 6/2009 Whitehead et al. 701/41

2010/0312428 A1 * 12/2010 Roberge et al. 701/23

2011/0015817 A1 1/2011 Reeve

2011/0018765 A1 1/2011 Whitehead et al.

2011/0054729 A1 3/2011 Whitehead et al.

2012/0059554 A1 3/2012 Omelchenko et al.

2012/0130593 A1 5/2012 Davis et al.

2012/0174445 A1 7/2012 Jones et al.

2012/0215410 A1 * 8/2012 McClure et al. 701/50

FOREIGN PATENT DOCUMENTS

WO 200024239 A1 5/2000

WO 2002080652 A1 10/2002

WO 2003019430 A1 3/2003

WO 2008080193 A1 7/2008

WO WO-2008080193 7/2008

WO 2010005945 A1 1/2010

WO WO-2010005945 1/2010

OTHER PUBLICATIONS

Web page for Orthman Manufacturing co. regarding the Tracer Quick-Hitch; www.orthman.com/htm/guidance.htm.

David M. Bevly; Comparison of INS vs. Carrier-Phase DGPS for Attitude Determination in the Control of Off-Road Vehicles; ION 55th Annual Meeting; Jun. 28-30, 1999; Cambridge, Massachusetts; pp. 497-504.

U.S. Appl. No. 60/465,146, filed Mar. 20, 2003, McClure et al.

Listing of Related Cases, Jul. 25, 2016, 1 page.

Noh, Kwang-Mo, Self-tuning controller for farm tractor guidance, Iowa State University Retrospective Theses and Dissertations, Paper 9874, (1990).

Van Zuydam, R.P., Centimeter-Precision Guidance of Agricultural Implements in the Open Field by Means of Real Time Kinematic DGPS, ASA-CSSA-SSSA, pp. 1023-1034 (1999).

Levine, Mike "Driving a Pickup with Electric Steering", <http://news.pickuptrucks.com/2010/05/driving-a-pickup-with-electric-power-steering.html>, (May 31, 2010).

Topcon Precision Agriculture, "AES-25 Accurate Electric Steering", <http://www.topconpa.com/products/guidance-systems/electric-steering/aes-25>, accessed Oct. 3, 2011.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

**SYSTEM AND METHOD FOR
INTEGRATING AUTOMATIC ELECTRICAL
STEERING WITH GNSS GUIDANCE**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED
APPLICATION

This application is a reissue application of U.S. patent application Ser. No. 13/944,767, filed Jul. 17, 2013, now issued U.S. Pat. No. 8,781,685, issued Jul. 15, 2014 which claims priority in U.S. Provisional Patent Application Ser. No. 61/672,621, filed Jul. 17, 2012, which [is] are all incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to automated equipment control using inputs based on global navigation satellite system (GNSS) navigation, and in particular to using an automatic steering system to guide between crop rows and against furrow row edges in agricultural applications.

2. Description of the Related Art

Current automated agricultural vehicle guidance and equipment control systems with GNSS-based technology and automatic steering can guide equipment through fields and control their operation with little or no direct human interaction. GNSS-based guidance systems are adapted for displaying directional guidance information to assist operators with manually steering the vehicles. For example, the OUTBACK S™ steering guidance system, which is available from AgJunction LTC (www.agjunction.com) and is covered by U.S. Pat. No. 6,539,303 and No. 6,711,501, which are incorporated herein by reference, includes an on-board computer capable of storing various straight-line and curved (“contour”) patterns. An advantage of this system is its ability to retain field-specific cultivating, planting, spraying, fertilizing, harvesting and other patterns in memory. This feature enables operators to accurately retrace such patterns. Another advantage relates to the ability to interrupt operations for subsequent resumption by referring to system-generated logs of previously treated areas.

Another type of GNSS vehicle guidance equipment automatically steers the vehicle along all or part of its travel path and can also control an agricultural procedure or operation, such as spraying, planting, tilling, harvesting, etc. Examples of such equipment are shown in U.S. Pat. No. 7,142,956, which is incorporated herein by reference. U.S. Pat. No. 7,437,230 shows satellite-based vehicle guidance control in straight and contour modes, and is also incorporated herein by reference. U.S. Pat. No. 7,162,348 is incorporated herein by reference and discloses an articulated equipment position control system and method whereby a working component, such as an implement, can be guided independently of a motive component, such as a tractor. The implement can optionally be equipped with its own GNSS antenna and/or receiver for interacting with a tractor-mounted GNSS system.

Ideally crops would be planted in perfectly straight, evenly-spaced rows. Guidance through such fields would consist of following relatively simple straight-line patterns. Such guidance modes are commonly referred to as straight line or “A-B” in reference to the equipment traveling in a straight line between point A and point B in a repeating pattern in order to cover an entire field, which is typically flat and rectangular and therefore efficiently divided into multiple, parallel swaths. However, field conditions in many areas are not suitable for A-B guidance. For example, hilly terrain sometimes requires the formation of constant-elevation terraces.

Guidance systems accommodate such irregular conditions by operating in “contour following” modes consisting of curvilinear tracks defined by multiple GNSS points along which the equipment is guided. Initial planting passes made with manual and visually-guided navigation, which may or may not be supplemented with GNSS navigational aids, can cause crop rows to deviate from straight lines. Accommodating such irregular crop rows in subsequent operations (e.g., spraying and harvesting) may require the equipment to deviate from straight-line passes.

Notwithstanding recent advances in GNSS-based guidance accuracy, the natural irregularities of row crop cultivation tend to compromise the effectiveness of navigation based solely on location-finding front satellite signals. Moreover, satellite signals are occasionally lost due to interference from atmospheric conditions, weather and electromagnetic fields (EMF). There are various levels of differential accuracy available for GNSS. The use of these can cause offsets and drifts, especially over the crop growth season from field preparation to harvesting. One option to compensate for such lapses in GNSS reception, inertial navigation systems (INS) with gyroscopes has been utilized for relatively short-term, supplemental guidance input.

An alternative concept includes automatic steering control upon collision detection by electrically or hydraulically controlling the physical steering control of the vehicle. Many systems accommodate operators overriding the automated functions. For example, an operator may respond to observed, actual field conditions in order to maintain the equipment on course. Custom applicators, who use their equipment on multiple farms, need guidance equipment capable of universal operation for optimizing their productivity while minimizing crop damage and avoiding vehicle collision on ground that is uneven or otherwise difficult to traverse. Such equipment should be usable by operators with minimal training operating at optimal speeds and should have the capacity for storing and recalling field data for reuse, for example front season-to-season. Higher equipment speeds also tend to create auto-steering discrepancies, which can lead to crop damage from equipment overruns.

Having an automatic steering system which detects user input and automatically disengages the steering system would lead to a synthesis between machine and man, resulting in the best of both worlds. Existing hydraulic steering systems make it difficult to override automatic control when manual control is desired. Such a system can be implemented simply and cheaply into existing machines, as opposed to the more intricate and expensive hydraulic steering systems currently being used.

All-terrain vehicles (ATVs) often utilize electrical steering assist consisting of a worm drive connected to an electrical steering motor for steering over and around obstacles and for power assist, e.g., at low speeds. Such a

drive can also be used to provide automatic steering in an agricultural vehicle, with manual over-ride through the use of a built-in slip gear.

Heretofore there has not been available an automatic steering system for an agricultural vehicle with the advantages and features of the present invention.

SUMMARY OF THE INVENTION

In the practice of the present invention, a system and method are provided for automatically controlling vehicles and equipment using GNSS and an electrical auto-steering system connected directly to the steering column. For example, agricultural equipment comprising a tractor and an implement can be equipped with a vector position and heading sensor subsystem including a GNSS receiver and antennas and an inertial (gyroscopic) subsystem with X, Y and Z axis sensors for sensing equipment attitude changes through six degrees of freedom. The GNSS and INS/gyroscopic input subsystems can be housed in a common enclosure for mounting on the tractor roof. A microprocessor-based controller processes the inputs and automatically controls the vehicle steering system in response thereto.

Using GNSS with auto-steering systems can provide further advantages. This invention allows manual or transparent switching between these modes, and also provides for a safety mechanism whereby the user's manual movement of the steering will automatically stop the automatic steering subsystem. Calibration of the recent line curvatures and offsets from previously logged GNSS tracks can be used to switch between modes while minimizing any crop damage should visual edge detection be lost. The edges can be defined by furrows, physical plants visible against soil or touching plants from adjacent rows. The main aspect of this invention applies an electrical automatic steering subsystem to an agricultural vehicle guided by GNSS.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an isometric view of a tractor with a block diagram of a vehicle control system with GNSS and automatic steering subsystems and embodying an aspect of the present invention.

FIG. 2 is a block diagram of a vehicle control system with GNSS and automatic steering subsystems and embodying an aspect of the present invention.

FIG. 3 is a plan view of an automatic steering subsystem embodying an element of an aspect of the present invention.

FIG. 4 is a flowchart demonstrating a method of practicing an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

I. Introduction and Environment

As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which may be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present invention in virtually any appropriately detailed structure.

Certain terminology will be used in the following description for convenience in reference only and will not be limiting. For example, up, down, front, back, right and left

refer to the invention as oriented in the view being referred to. The words "inwardly" and "outwardly" refer to directions toward and away from, respectively, the geometric center of the embodiment being described and designated parts thereof. Global navigation satellite systems (GNSS) are broadly defined to include GPS (U.S.), Galileo (European Union, proposed), GLONASS (Russia), Beidou (China), Compass (China, proposed), IRNSS (India, proposed), QZSS (Japan, proposed) and other current and future positioning technology using signals from satellites, with or without augmentation from terrestrial sources. Inertial navigation systems (INS) include gyroscopic (gyro) sensors, accelerometers and similar technologies for providing output corresponding to the inertia of moving components in all axes, i.e. through six degrees of freedom (positive and negative directions along transverse X, longitudinal Y and vertical Z axes). Yaw, pitch and roll refer to moving component rotation about the Z, X and Y axes respectively. Said terminology will include the words specifically mentioned, derivatives thereof and words of similar meaning.

II. Preferred Embodiment System 2

Referring to the drawings in more detail and as shown in FIG. 1, the reference numeral 2 generally designates a GNSS guidance system implementing an electrical direct-drive steering assistance mechanism 3, embodying an aspect of the present invention. Without limitation on the generality of useful applications of the guidance system 2, a GNSS receiver 4 and a guidance processor 6 are connected to a GNSS antenna 12 and installed into a vehicle 10, such as an agricultural vehicle or tractor. An auto-steering system 8 is electrically connected to the guidance processor 6, and is mechanically interfaced with the vehicle 10 via the steering assistance mechanisms 3. A remote base station 14 is placed in proximity to the working field which provides for differential GNSS guidance.

FIG. 2 displays additional detail for the guidance system 2. The GNSS receiver 4 is further comprised of an RF convertor (i.e., downconvertor) 16, a tracking device 18, and a rover RTK receiver element 20. The receiver electrically communicates with, and provides GNSS positioning data to, the guidance processor 6. This processor includes a graphical user interface (GUI) 26, a microprocessor 24, and a media element 22, such as a memory storage drive. The processor electrically communicates with, and provides control data to the auto-steering system 8. The auto-steering subsystem includes a wheel movement detection switch 28 and an encoder 30 for interpreting guidance and steering commands from the CPU 6.

The auto-steering system 8 primarily interfaces mechanically with the vehicle's steering column 34, which is mechanically attached to the physical steering wheel 32. A control line 42 transmits guidance data from the CPU 6 to the auto-steering system 8. An electrical subsystem 44, which powers the electrical needs of the vehicle 10, interfaces directly with the auto-steering system 8 through a power cable 46. The auto-steering subsystem can be mounted to the steering column 34 near the floor of the vehicle, and in proximity to the vehicle's control pedals 36. Alternatively, the auto-steering system 8 can be mounted at other locations along the steering column 34.

The auto-steering system 8 is shown in further detail in FIG. 3. A mounting rod 38 mounts the auto-steer system directly to the steering column 34. The main body 40 of the auto-steering system 8 is housed along the mounting rod, and includes the wheel move detection switch 28 or other means for detecting when the user desires to end the auto-steering commands.

5

The auto-steering system 8 physically drives and steers the vehicle 10 by actively turning the steering wheel 32 via the steering column 34. A motor 45 powered by the vehicle's electrical subsystem 44 powers a worm drive 50 which powers the worm gear 48 affixed to the auto-steering system 8. These components are preferably enclosed in an enclosure 51.

FIG. 4 demonstrates how a user would actively operate a vehicle with the preferred embodiment system presented above. The method of operating the system starts at 52. The GNSS receiver 4 acquires a GNSS signal at 54 and determines the vehicle's geographic position from this data. The GNSS receiver communicates this data to the CPU 6, which determines where the vehicle should be, according to pre-determined or actively-provided instructions for working the agricultural vehicle 10.

The user determines whether to engage the automatic steering feature at 56. If the user opts not to engage auto-steer, the user may maintain manual steering at 66. This allows the user to initially place the vehicle in a starting position.

If the user elects to activate auto-steering at 56, the auto-steering system engages at 58. The auto-steer features are similar to an electrical steering assist system commonly used with all-terrain-vehicles (ATVs). In an ATV, the electrical steering assist system engages when the system detects that the user is struggling because the wheels have encountered an obstacle or due to low ATV speeds. The electrical steering assist provides power to the steering column and actively aids the user in turning the wheels. In the present invention, this feature is reversed: when the auto-steering system is engaged, it automatically guides the vehicle along the path at 60 as instructed by the CPU until either the job is completed at 62, or until the operator manually grips the steering wheel and turns it at 64.

The operator's turning of the steering wheel at 64 cuts off the electrical auto-steer system, defaulting to manual steer control at 66. This is either caused by an automatic switch 28 which shuts off the auto-steer, or by use of a slip-gear which bypasses the worm drive's ability to control the steering column. The user may re-engage auto-steer at 56 at any time thereafter, either by activating a switch or by merely releasing the steering wheel.

If the job is complete at 62, the user disengages auto-steer at 68 in the same manner as above—either by flipping a switch or by manually gripping and turning the steering wheel, thereby over-riding auto-steer.

Once the job is completed and auto-steer is disengaged at 68, the job data may be downloaded to a portable device or an off-site computer at 70. This data can be used to improve field working procedures in the future. The data will determine if there was ever a time where the user manually took control of the vehicle, and will record the path taken by the user while auto-steer was disengaged. The next time this particular field is worked, the user will have the option to force the auto-steer system to follow the new path previously manually driven by the operator. The recorded results are displayed at 72 and the operation ends at 74.

It is to be understood that the invention can be embodied in various forms, and is not to be limited to the examples discussed above.

Having thus described the disclosed subject matter, what is claimed as new and desired to be secured by Letters Patent is:

1. A guidance system for a vehicle including steerable wheels and a steering mechanism connected to the steerable

6

wheels, the steering mechanism including a steering column mounting a steering wheel, which guidance system includes:

[a GNSS-based guidance subsystem including a GNSS receiver, a guidance processor including] a guidance CPU connected to [the] a GNSS-based guidance subsystem and a GNSS receiver thereof, an output from said guidance [processor] CPU for providing a steering signal output, a graphical user interface (GUI) connected to the guidance [processor] CPU, and a memory storage device connected to the [processor] guidance CPU;

an automatic steering subsystem including a drive connected to the steering mechanism and an encoder connected to the steering mechanism and the guidance [processor] CPU;

said drive including a motor connected to [said] an electrical subsystem; and

[an electrical subsystem connected to said automatic steering subsystem] a slip gear mechanically interfaced with said steering mechanism adapted to disconnect said drive from said steering mechanism.

2. The system of claim 1, further comprising:

[the vehicle steering mechanism including a steering column mounting a steering wheel; and]

a worm drive interfacing with said automatic steering subsystem and said steering column, wherein the slip gear is adapted to bypass said worm drive.

3. The system of claim 2, wherein said automatic steering subsystem is mounted in proximity to said steering column.

4. The system of claim 2, further comprising a mounting rod mounting said automatic steering subsystem to said steering column.

5. The system of claim 2, further comprising:

a wheel movement detection switch integrated into said automatic steering system; and

said wheel movement detection switch adapted to interrupt said automatic steering subsystem when said steering wheel is manually turned.

[6. The system of claim 2, further comprising:

a slip gear adapted to bypass said worm drive, said slip gear mechanically interfaced with said steering column.]

7. A system for controlling an agricultural vehicle including a steering column connected to steerable wheels and mounting a steering wheel, which guidance system includes:

a GNSS guidance subsystem including [an RF converter,] a GNSS receiver[,] and a GNSS antenna;

an automatic steering subsystem including a worm drive having a worm gear, [and an encoder;] said automatic steering subsystem mechanically interfaced with said steering column via said worm drive and

[an electrical subsystem adapted for powering a plurality of electrical components of the vehicle, said electrical subsystem interfaced with said automatic steering subsystem via a power cable;]

said worm drive powered by a motor connected to [said] an electrical subsystem;

a guidance CPU electronically connected to said GNSS guidance subsystem[,] and said automatic steering subsystem, a graphical user interface (GUI), and a memory storage device; and

[said automatic steering subsystem mechanically interfaced with said steering column via said worm drive; a mounting rod mounting said automatic steering subsystem to said steering column;

a wheel movement detection switch integrated into said automatic steering system; and

7

said wheel movement detection switch adapted to interrupt said automatic steering subsystem when said steering wheel is manually turned] *a slip gear mechanically interfaced with said steering column and adapted to bypass said worm drive.*

8. A method of controlling a vehicle having a steering column attached to a steering wheel, the method comprising the steps:

providing a GNSS guidance subsystem including an RF converter, a GNSS receiver and a GNSS antenna;

providing an automatic steering subsystem including a worm drive having a worm gear, and an encoder;

connecting said GNSS guidance subsystem and said automatic steering subsystem to an electrical subsystem integrated into the vehicle, said electrical subsystem powering a plurality of electrical components connected to said vehicle;

interfacing said worm drive with the steering column of the vehicle;

providing a guidance CPU electronically connected to said GNSS guidance subsystem and said automatic steering subsystem;

locating said vehicle location with said GNSS guidance subsystem;

sending guidance instructions to said automatic steering subsystem with said guidance CPU; [and]

steering the vehicle along a predetermined path by mechanically operating said steering column with said automatic steering subsystem, thereby guiding the vehicle;

providing a slip gear interfaced with said steering column;

activating said slip gear, thereby deactivating said automatic steering subsystem;

deactivating said slip gear; and

reactivating said automatic steering subsystem.

[9. The method according to claim **8**, further comprising the steps:

providing a slip gear interfaced with said steering column;

8

activating said slip gear, thereby deactivating said automatic steering subsystem;
deactivating said slip gear; and
reactivating said automatic steering subsystem.]

10. The method according to claim **8**, further comprising the steps:

providing a wheel movement detection switch integrated into said automatic steering system;

detecting manual interference of said steering wheel with said wheel movement detection switch; and

activating said automatic steering subsystem.

11. A system for controlling a vehicle including a steering column mounting a steering wheel, comprising:

a guidance central processing unit (CPU) to:

receive signals from a global navigation satellite system (GNSS);

identify a location of the vehicle based on the signals received from the GNSS;

send guidance instructions to an automatic steering subsystem to steer the vehicle along a predetermined path based on the identified location of the vehicle;

detect manual interference of the automatic steering of the vehicle by the automatic steering subsystem;

deactivate the automatic steering subsystem based on the detected manual interference; and

activate a slip gear interfaced with the steering column to deactivate the automatic steering subsystem.

12. The system of claim **11**, further comprising the guidance CPU to cause the automatic steering subsystem to steer the vehicle by controlling movement of the steering column for the steering wheel.

13. The system of claim **11**, further comprising the guidance CPU to:

receive a signal from a steering wheel movement detection switch to detect the manual interference of the automatic steering of the vehicle; and

deactivate the automatic steering subsystem in response to the signal from the steering wheel movement detection switch.

* * * * *