



US00RE48230E

(19) **United States**
(12) **Reissued Patent**
Lloyd et al.

(10) **Patent Number:** **US RE48,230 E**
(45) **Date of Reissued Patent:** **Sep. 29, 2020**

(54) **HIGH SPEED BYPASS CABLE ASSEMBLY**

(71) Applicant: **Molex, LLC**, Lisle, IL (US)

(72) Inventors: **Brian Keith Lloyd**, Maumelle, AR (US); **Christopher David Hirschy**, Conway, AR (US); **Munawar Ahmad**, Maumelle, AR (US); **Eran J. Jones**, Conway, AR (US); **Stephen W. Hamblin**, Little Rock, AR (US); **Darian Ross Schulz**, Little Rock, AR (US); **Todd David Ward**, Maumelle, AR (US); **Gregory B. Walz**, Maumelle, AR (US); **Ebrahim Abunasrah**, Little Rock, AR (US); **Rehan Khan**, Little Rock, AR (US)

(73) Assignee: **Molex, LLC**, Lisle, IL (US)

(21) Appl. No.: **15/715,939**

(22) Filed: **Sep. 26, 2017**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,011,177**
Issued: **Apr. 21, 2015**
Appl. No.: **13/987,296**
Filed: **Feb. 14, 2011**

U.S. Applications:

(63) Continuation of application No. 15/271,903, filed on Sep. 21, 2016, now Pat. No. Re. 47,342, which is an (Continued)

(51) **Int. Cl.**
H01R 13/58 (2006.01)
H01R 13/6461 (2011.01)
(Continued)

(52) **U.S. Cl.**
CPC **H01R 13/6461** (2013.01); **H01B 11/00** (2013.01); **H01R 13/6471** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC H01R 13/6477; H01R 13/6585; H01R 13/665; H01R 24/60; H01L 24/60; G01F 1/184

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,007,131 A 10/1961 Dahlgren et al.
3,594,613 A 7/1971 Prietula

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1316802 A 10/2001
CN 2624465 Y 7/2004

(Continued)

OTHER PUBLICATIONS

Amphenol TCS, "Amphenol TCS expands the XCede Platform with 85 Ohm Connectors and High-Speed Cable Solutions," Press Release, Published Feb. 25, 2009, http://www.amphenol.com/about/news_archive/2009/58.

(Continued)


Primary Examiner — Christopher E. Lee

(74) *Attorney, Agent, or Firm* — Molex, LLC

(57) **ABSTRACT**

A cable bypass assembly is disclosed for use in providing a high speed transmission line for connecting a [board mounted] connector of an electronic device to a chip on the device board. The bypass cable assembly has a structure that permits it, where it is terminated to the [board mounted] connector and the chip member, or closely proximate thereto, to replicate closely the geometry of the cable. The connector terminals are arranged in alignment with the cable signal conductors and shield extensions are provided so that shielding can be provided up to and over the termination between the cable signal conductors and the board connector terminal tails. Likewise, a similar termination structure is provided at the opposite end of the cable where a pair of

(Continued)



terminals are supported by a second connector body and enclosed in a shield collar. The shield collar has an extension that engages the second end of the cable], *to allow signals to be transmitted at greater than 10 GHz with substantially lower loss than a traditional FR4 circuit board.*

17 Claims, 23 Drawing Sheets

Related U.S. Application Data

application for the reissue of Pat. No. 9,011,177, which is a continuation-in-part of application No. PCT/US2010/022738, filed on Feb. 1, 2010.

(60) Provisional application No. 61/148,685, filed on Jan. 30, 2009.

(51) Int. Cl.

H01B 11/00 (2006.01)
H01R 13/6471 (2011.01)
H01R 13/6592 (2011.01)
H01R 13/6593 (2011.01)
H05K 1/02 (2006.01)
H05K 3/22 (2006.01)

(52) U.S. Cl.

CPC *H01R 13/6592* (2013.01); *H01R 13/6593* (2013.01); *H05K 1/0243* (2013.01); *H05K 3/222* (2013.01); *H05K 2201/10189* (2013.01); *H05K 2201/10356* (2013.01); *H05K 2201/10446* (2013.01); *H05K 2201/10674* (2013.01)

(58) Field of Classification Search

USPC 439/79, 108, 607.01; 361/785; 257/697
 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,963,319 A 6/1976 Schumacher et al.
 4,025,141 A 5/1977 Thelissen
 4,072,387 A 2/1978 Sochor
 4,083,615 A 4/1978 Volinskii
 4,157,612 A 6/1979 Rainal
 4,290,664 A 9/1981 Davis et al.
 4,307,926 A 12/1981 Smith
 4,346,355 A 8/1982 Tsukii
 4,417,779 A 11/1983 Wilson
 4,508,403 A 4/1985 Weltman
 4,611,186 A 9/1986 Ziegner
 4,615,578 A * 10/1986 Stadler et al. 439/607.47
 4,639,054 A 1/1987 Kersbergen
 4,656,441 A 4/1987 Takahashi et al.
 4,657,329 A 4/1987 Dechelette
 4,679,321 A 7/1987 Plonski
 4,697,862 A 10/1987 Hasircoglu
 4,724,409 A 2/1988 Lehman
 4,889,500 A * 12/1989 Lazar et al. 439/579
 4,924,179 A 5/1990 Sherman
 4,948,379 A 8/1990 Evans
 4,984,992 A 1/1991 Beamenderfer et al.
 4,991,001 A 2/1991 Takubo et al.
 5,112,251 A 5/1992 Cesar
 5,197,893 A 3/1993 Morlion et al.
 5,332,979 A 7/1994 Roskewitsch
 5,387,130 A 2/1995 Fedder et al.
 5,402,088 A 3/1995 Pierro et al.
 5,435,757 A 7/1995 Fedder et al.
 5,441,424 A 8/1995 Morlion et al.
 5,487,673 A 1/1996 Hurtarte

5,509,827 A 4/1996 Huppenthal et al.
 5,554,038 A 9/1996 Morlion et al.
 5,598,627 A 2/1997 Saka et al.
 5,632,634 A 5/1997 Soes
 5,691,506 A 11/1997 Miyazaki et al.
 5,781,759 A 7/1998 Kashiwabara
 5,876,239 A 3/1999 Morin et al.
 6,004,139 A 12/1999 Dramstad
 6,053,770 A 4/2000 Blom
 6,083,046 A 7/2000 Wu et al.
 6,095,872 A 8/2000 Lang et al.
 6,144,559 A 11/2000 Johnson et al.
 6,156,981 A 12/2000 Ward et al.
 6,203,376 B1 3/2001 Magajne et al.
 6,255,741 B1 7/2001 Yoshihara
 6,266,712 B1 7/2001 Henrichs
 6,273,753 B1 8/2001 Ko
 6,273,758 B1 * 8/2001 Lloyd et al. 439/607.01
 6,366,471 B1 4/2002 Edwards et al.
 6,368,120 B1 4/2002 Scherer
 6,371,788 B1 4/2002 Bowling et al.
 6,452,789 B1 9/2002 Pallotti et al.
 6,454,605 B1 9/2002 Bassler et al.
 6,489,563 B1 12/2002 Zhao et al.
 6,535,367 B1 3/2003 Carpenter
 6,574,115 B2 6/2003 Asano et al.
 6,575,772 B1 6/2003 Soubh et al.
 6,592,401 B1 7/2003 Gardner et al.
 6,652,296 B2 11/2003 Kuroda et al.
 6,652,318 B1 11/2003 Winings et al.
 6,685,501 B1 2/2004 Wu et al.
 6,692,262 B1 2/2004 Loveless
 6,705,893 B1 3/2004 Ko
 6,780,069 B2 8/2004 Scherer
 6,797,891 B1 9/2004 Blair et al.
 6,812,560 B2 * 11/2004 Recktenwald H01L 24/90
 257/697
 6,824,426 B1 11/2004 Spink, Jr.
 6,843,657 B2 1/2005 Driscoll et al.
 6,863,549 B2 * 3/2005 Bruner H01R 13/6477
 439/108
 6,882,241 B2 4/2005 Abo et al.
 6,903,934 B2 6/2005 Lo
 6,910,914 B1 6/2005 Spink, Jr.
 6,916,183 B2 7/2005 Alger et al.
 6,955,565 B2 * 10/2005 Lloyd et al. 439/607.01
 6,969,270 B2 11/2005 Renfro
 6,969,280 B2 11/2005 Chien
 6,971,887 B1 12/2005 Trobough
 7,004,765 B2 2/2006 Hsu
 7,004,767 B2 * 2/2006 Kim H01R 13/6585
 439/607.01
 7,004,793 B2 2/2006 Scherer
 7,044,772 B2 5/2006 McCreery
 7,052,292 B2 5/2006 Hsu et al.
 7,056,128 B2 6/2006 Driscoll et al.
 7,066,756 B2 6/2006 Lange et al.
 7,070,446 B2 7/2006 Henry
 7,086,888 B2 * 8/2006 Wu H01R 24/60
 439/108
 7,108,522 B2 9/2006 Verelst et al.
 7,148,428 B2 12/2006 Meier et al.
 7,168,961 B2 1/2007 Hsieh
 7,175,446 B2 2/2007 Bright
 7,192,300 B2 3/2007 Hashiguchi et al.
 7,214,097 B1 5/2007 Hsu et al.
 7,223,915 B2 * 5/2007 Hackman 174/36
 7,234,944 B2 6/2007 Nordin
 7,244,137 B2 7/2007 Renfro et al.
 7,280,372 B2 10/2007 Grundy et al.
 7,307,293 B2 12/2007 Fjelstad et al.
 7,331,816 B2 2/2008 Krohn et al.
 7,384,275 B2 6/2008 Ngo
 7,394,665 B2 7/2008 Hamasaki et al.
 7,402,048 B2 7/2008 Meier et al.
 7,431,608 B2 10/2008 Sakaguchi et al.
 7,445,471 B1 11/2008 Scherer et al.
 7,462,924 B2 12/2008 Shuey
 7,489,514 B2 2/2009 Hamasaki

(56)

References Cited

U.S. PATENT DOCUMENTS

7,534,142 B2	5/2009	Avery	8,992,258 B2	3/2015	Raschilla
7,540,773 B2	6/2009	Ko	9,011,177 B2	4/2015	Lloyd
7,549,897 B2	6/2009	Fedder et al.	9,028,281 B2	5/2015	Kirk
7,621,779 B2	11/2009	Laurx et al.	9,035,183 B2	5/2015	Kodama et al.
7,637,767 B2	12/2009	Davis	9,040,824 B2	5/2015	Guetig et al.
7,654,831 B1 *	2/2010	Wu 439/76.1	9,054,432 B2	6/2015	Yang
7,658,654 B2	2/2010	Ohyama	9,071,001 B2	6/2015	Scherer et al.
7,690,930 B2	4/2010	Chen et al.	9,118,151 B2	8/2015	Tran et al.
7,719,843 B2	5/2010	Dunham	9,119,292 B2	8/2015	Gundel
7,744,385 B2	6/2010	Scherer	9,136,652 B2	9/2015	Ngo
7,744,403 B2	6/2010	Barr	9,142,921 B2	9/2015	Wanha et al.
7,744,414 B2	6/2010	Scherer et al.	9,155,214 B2	10/2015	Ritter
7,748,988 B2	7/2010	Hori	9,160,123 B1	10/2015	Pao
7,771,207 B2	8/2010	Hamner et al.	9,160,151 B2	10/2015	Vinther
7,789,529 B2	9/2010	Roberts	9,161,463 B2	10/2015	Takamura
7,819,675 B2	10/2010	Ko et al.	9,166,320 B1	10/2015	Herring
7,824,197 B1	11/2010	Westman	9,196,983 B2	11/2015	Saur et al.
7,857,629 B2	12/2010	Chin	9,203,171 B2	12/2015	Yu
7,857,630 B2	12/2010	Hermant et al.	9,209,539 B2	12/2015	Herring
7,862,344 B2	1/2011	Morgan et al.	9,214,756 B2	12/2015	Nishio
7,892,019 B2	2/2011	Rao	9,214,768 B2	12/2015	Pao
7,906,730 B2	3/2011	Atkinson et al.	9,232,676 B2	1/2016	Sechrist et al.
7,931,502 B2	4/2011	Iida	9,246,251 B2	1/2016	Regnier
7,985,097 B2	7/2011	Gulla	9,277,649 B2	3/2016	Ellison
7,997,933 B2	8/2011	Feldman	9,312,618 B2	4/2016	Regnier
8,002,583 B2	8/2011	van Woensel	9,331,432 B1	5/2016	Phillips
8,018,733 B2	9/2011	Jia	9,350,108 B2	5/2016	Long
8,036,500 B2	10/2011	McColloch	9,356,366 B2	5/2016	Moore
8,157,573 B2	4/2012	Tanaka	9,385,455 B2	7/2016	Regnier
8,162,675 B2	4/2012	Regnier	9,391,407 B1	7/2016	Bucher
8,187,038 B2	5/2012	Kamiya	9,401,563 B2	7/2016	Simpson
8,192,222 B2	6/2012	Kameyama	9,413,090 B2	8/2016	Nagamine
8,226,441 B2	7/2012	Regnier	9,413,112 B2	8/2016	Helster
8,308,491 B2	11/2012	Nichols et al.	9,431,773 B2	8/2016	Chen
8,337,243 B2	12/2012	Elkhatib et al.	9,437,981 B2	9/2016	Wu
8,338,713 B2	12/2012	Fjelstad et al.	9,455,538 B2	9/2016	Nishio
8,398,433 B1	3/2013	Yang	9,484,671 B2	11/2016	Zhu
8,419,472 B1	4/2013	Swanger et al.	9,484,673 B1	11/2016	Yang
8,435,074 B1	5/2013	Grant	9,490,587 B1	11/2016	Phillips
8,439,704 B2	5/2013	Reed	9,496,655 B1	11/2016	Huang
8,449,312 B2	5/2013	Lan	9,515,429 B2	12/2016	DeGeest
8,449,330 B1	5/2013	Schroll	9,525,245 B2	12/2016	Regnier
8,465,302 B2	6/2013	Regnier	9,543,688 B2	1/2017	Pao
8,480,413 B2	7/2013	Minich	9,553,381 B2	1/2017	Regnier
8,517,765 B2	8/2013	Schroll	9,559,465 B2	1/2017	Phillips
8,535,069 B2	9/2013	Zhang	9,565,780 B2	2/2017	Nishio
8,540,525 B2	9/2013	Regnier	9,608,388 B2	3/2017	Kondo
8,575,529 B2	9/2013	Asahi	9,608,590 B2	3/2017	Hamner
8,553,102 B2	10/2013	Yamada	9,627,818 B1	4/2017	Chen
8,575,491 B2	11/2013	Gundel et al.	9,660,364 B2	5/2017	Wig et al.
8,588,561 B2	11/2013	Zbinden	9,666,998 B1	5/2017	deBoer
8,597,055 B2	12/2013	Regnier	9,673,570 B2	6/2017	Briant
8,651,890 B2	2/2014	Chiarelli	9,812,799 B2	11/2017	Wittig
8,672,707 B2	3/2014	Nichols et al.	9,985,367 B2	5/2018	Wanha et al.
8,690,604 B2	4/2014	Davis	2001/0016438 A1	8/2001	Reed
8,715,003 B2	5/2014	Buck et al.	2002/0111067 A1	8/2002	Sakurai et al.
8,740,644 B2	6/2014	Long	2002/0157865 A1	10/2002	Noda
8,747,158 B2	6/2014	Szczesny	2002/0180554 A1	12/2002	Clark et al.
8,753,145 B2	6/2014	Lang	2003/0064616 A1	4/2003	Reed et al.
8,758,051 B2	6/2014	Nonen et al.	2003/0073331 A1	4/2003	Peloza et al.
8,764,483 B2	7/2014	Ellison	2003/0222282 A1	12/2003	Fjelstad et al.
8,784,122 B2	7/2014	Soubh	2004/0094328 A1	5/2004	Fjelstad et al.
8,787,711 B2	7/2014	Zbinden	2004/0121633 A1	6/2004	David et al.
8,794,991 B2	8/2014	Ngo	2004/0155328 A1	8/2004	Kline
8,804,342 B2	8/2014	Behziz et al.	2004/0155734 A1	8/2004	Kosemura et al.
8,814,595 B2	8/2014	Cohen et al.	2004/0229510 A1 *	11/2004	Lloyd et al. 439/610
8,834,190 B2	9/2014	Ngo	2004/0264894 A1	12/2004	Cooke
8,864,521 B2	10/2014	Atkinson et al.	2005/0006126 A1	1/2005	Aisenbrey
8,888,533 B2	11/2014	Westman et al.	2005/0051810 A1	3/2005	Funakura
8,905,767 B2	12/2014	Putt, Jr. et al.	2005/0093127 A1	5/2005	Fjelstad et al.
8,911,255 B2	12/2014	Scherer et al.	2005/0130490 A1	6/2005	Rose
8,926,342 B2	1/2015	Vinther	2005/0142944 A1	6/2005	Ling et al.
8,926,377 B2	1/2015	Kirk	2005/0239339 A1	10/2005	Pepe
8,992,236 B2	3/2015	Wittig	2006/0001163 A1	1/2006	Kolbehdari et al.
8,992,237 B2	3/2015	Regnier	2006/0035523 A1	2/2006	Kuroda et al.
			2006/0038287 A1	2/2006	Hamasaki
			2006/0067066 A1 *	3/2006	Meier G06F 1/184 361/785
			2006/0079102 A1	4/2006	DeLessert

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0079119 A1 4/2006 Wu
 2006/0091507 A1 5/2006 Fjelstad et al.
 2006/0114016 A1 6/2006 Suzuki
 2006/0160399 A1 7/2006 Dawiedczyk
 2006/0189212 A1 8/2006 Avery
 2006/0194475 A1 8/2006 Miyazaki
 2006/0216969 A1 9/2006 Bright
 2006/0228922 A1 10/2006 Morriss
 2006/0234556 A1 10/2006 Wu
 2006/0238991 A1 10/2006 Drako
 2006/0282724 A1 12/2006 Roulo
 2006/0292898 A1 12/2006 Meredith
 2007/0032104 A1 2/2007 Yamada
 2007/0141871 A1 6/2007 Scherer
 2007/0243741 A1 10/2007 Yang
 2008/0131997 A1 6/2008 Kim et al.
 2008/0171476 A1 7/2008 Liu
 2008/0242127 A1* 10/2008 Murr H01R 13/665
 439/79
 2008/0297988 A1 12/2008 Chau
 2008/0305689 A1 12/2008 Zhang et al.
 2009/0023330 A1 1/2009 Stoner et al.
 2009/0166082 A1 7/2009 Liu et al.
 2009/0215309 A1 8/2009 Mongold et al.
 2010/0068944 A1 3/2010 Scherer
 2010/0112850 A1 5/2010 Rao
 2010/0159829 A1 6/2010 McCormack
 2010/0177489 A1 7/2010 Yagisawa
 2010/0203768 A1 8/2010 Kondo
 2011/0074213 A1 3/2011 Schaffer
 2011/0080719 A1 4/2011 Jia
 2011/0136387 A1 6/2011 Matsuura
 2011/0177699 A1 7/2011 Crofoot et al.
 2011/0212633 A1 9/2011 Regnier
 2011/0230104 A1 9/2011 Lang
 2011/0263156 A1 10/2011 Ko
 2011/0300757 A1 12/2011 Regnier
 2011/0304966 A1 12/2011 Schrempp
 2012/0003848 A1 1/2012 Casher et al.
 2012/0034820 A1 2/2012 Lang
 2012/0225585 A1 9/2012 Lee
 2012/0246373 A1 9/2012 Chang
 2013/0005178 A1 1/2013 Straka et al.
 2013/0012038 A1 1/2013 Kirk
 2013/0017715 A1 1/2013 Van Laarhoven
 2013/0040482 A1 2/2013 Ngo
 2013/0092429 A1 4/2013 Ellison
 2013/0148321 A1 6/2013 Liang
 2013/0340251 A1 12/2013 Regnier
 2014/0041937 A1* 2/2014 Lloyd et al. 174/74 R
 2014/0073173 A1 3/2014 Yang
 2014/0073174 A1 3/2014 Yang
 2014/0073181 A1 3/2014 Yang
 2014/0111293 A1 4/2014 Madeberg et al.
 2014/0217571 A1 8/2014 Ganesan et al.
 2014/0242844 A1 8/2014 Wanha
 2014/0273551 A1 9/2014 Resendez
 2014/0273594 A1 9/2014 Jones et al.
 2014/0335736 A1 11/2014 Regnier
 2015/0079845 A1 3/2015 Wanha
 2015/0090491 A1 4/2015 Dunwoody
 2015/0180578 A1 6/2015 Leigh et al.
 2015/0207247 A1 7/2015 Regnier et al.
 2016/0013596 A1 1/2016 Regnier
 2016/0064119 A1 3/2016 Grant
 2016/0104956 A1 4/2016 Santos

2016/0181713 A1 6/2016 Pelozza
 2016/0190720 A1 6/2016 Lindkamp
 2016/0190747 A1 6/2016 Regnier
 2016/0197423 A1 7/2016 Regnier
 2016/0218455 A1 7/2016 Sayre
 2016/0233598 A1 8/2016 Wittig
 2016/0233615 A1 8/2016 Scholeno
 2016/0336692 A1 11/2016 Champion
 2016/0380383 A1 12/2016 Lord
 2017/0033482 A1 2/2017 Liao
 2017/0033509 A1 2/2017 Liao
 2017/0077621 A1 3/2017 Liao
 2017/0098901 A1 4/2017 Regnier
 2017/0110222 A1 4/2017 Liptak et al.
 2017/0162960 A1 6/2017 Wanha
 2017/0302036 A1 10/2017 Regnier
 2017/0365942 A1 10/2017 Regnier
 2018/0034175 A1 2/2018 Lloyd

FOREIGN PATENT DOCUMENTS

CN 1647323 A 7/2005
 CN 102365907 A 2/2012
 DE 3447556 A1 7/1986
 JP 02-079571 U 6/1990
 JP 04-14372 U1 2/1992
 JP 05-059761 U 8/1993
 JP 2008-041285 A 2/2008
 JP 2008-059857 A 3/2008
 JP 2009-043590 A 2/2009
 JP 2010-017388 A 1/2010
 JP 2010-123274 A 6/2010
 JP 2013-016394 A 1/2013
 TW M359141 U 6/2009
 TW M408835 U 8/2011
 TW 201225455 A 6/2012
 WO WO 2008-072322 A1 6/2008
 WO WO 2012-078434 A2 6/2012
 WO WO 2013-006592 A2 1/2013
 WO 2016/112379 A1 7/2016

OTHER PUBLICATIONS

Amphenol Aerospace, "Size 8 High Speed Quadrax and Differential Twinax Contacts for Use in MIL-DTL-38999 Special Subminiature Cylindrical and ARINC 600 Rectangular Connectors", published May 2008. Retrieved from www.peigenesis.com/images/content/news/amphenol_quadrax.pdf.
 Hitachi Cable America Inc., "Direct Attach Cables: OMNIBIT supports 25 Gbit/s interconnections". Retrieved Aug. 10, 2017 from www.hca.hitachi-cable.com/products/hca/catalog/pdfs/direct-attach-cable-assemblies.pdf.
 U.S. Appl. No. 61/714,871, filed Oct. 17, 2012, Wig et al.
 Agilent, "Designing Scalable 10G Backplane Interconnect Systems Utilizing Advanced Verification Methodologies," White Paper, Published May 5, 2012, USA.
 International Search Report and Written Opinion received for PCT application No. PCT/US2016/012848, dated Apr. 25, 2016, 11 pages.
 International Preliminary Report on Patentability received for PCT Application No. PCT/US2016/012848, dated Jul. 20, 2017, 10 pages.
 "File:Wrt54gl-layout.jpg-Embedded Xinu", Internet Citation, Sep. 8, 2006. Retrieved from the Internet: URL:<http://xinu.ms.cs.mu.edu/File:Wrt54gl-layout.jpg> [retrieved on Sep. 23, 2014].

* cited by examiner




FIG. 1




FIG. 2





FIG. 3






FIG. 5




FIG. 6





FIG. 7






Fig 9 (Amended)




FIG. 10




FIG. 11




FIG. 11A




Fig. 12 (Amended)




Fig. 12A (Amended)




FIG. 12B




FIG. 13




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 14




FIG. 14A




FIG. 14B




FIG. 15




FIG. 16

HIGH SPEED BYPASS CABLE ASSEMBLY

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

REFERENCE TO RELATED APPLICATIONS

[The Present Disclosure] *This application is a reissue continuation of U.S. application Ser. No. 15/271,903, which is a reissue of U.S. Pat. No. 9,011,177, which issued on Apr. 21, 2015 from U.S. application Ser. No. 13/987,296, which is a continuation-in-part of International Application No. PCT/US2010/022738, filed Feb. 1, 2010, entitled "High Speed Interconnect Cable Assembly," filed 01 Feb. 2010 with the U.S. Patent And Trademark Office (USPTO) as Receiving Office for the Patent Cooperation Treaty. The '738 Application claims priority of prior-filed U.S. Provisional Application No. 61/145,685, entitled "High Speed Interconnect Cable Assembly," filed 30 Jan. 2009 also with the USPTO. The contents of each of the above Applications are fully incorporated in their entireties herein.*

BACKGROUND OF THE PRESENT DISCLOSURE

The Present Disclosure relates generally to cable interconnection systems, and more particularly, to bypass cable interconnection systems for transmitting high speed signals at low losses.

Conventional cable interconnection systems are found in electronic devices such as routers and servers and the like, and are used to form a signal transmission line that extends between a primary chip member mounted on a printed circuit board of the device, such as an ASIC, and a connector mounted to the circuit board. The transmission line typically takes the form of a plurality of conductive traces that are etched, or otherwise formed on or as part of the printed circuit board. These traces extend between the chip member and a connector that provides a connection between one or more external plug connectors and the chip member. Circuit boards are usually formed from a material known as FR-4, which is inexpensive. However, FR-4 is known to promote losses in high speed signal transmission lines, and these losses make it undesirable to utilize FR-4 material for high speed applications (10 GHz and above). Custom materials for circuit boards are available that reduce such losses but the price of these materials severely increase the cost of the circuit board and, consequently, the electronic devices in which they are used. Additionally, when traces are used to form the signal transmission line, the overall length of the transmission line typically may well exceed 10 inches in length. These long lengths require that the signals traveling through the transmission line be amplified and repeated, thereby increasing the cost of the circuit board, and complicating the design inasmuch as additional board space is needed to accommodate these amplifiers and repeaters. In addition, the routing of the traces of such a transmission line in the FR-4 may require multiple turns and the transitions which occur at terminations affect the integrity of the signals transmitted thereby. It becomes difficult to route transmission line traces in a manner so as to achieve consistent impedance and a low signal loss therethrough.

The Present Disclosure is therefore directed to a high speed, bypass cable assembly that defines a transmission line for transmitting high speed signals, 10 GHz and greater that removes the transmission line from on the circuit board and which has low loss characteristics.

SUMMARY OF THE PRESENT DISCLOSURE

Accordingly, there is provided an improved high speed bypass cable assembly that defines a signal transmission line useful for high speed applications at 10 GHz or above and with low loss characteristics.

In accordance with an embodiment as described in the disclosure, an electrical connector assembly is disclosed. The electrical connector assembly comprises a printed circuit board, a chip member, a termination member, a first connector member, a bypass cable member and a second connector member. The chip member and the termination member are mounted on the printed circuit board, with the termination member mounted toward the end of the printed circuit board. The first connector member is in electrical communication with the chip member at a first end, and the bypass cable member electrically connects the first connector member, where it is coupled at a second end thereof, and the termination member, at a first end. The second connector member, disposed at a second end of the termination member, is in electrical communication with the termination member. Generally, the electrical connector is capable of the transmission of high speed signals. As the chip member is located a long length from the board connector, the bypass cable provides a transmission line therebetween that has a consistent geometry and structure that resists signal loss and maintains the system impedance at a consistent level without discontinuities.

In accordance with a second embodiment of the disclosure, the cable bypass assembly provides a transmission line that is separate from the circuit board, and may include one or more associated signal wire pairs, such as is found in "twin-ax" cable. The wires of the bypass cable are configured at their opposite ends in two fashions. At a first end of the bypass cable, the wires are configured for a direct termination to a board mounted connector, and are arranged in a manner such that the conductors of the signal wires extend in alignment with terminal termination ends, or feet, of the board mounted connector. The shielding of the signal wires are rolled back upon the insulative coating of the wires and exterior shield extensions are preferably provided to ensure that the signal wire conductor leads are effectively shielded through the connection. In this manner of connection, the terminal tails need not be attached to the circuit board, either as surface mount or through hole tails, thereby significantly reducing losses and the impedance discontinuity that occurs in the tail to board mounting transition.

At the second end of the bypass cable the signal wires are terminated in a fashion so that they can either be connected directly to the chip member or to the board in close proximity to the chip member. In this regard, and as disclosed in this second embodiment, the signal wire conductors are terminated to associated tail portions that are aligned with the conductors, similar to the termination which occurs at the first end. These tails are maintained in a desired spacing and are further completely shielded by a surrounding conductive enclosure to provide full EMI shielding and reduction of cross talk. The termination of the ends of the bypass cable assembly are done in a manner such that to the extent possible, the geometry of the conductors in the bypass cable

3

is maintained through the termination of the cable to the board connector and/or the chip.

These and other objects, features and advantages of the Present Disclosure will be clearly understood through a consideration of the following detailed description.

BRIEF DESCRIPTION OF THE FIGURES

The organization and manner of the structure and operation of the Present Disclosure, together with further objects and advantages thereof, may best be understood by reference to the following Detailed Description, taken in connection with the accompanying Figures, wherein like reference numerals identify like elements, and in which:

FIG. 1 illustrates a perspective view of one embodiment of a high speed interconnect cable assembly, developed in accordance with the Present Disclosure;

FIG. 2 illustrates a perspective view of another embodiment of a high speed interconnect cable assembly, developed in accordance with the Present Disclosure;

FIG. 3 illustrates a perspective view of another embodiment of a high speed interconnect cable assembly, developed in accordance with the Present Disclosure;

FIG. 4 illustrates a perspective and inset view of the via transfer connector of the interconnect cable assembly of FIG. 3;

FIG. 5 illustrates a perspective and inset view of the first connector member of the interconnect cable assembly of FIG. 3;

FIG. 6 is a perspective view of a second embodiment of a cable bypass assembly constructed in accordance with the Present Disclosure;

FIG. 7 is a top plan view of the cable bypass assembly of FIG. 6;

FIG. 8 is an exploded view of the assembly of FIG. 6, illustrating in greater detail the board connector to which the cable bypass assembly is terminated;

FIG. 9 is a perspective view of the board mounted connector of FIG. 8, with the first ends of the bypass assembly attached thereto;

FIG. 10 is a partially exploded view of FIG. 9;

FIG. 11 is a top plan view of FIG. 9, with the EMI shield removed for clarity;

FIG. 11A is a side elevational view of FIG. 11;

FIG. 12 is perspective view of four pairs of signal wires terminated to the board connector terminal assembly and with one set of the shielding extensions removed for clarity;

FIG. 12A is the same view as FIG. 12, but taken from the rear thereof;

FIG. 12B is a end view of two pairs of signal wires with an associated shielding extension in place, illustrating the relative alignments of the signal conductors with each other and to the shielding of the cables;

FIG. 13 is a perspective view of one manner of terminating the ends of the cables of the cable bypass assembly which is opposite that of the termination to the board mounted connector;

FIG. 13A is the same view as FIG. 13, but with one of the exterior shielding components removed for clarity;

FIG. 13B is the same view as FIG. 13A but with the lower shielding component removed and the terminal support in place on the terminals attached to the second end of the cable;

FIG. 13C is the same view as FIG. 13B but with the terminal support removed for clarity;

FIG. 13D is the same view as FIG. 13C, but taken from the other end thereof;

4

FIG. 13E is a sectional view of FIG. 13;

FIG. 14 is an embodiment of a termination structure for direct connection to a chip member;

FIG. 14A is an exploded view of FIG. 14;

FIG. 14B is an enlarged detail view of FIG. 14A.

FIG. 15 is a partially exploded view of an extent of flexible circuitry which may be used as a signal transmission line in cable bypass assemblies of the disclosure; and,

FIG. 16 is a graph comparing the losses between 12-inch lengths of signal transmission lines incorporated on a circuit board made from FR-4 material and a cable bypass assembly constructed in accordance with the principles of the disclosure.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

While the Present Disclosure may be susceptible to embodiment in different forms, there is shown in the Figures, and will be described herein in detail, specific embodiments, with the understanding that the disclosure is to be considered an exemplification of the principles of the Present Disclosure, and is not intended to limit the Present Disclosure to that as illustrated.

In the embodiments illustrated in the Figures, representations of directions such as up, down, left, right, front and rear, used for explaining the structure and movement of the various elements of the Present Application, are not absolute, but relative. These representations are appropriate when the elements are in the position shown in the Figures. If the description of the position of the elements changes, however, these representations are to be changed accordingly.

While the Present Disclosure may be susceptible to embodiment in different forms, there is shown in the Figures, and will be described herein in detail, specific embodiments, with the understanding that the disclosure is to be considered an exemplification of the principles of the Present Disclosure, and is not intended to limit the Present Disclosure to that as illustrated.

FIGS. 1-5 provide various perspective views of some basic components of a high speed interconnect cable assembly, developed in accordance with the teachings and tenets of the Present Disclosure.

Referring more specifically to FIG. 1, high speed interconnect cable assembly 10 generally comprises chip member 12 mounted on printed circuit board member 14, first connector member 16 interfacing between chip member 12 and bypass cable member 18, and termination member 20 interfacing between bypass cable member 18 and second connector member 22 disposed at the edge of printed circuit board member 14.

Preferably, chip member 12 may comprise a PHY Chip, or any other surface-mounted, physical layer device, known in the art, from which a high speed signal is generated, such as an ASIC and transmitted to a cable assembly. Chip member 12 is mounted to any currently-known printed circuit board, using preferably any of the various currently-known mounting means. Preferably, an FR-4 type printed circuit board is used, in an effort to take advantage of its low cost and wide usage. For purposes of the Present Disclosure, the generated high speed signal may be any type of signal, but typically a data signal, generally having a frequency of 5 GHz and above, and most preferably and is a data signal having a frequency of 10 GHz or more.

Bypass cable member 18 is connected to chip member 12 by means of first connector member 16. First connector

5

member 16 is capable of transmitting a signal greater than 10 GHz between chip member 12 and bypass cable member 18. The interface between first connector member 16 and chip member 18 may be by any known means, including, for example, a plug-receptacle connection, a friction-based connection or the like. It is preferred that the interface be removable. First connector member 16 is preferably capable of receiving the high speed signal generated by the chip member and transmitting it to the bypass cable member without need for a repeater or an amplifier, and without having to use the conductive properties of printed circuit board 14.

Bypass cable member 18 comprises a flexible circuit member, such as a cable, extending from first connector member 16 to termination member 20. Preferably, bypass cable member 18 is capable of receiving and carrying signals above 10 GHz. Preferably, bypass cable member 18 includes one or more wire pairs that transmit differential signals at high speeds. Each such wire pair may have a ground, or drain, wire associated with it. Further, the pairs may be enclosed within bypass cable member 18 and within an associated cable shield. Like first connector member 16, bypass cable member 18 is preferably capable of receiving the high speed signal generated by first connector member 18 and transmitting it to termination member 20 without need for a repeater or an amplifier, and without having to use the conductive properties of printed circuit board 14.

Termination member 20 is electrically connected to bypass cable member 18, and receives the signal from bypass cable member 18. Like all other elements in interconnection assembly 10, termination member 20 is capable of receiving signals greater than 10 GHz. Preferably, termination member 20 is located at or near the edge of printed circuit board 14. Termination member 20 may be mounted to the edge of printed circuit board 14. Alternatively, termination member 20 may be "freestanding," and not connected to any aspect of assembly 10. Termination member 20 may receive bypass cable member 18 through any methods and means as currently described in the art.

Second connector member 22 preferably provides one end of a male-female relationship with termination member 20 (with termination member 20 providing the second end). It is not imperative that second connector member 22 (or termination member 20) be specifically relegated to the male or female end, as the teachings of the Present Disclosure will nevertheless be realized.

Second connector member 22 is preferably not disposed on any other aspect of interconnection assembly 10 of the Present Disclosure, i.e., second connector member 22 is not mounted on printed circuit board 14. Second connector member 22 receives the signal from termination member 20, and transmits the signal to its next or final destination.

The discussion above focused on a single interconnection assembly. Nevertheless, a plurality of interconnection assemblies may be used on a single printed circuit board, each generally comprising the above-referenced elements. A plurality of assemblies is generally illustrated in FIG. 1. Further, in a second embodiment, which is illustrated in FIG. 2, lamination member 24 may encompass all or part of multiple bypass cable members 18 for ease in assembly, as well as to maintain order on printed circuit board 14 and reduce the cost of assembly 10. Preferably, lamination member 24 may comprise a rigid, formable polymer material that can be molded over both first connector member 16 and bypass cable member 18.

Further, in another embodiment, a plurality of interconnection assemblies, used on a single printed circuit board,

6

may be channeled to a single termination member 26 for transmission of signals beyond the printed circuit board. As illustrated in FIG. 3, bypass cable members 18 extend from chip members 12, via first connector member 16, towards first via transfer connectors 28. Each via transfer connector 28 allows the signal being carried in bypass cable members 18 to pass through holes (or vias) in the printed circuit board where they connect with termination member 26.

FIG. 4 illustrates a perspective close up of the connection of via transfer connectors 28 to termination member (not shown in FIG. 4). As illustrated, each via transfer connector 28 houses the termination of bypass cable members 18. Individual wires 30 extending from bypass cable members 18 are mounted within connector housing 32. Connector housing 32, along with individual wires 30 and a portion of bypass cable members 18, are overmolded with terminal housing 34. Terminal housing 34 is then inserted into the via hole of the printed circuit board, where it couples to termination member.

FIG. 5 illustrates a perspective close up of first connector member 16. As illustrated, each first connector 16 houses the termination of bypass cable members 18. Individual wires 36 extending from bypass cable members are overmolded with terminal housing 38. Terminal housing 38 is then coupled to chip member 12.

FIGS. 6-13E illustrate another embodiment of a bypass cable assembly 100 constructed in accordance with the principles of the Present Disclosure. As shown in FIG. 6, a circuit board 101 that is used in an electronic device (not shown) has mounted thereon a chip member 104, such as an ASIC, at one location and a shielding cage 102 mounted to the circuit board at another location, remote from the one location. The shielding cage 102 houses a receptacle connector assembly 110 that includes a receptacle connector 112 configured to receive the mating blade (typically the leading edge of a circuit card) of an opposing, mating connector (not shown) in an elongated card-receiving slot 113. The connector 112 may also include a channel 114 disposed underneath the card slot 113 to receive a polarizing member of the mating connector. The connector 112 is accessible through an opening 103 at one end of the shielding cage 102. A portion of the shielding cage 102 extends past the edge of the circuit board 101 and out of the enclosure which houses the circuit board 101. This opening 103 permits access to the connector 112 from the exterior of the device and permits the insertion of a mating connector, typically in the form of a plug connector, therein in order to connect the device to another device and permit the transfer of signals between them.

A bypass cable assembly 105 is provided to connect together, the connector 112 and the chip member 104, in order to form a signal transmission line extending therebetween for transmitting signals at high speeds of approximately 5 GHz and greater and preferably of approximately 10 GHz and greater. The cable assembly 105 includes a preselected length of cable 107 that has at a first end 107a thereof, a first termination assembly and at a second and opposite end 107b thereof, a second termination assembly. As shown best in FIG. 12B, each cable 107 may be of the "twin-ax" type, in which a pair of signal conductors 144A, 144B are positioned in spaced-apart relationship within an insulative body 142. This cable body 142 is surrounded by an outer conductive shielding layer 148 that is located underneath an exterior, insulative covering 140 and all of the cable elements may be formed as the single component illustrated. The structure of this particular type of twin-ax cable lends itself to uniformity throughout its length so that

a consistent impedance profile is attained for the length of the cable. The cable assemblies **105** of this disclosure may include as few as one or two cables, or they may include greater numbers, such as the eight cables shown in FIGS. **6**, **9** & **11**.

In order to avoid losses that normally occur in the use of signal transmission lines in the circuit board **101** using FR-4 as the board material, the cables **107** are used as the signal transmission lines. As noted above, the cables **107** are made in a manner that controls their size, thickness and the position and spacing of the signal conductors **144A**, **144B** so as to define a constant impedance profile throughout the lengths of the cables. Accordingly, twin-ax type of cable is desirable as well as flexible circuitry where positioning of the conductors and insulators may be controlled to a high degree of tolerance. Problems with impedance profiles typically occur at the termination points of cables where the geometry of the cable disrupted in order to effect a termination. One such solution to this problem is disclosed in U.S. Pat. No. 6,454,605, issued Sep. 24, 2002 and assigned to the assignee of the Present Disclosure and which is hereby incorporated by reference, in its entirety.

The cable assemblies of the Present Disclosure are terminated at their opposite ends **107A**, **107B** in a manner that seeks to reduce the modification of the cable geometry in order to reduce the magnitude of the aforementioned discontinuities and to prevent to the extent possible excessive loss, noise and crosstalk. Returning to the drawings and in particular FIGS. **12** & **12A**, it can be seen that the terminals **120** of the receptacle connector **112** have tail portions **132** that extend outwardly from the rear face of the terminal assembly supports **118A**, **118B** and contact portions **130** that extend forwardly within the card-receiving slot **113** of the body of the receptacle connector **112**. The terminal contact and tail portions **130**, **132a**, **132b**, extend in a continuous, generally horizontal extent through the connector without any vertical terminal extents that would provide an interruption of the horizontal extent. Consequently, as used herein, the term uninterrupted means a generally horizontal extent without any vertical portions. Similarly, "generally horizontal extent" also means that there are no vertical portions of the terminals that change the levels of the terminal contact and tail portions as would be found in terminals configured for surface mounting such as the low speed, power and status terminals **134** that are interposed between the high speed terminal sets. These non-high speed terminals **134** may be positioned with the use of a tail aligner block **116** or the like. In order to provide strain relief and to facilitate assembly, two cables may be held together by a block **106** applied to the cables **107** downstream of the termination areas.

In this manner, a "direct connection" is effected between the cable first end **107A** and the connector **112**, in a manner such that the signal terminal tail portions **132a**, **132b** are aligned with the exposed leads of the cable conductors **144A**, **144B** so that the exposed leads may be placed on the flat surfaces which the terminal tail portions **132a**, **132b** preferably provide. The inner shielding **148** of each cable **107** is pulled back over the exposed end of the cable and a shield extension **146** is provided for engaging these cable ends. The extension **146** is shown as a dual extension that can accommodate two cables. The shield extension **146** has what may be considered a cup portion **145** that is formed in a configuration that is generally complementary to the exterior configuration of the cable **107**, and it is provided

with contact feet **146a-c** for contacting the associated terminal tail portions **132c** of ground terminals in the receptacle connector **112**.

The dual shield extension **146** shown in the drawings has two such cup portions **145** and three contact feet. Two contact feet **146a**, **146b** are formed along the outer edges of the cup portion **145**, while the third contact foot **14c** is formed between the cup portions **145**. The contact surfaces **147** formed on the bottom of the contact feet are preferably aligned with each other along a common plane, shown as "H" in FIG. **12B**. The conductors **144A**, **144B** of the cable **107** are also preferably aligned with the contact feet, along H as illustrated best in FIG. **12B**. In this manner a "direct" connection is effected between first ends **107A** of the cables **107** and the board mounted connector **112**, thereby eliminating the need for surface mounting or through hole mounting of the connector high speed terminal tails, all of which contribute to loss, noise and crosstalk at high speeds. Terminals of the connector **112** for which high speed performance is not an issue, such as low speed signal terminals and/or power and status terminals **134**, may be terminated in conventional manners mentioned above and they are shown in FIGS. **12** & **12A** as surface mounted, and such terminals may be disposed between sets of high speed terminals as illustrated for additional separation between the high speed terminal sets. Removing the high speed signals of the receptacle connector from attachment directly to the board, reduces the cost in formation and manufacture of the circuit board **102**. Additionally, the termination style shown in the drawings mirrors the geometry of the cable and provides generally complete shielding at the direct connection.

The shield extensions **146** provide as close as can be attained complete shielding at the direct termination to the board connector and they extend forwardly to completely cover the exposed ends of the cable signal conductors **144A**, **144B** as shown in FIG. **11**. The shield extension mounting feet **146a-c** thereof are spaced apart and contact opposing tail portions of ground terminals of the first connector **112**. The shield extension feet **146a-c** and the conductors **144A**, **144B** of the cables **107** can be soldered or welded in their attachment to the connector terminals and the shield extensions **146** may be attached to the cables **107** by contact, a conductive adhesive, soldering or other suitable means. In this manner, the cable geometry is closely replicated in the termination area and more effective shielding is provided than just an ordinary ground wire to ground terminal connection. An EMI housing **109** may be utilized to provide an enclosure, in combination with the shielding cage **102** about the cable termination area.

FIGS. **13A-D** illustrate one form of termination that may be applied to the second ends of the cables **107**, which may be either connected directly to the chip member or to the circuit board **101** in close proximity thereto. As illustrated in FIGS. **13B-D**, the exposed leads of the cable conductors **144A**, **144B** are attached to signal terminals **160**, shown as a pair of signal terminals **160A**, **160B**. These terminal preferably have flat tail portions **163** and through hole contact portions **162**. The flat tail portions **163** preferably provide a flat surface to which the exposed conductors **144A**, **144B** may be contacted and attached via solder, welding or the like. The signal terminal **160** may be held in by an insulative support **156** that as shown is molded over body portions of the terminal **160**, leaving the tail and contact portions **163**, **162** exposed for termination purposes. A shield collar **152** is provided that houses the signal terminal support **156** and substantially encloses the signal terminals with a conductive shield. The shield collar **152** has

a shield extension **153B** that is similar in configuration to cable first end shield extensions **146** in that it has a cup portion **145** that contacts and receives the cable **107** and its inner shielding **148** therein. A cap member **153** is also provided and the cap member includes a block portion **154** that preferably abuts the terminal support **156** and which further preferably engages the shield collar **152** by way of tabs **156** that engage like holes **157** in the walls of the collar **152**.

FIGS. **14-14B** illustrate another embodiment of a manner or termination to a second connector. In this embodiment, the second connector **200** is one that is used to attach directly to the chip member **104**, and typically to a top surface thereof. In this regard, the second connector **200** has a housing **202** that receives a plurality of cables **204**, and the type of cables illustrated are of a different twin-ax structure, namely one in which each cable **204** contains a pair of signal wires **205** and a drain (ground) wire **206**. The signal wires **205** have signal conductors **207** running their length and surrounded by an outer insulative covering **208** and an outer covering **209** is provided that encloses a pair of the signal wires **205** and an associated drain wire **206**. A perforated base portion **210** of the housing **202** has a plurality of slots, or cavities **211**, each of which is configured to receive a single terminal **212** therein. LGA-style terminals are illustrated and each such terminal **212** includes a body portion **213** that engages the housing cavity **211**, a tail portion or mounting stub **214** that extends out of the cavity **211** and into contact with an exposed conductor **207** of the signal wires **205**, and a contact portion **215** that extends out of the opposite end of the cavity **211**. The second connector **200** also includes second cavities **216** that receive ground terminals (not shown) that are connected at their upper ends to the drain wires **206** and at their lower ends to the chip member **104**. The termination arrangement of this connector **200** also maintains, to the extent possible the geometry of the cables **204** through the connector termination, in the sense that the triangular arrangement of the three wires of each cable is maintained until the point where the drain wire is attached to the ground terminal and then the extent of the ground terminal is spaced from the ends of the signal wire terminals **212** as evidenced by the pattern of the first and second terminal cavities **211**, **216**.

FIG. **15** illustrates an alternate construction for use as a signal transmission line in accordance with the disclosure and takes the form of an extent of flat flexible circuitry **300**. The extent includes a pair of signal conductors **302** that are spaced apart from each other and which run lengthwise between opposite ends of the cable **300**. The conductors **302** are surrounded on their top and bottom surfaces and sides by insulative portions **304**, **305**. Ground shields **306** are provided to enclose the signal conductors **302**, and although shown only as above and below the signal conductors **302**, it will be understood that they may be disposed alongside of the signal conductors. With this sort of structure, the signal conductors may be exposed and aligned with terminal tails, while the ground shield extended to cover the termination areas in a manner similar to that shown above.

FIG. **16** is a graph comparing the loss between two 12-inch lengths of signal transmission lines, with one of the transmission lines comprising a pair of circuit traces formed in or on FR-4 circuit board material and the other transmission line comprising cables of the Present Disclosure. It can be seen from FIG. **16** that the use of the cable of the Present Disclosure leads to a very low loss transition that only breaks past the 5 dB mark at approximately the 20 GHz frequency. Within the range of testing error, we believe that

the cables of the Present Disclosure have low loss characteristics of no greater than between about 5 dB and about 8 dB at frequencies greater than about 19 GHz.

While a preferred embodiment of the Present Disclosure is shown and described, it is envisioned that those skilled in the art may devise various modifications without departing from the spirit and scope of the foregoing Description and the appended Claims.

What is claimed is:

[1. A cable bypass assembly, the cable bypass assembly comprising:

a first connector, the first connector being configured for mounting to a circuit board, the first connector including a connector body, the connector body supporting a plurality of conductive terminals, the conductive terminals including contact portions and tail portions, the contact portions being held within the connector body for contacting a mating blade of an opposing, mating connector, the tail portions extending out from the connector body;

an elongated cable, the elongated cable including:

a pair of signal conductors, the signal conductors being disposed within an insulative body portion of the elongated cable, the signal conductors extending, in a spaced-apart relationship, lengthwise through a body portion of the elongated cable,

a conductive shield, the conductive shield extending over an exterior of the elongated cable body portion, an insulative outer covering, the insulative outer covering extending over the conductive shield, and opposing first and second free ends, the first free end terminating directly to selected terminal tails of the first connector in a manner so that the signal conductors are in electrical communication with a pair of signal terminal tails;

a shield extension member, the shield extension member being configured to engage a first length of the conductive shield exposed at the first free end and extending therefrom over the signal conductors attached to the pair of signal terminal tails, the shield extension member including at least two spaced apart mounting feet; and

a second connector, the second connector including:

an insulative body, the insulative body supporting at least a pair of conductive signal terminals in a spaced-apart relationship, each conductive signal terminal including contact and tail portions, and

a shielding collar, the shielding collar enclosing a body portion of the second connector, the shielding collar includes an extension portion, the extension portion engaging and receiving the conductive shield exposed at the second free end.]

[2. The cable bypass assembly of claim **1**, further including a second cable, the second cable including a pair of signal conductors, the second cable signal conductors disposed lengthwise therethrough in a spaced-apart relationship, the second cable signal conductors being attached to corresponding signal terminal tails of the first connector alongside the elongated cable.]

[3. The cable bypass assembly of claim **1**, wherein the shield extension member further includes a cup portion, the cup portion being configured to receive the first free end therein.]

[4. The cable bypass assembly of claim **2**, wherein the shield extension member further includes a pair of cup portions, each cup portion receiving ends of the two cables therein.]

11

[5. The cable bypass assembly of claim 4, wherein the shield extension member includes at least three mounting feet, two of the mounting feet being disposed on opposing side edges of the shield extension member and a third of the three mounting feet being disposed between the cup portions.]

[6. The cable bypass assembly of claim 5, wherein the mounting feet and the two cable signal conductors are aligned with each other.]

[7. The cable bypass assembly of claim 1, wherein the tail and contact portions extend uninterruptedly lengthwise in a general horizontal plane through the first connector body.]

[8. The cable bypass assembly of claim 1, wherein the elongated cable includes a preselected length of flexible circuitry.]

[9. The cable bypass assembly of claim 1, wherein the shielding collar further includes at least one through-hole terminal, the through-hole terminal extending from the shielding collar and engaging a through-hole of the circuit board.]

[10. The cable bypass assembly of claim 1, wherein the shielding collar further includes a cap portion, the cap portion having a cup portion formed therein, the cup portion being configured to receive an exposed second end of the cable therein and contact a length of exposed cable shielding.]

[11. The cable bypass assembly of claim 1, wherein the second connector is configured to connect directly to a chip member.]

[12. A cable bypass assembly with low loss performance at high data frequencies, the cable bypass assembly comprising:

a first connector, the first connector being configured for mounting to a circuit board, the first connector including a connector body, the connector body supporting a plurality of conductive terminals, the conductive terminals including contact portions and tail portions, the contact portions being held within the connector body for contacting a mating blade of an opposing, mating connector, the tail portions extending out from the connector body;

an elongated cable having, the elongated cable including: first and second opposing ends,

a pair of signal conductors, the signal conductors being disposed within the elongated cable in a spaced-apart relationship and extending lengthwise through the elongated cable, and

at least one conductive shield, each conductive shield extending lengthwise through the elongated cable and substantially enclosing the signal conductors, the signal conductors, at the first end, being terminated directly to selected terminal tails of the first connector in a manner so that the signal conductors are in electrical communication with a pair of signal terminal tails along a horizontal extent thereof;

a shield, the shield extending over the signal conductors attached to the signal terminal tails, the shield including a pair of ground shields; and

a second connector, the second connector including an insulative body, the insulative body supporting at least a pair of conductive signal terminals in a spaced-apart relationship, each conductive signal terminal including contact and tail portions, the cable signal conductors at the second end thereof being terminated to the contact portions, and the cable conductive shield being terminated to selected terminals of the second connector designated for ground purposes.]

12

[13. The cable bypass assembly of claim 12, wherein the cable is an extent of flexible circuitry, the signal conductors including two signal conductors.]

[14. The cable bypass assembly of claim 13, wherein the ground shields are disposed on opposite sides of the signal conductors.]

15. A cable bypass assembly, comprising:

a cage that defines a port;

a first connector positioned in the cage, the first connector including a first body with a card-slot, the first body supporting a plurality of terminals, each terminal of the plurality of terminals including a contact portion positioned in the card slot and a tail, wherein two terminals of the plurality of terminals are adjacent each other and form a first terminal pair and another terminal of the plurality of terminals is a first ground terminal, the first ground terminal positioned adjacent the first terminal pair;

a cable with a first end and a second end that defines a length, the cable including a pair of signal conductors disposed within an insulative body portion of the cable, the signal conductors extending in a spaced-apart relationship through the insulative body portion along the length, the cable further including a conductive shield extending over an exterior of the insulative body portion and an insulative outer covering extending over the conductive shield, the first end being terminated directly to the tails of the first terminal pair so that the pair of signal conductors are in electrical communication with the first terminal pair, and wherein the conductive shield is connected to the first ground terminal; and

a second connector connected to the second end, the second connector including a second body that supports a second pair of terminals, each terminal of the second pair of terminals including a contact portion and a tail portion, the tail portion of each terminal of the second pair of terminals connected to one of the signal conductors of the pair of signal conductors and the second connector further including a ground terminal connected to the ground shield, wherein the cable bypass assembly is configured to support a signaling frequency of 10 GHz.

16. The cable bypass assembly of claim 15, wherein the plurality of terminals in the first connector are supported by two terminal assembly supports that align a portion of the terminals on both sides of the card slot so that in operation, during mating with an opposing mating connector the contacts portions on both sides of the card slot are deflected in opposing directions.

17. The cable bypass assembly of claim 15, wherein the second connector is configured to be press-fit into a circuit board adjacent a chip member.

18. A cable bypass assembly, comprising:

a cage that defines a port with a front opening;

a first connector positioned in the cage and including a first body with a card-slot, the first body supporting a plurality of terminals, each terminal of the plurality of terminals including a contact portion positioned in the card slot and a tail, wherein two terminals of the plurality of terminals are adjacent each other and form a first terminal pair;

a cable with a first end and a second end that defines a length, the cable including a pair of signal conductors disposed within an insulative body portion of the cable, the signal conductors extending in a spaced-apart relationship through the insulative body portion along

13

the length, the first end being terminated directly to the tails of the first terminal pair so that the pair of signal conductors are in electrical communication with the tails of the first terminal pair; and

a second connector connected to the second end, the second connector including a second body that supports a second plurality of terminals that form a second terminal pair, each terminal of the second terminals pair including a contact portion and a tail portion, the tail portion of each terminal of the second terminal pair connected to one of the signal conductors, wherein the cable bypass assembly is configured to support a signaling frequency of 10 GHz.

19. The cable bypass assembly of claim 18, wherein the plurality of terminals in the first connector are supported by two terminal assembly supports that align a portion of the terminals on both sides of the card slot so that in operation, during mating with an opposing mating connector the contacts portions on both sides of the card slot are deflected in opposing directions.

20. The cable bypass assembly of claim 18, wherein the card slot is recessed a substantial distance from the front opening.

21. The cable bypass assembly of claim 18, wherein the second connector is configured to be press-fit into a circuit board adjacent a chip member.

22. The cable bypass assembly of claim 18, wherein the second connector is configured to be connected directly to a chip member.

23. The cable bypass assembly of claim 18, wherein the cable includes a drain wire and the first and second connectors each include a ground terminal, the ground terminals electrically connected together by the drain wire.

*24. A cable bypass assembly, comprising:
a cage that defines a port with a front opening and a rear side;*

a first connector positioned in the cage, the first connector defining a card-slot, the first connector supporting a first plurality of terminals, each terminal of the first plurality of terminals including a contact portion positioned in the card slot and a tail, the first plurality of terminals including terminals arranged on two opposing sides of the card slot so that, in operation, insertion of a mating blade causes the terminals on two opposing sides to deflect in opposite directions, wherein two terminals of the first plurality of terminals are adjacent each other and form a first terminal pair;

a cable with a first end and a second end that defines a length, the cable extending from the rear side and including a pair of signal conductors disposed within an insulative body portion of the cable, the pair of signal conductors surrounded by a conductive shield, the signal conductors extending in a spaced-apart relationship through the insulative body portion along the length, the first end being terminated directly to the tails of the first terminal pair so that the pair of signal conductors are in electrical communication with the tails of the first terminal pair; and

a second connector connected to the second end, the second connector including a second body that supports a second plurality of terminals, the second plurality of terminals including a second terminal pair, each terminal of the second terminal pair including a tail portion, the tail portion of each terminal of the second terminal pair connected to one of the signal conductors of the pair of signal conductors, wherein

14

the cable bypass assembly is configured to support a signaling frequency of 10 GHz.

25. The cable bypass assembly of claim 24, wherein the plurality of terminals includes a set of terminals that are configured to be directly connected to a supporting circuit board.

26. The cable bypass assembly of claim 25, wherein the set of terminals are configured to be surface mount attached to the supporting circuit board.

27. The cable bypass assembly of claim 26, wherein the set of terminals are arranged between separate high speed pairs of terminals.

28. A cable bypass assembly, comprising:

a cage with a front opening, the cage defining a port;

a first connector assembly positioned in the cage and configured to engage a module that is releasably inserted into the port, the first connector assembly including a receptacle connector with a card-slot, the receptacle connector supporting a first and second terminal assembly support, each of the first and second terminal assembly supports supporting a plurality of terminals in a row, the terminals in each row having a contact and a tail that are supported in a cantilever fashion by the terminal assembly supports, wherein the contacts of the plurality of terminals supported by the first and second terminal assembly supports are respectively arranged on opposite sides of the card-slot, wherein two terminals of the plurality of terminals are positioned in of the rows adjacent each other and form a first terminal pair;

a cable with a first end and a second end that defines a length, the cable including a pair of signal conductors disposed within an insulative body portion of the cable, the pair of signal conductors surrounded by a conductive shield, the signal conductors extending in a spaced-apart relationship through the insulative body portion along the length, the first end being terminated directly to the tails of the first terminal pair so that the pair of signal conductors are in electrical communication with the tails of the first terminal pair; and

a second connector connected to the second end, the second connector including a second body that supports a second plurality of terminals that include a second terminal pair, each terminal of the second terminals pair including a tail portion, the tail portion of each terminal of the second terminal pair connected to one of the signal conductors of the pair of signal conductors, wherein the cable bypass assembly is configured to support a signaling frequency of 10 GHz.

29. The cable bypass assembly of claim 28, wherein the terminals positioned on opposite sides of the card-slot are configured to deflect in opposite directions in response to insertion of a mating connector.

30. The cable bypass assembly of claim 28, wherein the cage is positioned in an enclosure and a portion of the cage extends out of the enclosure.

31. A cable bypass assembly, comprising:

a cage with a front opening, the cage defining a port;

a first connector assembly positioned in the cage and configured to engage a module that is releasably inserted into the port, the first connector assembly including a receptacle connector with a card-slot, the receptacle connector supporting a first and second terminal assembly support, each of the first and second terminal assembly supports supporting a plurality of terminals in a row, the terminals in each row having a contact and a tail that are supported in a cantilever

fashion by the terminal assembly supports, wherein the contacts of the plurality of terminals supported by the first and second terminal assembly supports are respectively arranged on opposite sides of the card-slot, wherein two terminals of the plurality of terminals are positioned in of the rows adjacent each other and form a first terminal pair; 5

a cable with a first end and a second end that defines a length, the cable including a pair of signal conductors disposed within an insulative body portion of the cable, the pair of signal conductors surrounded by a conductive shield, the signal conductors extending in a spaced-apart relationship through the insulative body portion along the length, the first end being terminated directly to the tails of the first terminal pair so that the pair of signal conductors are in electrical communication with the tails of the first terminal pair; and 10

a second connector connected to the second end, the second connector including a second body that supports a second plurality of terminals that include a second terminal pair, each terminal of the second terminals pair including a tail portion, the tail portion of each terminal of the second terminal pair connected to one of the signal conductors of the pair of signal conductors, wherein the terminals positioned on opposite sides of the card-slot are configured to deflect in opposite directions in response to insertion of a mating connector and wherein the cable bypass assembly is configured to support 19 GHz signaling frequency with not more than 8 dB of insertion loss. 15 20 25 30

* * * * *