



US00RE48686E

(19) **United States**
(12) **Reissued Patent**
Otsuka et al.

(10) **Patent Number: US RE48,686 E**
(45) **Date of Reissued Patent: Aug. 17, 2021**

(54) **INK-JET PRINTER**

(56) **References Cited**

(71) Applicant: **RISO KAGAKU CORPORATION**,
Tokyo (JP)

U.S. PATENT DOCUMENTS

(72) Inventors: **Shinichiro Otsuka**, Ibaraki (JP);
Hirohito Kubota, Ibaraki (JP)

6,390,618 B1 * 5/2002 Wotton B41J 11/002
347/102
8,308,284 B2 * 11/2012 Kanada B41J 2/175
347/102

(73) Assignee: **RISO KAGAKU CORPORATION**,
Tokyo (JP)

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **16/293,352**

JP 2-179761 7/1990
JP 2004-284058 10/2004

(22) Filed: **Mar. 5, 2019**

(Continued)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,586,412**
Issued: **Mar. 7, 2017**
Appl. No.: **15/040,325**
Filed: **Feb. 10, 2016**

OTHER PUBLICATIONS

Office Action in corresponding Japanese Patent Application No.
JP2015-035087 dated Sep. 4, 2018.

Primary Examiner — Minh Nguyen

(30) **Foreign Application Priority Data**

Feb. 25, 2015 (JP) 2015-035087

(74) *Attorney, Agent, or Firm* — Greenblum & Bernstein,
P.L.C.

(51) **Int. Cl.**
B41J 2/045 (2006.01)
B41J 2/18 (2006.01)
(Continued)


(57) **ABSTRACT**

A head holder has an opening through which a space between the head holder and a conveyer communicates with an inside of the head holder. Ahead cooler includes a blower configured to blow air into the head holder from an outside of the head holder with a flow rate of blow air and a suction unit configured to suction air from the head holder with a flow rate of suction air. The head cooler generates cooling air for cooling an ink-jet head inside the head holder by the blower and the suction unit. A controller controls the flow rate of blow air and the flow rate of suction air such that air containing ink mist is suctioned into the head holder through the opening.

(52) **U.S. Cl.**
CPC **B41J 2/04515** (2013.01); **B41J 2/175**
(2013.01); **B41J 2/1714** (2013.01); **B41J 2/18**
(2013.01);
(Continued)

(58) **Field of Classification Search**
CPC . B41J 2/1714; B41J 2/175; B41J 2/245; B41J
29/377; B41J 2/28; B41J 2/04515;
(Continued)

18 Claims, 12 Drawing Sheets



- (51) **Int. Cl.**
B41J 29/38 (2006.01)
B41J 2/17 (2006.01)
B41J 29/377 (2006.01)
B41J 2/175 (2006.01)
B41J 2/245 (2006.01)
B41J 2/185 (2006.01)
- (52) **U.S. Cl.**
CPC *B41J 2/245* (2013.01); *B41J 29/377*
(2013.01); *B41J 29/38* (2013.01); *B41J*
2002/1853 (2013.01); *B41J 2202/12* (2013.01)
- (58) **Field of Classification Search**
CPC . *B41J 29/38*; *B41J 2002/1853*; *B41J 2202/02*
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,050,812 B2 6/2015 Tanaka
2012/0001985 A1* 1/2012 Kumagai B41J 2/1714
347/34
2012/0281041 A1 11/2012 Leoni et al.
2014/0225959 A1* 8/2014 Kobayashi B41J 2/19
347/34

FOREIGN PATENT DOCUMENTS

JP 2005-271314 A * 10/2005 B41J 2/18
JP 2010-264752 11/2010
JP 2012-187862 10/2012
JP 2013-237172 11/2013
JP 2014-195886 10/2014
JP 2015-016623 1/2015

* cited by examiner

FIG. 1




FIG. 2





FIG. 3






FIG. 4

FIG. 5





FIG. 6






FIG. 7






FIG. 8

FIG. 9A



Amended

FIG. 9B



Amended

FIG. 10

		NEGATIVE-PRESSURE TANK INK LEVEL SENSOR	
		ON	OFF
POSITIVE-PRESSURE TANK INK LEVEL SENSOR	ON	INK PUMP: OFF INK SUPPLY VALVE: CLOSED	INK PUMP: OFF INK SUPPLY VALVE: CLOSED
	OFF	INK PUMP: ON INK SUPPLY VALVE: CLOSED	INK PUMP: OFF INK SUPPLY VALVE: OPEN




FIG. 12





FIG. 13



INK-JET PRINTER

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS REFERENCE TO RELATED APPLICATION

This application is an application for reissue of U.S. Pat. No. 9,586,412, which matured from U.S. application Ser. No. 15/040,325, which is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2015-035087, filed on Feb. 25, 2015, the entire contents of which are incorporated herein by reference.

BACKGROUND

1. Technical Field

The present disclosure relates to an ink-jet printer configured to perform printing by ejecting ink from an inkjet head.

2. Related Art

In an ink-jet printer, ink mist is generated by ink ejection from an ink-jet head. The ink mist causes contamination inside the printer. Also, the ink mist may deteriorate print image quality by adhering to paper to be printed.

To counter this problem, Japanese Patent Application Publication No. 2004-284058 discloses an ink-jet printer including a mist collector. The mist collector in the ink-jet printer sets a collection duct at a negative pressure by a sirocco fan, and collects ink mist by suctioning air containing the ink mist through an opening of the collection duct.

SUMMARY

However, the inkjet printer disclosed in Japanese Patent Application Publication No. 2004-284058 is increased in size since the dedicated mist collector is provided to collect the ink mist.

It is an object of the present disclosure to provide an ink-jet printer capable of reducing contamination inside the printer and deterioration in print image quality due to ink mist while an increase in size of the printer is suppressed.

An ink-jet printer in accordance with some embodiments includes: a conveyer configured to convey a printing medium; an ink-jet head configured to eject ink onto the printing medium conveyed by the conveyer; a head holder in a box shape configured to hold the ink-jet head, the head holder having an opening through which a space between the head holder and the conveyer communicates with an inside of the head holder; a head cooler including a blower configured to blow air into the head holder from an outside of the head holder with a flow rate of blow air and a suction unit configured to suction air from the head holder with a flow rate of suction air, the head cooler configured to generate cooling air for cooling the ink-jet head inside the head holder by the blower and the suction unit; and a controller configured to drive the conveyer to convey the printing medium while driving the ink-jet head to eject the ink onto the printing medium to perform printing and driving the head cooler to generate die cooling air. The controller is configured to control the flow rate of blow air

and the flow rate of suction air such that air containing ink mist is suctioned into the head holder through the opening.

According to the above configuration, the controller controls the blow air flow rate of the blower and the suction air flow rate of the suction unit such that the air containing ink mist can be suctioned into the head holder through the opening. Thus, the ink mist can be collected into the head holder. As a result, contamination inside the printer and deterioration in print image quality due to the ink mist can be reduced. Moreover, the ink mist is collected into the head holder by controlling the blow air flow rate of the blower and the suction air flow rate of the suction unit in the head cooler. Hence, there is no need to add a dedicated mechanism to collect the ink mist. Thus, an increase in size of the printer can be suppressed. Therefore, contamination inside the printer and deterioration in print image quality due to the ink mist can be reduced while an increase in size of the printer can be suppressed.

The controller may selectively use a first mode and a second mode. In the first mode, the controller may control the flow rate of blow air and the flow rate of suction air such that the cooling air in the head holder has an air volume required to cool the ink-jet head corresponding to a conveyance speed of the printing medium by the conveyer. In the second mode, the controller may control the flow rate of blow air and the flow rate of suction air such that the cooling air in the head holder has an air volume being smaller than the air volume of the cooling air in the head holder in the first mode and airflow flowing into the head holder through the opening has an air volume being smaller than an air volume of airflow flowing into the head holder through the opening in the first mode and capable of suctioning the ink mist.

According to the above configuration, the controller selectively uses the first mode capable of printing without reducing print productivity by ensuring cooling performance of the ink-jet head and the second mode capable of obtaining better print image quality than the first mode. Thus, convenience is improved since the printer can deal with the case where a user puts priority on the print productivity and the case where the user puts priority on the print image quality.

In the second mode, the controller may drive the conveyer to reduce the conveyance speed of the printing medium upon a temperature of the ink-jet head reaching a threshold.

According to the above configuration, an increase in temperature of the ink-jet head can be suppressed to reduce damage to the ink-jet head.

The ink-jet printer may further include an ink circulator configured to supply the ink to the ink-jet head while circulating the ink. The controller may drive the ink circulator such that an ink circulation flow rate in the second mode is higher than an ink circulation flow rate in the first mode.

According to the above configuration, an increase in temperature of the ink-jet head can be reduced in the second mode by increasing the ink circulation flow rate compared with the first mode. Thus, even in the second mode having a smaller flow rate of cooling air than the first mode, the damage to the ink-jet head can be reduced without a drop in print productivity.

The ink-jet printer may further include an ink circulator configured to supply the ink to the ink-jet head while circulating the ink. The ink circulator may include an ink cooler configured to cool the ink. In the first mode, the controller may drive the ink cooler to start cooling of the ink upon an ink temperature of the ink being a first temperature. In the second mode, the controller may drive the ink cooler

to start cooling of the ink upon an ink temperature of the ink being second temperature lower than the first temperature.

According to the above configuration, in the second mode than, the ink temperature low to start cooling of the ink by the ink cooler is set lower than in the first mode, and thereby an increase in the temperature of the inkjet head can be reduced. Thus, even in the second mode having a smaller flow rate of the cooling air than the first mode, the damage to the ink-jet head can be reduced without a drop in print productivity.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing a configuration of an ink-jet printer according to a first embodiment.

FIG. 2 is a schematic configuration diagram of a conveyer, a head unit and a head cooler in the ink-jet printer shown in FIG. 1.

FIG. 3 is a plan view of the head unit and the head cooler in the ink-jet printer shown in FIG. 1.

FIG. 4 is an exploded perspective view of the head unit and the head cooler in the ink-jet printer shown in FIG. 1.

FIG. 5 is a cross-sectional view taken along the line V-V in FIG. 3.

FIG. 6 is a schematic configuration diagram of an ink circulator, an ink supplier and a pressure generator in the ink-jet printer shown in FIG. 1.

FIG. 7 is a flowchart showing operations of the ink-jet printer shown in FIG. 1.

FIG. 8 is a flowchart showing operations of the ink-jet printer shown in FIG. 1.

FIG. 9A is a diagram showing an airflow inside a head holder as seen from above.

FIG. 9B is a diagram showing an airflow inside the head holder as seen from [front] right.

FIG. 10 is an explanatory diagram of ink level maintenance control.

FIG. 11 is a flowchart showing operations of an image priority mode in a second embodiment.

FIG. 12 is a flowchart showing operations of an image priority mode in a third embodiment.

FIG. 13 is a flowchart showing operations of an image priority mode in a fourth embodiment.

DETAILED DESCRIPTION

In the following detailed description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the disclosed embodiments. It will be apparent, however, that one or more embodiments may be practiced without these specific details. In other instances, well-known structures and devices are schematically shown in order to simplify the drawing.

Description will be hereinbelow provided for embodiments of the present invention by referring to the drawings. It should be noted that the same or similar parts and components throughout the drawings will be denoted by the same or similar reference signs, and that descriptions for such parts and components will be omitted or simplified. In addition, it should be noted that the drawings are schematic and therefore different from the actual ones.

First Embodiment

FIG. 1 is a block diagram showing a configuration of an ink-jet printer according to a first embodiment of the present

invention. FIG. 2 is a schematic configuration diagram at a conveyer, a head unit and a head cooler in the ink-jet printer shown in FIG. 1. FIG. 3 is a plan view of the head unit and the head cooler. FIG. 4 is an exploded perspective view of the head unit and the head cooler. FIG. 5 is a cross-sectional view taken along the line V-V in FIG. 1. FIG. 6 is a schematic configuration diagram of an ink circulator, an ink supplier and a pressure generator in the ink-jet printer shown in FIG. 1.

In the following description, it is assumed that a direction perpendicular to the page surface in FIG. 2 is a longitudinal direction and a page surface front direction is the front. In FIGS. 2 to 6, 9A and 9B, the right direction, left, direction, up direction, down direction, front direction and rear direction are denoted by RT, LT, UP, DN, FT and RR, respectively. The direction from left to right is the conveyance direction of paper P that is a printing medium.

As shown in FIG. 1, an ink-jet printer 1 according to the first embodiment includes a conveyer 2, a head unit 3, a head cooler 4, ink circulators 5A and 5B, ink suppliers 6A and 6B, a pressure generator 7 and a controller 8. Note that the alphabetical letters (A and B) in reference numerals of the ink circulators 5A and 5B and the ink suppliers 6A and 6B may be omitted for collective notation.

The conveyer 2 conveys the paper P. As shown in FIGS. 1 and 2, the conveyer 2 includes a conveyer belt 11, a drive roller 12, driven rollers 13, 14 and 15, a belt motor 16 and a paper adsorption fan 17.

The conveyer belt 11 conveys the paper P while holding the paper by adsorption. The conveyer belt 11 is a looped belt wound around the drive roller 12 and the driven rollers 13 to 15. The conveyer belt 11 has a number at belt holes (not shown) formed therein. The conveyer belt 11 holds the paper P by adsorption force generated in the belt holes by driving the paper adsorption fan 17. The conveyer belt 11 conveys the paper P, which is held by adsorption, rightward by rotating in a clockwise direction in FIG. 2.

The drive roller 12 rotates the conveyer belt 11 in the clockwise direction in FIG. 2.

The driven rollers 13 to 15 support the conveyer belt 11 together with the drive roller 12. The driven rollers 13 to 15 follow the drive roller 12 through the conveyer belt 11. The driven roller 13 is arranged to the left of the drive roller 12 at the same height as the drive roller 12. The driven rollers 14 and 15 are arranged at the same height at a distance from each other in a horizontal direction below the drive roller 12 and the driven roller 13.

The belt motor 16 rotationally drives the drive roller 12.

The paper adsorption fan 17 generates downward airflows. Thus, the paper adsorption fan 17 generates a negative pressure in the belt holes by suctioning air through the belt holes in the conveyer belt 11, thereby adsorbing the paper P on the conveyer belt 11. The paper adsorption fan 17 is arranged in a region surrounded by the looped conveyer belt 11.

The head unit 3 prints an image by ejecting ink onto the paper P conveyed by the conveyer 2. The head unit 3 includes ink-jet heads 21A and 21B and a head holder 22. Note that the alphabetical letters (A and B) in reference numerals of the ink-jet heads 21A and 21B may be omitted for collective notation.

The ink-jet heads 21A and 21B eject ink onto the paper P. The ink-jet heads 21A and 21B eject different colors of ink. The ink-jet heads 21A and 21B are arranged in parallel to each other along the conveyance direction (horizontal direction) of the paper P. Each of the ink jet heads 21A and 21B has six head modules 26.

The head modules 26 are arranged in a zigzag pattern as shown in FIGS. 3 and 4. More specifically, in the ink-jet head 21, two head module arrays, each including three head modules 26 arranged to be equally spaced apart along the longitudinal direction, are arranged to be shifted from each other by a half pitch in the longitudinal direction.

Each of the head modules 26 has an ink ejection surface 26a. The ink ejection surface 26a is a lower surface of the head module 26 facing the conveyer belt 11. The ink ejection surface 26a has a number of nozzles (not shown) provided therein, which are arranged along the longitudinal direction (main scanning direction). The head module 26 ejects ink, which is supplied from the ink circulator 5, through the nozzles.

Each of the head modules 26 is provided with a head temperature sensor 27. The head temperature sensor 27 measures the temperature of the head module 26.

The head holder 22 holds the ink-jet heads 21A and 21B. The head holder 22 is formed in a box shape having a hollow rectangular parallelepiped shape. As shown in FIGS. 4 and 5, the head holder 22 has a bottom plate 31, side plates 32 to 35 and a top plate 36.

The bottom plate 31 holds and fixes the head modules 26 in the ink-jet heads 21A and 21B. The bottom plate 31 is formed in a rectangular shape. As shown in FIG. 5, the bottom plate 31 has attachment openings 31a formed therein. The same number of the attachment openings 31a as that of the head modules 26 are formed.

Each of the head modules 26 is inserted into one of the attachment openings 31a and fixed therein such that the ink ejection surface 26a protrudes downward from the lower surface of the bottom plate 31. The attachment opening 31a is a through-hole larger than the cross-section of the head module 26 along the horizontal plane. Thus, the attachment position and angle of the head module 26 can be adjusted. Since the attachment openings 31a are thus formed, the head modules 26 are attached to the attachment openings 31a through gaps (openings) 31b. A space between the bottom plate 31 of the head holder 22 and the conveyer belt 11 in the conveyer 2 is communicated with the inside of the head holder 22 by the gaps 31b.

The side plates 32, 33, 34 and 35 form front, right, rear and left sidewalls of the head holder 22, respectively. The side plates 32 to 35 are integrally formed and provided upright around the bottom plate 31.

The front side plate 32 has four vent holes 32a formed therein. The vent holes 32a are inlets of air when the air is blown into the head holder 22 by a blower 41 to be described later. The four vent holes 32a are formed on extension lines of the four head module arrays including the head modules 26 in the ink-jet heads 21A and 21B, one vent hole 32a for each array.

The rear side plate 34 has four vent holes 34a formed therein. The vent holes 34a are outlets of air when the air is suctioned from the head holder 22 by a suction unit 42 to be described later. The four vent holes 34a are arranged at positions opposite to the respective four vent holes 32a in the front side plates 32. In other words, the four vent holes 34a are formed on extension lines of the four head module arrays including the head modules 26 in the ink-jet heads 21A and 21B, one vent hole 34a for each array.

The top plate 36 is a cover that closes an upper opening of the sidewall formed of the side plates 32 to 35. The top plate 36 is formed in a rectangular shape.

The head cooler 4 cools the ink-jet head 21 by generating cooling air in the head holder 22. The head cooler 4 includes the blower 41 and the suction unit 42.

The blower 41 blows air into the head holder 22 from outside. The blower 41 is arranged at the front of the head holder 22. The blower 41 includes a blowing chamber 46 and a blowing fan 47.

The blowing chamber 46 forms an airflow path between the blowing fan 47 and the head holder 22. The blowing chamber 46 is formed in a hollow shape that is elongated in the right-left direction. The blowing chamber 46 is arranged on the front side plate 32 of the head holder 22. In a surface of the blowing chamber 46 that comes into contact with the side plate 32, four blowing holes 46a are formed.

The blowing holes 46a are outlets of air from the blowing chamber 46 when the air is blown into the head holder 22. The blowing holes 46a are arranged at positions corresponding to the vent holes 32a in the side plate 32. In other words, the four blowing holes 46a are formed on extension lines of the four head module arrays including the head modules 26 in the ink-jet heads 21A and 21B, one blowing hole 46a for each array.

The blowing fan 47 sends air into the blowing chamber 46 from one end of the blowing chamber 46. Thus, air is blown into the head holder 22 through the blowing holes 46a in the blowing chamber 46.

The suction unit 42 suctioned air from the head holder 22. The suction unit 42 is arranged at the rear of the head holder 22. The suction unit 42 includes a suction chamber 48 and a suction fan 49.

The suction chamber 48 forms an airflow path between the head holder 22 and the suction fan 49. The suction chamber 48 is formed in a hollow shape that is elongated in the right-left direction. The suction chamber 48 is arranged on the rear side plate 34 of the head holder 22. In a surface of the suction chamber 48 that comes into contact with the side plate 34, four suction holes 48a are formed.

The suction holes 48a are inlets of air into the suction chamber 48 when the air is suctioned from the head holder 22. The suction holes 48a are arranged at positions corresponding to the vent holes 34a in the side plate 34. In other words, the four suction holes 48a are formed on extension lines of the four head module arrays including the head modules 26 in the ink-jet heads 21A and 21B, one suction hole 48a for each array.

The suction fan 49 suctioned air from one end of the suction chamber 48. Thus, air is suctioned from the head holder 22 through the suction holes 48a in the suction chamber 48 and the vent holes 34a in the side plate 34.

The ink circulator 5 supplies ink to the ink-jet head 21 while circulating the ink. The ink circulators 5A and 5B supply ink to the ink-jet heads 21A and 21B, respectively. As shown in FIG. 6, the ink circulator 5 includes a positive-pressure tank 51, an ink distributor 52, a collector 53, a negative-pressure tank 54, an ink pump 55, an ink temperature regulator 56, an ink temperature sensor 57 and ink circulation pipes 58 to 60.

The positive-pressure tank 51 stores ink to be supplied to the ink-jet head 21. The ink in the positive-pressure tank 51 is supplied to the ink-jet head 21 through the ink circulation pipe 58 and the ink distributor 52. Inside the positive-pressure tank 51, an air layer 61 is formed on the ink surface. The positive-pressure tank 51 is connected to a positive-pressure common air chamber 81 to be described later through a positive pressure-side communicating pipe 82 to be described later. The positive-pressure tank 51 is arranged at a position lower than the ink-jet head 21.

The positive-pressure tank 51 is provided with a positive-pressure ink level sensor 62 and an ink filter 63.

The positive-pressure ink level sensor **62** is configured to detect whether or not the ink level in the positive-pressure tank **51** has reached a reference level. The positive-pressure ink level sensor **62** outputs a signal indicating “on” when the ink level in the positive-pressure tank **51** is not less than the reference level, and outputs a signal indicating “off” when the ink level is less than the reference level.

The ink filter **63** removes unwanted material and the like in the ink.

The ink distributor **52** distributes the ink, which is supplied from the positive-pressure tank **51** through the ink circulation pipe **58**, to the head modules **26** in the ink-jet head **21**.

The collector **53** collects ink left unconsumed by the ink-jet head **21** from the head modules **26**. The ink collected by the collector **53** flows into the negative-pressure tank **54** through the ink circulation pipe **59**.

The negative-pressure tank **54** stores the ink left unconsumed by the ink-jet head **21** after receiving the ink from the collector **53**. The negative-pressure tank **54** also stores ink supplied from an ink cartridge **76** in an ink supplier **6** to be described later. Inside the negative-pressure tank **54**, an air layer **66** is formed on the ink surface. The negative-pressure tank **54** communicated with a negative-pressure common air chamber **88** to be described later through a negative pressure-side communicating pipe **89** to be described later. The negative-pressure tank **54** is arranged at the same height as the positive-pressure tank **51**.

The negative-pressure tank **54** is provided with a negative-pressure tank ink level sensor **67**. The negative-pressure tank ink level sensor **67** is configured to detect whether or not the ink level in the negative-pressure tank **54** has reached a reference level. The negative-pressure tank ink level sensor **67** outputs a signal indicating “on” when the ink level in the negative-pressure tank **54** is not less than the reference level, and outputs a signal indicating “off” when the ink level is less than the reference level.

The ink pump **55** sends ink to the positive-pressure tank **51** from the negative-pressure tank **54**. The ink pump **55** is provided in the ink circulation pipe **60**.

The ink temperature regulator **56** regulates the temperature of the ink in the ink circulator **5**. The ink temperature regulator **56** is provided in the ink circulation pipe **58**. The ink temperature regulator **56** includes a heater **71**, a heater temperature sensor **72**, a heat sink **73** and an ink cooling fan (ink cooler) **74**.

The heater **71** heats the ink passing inside the ink circulation pipe **58**. The heater temperature sensor **72** measures the temperature of the heater **71**. The heat sink **73** receives and releases heat from the ink passing inside the ink circulation pipe **58**. The ink cooling fan **74** sends air to the heat sink **73** to cool the ink passing inside the ink circulation pipe **58**.

The ink temperature sensor **57** measures the temperature of the ink in the ink circulator **5**. The ink temperature sensor **57** is provided in the ink circulation pipe **58**.

The ink circulation pipe **58** connects the positive-pressure tank **51** to the ink distributor **52**. A part of the ink circulation pipe **58** is divided into a portion passing through the heater **71** and a portion passing through the heat sink **73**. In the ink circulation pipe **58**, the ink flows toward the ink distributor **52** from the positive-pressure tank **51**. The ink circulation pipe **59** connects the collector **53** to the negative-pressure tank **54**. In the ink circulation pipe **59**, the ink flows toward the negative-pressure tank **54** from the collector **53**. The ink circulation pipe **60** connects the negative-pressure tank **54** to

the positive-pressure tank **51**. In the ink circulation pipe **60**, the ink flows toward the positive-pressure tank **51** from the negative-pressure tank **54**.

The ink suppliers **6A** and **6B** supply ink to the ink circulators **5A** and **5B**, respectively. The ink supplier **6** includes the ink cartridge **76**, an ink supply valve **77** and an ink supply pipe **78**.

The ink cartridge **76** houses ink to be used for printing by the ink-jet head **21**. The ink in the ink cartridge **76** is supplied to the negative-pressure tank **54** in the ink circulator **5** through the ink supply pipe **78**.

The ink supply valve **77** opens and closes an ink flow path inside the ink supply pipe **78**. The ink supply valve **77** is opened to supply the ink to the negative-pressure tank **54**.

The ink supply pipe **78** connects the ink cartridge **76** to the negative-pressure tank **54**. In the ink supply pipe **78**, the ink flows toward the negative-pressure tank **54** from the ink cartridge **76**.

The pressure generator **7** generates pressures for ink circulation in the positive-pressure tank **51** and the negative-pressure tank **54** in the ink circulator **5**. The pressure generator **7** is shared by the ink circulators **5A** and **5B**. The pressure generator **7** includes the positive-pressure common air chamber **81**, two positive pressure-side communicating pipes **82**, a positive pressure-side atmospheric air open valve **83**, a positive pressure-side atmospheric air open pipe **84**, a positive pressure-side pressure regulating valve **85**, a positive pressure-side pressure regulating pipe **86**, a positive pressure-side pressure sensor **87**, the negative-pressure common air chamber **88**, two negative pressure-side communicating pipes **89**, a negative pressure-side atmospheric air open valve **90**, a negative pressure-side atmospheric air open pipe **91**, a negative pressure-side pressure regulating valve **92**, a negative pressure-side pressure regulating pipe **93**, a negative pressure-side pressure sensor **94**, an air pump **95**, an air pump pipe **96**, a junction pipe **97**, an air filter **98** and an overflow pan **99**.

The positive-pressure common air chamber **81** is an air chamber configured to equalize the pressures in the positive-pressure tank **51** in the ink circulator **5A** and the positive-pressure tank **51** in the ink circulator **5B**. The positive-pressure common air chamber **81** is communicated with air layers **61** in the positive-pressure tanks **51** in the two ink circulators **5A** and **5B** through the two positive pressure-side communicating pipes **82**. Thus, the positive-pressure tanks **51** in the ink circulators **5A** and **5B** are communicated with each other through the positive-pressure common air chamber **81** and the positive pressure-side communicating pipes **82**.

The positive pressure-side communicating pipes **82** communicate the positive-pressure common air chamber **81** with the air layers **61** in the positive-pressure tanks **51**. The two positive pressure-side communicating pipes **82** are provided to correspond one by one to the two ink circulators **5A** and **5B**. Each of the positive pressure-side communicating pipes **82** has one end connected to the positive-pressure common air chamber **81** and the other end connected to the air layer **61** in the positive-pressure tank **51**.

The positive pressure-side atmospheric air open valve **83** opens and closes an airflow path inside the positive pressure-side atmospheric air open pipe **84** to switch the positive-pressure tank **51** between a sealed state (a state of being cut off from the atmosphere) and an atmospheric air open state (a state of being communicated with the atmosphere) through the positive-pressure common air chamber **81** and the positive pressure-side communicating pipe **82**. The posi-

tive pressure-side atmospheric air open valve **83** is provided on the positive pressure-side atmospheric air open pipe **84**.

The positive pressure-side atmospheric air open pipe **84** forms an airflow path for releasing the inside of the pressurized tank to the atmosphere through the positive-pressure common air chamber **81** and the positive pressure-side communicating pipe **82**. The positive pressure-side atmospheric air open pipe **84** has one end connected to the positive-pressure common air chamber **81** and the other end connected to the junction pipe **97**.

The positive pressure-side pressure regulating valve **85** opens and closes an airflow path inside the positive pressure-side pressure regulating pipe **86** to regulate the pressures in the positive-pressure common air chamber **81** and the positive-pressure tank **51**. The positive pressure-side pressure regulating valve **85** is provided on the positive pressure-side pressure regulating pipe **86**.

The positive pressure-side pressure regulating pipe **86** forms an airflow path for regulating the pressures in the positive-pressure common air chamber **81** and the positive-pressure tank **51**. The positive pressure-side pressure regulating pipe **86** has one end connected to the positive-pressure common air chamber **81** and the other end connected to the junction pipe **97**.

The positive pressure-side pressure sensor **87** measures the pressure in the positive-pressure common air chamber **81**. The pressure in the positive-pressure common air chamber **81** is equal to the pressures in the positive-pressure tanks **51** in the ink circulators **5A** and **5B**. This is because the positive-pressure common air chamber **81** is communicated with the air layers **61** in the positive-pressure tanks **51** in the ink circulators **5A** and **5B**.

The negative-pressure common air chamber **88** is an air chamber configured to equalize the pressures in the negative-pressure tank **54** in the ink circulator **5A** and the negative-pressure tank **54** in the ink circulator **5B**. The negative-pressure common air chamber **88** is communicated with air layers **66** in the negative-pressure tanks **54** in the two ink circulators **5A** and **5B** through the two positive pressure-side communicating pipes **89**. Thus, the negative-pressure tanks **54** in the ink circulators **5A** and **5B** are communicated with each other through the negative-pressure common air chamber **88** and the negative pressure-side communicating pipes **89**.

The negative pressure-side communicating pipes **89** communicate the negative-pressure common air chamber **88** with the air layers **66** in the negative-pressure tanks **54**. The two negative pressure-side communicating pipes **89** are provided to correspond one by one to the two ink circulators **5A** and **5B**. Each of the negative pressure-side communicating pipes **89** has one end connected to the negative-pressure common air chamber **88** and the other end connected to the air layer **66** in the negative-pressure tank **54**.

The negative pressure-side atmospheric air open valve **90** opens and closes an airflow path inside the negative pressure-side atmospheric air open pipe **91** to switch the negative-pressure tank **54** between the sealed state and the atmospheric air open state through the negative-pressure common air chamber **88** and the negative pressure-side communicating pipe **89**. The negative pressure-side atmospheric air open valve **90** is provided on the negative pressure-side atmospheric air open pipe **91**.

The negative pressure-side atmospheric air open pipe **91** forms an airflow path for releasing the negative pressure tank **54** to the atmosphere through the negative-pressure common air chamber **88** and the negative pressure-side communicating pipe **89**. The negative pressure-side atmo-

spheric air open pipe **91** has one end connected to the negative-pressure common air chamber **88** and the other end corrected to the junction pipe **97**.

The negative pressure-side pressure regulating valve **92** opens and closes an airflow path inside the negative pressure-side pressure regulating pipe **93** to regulate the pressures in the negative-pressure common air chamber **88** and the negative-pressure tank **54**. The negative pressure-side pressure regulating valve **92** is provided on the positive pressure-side pressure regulating pipe **93**.

The negative pressure-side pressure regulating pipe **93** forms an airflow path for regulating the pressures in the negative-pressure common air chamber **88** and the negative-pressure tank **54**. The negative pressure-side pressure regulating pipe **93** has one end connected to the negative-pressure common air chamber **88** and the other end connected to the junction pipe **97**.

The negative pressure-side pressure sensor **94** measures the pressure in the negative-pressure common air chamber **88**. The pressure in the negative-pressure common air chamber **88** is equal to the pressures in the negative-pressure tanks **54** in the ink circulators **5A** and **5B**. This is because the negative-pressure common air chamber **88** is communicated with the air layers **66** in the negative-pressure tanks **54** in the ink circulators **5A** and **5B**.

The air pump **95** suctions air from the negative-pressure tanks **54** in the ink circulators **5A** and **5B** through the negative-pressure common air chamber **88**, and sends air to the positive-pressure tanks **51** in the ink circulators **5A** and **5B** through the positive-pressure common air chamber **81**. The air pump **95** is provided in the air pump pipe **96**.

The air pump pipe **96** forms an airflow path to be sent to the positive-pressure common air chamber **81** from the negative-pressure common air chamber **88** by the air pump **95**. The air pump pipe **96** has one end connected to the positive-pressure common air chamber **81** and the other end connected to the negative-pressure common air chamber **88**.

The junction pipe **97** has one end connected to the overflow pan **99** and the other end (upper end) communicated with the atmosphere through the air filter **98**. The end of the junction pipe **97** on the overflow pan **99** side is closed by an overflow ball **100** to be described later during a normal operation. The positive pressure-side atmospheric air open pipe **84**, the positive pressure-side pressure regulating pipe **86**, the negative pressure-side atmospheric air open pipe **91** and the negative pressure-side pressure regulating pipe **93** are connected to the junction pipe **97**. Thus, the positive pressure-side atmospheric air open pipe **84**, the positive pressure-side pressure regulating pipe **86**, the negative pressure-side atmospheric air open pipe **91** and the negative pressure-side pressure regulating pipe **93** are communicated with the atmosphere.

The air filter **98** prevents unwanted material and the like in the air from entering the junction pipe **97**. The air filter **98** is provided at the upper end of the junction pipe **97**.

The overflow pan **99** receives ink overflowing from the positive-pressure tank **51** and the negative-pressure tank **54** due to abnormality in the ink supply valve **77**, for example, and also overflowing into the function pipe from the positive-pressure common air chamber **81** and the negative-pressure common air chamber **88**.

The overflow pan **99** is provided with the overflow ball **100**. The overflow ball **100** prevents external air from flowing into the junction pipe **97** by losing the end of the junction pipe **97** having an opening at the bottom of the overflow pan **99** when there is no ink in the overflow pan **99**. When the ink flows into the overflow pan **99** from the

11

junction pipe **97**, the overflow ball **100** floats to enable the ink to flow into the overflow pan **99**.

The overflow pan **99** is also provided with an overflow ink level sensor **101**. The overflow ink level sensor **101** is configured to detect whether or not the ink level inside the overflow pan **99** has reached a predetermined level.

The overflow pan **99** is connected to a waste tank (not shown) and configured to discharge the ink to the waste tank when the ink surface is detected by the overflow ink level sensor **101**.

The controller **8** controls operations of the respective units in the ink-jet printer **1**. The controller **8** includes a CPU, a RAM, a ROM, a hard disk and the like.

To be more specific, the controller **8** performs control to print on the paper **P** by ejecting ink from the ink-jet head **21** while convey in the paper **P** the conveyer **2**.

Also, during printing, the controller **8** controls the blower **41** and the suction unit **42** in the head cooler **4** to generate cooling air inside the head holder **22**. In this event, the controller **8** controls a flow rate of air (flow rate of blow air) of the blower **41** and a flow rate of air (flow rate of suction air) of the suction unit **42** to suction air containing ink mist into the head holder **22** from a space between the bottom plate **31** of the head holder **22** and the conveyer belt **11** through the gaps **31b** around the head modules **26**.

Moreover, the controller **8** selectively uses a production priority mode (first mode) and an image priority mode (second mode) as print modes. The production priority mode is a print mode for printing without reducing print productivity by ensuring cooling performance of the ink-jet head **21**. On the other hand, the image priority mode is a print mode that puts higher priority an print image quality compared with the production priority mode. The print mode is selected in advance and set by the user operating an operation panel (not shown), for example. The controller **8** controls the flow rate of blow air and the flow rate of suction air according to the print mode.

Next, operations of the ink-jet printer **1** are described.

FIGS. **7** and **8** are flowcharts showing the operations of the ink-jet printer **1**. The processing shown in the flowcharts of FIGS. **7** and **8** is started when a print job is inputted to the ink-jet printer **1**.

In Step **S1** of FIG. **7**, the controller **8** determines whether or not the print mode to be executed is the production priority mode.

After determining that the print mode to be executed is the production priority mode (Step **S1**: YES), the controller **8** make head cooling settings for the production priority mode. To be more specific, as duty ratios for driving the blowing fan **47** and the suction fan **49**, the controller **8** sets a duty ratio D_{sf} of the blowing fan **47** and a duty ratio D_{sk} of the suction fan **49** for the production priority mode.

The duty ratios D_{sf} and D_{sk} are determined. In advance such that the flow rate of cooling air W (see FIGS. **9A** and **9B**) inside the head holder **22**, which is determined based on the flow rate of blow air and the flow rate of suction air, is the flow rate of air required for cooling of the ink-jet head **21** according to a paper conveyance speed by the conveyer **2**, and are stored in the controller **8**. Here, as the paper conveyance speed becomes higher, the drive frequency of the head module **26** becomes higher and an amount of heat generated in the head module **26** is increased. Accordingly, the higher the paper conveyance speed, the larger the flow rate of the cooling air W required for cooling of the ink-jet head **21**.

Moreover, the duty ratios D_{sf} and D_{sk} take values such that the flow rate of suction air is larger than the flow rate of

12

blow air. When the flow rate of suction air is larger than the flow rate of blow air, a shortfall in the flow rate of blow air is covered by air from the space between the bottom plate **31** of the head holder **22** and the conveyer belt **11**. More specifically, airflows F (see FIGS. **9A** and **9B**) are generated, which flow into the head holder **22** from the space between the bottom plate **31** and the conveyer belt **11** through the gaps **31b** in the bottom plate **31**. These airflows F collect ink mist together with the air into the head holder **22**.

Assuming that a printing rate of print images is constant the higher the print productivity, the larger the amount of ink mist generated per unit time. Here, the print productivity is increased as the paper conveyance speed is increased. Accordingly, the higher the paper conveyance speed, the larger the amount of ink mist generated per unit time. Therefore, the duty ratios D_{sf} and D_{sk} are determined such that, in order to collect more ink mist, the amount of the airflow F flowing into the head holder through the gaps **31b** is increased as the paper conveyance speed is increased. Here, the air volume of the airflows F flowing into the head holder **22** through the gaps **31b** is determined by a difference between the flow rate of suction air and the flow rate of blow air.

Moreover, the duty ratios D_{sf} and D_{sk} are determined such that, as for the amount of the airflows F flowing into the head holder **22** through the gaps **31b**, a landing shift amount due to the airflows F is within an allowable range. The landing shift amount is an amount of shift in landing position of the ink elected from the head module **26** on the paper **P**.

Following Step **S2**, the controller starts a print operation in Step **S3**. To be more specific, the controller **8** first closes the positive pressure-side atmospheric air open valve **83** and the negative pressure-side atmospheric air open valve **90**.

Thus, the positive-pressure tanks **51** in the ink circulators **5A** and **5B** are set in the sealed state through the positive-pressure common air chamber **81** and the like, and the negative-pressure tanks **54** are set in the sealed state through the negative-pressure common air chamber **88** and the like. Note that, during standby when the ink-jet printer **1** does not operate, the positive pressure-side atmospheric air open valve **83** and the negative pressure-side atmospheric air open valve **90** are open and the positive pressure-side pressure regulating valve **85** and the negative pressure-side pressure regulating valve **92** are closed.

Next, the controller **8** starts the air pump **95**. Thus, air is sent into the positive-pressure common air chamber **81** from the negative-pressure common air chamber **88**, thereby reducing the pressures in the negative-pressure common air chamber **88** and the negative-pressure tank **54** and increasing the pressures in the positive-pressure common air chamber **81** and the positive-pressure tank **51**. Thus, the ink flows toward the ink-jet head **21** from the positive-pressure tank **51**.

When the pressure (positive pressure-side pressure) of the positive-pressure common air chamber **81** and the positive-pressure tank **51**, which is measured by the positive pressure-side pressure sensor **87**, and the pressure (negative pressure-side pressure) of the negative-pressure common air chamber **88** and the negative-pressure tank **54**, which is measured by the negative pressure-side pressure sensor **94**, reach set pressures P_k and P_f , respectively, the controller **8** stops the air pump **95**. Here, the controller **8** controls opening and closing of the positive pressure-side pressure regulating valve **85** and the negative pressure-side pressure regulating valve **92** according to the measured values by the positive pressure-side pressure sensor **87** and the negative pressure-side pressure sensor **94**, so that the positive pres-

sure-side pressure and the negative pressure-side pressure are set to the set pressures Pk and Pf after the start of the air pump 95.

The set pressures Pk and Pf are set in advance as pressure values for setting the nozzle pressure of the head modules 26 at a proper value (negative pressure) while circulating the ink at a predetermined ink circulation flow rate in the ink circulators 5A and 5B.

When the positive pressure-side pressure and the negative pressure-side pressure reach the set pressures Pk and Pf, the controller 8 starts the drive roller 12 by the belt motor 16. Thus, circling drive of the conveyer belt 11 is started. The controller 8 controls the belt motor 16 such that the paper conveyance speed is set to a predetermined print conveyance speed.

The controller 8 also starts the paper adsorption fan 17. Thus, the paper adsorption fan 17 suctions air through the belt holes in the conveyer belt 11, thereby generating adsorption force in the belt holes.

Moreover, the controller 8 starts the blowing fan 47 and the suction fan 49. The controller 8 drives the blowing fan 47 and the suction fan 49 at the duty ratios Dsf and Dsk for the production priority mode set in Step S2, respectively.

By driving the blowing fan 47, air is blown into the head holder 22 through the blowing holes 46a in the blowing chamber 46 and the vent holes 32a in the side plate 32 of the head holder 22. Meanwhile, by driving the suction fan 49, air is suctioned from the head holder 22 through the vent holes 34a in the side plate 34 of the head holder 22 and the suction holes 48a in the suction chamber 48.

Thus, as shown in FIGS. 9A and 9B, cooling air W is generated in the head holder 22, which flows from the front toward the rear. Also, airflows F are generated, which flow into the head holder 22 from the space between the bottom plate 31 and the conveyer belt 11 through the gaps 31b.

When the paper P is supplied to the conveyer 2 from an unillustrated paper feeder, the paper P is conveyed while being, adsorbed to and held by the conveyer belt 11. The controller 8 controls the head unit 3 to print an image by ejecting ink from the ink-jet heads 21A and 21B, based on the print job, onto the paper P conveyed below the head unit 3. When the specified number of sheets to be printed is more than one, the controller 8 performs control to print images by ejecting ink from the ink-jet heads 21A and 21B onto the sheets of the paper P, which are sequentially fed and conveyed on the conveyance belt 11.

During such a print operation, the controller 8 performs ink level maintenance control. The ink level maintenance control is control of the ink pump 55 and the ink supply valve 77 for circulating the ink while maintaining the ink levels in the positive-pressure tank 51 and the negative-pressure tank 54 at the reference level.

To be more specific, as shown in FIG. 10, the controller 8 turns off the ink pump 55 and closes the ink supply valve 77 in a state where the positive-pressure ink level sensor 62 and the negative-pressure tank ink level sensor 67 are both on. Likewise, the controller 8 turns off the ink pump 55 and closes the ink supply valve 77 in a state where the positive-pressure ink level sensor 62 is on and the negative-pressure tank ink level sensor 67 is off.

In a state where the positive-pressure ink level sensor 62 is off and the negative-pressure tank ink level sensor 67 is on, the controller 8 turns on the ink pump 55 and closes the ink supply valve 77.

In a state where the positive-pressure ink level sensor 62 and the negative-pressure tank ink level sensor 67 are both off, the controller 8 turns off the ink pump 55 and opens the ink supply valve 77.

During execution of the print job, the ink is supplied to the ink-jet head 21 from the positive-pressure tank 51, and the ink left unconsumed by the ink-jet head 21 is collected to the negative-pressure tank 54. When the positive-pressure ink level sensor 62 is turned off and the negative-pressure tank ink level sensor 67 is turned on, the ink pump 55 sends the ink to the positive-pressure tank 51 from the negative-pressure tank 54 under the ink level maintenance control. Thus, printing is performed while the ink is being circulated.

When the positive-pressure ink level sensor 62 and the negative-pressure tank ink level sensor 67 are both turned off as the ink is consumed and the amount of ink circulated is reduced, the ink supply valve 77 is opened to supply the ink to the negative-pressure tank 54 under the ink level maintenance control.

Even with the ink level maintenance control as described above, minute changes in ink level occurs in the positive-pressure tank 51 and the negative-pressure tank 54. For example, the ink levels in the positive-pressure tank 51 and the negative-pressure tank 54 change due to outflow of the ink to the ink-jet head 21 from the positive-pressure tank 51 and return of the ink left unconsumed by the ink-jet head 21 to the negative-pressure tank 54. Also, ink supply from the ink cartridge 76 changes the ink level in the negative-pressure tank 54. Moreover, sending of the ink by the ink pump 55 changes the ink levels in the positive-pressure tank 51 and the negative-pressure tank 54.

The ink level changes in the positive-pressure tank 51 and the negative-pressure tank 54 cause changes in the positive pressure-side pressure and the negative pressure-side pressure. To cope with such changes, the controller 8 appropriately performs driving of the air pump 95 and opening and closing of the positive pressure-side pressure regulating valve 85 and the negative pressure-side pressure regulating valve 92 according to the measured values by the positive pressure-side pressure sensor 87 and the negative pressure-side pressure sensor 94 to maintain the set pressures Pk and Pf of the positive pressure-side pressure and the negative pressure-side pressure.

Incidentally, the ink has a printable temperature range. The printable temperature range is a temperature range within which normal ink ejection by the ink-jet head 21 can be ensured. When the ink temperature measured by the ink temperature sensor 57 is outside the printable temperature range at the start of the print operation, the controller 8 controls the ink temperature regulator 56 to regulate the ink temperature while circulating the ink by the ink circulator 5.

When the head modules 26 in the ink-jet head 21 are driven in the print operation, the head modules 26 generate heat. Although the head modules 26 are cooled by the cooling air W, the temperature of the head modules 26 may become higher than the ink temperature and the ink temperature may be increased. To counter this situation, the controller 8 starts the ink cooling fan 74 when the ink temperature measured by the ink temperature sensor 57 reaches an ink cooling start temperature Tk within the printable temperature range, to prevent the ink temperature from deviating from the printable temperature range. Thus, the ink temperature in the ink circulator 5 is lowered. When the ink temperature is lowered by a predetermined temperature from the ink cooling start temperature Tk, the controller 8 stops the ink cooling fan 74.

15

During the print operation, ink mist is generated by ink ejection by the head modules **26**. Some of the ink mist is collected to the paper adsorption fan **17** through the belt holes in the conveyer belt **11**. Also, part of the remaining ink mist is collected into the head holder **22** by the airflows **F** flowing into the head holder **22** through the gaps **31b** in the bottom plate **31**.

Referring back to FIG. 7, following Step **S3**, the controller **8** determines in Step **S4** whether or not at least one of the ink-jet heads **21A** and **21B** has reached a head temperature threshold **Th**, based on the temperature measured by each head temperature sensor **27**. Here, when the ink-jet head **21** includes a head module **26** in which the temperature measured by the head temperature sensor **27** has reached the head temperature threshold **Th**, the controller **8** determines that the ink-jet head **21** has reached the head temperature threshold **Th**.

The head temperature threshold **Th** is a threshold for determining whether or not cooling of the ink-jet head **21** is insufficient. The head temperature threshold **Th** is set to a temperature lower than a head temperature upper limit **Tu**. The head temperature upper limit **Tu** is an upper limit of a usable temperature range of the head modules **26**.

After determining that at least one of the ink-jet heads **21A** and **21B** has reached the head temperature threshold **Th** (Step **S4**: YES), the controller **8** determines in Step **S5** whether or not at least one of the ink-jet heads **21A** and **21B** has reached the head temperature upper limit **Tu**. Here, when the ink-jet head **21** includes a head module **26** in which the temperature measured by the head temperature sensor **27** has reached the head temperature upper limit **Tu**, the controller **8** determines that the ink-jet head **21** has reached the head temperature upper limit **Tu**.

After determining that neither of the ink-jet heads **21A** and **21B** has reached the head temperature upper limit **Tu** (Step **S5**: NO), the controller **8** determines in Step **S6** whether or not the duty ratios of the blowing fan **47** and the suction fan **49** have been changed. After determining that the duty ratios of the blowing fan **47** and the suction fan **49** have been changed (Step **S6**: YES), the controller **8** returns to Step **S4**.

After determining that the duty ratios of the blowing fan **47** and the suction fan **49** are not changed (Step **S6**: NO), the controller **8** changes the duty ratios of the blowing fan **47** and the suction fan **49** in Step **S7** to increase the flow rate of the cooling air **W**. For example, the controller **8** changes the duty ratios of the blowing fan **47** and the suction fan **49** to the maximum value (100%). Thereafter, the controller **8** returns to Step **S4**.

After determining in Step **S5** that at least one of the ink-jet heads **21A** and **21B** has reached the head temperature upper limit **Tu** (Step **S5**: YES), the controller **8** stops the print operation in Step **S8**. To be more specific, the controller **8** stops the ink-jet heads **21A** and **21B**, the drive roller **12**, the paper adsorption fan **17**, the blowing fan **47** and the suction fan **49**. The controller **8** opens the positive pressure-side atmospheric air open valve **83** and the negative pressure-side atmospheric air open valve **90**. Thus, a series of operations are finished.

After determining in Step **S4** that neither of the ink-jet heads **21A** and **21B** has reached the head temperature threshold **Th** (Step **S4**: NO), the controller **8** determines in Step **S9** whether or not the printing is finished for the specified number of sheets to be printed. After determining that the printing is not finished for the specified number of sheets to be printed. (Step **S9**: NO), the controller **8** returns to Step **S4**.

16

After determining that the printing is finished for the specified number of sheets to be printed (Step **S9**: YES), the controller **8** stops the drive roller **12**, the paper adsorption fan **17**, the blowing fan **47** and the suction fan **49**, and opens the positive pressure-side atmospheric air open valve **83** and the negative pressure-side atmospheric air open valve **90** to finish the series of operations.

After determining in Step **S1** that the print mode to be executed is the Image priority mode (Step **S1**: NO), the controller **8** makes head cooling settings for the image priority mode in Step **S10** of FIG. 8. To be more specific, as duty ratios for driving the blowing fan **47** and the suction fan **49**, the controller **8** sets a duty ratio **Dgf** of the blowing fan **47** and a duty ratio **Dgk** of the suction fan **49** for the image priority mode.

The duty ratios **Dgf** and **Dgk** are determined in advance such that the flow rate of blow air and the flow rate of suction air are set to those that put higher priority on print image quality than on the cooling of the ink-jet head **21**, and are stored in the controller **8**.

To be more specific, the duty ratios **Dgf** and **Dgk** take such values that the flow rate of the cooling air **W** becomes smaller than that in the production priority mode. Thus, excessive cooling of the ink-jet head **21** can be suppressed. The excessive cooling of the ink-jet head **21** lowers the temperature of the ink in the head modules **26** and therefore increases the viscosity. Thus, the print image quality may be deteriorated by reduction in ink ejection amount and the like.

The duty ratios **Dgf** and **Dgk** take such values that the flow rate of suction air is larger than the flow rate of blow air. Moreover, the values of the duty ratios **Dgf** and **Dgk** are set such that the flow rate of the airflows **F** flowing into the head holder **22** through the gaps **31b** in the bottom plate **31** is smaller than that in the production priority mode and enables suction of ink droplets (ink mist) of a predetermined size or less. Furthermore, the values of the duty ratios **Dgf** and **Dgk** are set such that the flow rate of the airflows **F** does not bend the flight trajectory of main droplets of ink ejected from the head modules. Thus, ink landing shift due to the airflows **F** is reduced, while the ink mist is suctioned into the head holder **22** by the airflows **F**.

The controller **8** advances to Step **S11** after Step **S10**. The processing in Steps **S11** to **S13** is the same as the processing in Steps **S3** to **S5** of FIG. 7 described above.

When a print operation is started in Step **S11**, cooling air **W** and airflows **F** shown in FIGS. 9A and 9B are also generated in the image priority mode. In the image priority mode, the flow rates of the cooling air **W** and the airflows **F** are smaller than those in the production priority mode. The cooling air **W** is set to the flow rate that prevents excessive cooling of the ink-jet head **21**. The airflows **F** are set to the flow rate that enables the ink mist to be suctioned into the head holder **22** while suppressing landing shift on the paper **P**.

After determining in Step **S13** that neither of the ink-jet heads **21A** and **21B** has reached the head temperature upper limit **Tu** (Step **S13**: NO), the controller **8** determines in Step **S14** whether or not the paper conveyance speed by the conveyer **2** has been reduced. After determining that the paper conveyance speed has been reduced (Step **S14**: YES), the controller **8** returns to Step **S12**.

After determining that the paper conveyance speed is not reduced (Step **S14**: NO), the controller **8** reduces the paper conveyance speed to a preset speed by controlling the belt motor **16** in Step **S15**. Thereafter, the controller **8** returns to Step **S12**.

After the paper conveyance speed is reduced, the controller **8** drives the head modules **26** at a drive frequency

17

corresponding to the reduced paper conveyance speed. Thus, the amount of heat generated in the head modules **26** is reduced to suppress temperature rise.

After determining in Step **S13** that at least one of the ink-jet heads **21A** and **21B** has reached the head temperature upper limit T_u (Step **S13**: YES), the controller **8** stops the print operation in Step **S16**. Thus, a series of operations are finished.

After determining in Step **S12** that neither of the ink-jet heads **21A** and **21B** has reached the head temperature threshold T_h (Step **S12**: NO), the controller **8** determines in Step **S17** whether or not the printing is finished for the specified number of sheets to be printed. After determining that the printing is not finished for the specified number of sheets to be printed (Step **S17**: NO), the controller **8** returns to Step **S12**.

After determining that the printing is finished for the specified number of sheets to be printed (Step **S17**: YES), the controller **8** stops the drive roller **12**, the paper adsorption fan **17**, the blowing fan **47** and the suction fan **49**, and opens the positive pressure-side atmospheric air open valve **83** and the negative pressure-side atmospheric air open valve **90** to finish the series of operations.

In the ink-jet primer **1**, as described above, the controller **8** controls the flow rate of blow air and the flow rate of suction air to suction air containing ink mist into the head holder **22** from the space between the bottom plate **31** and the conveyer belt **11** through the gaps **31b** in the bottom plate **31** of the head holder **22**. Thus, the ink mist can be collected into the head holder **22**. As a result, contamination inside the printer and deterioration in print image quality due to the ink mist can be reduced.

Moreover, in the ink-jet printer **1**, the ink mist is collected into the head holder **22** by controlling the flow rate of blow air and the flow rate of suction air of the head cooler **4**. This eliminates the need to add a dedicated mechanism to collect the ink mist, thus suppressing an increase in size of the printer.

Therefore, the ink-jet printer **1** can reduce the contamination inside the printer and deterioration in print image quality due to the ink mist while suppressing an increase in size of the printer.

Moreover, in the ink-jet printer **1**, the controller **8** controls the flow rate of blow air and the flow rate of suction air in the production priority mode such that the cooling air **W** has an air volume required for cooling or the ink-jet head **21** corresponding to the paper conveyance speed. Thus, in the production priority mode, printing can be performed without reducing the print productivity by ensuring cooling performance of the ink-jet head **21**.

Meanwhile, in the image priority mode, the controller **8** controls the flow rate of blow air and the flow rate of suction air such that the cooling air **W** has an air volume which is smaller than that in the production priority mode, and makes the flow rate of airflows **F** flowing into the head holder **22** through the gaps **31b** in the bottom plate **31** smaller than that in the production priority mode, so that the ink mist can be suctioned. Thus, excessive cooling of the ink-jet head **21** is reduced in the image priority mode compared with the production priority mode. At the same time, the ink mist can be collected into the head holder **22** while reducing the ink landing shift. As a result, better print image quality can be obtained in the image priority mode compared with the production priority mode.

The controller **8** selectively uses the production priority mode and the image priority mode as described above. Thus, convenience is improved since the printer can deal with the

18

case where the user puts priority on the print productivity and the case where the user puts priority on the print image quality.

Moreover, the controller **8** reduces the paper conveyance speed when the temperature of the ink-jet head **21** reaches the head temperature threshold T_h in the image priority mode. Thus, the amount of heat generated in the head modules **26** in the ink-jet head **21** is reduced to suppress temperature rise. As a result, damage to the ink-jet head **21** can be reduced.

Note that, in the image priority mode, the flow rate of blow air may be set to 0 (zero). In this case, the controller **8** drives the suction fan **49** only without driving the blowing fan **47** in the head cooler **4** during the print operation.

In this case, the cooling air **N** shown in FIGS. **9A** and **9B** is not generated but the airflows **F** are generated. The controller **8** drives the suction fan **49** at the duty ratios such that the flow rate of the airflows **F** enables suction of ink droplets (ink mist) of a predetermined size or less without suctioning main droplets of ink ejected from the head modules. Thus, the ink mist can be collected into the head holder **22** while reducing the ink landing shift.

Note that, although the cooling air **W** is not generated, a cooling effect of the airflows **F** on the ink-jet head **21** can be obtained.

Moreover, in the production priority mode, the flow rate of blow air and the flow rate of suction air may be set equal. In this case, a s generated by the blowing fan **62** and the suction fan **67** cancel out inside the head holder **22**. Thus, the airflows **F** flowing into the head holder **22** through the gaps **31b** in the bottom plate **31** are not generated. Thus, although the ink mist cannot be collected into the head holder **22**, ink landing shift due to the airflows **F** can be suppressed.

Second Embodiment

Next, description is given of a second embodiment in which changes are made to the operation of the image priority mode in the first embodiment described above. Note that an inkjet printer of the second embodiment has the same structure as that of the ink-jet printer **1** of the first embodiment. Also, operations in a production priority mode according to the second embodiment are the same as those in the first embodiment, i.e., the operations in Steps **S2** to **S9** of FIG. **7**.

FIG. **11** is a flowchart showing operations in an image priority mode in the second embodiment.

In Step **S21** of FIG. **11**, the controller **8** sets a paper conveyance speed for the image priority mode. To be more specific, the controller **8** sets a paper conveyance speed V_g for the image priority mode as a paper conveyance speed by the conveyer **2** during a print operation in the image priority mode. The paper conveyance speed V_g for the image priority mode is determined in advance to be lower than that in the production priority mode, and is stored in the controller **8**.

Next, in Step **S22**, the controller **8** makes head cooling settings for the image priority mode. To be more specific, as duty ratios for driving the blowing fan **47** and the suction fan **49**, the controller **8** sets a duty ratio D_{gf} of the blowing fan **47** and a duty ratio D_{gk} of the suction fan **49** for the image priority mode.

As in the case of the first embodiment, the duty ratios D_{gf} and D_{gk} take such values that the flow rate of the cooling air **W** becomes smaller than that in the production priority mode. Moreover, as in the case of the first embodiment, the values of the duty ratios D_{gf} and D_{gk} are set such that the

flow rate of the airflows F flowing into the head holder **22** through the gaps **31b** in the bottom plate **31** is smaller than that in the production priority mode and enables suction of ink droplets (ink mist) of a predetermined size or less. Furthermore, the values of the duty ratios D_{gf} and D_{gk} are set such that the flow rate of the airflows F does not bend the flight trajectory of main droplets of ink ejected from the head modules. The duty ratios D_{gf} and D_{gk} are determined in advance and stored in the controller **8**.

Here, in the image priority mode of the second embodiment, since the paper conveyance speed V_g is lower than that in the production priority mode, the amount of ink mist generated per unit time is reduced. Thus, in the image priority mode of the second embodiment, the values of the duty ratios D_{ef} and D_{gk} can be set such that a difference between the flow rate of blow air and the flow rate of suction air is reduced and the flow rate of the airflows F is reduced compared with the first embodiment.

The controller **8** advances to Step **S23** after Step **S22**. The processing in Steps **S23** to **S29** is the same as the processing in Steps **S11** to **S17** of FIG. **8** described above.

As described above, in the second embodiment, the paper conveyance speed V_g for the image priority mode is set lower than that in the production priority mode. Thus, the drive frequency of the head modules **26** is reduced in the image priority mode compared with the production mode. The amount of heat generated in the head modules **26** is therefore reduced to suppress temperature rise. As a result, damage to the ink-jet head **21** can be reduced.

Third Embodiment

Next, description is given of a third embodiment in which changes are made to the image priority mode in the first embodiment described above. Note that an ink-jet printer of the third embodiment has the same structure as that of the ink-jet printer **1** of the first embodiment. Also, operations in the production priority mode according to the second embodiment are the same as those in the first embodiment, i.e., the operations in Steps **S2** to **S9** of FIG. **7**.

FIG. **12** is a flowchart showing operations in an image priority mode in the third embodiment.

The processing in Step **S31** of FIG. **12** is the same as that in Step **S10** of FIG. **8** described above.

Following Step **S31**, the controller **8** makes ink circulation settings for the image priority mode in Step **S32**. To be more specific, as set pressures by the pressure generator **7**, the controller **8** sets a set pressure P_{kg} of a positive pressure-side pressure and a set pressure P_{fg} of a negative pressure-side pressure for the image priority mode. The controller **8** also sets a duty ratio D_{ig} of the ink pump **55** for the image priority mode, as a duty ratio for driving the ink pump **55**.

The set pressures P_{kg} and P_{fg} and the duty ratio D_{ig} are set in advance as values that set an ink circulation flow rate in the ink circulator **5** in the image priority mode to be higher than that in the production priority mode, and are stored in the controller **8**.

To be more specific, the set pressure P_{kg} of the positive pressure-side pressure for the image priority mode is larger than the set pressure P_k of the positive pressure-side pressure in the production priority mode. Meanwhile, the set pressure P_{fg} of the negative pressure-side pressure for the image priority mode has an absolute value larger than that of the set pressure P_f of the negative pressure-side pressure in the production priority mode. The duty ratio D_{ig} of the ink pump **55** for the image priority mode is larger than that of the ink pump **55** in the production priority mode.

Next, the controller **8** starts a print operation in Step **S33**. During the print operation, the controller **8** controls the pressure generator **7** such that the positive pressure-side pressure and the negative pressure-side pressure are set to the set pressures P_{kg} and P_{fg} , respectively. Moreover, the controller **8** drives the ink pump **55** at the duty ratio D_{ig} under ink level maintenance control. Thus, the ink circulator **5** circulates ink at the ink circulation flow rate larger than that in the production priority mode.

The controller **8** advances to Step **S34** after the print operation is started in Step **S33**. The processing in Steps **S34** and **S35** is the same as the processing in Steps **S5** and **S8** of FIG. **7** described above.

After determining in Step **S34** that neither of the ink-jet heads **21A** and **21B** has reached the head temperature upper limit T_u (Step **S34**: NO), the controller **8** determines in Step **S36** whether or not the printing is finished for the specified number of sheets to be printed. After determining that the printing is not finished for the specified number of sheets to be printed (Step **S36**: NO), the controller **8** returns to Step **S34**.

After determining that the printing is finished for the specified number of sheets to be printed (Step **S36**: YES), the controller **8** stops the drive roller **12**, the paper adsorption fan **17**, the blowing fan **47** and the suction fan **49**, and opens the positive pressure-side atmospheric air open valve **83** and the negative pressure-side atmospheric air open valve **90** to finish a series of operations.

As described above, in the third embodiment, the ink circulation flow rate in the ink circulator **5** in the image priority mode is set larger than that in the production priority mode. Thus, the ink flow rate in the head modules **26** per unit time is increased in the image priority mode compared with the production priority mode. Thus, heat transfer from the head modules **26** to the ink can be facilitated. Thus, even in the image priority mode having a smaller flow rate of the cooling air W than the production priority mode, an increase in temperature of the head modules **26** can be reduced without decreasing the print conveyance speed. Therefore, also in the image priority mode, damage to the ink-jet head **21** can be reduced without deteriorating the print productivity.

In the image priority mode of the third embodiment, an increase in ink circulation flow rate increases load on the air pump **95** and the ink pump **55**. However, since such an increase is only in the image priority mode, reduction in product life can be suppressed.

Fourth Embodiment

Next, description is given of a fourth embodiment in which changes are made to the image priority mode in the first embodiment described above. Note that an ink-jet printer of the fourth embodiment has the same structure as that of the ink-jet printer **1** of the first embodiment. Also, operations in a production priority mode according to the fourth embodiment are the same as those in the first embodiment, i.e., the operations in Steps **S2** to **S9** of FIG. **7**.

FIG. **13** is a flowchart showing operations in an image priority mode in the fourth embodiment.

The processing in Step **S41** of FIG. **13** is the same as that in Step **S10** of FIG. **8** described above.

Following Step **S41**, the controller **8** makes ink cooling settings for the image priority mode in Step **S42**. To be more specific, the controller **8** sets an ink cooling start temperature

21

Tkg for the image priority mode, as a temperature to start cooling of ink by the ink temperature regulator 56 during a print operation.

The ink cooling start temperature Tkg is lower than the ink cooling start temperature Tk in the production priority mode within the printable temperature range. The value of the ink cooling start temperature Tkg is determined in advance and stored in the controller 8.

Next, the controller 8 starts a print operation in Step S43. During the print operation, the controller 8 starts the ink cooling fan 74 when the ink temperature measured by the ink temperature sensor 57 reaches the ink cooling start temperature Tkg. Then, when the ink temperature is lowered by a predetermined temperature from the ink cooling start temperature Tkg, the controller 8 stops the ink cooling fan 74.

The controller 8 advances to Step S44 after the print operation is started in Step S43. The processing in Steps S44 to S46 is the same as that in Steps S34 to S36 of FIG. 12 described above.

As described above, in the fourth embodiment, the ink cooling start temperature Tkg for the image priority mode is set lower than the ink cooling start temperature Tk in the production priority mode. Thus, the temperature of the ink flowing into the head modules 26 can be suppressed low in the image priority mode compared with the production priority mode. Accordingly, heat exchange efficiency can be increased in the image priority mode by increasing a temperature difference between the head modules 26 and the ink, compared with the production priority mode. Thus, even in the image priority mode having a smaller flow rate of the cooling air W than the production priority mode, an increase in temperature of the head modules 26 can be reduced without decreasing the print conveyance speed. Therefore, also in the image priority mode, damage to the ink-jet head 21 can be reduced without deteriorating the print productivity.

Other Embodiments

As described above, the present invention has been described through the first to fourth embodiments. However, it should be understood that the present invention is not limited to the description and drawings which constitute a part of this disclosure. From this disclosure, various alternative embodiments, examples and operational techniques will become apparent to those skilled in the art.

In the first to fourth embodiments described above, the gaps 31b between the attachment openings 31a and the head modules 26 form the openings in the bottom plate 31 of the head holder 22. However, the openings may be formed at any other positions.

Moreover, in the first to fourth embodiments described above, the ink head 21 includes a number of the head modules 26. However, the ink-jet head may be a single elongated one.

Embodiments of the present invention have been described above. However the invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

22

Moreover, the effects described in the embodiments of the present invention are only a list of optimum effects achieved by the present invention. Hence, the effects of the present invention are not to those described in the embodiment of the present invention.

What is claimed is:

1. An ink-jet printer comprising:

a conveyer configured to convey a printing medium;
an ink-jet head configured to eject ink onto the printing medium conveyed by the conveyer;

a head holder in a box shape configured to hold the ink-jet head, the head holder having an opening through which a space between the head holder and the conveyer communicates with an inside of the head holder;

a head cooler including:

a blower configured to blow air into the head holder from an outside of the head holder toward the ink-jet head with a flow rate of blow air; and

a suction unit configured to suction air from the head holder with a flow rate of suction air, the head cooler being configured to generate cooling air for cooling the ink-jet head inside the head holder by the blower and the suction unit such that the cooling air generated by the head cooler flows into the head holder in a flow direction parallel to a conveying [direction] surface of the conveyer; and

a controller configured to drive the conveyer to convey the printing medium while driving the ink-jet head to eject the ink onto the printing medium to perform printing and driving the head cooler to generate the cooling air,

wherein the controller is configured to control the flow rate of blow air and the flow rate of suction air such that air containing ink mist *generated by ink ejection by the ink-jet head* is suctioned into the head holder through the opening, and

the flow direction is perpendicular to a conveying direction of the printing medium along the conveying surface.

2. The ink-jet printer according to claim 1, wherein the controller selectively uses a first mode and a second mode,

in the first mode, the controller controls the flow rate of blow air and the flow rate of suction air such that the cooling air in the head holder has an air volume required to cool the ink-jet head corresponding to a conveyance speed of the printing medium by the conveyer, and

in the second mode, the controller controls the flow rate of blow air and the flow rate of suction air such that the cooling air in the head holder has an air volume that is smaller than the air volume of the cooling air in the head holder in the first mode and airflow flowing into the head holder through the opening has an air volume that is smaller than an air volume of airflow flowing into the head holder through the opening in the first mode and capable of suctioning the ink mist.

3. The ink-jet printer according to claim 2, wherein, in the second mode, the controller drives the conveyer to reduce the conveyance speed of the printing medium upon a temperature of the ink-jet head reaching a threshold.

4. The ink-jet printer according to claim 2, further comprising an ink circulator configured to supply the ink to the ink-jet head while circulating the ink,

wherein the controller drives the ink circulator such that an ink circulation flow rate in the second mode is higher than an ink circulation flow rate in the first mode.

23

5. The ink-jet printer according to claim 2, further comprising an ink circulator configured to supply the ink to the ink-jet head while circulating the ink, wherein the ink circulator includes an ink cooler configured to cool the ink, 5
 in the first mode, the controller drives the ink cooler to start cooling of the ink upon an ink temperature of the ink being a first temperature, and
 in the second mode, the controller drives the ink cooler to start cooling of the ink upon an ink temperature of the ink being a second temperature lower than the first temperature. 10

6. The ink-jet printer according to claim 1, wherein the ink-jet head comprises a plurality of head modules each configured to eject the ink, and 15
 the head holder has a hollow interior space for housing the plurality of head modules inside the head holder.

7. The ink-jet printer according to claim 1, wherein the opening of the head holder includes openings arranged along [the] a conveying direction of the printing medium. 20

8. The ink-jet printer according to claim 1, wherein the ink-jet head comprises a head module configured to eject the ink, 25
 the conveyer comprises a conveyer belt,
 the head holder comprises a bottom plate having the opening and a lower surface facing the conveyer belt, and
 the head module has an ink ejection surface arranged in between the conveyer belt and the lower surface. 30

9. An ink-jet printer comprising:
 a conveyer configured to convey a printing medium;
 an ink-jet head configured to eject ink onto the priming medium conveyed by the conveyer;
 a head holder in a box shape configured to hold the ink-jet head, the head holder having an opening through which a space between the head holder and the conveyer communicates with an inside of the head holder; 35
 a head cooler including:
 a blower configured to blow air into the head holder from an outside of the head holder with a flow rate of blow air; and 40
 a suction unit configured to suction air from the head holder with a flow rate of suction air, the head cooler being configured to generate cooling air for cooling the ink-jet head inside the head holder by the blower and the suction unit; and 45
 a controller configured to drive the conveyer to convey the printing medium while driving the ink-jet head to eject the ink onto the printing medium to perform printing and driving the head cooler to generate the cooling air, wherein 50
 the controller is configured to control the flow rate of blow air and the flow rate of suction air such that air containing ink mist is suctioned into the head holder through the opening, 55
 the controller selectively uses a first mode and a second mode,
 in the first mode, the controller controls the flow rate of blow air and the flow rate of suction air such that the cooling air in the head holder has an air volume required to cool the ink-jet head corresponding to a conveyance speed of the printing medium by the conveyer, and 60
 in the second mode, the controller controls the flow rate of blow air and the flow rate of suction air such that the cooling air in the head holder has an air volume 65

24

that is smaller than the air volume of the cooling air in the head holder in the first mode and airflow flowing into the head holder through the opening has an air volume that is smaller than an air volume of airflow flowing into the head holder through the opening in the first mode and capable of suctioning the ink mist.

10. The ink-jet printer according to claim 1, wherein the suction unit is arranged to face the blower with the ink-jet head therebetween, and 15
 the head cooler is configured to generate the cooling air such that the cooling air flows from the blower to the suction unit.

11. The ink-jet printer according to claim 1, wherein the controller is configured to control an air volume of airflow flowing into the head holder through the opening depending on a difference between the flow rate of blow air and the flow rate of suction air. 20

12. The ink-jet printer according to claim 1, further comprises a plurality of the ink-jet heads, 25
 wherein the head holder holds the plurality of the ink-jet heads.

13. The ink-jet printer according to claim 1, wherein, during printing, the controller controls the flow rate of the blow air and the flow rate of the suction air such that the air containing the ink mist generated by the ink ejected by the ink-jet head is suctioned into the head holder through the opening. 30

14. An ink-jet printer comprising:

a conveyer configured to convey a printing medium;
 an ink-jet head configured to eject ink onto the printing medium conveyed by the conveyer;
 a head holder in a box shape configured to hold the ink-jet head, the head holder having an opening through which a space between the head holder and the conveyer communicates with an inside of the head holder; 35
 a head cooler including:

a blower mounted to the head holder and configured to blow air into the head holder from an outside of the head holder toward the ink-jet head with a flow rate of blow air; and 40

a suction unit mounted to the head holder and configured to suction air from the head holder with a flow rate of suction air, the head cooler being configured to generate cooling air for cooling the ink-jet head inside the head holder by the blower and the suction unit such that the cooling air generated by the head cooler flows into the head holder in a flow direction parallel to a conveying surface of the conveyer; and 45

a controller configured to drive the conveyer to convey the printing medium while driving the ink-jet head to eject the ink onto the printing medium to perform printing and driving the head cooler to generate the cooling air, wherein 50

the controller is configured to control the flow rate of blow air and the flow rate of suction air such that air containing ink mist generated by ink ejection by the ink-jet head is suctioned into the head holder through the opening. 55

15. The inkjet printer according to claim 1, wherein the head holder comprises:

a first sidewall with at least one first vent hole; and
 a second sidewall with at least one second vent hole, the first sidewall and the second sidewall face each other in the flow direction, 60
 the blower comprises a blowing chamber with at least one blowing hole arranged at a position corresponding to 65

the at least one first vent hole, the blower being configured to blow the air into the head holder through the at least one blowing hole and the at least one first vent hole, and

the suction unit comprises a suction chamber with at least one suction hole arranged at a position corresponding to the at least one second vent hole, the suction unit being configured to suction the air from the head holder through the at least one second vent hole and the at least one suction hole.

16. *The ink-jet printer according to claim 9, wherein the blower is configured to blow the air toward the ink-jet head,*

the suction unit is arranged to face the blower with the ink-jet head therebetween, and

the head cooler is configured to generate the cooling air such that the cooling air flows from the blower to the suction unit.

17. *The ink-jet printer according to claim 9, wherein the controller is configured to control an air volume of airflow flowing into the head holder through the opening depending on a difference between the flow rate of blow air and the flow rate of suction air.*

18. *The ink-jet printer according to claim 9, further comprises a plurality of the ink-jet heads wherein the head holder holds the plurality of the ink-jet heads.*

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE48,686 E
APPLICATION NO. : 16/293352
DATED : August 17, 2021
INVENTOR(S) : S. Otsuka et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

Item [57], (Line 3), change "Ahead" to -- A head --.

In the Claims

Column 23, Line 33 (Claim 9), change "priming" to -- printing --.

Column 25, Line 25 (Claim 18), change "heads" to -- heads, --.

Signed and Sealed this
Fifteenth Day of February, 2022



Drew Hirshfeld
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*