



US00RE48828E

(19) **United States**  
(12) **Reissued Patent**  
**Chen et al.**

(10) **Patent Number:** **US RE48,828 E**  
(45) **Date of Reissued Patent:** **Nov. 23, 2021**

(54) **COMPACT OPTICAL SYSTEM, IMAGE CAPTURING UNIT AND ELECTRONIC DEVICE**

(71) Applicant: **LARGAN Precision Co., Ltd.**,  
Taichung (TW)

(72) Inventors: **Kuan-Ming Chen**, Taichung (TW);  
**Hsin-Hsuan Huang**, Taichung (TW)

(73) Assignee: **LARGAN PRECISION CO., LTD.**,  
Taichung (TW)

(21) Appl. No.: **16/709,871**

(22) Filed: **Dec. 10, 2019**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **9,885,856**  
Issued: **Feb. 6, 2018**  
Appl. No.: **14/699,848**  
Filed: **Apr. 29, 2015**

(30) **Foreign Application Priority Data**

Jan. 9, 2015 (TW) ..... 104100808

(51) **Int. Cl.**  
**G02B 13/00** (2006.01)  
**G02B 9/12** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G02B 13/0035** (2013.01); **G02B 9/12**  
(2013.01); **G02B 13/18** (2013.01); **G02B 3/04**  
(2013.01)

(58) **Field of Classification Search**  
CPC ..... **G02B 13/0035**; **G02B 9/12**; **G02B 13/18**;  
**G02B 3/04**; **G02B 9/14**; **G02B 9/16**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,877,792 A 4/1975 Cox et al.  
3,936,154 A 2/1976 Fleischmann  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 102608730 A 7/2012  
CN 203630432 A 6/2014  
(Continued)

OTHER PUBLICATIONS


“Focal power.” (1992) In C. G. Morris (Ed.), Academic Press Dictionary of Science and Technology, 4th ed., Oxford, UK: Elsevier Science & Technology. (Year: 1992).\*  
(Continued)

*Primary Examiner* — Christina Y. Leung  
(74) *Attorney, Agent, or Firm* — Maschoff Brennan

(57) **ABSTRACT**

A compact optical system includes, in order from an object side to an image side, a first lens element, a second lens element and a third lens element. The first lens element with negative refractive power has an image-side surface being concave in a paraxial region thereof. The second lens element has refractive power, wherein at least one of two surfaces of the second lens element is aspheric, and the second lens element is made of plastic material. The third lens element has positive refractive power, wherein at least one of two surfaces of the third lens element is aspheric, and the third lens element is made of plastic material. The compact optical system further comprises a stop located between the first lens element and the second lens element. The first, second, and third lens elements are all stationary relative to one another in a paraxial region.

**63 Claims, 32 Drawing Sheets**



**US RE48,828 E**

(51) **Int. Cl.**  
**G02B 9/16** (2006.01)  
**G02B 13/18** (2006.01)  
**G02B 3/04** (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,009,928 A 3/1977 Back  
5,418,649 A 5/1995 Igarashi  
5,502,592 A 3/1996 Jamieson  
5,745,301 A \* 4/1998 Betensky ..... G02B 13/0035  
359/687  
5,828,498 A 10/1998 Sekiya et al.  
8,189,276 B1 5/2012 Hsu et al.  
8,451,547 B2 \* 5/2013 Imaoka ..... G02B 9/12  
359/716  
8,891,142 B2 \* 11/2014 Nagano ..... G02B 9/34  
358/471  
2006/0202038 A1 \* 9/2006 Wang ..... G06K 7/10732  
235/462.24  
2010/0232013 A1 \* 9/2010 Yin ..... G02B 13/0035  
359/356  
2010/0290129 A1 \* 11/2010 Nishio ..... G02B 25/001  
359/645  
2011/0043916 A1 2/2011 Wang et al.  
2013/0094099 A1 4/2013 Ko  
2013/0279026 A1 10/2013 Asami et al.  
2014/0016212 A1 \* 1/2014 Kim ..... G02B 13/04  
359/716  
2014/0293456 A1 10/2014 Komiyama  
2015/0248050 A1 \* 9/2015 Nakamura ..... G03B 17/565  
359/675  
2016/0018639 A1 \* 1/2016 Spitzer ..... G02B 5/30  
345/156

FOREIGN PATENT DOCUMENTS

EP 0905646 A1 \* 3/1999 ..... G06F 3/03547  
JP S57192915 A 11/1982  
JP S58140713 A 8/1983

JP S60-091317 A 5/1988  
JP S63-06713 A 5/1988  
JP S63-106713 A 5/1988  
JP S6091317 A 5/1988  
JP H02208617 A 8/1990  
JP H05215964 A 8/1993  
JP 1994-082690 A 3/1994  
JP 06082690 3/1994  
JP H0682690 A 3/1994  
JP H08122634 A 5/1996  
JP 1996-220430 A 8/1996  
JP H08220429 A 8/1996  
JP H08220430 A 8/1996  
JP H09197264 A 7/1997  
JP H10288736 A 10/1998  
JP H10301023 A 11/1998  
JP 1998-319315 A 12/1998  
JP H10319315 A 12/1998  
JP H11271607 A 10/1999  
JP 2006162829 A 6/2006  
JP 2007078800 A 3/2007  
JP 2007279547 A 10/2007  
JP 2007279548 A 10/2007  
JP 2008164989 7/2008  
JP 2008180887 A 8/2008  
JP 2009156950 A 7/2009  
JP 2009297401 A 12/2009  
JP 2014209190 A 11/2014  
JP 2016-031501 A 3/2016  
TW M426829 U 4/2012  
WO WO-9852076 A1 \* 11/1998 ..... G02B 13/0035  
WO 2012-066750 A1 8/2010

OTHER PUBLICATIONS

“F-number.” (1992) In C. G. Morris (Ed.), Academic Press Dictionary of Science and Technology, 4th ed., Oxford, UK: Elsevier Science & Technology. (Year: 1992).\*  
Intellectual Property Office, Ministry of Economic Affairs, R. O. C., “Office Action”, dated Oct. 13, 2015, Taiwan.

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4






FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A




FIG. 9B






FIG. 10




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13A







FIG. 13B



LONGITUDINAL  
SPHERICAL ABER.



ASTIGMATIC  
FIELD CURVES



DISTORTION




FIG. 14




FIG. 15A






FIG. 15B




FIG. 16




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19A




FIG. 19B




FIG. 20






FIG. 21




FIG. 22

1

**COMPACT OPTICAL SYSTEM, IMAGE  
CAPTURING UNIT AND ELECTRONIC  
DEVICE**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.**

RELATED APPLICATIONS

This application claims priority to Taiwan Application 104100808, filed Jan. 9, 2015, which is incorporated by reference herein in its entirety.

BACKGROUND

Technical Field

The present disclosure relates to a compact optical system, an image capturing unit and an electronic device, more particularly to a compact optical system and an image capturing unit applicable to an electronic device.

Description of Related Art

A conventional biometric system equipped in a mobile device generally utilizes a capacitive sensor. Although the capacitive sensor is favorable for miniaturizing the biometric system, complex electronic circuits in the capacitive sensor are unfavorable for reducing the manufacturing cost. Therefore, the mobile device with the capacitive biometric system requires a higher production cost which makes it difficult to gain popularity.

Other biometric systems with conventional optical system are developed, such as fingerprint recognition systems and vein recognition systems. However, the larger volume of the conventional optical system is unfavorable for miniaturizing an electronic device having the biometric system and keeping the electronic device compact, and therefore the portability of the electronic device is reduced. Thus, there is a need for a compact optical system of low costs and good manufacturing yield rate, which can be favorably applied to biometric applications.

SUMMARY

According to one aspect of the present disclosure, a compact optical system includes, in order from an object side to an image side, a first lens element, a second lens element and a third lens element. The first lens element with negative refractive power has an image-side surface being concave in a paraxial region thereof. The second lens element has refractive power, wherein at least one of an object-side surface and an image-side surface of the second lens element is aspheric, and the second lens element is made of plastic material. The third lens element has positive refractive power, wherein at least one of an object-side surface and an image-side surface of the third lens element is aspheric, and the third lens element is made of plastic material. The compact optical system has a total of three lens elements with refractive power. The compact optical system further comprises a stop located between the first lens element and the second lens element. The first lens element, the second lens element and the third lens element are all stationary relative to one another in a paraxial region thereof. When a focal length of the compact optical system

2

is  $f$ , a maximum image height of the compact optical system is  $\text{ImgH}$ , a refractive index of the first lens element is  $N1$ , a refractive index of the second lens element is  $N2$ , a refractive index of the third lens element is  $N3$ , an axial distance between the stop and the object-side surface of the second lens element is  $Dsr3$ , an axial distance between the stop and the object-side surface of the third lens element is  $Dsr5$ , the following conditions are satisfied:

$$f/\text{ImgH} < 0.55;$$

$$4.70 < N1 + N2 + N3 < 5.50; \text{ and}$$

$$0 < |Dsr3/Dsr5| < 0.50.$$

According to another aspect of the present disclosure, an image capturing unit includes an image sensor and the aforementioned compact optical system, wherein the image sensor is disposed on the image side of the compact optical system.

According to still another aspect of the present disclosure, an electronic device includes a biometric system, and the biometric system includes the aforementioned image capturing unit.

According to yet another aspect of the present disclosure, a compact optical system includes, in order from an object side to an image side, a first lens element, a second lens element and a third lens element. The first lens element with negative refractive power has an image-side surface being concave in a paraxial region thereof. The second lens element has refractive power, wherein at least one of an object-side surface and an image-side surface of the second lens element is aspheric, and the second lens element is made of plastic material. The third lens element has positive refractive power, wherein at least one of an object-side surface and an image-side surface of the third lens element is aspheric, and the third lens element is made of plastic material. The compact optical system has a total of three lens elements with refractive power. The compact optical system further comprises a stop located between the first lens element and the second lens element. The first lens element, the second lens element and the third lens element are all stationary relative to one another in a paraxial region thereof. When a focal length of the compact optical system is  $f$ , a maximum image height of the compact optical system is  $\text{ImgH}$ , a refractive index of the first lens element is  $N1$ , a refractive index of the second lens element is  $N2$ , a refractive index of the third lens element is  $N3$ , an axial distance between the stop and the object-side surface of the second lens element is  $Dsr3$ , an axial distance between the stop and the object-side surface of the third lens element is  $Dsr5$ , an axial distance between an imaged object and an image surface is  $\text{OTL}$ , a sum of central thicknesses of the first lens element, the second lens element and the third lens element is  $\Sigma/CT$ , the following conditions are satisfied:

$$f/\text{ImgH} < 0.70;$$

$$4.70 < N1 + N2 + N3 < 5.50;$$

$$0 < |Dsr3/Dsr5| < 0.50; \text{ and}$$

$$\text{OTL}/\Sigma CT < 4.0.$$

According to yet still another aspect of the present disclosure, an image capturing unit includes a light source, an image sensor and the aforementioned compact optical sys-

tem, wherein the image sensor is disposed on the image side of the compact optical system.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure can be more fully understood by reading the following detailed description of the embodiments, with reference made to the accompanying drawings as follows:

FIG. 1A is a schematic view of an image capturing unit according to the 1st embodiment of the present disclosure;

FIG. 1B is a partially enlarged schematic view of the image capturing unit in FIG. 1A;

FIG. 2 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 1st embodiment;

FIG. 3A is a schematic view of an image capturing unit according to the 2nd embodiment of the present disclosure;

FIG. 3B is a partially enlarged schematic view of the image capturing unit in FIG. 3A;

FIG. 4 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 2nd embodiment;

FIG. 5A is a schematic view of an image capturing unit according to the 3rd embodiment of the present disclosure;

FIG. 5B is a partially enlarged schematic view of the image capturing unit in FIG. 5A;

FIG. 6 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 3rd embodiment;

FIG. 7A is a schematic view of an image capturing unit according to the 4th embodiment of the present disclosure;

FIG. 7B is a partially enlarged schematic view of the image capturing unit in FIG. 7A;

FIG. 8 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 4th embodiment;

FIG. 9A is a schematic view of an image capturing unit according to the 5th embodiment of the present disclosure;

FIG. 9B is a partially enlarged schematic view of the image capturing unit in FIG. 9A;

FIG. 10 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 5th embodiment;

FIG. 11A is a schematic view of an image capturing unit according to the 6th embodiment of the present disclosure;

FIG. 11B is a partially enlarged schematic view of the image capturing unit in FIG. 11A;

FIG. 12 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 6th embodiment;

FIG. 13A is a schematic view of an image capturing unit according to the 7th embodiment of the present disclosure;

FIG. 13B is a partially enlarged schematic view of the image capturing unit in FIG. 13A;

FIG. 14 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 7th embodiment;

FIG. 15A is a schematic view of an image capturing unit according to the 8th embodiment of the present disclosure;

FIG. 15B is a partially enlarged schematic view of the image capturing unit in FIG. 15A;

FIG. 16 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 8th embodiment;

FIG. 17A is a schematic view of an image capturing unit according to the 9th embodiment of the present disclosure;

FIG. 17B is a partially enlarged schematic view of the image capturing unit in FIG. 17A;

FIG. 18 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 9th embodiment;

FIG. 19A is a schematic view of an image capturing unit according to the 10th embodiment of the present disclosure;

FIG. 19B is a partially enlarged schematic view of the image capturing unit in FIG. 19A;

FIG. 20 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 10th embodiment;

FIG. 21 is a schematic view of OL, TL and OTL in FIG. 1; and

FIG. 22 shows an electronic device according to an embodiment.

#### DETAILED DESCRIPTION

A compact optical system includes, in order from an object side to an image side, a first lens element, a second lens element and a third lens element. The compact optical system has a total of three lens elements with refractive power. The first lens element, the second lens element and the third lens element can all be stationary relative to one another in a paraxial region thereof. For example, in some embodiments, an air gap in a paraxial region is located between every two of the first lens element, the second lens element and the third lens element that are adjacent to each other, and the air gaps are all constant.

The first lens element with negative refractive power has an image-side surface being concave in a paraxial region thereof. Therefore, it is favorable for enlarging the field of view of the compact optical system so as to provide a wider field of view for the same.

The second lens element can have positive refractive power. The second lens element can have an image-side surface being convex in a paraxial region thereof. Therefore, the second lens element is favorable for correcting the aberration from the first lens element and the spherical aberration of the compact optical system so as to improve the image quality.

The third lens element has positive refractive power. The third lens element can have an image-side surface being convex in a paraxial region thereof. At least one of an object-side surface and the image-side surface of the third lens element can have at least one inflection point. Therefore, it is favorable for providing the compact optical system with retrofocus (reversed telephoto) performance so as to reduce the chief ray angle of the compact optical system, thereby providing the compact optical system with enhanced telecentric performance.

When a focal length of the compact optical system is  $f$ , a maximum image height of the compact optical system (half of a diagonal length of an effective photosensitive area of an image sensor) is  $ImgH$ , the following condition is satisfied:  $f/ImgH < 0.70$ . Therefore, it is favorable for collecting the light with large incident angle so as to allow the compact optical system to capture a wide field of view and recognize an imaged object while the distance between the imaged object and the compact optical system is extremely close. Preferably, the following condition is satisfied:  $f/ImgH < 0.55$ . More preferably, the following condition is satisfied:  $f/ImgH < 0.45$ .

When a refractive index of the first lens element is  $N1$ , a refractive index of the second lens element is  $N2$ , a refractive index of the third lens element is  $N3$ , the following

## 5

condition is satisfied:  $4.70 < N1 + N2 + N3 < 5.50$ . Therefore, it is favorable for reducing a required distance for image capturing between the imaged object and the compact optical system so as to keep the compact optical system compact.

According to the present disclosure, the compact optical system further comprises a stop located between the first lens element and the second lens element. When an axial distance between the stop and an object-side surface of the second lens element is  $Dsr3$ , an axial distance between the stop and the object-side surface of the third lens element is  $Dsr5$ , the following condition is satisfied:  $0 < |Dsr3/Dsr5| < 0.50$ . Therefore, it is favorable for properly allocating the stop so as to enlarge the field of view of the compact optical system, thereby providing a wider field of view for the same.

When an axial distance between the imaged object and an image surface is  $OTL$ , a sum of central thicknesses of the first lens element, the second lens element and the third lens element is  $\Sigma CT$  (That is, a sum of a central thickness of the first lens element, a central thickness of the second lens element and a central thickness of the third lens element), the following condition is satisfied:  $OTL/\Sigma CT < 4.0$ . Therefore, it is favorable for further keeping the compact optical system compact. As seen in FIG. 21, it shows a schematic view of  $OTL$  in FIG. 1.

When a curvature radius of the object-side surface of the third lens element is  $R5$ , a curvature radius of the image-side surface of the third lens element is  $R6$ , the following condition can be satisfied:  $(R5 + R6)/(R5 - R6) < 0.90$ . Therefore, it is favorable for avoiding excessive astigmatism and spherical aberration of the compact optical system so as to improve the image quality. Preferably, the following condition can be satisfied:  $-0.50 < (R5 + R6)/(R5 - R6) < 0.50$ .

When the axial distance between the imaged object and the image surface is  $OTL$ , the following condition can be satisfied:  $OTL < 8.0$  millimeters (mm). Therefore, it is favorable for keeping the compact optical system compact so as to be equipped in a compact electronic device having a biometric system. Preferably, the following condition can be satisfied:  $OTL < 5.0$  mm.

When an Abbe number of the first lens element is  $V1$ , an Abbe number of the second lens element is  $V2$ , an Abbe number of the third lens element is  $V3$ , the following condition can be satisfied:  $V1 + V2 + V3 < 80$ . Therefore, it is favorable for correcting the chromatic aberration of the compact optical system.

When the focal length of the compact optical system is  $f$ , an entrance pupil diameter of the compact optical system is  $EPD$ , the following condition can be satisfied:  $f/EPD < 2.60$ . Therefore, it is favorable for obtaining a large aperture for receiving sufficient incoming light, thereby increasing the image quality in a low light condition.

When the focal length of the compact optical system is  $f$ , a focal length of the first lens element is  $f1$ , a focal length of the second lens element is  $f2$ , a focal length of the third lens element is  $f3$ , the following condition can be satisfied:  $0.5 < |f/f1| + |f/f2| + |f/f3| < 1.1$ . Therefore, it is favorable for balancing the arrangement of the compact optical system so as to effectively correct the aberration of the compact optical system and reducing the sensitivity of the compact optical system.

When the axial distance between the imaged object and the image surface is  $OTL$ , the maximum image height of the compact optical system is  $ImgH$ , the following condition can be satisfied:  $OTL/ImgH < 12$ . Therefore, it is favorable

## 6

for keeping the compact optical system compact so as to be equipped in an electronic device.

When a maximal field of view of the compact optical system is  $FOV$ , the following condition can be satisfied:  $140.0 \text{ degrees (deg.)} < FOV < 180.0 \text{ deg}$ . Therefore, it is favorable for providing a sufficient field of view so as to obtain more of the image scene and properly reducing the image distortion simultaneously.

According to the present disclosure, the compact optical system further comprises a flat panel located between the imaged object and an object-side surface of the first lens element. The flat panel is, for example, a glass cover or a plastic cover. When a central thickness of the flat panel is  $CTf$ , a central thickness of the first lens element is  $CT1$ , the following condition can be satisfied:  $0.95 < CTf/CT1 < 5.5$ . Therefore, the thicknesses of the flat panel and the first lens element are properly distributed so that it is favorable for reducing manufacturing cost and keeping in a compact size thereof.

When an axial distance between the first lens element and the second lens element is  $T12$ , the central thickness of the first lens element is  $CT1$ , the following condition can be satisfied:  $1.50 < T12/CT1 < 10$ . Therefore, it is favorable for assembling the compact optical system so as to increase the manufacturing yield rate.

When an axial distance between the imaged object and the object-side surface of the first lens element is  $OL$ , an axial distance between the object-side surface of the first lens element and the image surface is  $TL$ , the following condition can be satisfied:  $0 < OL/TL < 1.0$ . Therefore, it is favorable for reducing the required distance for image capturing between the imaged object and the compact optical system so as to keep the compact optical system compact. As seen in FIG. 21, it shows a schematic view of  $OL$  and  $TL$  in FIG. 1.

When an axial distance between the object-side surface of the first lens element and the image-side surface of the third lens element is  $TD$ , the focal length of the compact optical system is  $f$ , the following condition can be satisfied:  $8 < TD/f < 30$ . Therefore, it is favorable for tightly arranging the lens elements so as to reduce a total track length of the compact optical system.

According to the compact optical system of the present disclosure, an aperture stop can be configured as a middle stop. A middle stop disposed between the first lens element and the image surface is favorable for enlarging the field of view of the compact optical system and thereby provides a wider field of view for the same.

According to the compact optical system of the present disclosure, the lens elements thereof can be made of glass or plastic material. When the lens elements are made of glass material, the distribution of the refractive power of the compact optical system may be more flexible to design. When the lens elements are made of plastic material, the manufacturing cost can be effectively reduced. Furthermore, surfaces of each lens element can be arranged to be aspheric or spherical. The aspheric surface of the lens element is easy to form a shape other than spherical surface so as to have more controllable variables for eliminating the aberration thereof, and to further decrease the required number of the lens elements. Therefore, the total track length of the compact optical system can also be reduced.

According to the compact optical system of the present disclosure, each of an object-side surface and an image-side surface has a paraxial region and an off-axis region. The paraxial region refers to the region of the surface where light rays travel close to the optical axis, and the off-axis region refers to the region of the surface away from the paraxial

region. Particularly, when the lens element has a convex surface, it indicates that the surface is convex in the paraxial region thereof; when the lens element has a concave surface, it indicates that the surface is concave in the paraxial region thereof. Moreover, when a region of refractive power or focus of a lens element is not defined, it indicates that the region of refractive power or focus of the lens element is in the paraxial region thereof.

According to the compact optical system of the present disclosure, an image surface of the compact optical system, based on the corresponding image sensor, can be flat or curved, especially a curved surface being concave facing towards the object side of the compact optical system.

According to the compact optical system of the present disclosure, the compact optical system can include at least one stop, such as an aperture stop, a glare stop or a field stop. Said glare stop or said field stop is set for eliminating the stray light and thereby improving the image quality thereof.

According to the present disclosure, an image capturing unit is provided. The image capturing unit includes the compact optical system according to the aforementioned compact optical system of the present disclosure, and an image sensor, wherein the image sensor is disposed on the image side of the aforementioned compact optical system, that is, the image sensor can be disposed on or near an image surface of the aforementioned compact optical system. In some embodiments, the image capturing unit can further include a barrel member, a holding member or a combination thereof.

In FIG. 22, an image capturing device 10 may be installed in, but not limited to, an electronic device including a biometric system, such as a fingerprint recognition device (FIG. 22) and a vein recognition device. The image capturing device 10 can comprise a light source S located at one side of the compact optical system. The figure of the electronic device are only exemplary for showing the image capturing device of present disclosure installing in an electronic device and is not limited thereto. In some embodiments, the electronic device can further include, but not limited to, a display unit, a control unit, a storage unit, a random access memory unit (RAM), a read only memory unit (ROM) or a combination thereof.

According to the compact optical system of the present disclosure, the compact optical system is featured with good capability in the correction of aberration and high image quality, and can be applied to 3D (three-dimensional) image capturing applications, in products such as digital cameras, mobile devices, digital tablets, wearable devices, smart televisions and other electronic imaging devices. Furthermore, the compact optical system is favorable for being operated within a wavelength range of blue light spectrum, red light spectrum or visible light spectrum. When the compact optical system is operated within the wavelength range of blue light spectrum (400 nm~500 nm), it is favorable for miniaturizing the compact optical system. When the compact optical system is operated within the wavelength range of red light spectrum (620 nm~750 nm), it is favorable for reducing the interference with the human eyes so as to enhance the degree of comfort. According to the above description of the present disclosure, the following specific embodiments are provided for further explanation.

#### 1st Embodiment

FIG. 1A is a schematic view of an image capturing unit according to the 1st embodiment of the present disclosure. FIG. 1B is a partially enlarged schematic view of the image

capturing unit in FIG. 1A. FIG. 2 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 1st embodiment. In FIG. 1A and FIG. 1B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor 160. The compact optical system includes, in order from an object side to an image side, a flat panel 140, a first lens element 110, an aperture stop 100, a second lens element 120, a third lens element 130 and an image surface 150, wherein the compact optical system has a total of three lens elements (110-130) with refractive power. The first lens element 110, the second lens element 120 and the third lens element 130 are all stationary relative to one another in a paraxial region thereof.

The first lens element 110 with negative refractive power has an object-side surface 111 being convex in a paraxial region thereof and an image-side surface 112 being concave in a paraxial region thereof. The first lens element 110 is made of plastic material, and has the object-side surface 111 and the image-side surface 112 being both aspheric.

The second lens element 120 with positive refractive power has an object-side surface 121 being convex in a paraxial region thereof and an image-side surface 122 being convex in a paraxial region thereof. The second lens element 120 is made of plastic material, and has the object-side surface 121 and the image-side surface 122 being both aspheric.

The third lens element 130 with positive refractive power has an object-side surface 131 being convex in a paraxial region thereof and an image-side surface 132 being convex in a paraxial region thereof. The third lens element 130 is made of plastic material, and has the object-side surface 131 and the image-side surface 132 being both aspheric. The object-side surface 131 and the image-side surface 132 of the third lens element 130 have at least one inflection point.

The flat panel 140 is made of glass and located between an imaged object O and the first lens element 110, and will not affect the focal length of the compact optical system. The image sensor 160 is disposed on or near the image surface 150 of the compact optical system.

The equation of the aspheric surface profiles of the aforementioned lens elements of the 1st embodiment is expressed as follows:

$$X(Y) = (Y^2/R)/(1 + \sqrt{1 - (1+k) \times (Y/R)^2}) + \sum_i (A_i) \times (Y^i),$$

where,

X is the relative distance between a point on the aspheric surface spaced at a distance Y from an optical axis and the tangential plane at the aspheric surface vertex on the optical axis;

Y is the vertical distance from the point on the aspheric surface to the optical axis;

R is the curvature radius;

k is the conic coefficient; and

A<sub>i</sub> is the i-th aspheric coefficient, and in the embodiments, i may be, but is not limited to, 4, 6, 8, 10, 12, 14 and 16.

In the compact optical system of the image capturing unit according to the 1st embodiment, when a focal length of the compact optical system is f, an f-number of the compact optical system is F<sub>no</sub>, and half of a maximal field of view of the compact optical system is HFOV, these parameters have the following values: f=0.14 millimeters (mm); F<sub>no</sub>=2.20;

and HFOV=84.5 degrees (deg.). The value of the aforementioned f-number (Fno) is obtained when the compact optical system is focused on infinity.

When the f-number of the compact optical system is Fno, the following condition is satisfied: FOV=169.0 degrees. 5

When an Abbe number of the first lens element **110** is V1, an Abbe number of the second lens element **120** is V2, an Abbe number of the third lens element **130** is V3, the following condition is satisfied: V1+V2+V3=64.5.

When a refractive index of the first lens element **110** is N1, a refractive index of the second lens element **120** is N2, a refractive index of the third lens element **130** is N3, the following condition is satisfied: N1+N2+N3=5.022. 10

When an axial distance between the first lens element **110** and the second lens element **120** is T12, a central thickness of the first lens element **110** is CT1, the following condition is satisfied: T12/CT1=1.84. 15

When a central thickness of the flat panel **140** is CTf, the central thickness of the first lens element **110** is CT1, the following condition is satisfied: CTf/CT1=1.25. 20

When a curvature radius of the object-side surface **131** of the third lens element **130** is R5, a curvature radius of the image-side surface **132** of the third lens element **130** is R6, the following condition is satisfied: (R5+R6)/(R5-R6)=0.21.

When the axial distance between the imaged object O and the image surface **150** is OTL, a sum of central thicknesses of the first lens element **110**, the second lens element **120** and the third lens element **130** is  $\Sigma$ CT, the following condition is satisfied: OTL/ $\Sigma$ CT=2.22.

When the axial distance between the imaged object O and the image surface **150** is OTL, the maximum image height of the compact optical system is ImgH, the following condition is satisfied: OTL/ImgH=8.34.

When an axial distance between the object-side surface **111** of the first lens element **110** and the image-side surface **132** of the third lens element **130** is TD, the focal length of the compact optical system is f, the following condition is satisfied: TD/f=22.91.

When an axial distance between the stop **100** and the object-side surface **121** of the second lens element **120** is Dsr3, an axial distance between the stop **100** and the object-side surface **131** of the third lens element **130** is Dsr5, the following condition is satisfied: |Dsr3/Dsr5|=0.04.

The detailed optical data of the 1st embodiment are shown in Table 1 and the aspheric surface data are shown in Table 2 below.

TABLE 1

1st Embodiment							
f = 0.14 mm, Fno = 2.20, HFOV = 84.5 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.737	Glass	1.523	64.2	—
2		Plano	0.143				
3	Lens 1	42.472 (ASP)	0.589	Plastic	1.674	21.5	-0.50
4		0.331 (ASP)	1.039				
5	Ape. Stop	Plano	0.046				
6	Lens 2	0.703 (ASP)	0.907	Plastic	1.674	21.5	0.97
7		-4.342 (ASP)	0.201				
8	Lens 3	0.487 (ASP)	0.411	Plastic	1.674	21.5	0.36
9		-0.315 (ASP)	0.164				
10	Image	Plano	—				

Note:  
Reference wavelength is 480 nm.

When the focal length of the compact optical system is f, a focal length of the first lens element **110** is f1, a focal length of the second lens element **120** is f2, a focal length of the third lens element **130** is f3, the following condition is satisfied: |f/f1|+|f/f2|+|f/f3|=0.81.

When the focal length of the compact optical system is f, a maximum image height of the compact optical system is ImgH, the following condition is satisfied: f/ImgH=0.27.

When the focal length of the compact optical system is f, an entrance pupil diameter of the compact optical system is EPD, the following condition is satisfied: f/EPD=2.20, wherein the value of the aforementioned entrance pupil diameter (EPD) is obtained when the compact optical system is focused on infinity.

When an axial distance between the imaged object O and the object-side surface **111** of the first lens element **110** is OL, an axial distance between the object-side surface **111** of the first lens element **110** and the image surface **150** is TL, the following condition is satisfied: OL/TL=0.26.

When an axial distance between the imaged object O and the image surface **150** is OTL, the following condition is satisfied: OTL=4.24 mm.

TABLE 2

Aspheric Coefficients			
Surface #	3	4	6
k =	-9.9987E-01	-5.1522E-01	8.1551E-01
A4 =	2.5345E-02	7.5635E+00	7.8826E-32
A6 =	4.3784E-02	-2.1253E+01	2.6020E-63
A8 =	-4.8657E-02	1.3223E+02	—
A10 =	2.2663E-02	-7.0557E+02	—
A12 =	-5.2380E-03	6.0711E+03	—
A14 =	4.8729E-04	-3.2973E+04	—
A16 =	-1.3106E-07	6.4174E+04	—
Surface #	7	8	9
k =	-1.1768E+01	-9.6555E+00	-1.4512E+00
A4 =	-1.6706E+01	-9.8058E+00	4.8582E+00
A6 =	2.8312E+02	1.4240E+02	3.9655E+00
A8 =	-2.5732E+03	-8.3240E+02	-3.7622E+01
A10 =	1.1960E+04	2.1542E+03	—
A12 =	-2.0337E+04	-2.5845E+03	—
A14 =	—	1.1841E+03	—

## 11

In Table 1, the curvature radius, the thickness and the focal length are shown in millimeters (mm). Surface numbers 0-10 represent the surfaces sequentially arranged from the object-side to the image-side along the optical axis. In Table 2, k represents the conic coefficient of the equation of the aspheric surface profiles. A4-16 represent the aspheric coefficients ranging from the 4th order to the 16th order. The tables presented below for each embodiment are the corresponding schematic parameter and aberration curves, and the definitions of the tables are the same as Table 1 and Table 2 of the 1st embodiment. Therefore, an explanation in this regard will not be provided again.

## 2nd Embodiment

FIG. 3A is a schematic view of an image capturing unit according to the 2nd embodiment of the present disclosure. FIG. 3B is a partially enlarged schematic view of the image capturing unit in FIG. 3A. FIG. 4 shows spherical aberration

## 12

The third lens element **230** with positive refractive power has an object-side surface **231** being convex in a paraxial region thereof and an image-side surface **232** being convex in a paraxial region thereof. The third lens element **230** is made of plastic material, and has the object-side surface **231** and the image-side surface **232** being both aspheric. The object-side surface **231** and the image-side surface **232** of the third lens element **230** have at least one inflection point.

The flat panel **240** is made of glass and located between an imaged object O and the first lens element **210**, and will not affect the focal length of the compact optical system. The image sensor **260** is disposed on or near the image surface **250** of the compact optical system.

The detailed optical data of the 2nd embodiment are shown in Table 3 and the aspheric surface data are shown in Table 4 below.

TABLE 3

2nd Embodiment							
f = 0.10 mm, Fno = 2.10, HFOV = 82.4 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.550	Glass	1.523	64.2	—
2		Plano	0.050				
3	Lens 1	31.696 (ASP)	0.475	Plastic	1.661	23.3	-0.37
4		0.244 (ASP)	0.775				
5	Ape. Stop	Plano	0.010				
6	Lens 2	0.644 (ASP)	0.590	Plastic	1.661	23.3	0.60
7		-0.666 (ASP)	0.081				
8	Lens 3	0.485 (ASP)	0.324	Plastic	1.674	21.5	0.32
9		-0.289 (ASP)	0.133				
10	Image	Plano	—				

Note:  
Reference wavelength is 480 nm.

curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 2nd embodiment. In FIG. 3A and FIG. 3B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor **260**. The compact optical system includes, in order from an object side to an image side, a flat panel **240**, a first lens element **210**, an aperture stop **200**, a second lens element **220**, a third lens element **230** and an image surface **250**, wherein the compact optical system has a total of three lens elements (**210-230**) with refractive power. The first lens element **210**, the second lens element **220** and the third lens element **230** are all stationary relative to one another in a paraxial region thereof.

The first lens element **210** with negative refractive power has an object-side surface **211** being convex in a paraxial region thereof and an image-side surface **212** being concave in a paraxial region thereof. The first lens element **210** is made of plastic material, and has the object-side surface **211** and the image-side surface **212** being both aspheric.

The second lens element **220** with positive refractive power has an object-side surface **221** being convex in a paraxial region thereof and an image-side surface **222** being convex in a paraxial region thereof. The second lens element **220** is made of plastic material, and has the object-side surface **221** and the image-side surface **222** being both aspheric.

TABLE 4

Aspheric Coefficients			
Surface #	3	4	6
k =	-9.9987E-01	-5.1522E-01	3.7355E-01
A4 =	2.1227E-01	1.8634E+01	1.8966E-31
A6 =	-1.5024E-01	-9.5138E+01	1.1212E-62
A8 =	6.9193E-02	1.0756E+03	—
A10 =	-1.0759E-02	-1.0428E+04	—
A12 =	-3.8825E-03	1.6303E+05	—
A14 =	1.7994E-03	-1.6088E+06	—
A16 =	-2.0157E-04	5.6892E+06	—
Surface #	7	8	9
k =	-4.7025E-01	-5.4711E+01	-7.1549E-01
A4 =	-2.2916E+01	-3.1050E+00	1.2747E+01
A6 =	4.8764E+02	4.4635E+01	-3.4918E+01
A8 =	-4.9292E+03	2.7280E+02	5.2167E+01
A10 =	2.6991E+04	-7.8370E+03	—
A12 =	-5.8653E+04	4.8880E+04	—
A14 =	—	-1.0511E+05	—

In the 2nd embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 2nd embodiment, so an explanation in this regard will not be provided again.



## 13

Moreover, these parameters can be calculated from Table 3 and Table 4 as the following values and satisfy the following conditions:

2nd Embodiment			
f [mm]	0.10	$ f/f1  +  f/f2  +  f/f3 $	0.74
Fno	2.10	f/ImgH	0.19
HFOV [deg.]	82.4	fEPD	2.10
FOV [deg.]	164.8	OL/TL	0.25
V1 + V2 + V3	68.1	OTL [mm]	2.99
N1 + N2 + N3	4.997	OTL/ $\Sigma$ CT	2.15
T12/CT1	1.65	OTL/ImgH	5.81
CTf/CT1	1.16	TD/f	22.61
$(R5 + R6)/(R5 - R6)$	0.25	$ Dsr3/Dsr5 $	0.01

## 3rd Embodiment

FIG. 5A is a schematic view of an image capturing unit according to the 3rd embodiment of the present disclosure.

## 14

**320** is made of plastic material, and has the object-side surface **321** and the image-side surface **322** being both aspheric.

The third lens element **330** with positive refractive power has an object-side surface **331** being convex in a paraxial region thereof and an image-side surface **332** being convex in a paraxial region thereof. The third lens element **330** is made of plastic material, and has the object-side surface **331** and the image-side surface **332** being both aspheric. The object-side surface **331** and the image-side surface **332** of the third lens element **330** have at least one inflection point.

The flat panel **340** is made of glass and located between an imaged object **O** and the first lens element **310**, and will not affect the focal length of the compact optical system. The image sensor **360** is disposed on or near the image surface **350** of the compact optical system.

The detailed optical data of the 3rd embodiment are shown in Table 5 and the aspheric surface data are shown in Table 6 below.

TABLE 5

3rd Embodiment							
f = 0.14 mm, Fno = 2.00, HFOV = 74.3 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				—
1	Flat Panel	Plano	0.737	Glass	1.523	64.2	—
2		Plano	0.505				
3	Lens 1	42.472 (ASP)	0.200	Plastic	1.674	21.5	-0.47
4		0.311 (ASP)	1.039				
5	Ape. Stop	Plano	0.135				
6	Lens 2	1.397 (ASP)	0.508	Plastic	1.661	23.3	0.96
7		-0.992 (ASP)	0.072				
8	Lens 3	0.629 (ASP)	0.709	Plastic	1.674	21.5	0.60
9		-0.625 (ASP)	0.174				
10	Image	Plano	—				

Note:  
Reference wavelength is 480 nm.

40

FIG. 5B is a partially enlarged schematic view of the image capturing unit in FIG. 5A. FIG. 6 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 3rd embodiment. In FIG. 5A and FIG. 5B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor **360**. The compact optical system includes, in order from an object side to an image side, a flat panel **340**, a first lens element **310**, an aperture stop **300**, a second lens element **320**, a third lens element **330** and an image surface **350**, wherein the compact optical system has a total of three lens elements (**310-330**) with refractive power. The first lens element **310**, the second lens element **320** and the third lens element **330** are all stationary relative to one another in a paraxial region thereof.

The first lens element **310** with negative refractive power has an object-side surface **311** being convex in a paraxial region thereof and an image-side surface **312** being concave in a paraxial region thereof. The first lens element **310** is made of plastic material, and has the object-side surface **311** and the image-side surface **312** being both aspheric.

The second lens element **320** with positive refractive power has an object-side surface **321** being convex in a paraxial region thereof and an image-side surface **322** being convex in a paraxial region thereof. The second lens element

65

TABLE 6

Aspheric Coefficients			
Surface #	3	4	6
k =	-9.9987E-01	-5.1522E-01	-9.0865E+00
A4 =	1.6180E+00	8.0055E+00	7.8826E-32
A6 =	-2.7423E+00	-2.3142E+01	1.0758E-59
A8 =	2.5003E+00	1.4814E+02	—
A10 =	-9.2504E-01	-8.1321E+02	—
A12 =	-2.2419E-01	7.1988E+03	—
A14 =	3.0513E-01	-4.0224E+04	—
A16 =	-7.2247E-02	8.0542E+04	—
Surface #	7	8	9
k =	-5.6437E-01	-4.0679E+00	-3.2004E-01
A4 =	-1.5072E+00	-3.3687E-01	2.2964E+00
A6 =	2.7810E+00	1.0720E+00	-5.8735E+00
A8 =	4.8165E+00	-8.6659E+00	8.0988E+00
A10 =	-3.1535E+01	-4.4549E+00	—
A12 =	4.3669E+01	6.7302E+01	—
A14 =	—	-7.0683E+01	—

In the 3rd embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with

## 15

corresponding values for the 3rd embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 5 and Table 6 as the following values and satisfy the following conditions:

3rd Embodiment			
f [mm]	0.14	$ f/f1  +  f/f2  +  f/f3 $	0.70
Fno	2.00	$f/\text{ImgH}$	0.26
HFOV [deg.]	74.3	$f/\text{EPD}$	2.00
FOV [deg.]	148.6	OL/TL	0.44
V1 + V2 + V3	66.3	OTL [mm]	4.08
N1 + N2 + N3	5.010	OTL/ $\Sigma$ CT	2.88
T12/CT1	5.87	OTL/ImgH	7.45
CTf/CT1	3.69	TD/f	18.43
$(R5 + R6)/(R5 - R6)$	0.003	$ Dsr3/Dsr5 $	0.19

## 4th Embodiment

FIG. 7A is a schematic view of an image capturing unit according to the 4th embodiment of the present disclosure. FIG. 7B is a partially enlarged schematic view of the image

## 16

paraxial region thereof and an image-side surface **422** being convex in a paraxial region thereof. The second lens element **420** is made of plastic material, and has the object-side surface **421** and the image-side surface **422** being both aspheric.

The third lens element **430** with positive refractive power has an object-side surface **431** being convex in a paraxial region thereof and an image-side surface **432** being convex in a paraxial region thereof. The third lens element **430** is made of plastic material, and has the object-side surface **431** and the image-side surface **432** being both aspheric. The object-side surface **431** and the image-side surface **432** of the third lens element **430** have at least one inflection point.

The flat panel **440** is made of glass and located between an imaged object O and the first lens element **410**, and will not affect the focal length of the compact optical system. The image sensor **460** is disposed on or near the image surface **450** of the compact optical system.

The detailed optical data of the 4th embodiment are shown in Table 7 and the aspheric surface data are shown in Table 8 below.

TABLE 7

4th Embodiment							
$f = 0.11 \text{ mm}, Fno = 2.00, HFOV = 75.5 \text{ deg.}$							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.550	Glass	1.523	64.2	—
2		Plano	0.361				
3	Lens 1	31.696 (ASP)	0.200	plastic	1.674	21.5	-0.34
4		0.230 (ASP)	0.775				
5	Ape. Stop	Plano	0.047				
6	Lens 2	1.182 (ASP)	0.316	Plastic	1.661	23.3	0.59
7		-0.523 (ASP)	0.098				
8	Lens 3	0.701 (ASP)	0.431	Plastic	1.674	21.5	0.47
9		-0.434 (ASP)	0.173				
10	Image	Plano	—				

Note:  
Reference wavelength is 480 nm.

capturing unit in FIG. 7A. FIG. 8 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 4th embodiment. In FIG. 7A and FIG. 7B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor **460**. The compact optical system includes, in order from an object side to an image side, a flat panel **440**, a first lens element **410**, an aperture stop **400**, a second lens element **420**, a third lens element **430** and an image surface **450**, wherein the compact optical system has a total of three lens elements (**410-430**) with refractive power. The first lens element **410**, the second lens element **420** and the third lens element **430** are all stationary relative to one another in a paraxial region thereof.

The first lens element **410** with negative refractive power has an object-side surface **411** being convex in a paraxial region thereof and an image-side surface **412** being concave in a paraxial region thereof. The first lens element **410** is made of plastic material, and has the object-side surface **411** and the image-side surface **412** being both aspheric.

The second lens element **420** with positive refractive power has an object-side surface **421** being convex in a

TABLE 8

Aspheric Coefficients			
	Surface #		
	3	4	6
k =	-9.9987E-01	-5.1522E-01	-7.6822E+00
A4 =	3.0712E+00	1.9262E+01	1.8966E-31
A6 =	-7.8509E+00	-9.9985E+01	4.3187E-59
A8 =	1.0861E+01	1.1492E+03	—
A10 =	-4.7991E+00	-1.1328E+04	—
A12 =	-6.4306E+00	1.8006E+05	—
A14 =	9.4595E+00	-1.8065E+06	—
A16 =	-3.5569E+00	6.4953E+06	—
	Surface #		
	7	8	9
k =	-9.1753E-01	-8.8837E+00	-3.3096E-01
A4 =	-4.1660E+00	-1.6434E+00	3.2705E+00
A6 =	9.9102E+00	-2.8362E+01	-1.6737E+01
A8 =	3.3776E+02	2.8018E+02	8.6517E+01
A10 =	-3.8793E+03	-1.1781E+03	—

TABLE 8-continued

Aspheric Coefficients			
A12 =	1.3258E+04	2.6959E+03	—
A14 =	—	-2.8184E+03	—

In the 4th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 4th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 7 and Table 8 as the following values and satisfy the following conditions:

4th Embodiment			
f [mm]	0.11	$ f/f1  +  f/f2  +  f/f3 $	0.75
Fno	2.00	$f/ImgH$	0.23
HFOV [deg.]	75.5	$f/EPD$	2.00
FOV [deg.]	151.0	OL/TL	0.45
V1 + V2 + V3	66.3	OTL [mm]	2.95
N1 + N2 + N3	5.010	OTL/ $\Sigma$ CT	3.12
T12/CT1	4.11	OTL/ImgH	6.01
CTf/CT1	2.75	TD/f	16.80
$(R5 + R6)/(R5 - R6)$	0.23	$ Dsr3/Dsr5 $	0.10

## 5th Embodiment

FIG. 9A is a schematic view of an image capturing unit according to the 5th embodiment of the present disclosure. FIG. 9B is a partially enlarged schematic view of the image

the second lens element **520** and the third lens element **530** are all stationary relative to one another in a paraxial region thereof.

The first lens element **510** with negative refractive power has an object-side surface **511** being convex in a paraxial region thereof and an image-side surface **512** being concave in a paraxial region thereof. The first lens element **510** is made of plastic material, and has the object-side surface **511** and the image-side surface **512** being both aspheric.

The second lens element **520** with positive refractive power has an object-side surface **521** being convex in a paraxial region thereof and an image-side surface **522** being convex in a paraxial region thereof. The second lens element **520** is made of plastic material, and has the object-side surface **521** and the image-side surface **522** being both aspheric.

The third lens element **530** with positive refractive power has an object-side surface **531** being convex in a paraxial region thereof and an image-side surface **532** being convex in a paraxial region thereof. The third lens element **530** is made of plastic material, and has the object-side surface **531** and the image-side surface **532** being both aspheric. The object-side surface **531** of the third lens element **530** has at least one inflection point.

The flat panel **540** is made of glass and located between an imaged object **O** and the first lens element **510**, and will not affect the focal length of the compact optical system. The image sensor **560** is disposed on or near the image surface **550** of the compact optical system.

The detailed optical data of the 5th embodiment are shown in Table 9 and the aspheric surface data are shown in Table 10 below.

TABLE 9

5th Embodiment							
$f = 0.14$ mm, $Fno = 2.00$ , $HFOV = 73.4$ deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.737	Glass	1.523	64.2	—
2		Plano	0.552				
3	Lens 1	42.472 (ASP)	0.249	Plastic	1.674	21.5	-0.47
4		0.311 (ASP)	1.039				
5	Ape. Stop	Plano	0.147				
6	Lens 2	1.381 (ASP)	0.502	Plastic	1.661	23.3	0.99
7		-1.057 (ASP)	0.059				
8	Lens 3	0.604 (ASP)	0.615	Plastic	1.674	21.5	0.57
9		-0.624 (ASP)	0.207				
10	Image	Plano	—				

Note:  
Reference wavelength is 480 nm.

capturing unit in FIG. 9A. FIG. 10 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 5th embodiment. In FIG. 9A and FIG. 9B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor **560**. The compact optical system includes, in order from an object side to an image side, a flat panel **540**, a first lens element **510**, an aperture stop **500**, a second lens element **520**, a third lens element **530** and an image surface **550**, wherein the compact optical system has a total of three lens elements (**510-530**) with refractive power. The first lens element **510**,

TABLE 10

Aspheric Coefficients			
Surface #			
	3	4	6
k =	-9.9987E-01	-5.1522E-01	-1.0055E+01
A4 =	1.4034E+00	8.0055E+00	7.8826E-32
A6 =	-2.2020E+00	-2.3142E+01	-6.6466E-60
A8 =	1.8647E+00	1.4814E+02	—
A10 =	-6.2729E-01	-8.1321E+02	—
A12 =	-1.7041E-01	7.1988E+03	—

TABLE 10-continued

Aspheric Coefficients			
	7	8	9
A14 =	1.9992E-01	-4.0224E+04	—
A16 =	-4.4073E-02	8.0542E+04	—
Surface #			
	7	8	9
k =	-6.9910E-01	-3.6343E+00	-3.0516E-01
A4 =	-1.3267E+00	-2.3442E-01	2.1915E+00
A6 =	1.9601E+00	2.6443E-01	-5.2437E+00
A8 =	6.9811E+00	-2.3494E+00	6.7749E+00
A10 =	-3.4744E+01	-2.3961E+01	—
A12 =	4.7385E+01	9.1454E+01	—
A14 =	—	-8.0498E+01	—

In the 5th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 5th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 9 and Table 10 as the following values and satisfy the following conditions:

5th Embodiment			
f [mm]	0.14	$ f/f1  +  f/f2  +  f/f3 $	0.67
Fno	2.00	$f/ImgH$	0.28
HFOV [deg.]	73.4	$f/EPD$	2.00
FOV [deg.]	146.8	OL/TL	0.46
V1 + V2 + V3	66.3	OTL [mm]	4.11
N1 + N2 + N3	5.010	OTL/ $\Sigma$ CT	3.01
T12/CT1	4.76	OTL/ImgH	8.41
CTf/CT1	2.96	TD/f	19.25
$(R5 + R6)/(R5 - R6)$	-0.02	$ Dsr3/Dsr5 $	0.21

## 6th Embodiment

FIG. 11A is a schematic view of an image capturing unit according to the 6th embodiment of the present disclosure. FIG. 11B is a partially enlarged schematic view of the image

capturing unit in FIG. 11A. FIG. 12 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 6th embodiment. In FIG. 11A and FIG. 11B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor 660. The compact optical system includes, in order from an object side to an image side, a flat panel 640, a first lens element 610, an aperture stop 600, a second lens element 620, a third lens element 630 and an image surface 650, wherein the compact optical system has a total of three lens elements (610-630) with refractive power. The first lens element 610, the second lens element 620 and the third lens element 630 are all stationary relative to one another in a paraxial region thereof.

The first lens element 610 with negative refractive power has an object-side surface 611 being convex in a paraxial region thereof and an image-side surface 612 being concave in a paraxial region thereof. The first lens element 610 is made of plastic material, and has the object-side surface 611 and the image-side surface 612 being both aspheric.

The second lens element 620 with negative refractive power has an object-side surface 621 being convex in a paraxial region thereof and an image-side surface 622 being concave in a paraxial region thereof. The second lens element 620 is made of plastic material, and has the object-side surface 621 and the image-side surface 622 being both aspheric.

The third lens element 630 with positive refractive power has an object-side surface 631 being convex in a paraxial region thereof and an image-side surface 632 being convex in a paraxial region thereof. The third lens element 630 is made of plastic material, and has the object-side surface 631 and the image-side surface 632 being both aspheric. The object-side surface 631 of the third lens element 630 has at least one inflection point.

The flat panel 640 is made of glass and located between an imaged object O and the first lens element 610, and will not affect the focal length of the compact optical system. The image sensor 660 is disposed on or near the image surface 650 of the compact optical system.

The detailed optical data of the 6th embodiment are shown in Table 11 and the aspheric surface data are shown in Table 12 below.

TABLE 11

6th Embodiment							
f = 0.10 mm, Fno = 2.00, HFOV = 75.1 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.737	Glass	1.523	64.2	—
2		Plano	0.507				
3	Lens 1	42.472 (ASP)	0.230	Plastic	1.717	20.0	-0.44
4		0.311 (ASP)	1.039				
5	Ape. Stop	Plano	0.011				
6	Lens 2	1.523 (ASP)	0.369	Plastic	1.661	23.3	-2.24
7		0.679 (ASP)	0.020				
8	Lens 3	0.233 (ASP)	0.508	Plastic	1.674	21.5	0.32
9		-0.326 (ASP)	0.192				
10	Image	Plano	—				

Note:

Reference wavelength is 480 nm.

TABLE 12

Aspheric Coefficients			
	Surface #		
	3	4	6
k =	-9.9987E-01	-5.1522E-01	-7.0741E+01
A4 =	1.3047E+00	8.0055E+00	7.8826E-32
A6 =	-2.0646E+00	-2.3142E+01	-6.3405E-61
A8 =	1.7079E+00	1.4814E+02	—
A10 =	-6.3998E-01	-8.1321E+02	—
A12 =	-1.6732E-03	7.1988E+03	—
A14 =	7.6570E-02	-4.0224E+04	—
A16 =	-1.6643E-02	8.0542E+04	—

	Surface #		
	7	8	9
k =	-7.3919E+01	-8.0113E+00	-5.5724E-01
A4 =	-3.1588E+01	-1.2590E-03	1.0608E+01
A6 =	7.4251E+02	-1.1784E+01	-4.7779E+01
A8 =	-1.3347E+04	-4.5766E+01	1.2667E+02
A10 =	1.3063E+05	-1.9406E+02	—
A12 =	-5.2744E+05	2.1210E+03	—
A14 =	—	-3.2702E+03	—

In the 6th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 6th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 11 and Table 12 as the following values and satisfy the following conditions:

6th Embodiment			
f [mm]	0.10	f/f1  +  f/f2  +  f/f3	0.59
Fno	2.00	f/ImgH	0.26
HFOV [deg.]	75.1	f/EPD	2.00
FOV [deg.]	150.1	OL/TL	0.52
V1 + V2 + V3	64.8	OTL [mm]	3.61
N1 + N2 + N3	5.052	OTL/ΣCT	3.26
T12/CT1	4.56	OTL/ImgH	9.40
CTf/CT1	3.20	TD/f	21.59
(R5 + R6)/(R5 - R6)	-0.17	Dsr3/Dsr5	0.03

FIG. 13A is a schematic view of an image capturing unit according to the 7th embodiment of the present disclosure. FIG. 13B is a partially enlarged schematic view of the image capturing unit in FIG. 13A. FIG. 14 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 7th embodiment. In FIG. 13A and FIG. 13B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor 760. The compact optical system includes, in order from an object side to an image side, a flat panel 740, a first lens element 710, an aperture stop 700, a second lens element 720, a third lens element 730 and an image surface 750, wherein the compact optical system has a total of three lens elements (710-730) with refractive power. The first lens element 710, the second lens element 720 and the third lens element 730 are all stationary relative to one another in a paraxial region thereof.

The first lens element 710 with negative refractive power has an object-side surface 711 being convex in a paraxial region thereof and an image-side surface 712 being concave in a paraxial region thereof. The first lens element 710 is made of plastic material, and has the object-side surface 711 and the image-side surface 712 being both aspheric.

The second lens element 720 with positive refractive power has an object-side surface 721 being concave in a paraxial region thereof and an image-side surface 722 being convex in a paraxial region thereof. The second lens element 720 is made of plastic material, and has the object-side surface 721 and the image-side surface 722 being both aspheric.

The third lens element 730 with positive refractive power has an object-side surface 731 being concave in a paraxial region thereof and an image-side surface 732 being convex in a paraxial region thereof. The third lens element 730 is made of plastic material, and has the object-side surface 731 and the image-side surface 732 being both aspheric. The object-side surface 731 of the third lens element 730 has at least one inflection point.

The flat panel 740 is made of glass and located between an imaged object O and the first lens element 710, and will not affect the focal length of the compact optical system. The image sensor 760 is disposed on or near the image surface 750 of the compact optical system.

The detailed optical data of the 7th embodiment are shown in Table 13 and the aspheric surface data are shown in Table 14 below.

TABLE 13

7th Embodiment							
f = 0.09 mm, Fno = 2.40, HFOV = 80.5 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.500	Glass	1.523	64.2	—
2		Plano	0.398				
3	Lens 1	15.000 (ASP)	0.300	Plastic	1.674	21.5	-0.25
4		0.162 (ASP)	0.393				
5	Ape. Stop	Plano	0.010				
6	Lens 2	-5.418 (ASP)	0.380	Plastic	1.674	21.4	0.46
7		-0.301 (ASP)	0.050				
8	Lens 3	-1.337 (ASP)	0.447	Plastic	1.660	23.5	0.33
9		-0.215 (ASP)	0.257				
10	Image	Plano	—				

Note:

Reference wavelength is 480 nm.

TABLE 14

Aspheric Coefficients			
	Surface #		
	3	4	6
k =	-1.0000E+00	-5.1522E-01	-3.2825E-14
A4 =	-2.0759E-01	-1.0338E+01	4.5040E+00
A6 =	1.9664E+00	5.9030E+02	—
A8 =	-3.2004E+00	-6.4492E+04	—
A10 =	2.4242E+00	1.5168E+06	—
A12 =	-6.8958E-01	-9.9874E+06	—
A14 =	4.4762E-03	—	—

	Surface #		
	7	8	9
k =	-1.4160E+00	-9.0000E+01	-7.3530E-01
A4 =	-4.3664E+00	2.7081E+00	1.8200E+01
A6 =	6.8533E+01	-1.1956E+01	-8.9143E+01
A8 =	-1.4923E+03	1.1073E+01	5.8239E+02
A10 =	1.5227E+04	-1.0257E+01	-1.0583E+03

In the 7th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 7th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 13 and Table 14 as the following values and satisfy the following conditions:

7th Embodiment			
f [mm]	0.09	$ f/f1  +  f/f2  +  f/f3 $	0.84
Fno	2.40	f/ImgH	0.24
HFOV [deg.]	80.5	f/EPD	2.40
FOV [deg.]	160.9	OL/TL	0.49
V1 + V2 + V3	66.4	OTL [mm]	2.74
N1 + N2 + N3	5.009	OTL/ $\Sigma$ CT	2.43
T12/CT1	1.34	OTL/ImgH	7.25
CTf/CT1	1.67	TD/f	17.30
(R5 + R6)/(R5 - R6)	1.38	Dsr3/Dsr5	0.02

8th Embodiment

FIG. 15A is a schematic view of an image capturing unit according to the 8th embodiment of the present disclosure. FIG. 15B is a partially enlarged schematic view of the image capturing unit in FIG. 15A. FIG. 16 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 8th embodiment. In FIG. 15A and FIG. 15B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor 860. The compact optical system includes, in order from an object side to an image side, a flat panel 840, a first lens element 810, an aperture stop 800, a second lens element 820, a third lens element 830 and an image surface 850, wherein the compact optical system has a total of three lens elements (810-830) with refractive power. The first lens element 810, the second lens element 820 and the third lens element 830 are all stationary relative to one another in a paraxial region thereof.

The first lens element 810 with negative refractive power has an object-side surface 811 being concave in a paraxial region thereof and an image-side surface 812 being concave in a paraxial region thereof. The first lens element 810 is made of plastic material, and has the object-side surface 811 and the image-side surface 812 being both aspheric.

The second lens element 820 with positive refractive power has an object-side surface 821 being convex in a paraxial region thereof and an image-side surface 822 being convex in a paraxial region thereof. The second lens element 820 is made of plastic material, and has the object-side surface 821 and the image-side surface 822 being both aspheric.

The third lens element 830 with positive refractive power has an object-side surface 831 being convex in a paraxial region thereof and an image-side surface 832 being concave in a paraxial region thereof. The third lens element 830 is made of plastic material, and has the object-side surface 831 and the image-side surface 832 being both aspheric. The object-side surface 831 and the image-side surface 832 of the third lens element 830 have at least one inflection point.

The flat panel 840 is made of glass and located between an imaged object O and the first lens element 810, and will not affect the focal length of the compact optical system. The image sensor 860 is disposed on or near the image surface 850 of the compact optical system.

The detailed optical data of the 8th embodiment are shown in Table 15 and the aspheric surface data are shown in Table 16 below.

TABLE 15

8th Embodiment							
f = 0.21 mm, Fno = 2.40, HFOV = 74.3 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.500	Glass	1.523	64.2	—
2		Plano	0.708				
3	Lens 1	-8.835 (ASP)	0.200	Plastic	1.660	23.5	-0.49
4		0.338 (ASP)	0.429				
5	Ape. Stop	Plano	0.022				
6	Lens 2	1.428 (ASP)	0.515	Plastic	1.598	30.2	0.50
7		-0.324 (ASP)	0.020				
8	Lens 3	0.589 (ASP)	0.211	Plastic	1.660	23.5	1.62
9		1.126 (ASP)	0.355				
10	Image	Plano	—				

Note:

Reference wavelength is 480 nm.

TABLE 16

Aspheric Coefficients			
	Surface #		
	3	4	6
k =	-9.9992E-01	-5.1522E-01	1.7181E+01
A4 =	1.1491E+01	3.6278E+01	-1.6594E+00
A6 =	-7.3638E+01	-3.0095E+02	-7.3073E+00
A8 =	2.8193E+02	4.0905E+03	—
A10 =	-3.8213E+02	1.6377E+04	—
A12 =	-9.1428E+02	-7.4275E+05	—
A14 =	3.7522E+03	4.2082E+06	—
A16 =	-3.5581E+03	-6.7616E+06	—

	Surface #		
	7	8	9
k =	-6.7877E-01	4.3772E-01	3.0043E+00
A4 =	1.9698E-01	-2.2897E+00	-5.3307E+00
A6 =	-1.7633E+01	-2.8553E+01	-4.1074E-01
A8 =	-7.0664E+01	3.2916E+02	3.9246E+02
A10 =	2.6099E+03	-1.5627E+03	-2.6874E+03
A12 =	-1.0959E+04	2.5641E+03	6.9987E+03
A14 =	—	-3.3699E+03	-6.5280E+03

In the 8th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 8th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 15 and Table 16 as the following values and satisfy the following conditions:

8th Embodiment			
f [mm]	0.21	f/f1  +  f/f2  +  f/f3	1.00
Fno	2.40	f/ImgH	0.29
HFOV [deg.]	74.3	f/EPD	2.40
FOV [deg.]	148.6	OL/TL	0.69
V1 + V2 + V3	77.2	OTL [mm]	2.96
N1 + N2 + N3	4.919	OTL/ΣCT	3.20
T12/CT1	2.26	OTL/ImgH	4.05
CTf/CT1	2.50	TD/f	6.57
(R5 + R6)/(R5 - R6)	-3.19	Dsr3/Dsr5	0.04

FIG. 17A is a schematic view of an image capturing unit according to the 9th embodiment of the present disclosure. FIG. 17B is a partially enlarged schematic view of the image capturing unit in FIG. 17A. FIG. 18 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 9th embodiment. In FIG. 17A and FIG. 17B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor 960. The compact optical system includes, in order from an object side to an image side, a flat panel 940, a first lens element 910, an aperture stop 900, a second lens element 920, a third lens element 930 and an image surface 950, wherein the compact optical system has a total of three lens elements (910-930) with refractive power. The first lens element 910, the second lens element 920 and the third lens element 930 are all stationary relative to one another in a paraxial region thereof.

The first lens element 910 with negative refractive power has an object-side surface 911 being concave in a paraxial region thereof and an image-side surface 912 being concave in a paraxial region thereof. The first lens element 910 is made of plastic material, and has the object-side surface 911 and the image-side surface 912 being both aspheric.

The second lens element 920 with positive refractive power has an object-side surface 921 being convex in a paraxial region thereof and an image-side surface 922 being convex in a paraxial region thereof. The second lens element 920 is made of plastic material, and has the object-side surface 921 and the image-side surface 922 being both aspheric.

The third lens element 930 with positive refractive power has an object-side surface 931 being convex in a paraxial region thereof and an image-side surface 932 being convex in a paraxial region thereof. The third lens element 930 is made of plastic material, and has the object-side surface 931 and the image-side surface 932 being both aspheric. The object-side surface 931 and the image-side surface 932 of the third lens element 930 have at least one inflection point.

The flat panel 940 is made of glass and located between an imaged object O and the first lens element 910, and will not affect the focal length of the compact optical system. The image sensor 960 is disposed on or near the image surface 950 of the compact optical system.

The detailed optical data of the 9th embodiment are shown in Table 17 and the aspheric surface data are shown in Table 18 below.

TABLE 17

9th Embodiment							
f = 0.15 mm, Fno = 1.60, HFOV = 79.3 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.500	Glass	1.523	64.2	—
2		Plano	0.739				
3	Lens 1	-16.036 (ASP)	0.200	Plastic	1.674	21.5	-0.42
4		0.287 (ASP)	0.473				
5	Ape. Stop	Plano	0.025				
6	Lens 2	1.260 (ASP)	0.386	Plastic	1.598	30.2	0.85
7		-0.750 (ASP)	0.075				
8	Lens 3	0.493 (ASP)	0.317	Plastic	1.674	21.5	0.41
9		-0.458 (ASP)	0.267				
10	Image	Plano	—				

Note:

Reference wavelength is 480 nm.

TABLE 18

Aspheric Coefficients			
	Surface #		
	3	4	6
k =	-9.9986E-01	-5.1522E-01	3.4814E+00
A4 =	2.1555E+00	6.0675E+00	-7.2076E-01
A6 =	-5.5319E+00	-1.5280E+01	—
A8 =	8.5214E+00	6.3044E+01	—
A10 =	-5.9901E+00	7.6621E+01	—
A12 =	6.2520E-01	-1.0549E+03	—
A14 =	1.2884E+00	1.8143E+03	—
A16 =	-4.6567E-01	-8.8491E+02	—

	Surface #		
	7	8	9
k =	1.4447E+00	-3.7783E-01	-2.5927E-01
A4 =	-9.9434E+00	-1.0543E+01	5.0921E+00
A6 =	4.9153E+01	9.6135E+01	-3.2901E+01
A8 =	2.7144E+00	-1.0514E+03	1.3855E+02
A10 =	-3.7730E+02	6.2546E+03	—
A12 =	5.0995E+02	-1.6837E+04	—
A14 =	—	1.6440E+04	—

In the 9th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 9th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 17 and Table 18 as the following values and satisfy the following conditions:

9th Embodiment			
f [mm]	0.15	$ f/f1  +  f/f2  +  f/f3 $	0.92
Fno	1.60	$f/ImgH$	0.22
HFOV [deg.]	79.3	$f/EPD$	1.60
FOV [deg.]	158.7	$OL/TL$	0.71
V1 + V2 + V3	73.2	$OTL [mm]$	2.98
N1 + N2 + N3	4.947	$OTL/\Sigma CT$	3.30
T12/CT1	2.49	$OTL/ImgH$	4.39
CTf/CT1	2.50	$TD/f$	9.70
$(R5 + R6)/(R5 - R6)$	0.04	$ Dsr3/Dsr5 $	0.05

FIG. 19A is a schematic view of an image capturing unit according to the 10th embodiment of the present disclosure. FIG. 19B is a partially enlarged schematic view of the image capturing unit in FIG. 19A. FIG. 20 shows spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing unit according to the 10th embodiment. In FIG. 19A and FIG. 19B, the image capturing unit includes the compact optical system (its reference numeral is omitted) of the present disclosure and an image sensor 1060. The compact optical system includes, in order from an object side to an image side, a flat panel 1040, a first lens element 1010, an aperture stop 1000, a second lens element 1020, a third lens element 1030 and an image surface 1050, wherein the compact optical system has a total of three lens elements (1010-1030) with refractive power. The first lens element 1010, the second lens element 1020 and the third lens element 1030 are all stationary relative to one another in a paraxial region thereof.

The first lens element 1010 with negative refractive power has an object-side surface 1011 being convex in a paraxial region thereof and an image-side surface 1012 being concave in a paraxial region thereof. The first lens element 1010 is made of plastic material, and has the object-side surface 1011 and the image-side surface 1012 being both aspheric.

The second lens element 1020 with positive refractive power has an object-side surface 1021 being flat in a paraxial region thereof and an image-side surface 1022 being convex in a paraxial region thereof. The second lens element 1020 is made of plastic material, and has the object-side surface 1021 and the image-side surface 1022 being both aspheric.

The third lens element 1030 with positive refractive power has an object-side surface 1031 being convex in a paraxial region thereof and an image-side surface 1032 being convex in a paraxial region thereof. The third lens element 1030 is made of plastic material, and has the object-side surface 1031 and the image-side surface 1032 being both aspheric. The image-side surface 1032 of the third lens element 1030 has at least one inflection point.

The flat panel 1040 is made of glass and located between an imaged object O and the first lens element 1010, and will not affect the focal length of the compact optical system. The image sensor 1060 is disposed on or near the image surface 1050 of the compact optical system.

The detailed optical data of the 10th embodiment are shown in Table 19 and the aspheric surface data are shown in Table 20 below.

TABLE 19

10th Embodiment							
f = 0.12 mm, Fno = 2.40, HFOV = 76.4 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	0.000				
1	Flat Panel	Plano	0.500	Glass	1.523	64.2	—
2		Plano	0.661				
3	Lens 1	15.000 (ASP)	0.249	Plastic	1.674	21.5	-0.42
4		0.276 (ASP)	0.558				
5	Ape. Stop	Plano	0.009				
6	Lens 2	Plano	0.290	Plastic	1.660	23.5	0.80
7		-0.531 (ASP)	0.045				
8	Lens 3	1.324 (ASP)	0.434	Plastic	1.660	23.5	0.33
9		-0.226 (ASP)	0.249				
10	Image	Plano	—				

Note:

Reference wavelength is 480 nm.



TABLE 20

Aspheric Coefficients			
	Surface #		
	3	4	7
k =	-1.0000E+00	-5.1522E-01	-1.0629E+01
A4 =	-5.5241E-01	8.2831E+00	-5.1546E+00
A6 =	3.0468E+00	-4.4169E+02	1.8667E+02
A8 =	-4.6870E+00	5.1872E+03	-5.1532E+03
A10 =	3.3702E+00	-2.3830E+04	5.0028E+04
A12 =	-9.5570E-01	3.7594E+04	—
A14 =	2.0562E-03	—	—

	Surface #	
	8	9
k =	-4.5453E+01	-7.3057E-01
A4 =	5.7245E+00	1.5752E+01
A6 =	-2.7525E+01	-1.6147E+01
A8 =	3.7878E+01	-1.6867E+02
A10 =	-2.6500E+01	1.3324E+03

In the 10th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in the following table are the same as those stated in the 1st embodiment with corresponding values for the 10th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 19 and Table 20 as the following values and satisfy the following conditions:

10th Embodiment			
f [mm]	0.12	$ f/f1  +  f/f2  +  f/f3 $	0.78
Fno	2.40	$f/ImgH$	0.34
HFOV [deg.]	76.4	$f/EPD$	2.40
FOV [deg.]	152.9	OL/TL	0.63
V1 + V2 + V3	68.5	OTL [mm]	3.00
N1 + N2 + N3	4.995	OTL/ $\Sigma$ CT	3.08
T12/CT1	2.28	OTL/ImgH	8.61
CTf/CT1	2.01	TD/f	13.47
$(R5 + R6)/(R5 - R6)$	0.71	$ Dsr3/Dsr5 $	0.03

The foregoing image capturing unit is able to be installed in, but not limited to, an electronic device, including smart phones, tablet personal computers, wearable apparatus and driving assist devices. According to the present disclosure, the compact optical system has a total of three lens elements with refractive power. In order to satisfy the requirements of compact size and wide field of view when the imaged object is extremely close to the compact optical system, the first lens element has negative refractive power, and the third lens element has positive refractive power. Therefore, it is favorable for providing the compact optical system with retrofocus performance so as to reduce the chief ray angle of the compact optical system, thereby providing the compact optical system with enhanced telecentric performance. Furthermore, when specific conditions are satisfied, it is favorable for collecting the light with large incident angle so as to allow the compact optical system to capture a wide field of view and recognize an imaged object while the distance between the imaged object and the compact optical system is extremely close. Moreover, it is favorable for reducing a required distance for imaging capturing between the imaged object and the compact optical system so as to keep the compact optical system compact.

The foregoing description, for the purpose of explanation, has been described with reference to specific embodiments. It is to be noted that TABLES 1-20 show different data of the different embodiments; however, the data of the different embodiments are obtained from experiments. The embodiments were chosen and described in order to best explain the principles of the disclosure and its practical applications, to thereby enable others skilled in the art to best utilize the disclosure and various embodiments with various modifications as are suited to the particular use contemplated. The embodiments depicted above and the appended drawings are exemplary and are not intended to be exhaustive or to limit the scope of the present disclosure to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings.

What is claimed is:

1. A compact optical system comprising, in order from an object side to an image side:

a first lens element with negative refractive power having an image-side surface being concave in a paraxial region thereof;

a second lens element, wherein at least one of an object-side surface and an image-side surface of the second lens element is aspheric, and the second lens element is made of plastic material; and

a third lens element having positive refractive power, wherein at least one of an object-side surface and an image-side surface of the third lens element is aspheric, and the third lens element is made of plastic material;

wherein the compact optical system has a total of three lens elements, the compact optical system further comprises an aperture stop located between the first lens element and the second lens element, the first lens element, the second lens element and the third lens element are all stationary relative to one another in a paraxial region thereof;

wherein a focal length of the compact optical system is  $f$ , a maximum image height of the compact optical system is  $ImgH$ , an entrance pupil diameter of the compact optical system is  $EPD$ , a refractive index of the first lens element is  $N1$ , a refractive index of the second lens element is  $N2$ , a refractive index of the third lens element is  $N3$ , an axial distance between the aperture stop and the object-side surface of the second lens element is  $Dsr3$ , an axial distance between the aperture stop and the object-side surface of the third lens element is  $Dsr5$ , and the following conditions are satisfied:

$$f/ImgH < 0.55;$$

$$f/EPD < 2.60;$$

$$4.70 < N1 + N2 + N3 < 5.50; \text{ and}$$

$$0 < |Dsr3/Dsr5| < 0.50.$$

2. The compact optical system of claim 1, wherein the image-side surface of the third lens element is convex in a paraxial region thereof.

3. The compact optical system of claim 2, wherein the second lens element has positive refractive power, and the image-side surface of the second lens element is convex in a paraxial region thereof.

4. The compact optical system of claim 2, wherein a curvature radius of the object-side surface of the third lens element is  $R5$ , a curvature radius of the image-side surface of the third lens element is  $R6$ , and the following condition is satisfied:

$$-0.50 < (R5 + R6)/(R5 - R6) < 0.50.$$

## 31

5. The compact optical system of claim 1, wherein at least one of the object-side surface and the image-side surface of the third lens element has at least one inflection point, a curvature radius of the object-side surface of the third lens element is R5, a curvature radius of the image-side surface of the third lens element is R6, and the following condition is satisfied:

$$(R5+R6)/(R5-R6)<0.90.$$

6. The compact optical system of claim 1, wherein an axial distance between an imaged object and an image surface is OTL, and the following condition is satisfied:

OTL $\geq$  8.0 millimeters (mm).

7. The compact optical system of claim 1, wherein the focal length of the compact optical system is f, the maximum image height of the compact optical system is ImgH, and the following condition is satisfied:

$$f/ImgH<0.45.$$

8. The compact optical system of claim 1, wherein an Abbe number of the first lens element is V1, an Abbe number of the second lens element is V2, an Abbe number of the third lens element is V3, and the following condition is satisfied:

$$V1+V2+V3<80.$$

9. The compact optical system of claim 1, further comprising a flat panel, wherein the flat panel is located between so an imaged object and an object-side surface of the first lens element.

10. An image capturing unit, comprising:  
the compact optical system of claim 1; and  
an image sensor, wherein the image sensor is disposed on the image side of the compact optical system.

11. An electronic device comprising:  
a biometric system, wherein the biometric system comprises the image capturing unit of claim 10.

12. A compact optical system comprising, in order from an object side to an image side:

a first lens element with negative refractive power having an image-side surface being concave in a paraxial region thereof;

a second lens element, wherein at least one of an object-side surface and an image-side surface of the second lens element is aspheric, and the second lens element is made of plastic material; and

a third lens element having positive refractive power, wherein at least one of an object-side surface and an image-side surface of the third lens element is aspheric, and the third lens element is made of plastic material;

wherein the compact optical system has a total of three lens elements, the compact optical system further comprises an aperture stop located between the first lens element and the second lens element, the first lens element, the second lens element and the third lens element are all stationary relative to one another in a paraxial region thereof;

wherein a focal length of the compact optical system is f, a focal length of the first lens element is f1, a focal length of the second lens element is f2, a focal length of the third lens element is f3, a maximum image height of the compact optical system is ImgH, a refractive index of the first lens element is N1, a refractive index of the second lens element is N2, a refractive index of the third lens element is N3, an axial distance between the aperture stop and the object-side surface of the second lens element is Dsr3, an axial distance between

## 32

the aperture stop and the object-side surface of the third lens element is Dsr5, an axial distance between an imaged object and an image surface is OTL, a sum of central thicknesses of the first lens element, the second lens element and the third lens element is  $\Sigma$ CT, and the following conditions are satisfied:

$$0.5<|f/f1|+|f/f2|+|f/f3|<1.1;$$

$$f/ImgH<0.70;$$

$$4.70<N1+N2+N3<5.50;$$

$$0<|Dsr3/Dsr5|<0.50; \text{ and}$$

$$OTL/\Sigma CT<4.0.$$

13. The compact optical system of claim 12, wherein the image-side surface of the third lens element is convex in a paraxial region thereof.

14. The compact optical system of claim 12, wherein the axial distance between the imaged object and the image surface is OTL, the maximum image height of the compact optical system is ImgH, and the following condition is satisfied:

$$OTL/ImgH<12.$$

15. The compact optical system of claim 14, wherein a maximal field of view of the compact optical system is FOV, and the following condition is satisfied:

$$140.0 \text{ degrees (deg.)}<FOV<180.0 \text{ deg.}$$

16. The compact optical system of claim 14, wherein the compact optical system further comprises a flat panel located between the imaged object and an object-side surface of the first lens element, a central thickness of the flat panel is CTf, a central thickness of the first lens element is CT1, and the following condition is satisfied:

$$0.95<CTf/CT1<5.5.$$

17. The compact optical system of claim 12, wherein at least one of the object-side surface and the image-side surface of the third lens element has at least one inflection point, the axial distance between the imaged object and the image surface is OTL, and the following condition is satisfied:

$$OTL<5.0 \text{ mm.}$$

18. The compact optical system of claim 12, wherein a curvature radius of the object-side surface of the third lens element is R5, a curvature radius of the image-side surface of the third lens element is R6, and the following condition is satisfied:

$$(R5+R6)/(R5-R6)<0.90.$$

19. The compact optical system of claim 12, wherein an axial distance between the first lens element and the second lens element is T12, a central thickness of the first lens element is CT1, and the following condition is satisfied:

$$1.50<T12/CT1<10.$$

20. The compact optical system of claim 12, wherein an axial distance between the imaged object and an object-side surface of the first lens element is OL, an axial distance between the object-side surface of the first lens element and the image surface is TL, and the following condition is satisfied:

$$0<OL/TL<1.0.$$

33

21. The compact optical system of claim 12, wherein an axial distance between the object-side surface of the first lens element and the image-side surface of the third lens element is TD, the focal length of the compact optical system is f, and the following condition is satisfied:

$$8 < TD/f < 30.$$

22. An image capturing unit, comprising:  
the compact optical system of claim 12;  
a light source; and

an image sensor, wherein the image sensor is disposed on the image side of the compact optical system.

23. The image capturing unit of claim 22, wherein the light source is within a wavelength range of 400 nanometers (nm) to 500 nm.

24. A compact optical system comprising three lens elements, the three lens elements being, in order from an object side to an image side, a first lens element, a second lens element and a third lens element; each of the three lens elements having an object-side surface facing toward the object side and an image-side surface facing toward the image side;

wherein the first lens element has negative refractive power, the object-side surface of the second lens element is convex in a paraxial region thereof, the third lens element has positive refractive power, and the object-side surface of the third lens element is convex in a paraxial region thereof;

wherein the compact optical system has a total of three lens elements, an axial distance between the first lens element and the second lens element is larger than an axial distance between the second lens element and the third lens element, an absolute value of a curvature radius of the object-side surface of the third lens element is larger than an absolute value of a curvature radius of the image-side surface of the third lens element;

wherein a focal length of the compact optical system is f, an entrance pupil diameter of the compact optical system is EPD, an axial distance between an imaged object and an image surface is OTL, and the following conditions are satisfied:

$$f/EPD \geq 1.60; \text{ and}$$

$$OTL < 5.0 \text{ mm.}$$

25. The compact optical system of claim 24, wherein the object-side surface of the first lens element is concave in a paraxial region thereof.

26. The compact optical system of claim 24, wherein the second lens element has positive refractive power, and the image-side surface of the first lens element is concave in a paraxial region thereof.

27. The compact optical system of claim 24, wherein the image-side surface of the third lens element is convex in a paraxial region thereof.

28. The compact optical system of claim 24, wherein at least one of the object-side surface and the image-side surface of the third lens element has at least one inflection point.

29. The compact optical system of claim 24, wherein each of the first lens element, the second lens element and the third lens element is made of plastic material, the curvature radius of the object-side surface of the third lens element is R5, the curvature radius of the image-side surface of the third lens element is R6, and the following condition is satisfied:

$$(R5+R6)/(R5-R6) < 0.90.$$

34

30. The compact optical system of claim 24, wherein the axial distance between the imaged object and the image surface is OTL, a sum of central thicknesses of the first lens element, the second lens element and the third lens element is  $\Sigma CT$ , and the following condition is satisfied:

$$OTL/\Sigma CT < 4.0.$$

31. The compact optical system of claim 24, further comprises a flat panel located between an imaged object and the object-side surface of the first lens element.

32. The compact optical system of claim 24, wherein a refractive index of the first lens element is N1, a refractive index of the second lens element is N2, a refractive index of the third lens element is N3, and the following condition is satisfied:

$$4.70 < N1+N2+N3 < 5.50.$$

33. An image capturing unit, comprising:  
the compact optical system of claim 24;  
a barrel member; and

an image sensor, disposed on the image side of the compact optical system.

34. An electronic device comprising:  
a biometric system, wherein the biometric system comprises the image capturing unit of claim 33.

35. A compact optical system comprising three lens elements, the three lens elements being, in order from an object side to an image side, a first lens element, a second lens element and a third lens element; each of the three lens elements having an object-side surface facing toward the object side and an image-side surface facing toward the image side;

wherein the first lens element has negative refractive power, the object-side surface of the first lens element is concave in a paraxial region thereof, the first lens element is made of plastic material, the object-side surface of the second lens element is convex in a paraxial region thereof, the third lens element has positive refractive power, and the object-side surface of the third lens element is convex in a paraxial region thereof;

wherein the compact optical system has a total of three lens elements, an axial distance between the first lens element and the second lens element is larger than an axial distance between the second lens element and the third lens element, the axial distance between the first lens element and the second lens element is larger than a central thickness of the second lens element, an absolute value of a curvature radius of the object-side surface of the third lens element is larger than an absolute value of a curvature radius of the image-side surface of the third lens element;

wherein a focal length of the compact optical system is f, an entrance pupil diameter of the compact optical system is EPD, and the following condition is satisfied:

$$f/EPD < 2.60.$$

36. The compact optical system of claim 35, wherein the second lens element has positive refractive power, and the image-side surface of the first lens element is concave in a paraxial region thereof.

37. The compact optical system of claim 35, wherein at least one of the object-side surface and the image-side surface of the first lens element has at least one inflection point, at least one of the object-side surface and the image-side surface of the first lens element is aspheric, at least one of the object-side surface and the image-side surface of the

## 35

second lens element is aspheric, at least one of the object-side surface and the image-side surface of the third lens element is aspheric, and the image-side surface of the third lens element is convex in a paraxial region thereof.

38. The compact optical system of claim 35, wherein the axial distance between the first lens element and the second lens element is  $T12$ , a central thickness of the first lens element is  $CT1$ , and the following condition is satisfied:

$$1.50 < T12/CT1 < 10.$$

39. The compact optical system of claim 35, wherein an axial distance between an imaged object and an image surface is  $OTL$ , a maximum image height of the compact optical system is  $ImgH$ , and the following condition is satisfied:

$$OTL/ImgH < 12.$$

40. The compact optical system of claim 35, further comprises a flat panel located between an imaged object and the object-side surface of the first lens element, wherein an axial distance between an imaged object and the object-side surface of the first lens element is  $OL$ , an axial distance between the object-side surface of the first lens element and an image surface is  $TL$ , and the following condition is satisfied:

$$0 < OL/TL < 1.0.$$

41. The compact optical system of claim 35, wherein an absolute value of a curvature radius of the object-side surface of the first lens element is larger than an absolute value of a curvature radius of the image-side surface of the first lens element.

42. A compact optical system comprising three lens elements, the three lens elements being, in order from an object side to an image side, a first lens element, a second lens element and a third lens element; each of the three lens elements having an object-side surface facing toward the object side and an image-side surface facing toward the image side;

wherein the first lens element has negative refractive power, the object-side surface and the image-side surface of the first lens element are both aspheric, the object-side surface of the first lens element is concave in a paraxial region thereof and has at least one convex shape in an off-axis region thereof, at least one of the object-side surface and the image-side surface of the first lens element has at least one inflection point, the first lens element is made of plastic material, and the third lens element has positive refractive power;

wherein the compact optical system has a total of three lens elements, there is an air gap in a paraxial region between each of adjacent lens elements of the compact optical system;

wherein a focal length of the compact optical system is  $f$ , an entrance pupil diameter of the compact optical system is  $EPD$ , and the following condition is satisfied:

$$f/EPD \leq 1.60.$$

43. The compact optical system of claim 42, wherein the object-side surface and the image-side surface of the second lens element are both aspheric, the object-side surface and the image-side surface of the third lens element are both aspheric, and the object-side surface of the first lens element is concave in a paraxial region thereof.

44. The compact optical system of claim 42, further comprising an aperture stop located between the first lens

## 36

element and the second lens element, wherein each of the second lens element and the third lens element is made of plastic material.

45. The compact optical system of claim 42, further comprises a flat panel located between an imaged object and the object-side surface of the first lens element.

46. The compact optical system of claim 42, further comprising a glare stop located between the first lens element and the third lens element.

47. The compact optical system of claim 42, wherein at least one of the object-side surface and the image-side surface of the second lens element is aspheric, at least one of the object-side surface and the image-side surface of the third lens element is aspheric, an axial distance between an imaged object and an image surface is  $OTL$ , and the following condition is satisfied:

$$OTL < 5.0 \text{ mm.}$$

48. The compact optical system of claim 42, wherein an axial distance between an imaged object and an image surface is  $OTL$ , a sum of central thicknesses of the first lens element, the second lens element and the third lens element is  $\Sigma CT$ , and the following condition is satisfied:

$$OTL/\Sigma CT < 4.0.$$

49. The compact optical system of claim 42, wherein the object-side surface of the second lens element is convex in a paraxial region thereof.

50. The compact optical system of claim 42, wherein the image-side surface of the second lens element is convex in a paraxial region thereof, an axial distance between an imaged object and an image surface is  $OTL$ , and the following condition is satisfied:

$$OTL < 8.0 \text{ mm.}$$

51. The compact optical system of claim 42, wherein the object-side surface of the third lens element is convex in a paraxial region thereof, an axial distance between an imaged object and an image surface is  $OTL$ , a maximum image height of the compact optical system is  $ImgH$ , and the following condition is satisfied:

$$OTL/ImgH < 12.$$

52. The compact optical system of claim 42, further comprising an aperture stop located between the first lens element and the third lens element, wherein the image-side surface of the third lens element is convex in a paraxial region thereof.

53. The compact optical system of claim 42, wherein the image-side surface of the first lens element is concave in a paraxial region thereof, a curvature radius of the object-side surface of the third lens element is  $R5$ , a curvature radius of the image-side surface of the third lens element is  $R6$ , and the following condition is satisfied:

$$(R5+R6)/(R5-R6) < 0.90.$$

54. The compact optical system of claim 42, wherein at least one of the object-side surface and the image-side surface of the third lens element has at least one inflection point.

55. The compact optical system of claim 42, wherein the focal length of the compact optical system is  $f$ , a maximum image height of the compact optical system is  $ImgH$ , and the following condition is satisfied:

$$f/ImgH < 0.45.$$

56. The compact optical system of claim 42, wherein a refractive index of the first lens element is  $N1$ , a refractive

37

*index of the second lens element is  $N_2$ , a refractive index of the third lens element is  $N_3$ , and the following condition is satisfied:*

$$4.70 < N_1 + N_2 + N_3 < 5.50.$$

*57. The compact optical system of claim 42, wherein a maximal field of view of the compact optical system is FOV, and the following condition is satisfied:*

$$140.0 \text{ deg.} < \text{FOV} < 180.0 \text{ deg.}$$

*58. The compact optical system of claim 42, further comprising an aperture stop, wherein an axial distance between the aperture stop and the object-side surface of the second lens element is  $D_{sr3}$ , an axial distance between the aperture stop and the object-side surface of the third lens element is  $D_{sr5}$ , and the following condition is satisfied:*

$$0 < |D_{sr3}/D_{sr5}| < 0.50.$$

*59. The compact optical system of claim 42, wherein an axial distance between the first lens element and the second*

38

*lens element is larger than an axial distance between the second lens element and the third lens element.*

*60. The compact optical system of claim 42, wherein a central thickness of the second lens element is larger than a central thickness of the third lens element.*

*61. The compact optical system of claim 42, wherein an absolute value of a curvature radius of the object-side surface of the second lens element is larger than an absolute value of a curvature radius of the image-side surface of the second lens element.*

*62. An image capturing unit, comprising:*

*the compact optical system of claim 42;*

*a barrel member; and*

*an image sensor, disposed on the image side of the compact optical system.*

*63. An electronic device comprising:*

*a biometric system, wherein the biometric system comprises the image capturing unit of claim 62.*

\* \* \* \* \*