



US00RE48895E

(19) **United States**
(12) **Reissued Patent**
Jeong et al.

(10) **Patent Number:** **US RE48,895 E**
(45) **Date of Reissued Patent:** ***Jan. 18, 2022**

(54) **ORGANIC LIGHT-EMITTING DIODE
DISPLAY APPARATUS**

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si (KR)

(72) Inventors: **Minjae Jeong**, Yongin-si (KR);
Gyungsoon Park, Yongin-si (KR);
Jongho Hong, Yongin-si (KR)

(73) Assignee: **SAMSUNG DISPLAY CO., LTD.**,
Yongin (KR)

(*) Notice: This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/503,971**

(22) Filed: **Jul. 5, 2019**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,698,205**
Issued: **Jul. 4, 2017**
Appl. No.: **15/333,522**
Filed: **Oct. 25, 2016**

U.S. Applications:

(63) Continuation of application No. 14/625,472, filed on
Feb. 18, 2015, now Pat. No. 9,490,308.

(30) **Foreign Application Priority Data**

Oct. 21, 2014 (KR) 10-2014-0142768

(51) **Int. Cl.**
H01L 27/32 (2006.01)
H01L 51/00 (2006.01)

(52) **U.S. Cl.**
CPC **H01L 27/3248** (2013.01); **H01L 27/3276**
(2013.01); **H01L 51/0097** (2013.01); **H01L**
2251/5338 (2013.01); **Y02E 10/549** (2013.01)

(58) **Field of Classification Search**
CPC **H01L 27/3248**; **H01L 27/3276**; **H01L**
51/0097; **H01L 2251/5338**; **Y02E 10/549**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,469,020 A * 11/1995 Herrick G02F 1/1365
257/E25.02
7,242,398 B2 7/2007 Nathan et al.
9,490,308 B2 * 11/2016 Jeong H01L 27/3248
(Continued)

FOREIGN PATENT DOCUMENTS

KR 10-0222896 7/1999
KR 10-0222896 B1 7/1999
(Continued)


Primary Examiner — Ling X Xu

(74) *Attorney, Agent, or Firm* — F. Chau & Associates,
LLC

(57) **ABSTRACT**

An organic light-emitting diode (OLED) display is dis-
closed. In one aspect, the display includes a stretchable
substrate, a thin film transistor (TFT) formed over the
stretchable substrate and including a plurality of electrodes,
an OLED electrically connected to the TFT and including a
plurality of electrodes, and a plurality of interconnection
lines connected to the electrodes of the OLED and the TFT.
At least one of the interconnection lines is configured to
move in a stretching direction and rotate an electrode
selected from the electrodes of the OLED and the TFT
connected to the at least one interconnection line.

30 Claims, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,698,205 B2 7/2017 Jeong et al.
9,786,861 B2 10/2017 Kim et al.
2011/0316803 A1 12/2011 Kim
2013/0041235 A1 2/2013 Rogers et al.
2014/0138635 A1 5/2014 Lee et al.

FOREIGN PATENT DOCUMENTS

KR 10-2001-0103431 11/2001
KR 10-2001-0103431 A 11/2001
KR 10-2012-0001406 1/2012
KR 10-2012-0001406 A 1/2012
KR 10-2014-0063306 5/2014
KR 10-2014-0063306 A 5/2014

* cited by examiner

FIG. 1




FIG. 2




FIG. 4A




FIG. 4B




FIG. 4C





FIG. 4D



ORGANIC LIGHT-EMITTING DIODE DISPLAY APPARATUS

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

RELATED APPLICATION

[This application is a continuation of U.S. patent application Ser. No. 14/625,472, filed Feb. 18, 2015, which claims priority under 35 U.S.C. §119 to Korean Patent Application No. 10-2014-0142768, filed on Oct. 21, 2014, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.] *This is a reissue application from U.S. Pat. No. 9,698,205, issued on Jul. 4, 2017, which is a continuation of U.S. patent application Ser. No. 14/625,472, filed Feb. 18, 2015, which claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2014-0142768, filed on Oct. 21, 2014, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.*

BACKGROUND

Field

The described technology generally relates to a stretchable organic light-emitting diode display.

Description of the Related Technology

In general, an organic light-emitting diode (OLED) display includes a thin film transistor (TFT) and an OLED. It also has a structure in which the OLED receives a driving signal from the TFT and emits light to produce a desired image.

The TFT has a structure in which an active region, a gate electrode, a source electrode, and a drain electrode are stacked on a substrate. Accordingly, when current is supplied to the gate electrode through an interconnection line formed on the substrate, current flows through the source electrode and the drain electrode via the active layer, and at the same time, current flows through a pixel electrode of the OLED, which is connected to the drain electrode.

The OLED includes the pixel electrode, an opposite electrode that is opposite to the pixel electrode, and an emission layer interposed between the pixel electrode and the opposite electrode. In such a structure, when current flows through the pixel electrode via the TFT as described above, an appropriate voltage is formed between the opposite electrode and the pixel electrode, and thus, an image is produced while light is emitted from the emission layer.

Recently, there have been increased attempts to form an OLED display having a flexible structure that is stretchable.

SUMMARY OF CERTAIN INVENTIVE ASPECTS

One inventive aspect is a stretchable OLED display.

Another aspect is an OLED display that includes: a stretchable substrate; a thin film transistor formed on the stretchable substrate; an OLED connected to the thin film transistor; and interconnection lines connected to electrodes of the OLED and thin film transistors, wherein at least one

of the interconnection lines moves in a stretching direction and rotates an electrode connected to the at least one interconnection line.

The at least one interconnection line can be connected to a corner portion of the electrode.

The least one interconnection line connected to the corner portion of the electrode can include a bent portion that can be straightened when the stretchable substrate is stretched.

The thin film transistor can include an active layer, a gate electrode, a source electrode, and a drain electrode, and the OLED can include a pixel electrode, an emission layer, and an opposite electrode.

The electrode having the corner portion connected to the least one interconnection line can be any one selected from the pixel electrode, the gate electrode, the source electrode, the drain electrode, and the opposite electrode.

The electrode can have four corners, and interconnection lines can be respectively connected to the four corners.

Another aspect is an organic light-emitting diode (OLED) display comprising a stretchable substrate, a thin film transistor (TFT) formed over the stretchable substrate and including a plurality of electrodes, an OLED electrically connected to the TFT and including a plurality of electrodes, and a plurality of interconnection lines connected to the electrodes of the OLED and the TFT. At least one of the interconnection lines is configured to move in a stretching direction and rotate an electrode selected from the electrodes of the OLED and the TFT connected to the at least one interconnection line.

In the above OLED display, the at least one interconnection line is connected to a corner portion of the selected electrode.

In the above OLED display, the least one interconnection line comprises a bent portion configured to be straightened when the stretchable substrate is stretched.

In the above OLED display, the TFT comprises an active layer, a gate electrode, a source electrode, and a drain electrode, wherein the OLED comprises a pixel electrode, an emission layer, and an opposite electrode.

In the above OLED display, the selected electrode includes at least one of the pixel electrode, the gate electrode, the source electrode, the drain electrode, and the opposite electrode.

In the above OLED display, the selected electrode has four corners, wherein the interconnection lines are respectively connected to the four corners.

Another aspect is an organic light-emitting diode (OLED) display comprising an elastic substrate, an OLED formed over the substrate and including a plurality of electrodes, and a plurality of first interconnection lines each having a plurality of bent portions and a plurality of substantially straight portions connected to the bent portions. One of the bent portions is connected to a first electrode selected from the OLED electrodes, wherein one end of the interconnection lines is configured to be pulled away from the first selected electrode so as to rotate the first selected electrode.

In the above OLED display, the substantially straight portions are substantially parallel to each other.

The above OLED display further comprises a thin film transistor (TFT) formed over the OLED and including a plurality of electrodes. The above OLED display further comprises a plurality of second interconnection lines each having a plurality of bent portions and a plurality of substantially straight portions connected to the bent portions, wherein one of the bent portions is connected to a second electrode selected from the TFT electrodes, and wherein one end of the second interconnection lines is configured to be

pulled away from the second selected electrode so as to rotate the second selected electrode.

In the above OLED display, the substantially straight portions are substantially parallel to each other,

In the above OLED display, each of the first and second interconnection lines is respectively connected to corner portions of the first and second electrodes.

In the above OLED display, the bent portions are configured to be straightened when the substrate is stretched.

In the above OLED display, the first selected electrode includes one of a pixel electrode and an opposite electrode.

In the above OLED display, the second selected electrode includes one of a gate electrode, a source electrode, and a drain electrode.

In the above OLED display, each of the first and second selected electrodes has four corner portions, wherein the interconnection lines are respectively connected to the four corners.

In the above OLED display, the first interconnection lines have a substantially zigzag shape.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a cross-sectional view illustrating a structure of an OLED display according to an embodiment.

FIG. 2 is a diagram illustrating an interconnection structure of a pixel electrode in the OLED display of FIG. 1.

FIG. 3 is a diagram illustrating a form in which the interconnection structure of FIG. 2 is modified during the stretching of the OLED display of FIG. 1.

FIG. 4A through 4D are diagrams illustrating cases in which the interconnection structure of FIG. 2 is applied to other electrodes.

DETAILED DESCRIPTION OF CERTAIN INVENTIVE EMBODIMENTS

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In this regard, the present embodiments can have different forms and should not be construed as being limited to the descriptions set forth herein. Accordingly, the embodiments are merely described below, by referring to the figures, to explain aspects of the present description.

In the accompanying drawings, those components that are the same or are in correspondence are rendered the same reference numeral regardless of the figure number, and redundant explanations are omitted.

Throughout the specification, a singular form can include plural forms, unless there is a particular description contrary thereto.

Throughout the specification, it will be further understood that the terms “comprises” and/or “comprising” used herein specify the presence of stated features or components, but do not preclude the presence or addition of one or more other features or components.

Throughout the specification, it will be understood that when a layer, region, or component is referred to as being “formed on,” another layer, region, or component, it can be directly or indirectly formed on the other layer, region, or component. That is, for example, intervening layers, regions, or components can be present.

In the drawings, for convenience of description, the thicknesses or sizes of elements are exaggerated for clarity, but one or more embodiments of the present invention are not limited thereto.

Also, it should also be noted that in some alternative implementations, the steps of all methods described herein can occur out of the order. For example, two steps illustrated in succession can in fact be executed substantially concurrently or the two steps can sometimes be executed in the reverse order. In this disclosure, the term “substantially” includes the meanings of completely, almost completely or to any significant degree under some applications and in accordance with those skilled in the art. Moreover, “formed on” can also mean “formed over.” The term “connected” can include an electrical connection.

FIG. 1 is a schematic cross-sectional view illustrating a portion of a stretchable OLED display according to an embodiment.

As illustrated in FIG. 1, the stretchable OLED display has a structure in which a TFT and an OLED EL are formed on a buffer layer 11 of a substrate 10. The substrate 10 is formed of a stretchable ductile material or elastic material.

The TFT includes an active layer 21, a gate electrode 20, a source electrode 27, and a drain electrode 29. The gate electrode 20 includes a lower gate electrode 23 and an upper gate electrode 25. The lower gate electrode 23 is formed of a transparent conductive material. The upper gate electrode 25 is formed of a metal material. A gate insulating layer 15 is interposed between the gate electrode 20 and the active layer 21 to insulate the gate electrode 20 from the active layer 21. In addition, source and drain regions, in which high concentration impurities are implanted, are formed at both edges of the active layer 21. The source electrode 27 and the drain electrode 29 are respectively connected to the source region and the drain region.

The active layer 21 can be formed of an oxide semiconductor. For example, the oxide semiconductor is formed of an oxide of a Group 12, 13, or 14 metal element, such as zinc (Zn), indium (In), gallium (Ga), tin (Sn), cadmium (Cd), germanium (Ge), or hafnium (Hf), and a material selected from combinations thereof. For example, the active layer 21 includes $G-I-Z-O[(In_2O_3)_a(Ga_2O_3)_b(ZnO)_c]$ (where a, b, and c are real numbers that respectively satisfy conditions of $a \geq 0$, $b \geq 0$, and $c > 0$).

The OLED EL includes a pixel electrode 31 connected to the drain electrode 29 of the TFT, an opposite electrode 35 functioning as a cathode, and an emission layer 33 interposed between the pixel electrode 31 and the opposite electrode 35. Reference numeral 50 denotes an interlayer insulating layer, and reference numeral 55 denotes a pixel-defining layer defining a pixel region.

A hole injection layer (HIL), a hole transport layer (HTL), an electron transport layer (ETL), and an electron injection layer (EIL) can be stacked adjacent to the emission layer 33.

The emission layer 33 can be separately formed for each pixel so that pixels emitting red light, green light, and blue light can be included in one unit pixel. The emission layer 33 can also be formed in common throughout the entire pixel region regardless of the positions of the pixels. Here, the emission layer 33 can have a structure in which layers formed of emission materials for emitting red light, green light, and blue light are stacked or the emission materials are combined. A combination of other colors can also be possible, provided that the combination of other colors can emit white light. Also, the emission layer 33 can further include a color conversion layer or a color filter that converts the emitted white light into a predetermined color.

The substrate 10 can be formed of a flexible material that is stretchable, as described above. For example, the substrate 10 is formed of a material such as polydimethylsiloxane

5

(PDMS). Accordingly, the substrate **10** is stretchable when pulling the substrate **10** in a plane direction.

However, in some embodiments, when interconnection lines formed in the OLED EL or the TFT are cut when pulling the substrate **10** to stretch the substrate **10**, a display operation is not normally performed. Accordingly, in the current embodiment, a structure, as shown in FIG. **2**, is provided as an interconnection structure for preventing such a problem.

The OLED display includes a great number of electrodes, such as the pixel electrode **31**, the opposite electrode **35**, the gate electrode **20**, the source electrode **27**, and the drain electrode **29**. The OLED display also includes many interconnection lines formed in the OLED display to electrically connect the electrodes to each other. In FIG. **2**, an interconnection structure of the pixel electrode **31** is illustrated as an example.

FIG. **2** is a plan view of the pixel electrode **31** and interconnection lines **61** connected to the pixel electrode **31** illustrated in FIG. **1**. The interconnection lines **61** connect the pixel electrode **31** to the drain electrode **29**.

Each of the interconnection lines **61** is not formed as a straight line but a shape having a tortuously curved bent portion **61a**. The bent portion **61a** is straightened into a substantially straight line (refer to FIG. **3**) when stretching the substrate **10** such that the interconnection lines are pulled away from the pixel electrode **31**, and thus, the cutting of the interconnection lines **61** is suppressed. For example, if each of the interconnection lines **61** is a substantially straight line in a contraction state of the substrate **10** when there is no slack in the interconnection lines **61**, cracks or cutting of the interconnection lines **61** occurs in the interconnection lines **61** when stretching the substrate **10**. However, when the bent portion **61a** is included in each of the interconnection lines **61**, like in the current embodiment, it is possible to prevent cracks or cutting of the interconnection lines **61**, when stretching the substrate **10**, since the interconnection lines **61** have a sufficient length margin.

Furthermore, the interconnection lines **61** are respectively connected to four corner portions of the pixel electrode **31** to increase the amount of stretching of the substrate **10** while suppressing risk of damaging the interconnection lines **61**. For example, when the interconnection lines **61** are connected to the four corner portions of the pixel electrode **31**, the pixel electrode **31** is slightly rotated as illustrated in FIG. **3** while the interconnection lines **61** are substantially straightened when stretching the substrate **10**. When the stretching of the substrate **10** is performed in the direction of the arrow F, the interconnection lines **61** move while being straightened into straighter lines along a stretching direction. Accordingly, a turning force acts on the pixel electrode **31** connected to the interconnection lines **61** and the corner portions, and thus, the pixel electrode **31** is slightly rotated in the direction of the arrow R. As a result, the interconnection lines **61** can have a margin to move farther in the stretching direction (the direction of the arrow F) by as much as the pixel electrode **31** is rotated, and thus, the amount of stretching of the substrate **10** can be increased while damage to the interconnection lines **61** is suppressed.

An operation of stretching the OLED display is as follows. When the substrate **10** is pulled and stretched in the direction of the arrow F which is a plane direction, as shown in FIG. **3**, the interconnection lines **61** each having the bent portion **61a** are straightened into straighter lines and, at the same time, the pixel electrode **31** is rotated in the direction of the arrow R.

6

Accordingly, the interconnection lines **61** can be stretched by a sufficient amount without receiving stress due to the modification of the bent portion **61a** and the rotation of the pixel electrode **31**. Therefore, an OLED display that is able to be stretched a large amount can be implemented.

Although the interconnection lines **61** connected to the pixel electrode **31** are described as an example in the current embodiment, the same interconnection structure can be applied to other electrodes, as illustrated in FIGS. **4A** through **4D**.

As illustrated in FIG. **4A**, interconnection lines **62** each having a bent portion **62a** are connected to corners of a gate electrode **20**. As illustrated in FIG. **4B**, interconnection lines **63** each having a bent portion **63a** are connected to corners of a source electrode **27**. As illustrated in FIG. **4C**, interconnection lines **64** each having a bent portion **64a** are connected to corners of a drain electrode **29**. As illustrated in FIG. **4D**, interconnection lines **65** each having a bent portion **65a** are connected to corners of an opposite electrode **35**. Accordingly, when the substrate **10** is stretched, the bent portions **62a**, **63a**, **64a**, and **65a** can be straightened and the gate, source, drain, and opposite electrodes **20**, **27**, **29**, and **35** can be rotated. Thus, a safe and sufficient amount of stretching can be obtained, similar to the case described above.

In addition, although the gate, source, drain, and opposite electrodes **20**, **27**, **29**, and **35** of FIGS. **4A** through **4D** have tetragonal shapes and interconnection lines are connected to corner portions of the electrodes **20**, **27**, **29**, and **35**, the described technology is not limited thereto. For example, if turning forces act on the electrodes **20**, **27**, **29**, and **35** according to a movement of the interconnection lines in a stretching direction, the same effect can be obtained even if the electrodes **20**, **27**, **29**, and **35** have other shapes. For example, each of the electrodes **20**, **27**, **29**, and **35** has a different polygonal shape having a different number of vertices than that of a tetragon.

In addition, as well as vertices, the corner portions can be portions adjacent to the vertices, which allow the electrodes **20**, **27**, **29**, and **35**, to be rotated when pulling the interconnection lines.

As described above, in the OLED display according to the one or more of the above exemplary embodiments, interconnection lines are straightened during the stretching of the OLED display and an electrode connected to the interconnection lines is rotated, and thus, the amount of stretching can be considerably increased. Accordingly, when the OLED display according to the one or more of the above exemplary embodiments is used, a product having a very excellent stretching capability can be implemented.

It should be understood that the exemplary embodiments described therein should be considered in a descriptive sense only and not for purposes of limitation. Descriptions of features or aspects within each exemplary embodiment should typically be considered as available for other similar features or aspects in other exemplary embodiments.

While the inventive technology has been described with reference to the figures, it will be understood by those of ordinary skill in the art that various changes in form and details can be made therein without departing from the spirit and scope as defined by the following claims.

What is claimed is:

1. An organic light-emitting diode (OLED) display apparatus comprising:

7

a stretchable substrate;
 a thin film transistor (TFT) over the stretchable substrate
 and comprising a plurality of electrodes *over the stretchable substrate*;
 an OLED electrically connected to the TFT and including
 a plurality of electrodes; and
 a plurality of interconnection lines connected to [a corner
 portion of one selected from among] the plurality of
 electrodes of the OLED and the plurality of electrodes
 of the TFT,

wherein *at least one of the* [selected electrode has at least
 four corners, and the] interconnection lines [are respec-
 tively connected to the four corners, and wherein the
 interconnection lines and the selected electrode are] *is*
 movable in a stretching direction, *and*

wherein at least one of the electrodes of the plurality of
electrodes of the OLED and the plurality of electrodes
of the TFT is rotatable in a first direction with respect
to the stretchable substrate when the stretchable sub-
strate is stretched in a second direction.

2. The OLED display apparatus of claim 1, wherein [a
 selected electrode is rotatable] *the at least one interconnec-*
tion line is connected to a corner portion of the at least one
of the electrodes of the plurality of electrodes of the OLED
and the plurality of electrodes of the TFT.

3. The OLED display apparatus of claim [1] 2, wherein
 the [selected electrode has a square shape] *at least one*
interconnection line comprises a bent portion configured to
be straightened when the stretchable substrate is stretched.

4. The OLED display apparatus of claim [3] 2, wherein
 the [interconnection lines connected to opposite corners of
 the selected electrode are stretchable opposite to each other]
at least one of the electrodes of the plurality of electrodes of
the OLED and the plurality of electrodes of the TFT has four
corners, and

wherein the interconnection lines are respectively con-
nected to the four corners.

5. [The] An OLED display [of claim 4, wherein the
 interconnection lines connected to the four corners are
 arranged at a regular interval of 90 degrees] apparatus

comprising:
an elastic substrate;

a plurality of electrodes; and

a plurality of first interconnection lines each having a
plurality of bent portions and a plurality of substan-
tially straight portions connected to the bent portions,
wherein one of the bent portions is connected to a first
electrode selected from the electrodes, and

wherein one end of the first interconnection lines is
movable away from the first selected electrode so as to
rotate the first selected electrode.

6. The OLED display apparatus of claim [3] 5, wherein
 the [interconnection lines are respectively connected to four
 corners of the selected electrode of the square shape and
 extended to outside the selected electrode from the four
 corners, and directions in which the interconnection lines
 extend are not in parallel with a center line between two
 facing sides of the selected electrode of the square shape]
substantially straight portions are substantially parallel to
each other.

7. The OLED display apparatus of claim 6, wherein the
 [interconnection lines connected to the four corners each
 extends from one of two facing sides of the electrode of the
 square shape toward the other of the two facing sides while
 forming an entirely whirlwind shape] *first interconnec-*
tion lines are respectively connected to corner portions of the
electrodes.

8

8. The OLED display apparatus of claim [7] 6, wherein
 the [whirlwind shape is made in a clockwise direction or in
 a counter-clockwise direction] *bent portions are configured*
be straightened when the elastic substrate is stretched.

9. The OLED display apparatus of claim [1] 6, wherein
 the [interconnection lines comprise a bent portion config-
 ured to be straightened when the stretchable substrate is
 stretched] *first selected electrode has four corner portions,*
and

wherein the first interconnection lines are respectively
connected to the four corner portions.

10. The OLED display apparatus of claim [1] 6, wherein
 the [TFT comprises an active layer, a gate electrode, a source
 electrode, and a drain electrode, and wherein the OLED
 comprises a pixel electrode, an emission layer, and an
 opposite electrode] *first interconnection lines have a sub-*
stantially zigzag shape.

11. The OLED display apparatus of claim [10] 5, wherein
 [the selected electrode includes the pixel electrode] *two or*
more of the first interconnection lines are movable in a
stretching direction for the elastic substrate.

12. [The] An OLED display [of claim 10, wherein the
 selected electrode includes the gate electrode] apparatus

comprising:

a stretchable substrate;

a plurality of electrodes over the stretchable substrate;
and

a plurality of interconnection lines directly connected to
a corner portion of one selected from among the
plurality of electrodes,

wherein the selected electrode has at least four corners,
the interconnection lines are respectively directly con-
nected to the four corners, and the interconnection
lines and the selected electrode are movable in a
stretching direction.

13. The OLED display apparatus of claim [10] 12,
 wherein the selected electrode [includes the source elec-
 trode] *is rotatable.*

14. The OLED display apparatus of claim [10] 12,
 wherein the selected electrode [includes the drain electrode]
has a square shape.

15. The OLED display apparatus of claim [10] 14,
 wherein the [selected electrode includes the opposite elec-
 trode] *interconnection lines connected to opposite corners of*
the selected electrode are stretchable opposite to each other.

16. The OLED display apparatus of claim 15, wherein the
 interconnection lines connected to the four corners are
 arranged at a regular interval of 90 degrees.

17. The OLED display apparatus of claim 14, wherein the
 interconnection lines are respectively connect to four cor-
 ners of the selected electrode of the square shape and
 extended to outside the selected electrode from the four
 corners, and directions in which the interconnection lines
 extend are not in parallel with a center line between two
 facing sides of the selected electrode of the square shape.

18. The OLED display apparatus of claim 17, wherein the
 interconnection lines connected to the four corners each
 extend from one of two facing sides of the electrode of the
 square shape toward the other of the two facing sides while
 forming an entirely whirlwind shape.

19. The display apparatus of claim 18, wherein the
 whirlwind shape is made in a clockwise direction or in a
 counter-clockwise direction.

20. The display apparatus of claim 12, wherein the
 interconnection lines comprise a bent portion configured to
 be straightened when the stretchable substrate is stretched.

21. An OLED display apparatus comprising:
 a stretchable substrate;
 a unit pixel over the stretchable substrate and including
 a plurality of emission layers configured to respectively
 emit light; and
 a plurality of interconnection lines directly connected to
 a corner portion of the unit pixel,
 wherein the unit pixel has at least four corners, and
 wherein the interconnection lines are respectively directly
 connected to the four corners.

22. The OLED display apparatus of claim 21, wherein the
 interconnection lines are movable in a stretching direction.

23. The OLED display apparatus of claim 21, wherein the
 unit pixel is rotatable.

24. The OLED display apparatus of claim 21, wherein the
 unit pixel has a square shape.

25. The OLED display apparatus of claim 24, wherein the
 interconnection lines connected to opposite corners of the
 unit pixel are stretchable opposite to each other.

26. The OLED display apparatus of claim 25, wherein the
 interconnection lines connected to the four corners are
 arranged at a regular interval of 90 degrees.

27. The OLED display apparatus of claim 24, wherein the
 interconnection lines are respectively connected to four
 corners of the unit pixel of the square shape and extended to
 outside the unit pixel from the four corners, and directions
 in which the interconnection lines extend are not in parallel
 with a center line between two facing sides of the unit pixel
 of the square shape.

28. The OLED display apparatus of claim 27, wherein the
 interconnection lines connected to the four corners each
 extend from one of two facing sides of the unit pixel of the
 square shape toward the other of the two facing sides while
 forming an entirely whirlwind shape.

29. The OLED display apparatus of claim 28, wherein the
 whirlwind shape is made in a clockwise direction or in a
 counter-clockwise direction.

30. The OLED display apparatus of claim 21, wherein the
 interconnection lines comprise a bent portion configured to
 be straightened when the stretchable substrate is stretched.

* * * * *