

US00RE48981E

(19) United States

(12) Reissued Patent

Taneichi

(10) Patent Number: US RE48,981 E

(45) Date of Reissued Patent: Mar. 22, 2022

(54) THRUST NUT

(71) Applicant: Simpson Strong-Tie Company Inc.,

Pleasanton, CA (US)

(72) Inventor: Kaoru Taneichi, Atsugi (JP)

(73) Assignee: Simpson Strong-Tie Company Inc.,

Pleasanton, CA (US)

(21) Appl. No.: 15/789,927

(22) Filed: Oct. 20, 2017

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: 9,163,655

Issued: Oct. 20, 2015

Appl. No.: 14/154,537

Filed: Jan. 14, 2014

(51) **Int. Cl.**

F16B 37/08 (2006.01) F16B 43/00 (2006.01)

(52) U.S. Cl.

CPC *F16B 37/0807* (2013.01); *F16B 37/0857* (2013.01); *F16B 43/00* (2013.01)

(58) Field of Classification Search

(56) References Cited

U.S. PATENT DOCUMENTS

179,994 A	7/1876	Brallier
487,721 A	12/1891	De Kalb
518,165 A	4/1894	Thalaker
560,554 A	12/1895	Wiestner
573.452 A	12/1896	Delahunt

582,424 A	12/1896	Hunt
581,551 A	4/1897	Green
601,249 A	3/1898	Geise
807,021 A	12/1905	Falk
856,868 A	6/1907	Heffner
901,681 A	10/1908	Collet
991,517 A	5/1911	Kennedy
	(Con	tinued)

FOREIGN PATENT DOCUMENTS

CA	2313735	3/2001
CA	2364582	2/2010
	(Cor	ntinued)

OTHER PUBLICATIONS


US 5,961,265 A, 10/1999, Kato (withdrawn) (Continued)

Primary Examiner — William C Doerrler (74) Attorney, Agent, or Firm — James R. Cypher; Charles R. Cypher

(57) ABSTRACT

A nut main body has a slanted hole with a smaller inner end portion having a plurality of stepped portions of differing height. This gives the slanted hole a differing depth relative to a large-diameter end portion of the slanted hole at a plurality of locations about a circumference of the slanted hole. A plurality of nut segments are slidable within the slanted hole and come into contact with at least one of the stepped portions. The nut segments have screw threads at an inner wall surface. A washer is provided at a large-diameter side of the plurality of nut segments. A bias spring is attached within the nut main body so as to urge the plurality of nut segments towards the small-diameter side of the nut main body with the washer therebetween. A stopper piece holds the bias spring within the nut main body.

20 Claims, 20 Drawing Sheets



US RE48,981 E Page 2

(56)		Referen	ices Cited	,	479,897			Holthofer	
	TIC	DATENIT	DOCUMENTS		509,670 514 917			Boll et al. Merrill, Sr.	
	U.S.	PAIENI	DOCUMENTS	•	•			Luebkeman	
1.00	5,227 A	10/1911	Iones	,	540,762		11/1970		
,	,	2/1912		,	579,938			Hanson	
,	5,562 A		Kennedy	,	,			Herbenar	
1,07	2,361 A		Rickman	,	,		9/1972		
· · · · · · · · · · · · · · · · · · ·	5,765 A		Brooks	,	695,139 722,165		10/1972 3/1073	Forsberg et al.	
,	4,189 A		Keator	•	742,809			Zifferer	
,	,	6/1920	Ellis et al. Lovekin	,	724,151			Kaywood	
,	4,713 A	4/1921		•	728,933		4/1973	-	
,	5,028 A	11/1922		_ ′	769,774				
/	7,515 A	3/1923		/	764,157			LeBlanc Minutali et al	
· · · · · · · · · · · · · · · · · · ·	9,348 A		Botscheller	/	797,336			Minutoli et al. Howe	
/	9,307 A 7,543 A		Svebili Schaefer	•	798,866			Werstein	
,	6,978 A	2/1930		/	842,709		10/1974		
,	7,296 A		Woodruff		843,080			Imai et al.	
1,91	8,378 A	7/1933	Burnham	,	844,137		10/1974	•	
,	0,545 A	12/1933		,	850,535 861 814		1/19/4	Howlett et al.	
,	3,354 A		Holland-Letz	/	867,804				
,	6,780 A 1 051 A	7/1934 11/1935	Desbrueres	,	870,332		3/1975		
,	6,541 A		Schenk	,	878,757			Puklus, Jr.	
,	3,601 A			,	884,004			Douma et al.	
/	4,756 A	9/1940		/	889,916 896,599			Ilukowicz Werstein et al.	
,	1,537 A	11/1941		/	927,497			Yoshinaga et al.	
,	4,480 A 4,745 A	12/1941 9/1942		,	935,685			Howlett	
,	6,401 A		Haskell	/	948,141		4/1976	5	
2,36	7,480 A	1/1945	Beswick	,	960,047		6/1976		
/	5,889 A		Kennedy	,	000,591 000,681			Courtois Coldren	
/	9,846 A 6,579 A		Gilman Donovan		007,563			Nakagawa	
,	7,560 A		Widmer	4,	007,564	A		Chisholm	
,	5,815 A			· · · · · · · · · · · · · · · · · · ·	011,397			Bouche	
,	9,625 A		Johnson	•	020,734 037,516		5/1977 7/1977		
,	0,844 A		Shemorry	,	047,463			Coldren	
,	5,812 A 7,788 A	8/1954	Dmitroff Rapp	/	055,875			Strickland	
•	9,987 A		Berger	,	083,162		4/1978	•	
,	0,682 A		Passman	•	083,393		4/1978		
/	2,560 A		Neptune	· · · · · · · · · · · · · · · · · · ·	117,643			Lamothe McSherry et al.	
,	6,496 A 1,794 A	2/1962	Jansen Knox	· · · · · · · · · · · · · · · · · · ·	146,951			Howlett	
,	2,161 A	7/1962		/	149,446			Spengler	
3,08	8,784 A		Melton et al.	,	157,876			Digiulio	
/	4,645 A		Harrison	,	169,569 172,606		10/19/9	Riegler et al.	
,	5,804 A 8,681 A	12/1963 1/1964		,	195,709			Gianotti et al.	
,	,		Zahodiakin F16B 5/0208	•	•			Ellman et al.	
,	,		411/267	,	,			Erickson et al.	
3,15	1,653 A *	10/1964	Zahodfakin F16B 5/0208	/	250,681			Helderman Cornwall	
		404054	411/267		261,598 271,654			Jungbluth	
,	3,333 A 7,215 A		Chisholm Zahodiakin	/	286,482			Marsch	
,	7,213 A 7,966 A		Shelburne	· · · · · · · · · · · · · · · · · · ·	287,807			Pacharis et al.	
,	0,188 A	12/1964		· · · · · · · · · · · · · · · · · · ·	325,575			Holt et al.	D25D 27/14
,	1,174 A		Harrison	4,	303,104	A	12/1982	Okada	29/270
/	4,386 A	3/1965		4.	370,018	A	1/1983	Lane	23/2/0
,	7,621 A 9,373 A		Turner Sutliff	· · · · · · · · · · · · · · · · · · ·	378,187			Fullerton	
/	4,591 A	12/1965		·	403,561			Schaeflern et al.	
•	6,144 A		•	,	,		10/1983		
,	5,120 A			,	445,303		2/1984 5/1984	Judkins	
,	6,154 A 5,175 A	2/1967 6/1967		/	479,747		10/1984		
,	,	6/1967 11/1967	Schertz F16B 37/0864	4,	509,724	A	4/1985	Okada	
2,20	,		411/270	,	604,014		8/1986		
,	2,523 A	3/1968		<i>'</i>	650,276			Lanzisera et al.	
,	8,891 A	4/1968		<i>'</i>	665,672 684,284			Commins Bradley, Jr.	
/	1,514 A 9,092 A	7/1968 2/1969	Hall Perry et al.	,	701,065		10/1987		
,	0,334 A		Blomstrand	<i>'</i>	703,711		11/1987		
3,44	3,351 A	5/1969	Kumazawa	,	,	A	11/1987	Terry	
•	9,492 A	9/1969		•	720,223			Neights	
5,47	6,010 A	11/1969	магкеу	4,	720,561	A	2/1988	Worzala, Jr.	

US RE48,981 E Page 3

(56)		Referen	ces Cited	5,575,129 A	11/1996	
	ΠS	DATENT	DOCUMENTS	5,582,496 A 5,605,423 A	2/1990	Ambrico Janusz
	0.5.		DOCOMENTS	5,606,839 A		Baumann
4,729,70	03 A	3/1988	Sato	5,628,161 A	5/1997	Giannuzzi et al.
4,761,86		8/1988		5,632,129 A	5/1997	Imai et al.
4,801,2			Everman	5,641,256 A	6/1997	
4,812,09	96 A	3/1989	Peterson	5,649,798 A	7/1997	
4,823,5		4/1989		5,653,078 A 5,653,563 A		Kies et al. Ernst et al.
4,848,4		7/1989	±	5,661,935 A		Erickson et al.
4,850,7° 4,875,3		10/1989	Lawrence et al.	5,664,389 A		Williams
			Calmettes	5,667,181 A		Van Leeuwen et al.
, ,			Commins	5,678,375 A	10/1997	
4,909,0			Thompson, Jr. et al.	5,704,572 A	1/1998	\mathbf{c}
4,911,7			Warkentin	5,718,090 A		Wei-Hwang
4,919,13			Kohlenbrenner	5,722,645 A 5,729,952 A	3/1998 3/1998	
4,922,7			Campbell	5,723,932 A 5,733,084 A		Fullerton
4,930,9 4,936,8			Jagelid Sohngen	5,740,651 A		Vanotti
4,945,7			Brown, Jr.	5,743,670 A	4/1998	Adler
4,954,0		9/1990		5,746,556 A	5/1998	
4,974,8	88 A	12/1990	Childers	5,769,581 A		Wallace
4,979,8		12/1990	•	· · · · · · · · · · · · · · · · · · ·		Lins et al. Ramirez
5,015,13		5/1991		5,782,048 A 5,809,719 A		Ashton et al.
5,015,13 5,048,2		5/1991		, ,		Williams
5,048,24 5,050,34		9/1991 9/1991	Johnson et al.	5,816,762 A		
5,056,76			Mochizuki	5,819,484 A	10/1998	Kar
5,067,8			Bowner et al.	5,829,531 A		
5,081,8	11 A	1/1992	Sasaki	5,839,321 A		
, ,		2/1992		5,885,034 A 5,906,361 A		Fergusson Carranza
5,090,8		2/1992	•	5,900,301 A 5,921,042 A		Ashton et al.
5,100,2°		3/1992 6/1992	Schirrmacher Wright	· · · · · · · · · · · · · · · · · · ·	8/1999	
			Lubreski F16B 37/0857	5,937,609 A	8/1999	
5,155,5		0, 1332	411/267	5,944,467 A	8/1999	
5,168,6	81 A	12/1992	Ayrapetyan	5,957,644 A		Vaughan
5,180,26			Richardson			Lancelot, III
5,197,1		3/1993		5,979,130 A 5,987,828 A		
5,199,83		4/1993		5,988,965 A		•
5,205,69 5,207,5		4/1993 5/1003		5,992,126 A		
5,207,5 ⁴ 5,228,2		5/1993 7/1993	Kirma Kesselman	, ,		Taneichi E04B 1/2604
5,249,4		10/1993				411/267
5,254,0		10/1993		6,019,556 A	2/2000	
5,261,19			McMillan	, ,		Locke et al.
/		11/1993		6,062,784 A 6,068,250 A		Wisser et al. Hawkins
5,308,13 5,316,3		5/1994		, ,	6/2000	
5,316,3 5,324,1		5/1994 6/1994		6,079,179 A		<u> </u>
/ /			Weddendorf F16B 37/0864	6,099,196 A	8/2000	Lancelot, III
- , ,-			411/267	* *		Ashton et al.
5,340,2	58 A	8/1994	Simon	, , , , , , , , , , , , , , , , , , ,	9/2000	
5,347,7			Kobori et al.	, ,	10/2000	Leek et al.
5,347,7		9/1994			11/2000	<u> </u>
5,364,2 5,365,7		11/1994 11/1994	Steinmetz et al.			Ashton et al.
5,370,4		12/1994		6,158,188 A	12/2000	Shahnazarian
5,375,3		12/1994		· · · · · · · · · · · · · · · · · · ·		Cornett, Sr. et al.
5,378,10	00 A	1/1995	Fullerton			Espinosa
5,379,50		1/1995		6,167,785 B1 6,168,455 B1	1/2001	Hussaini
5,384,99		1/1995		6,176,051 B1		
5,386,74 5,398,4		2/1995 3/1995	•	6,192,647 B1	2/2001	
5,336, 4 5,411,3			Bowmer et al.	6,195,949 B1	3/2001	Schuyler
5,427,4			Fullerton et al.			Thompson et al.
5,428,9		7/1995		6,244,806 B1	6/2001	
5,466,0		11/1995		6,250,041 B1		Seccombe Babcock et al
5,468,10		11/1995		6,256,960 B1 6,257,813 B1		Babcock et al. Tanimura
5,487,63 5,505,03		1/1996 4/1006		6,279,813 B1	8/2001	
5,505,03 5,522,63		4/1996 6/1996		6,282,994 B1	9/2001	
5,522,0		7/1996		, ,	10/2001	
5,535,50		7/1996				Bellinghausen et al.
5,540,5	30 A	7/1996	Fazekas	6,327,829 B1	12/2001	Taguchi
5,558,4		9/1996		6,327,831 B1		
5,568,7			Popp et al.	6,341,452 B1		Bollinghaus
5,570,5	49 A	11/1996	Lung et al.	6,350,093 B1	2/2002	retersen et al.

US RE48,981 E Page 4

(56)		Referer	ices Cited		,	,725 B2 ,412 B2		Oh et al.	
	U.S	. PATENT	DOCUMENTS		,	,019 B2		Espinosa	
						•	9/2013		
6,361,2			Schirrmacher		,	•	11/2013 1/2014		
6,367,2 6,389,7			Cornett, Sr. Lucey et al.		,	·	2/2014		
6,390,7			Commins		8,708	,629 B2	4/2014	Smith	
6,406,2	40 B1	6/2002	Potter		· ·	•	8/2014	-	
6,425,2			Ashton et al.			,478 B2 .777 B2	2/2014	Gray et al. Espinosa	
6,494,6 6,513,2		2/2002	Espinosa Leek		,	•	4/2015	-	
6,513,3			James			,452 B2		Espinosa	
6,546,6			Ashton et al.		· ·	,000 B2 ,001 B2		Espinosa Espinosa	
6,564,5 6,585,4			Lucey et al. Commins			,691 B2		Thompson	
6,625,9			Commins		9,188	,147 B2	11/2015	Smith	
6,679,0						,251 B2		Espinosa	
6,688,0 6,688,0			Espinosa Evers et al.			,073 B2 ,399 B2		Taneichi Espinosa	
6,712,5			Roopnarine	F16B 37/0857	,	,676 B2		. •	
,			ı	411/267	,	,677 B2		Espinosa	
6,745,6						,841 B2 ,706 B2		Allmon et al.	
6,773,0 6,773,1			Adoline et al. Copping			,530 B2		Espinosa	
6,826,8			Lucey et al.			,574 B2	9/2016	Espinosa	
6,854,9	44 B2	2/2005	Hoffmann et al.			,741 B2 ,139 B2		Espinosa	
6,860,6						,009 B2		Espinosa Espinosa	
6,880,4 6,904,7			Tanimura Stutts		,	,277 B2	3/2018	Oh	
6,925,7			Gregel et al.		,	,753 B2		Espinosa	
6,942,4			Unverzagt et al.		2002/0037	,557 B2 205 A1		Espinosa Taneichi	F16B 37/0857
6,951,0 6,959,9		10/2005	Espinosa Leaby		2002,000,	200 111	5,2002	1011010111	411/267
6,964,1					2002/0092			Nezigane	
7,007,4			Commins		2002/0094				
, ,		5/2006 10/2006	Commins		2002/0189 2003/0230			Lancelot et al. Shahnazarian	
/ /	30 B2		Ward et al.		2004/0096	5292 A1	5/2004	Duran et al.	
7,150,1	32 B2	12/2006	Commins					Giesel et al.	E16D 27/0964
·		1/2007	-		2005/0238	3460 A1	* 10/2005	L1	F16B 37/0864 411/432
		2/2007	Lucey et al. Mueller		2005/0284	057 A1	12/2005	Commins	711/732
7,287,3			Commins		2006/0133			Commins	
7,296,3					2006/0137 2008/0060				
7,316,5 $7,331.7$		1/2008 2/2008	Tanimura Giehl		2008/0000			Espinosa Spence et al.	
, ,		3/2008			2009/0226			±	F16B 37/0857
7,416,3			Virdee		2000/0252	0.65 4.1	11/2000	C'11	411/433
7,422,4 7,445,1			Kitamura et al. Gridley et al.		2009/0272 2010/0037				
			Adoline et al.		2011/0182				
7,509,7	78 B2	3/2009	Leek					White et al.	
, ,		4/2009			2013/0000 2016/0244		1/2013 8/2016	Espinosa Espinosa	
		11/2009	Lucey et al. Espinosa		2010/0244			Espinosa	
			Cloyd et al.		2017/0037		2/2017	Espinosa	
·		2/2010	<u>-</u>		2018/0135 2018/0187			Taneichi	
7,009,3 7,744,3		3/2010 6/2010	van Kijn Kaneichi		2019/0167			Espinosa	
7,752,8			Brown et al.		2019/0161			Espinosa	
7,762,0			Espinosa						
7,766,2 7,802,9		8/2010 9/2010	Titus, II et al. Parker			FORE	IGN PATE	NT DOCUMI	ENTS
7,891,6			Schroeder		СН	6	584648	11/1994	
7,905,0			Pryor et al.		DE)39822 A1	3/2011	
7,946,0 7,971,4			Hammer et al. Commins		EP		352542	1/1990	
8,051,6			Mathews et al.		EP EP		103734 536149	3/2004 1/2008	
8,112,9	55 B2	2/2012	Espinosa		FR		332745	6/1963	
8,132,7 8,136,3			Oh et al. Espinosa		GB	3	383460	11/1932	
8,136,3 8,186,9			Espinosa Espinosa		GB GB		558302 500430	12/1943 7/1947	
8,201,3	81 B2	6/2012	Heath		GB GB		590430 752272	7/1947 7/1956	
8,257,0					GB	9	901681	7/1962	
8,267,6 8,276,3			Noce et al. Mathews et al.		GB)99472	1/1968	
8,270,3					GB GB		384511 201216	2/1975 8/1988	
·			Commins et al.		GB		262583	6/1993	

(56) References Cited FOREIGN PATENT DOCUMENTS 3404708 9/2005

GB	2404708	9/2005
JP	46001521	1/1971
JP	59140604	9/1984
JP	62135703	8/1987
JP	2200936	8/1990
JP	476136	3/1992
JP	5230893	9/1993
JP	781325	8/1995
JP	9317030	12/1997
JP	1998-009244	1/1998
JP	2001214534	8/2001
JP	2002106535 A	4/2002
JP	2002168222 A	6/2002
JP	4201219	10/2008
JP	4201219 B	32 * 12/2008
JP	4531585	6/2010
JP	4531585 B	82 * 8/2010
JP	2010196355	9/2010
JP	201247244	3/2012
JP	201364415	4/2013
JP	2013234731	11/2013
JP	5912829	4/2016
SU	706586	12/1979
SU	796498	1/1981
WO	WO 1999/024724	5/1999
WO	WO 2004/002702	1/2004
WO	WO 2006/055905	5/2006
WO	WO 2008/016543	2/2008
WO	WO 2008/105045	9/2008
WO	WO 2008/124578	10/2008
WO	WO 2010/090736	8/2011
WO	WO 2010/090748	8/2011
WO	WO 2011/111087	9/2011
WO	WO 2011/150537	12/2011
WO	WO 2013/020027	2/2013

OTHER PUBLICATIONS

"Device Keeps Shear Walls Tight," magazine, published at least as early as May 2000, pp. 49-50, Circle Reader Service #1263, Rura Builder, Iola, WI.

"Inquest Engineering: Manufacturers of the Earthbound System: Redefining the state of the art in seismic holdown technology," brochure, published at least as early as Jan. 21, 1998, 4 pages, InQuest Engineering, L.L.C., Woodinville, WA.

Greenwood, Douglas C. ed., "Product Engineering Design Manual," manual, 1959, title and copyright page, pp. 90-97, 316-329, McGraw-Hill Book Company, Inc., New York, NY.

Richardson, Arthur B., "Declaration," legal document, Dec. 21, 2002, 7 pages, Mill Valley, CA; and Exhibits A-Q, 82 pages.

"Expansion Jack Washer," brochure, 1999, 1 page, Anchor Tiedown Systems, Inc., Mill Valley, CA and Burien, WA.

"Thru-Bolt Log Fastening System," webpage, 1999, 1 page, Heritage Log Homes, Kodak, TN.

"Earthbound Seismic Holdown System Using The 'Impasse Device'," evaluation report, Nov. 1, 1997, 6 pages, ER-5378, ICBO Evaluation Service, Inc., Whittier, CA.

"The Impasse Devise," webpage, 1997, 1 page, InQuest Engineering, Woodinville, WA.

"LocTite Automatic Self-Locking Nuts," brochure, Oct. 1992, 6 pages, LocTite, Kennesaw, GA.

"Auto Take-Up," webpage, 2000, 4 pages, Zone Four LLC, San Leandro, CA.

"AT Auto Take-Up," brochure, Mar. 28, 2001, 2 pages, Commins Manufacturing Inc., Friday Harbor, WA.

"ATS-Components," webpage, submitted Jun. 28, 2010, 2 pages, Simpson Strong-Tie Co., Inc., Pleasanton, CA.

Commins, Al. "Acceptance Criteria for Shrinkage Compensating Devices and Similar Devices," report draft, Dec. 9, 1999, 3 pages, Commins Design LLC, Friday Harbor, WA.

"Evaluation Report," report, Dec. 10, 1999, 5 pages, ER-XXX, ICBO Evaluation Services, Inc., Whittier, CA.

"AT Auto Take-Up," brochure, Jan. 3, 2000, 1 page, Commins Design LLC, Friday Harbor, WA.

"Our Solution to Wood Shrinkage Solves Shearwal Problems," brochure, Jan. 2000, 2 pages, Tech Note #1, Commins Design LLC, Friday Harbor, WA.

Commins, Alfred, "Shrinkage Compensator for Building Tiedowns," provision patent application, Sep. 24, 1999, 31 pages, U.S. Appl. No. 60/156,042, USA.

Commins, Alfred D., "Automatic Take-Up Device," disclosure, Feb. 10, 1997, 5 pages, Simpson Strong-Tie Company, Inc., Pleasanton, CA.

Commins, Alfred D., "Automatic Take-Up Device," disclosure, Aug. 15, 1996, 7 pages, Simpson Strong-Tie Company, Inc., Pleasanton, CA.

Commins, Alfred D., "Automatic Take-Up Device," disclosure, Mar. 6, 1996, 3 pages, Simpson Strong-Tie Company, Inc., Pleasanton, CA.

"Acceptance Criteria for Shrinkage Compensating Devices," evaluation report, 2005, 5 pages, AC316, ICC Evaluation Service, Inc., Whittier, CA.

Commins, Alfred D., "Automatic Take-Up Device," disclosure, Mar. 6, 1996 and Jan. 25, 1996, 5 pages, Simpson Strong-Tie Company, Inc., Pleasanton, CA.

Commins, Alfred D., "Automatic Take-Up Device," disclosure, Dec. 20, 1995, 3 pages, Simpson Strong-Tie Company, Inc., Pleasanton, CA.

"Connectors for Wood Construction", catalog, 1987, 2 pages, C87H-1, Simpson Strong-Tie Company, Inc., Pleasanton, CA.

"Strong-Tie Rod System", catalog, Nov. 2002, 2 pages, C-HW02, Simpson Strong-Tie Company, Inc., Pleasanton, CA.

"Cinch Nut Shrinkage Compensation Device: Models CN6, CN7, CN8 and CN10," evaluation report, Oct. 1, 2006, 4 pages, ESR-2190, ICC Evaluation Service, Inc., Whittier, CA.

"Structural Tie Down System," product data sheet, installation instructions, and SBCCI Report No. 9916, 1999, 18 pages, Probolt, Orlando, FL.

"Quake-Tie: The Superior Hold-Down Solutoin," brochure, Jan. 1998 and Jan. 20, 1997, 9 pages, Seismic Solutions, Inc., Glen Ellen, CA.

"Blue Banger Hanger: Pre-Poured Concrete Steel Deck Inserts," webpage, accessed Jan. 26, 2012, 2 pages, Construction Engineered Attachment Solutions (CEAS), USA.

"The PT Anchor," webpage, 2009, 2 pages, Chainring Construction Products LLC, Portland, OR.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

Mar. 22, 2022





FIG. 20



THRUST NUT

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a thrust nut that includes a plurality of nut segments that slide in an axial direction and are screwed together with a screw portion of a bolt by being rotated in a fastening direction, after the bolt is inserted to a predetermined position.

2. Description of the Related Art

This type of thrust nut of the past is configured by: a nut main body of which an outer wall is formed into a polygonal shape and that has a slanted hole in an inner wall that successively becomes smaller in diameter; a stopper piece that has a bolt insertion hole and is formed in an end portion 25 on a large-diameter side of the nut main body; three guide pieces that are formed in an axial-center direction on an inner wall surface of the nut main body; three nut segments that are attached between the guide pieces such as to be slidable in the axial-center direction and on an inner wall 30 surface of which threads are formed that are screwed together with the bolt; a flange-shaped attachment piece that is fixed to an end portion on the small-diameter side of the nut main body, prevents detachment of the three nut segments, and projects further outward than an outer circum- ³⁵ ferential portion of the nut main body; and a bias spring that is housed within the nut main body such as to urge the three nut segments towards the small-diameter side of the nut main body at all times.

The thrust nut, configured as described above, is configured such that the three nut segments are screwed together with a screw portion of a bolt by being inserted into the bolt and rotated in a fastening direction. However, there is a problem in that a clearance amounting to a single thread is present or not present at all times.

[Patent Literature 1] Patent Publication No. 4531585 [Patent Literature 2] Patent Publication No. 4201210

SUMMARY OF THE INVENTION

The present invention has been achieved in light of such issues of the past. An object of the present invention is to provide a thrust nut of which fastening operation is easy and handling is easy, in which two or more nut segments are each capable of being urged in a counter-bolt-insertion direction even when a bolt is inserted, screw portions of the two or more nut segments are screwed together with a screw portion of the bolt with certainty by being rotated in a fastening direction, the screwed engagement allows the screw portions of the two or more nut segments to be screwed such as to be continuous with the screw portion of the bolt, and the two or more nut segments can be worked such as to be capable of maintaining a secure screwed state.

(1) and (2) are achieved. In that can lock with a fast fastening member contract move in the fastening direct on the fastening direct move in the fastening member contract move in the fastening member contract move in the fastening member contract move in the fastening direct move in the fastening direc

The description above, other objects, and novel features of the present invention will become more completely clear 65 when the following description is read with reference to the accompanying drawings.

2

However, the drawings are mainly for description and do not limit the technical scope of the present invention.

To achieve the above-described object, a thrust nut of the present invention is configured by: a nut main body of which an outer wall is formed into a polygonal shape and that has a slanted hole of which an inner diameter becomes successively smaller, and a small-diameter end portion is formed into two or more stepped portions; two or more nut segments that are slidable within the slanted hole of the nut main body, or which end portions on the small-diameter side come into contact with stepped portions, and pressing projection pieces are formed in end portions on the large-diameter side; screw portions formed on inner wail surfaces of the two or more nut segments such as to be continuous with the nut segments that are in contact with a stepped portion having the smallest diameter; a washer that is provided in the end portions on the large-diameter side of the two or more nut segments; a bias spring that is attached within the nut main body such as to urge the two or more nut segments towards the smalldiameter side at all times with the washer therebetween; and a stopper piece that holds the bias spring within the nut main body, in which a bolt insertion hole is formed, and is attached to the nut main body.

Effects of the Invention

As is clear from the description above, the present invention achieves the following effects:

(1) According to a first aspect, the two or more nut segments are each capable of being evenly urged with certainty towards a direction in which the two or more nut segments are screwed together with the screw portion of a bolt, even when the nut main body is thrust onto the bolt. In addition, the screw portion of the bolt and the screw portions of the two or more nut segments can be screwed together such as to be continuous, by rotation in the fastening direction.

Therefore, a secure screwed state can be maintained.

(2) As a result of above-described (1), two or more stepped portions are formed in a small-diameter end portion of the slanted hole of the nut main body. End portions of the nut segments on the small-diameter side are placed in contact with the stepped portions. Therefore, the two or more nut segments can be disposed with certainty such that the screw portions are continuous.

Therefore, attachment of the two or more nut segments into the nut main body can be easily performed.

(3) According to a second aspect, effects similar to (1) and (2) are achieved.

(4)According to a third aspect as well, effects similar to (1) and (2) are achieved. In addition, as a result of the washer that can lock with a fastening member, even when the fastening member contracts, the two or more nut segments move in the fastening direction. Therefore, loosening of the nut can be prevented with certainty.

BRIEF DESCRIPTION OF THE DRAWING

FIG. 1 is a planar view of a first embodiment for carrying out the present invention;

FIG. 2 is a cross-sectional view taken along line 2-2 in FIG. 1;

FIG. 3 is a development view of a nut main body, showing a steppe d portion according to the first embodiment for carrying out the present invention;

FIG. 4 is a planar view of the nut main body according to the first embodiment for carrying out the present invention;

3

FIG. 5 is a cross-sectional view taken along line 5-5 in FIG. 4;

FIG. 6 is an explanatory diagram of nut segments according to the first embodiment for carrying out the present invention;

FIG. 7 is an explanatory diagram of a bias spring according to the first embodiment for carrying out the present invention;

FIG. **8** is an explanatory diagram of a state in which a bolt is inserted according to the first embodiment for carrying out 10 the present invention;

FIG. 9 is an explanatory diagram of a state in which a washer is fixed to a fastening member according to the first embodiment for carrying out the present invention;

FIG. 10 is an explanatory diagram of a state in which the nut main body is rotated in a fastening direction, fastened, and fixed according to the first embodiment for carrying out the present invention;

FIG. 11 is a development view of a state in which the bolt and the nut segments are screwed together according to the ²⁰ first embodiment for carrying out the present invention;

FIG. 12 is a planar view of a second embodiment for carrying out the present invention;

FIG. 13 is a cross-sectional view taken along line 13-13 in FIG. 12;

FIG. 14 is a development view of a stepped portion according to the second embodiment for carrying out the present invention;

FIG. 15 is a planar view of a third embodiment for carrying out the present invention;

FIG. 16 is a cross-sectional view taken along line 16-16 in FIG. 15;

FIG. 17 is a development view of a stepped portion according to the third embodiment for carrying out the present invention;

FIG. 18 is a planar view of a fourth embodiment for carrying out the present invention;

FIG. 19 is a cross-sectional view taken along line 19-19 in FIG. 18; and

FIG. 20 is a development view of a stepped portion 40 according to the fourth embodiment for carrying out the present invention.

EXPLANATION OF REFERENCE NUMBERS

1, 1A, 1B, 1C: thrust nut

2: bolt

3: screw portion

4: outer wall

5, 5A, 5b: stepped portion

6: slanted hole

7: nut main body

8: nut segment

9: screw portion

10, 10A: guide piece

11, 11A: projection piece

12, 12A: bias spring

12: bolt insertion hole

14: rivet

15: stopper piece

16: washer insertion piece

17: rivet

18: screw insertion hole

19, 19A: washer

20: wood member

21: bolt insertion hole

22: washer

4

23: screw

24: ring-shaped groove

25: engaging piece

26: washer

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will be described in detail based on embodiments for carrying out the present invention shown in the drawings.

According to a first embodiment for carrying out the present invention shown in FIG. 1 to FIG. 11, reference number 1 represents a thrust nut of the present invention that can be thrust onto a bolt 2 to a predetermined position, and screwed together with a right screw portion 3 of the bolt 2, thereby being fastened and fixed, by being rotated in a fastening direction from the predetermined position. The thrust nut 1 is configured by: a nut main body 7 of which an outer wall 4 has a polygonal shape that is hexagonal according to the first embodiment, the nut main body 7 having a slanted hole 6 of which the inner diameter becomes successively smaller and a small-diameter end portion is formed 25 into two or more stepped portions that are three stepped portions 5, 5A, and 5B according to the first embodiment of the present invention; three nut segments 8, 8, and 8 that are slidable within the slanted hole 6 of the nut main body 7, of which small-diameter side end portions 8a, 8a, and 8a are in 30 contact with the stepped portions 5, 5A, and 5B, and pressing projection pieces 11, 11, and 11 are formed in center portions of large-diameter side end portions 8b, 8b, and 8b; right screw portions 9, 9, and 9 that are formed on the inner wall surfaces of the three nut segments 8, 8, and 8 such as to be continuous with the nut segments 8 that are in contact with the stepped portion 5 having the smallest diameter; guide pieces 10, 10, and 10 that are formed in an axial-center direction on the inner wall surfaces at end portion positions of the stepped portions 5, 5A, and 5B in the slanted hole 6 of the nut main body 7, between the nut segments 8, 8, and 8; a washer 26 that is disposed above the pressing projection pieces 11, 11, and 11 of the nut segments 8, 8, and 8; a bias spring 12 that uses a coil spring attached within the nut main body 7 such as to urge the nut segments 8, 8, and 8 towards 45 the small-diameter side at all times with the washer **26**, and the pressing projection pieces 11, 11, and 11 therebetween; a washer-shaped stopper piece 15 that holds the bias spring 12 within the nut main body 7, in which a bolt insertion hole 13 is formed, and is prevented from falling out by a rivet 14 50 in an end portion of the nut main body 7; a ring-shaped washer insertion piece 16 that is formed in an end portion on the small-diameter side of the nut main body 7; and a washer 19 into which the washer insertion piece 16 is inserted, that has screw insertion holes 18 and 18, and of which the tip 55 portion is rotatably attached by a rivet 17.

In the thrust nut 1 configured as described above, the nut segments 8, 8, and 8 are set within the slanted hole 6 of the nut main body 7. The pressing projection pieces 11, 11, and 11 of the nut segments 8, 8, and 8 are pressed by the biasing force of the bias spring 12 with the washer 26 therebetween. The end portions 8a, 8a, and 8a on the small-diameter side of the nut segments 8, 8, and 8 are set such as to be pressed into the stepped portions 5, 5A and 5B. As a result, the nut segments 8, 8, and 8 are automatically disposed by the stepped portions 5, 5A, and 5B such that right screw portions 9, 9, and 9 of the nut segments 8, 8, and 8 are screwed with the right screw portion 3 of the bolt 2 in a continuous state.

In the thrust nut 1 assembled as described above, the bolt 2 is inserted into bolt holes 21 and 21 formed in wood members 20 and 20 that are fastening members to be connected as shown in FIG. 8. A washer 22 having screw insertion holes 18 and 18 is fixed to a head portion 2a of the bolt 2 by welding or the like. Screws 23 and 23 are inserted into the screw insertion holes 18 and 18 of the washer 22 and driven into the wood member 20, thereby fixing the washer 22 to the wood member 20. Thereafter, the thrust nut I is thrust onto the tip portion of the bolt 2 that projects from the 10 bolt insertion hole 21. The screws 23 and 23 are inserted into the screw insertion holes 18 and 18 in the washer 19 as shown in FIG. 9 and driven into the wood member 20, thereby fixing the washer 19 to the wood member 20.

At this time, the nut segments 8, 8, and 8 within the nut main body 7 are pressed back against the biasing force of the bias spring 12 by the right screw portion 3 of the bolt 2. When the nut segments 8, 8, and 8 spread open, the bolt 2 1 is stopped, the biasing force of the bias spring 12 urges the nut segments 8, 8, and 8 towards the direction of the end portions 8a, 8a, and 8a on the small-diameter side, with the washer 26 and the pressing projection pieces 11, 11, and 11 of the nut segments **8**, **8**, and **8** therebetween. As a result, the nut segments 8, 8, and 8 are pressed back, with certainty, into to a position at which the right screw portion 3 of the bolt 2 and the right screw portions 9, 9, and 9 of the nut segments 8, 8, and 8 are screwed together.

In this state, when the nut main body 7 is rotated in the 30 fastening direction as shown in FIG. 10, the nut segments 8, 8, and 8 are each urged towards the direction of the end portions 8a, 8a, and 8a on the small-diameter side with certainty by the biasing force of the bias spring 12, as shown in FIG. 11. The right screw portion 3 of the bolt 2 and the 35 right screw portions 9, 9, and 9 of the nut segments 8, 8, and 8 are screwed together such as to be continuous, and the nut main body 7 can be fastened and fixed.

In an instance in which the wood members 20 and 20 that are fastening members contract during fastening and fixing, 40 the nut main body 7 moves in the contracting direction via the washer 19. Therefore, the biasing force of the bias spring 12 is transmitted to the pressing projection pieces 11, 11, and 11 of the nut segments 8, 8, and 8 via the washer 26. The nut segments 8, 8, and 8 can be moved in the fastening direction 45 with certainty, and automatically tightened.

[Other Embodiments for Carrying out the Invention]

Next, other embodiments for carrying out the present invention, shown in FIG. 12 to FIG. 20, will be described. In the description of the other embodiments for carrying out 50 the present invention, constituent components that are the same as those according to the first embodiment for carrying out the present invention are given the same reference numbers. Redundant descriptions are omitted.

According to a second embodiment for carrying out the 55 present invention shown in FIG. 12 to FIG. 14, the main difference with the first embodiment for carrying out the present invention is that nut-segments 8, 8A, and 8B, and wedge-shaped guide pieces 10A, 10A, and 10A are used. The upper end portions of the nut-segments 8, 8A, and 8B 60 are on substantially the same plane in a state in which the nut segments 8, 8A, and 8B are housed within the slanted hole 6 of the nut main body 7. The guide pieces 10A, 10A, and 10A reduce the allowance of the nut segments 8, 8A, and 8B. A thrust nut 1A that is configured using the nut segments 8, 65 **8**A, and **8**B, formed as described above, achieves working effects similar to those according to the first embodiment for

carrying out the present invention. In addition, the biasing force of the bias spring 12 can he evenly transmitted to the nut segments 8, 8A, and 8B.

According to a third embodiment for carrying out the present invention shown in FIG. 15 to FIG. 17, the main difference with the first embodiment for carrying out the present invention is that a ring-shaped groove 24 is formed in an outer circumferential portion of the nut main body 7 on the small-diameter side, and a washer 19A is used in which reverse L-shaped engaging pieces 25 and 25 are formed. The engaging pieces 25 and 25 are engaged with the nut main body 7 in areas opposing the ring-shaped groove 24. A thrust nut 1B that is configured using the nut main body 7 in which the ring-shaped groove 24 is formed and the wisher 19A, formed as described above, can also achieve working effects similar to those according to the first it for carrying out the present invention.

According to a fourth embodiment for carrying out the smoothly passes through, and the thrusting of the thrust nut 20 present invention shown in FIG. 18 to FIG. 20, the main difference with the first embodiment for carrying out the present invention is that two stepped portions 5 and SA are formed in the small-diameter end portion of the slanted hole 6 of the nut main body 7, and pressing projection pieces 11 and 11A are formed that have differing heights, of which the lower end portions come into contact with the two stepped portions 5 and 5A, and the upper surfaces are on a same plane in the center portions of the large-diameter end portions 8b and 8b. In addition, two nut segments 8C and 8C are used that rotate integrally with the nut main body 7. A thrust nut 1C that is configured using the two nut segments 8C and 8D in this way can also achieve working effects similar to those according to the first embodiment for carrying out the present invention.

> The stopper piece may be formed into a cylindrical shape as in Japanese Laid-Open Patent Publication No 2012-47244. The stopper piece may be fitted and fixed such as to cover the nut main body 7, or may be fixed to the nut main body 7 by an adhesive or by welding.

> In addition, although use of the bolt 2 in which the right screw portion 3 is formed is described, the present invention is not limited thereto. The thrust nut may be configured such that a bolt on which a left screw portion is formed can be used, by using nut segments in which left screw portions are formed that can be screwed together with the left screw portion of the bolt.

> According to the embodiments of the present invention, a thrust nut in which the nut main body is integrally formed is described. However, the present invention is not limited thereto. Similar working effects can be achieved even with a nut main body configured by an inner cylinder member of which the inner diameter becomes successively smaller and in which two or more stepped portions are formed in the small-diameter end portion, and an outer cylinder member of which the outer wall is formed into a polygonal shape, as disclosed in Japanese Laid-Open Patent Publication No. 2012-47244.

> In addition, according to the embodiments of the present invention, materials of the components are not specified. However, materials that can be used for a nut, such as an iron material, various alloys, synthetic resin materials, carbon fiber materials, are selectively used.

Industrial Applicability

The present invention is used in an industry for manufacturing a thrust nut that is screwed together with a screw

7

portion of a bolt by being rotated in a fastening direction after the bolt is inserted to a predetermined position.

What is claimed is:

- 1. A [thrust] nut comprising:
- a [nut] main body [of which an outer wall is formed into a polygonal shape and] that has a slanted hole of which an inner diameter becomes successively smaller, and a small-diameter end portion having about a circumference of said small-diameter end portion a plurality of stepped portions of differing height so that said slanted hole has a differing depth relative to a large-diameter end portion of the slanted hole at a plurality of locations about a circumference of the slanted hole, the stepped portions having end portion positions that are adjacent to each other;
- a plurality of [nut] segments that are slidable within the slanted hole of the [nut] main body, each one of the plurality of [nut] segments having a small-diameter side that comes into contact with at least one of said plurality of stepped portions[, and each one of the plurality of nut segments having a pressing projection piece formed at a large-diameter side of said one nut segment];
- [a respective set of screw thread] *rod engaging* portions formed on an inner wall surface of each one of said ²⁵ plurality of [nut] segments[, said respective set occurring from said large diameter side to said small-diameter side of said one nut segment and including a thread portion extending to said small diameter side that is in contact with said at least one stepped portion];
- [a washer that is provided at the large-diameter side of the plurality of nut segments]; and
- a [bias] spring that [is attached within the nut main body such as to urge] *urges* the plurality of [nut] segments towards the small-diameter side at all times [with the ³⁵ washer therebetween; and
- a stopper piece, in which a bolt insertion hole is formed, that holds the bias spring within the nut main body and is attached to the nut main body.
- 2. The [thrust] nut according to claim 1, wherein:
- a plurality of guide pieces are formed on an inner wall surface of the [nut] main body that guide sliding of the plurality of [nut] segments in an axial-center direction.
- 3. The [thrust] nut according to any one of claim 1 or 2, wherein:
 - a washer capable of locking with a fastening member is fixed or rotatably attached to [a] *said* small-diameter end portion of the [nut] main body.
- 4. The [thrust] nut according to claim 2, wherein each one of said guide pieces extends axially along [an] *the* inner wall surface of said [nut] main body toward a corresponding stepped portion among said plurality of stepped portions at said small-diameter end portion of said [nut] main body.
- 5. The nut according to claim 1, wherein the main body has an outer wall that is formed into a polygonal shape.

8

- 6. The nut according to claim 1, wherein each one of the plurality of segments has a projection formed at a large-diameter side of each one of said plurality of segments.
- 7. The nut according to claim 1, wherein the rod engaging portions formed on the inner wall surfaces of said plurality of segments are adapted to engage threads on a rod received by the nut.
- 8. The nut according to claim 1, wherein the rod engaging portions formed on the inner wall surface of each one of said plurality of segments occur from said large-diameter side to said small-diameter side of each one of said plurality of segments.
- 9. The nut according to claim 1, wherein the rod engaging portions formed on the inner wall surface of each one of said plurality of segments include a thread portion extending to said small-diameter side that is in contact with at least one of said plurality of stepped portions.
 - 10. The nut according to claim 1, wherein a washer is provided at the large-diameter side of the plurality of segments and the washer is disposed between said plurality of segments and said spring.
 - 11. The nut according to claim 1, wherein a stopper piece is provided that holds the spring within the main body.
 - 12. The nut according to claim 1, wherein the spring is substantially disposed within the nut main body.
 - 13. The nut according to claim 2, wherein the guide pieces are wedge-shaped.
 - 14. The nut according to claim 6, wherein the projections have differing heights.
 - 15. The nut according to claim 1, wherein the rod engaging portions formed on the inner wall surfaces of said plurality of segments comprise grooves and ridges.
 - 16. The nut according to claim 1, wherein the plurality of stepped portions are arranged about the circumference of the slanted hole in ascending order of said differing depths relative to the large-diameter end portion of the slanted hole.
 - 17. An apparatus, comprising:
 - a. the nut according to claim 1;
 - b. a fastening member connected to another fastening member by a rod, with the nut fixed to the fastening member wherein one or more of the fastening members contract in a contracting direction along the rod; and
 - c. the rod is at least partially held within the slanted hole of the nut.
 - 18. The nut according to claim 11, wherein the stopper piece is formed with a rod insertion hole.
 - 19. The nut according to claim 15, wherein a plurality of guide pieces are formed on an inner wall surface of the main body that guide sliding of the plurality of segments in an axial-center direction.
 - 20. The nut according to claim 2, wherein the rod engaging portions formed on the inner wall surfaces of said plurality of segments comprise grooves and ridges.

* * * *