



US00RE49039E

(19) **United States**
(12) **Reissued Patent**
Crowley et al.

(10) **Patent Number:** **US RE49,039 E**
(45) **Date of Reissued Patent:** **Apr. 19, 2022**

(54) **TECHNIQUES TO AUTOMATICALLY FOCUS A DIGITAL CAMERA**

(56) **References Cited**

(71) Applicant: **QUALCOMM Incorporated**, San Diego, CA (US)
(72) Inventors: **Matthew Crowley**, Los Altos, CA (US); **Jeff Finkelstein**, San Francisco, CA (US); **Richard Dellinger**, San Jose, CA (US)
(73) Assignee: **Qualcomm Incorporated**, San Diego, CA (US)

U.S. PATENT DOCUMENTS

5,426,732 A * 6/1995 Boies et al. 715/839
5,612,719 A 3/1997 Beernink et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0565830 A2 10/1993
EP 1526756 A2 4/2005

(Continued)

OTHER PUBLICATIONS

European Search Report—EP20158892—Search Authority—Munich—dated Jun. 3, 2020 (142638EPD1D1).

(Continued)

(21) Appl. No.: **16/908,579**
(22) Filed: **Jun. 22, 2020**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,497,928**
Issued: **Jul. 30, 2013**
Appl. No.: **11/831,051**
Filed: **Jul. 31, 2007**

Primary Examiner — Peng Ke

(74) *Attorney, Agent, or Firm* — Norton Rose Fulbright US LLP

(51) **Int. Cl.**
G03B 13/36 (2021.01)
H04N 5/232 (2006.01)
G02B 7/28 (2021.01)

(52) **U.S. Cl.**
CPC **G03B 13/36** (2013.01); **G02B 7/285** (2013.01); **H04N 5/232127** (2018.08); **H04N 5/232935** (2018.08)

(58) **Field of Classification Search**
CPC G06F 3/04845; G06F 3/0488; G06F 3/04883; H04N 5/232945; H04N 5/232127; H04N 5/232935; G02B 7/285; G03B 13/36; G03B 17/56; G03B 31/00


See application file for complete search history.

(57) **ABSTRACT**

Various embodiments are directed to techniques to automatically focus a digital camera. In one or more embodiments, a mobile electronics device may comprise a digital camera having a lens component and lens position component. A display may be coupled to the digital camera to reproduce an image with a first focal point. The digital camera may also include a focal point selection module coupled to the display to select a second focal point for the image and a focus control module coupled to the focal point selection module and the lens position component to provide focus control signals to the lens position component to focus the lens component on the second focal point. Other embodiments are described and claimed.

51 Claims, 4 Drawing Sheets

200



(56)

References Cited

U.S. PATENT DOCUMENTS

5,852,667 A * 12/1998 Pan G10K 11/17881
381/71.1

5,923,908 A 7/1999 Schrock et al.

6,151,073 A 11/2000 Steinberg et al.

6,327,436 B2 12/2001 Kawabe et al.

6,529,234 B2 * 3/2003 Urisaka et al. 348/211.99

6,684,087 B1 * 1/2004 Yu et al. 455/566

6,775,361 B1 * 8/2004 Arai et al. 379/93.17

6,812,968 B1 * 11/2004 Kermani 348/345

6,919,927 B1 * 7/2005 Hyodo H04N 1/00411
348/333.02

6,977,687 B1 * 12/2005 Suh H04N 5/232127
348/345

7,034,881 B1 * 4/2006 Hyodo et al. 348/333.12

7,215,371 B2 5/2007 Fellegara et al.

7,253,836 B1 * 8/2007 Suzuki H04N 5/772
348/234

7,471,846 B2 * 12/2008 Steinberg et al. 382/274

7,561,748 B2 7/2009 Suzuki

7,643,742 B2 * 1/2010 Watanabe et al. 396/60

7,664,384 B2 2/2010 Hope

7,697,057 B2 * 4/2010 Yoshida 348/346

7,705,908 B2 4/2010 Fredlund et al.

7,781,710 B2 8/2010 Higashino

7,791,669 B2 * 9/2010 Nonaka 348/349

7,808,533 B2 10/2010 Tsuda

7,812,826 B2 10/2010 Ording et al.

7,844,174 B2 * 11/2010 Pickens et al. 396/121

7,852,381 B2 12/2010 Abe

7,932,949 B2 4/2011 Hyodo

8,169,421 B2 5/2012 Wright et al.

8,497,928 B2 7/2013 Crowley et al.

8,525,892 B2 9/2013 Shimosato

8,767,082 B2 7/2014 Thorn

9,767,539 B2 9/2017 Zamfir et al.

2002/0003958 A1 * 1/2002 Nagata 396/106

2002/0080257 A1 6/2002 Blank

2003/0064688 A1 4/2003 Mizuta et al.

2003/0064757 A1 * 4/2003 Yamadera et al. 455/566

2003/0193600 A1 * 10/2003 Kitamura H04N 5/232123
348/333.01

2004/0012709 A1 * 1/2004 Hirai 348/345

2004/0085360 A1 * 5/2004 Pratt et al. 345/773

2004/0189856 A1 * 9/2004 Tanaka H04N 5/232935
348/345

2004/0189857 A1 * 9/2004 Hirai 348/345

2004/0218086 A1 11/2004 Voss et al.

2004/0246360 A1 12/2004 Stavely et al.

2005/0036708 A1 2/2005 Boll

2005/0079896 A1 * 4/2005 Kokko et al. 455/566

2005/0117049 A1 6/2005 Suzuki

2005/0140810 A1 * 6/2005 Ozawa 348/333.02

2006/0008264 A1 1/2006 Yamaguchi et al.

2006/0026521 A1 2/2006 Hotelling et al.

2006/0055814 A1 * 3/2006 Okawa H04N 5/232123
348/346

2006/0146144 A1 7/2006 Salmelin et al.

2006/0146174 A1 * 7/2006 Hagino 348/349

2006/0165399 A1 7/2006 Feng et al.

2006/0204056 A1 * 9/2006 Steinberg H04N 5/2352
382/118

2006/0210265 A1 9/2006 Adachi

2006/0291816 A1 12/2006 Ozawa

2007/0002150 A1 1/2007 Abe

2007/0018069 A1 1/2007 Higashino

2007/0071432 A1 3/2007 Senba

2007/0086764 A1 * 4/2007 Konicek G10L 15/22
396/56

2007/0098396 A1 5/2007 Watanabe et al.

2007/0222859 A1 * 9/2007 Chang et al. 348/148

2007/0279492 A1 * 12/2007 Ohnishi H04N 5/23299
348/143

2007/0280660 A1 12/2007 Yeh et al.

2008/0068490 A1 * 3/2008 Ueda et al. 348/341

2008/0079837 A1 * 4/2008 Masubuchi 348/345

2008/0107411 A1 5/2008 Hope

2008/0278589 A1 11/2008 Thorn

2008/0284899 A1 * 11/2008 Haubmann et al. 348/345

2008/0303922 A1 * 12/2008 Chaudhri et al. 348/231.99

2009/0310012 A1 * 12/2009 Ueda et al. 348/348

FOREIGN PATENT DOCUMENTS

EP 1830564 A1 9/2007

JP H09116792 A 5/1997

JP 2001159730 A 6/2001

JP 2004117490 A 4/2004

JP 2004242010 A 8/2004

JP 2005173087 A 6/2005

KR 20070040107 A 4/2007

KR 20070074251 A 7/2007

WO WO-2006057101 A1 6/2006

WO WO-2009018279 A1 2/2009

OTHER PUBLICATIONS

Boozer S., et al., "Sony DSC-H2 Review," 2006, pp. 1-9.

Canon: "EOS-3 Instructions," 1998-2007, 24 pages.

Definition of "instruction", thefreedictionary.com (citing The American Heritage Dictionary of the English Language, Fourth Edition, 2000, Houghton Mifflin Company), retrieved from the Internet at <www.thefreedictionary.com/p/instruction> on Mar. 29, 2014.

European Search Report—EP19154330—Search Authority—Munich—dated Mar. 19, 2019 (142638EPD2D1).

European Search Report—EP16190939—Search Authority—Munich—dated Jan. 24, 2017 (142638EPD1).

European Search Report—EP16206486—Search Authority—Munich—dated Apr. 5, 2017 (142638EPD2).

Fujitsu: "LCM Assembly Techniques," Aug. 2002, 5 pages.

Graf R.F., "Modern Dictionary of Electronics," 7th Edition, Central Processing Unit, 1999, 6 pages.

Grotta S.W., et al., "Digital Camera Basics: Understanding Exposure," Mar. 21, 2005, pp. 1-2, retrieved from the URL: <https://www.pcmag.com/article2/0,2817,1777910,00.asp>.

Harry Newton, Newton's Telecom Dictionary, 22nd Updated and Expanded Edition, ISBN 1-57820-319-8, cover page, copyright page and p. 936.

Havlik D., "Canon SD700 Is Review," Feb. 2, 2007, pp. 1-6.

Hewlett-Packard: "Battery Usage in HP Digital Cameras," 2005, pp. 1-11.

Jenkins F.A., et al., "Fundamental of optics," McGraw Hill Publication, Fourth Edition, 2001, 766 pages.

Keller J., "DCRP Review: Minolta DiIMAGE 7Hi," Dec. 9, 2009 (Dec. 9, 2009), XP055354922, Retrieved from the Internet: URL: http://www.dcresource.com/reviews/minolta/dimage_7hi-review/ [retrieved on Mar. 15, 2017].

King J.A., "Digital Photography for Dummies," Wiley Publishing, Inc. 5th Edition, 2005, 402, pages.

Malacara D., et al., "Handbook of Optical Design," Marcel Dekker, Inc. 2nd Edition, 2004, 522 pages.

Marriott M., "A Liberated View of the World as Viewfinders Eclipse Eyepieces," The Newyork Times, Trends, Jun. 7, 2006, pp. 1-5.

Merriam-Webster's Collegiate Dictionary, Merriam-Webster, Inc., Eleventh Edition, 2008.

Merriam-Webster's Collegiate Dictionary, Merriam-Webster, Inc., Eleventh Edition, 2008, ("focal").

Microsoft Computer Dictionary, Fifth Edition, 2002, ("frame rate").

Motorola Inc: "White Balance and Color Correction in Digital Cameras," (2005) pp. 1-6.

Murphy M., et al., "Lens Drivers Focus on Performance in High-Resolution Camera Modules," Analog Dialogue, Nov. 2006, vol. 40, pp. 1-3.

Nielsen J., "10 Usability Heuristics for User Interface Design," 1995, 2 pages.

Nikitas T., "Canon SD1000 Review," May 2007, 9 pages.

PENTAX: "Optio T10 Digital Camera Operating Manual," 2006, 163 pages.

(56)

References Cited

OTHER PUBLICATIONS

PENTAX: "Optio T20 Digital Camera Operating Manual," 2006, 168 pages.

PENTAX: "Optio T30 Digital Camera Operating Manual," 2007, 192 pages.

Shene C-K., "Nikon Coolpix 5700 User Guide," 2004, 6 pages.

Sony: "Cyber-shot Handbook: DSC-N2," 2006, 132 pages.

Sony: "Cyber-shot Instruction Manual: DSC-N2," 2006, 32 pages.

Sony: "Cyber-shot Specification: DSC-N2," 2006, 12 pages.

Sony: "DCR-DVD505/DVD905 Operating Instructions," 2006, 152 pages.

Sony: "DVCAM DSR-PDX10 Operating Instructions," 2002, pp. 1-262.

Sony: "DVCAM HVR-A1U/A1N Operating Instructions," 2005, 128 pages.

Sony Electronics Inc: "Sony Cybershot DSC-N2 Digital Camera," 2006.

Sony: "Handycam DCR-HC1000 Operating Instructions," 2004, 140 pages.

Sony: "Handycam DCR-HC26 Operating Instructions," 2006, 92 pages.

Sony: "Handycam DCR-PC55 Operating Instructions," 2005, 115 pages.

Sony: "Handycam DCR-TRV940/TRV950 Operating Instructions," 2002, 256 pages.

Stetson J.W., "Analog Resistive Touch Panels and Sunlight Readability," *Information Display*, vol. 22, No. 12, Dec. 2006, pp. 26-30.

"Using Digital White Balance Indoors," *A Web Photo School Lesson*, Jun. 11, 2004 to May 4, 2009, 6 pages.

Webster's II New College Dictionary, Third Edition, 2005 (excerpt).

Webster's New World Computer Dictionary, 10th Edition, 2003.

Webster's New World Computer Dictionary, 10th Edition, ("frame rate"), 2003.

European Search Report—EP20198227—Search Authority—Munich—dated Nov. 9, 2020 (142638EPD2D1D1).

Supplementary European Search Report—EP08782499—Search Authority—Munich—dated Jul. 2, 2010 (142638EP).

* cited by examiner




FIG. 1

200




FIG. 2

300




FIG. 3

400




FIG. 4

TECHNIQUES TO AUTOMATICALLY FOCUS A DIGITAL CAMERA

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

This application is a Reissue of U.S. Pat. No. 8,497,928, issued Jul. 30, 2013, which issued from U.S. application Ser. No. 11/831,051, filed Jul. 31, 2007.

BACKGROUND

A digital camera is an electronic device used to capture and store images electronically in a digital format, instead of using photographic film like conventional cameras, or recording images in an analog format to magnetic tape like many video cameras. Modern compact digital cameras are typically multifunctional, with some devices capable of recording sound and/or video as well as still images.

Many digital cameras provide an autofocus feature. Autofocus is a feature that allows a user of a digital camera to obtain the correct focus on a subject rather than requiring the operator to adjust focus manually. Typically a user may assist the camera by determining which area of the photograph to focus on by performing a button half press or other convoluted user interaction to achieve the desired focus. Providing a technique to allow users to more easily determine the area of the photograph they wish to focus on may be desirable. Accordingly, there may be a need for improved techniques to automatically focus a digital camera.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates one embodiment of a mobile electronic device.

FIG. 2 illustrates one embodiment of a first digital camera.

FIG. 3 illustrates one embodiment of a logic flow.

FIG. 4 illustrates one embodiment of a second digital camera.

DETAILED DESCRIPTION

Various embodiments are generally directed to techniques to automatically focus a digital camera. Some embodiments are particularly directed to automatically focusing a digital camera using a display device. The display device may be integrated with, or separate from, the digital camera. In one embodiment, for example, a mobile electronics device may comprise a digital camera having a lens component and lens position component. A display may be coupled to the digital camera to reproduce an image with a first focal point. The digital camera may also include a focal point selection module coupled to the display to select a second focal point for the image. The digital camera may also include a focus control module coupled to the focal point selection module and the lens position component to provide focus control signals to the lens position component to focus the lens component on the second focal point. Other embodiments are described and claimed.

FIG. 1 illustrates a mobile electronic device 100 in accordance with one or more embodiments. The mobile electronic device 100 may be implemented as a combination handheld computer and mobile telephone, sometimes referred to as a smart phone. Examples of smart phones include, for example, Palm® products such as Palm® Treo™ smart phones. Although some embodiments may be described with the mobile electronic device 100 implemented as a smart phone by way of example, it may be appreciated that the embodiments are not limited in this context. For example, the mobile electronic device 100 may comprise, or be implemented as, any type of wireless device, mobile station, or portable computing device with a self-contained power source (e.g., battery) such as a laptop computer, ultra-laptop computer, personal digital assistant (PDA), cellular telephone, combination cellular telephone/PDA, mobile unit, subscriber station, user terminal, portable computer, handheld computer, palmtop computer, wearable computer, media player, pager, messaging device, data communication device, and so forth.

The mobile electronic device 100 may provide voice communications functionality in accordance with different types of cellular radiotelephone systems. Examples of cellular radiotelephone systems may include Code Division Multiple Access (CDMA) systems, Global System for Mobile Communications (GSM) systems, North American Digital Cellular (NADC) systems, Time Division Multiple Access (TDMA) systems, Extended-TDMA (E-TDMA) systems, Narrowband Advanced Mobile Phone Service (NAMPS) systems, third generation (3G) systems such as Wide-band CDMA (WCDMA), CDMA-2000, Universal Mobile Telephone System (UMTS) systems, and so forth.

In addition to voice communications functionality, the mobile electronic device 100 may be arranged to provide data communications functionality in accordance with different types of cellular radiotelephone systems. Examples of cellular radiotelephone systems offering data communications services may include GSM with General Packet Radio Service (GPRS) systems (GSM/GPRS), CDMA/1xRTT systems, Enhanced Data Rates for Global Evolution (EDGE) systems, Evolution Data Only or Evolution Data Optimized (EV-DO) systems, Evolution For Data and Voice (EV-DV) systems, High Speed Downlink Packet Access (HSDPA) systems, High Speed Uplink Packet Access (HSUPA), and so forth.

The mobile electronic device 100 may be arranged to provide voice and/or data communications functionality in accordance with different types of wireless network systems. Examples of wireless network systems may include a wireless local area network (WLAN) system, wireless metropolitan area network (WMAN) system, wireless wide area network (WWAN) system, and so forth. Examples of suitable wireless network systems offering data communication services may include the Institute of Electrical and Electronics Engineers (IEEE) 802.xx series of protocols, such as the IEEE 802.11a/b/g/n series of standard protocols and variants (also referred to as “WiFi”), the IEEE 802.16 series of standard protocols and variants (also referred to as “WiMAX”), the IEEE 802.20 series of standard protocols and variants, and so forth.

The mobile electronic device 100 may be arranged to perform data communications in accordance with different types of shorter range wireless systems, such as a wireless personal area network (PAN) system. One example of a suitable wireless PAN system offering data communication services may include a Bluetooth system operating in accordance with the Bluetooth Special Interest Group (SIG) series

of protocols, including Bluetooth Specification versions v1.0, v1.1, v1.2, v2.0, v2.0 with Enhanced Data Rate (EDR), as well as one or more Bluetooth Profiles, and so forth. Other examples may include systems using infrared techniques or near-field communication techniques and protocols, such as electromagnetic induction (EMI) techniques. All example of EMI techniques may include passive or active radio-frequency identification (RFID) protocols and devices.

As shown in the embodiment of FIG. 1, the mobile electronic device **100** may comprise a dual processor architecture including a host processor **102** and a radio processor **104**. In various implementations, the host processor **102** and the radio processor **104** may be arranged to communicate with each other using interfaces **106** such as one or more universal serial bus (USB) interfaces, micro-USB interfaces, universal asynchronous receiver-transmitter (UART) interfaces, general purpose input/output (GPIO) interfaces, control/status lines, control/data lines, audio lines, and so forth.

The host processor **102** may be responsible for executing various software programs such as system programs and applications programs to provide computing and processing operations for the mobile electronic device **100**. The radio processor **104** may be responsible for performing various voice and data communications operations for the mobile electronic device **100** such as transmitting and receiving voice and data information over one or more wireless communications channels. Although some embodiments may be described as comprising a dual processor architecture for purposes of illustration, it is worthy to note that the mobile electronic device **100** may comprise any suitable processor architecture and/or any suitable number of processors consistent with the described embodiments.

The host processor **102** may be implemented as a host central processing unit (CPU) using any suitable processor or logic device, such as a general purpose processor. Although some embodiments may be described with the host processor **102** implemented as a CPU or general purpose processor by way of example, it may be appreciated that the embodiments are not limited in this context. For example, the host processor **102** may comprise, or be implemented as, a chip multiprocessor (CMP), dedicated processor, embedded processor, media processor, input/output (I/O) processor, co-processor, microprocessor, controller, microcontroller, application specific integrated circuit (ASIC), field programmable gate array (FPGA), programmable logic device (PLD), or other processing device in accordance with the described embodiments.

As shown, the host processor **102** may be coupled through a memory bus **108** to a memory **110**. The memory bus **108** may comprise any suitable interface and/or bus architecture for allowing the host processor **102** to access the memory **110**. Although the memory **110** may be shown as being separate from the host processor **102** for purposes of illustration, it is worthy to note that in various embodiments some portion or the entire memory **110** may be included on the same integrated circuit as the host processor **102**. Alternatively, some portion or the entire memory **110** may be disposed on an integrated circuit or other medium (e.g., hard disk drive) external to the integrated circuit of host processor **102**. In various embodiments, the mobile electronic device **100** may comprise an expansion slot to support a multimedia and/or memory card, for example.

The memory **110** may be implemented using any machine-readable or computer-readable media capable of storing data such as volatile memory or non-volatile memory, removable or non-removable memory, erasable or non-erasable memory, writable or re-writable memory,

and so forth. Examples of machine-readable storage media may include, without limitation, random-access memory (RAM), dynamic RAM (DRAM), Double-Data-Rate DRAM (DDRAM), synchronous DRAM (SDRAM), static RAM (SRAM), read-only memory (ROM), programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), flash memory (e.g., NOR or NAND flash memory), content addressable memory (CAM), polymer memory (e.g., ferroelectric polymer memory), phase-change memory, ovonic memory, ferroelectric memory, silicon-oxide-nitride-oxide-silicon (SONOS) memory, magnetic or optical cards, or any other type of media suitable for storing information.

The host processor **102** may also be coupled to various components, such as a keypad **112**, a display **114**, an input/output (I/O) interface **116**, various audio/visual (A % V) devices **118**, a power supply **120**, and so forth. In some cases, the host processor **102** may further implement a digital interface to communicate digital signals between the host processor **102** and the various coupled components. Examples of such digital signals may include, without limitation, digital clock signals such as from an integrated circuit (IC) clock source. The digital clock signal is typically a signal used to coordinate the actions of two or more circuits. The clock signal oscillates between a high and low state, normally with a fifty percent duty cycle, and is usually a square waveform. Circuits using the clock signal for synchronization may become active at either the rising edge or falling edge, or both, of the oscillating clock signal. Consequently, the host processor **102** typically delivers a clock signal to the various components coupled to the host processor **102** in part to synchronize and control the coupled components.

The mobile electronic device **100** may comprise an alphanumeric keypad **112** coupled to the host processor **102**. The keypad **112** may comprise, for example, a QWERTY key layout and an integrated number dial pad. In some cases, the keypad **112** may comprise a thumbboard arranged for operation using the thumbs of a user. The mobile electronic device **100** also may comprise various keys, buttons, and switches such as, for example, input keys, preset and programmable hot keys, left and right action buttons, a navigation button such as a multidirectional navigation button, phone/send and power/end buttons, preset and programmable shortcut buttons, a volume rocker switch, a ringer on/off switch having a vibrate mode, and so forth.

The mobile electronic device **100** may comprise a display **114** coupled to the host processor **102**. The display **114** may comprise any suitable visual interface for displaying content to a user of the mobile electronic device **100**. In one embodiment, for example, the display **114** may be implemented by a LCD such as a touch-sensitive color (e.g., 16-bit color) thin-film transistor (TFT) LCD screen. In some embodiments, the touch-sensitive LCD may be used with a stylus and/or a handwriting recognizer program.

The mobile electronic device **100** may comprise an I/O interface **116** coupled to the host processor **102**. The I/O interface **116** may comprise one or more I/O devices such as a serial connection port, an infrared port, integrated Bluetooth® wireless capability, and/or integrated 802.11x (WiFi) wireless capability, to enable wired (e.g., USB cable) and/or wireless connection to a local computer system, such as a local personal computer (PC). In various implementations, mobile electronic device **100** may be arranged to transfer and/or synchronize information with the local computer system.

The host processor **102** may be coupled to various A/V devices **118** that support A/V capability of the mobile electronic device **100**. Examples of A/V devices **114** may include, for example, a microphone, one or more speakers, an audio port to connect an audio headset, an audio coder/decoder (codec), an audio player, a digital camera, a video camera, a video codec, a video player, and so forth.

The host processor **102** may be coupled to a power supply **120** arranged to supply and manage power to the elements of the mobile electronic device **100**. In various embodiments, the power supply **120** may be implemented by a rechargeable battery, such as a removable and rechargeable lithium ion battery to provide direct current (DC) power, and/or an alternating current (AC) adapter to draw power from a standard AC main power supply.

As mentioned above, the radio processor **104** may perform voice and/or data communication operations for the mobile electronic device **100**. For example, the radio processor **104** may be arranged to communicate voice information and/or data information over one or more assigned frequency bands of a wireless communication channel. In various embodiments, the radio processor **104** may be implemented as a communications processor using any suitable processor or logic device, such as a modem processor or baseband processor. Although some embodiments may be described with the radio processor **104** implemented as a modem processor or baseband processor by way of example, it may be appreciated that the embodiments are not limited in this context. For example, the radio processor **104** may comprise, or be implemented as, a digital signal processor (DSP), media access control (MAC) processor, or any other type of communications processor in accordance with the described embodiments.

In various embodiments, the radio processor **104** may perform analog and/or digital baseband operations for the mobile electronic device **100**. For example, the radio processor **104** may perform digital-to-analog conversion (DAC), analog-to-digital conversion (ADC), modulation, demodulation, encoding, decoding, encryption, decryption, and so forth.

The mobile electronic device **100** may comprise a memory **122** coupled to the radio processor **104**. The memory **122** may be implemented using one or more types of machine-readable or computer-readable media capable of storing data such as volatile memory or non-volatile memory, removable or non-removable memory, erasable or non-erasable memory, writeable or re-writable memory, and so forth. The memory **122** may comprise, for example, flash memory and secure digital (SD) RAM. Although the memory **122** may be shown as being separate from and external to the radio processor **104** for purposes of illustration, it is worthy to note that in various embodiments some portion or the entire memory **122** may be included on the same integrated circuit as the radio processor **104**.

The mobile electronic device **100** may comprise a transceiver module **124** coupled to the radio processor **104**. The transceiver module **124** may comprise one or more radio transceivers arranged to communicate using different types of protocols, communication ranges, operating power requirements, RF sub-bands, information types (e.g., voice or data), use scenarios, applications, and so forth. In various embodiments, the transceiver module **124** may comprise one or more transceivers arranged to support voice communication for a cellular radiotelephone system such as a GSM, UMTS, and/or CDMA system. The transceiver module **124** also may comprise one or more transceivers arranged to perform data communications in accordance with one or

more wireless communications protocols such as WWAN protocols (e.g., GSM/GPRS protocols, CDMA/1xRTT protocols, EDGE protocols, EV-DO protocols, EV-DV protocols, HSDPA protocols, etc.), WLAN protocols (e.g., IEEE 802.11a/b/g/n, IEEE 802.16, IEEE 802.20, etc.), PAN protocols, infrared protocols, Bluetooth protocols, EMI protocols including passive or active RFID protocols, and so forth. In some embodiments, the transceiver module **124** may comprise a Global Positioning System (GPS) transceiver to support position determination and/or location-based services. It may be appreciated that the term "transceiver" as used herein may describe a transmitter, a receiver, or both a transmitter and receiver.

The transceiver module **124** generally may be implemented using one or more chips as desired for a given implementation. Although the transceiver module **124** may be shown as being separate from and external to the radio processor **104** for purposes of illustration, it is worthy to note that in various embodiments some portion or the entire transceiver module **124** may be included on the same integrated circuit as the radio processor **104**. The embodiments are not limited in this context.

The mobile electronic device **100** may comprise an antenna system **126** for transmitting and/or receiving electrical signals. As shown, the antenna system **126** may be coupled to the radio processor **104** through the transceiver module **124**. The antenna system **126** may comprise or be implemented as one or more internal antennas and/or external antennas.

The mobile electronic device **100** may comprise a subscriber identity module (SIM) **128** coupled to the radio processor **104**. The SIM **128** may comprise, for example, a removable or non-removable smart card arranged to encrypt voice and data transmissions and to store user-specific data for allowing a voice or data communications network to identify and authenticate the user. The SIM **128** also may store data such as personal settings specific to the user.

As mentioned above, the host processor **102** may be arranged to provide processing or computing resources to the mobile electronic device **100**. For example, the host processor **102** may be responsible for executing various software programs such as system programs and application programs to provide computing and processing operations for the mobile electronic device **100**.

System programs generally may assist in the running of the mobile electronic device **100** and may be directly responsible for controlling, integrating, and managing the individual hardware components of the computer system. Examples of system programs may include, without limitation, an operating system (OS), device drivers, programming tools, utility programs, software libraries, application programming interfaces (APIs), and so forth. The mobile electronic device **100** may utilize any suitable OS in accordance with the described embodiments such as a Palm OS®, Palm OS® Cobalt, Microsoft® Windows OS, Microsoft Windows® CE, Microsoft Pocket PC, Microsoft Mobile, Symbian OS™, Embedix OS, Linux, Binary Run-time Environment for Wireless (BREW) OS, JavaOS, a Wireless Application Protocol (WAP) OS, Mac OS X, and so forth.

Application programs generally may allow a user to accomplish one or more specific tasks. Examples of application programs may include, without limitation, one or more messaging applications (e.g., telephone, voicemail, facsimile, e-mail, IM, SMS, MMS, video conferencing), a web browser application, personal information management (PIM) applications (e.g., contacts, calendar, scheduling, tasks), word processing applications, spreadsheet applica-

tions, database applications, media applications (e.g., video player, audio player, multimedia player, digital camera, video camera, media management), gaming applications, and so forth. In various implementations, the application programs may provide one or more graphical user interfaces (GUIs) to communicate information between the mobile electronic device **100** and a user. In some embodiments, application programs may comprise upper layer programs running on top of the OS of the host processor **102** that operate in conjunction with the functions and protocols of lower layers including, for example, a transport layer such as a Transmission Control Protocol (TCP) layer, a network layer such as an Internet Protocol (IP) layer, and a link layer such as a Point-to-Point (PPP) layer used to translate and format data for communication.

As shown in FIG. 1, the mobile electronic device **100** may comprise or implement a focus management module **130**. Focus management module **130** may be arranged to provide automatic focus control to a user. For example, focus management module **130** may be responsible for providing control signals to control one or more of A/V devices **118** of mobile electronic device **100**. Although the focus management module **130** may be shown as being implemented on the same integrated circuit as the host processor **102** for purposes of illustration, it is worthy to note that in various embodiments some portion or the entire focus management module **130** may be included separate from the host processor **102**. The embodiments are not limited in this context.

FIG. 2 illustrates one embodiment of a digital camera system **200**. The digital camera system **200** may be representative of, for example, a digital camera system of mobile electronics device **100**. Although some embodiments may be described with reference to a digital camera by way of example, it may be appreciated that the principles and techniques may be implemented using various A/V devices **118** and accompanying technology. For example, some embodiments may employ a digital video camera in various implementations.

As shown, digital camera system **200** may comprise or implement focus management module **130**, pointing component **214**, display **114**, digital camera **202** and bus **240**. The bus **240** may comprise any suitable interface and/or bus architecture for allowing the digital camera **202** to communicate with focus management module **130**. Although focus management module **130** may be shown as being separate from digital camera **202** for purposes of illustration, it is worthy to note that in various embodiments some portion or the entire focus management module **130** may be included on the same integrated circuit as the digital camera **202**. Alternatively, some portion or the entire focus management module **130** may be disposed on an integrated circuit or other medium (e.g., hard disk drive) external to the integrated circuit of digital camera **202**.

Focus management module **130** may comprise or implement focal point selection module **232**, focus control module **234** and white balance control module **236**. Digital camera **202** may comprise or implement controller **220**, lens component **204**, lens position component **206**, microphone position component **208**, directional microphone **210**, memory **212**, flash control module **216** and flash component **218**. It can be appreciated that a limited number of elements are shown for purposes of illustration and not limitation.

Display **114** of digital camera system **200** may be representative of, for example, display **114** of mobile electronic device **100**. The display **114** may comprise any suitable visual interface for displaying content to a user of digital camera system **200**. In one embodiment, for example, the

display **114** may be implemented by a LCD such as a touch-sensitive color (e.g., 16-bit color) thin-film transistor (TFT) LCD screen. In some embodiments, the touch-sensitive LCD may be used with a stylus or other pointing device. The embodiments are not limited in this context.

Digital camera system **200** may be representative of, for example, one of A/V devices **118** of mobile electronics device **100**. In one embodiment, digital camera system **200** may be implemented as an electronic device used to capture and store images electronically in a digital format. Additionally, in some embodiments digital camera system **200** may be capable of recording sound and/or video in addition to still images. The embodiments are not limited in this context.

Digital camera **202** of digital camera system **200** may comprise controller **220**. Controller **220** may provide control signals to components of digital camera **202**, including lens position component **206**, microphone position component **208** and flash control module **216**, to provide functionality for digital camera system **200**. In some embodiments, controller **220** may also provide control signals to focus management module **130** via bus **240**. In one embodiment, controller **220** may be implemented as, for example, host processor **102** of mobile electronics device **100**. Alternatively, controller **220** may be implemented as a separate processor from host processor **102**. The embodiments are not limited in this context.

Digital camera **202** may further comprise memory **212**. Memory **212** may be implemented as, for example, memory **110** of mobile electronics device **100**. Although the memory **212** may be shown as being separate from controller **220** for purposes of illustration, it is worthy to note that in various embodiments some portion or the entire memory **212** may be included on the same integrated circuit as controller **220**. Alternatively, some portion or the entire memory **212** may be disposed on an integrated circuit or other medium (e.g., hard disk drive) external to the integrated circuit of controller **220**.

Focus management module **130** of digital camera system **200** may be representative of, for example, focus management module **130** of mobile electronics device **100**. Focus management module **130** may be arranged to provide automatic focus control to a user by, for example, providing control signals to control one or more of lens position component **206**, microphone position component **208** and flash control module **216**, for example. In some embodiments the focus management module **130** may be implemented on the same integrated circuit as controller **220**. In various embodiments some portion or the entire focus management module **130** may be included separate from controller **220**. In various embodiments, focus management module **130** may be implemented by one or more hardware components, software components, and/or combination thereof. Focus management module **130** may, for example, be implemented as computer executable instructions stored on memory **212** to be executed by controller **220**. The embodiments are not limited in this context.

Digital camera **202** may comprise a lens component **204** and a lens position component **206**. Lens component **204** may consist of a photographic or optical lens or assembly of lenses made of a transparent material such as glass, plastic, acrylic or Plexiglass, for example. In one embodiment, the one or more lens elements of lens component **204** may reproduce an image of an object and allow for zooming in or out on the object by mechanically changing the focal length of the lens elements. In various embodiments, digital zoom may be employed in digital camera system **200** to

zoom in or out on an image. In some embodiments the one or more lens elements of lens component **204** may be used to focus on different portions of the image by varying the focal length of the lens elements. The desired focus can be obtained with an autofocus feature of digital camera system **200** or by manually focusing on the desired portion of the image, for example.

Lens position component **206** may be configured to receive control signals from controller **220** and focus control module **234** and use this control information to adjust the lens component **204**. In various embodiments, the lens position component **206** may be implemented by one or more hardware components, software components, and/or combination thereof. The embodiments are not limited in this context. For example, lens position component may receive control information from controller **220** indicating that a user wishes to focus on a particular portion of an object. Lens position component **206** may use this control information to configure the lens elements of lens component **204** into the proper configuration to deliver the desired focus.

In one embodiment, display **114** of digital camera system **200** may be coupled to digital camera **202** and may be arranged to capture and reproduce an image with a first focal point. The image may be viewed through lens component **204** and reproduced on display **114**. The image on display **114** may comprise a substantially real-time preview of the image to allow for framing and previewing before capturing a photograph. In some embodiments, the focal point refers to the intended center of interest of a photograph and is typically the point where the image will be in the clearest focus.

Focal point selection module **232** be coupled to the display **114** and may allow for the selection of a second focal point for the image. The second focal point may be selected, for example, by an operator using the display **114** to indicate that a second focal point is desired. In some embodiments, for example, display **114** may comprise a touchscreen display and may be configured to send coordinates for the second focal point to the focal point selection module **232**. These coordinates, which may in one example comprise X, Y coordinates, may correspond to pressure applied to an area of the display **114**. Pressure may be applied to the display **114** by any suitable input device, including a stylus or a finger, for example, and this pressure may be digitized to represent the coordinates. The embodiments are not limited in this context.

Focus control module **234** may be coupled to the focal point selection module **232** and the lens position component **206** to provide focus control signals to the lens position component **206** to focus the lens component **204** on the second focal point. In various embodiments, the focus control signals may represent a focal length for the lens component **204**. In some embodiments, focus control module **234** may determine the focal length for lens component **204** based on the coordinates for the second focal point determined by focal point selection module **232**. Lens position component **206** may use the control signals from focus control module **234** to adjust the lens elements of lens component **204** to achieve the desired focus on the second focal point.

The digital camera system **200** may further comprise a pointing component **214** coupled to the display **114** and the focal point selection module **232**. The pointing component **214** may be configured to control a pointer on the display **114** in response to user or operator commands. The pointing component **214** may send coordinates for the second focal

point to the focal point selection module **232**. The coordinates may correspond to a position for the pointer on the display **114**. In various embodiments the pointer may comprise any overlay image on display **114** that is capable of indicated the currently selected area or focal point. For example, the pointer may include an arrow, box, circle, oval or any other suitable image. The overlay image may have varying degrees of translucency as desired for a given implementation.

In some embodiments, the digital camera system **200** may comprise a directional microphone **210** and a microphone position component **208** coupled to the focus control module **234**. In various embodiments, the focus control module **234** may provide focus control signals to the microphone position component **208** to focus the directional microphone **210** on the second focal point. For example, focus control module **234** may provide coordinates to microphone position component **208**. Microphone position component **208** may use the coordinates to focus directional microphone **210** on the sound emanating from the focal point defined by the coordinates.

Directional microphone **210** may consist of one or more microphones whose response varies with the direction of sound incidence. In one embodiment, directional microphone **240** may be implemented as a digital directional microphone capable of creating null points at different frequencies to cancel various sounds around a desired focal point. In various embodiments, the microphone position component **208** may be implemented by one or more hardware components, software components, and/or combination thereof. The embodiments are not limited in this context.

In some embodiments, the digital camera system **200** may comprise a white balance control module **236** coupled to the focal point selection module **232**. The white balance control module **236** may be configured to modify a white balance setting value for the image based on the second focal point. In various embodiments, white balance control module **236** may be implemented by one or more hardware components, software components, and/or combination thereof. White balance control may refer to the adjustment of the relative amounts of red, green, and blue primary colors in an image such that neutral colors are reproduced correctly. Changing the white balance may change the overall mixture of colors in an image and can be used for generalized color correction.

Flash component **218** and flash control module **216** of digital camera system **200** may be coupled to the focal point selection module **232** and/or controller **220**. The flash control module **216** may be configured to select a flash level value representing flash intensity for the flash component **218** based on the second focal point. In various embodiments, the flash control module **216** may be implemented by one or more hardware components, software components, and/or combination thereof. Flash component **218** may consist of a device or group of devices that produce an instantaneous flash of light, typically around $\frac{1}{3000}$ of a second at a color temperature of about 5500K, to help illuminate a scene. Flash component **218** may be used, for example, to aid in capturing images of quickly moving objects, to create a different temperature light than the ambient light, and to illuminate scenes that do not have enough available light to adequately expose the image.

Operations for the mobile electronic device **100** may be further described with reference to one or more logic flows. It may be appreciated that the representative logic flows do not necessarily have to be executed in the order presented, or in any particular order, unless otherwise indicated. More-

11

over, various activities described with respect to the logic flows can be executed in serial or parallel fashion. The logic flows may be implemented using any desired hardware elements, software elements, or combination of both.

FIG. 3 illustrates a logic flow 300. Logic flow 300 may be representative of the operations executed by one or more embodiments described herein. The logic flow 300 may be performed by various systems and/or devices and may be implemented as hardware, software, and/or any combination thereof, as desired for a given set of design parameters or performance constraints. For example, the logic flow 300 may be implemented by a logic device (e.g., processor) and/or logic comprising instructions, data, and/or code to be executed by a logic device. For purposes of illustration, and not limitation, the logic flow 300 is described with reference to FIGS. 1 and 2. The embodiments are not limited in this context.

As shown in FIG. 3, the logic flow 300 may comprise displaying an image with a first focal point from a digital camera at block 302. The image may be displayed with a touchscreen display such as, for example, display 114 of mobile electronics device 100.

The logic flow 300 may further comprise selecting a second focal point for the image at block 304. The selection of the second focal point for the image may be performed using a touchscreen display. The touchscreen display may be, for example, display 114 of mobile electronic device 100.

At block 306, logic flow 300 may comprise focusing the digital camera on the second focal point. Focusing the digital camera on the second focal point may further comprise generating a set of coordinates for the second focal point and focusing a lens for the digital camera on the second focal point.

In various embodiments, a directional microphone may be focused on the second focal point and/or a flash level value representing flash intensity for a flash component may be selected based on the second focal point.

In some embodiments, the image may be captured using a touchscreen display. Capturing the image using a touchscreen display may comprise a user applying pressure to the touchscreen display to indicate that the image on the display is ready to be committed to memory. Capturing the image, for example, may require a double tap on the touchscreen display or pressure applied to the touchscreen display in the area of the selected second focal point.

The digital camera may be capable of zooming in or out on the image displayed on the touchscreen display in various embodiments. For example, a user may desire to zoom in on an object to focus a photograph on a specific element of the object. In some embodiments, the user may accomplish this goal by applying pressure to the touchscreen display in the area where the user wishes to zoom, similar to the way in which a second focal point is selected. Alternatively, a user may slide a pointer across the touchscreen display to zoom in or out on the object. User interface or graphic user interface (GUI) elements may be implemented and shown by the display 114 to provide zoom controls and information.

In various embodiments, a user may edit or crop the image on the touchscreen display by manipulating the image using the touchscreen display. For example, a user who wishes to crop an image may use the touchscreen display to indicate the desired size of the cropped image by sliding the corners of the image to the desired position. As with zoom controls, a GUI may be implemented for the cropping operations.

12

FIG. 4 illustrates one embodiment of a digital camera system 400. The digital camera system 400 may be representative of, for example, digital camera system 200. As shown, digital camera system 400 may comprise or implement lens component 204, directional microphone 240, visual focal point 402 and audio focal point 404. It can be appreciated that a limited number of elements are shown for purposes of illustration and not limitation.

A mobile electronic device 100 may comprise a digital camera 200 having a lens component 204 and lens position component 206, and a directional microphone 210 and a microphone position component 208. A display 114 may be coupled to the digital camera 200 to reproduce an image from the digital camera 200 with a first focal point. A focal point selection module 232 may be coupled to the display 114 to select a second and a third focal point for the image. A focus control module 234 may be coupled to the focal point selection module 232 and the lens position component 206 and microphone position component 208 to provide focus control signals to the lens position component 206 and the microphone position component 208. The focus control signals may be used to focus the lens component 204 on the second focal point and the directional microphone 210 on the third focal point, for example.

In one embodiment, the second focal point may comprise visual focal point 402. Visual focal point 402 may comprise, for example, an object that a user desires to focus on when capturing a digital image. In one embodiment, the third focal point may comprise audio focal point 404. Audio focal point 404 may comprise a sound or series of sounds, such as the voice of an individual that a user desires to focus on when capturing a digital video, for example. In various embodiments, the visual focal point 402 and the audio focal point 404 may be located remotely from each other.

In one embodiment, directional microphone 210 may be configured to track audio focal point 404 as the position of audio focal point 404 changes. For example, if the selected audio focal point 404 comprises the voice of an individual located in a first position, the individual may move to a second, remote position, and the directional microphone 210 may be configured to follow the voice of the individual to the second position without requiring the user to physically change the position of the digital camera. Tracking an audio focal point 404 may be implemented by any suitable means known in the art, such as sound source localization, for example.

The embodiment described in FIG. 4 may be applicable if a user desires to record a digital video with different audio and video focal points. For example, a user may desire to record a digital video of a waterfall while another individual standing nearby describes the waterfall. In this example, the user may wish to select the waterfall as the visual focal point 402 and the individual describing the scene as the audio focal point 404. In this embodiment, the quality of the recorded digital video may be increased as a result of increased options presented to the user.

A user of a mobile electronic device may desire to capture a digital photograph of a friend standing near a waterfall with a digital camera contained in a mobile electronic device. To view the desired image, the user points the lens of the camera of the mobile electronic device in the direction of the friend and an image is displayed on the touchscreen display of the mobile electronic device. The intended focal point of the image is the face of the friend. However, the digital camera may originally set the default focal point as the waterfall, for example.

In the above described embodiments, the user need only tap the portion of the touchscreen display of the mobile electronic device to set the focal point on a different, desired location. In the given example, the user may tap the touchscreen display in the area of the face of their friend to change the focal point away from the waterfall. In various embodiments the user may also capture the image by tapping the touchscreen a second time or by performing a double tap on the touchscreen. The image may also be captured using the various buttons on the mobile electronic device, including a five way center button press, for example.

If, for example, the user in the same situation desired to record a digital video of their friend and the waterfall using the mobile electronic device, the touchscreen display could be used to continually change the focal point of the video in a manner similar to that described above. Additionally, the touchscreen display could be utilized to control a directional microphone of the mobile electronic device. For example, if the intended video target is the waterfall that is several yards away from the user, and a group of individuals carrying on a conversation are standing near the user, the user could use the touchscreen display to indicate that the sound of the waterfall, and not the conversation of the members of the nearby group, are the intended audio target. As described above, a user may also wish to select different audio and visual focal points. The above described embodiments may provide a user with enhanced ease of operation and may help to ensure better picture quality and a better photographic experience.

Numerous specific details have been set forth to provide a thorough understanding of the embodiments. It will be understood, however, that the embodiments may be practiced without these specific details. In other instances, well-known operations, components and circuits have not been described in detail so as not to obscure the embodiments. It can be appreciated that the specific structural and functional details are representative and do not necessarily limit the scope of the embodiments.

Various embodiments may comprise one or more elements. An element may comprise any structure arranged to perform certain operations. Each element may be implemented as hardware, software, or any combination thereof, as desired for a given set of design and/or performance constraints. Although an embodiment may be described with a limited number of elements in a certain topology by way of example, the embodiment may include more or less elements in alternate topologies as desired for a given implementation.

It is worthy to note that any reference to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in the specification are not necessarily all referring to the same embodiment.

Although some embodiments may be illustrated and described as comprising exemplary functional components or modules performing various operations, it can be appreciated that such components or modules may be implemented by one or more hardware components, software components, and/or combination thereof. The functional components and/or modules may be implemented, for example, by logic (e.g., instructions, data, and/or code) to be executed by a logic device (e.g., processor). Such logic may be stored internally or externally to a logic device on one or more types of computer-readable storage media.

It also is to be appreciated that the described embodiments illustrate exemplary implementations, and that the functional components and/or modules may be implemented in various other ways which are consistent with the described embodiments. Furthermore, the operations performed by such components or modules may be combined and/or separated for a given implementation and may be performed by a greater number or fewer number of components or modules.

Unless specifically stated otherwise, it may be appreciated that terms such as “processing,” “computing,” “calculating,” “determining,” or the like, refer to the action and/or processes of a computer or computing system, or similar electronic computing device, that manipulates and/or transforms data represented as physical quantities (e.g., electronic) within registers and/or memories into other data similarly represented as physical quantities within the memories, registers or other such information storage, transmission or display devices.

It is worthy to note that some embodiments may be described using the expression “coupled” and “connected” along with their derivatives. These terms are not intended as synonyms for each other. For example, some embodiments may be described using the terms “connected” and/or “coupled” to indicate that two or more elements are in direct physical or electrical contact with each other. The term “coupled,” however, may also mean that two or more elements are not in direct contact with each other, but yet still co-operate or interact with each other. With respect to software elements, for example, the term “coupled” may refer to interfaces, message interfaces, API, exchanging messages, and so forth.

While certain features of the embodiments have been illustrated as described above, many modifications, substitutions, changes and equivalents will now occur to those skilled in the art. It is therefore to be understood that the appended claims are intended to cover all such modifications and changes as fall within the scope of the embodiments.

The invention claimed is:

1. A mobile electronic device, comprising:

a lens component coupled to a lens position component; a touchscreen display to display an image having a first focal point, *the image being a substantially real-time preview of a view through the lens component*; and one or more processors to provide:

a focal point selection module to receive a user input of a first type to select a second focal point, the second focal point corresponding to a location on the image displayed on the touchscreen display;

a focus control module coupled to the focal point selection module to provide one or more focus control signals to the lens position component in order to cause the lens position component to *automatically* focus the lens component from the first focal point to the second focal point while the image is being displayed *as the substantially real-time preview of the view through the lens component*;

a flash [component] control module coupled to a flash [control module] component, wherein the flash control module is configured to select a flash level value representing a flash intensity for the flash component based on the second focal point; and

wherein the one or more processors captures the image, based on the flash level value, in response to a second type of user input on the touchscreen display, the second type of user input being different than the first type of user input, *and performs cropping operations to*

15

crop the image in response to a user using cropping controls of a graphical user interface (GUI) shown by the touchscreen display to indicate a desired size of cropped image by sliding corners of the image to a desired position.

2. The mobile electronic device of claim 1, wherein the touchscreen, display sends coordinates for the second focal point to the focal point selection module, the coordinates corresponding to the location of the first type of user input on the touchscreen display.

3. The mobile electronic device of claim 1, wherein the one or more processors is further configured to provide a pointing component to control a pointer on the touchscreen display, a location of the pointer on the touchscreen display corresponding to the second focal point.

4. The mobile electronic device of claim 1, wherein the focus control signals designate a focal length for the lens component.

5. The mobile electronic device of claim 1, further comprising a directional microphone component, and wherein the focus control module is configured to provide focus control signals to focus the directional microphone component on the second focal point.

6. The mobile electronic device of claim 1, wherein the one or more processors is further configured to provide a white balance control module, the white balance control module being configured to modify a white balance setting value for the image based on the second focal point.

7. A method for operating a mobile device, the method being performed by one or more processors and comprising: displaying, on a touchscreen display, an image having a first focal point, the image being provided by a lens component;

selecting a second focal point for the image in response to receiving a first type of user input on the touchscreen display, the second focal point corresponding to a location on the image displayed on the touchscreen display;

focusing the lens component from the first focal point to the second focal point while the image is being displayed;

selecting a flash level value representing a flash intensity for a flash component based on the second focal point; and

capturing the image, based on the flash level value, in response to a second type of user input on the touchscreen display, the second type of user input being different than the first type of user input.]

8. The method of claim 7, wherein focusing the lens component on the second focal point includes generating a set of coordinates for the second focal point.]

9. The method of claim 7, wherein focusing the lens component on the second focal point includes focusing a directional microphone component on the second focal point.

10. A non-transitory computer readable storage medium storing instructions, the instructions when executed by one or more processors cause the one or more processors to perform a method comprising:

displaying, on a touchscreen display, an image having a first focal point, the image being provided by a lens component;

selecting a second focal point for the image in response to a first type of user input on the touchscreen display, the second focal point corresponding to a location on the image displayed on the touchscreen display;

16

focusing the lens component from the first focal point to the second focal point while the image is being displayed;

selecting a flash level value representing a flash intensity for a flash component based on the second focal point; and

capturing the image, based on the flash level value, in response to a second type of user input on the touchscreen display, the second type of user input being different than the first type of user input.]

11. The storage medium of claim 10, wherein focusing the lens component on the second focal point includes generating a set of coordinates for the second focal point.]

12. The storage medium of claim 10, wherein focusing the lens component on the second focal point includes focusing a directional microphone component on the second focal point.

13. The storage medium of claim 10, wherein the instructions when executed by the one or more processors cause the one or more processors to perform a method further comprising modifying a white balance setting value for the image based on the second focal point.]

14. A mobile electronic device, comprising:

a lens component;

a touchscreen display to display an image having a first visual focal point, *the image being a substantially real-time preview of a view through the lens component*;

a directional microphone component; and

one or more processors coupled to the lens component, the touchscreen display, and the directional microphone component, the one or more processors being configured to provide:

a focal point selection module to select a second visual focal point and an audio focal point for the image, wherein the second visual focal point and the audio focal point correspond to different portions of the image; and

a focus control module coupled to the focal point selection module to (i) provide focus control signals to the lens component in order to *automatically* change a focus of the lens component from the first visual focal point to the second visual focal point, and (ii) provide focus control signals to the directional microphone component in order to *automatically* focus the directional microphone component on a target, in the image, of the audio focal point, while continuing to display the image *as the substantially real-time preview of the view through the lens component* on the touchscreen display.

15. The mobile electronic device of claim 14, wherein the directional microphone component is configured to track the audio focal point as a position of the audio focal point changes.

16. The mobile electronic device of claim 1, wherein the first type of input includes a single tap, and wherein the second type of input includes a double tap.

17. The mobile electronic device of claim 1, wherein the second focal point corresponds to coordinates of the first type of user input.

18. The mobile electronic device of claim 1, wherein focusing the lens component on the second focal point includes generating a set of coordinates corresponding to coordinates of the first type of user input.

19. The mobile electronic device of claim 18, wherein the set of coordinates comprise X, Y coordinates.

20. The mobile electronic device of claim 19, wherein the second focal point corresponds to an area where the image will be in the clearest focus.

21. The mobile electronic device of claim 19, wherein the second focal point comprises an intended center of interest of the image.

22. The mobile electronic device of claim 19, wherein the second focal point comprises an object that the user desires to focus the image on when capturing the image.

23. The mobile electronic device of claim 1, wherein graphic user interface (GUI) elements are shown by the touchscreen display to provide cropping operations.

24. The mobile electronic device of claim 1, wherein the one or more processors automatically focus a directional microphone on the second focal point.

25. The mobile electronic device of claim 24, wherein focusing the directional microphone comprises creating null points at different frequencies to cancel various sounds around the second focal point.

26. A method for operating a mobile device, the method being performed by one or more processors and comprising:

displaying, on a touchscreen display, an image having a first focal point, the image being provided by a lens component as a substantially real-time preview of a view through the lens component;

selecting a second focal point for the image in response to receiving a first type of user input on the touchscreen display, the second focal point corresponding to a location on the image displayed on the touchscreen display;

automatically focusing the lens component from the first focal point to the second focal point while the image is being displayed as the substantially real-time preview of the view through the lens component;

selecting a flash level value representing a flash intensity for a flash component based on the second focal point; capturing the image, based on the flash level value, in response to a second type of user input on the touchscreen display, the second type of user input being different than the first type of user input; and

cropping the image in response to a user using cropping controls of a graphical user interface (GUI) shown by the touchscreen display to indicate a desired size of cropped image by sliding corners of the image to a desired position.

27. The method of claim 26, wherein the second focal point corresponds to coordinates of the first type of user input.

28. The method of claim 26, wherein the focusing the lens component on the second focal point includes generating a set of coordinates corresponding to coordinates of the first type of user input.

29. The method of claim 28, wherein the set of coordinates comprise X, Y coordinates.

30. The method of claim 29, wherein the second focal point corresponds to an area where the image will be in the clearest focus.

31. The method of claim 29, wherein the second focal point comprises an intended center of interest of the image.

32. The method of claim 29, wherein the second focal point comprises an object that the user desires to focus the image on when capturing the image.

33. The method of claim 26, wherein graphic user interface (GUI) elements are shown by the touchscreen display to provide cropping operations.

34. The method of claim 26, further comprising: automatically focusing a directional microphone on the second focal point.

35. The method of claim 34 wherein focusing the directional microphone comprises: creating null points at different frequencies to cancel various sounds around the second focal point.

36. A non-transitory computer readable storage medium storing instructions, the instructions when executed by one or more processors cause the one or more processors to perform a method comprising:

displaying, on a touchscreen display, an image having a first focal point, the image being provided by a lens component as a substantially real-time preview of a view through the lens component;

selecting a second focal point for the image in response to a first type of user input on the touchscreen display, the second focal point corresponding to a location on the image displayed on the touchscreen display;

automatically focusing the lens component from the first focal point to the second focal point while the image is being displayed as the substantially real-time preview of the view through the lens component;

selecting a flash level value representing a flash intensity for a flash component based on the second focal point; capturing the image, based on the flash level value, in response to a second type of user input on the touchscreen display, the second type of user input being different than the first type of user input; and

cropping the image in response to a user using cropping controls of a graphical user interface (GUI) shown by the touchscreen display to indicate a desired size of cropped image by sliding corners of the image to a desired position.

37. The storage medium of claim 36, wherein the second focal point corresponds to coordinates of the first type of user input.

38. The storage medium of claim 36, wherein the focusing the lens component on the second focal point includes generating a set of coordinates corresponding to coordinates of the first type of user input.

39. The storage medium of claim 38, wherein the set of coordinates comprise X, Y coordinates.

40. The storage medium of claim 39, wherein the second focal point corresponds to an area where the image will be in the clearest focus.

41. The storage medium of claim 39, wherein the second focal point comprises an intended center of interest of the image.

42. The storage medium of claim 39, wherein the second focal point comprises an object that the user desires to focus the image on when capturing the image.

43. The storage medium of claim 36, wherein graphic user interface (GUI) elements are shown by the touchscreen display to provide cropping operations.

44. The storage medium of claim 36, wherein the instructions when executed by one or more processors cause the one or more processors to perform a method further comprising:

automatically focusing a directional microphone on the second focal point.

45. The storage medium of claim 44, wherein focusing the directional microphone comprises:

creating null points at different frequencies to cancel various sounds around the second focal point.

46. The mobile electronic device of claim 14, wherein the one or more processors crops the image in response to a user

19

using cropping controls of a graphical user interface (GUI) shown by the touchscreen display.

47. The mobile electronic device of claim 46, wherein the one or more processors crops the image in response to the user using the touchscreen display to indicate a desired size of cropped image by sliding corners of the image to a desired position.

48. The mobile electronic device of claim 14, wherein the second visual focal point is selected in response to a first type of user input on the touchscreen display.

49. The mobile electronic device of claim 48, wherein the second focal point corresponds to coordinates of the first type of user input.

50. The mobile electronic device of claim 48, wherein the focusing the lens component on the second focal point includes generating a set of coordinates corresponding to coordinates of the first type of user input.

51. The mobile electronic device of claim 50, wherein the set of coordinates comprise X, Y coordinates.

20

52. The mobile electronic device of claim 51, wherein the second focal point corresponds to an area where the image will be in the clearest focus.

53. The mobile electronic device of claim 51, wherein the second focal point comprises an intended center of interest of the image.

54. The mobile electronic device of claim 51, wherein the second focal point comprises an object that the user desires to focus the image on when capturing the image.

55. The mobile electronic device of claim 14, wherein graphic user interface (GUI) elements are shown by the touchscreen display to provide cropping operations.

56. The mobile electronic device of claim 14, wherein focusing the directional microphone comprises creating null points at different frequencies to cancel various sounds around the second focal point.

* * * * *