



US00RE49085E

(19) **United States**
(12) **Reissued Patent**
Miller et al.

(10) **Patent Number:** **US RE49,085 E**
(45) **Date of Reissued Patent:** **May 31, 2022**

(54) **METHOD AND COMPOSITION FOR AGRICULTURAL POTASSIUM FERTIGATION**

(71) Applicants: **John C. Miller**, Fresno, CA (US);
Deborah L. Miller, Fresno, CA (US)

(72) Inventors: **John C. Miller**, Fresno, CA (US);
Deborah L. Miller, Fresno, CA (US)

(21) Appl. No.: **15/706,527**

(22) Filed: **Sep. 15, 2017**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,148,993**
Issued: **Oct. 6, 2015**
Appl. No.: **14/564,510**
Filed: **Dec. 9, 2014**

U.S. Applications:

(63) Continuation-in-part of application No. 14/243,184, filed on Apr. 2, 2014, now Pat. No. 8,986,417, which is a continuation-in-part of application No. 13/385,736, filed on May 12, 2012, now Pat. No. 8,721,758, which is a continuation-in-part of application No. 13/136,032, filed on Jul. 21, 2011, now Pat. No. 8,568,506, which is a continuation of application No. 12/283,448, filed on Sep. 12, 2008, now abandoned.

(60) Provisional application No. 61/056,151, filed on May 27, 2008.

(51) **Int. Cl.**
A01C 23/04 (2006.01)
C05G 5/23 (2020.01)
A01G 7/00 (2006.01)
A01G 25/02 (2006.01)
C05C 5/02 (2006.01)
C05D 1/00 (2006.01)
C05B 7/00 (2006.01)

(52) **U.S. Cl.**
CPC **A01C 23/042** (2013.01); **A01G 7/00** (2013.01); **A01G 25/02** (2013.01); **C05B 7/00** (2013.01); **C05C 5/02** (2013.01); **C05D 1/00** (2013.01); **C05G 5/23** (2020.02)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,038,316 A	4/1936	Rosenstein	
2,088,869 A	8/1937	Porter	
2,163,065 A *	6/1939	Rosenstein	71/1
2,969,280 A	1/1961	Peck	
3,326,232 A	6/1967	Stamps et al.	
3,332,767 A	7/1967	Heins	
3,578,432 A	5/1971	Stiles	
3,888,652 A	6/1975	Yie et al.	
4,133,671 A	1/1979	Mikel	

(Continued)

Primary Examiner — Jerry D Johnson


Assistant Examiner — Alan Diamond

(74) *Attorney, Agent, or Firm* — Andrew D. Fortney;
Central California IP Group, P.C.

(57) **ABSTRACT**

An agricultural potassium-fertigation method for emitter-irrigation potassium fertigation feeds a potassium-nutrient feedstock comprised of potassium formate and water to an active emitter-irrigation system continuously, or substantially continuously, at low levels, during the entire time, or substantially the entire time, that irrigation water is sufficiently flowing through the irrigation system during a prolonged term.

17 Claims, 4 Drawing Sheets




(56)

References Cited

U.S. PATENT DOCUMENTS

4,145,208	A	3/1979	Gulko et al.	
4,337,786	A	7/1982	Myers et al.	
4,878,614	A	11/1989	Hach et al.	
4,917,304	A	4/1990	Mazzei et al.	
4,969,947	A *	11/1990	Moore	71/28
5,246,164	A	9/1993	McCann et al.	
5,678,771	A	10/1997	Chapman	
7,207,503	B1	4/2007	Stengel et al.	
7,325,756	B1	2/2008	Giorgis	
8,568,506	B1 *	10/2013	Miller et al.	71/28
8,628,598	B1	1/2014	Miller et al.	
8,690,982	B1	4/2014	Miller et al.	
8,690,983	B1	4/2014	Miller et al.	
8,690,984	B1	4/2014	Miller et al.	
8,721,758	B1	5/2014	Miller et al.	
8,721,759	B1	5/2014	Miller et al.	
8,821,646	B1 *	9/2014	Miller et al.	134/22.12
8,979,969	B1	3/2015	Miller et al.	
8,986,417	B1	3/2015	Miller et al.	
8,986,418	B1	3/2015	Miller et al.	
9,161,489	B1 *	10/2015	Miller	C05G 5/23
9,474,215	B1 *	10/2016	Miller	C05F 11/00
2009/0249848	A1	10/2009	Peters	
2016/0185673	A1 *	6/2016	Miller	C05B 7/00
				239/10
2016/0347675	A1 *	12/2016	Roach	C05C 11/00

* cited by examiner






Fig. 2




Fig. 3




Fig. 4

**METHOD AND COMPOSITION FOR
AGRICULTURAL POTASSIUM
FERTIGATION**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

This application is a continuation in part of application Ser. No. 14/243,184, filed on Apr. 2, 2014, which is a continuation in part of Ser. No. 13,385,736, filed Mar. 5, 2012, which is a continuation in part of application Ser. No. 13/136,032, filed on Jul. 21, 2011, which is a continuation in part of application Ser. No. 12/283,448, filed on Sep. 12, 2008, claiming the domestic priority benefit of application No. 61/056,151 filed on May 27, 2008, inventors Miller et al.

BACKGROUND OF THE INVENTION

The present invention relates to methods for fertilization by adding fertilizer nutrients to agricultural irrigation systems.

The agriculture industry adds fertilizers to the plant environs, such as the soil, to enhance crop growth and subsequent yields. Commercial fertilizers are usually selected of a variety of formulations depending on the crop and its nutrient requirements.

Fertilizers generally are classified according to their NPK content. NPK is common terminology used in the fertilizer industry and stands for (1) N—the amount of nitrogen in the formulation as N; (2) P—the amount of phosphorus in the formulation as P₂O₅; and (3) K—the amount of potassium in the formulation as K₂O. Nitrogen, phosphorus and potassium are the basic plant nutrients or macronutrients that are taken up and utilized by the growing crops, and they are commonly provided or augmented by the addition of fertilizers (NPK fertilizers).

A fertilizer, as that term is used herein and as generally understood, refers to the nutrient-containing materials used to deliver fertilizer nutrients to a crop. Conventional fertilizers typically will contain materials that are extraneous to the crops's nutrient-uptake and solid condition ("yield-extraneous constituents") but which, for practical and/or other reasons, are necessary to the delivery of the nutrients. The process of delivering fertilizer nutrients to crops is referred to as fertilization.

The fertilization method of adding fertilizers to the water being used to irrigate the crops is called "fertigation", reflecting this combination of irrigation and fertilization. Fertigation reduces equipment, fuel and labor expended in the addition of fertilizers in comparison to mechanical delivery of fertilizers to the crops, and thus fertigation achieves a significant overall cost savings.

To conserve water, which is decreasing in availability and increasing in cost, current conventional technology includes micro-irrigation systems that deliver precise amounts of water directly to the soil holding the root system of the plant that is being grown. In the past twenty to thirty years, a large percentage of crop producers in the western and southwestern United States have converted from flood and sprinkler irrigation systems to micro-irrigation technology. Micro-

irrigation systems contain devices called emitters, micro-sprinklers or other such devices that provide the precise amounts of water directly to the desired soil site, namely the soil holding the roots of the plant or crop being irrigated.

Micro-irrigation systems are sensitive to water quality and the inclusion of fertilizers and other additives stemming from the refinement of the micro components. These emitters, micro-sprinklers or other micro devices have very tiny orifices and/or a long tortuous narrow passageway that provide the requisite pressure for delivery of precise amounts of water in a uniform manner to each plant in the crop being irrigated so long as deposits do not build up inside them. Deposits from any source foul or plug these micro components. The smallest particle or foreign material can cause fouling of these devices. Water quality and the inclusion of fertilizers can, and frequently does, cause severe plugging problems. The problems arise from a number of factors: (1) the irrigation water is typically obtained from wells, reservoirs, canals, lakes, or rivers which contain various amounts of dissolved minerals; and (2) fertilizers can form insoluble salts and/or cause particulate formation when added to the water. Macro-irrigation systems (macro-sprinkler irrigation systems) mainly tolerate these conditions, while micro-irrigation systems are extremely intolerant.

In more detail, the addition of conventional fertilizer formulations to irrigation water normally increases the loading of inorganic salts over that already in the water. When the loading, or the combined loading, is too high, the solubilities of at least some of the naturally-occurring irrigation-water minerals and/or added compounds are exceeded and particulate formation increases dramatically. When particulates form, significant deposits begin to build up throughout the irrigation system. The end result for emitters or micro-sprinklers is plugging.

Plugging results in uneven distribution of water and nutrients to the crop being irrigated, and in some cases, the complete shut-down of the micro-irrigation system. Problem-free use of additives such as fertilizers in micro-irrigation systems is normally seen only in irrigation systems that use relatively pure water sources.

The conventional agricultural practice is to make intermittent or periodic applications of fertilizers. Such intermittent additions might be a single addition, or a plurality of additions, of large amounts (high concentrations) of fertilizer during a brief time interval each growing season or crop cycle. (The number of applications per growing season or crop cycle usually depends on the crop and/or the type of fertilizer being added.) When the fertilizer-delivery method is fertigation, fertilizers are typically slug fed into the irrigation system as quickly as possible to minimize the labor requirements and ease material handling. Slug feeding of a block (portion of a field) normally entails feeding the large amounts (high concentrations) of fertilizer to the irrigation water over a six to seven hour period during irrigation, and then, after the fertilizer feed is shut off, continuing the irrigation of that block for an additional two to three hours to rinse out all of the fertilizer that is contained inside the irrigation system, insuring that all of the fertilizer intended for the block is in fact delivered to the block.

The cost of commercial fertilizer formulations is, however, itself significant, and commercially viable fertilizer formulations (formulations sufficiently inexpensive for bulk agricultural use) typically include, as mentioned above, yield-extraneous constituents which do not contribute to plant nutrition or soil condition, and can even be undesirable components. Further, the bulk weight of commercial fertil-

izer formulations typically is water which increases the shipping costs. The water of a fertilizer formulation is analogous to, or at least approaches being, a yield-extraneous constituent because its contribution to the water requirements of a crop normally is negligible, particularly in comparison to its adverse impact on shipping, storage and handling but since water is normally required for an unimpeded container-to-irrigation-system fertilizer addition it is analogous to, but still not considered herein, an "essential yield-extraneous constituent material".

The terms "micro-irrigation" and "macro-irrigation" as used herein refer respectively to (1) micro-sprinklers, drip, and subsurface drip systems and (2) sprinkler systems without micro components which are primarily overhead sprinklers. The terms "overhead sprinkler" and "overhead sprinklers" as used herein refer to irrigation systems in which the irrigation water is emitted or sprayed from sprinkler heads, nozzles or other irrigation devices disposed at a position elevated from ground level, that normally (but not necessarily) are engaged directly above the crop being irrigated. Overhead sprinkler irrigation systems are normally macro-irrigation systems because micro-irrigation normally depend on a close proximity between the emitters and soil immediate the crop while overhead sprinklers are normally spaced apart from the soil immediate the crop. Such micro- and macro-irrigation systems are collectively referred to herein as "emitter-irrigation" systems because they each emit or eject sequential small quantities of irrigation water from irrigation lines or tubes directed more or less towards the crop being irrigated.

SUMMARY OF THE INVENTION

The present invention provides a method for emitter-irrigation potassium fertigation wherein a potassium-nutrient feedstock comprised of potassium formate and water is charged to an active emitter-irrigation system continuously, or substantially continuously, at low levels, during the entire time, or substantially the entire time, that irrigation water is sufficiently flowing through the irrigation system during a prolonged term ("prolonged-termed continuous charge" or prolonged-termed continuous fertigation") wherein the potassium-nutrient feedstock has a high potassium-nutrient content, has a high organic carbon content, has a minimal amount of water, has no essential yield-extraneous constituent such as sulfate, has no essential yield-adverse constituent such as degradable thiosulfate, phosphate or chloride and its minimal water content drastically reduces shipping, storage and handling costs.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is an at least partially diagrammatic view of a system used in certain embodiments of the present invention;

FIG. 2 is an at least partially diagrammatic view of a section of the system of FIG. 1.

FIG. 3 is an at least partially diagrammatic view of a section of the system of FIG. 1.

FIG. 4 is an at least partially diagrammatic view of a section of a system used in certain embodiments of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Prolonged Term

The prolonged-term charge of the potassium-nutrient feedstock to the irrigation system continuously or substan-

tially continuously at low levels of the present invention provides uniform, consistent levels of available potassium during a crop cycle until it is no longer desired as fruiting approaches, in comparison to conventional fertigation techniques.

By prolonged term is meant herein a time period that extends from an interval (term) during a crop cycle comprising at least multiple consecutive irrigations, and preferably comprising at least a three month time period or a time period comprising fifty percent of the respective crop cycle, and more preferably at least a four month time period or a time period comprising seventy-five percent of the respective crop cycle, or ninety percent of the respective crop cycle or even an entire crop cycle. (A crop cycle is a crop's growing period, from embryonic to maturity or harvest, during which the crop is irrigated.) Since potassium promotes fruiting (fruit development), that is, the ripening of a crop plant's fruit, when such ripening is at, or approaches, optimal, potassium fertilization normally is ceased to avoid fruit development beyond the point that provides the crop's best agronomic output (agronomic payload or payout), such as fruit, vegetable, nut and the like sections of the plant, prior to harvest.

Prolonged-Termed Continuous:

The charge of the potassium-nutrient feedstock to the irrigation water is prolonged-termed continuous. By a prolonged-termed (or prolonged-term) continuous charge of potassium-nutrient feedstock (or continuously charging potassium-nutrient feedstock over a prolonged term) is meant herein that the charge is continuous when the irrigation system is active during a given prolonged term. In more detail, when an irrigation system is idled, water usually drains out and the system becomes mainly filled with air. Upon reactivation, there is a time delay between the start of water flowing into the irrigation system and the point of time at which the system reaches its full or normal operating pressure (from about 10 to 150 psi depending on the system). The continuous charge of potassium-nutrient feedstock normally ceases when the shutdown (the idling) of the irrigation system initiates (and the water pressure falls below full or normal operating pressure for the given system) and does not recommence until at least a prependerance of the irrigation system is refilled with water, at which point the system is typically approaching, but might not yet be at, its full or normal operating pressure. In other words, by a continuous charge of potassium-nutrient feedstock on a given irrigation day is meant herein that the charge is continuous when irrigation water is flowing at least at ninety percent of full or normal operating pressure.

The Potassium-Nutrient Feedstock

The method and/or system of the present invention, namely the method and/or system for fertigation by charging a potassium-nutrient feedstock comprised of potassium formate and water to the irrigation system, is drastically advantageous because the feedstock has a high potassium-nutrient content, has a high organic carbon content, has a minimal amount of water, has no essential yield-extraneous constituent such as sulfate, has no yield-adverse constituent such as degradable thiosulfate, phosphate or chloride and its minimal water content drastically reduces shipping, storage and handling costs. It has no cations or anions (such as phosphate as mentioned above) that increase the deposit-forming load of the irrigation water to which it is fed. Such anions or cations, and other adverse constituents such as degradable thiosulfate, are typically present in commercial fertilizers because they are needed for the delivery of the nutrient or for other reasons tied to the respected formulation; in other

words, they are essential yield-adverse constituents with respect to those formulations.

At the preferred concentration levels of potassium formate of from 50 to 75 wt. percent, the feedstock ranges from a 0-0-28 NPK fertilizer to a 0-0-42 NPK fertilizer. In more preferred embodiments, the concentration level of potassium formate in the feedstock is from 65 to 75 wt. percent, and therefore the feedstock ranges from about a 0-0-36 NPK fertilizer to a 0-0-42 NPK fertilizer.

Further, in preferred embodiments, the potassium-nutrient feedstock is charged to the irrigation system at levels sufficient to provide a concentration of from 1 to 200 ppm of potassium as K₂O in said treated irrigation water, and more preferably from 5 to 100 ppm of potassium as K₂O in said treated irrigation water.

In contrast, the most basic (simple) sources of potassium used in conventional agricultural fertigation are potassium sulfate and potassium thiosulfate. Potassium sulfate is soluble only up to 8% potassium as K₂O (a 0-0-8 NPK fertilizer), requiring huge costs for (a) the shipment and storage of this dilute fertilizer and (b) the time and labor required to slug-feed such a dilute material to an irrigation system. Potassium thiosulfate (a 0-0-25 NPK fertilizer) has a higher solubility than potassium sulfate (but still far lower than the present invention's more preferred 0-0-36 NPK to 0-0-42 NPK feedstock) but it is expensive and, since the sulfur of thiosulfate is not in its highest oxidation state, it is at risk of decomposition and precipitation, which leads to fouling of the irrigation system and impaired irrigation. (No oxidants, such as chlorine, can be used in the irrigation system at or about the same time as potassium thiosulfate.) Potassium nitrate, another potassium source, is very soluble but (a) its distribution is restricted or prohibited by laws and/or regulations because of security risks associated with its nitrate content and (b) it is prohibitively expensive. Potassium phosphate, another highly soluble potassium source, is also much too expensive for conventional fertigation practices and the phosphate, an essential yield-adverse constituent with respect to this fertilizer, can cause precipitation and fouling problems.

The present invention does not exclude sequential and/or concomitant addition of other materials if desired, including but not limited to one or more other fertilizers and the like. In preferred embodiments, particularly with respect to micro-irrigation systems, concomitant addition of other materials is limited to materials having molecular weights that do not exceed 1,000 as charged or as developed within the irrigation system.

The potassium-nutrient feedstock is charged to an irrigation system by feeding it to the irrigation water either (1) flowing through a mixing chamber that discharges to a main line of an irrigation system downstream of any irrigation-system filters and upstream of the delivery points of the irrigation system or (2) flowing through a main line of an irrigation system (that is, directly charging to a main line of an irrigation system) downstream of any irrigation-system filters and upstream of the delivery points of the irrigation system, as illustrated in FIG. 1 to FIG. 3 and discussed below.

The method of the present invention in certain preferred embodiments employs an automated feed system which feeds or charges the material to the mixing chamber or main line at a pre-selected or pre-determined rate, which is discussed below. Such an automated feed system therefore charges the potassium-nutrient feedstock at a pre-selected or pre-determined rate. The automatic feeding of the potassium-nutrient feedstock at a pre-selected or pre-determined

rate is particularly important when it is desirable to feed the feedstock at a rate relative to the irrigation-water flow rate, so as to automatically provide and maintain a pre-selected or pre-determined concentration of the feedstock in the irrigation water throughout the fertigation period, including when the irrigation water flow rate varies from one set to the next. Such an automated feed system would be inactive or idle when there is no irrigation water flow in the irrigation line served by the automated feed system. That automated feed system may be, and in certain embodiments is preferably, automatically activated or triggered upon the commencement of water flow in the irrigation line, and may be, and in certain embodiments is preferably, automatically deactivated or halted when the flow of irrigation water ceases.

The System of FIG. 1 to FIG. 3

Referring to FIG. 1 and, to the extent components are shown in FIG. 2 and FIG. 3, to FIG. 2 and FIG. 3 also, there is shown a system of the present invention designated by the general reference numeral 10. An agricultural irrigation system distributes irrigation water typically from a water source whether it be a well, surface water (such as water in a canal, reservoir, stream or the like), reclaimed or recycled water. A stream of irrigation water is pumped into a main line (irrigation system main line) and then is filtered. The system 10, as shown in FIG. 1, FIG. 2 and FIG. 3, is an embodiment of an extended system used in certain embodiments of the present invention because system 10 includes such filters and a segment of such a main line from a point upstream of the filters to a point downstream of the filters, and the addition of potassium-nutrient feedstock occurs between these two points.

As described below, a segment of a stream of irrigation water that is running between the irrigation-water source and the irrigation line(s) in the field(s) is within the system 10 wherein the irrigation water is first filtered and then treated with the feedstock of the present invention. The system 10 includes a control unit 12, optionally a plurality of filters, which here are shown as sand-media filters 16, an irrigation-water line, which here is shown as a pre-filter (and somewhat higher pressure) segment of an irrigation-water main line, or pre-filter main line 18, which feeds irrigation water (identified and discussed below) through each of the sand-media filters 16, and also through a mixing chamber 14, to a post-filter (and somewhat lower pressure) segment of the irrigation-water main line, or post-filter main line 20. (The post-filter main line 20 is a transport pipe that carries irrigation water to one or more agricultural fields, such as the agricultural field 510 shown in phantom, and obviously not to scale, in FIG. 1. One or more secondary transport pipes service a typical agricultural field, such as transport pipes 520 shown in FIG. 1. Devices for delivering the irrigation water at points in the field, shown as devices 530 in FIG. 1, can be overhead sprinklers or micro-devices (such as emitters or micro-sprinklers.) The potassium-nutrient feedstock is stored in one of the storage containers 22 which may be conveniently disposed nearby the control unit 12 as shown. As shown, such storage containers or tanks 22 include one for each of the materials to be added, including but not limited to extraneous fertilizers, are shown. (The storage tanks 22 are shown staggered for simplicity in showing each of the feed lines 40.)

In other words, the method of the present invention requires at least one storage facility, namely one for the potassium formate solution. The method of the present invention does not exclude the feeding of other materials as described in more detail below.

There is a feed line **40** between each of the raw-material tanks **22** and the mixing chamber **14**. These feed lines **40** run through the interior of the control unit **12** (not shown in FIG. **1**) to the mixing chamber **14**. (Only one of such feed lines **40** is shown running to the mixing chamber **14** for simplicity). For each of the materials, and feed lines **40**, there is an injection valve **96** along the feed line **40** just ahead of the point at which the feed line **40** enters the mixing chamber **14**, none of which is shown in FIG. **1** for simplicity, and all of which are shown in FIG. **2** and FIG. **3**.

Irrigation water flows to and through each of the sand-media filters **16** through filter feed lines **72**. A stream of the irrigation water also flows from the pre-filter main line **18** to the mixing chamber **14** through a mixing-chamber feed line **70**, except when the mixing-chamber feed line **70** is closed off. The water flows from the mixing chamber **14** and from each of the sand-media filters **16** discharge to the post-filter main line **20**.

Referring now in particular to FIG. **2** (where the storage tanks **22** are again shown staggered for simplicity in showing each of the feed lines **40**), each of the feed lines **40** is equipped with a feed pump **74**. Each of these feed pumps **74** is controlled by a flow controller **76** and a master controller **78**. Each of these feed pumps **74** is in electrical communication with a flow controller **76** and the master controller **78** (the electrical connections are not shown) and injects or pumps in its respective material to its respective feed line **40** at the rate determined by the flow controller **76** and the master controller **78**.

The control unit **12** is divided into two chambers, one of which is a lower chamber **82** which houses the feed pumps **74** and a portion of the feed lines **40** downstream of the respective tanks **22** and upstream of the mixing chamber **14**. The second chamber of the control unit **12** is an upper chamber **92** which houses the flow controller **76**, the master controller **78** and an optional temperature controller **77**.

Along each of the feed lines **40** downstream of the respective feed pumps **74** and upstream of the mixing chamber **14** is, as mentioned above, an injection valve **96**, each of which is preferably equipped with a backflow preventer (not shown). Along the mixing-chamber feed line **70** are, in the order of from upstream (closest to the pre-filter main line **18**) to downstream (closest to the mixing chamber **14**) an optional booster pumps **98**, a mixing-chamber feed-line flow meter **100**, a mixing-chamber feed-line flow sensor **102** and a mixing-chamber feed-line shut-off valve **104**. The line opposite the mixing-chamber feed line **70** is a mixing-chamber discharge line **71** that is open to the post-filter main line **20**. Along the mixing-chamber discharge line **71**, in the order of from upstream (closest to the mixing chamber **14**) to downstream (closest to the post-filter main line **20**), are an optional mixing-chamber discharge-line thermocouple **106** and a mixing-chamber discharge-line shut-off valve **108**.

The pre-filter main line **18** is open to the mixing chamber **14** through the mixing-chamber feed line **70**, and is open to each of the sand-media filters **16** through filter feed lines **72** or openings. Untreated irrigation water, that is, irrigation water that is not yet treated by the system of the present invention, which is shown by flow arrows and is designated as untreated irrigation water **110** in FIG. **3**, flows through the pre-filter main line **18** and discharges to the mixing chamber **14** and the sand-media filters **16** through these respective lines.

As noted above, the mixing-chamber discharge line **71** is open to, and discharges to, the post-filter main line **20**, which is best seen in FIG. **3**. In addition, each of the sand-media filters **16** is open to and discharges to, the post-filter main

line **20** via filter discharge lines **114** or openings. The untreated irrigation water **110** of the pre-filter main line **18** thus flows to the post-filter main line **20** and therein receives the discharge from the mixing-chamber discharge line **71**, becoming irrigation water that carries or has been treated with the potassium-nutrient feedstock of the present invention. Such treated irrigation water is shown by flow arrows and is designated as treated irrigation water **111** in FIG. **3** and elsewhere herein.

Along the post-filter main line **20**, in the order of from upstream (closest to the mixing-chamber discharge line **71**) to downstream (farthest from the mixing-chamber discharge line **71**), are a post-filter main-line pressure gauge **126** and a post-filter main-line flow sensor **128**.

Along the pre-filter main line **18**, in the order of from upstream (closest to the mixing-chamber feed line **70**) to downstream (farthest from the mixing-chamber feed line **70**), are a pre-filter main-line pressure sensor **130** and a pre-filter main-line pressure gauge **132**.

The storage tanks **22** can vary in size depending on the size and nutrient needs of the irrigation site they service. Typical storage container sizes are between 300 and 6,500 gallons. The electrical connections between the feed pumps **74** along the feed lines **40** and the controlling flow controller **76** and master-controller **78** each consist separately of an on/off power control (not shown) and a feedback loop (not shown) which controls the output of the respective feed pumps **74**, and the construction and operation of such electrical connections are well within the skill of an ordinary person skilled in the art. The upper chamber **92** of the control unit **12**, which houses the electrical controls, namely the flow controller **76**, the temperature controller **77** and the master controller **78**, is isolated from the lower chamber **82** (which houses the feed pumps **74**) to avoid, or at least inhibit, corrosion of the electrical components of the electrical controls. The control unit **12** generally is preferably constructed of heavy gauge steel that is anodized to inhibit corrosion. It preferably is secured with a high security lock system (not shown) and is preferably anchored to the ground with several six foot deep spikes (not shown) to prevent tampering and/or theft of the equipment held within the control unit **12**.

The flow controller **76** within the control unit **12**, which is one of the controls over the feed pumps **74**, is also in electrical connections (not shown) with the post-filter main-line flow sensor **128** along the post-filter main line **20**. (The construction and operation of these electrical connections are well within the skill of an ordinary person skilled in the art.) The flow controller **76** proportionately varies the input of the materials through the respective feed pumps **74** based on the flow rate of the treated irrigation water **111** which is read by the post-filter main-line flow sensor **128** downstream of (beyond) the sand-media filters **16**.

The temperature controller **77** within the controller unit **12** is in electrical connection (not shown) with the mixing-chamber discharge-line thermocouple **106** along the mixing-chamber discharge-line **71**. (The construction and operation of these electrical connections are well within the skill of an ordinary person skilled in the art.) The materials from the storage tanks **22** are routed through the respective feed lines **40** and charged to the mixing chamber **14**. The potassium-nutrient feedstock is intermixed with any other material being concomitantly fed and with a stream of untreated irrigation water **110** being fed into the mixing chamber **14** through the mixing-chamber feed line **70**. The treated irrigation water may be monitored by the mixing-chamber discharge-line thermocouple **106** as it exits the mixing

chamber 14. If that temperature is undesirably high, for instance 40° C. or higher (higher than 39° C.), the temperature controller 77 sends a feedback signal to the measure controller 78 and the master controller 78 shuts off the feed pumps 74 until a safe temperature is seen at the mixing-chamber discharge-line thermocouple 106, and this off/on sequence is repeated until a safe temperature, as seen at the mixing-chamber discharge-line thermocouple 106, is maintained.

The master controller 78 automatically turns the system 10 on. The master controller 78 is electrically connected (not shown) both to the pre-filter main-line pressure sensor 130 and to the mixing-chamber feed-line flow sensor 102. (The construction and operation of these electrical connections are well within the skill of an ordinary person skilled in the art.) When a minimum pressure (typically 15 psi) is seen at the pre-filter main-line pressure sensor 130 and a minimum flow of water (typically twenty gallons per minute) is seen at the mixing-chamber feed-line flow sensor 102, the master controller 78 actuates the feed pumps 74 and injection valves 96 any other component of the system 10 which facilitate the treatment of the untreated irrigation water that are then in an inactive state. Upon such actuation, materials start feeding to, and mixing in, the mixing chamber 14. (The master controller 78, pre-filter main-line pressure sensor 130 and mixing-chamber feed-line flow sensor 102 are typically always in an active state.) The master controller 78 will not allow such actuation unless both minimums are met. Once the feed pumps 74 and injection valves 96 are actuated, the master controller 78, for safety reasons and preferably, will automatically shut down the feed pumps 74 and injection valves 96 when either of the values seen at the pre-filter main-line pressure sensor 130 and the mixing-chamber feed-line flow sensor 102 falls below its respective minimum, and automatically restart the feed pumps 74 and injection valves 96 when both of the values seen at the pre-filter main-line pressure sensor 130 and the mixing-chamber feed-line flow sensor 102 meet or exceed its respective minimum. In other words, once the flow of untreated irrigation water 110 to the fields begins, it starts flowing (a) through the pre-filter main line 18, (b) to and through the sand-media filters 16, (c) discharging to, and flowing through the post-filter main line 20, and (d) from there to the irrigation lines in the field(s) (not shown), the master controller 78 will actuate the feed pumps 74 and injection valves 96 if the irrigation water is at the normal or expected pressure, flow and flow rate. Note that generally the flow of irrigation will occur as described above regardless of whether the master controller 78 has actuated the feed pumps 74 and injection valves 96 or has shut down the feed pumps 74 and injection valves 96 after initial actuation because that flow sequence and infrastructure are the conventional elements of the irrigation system.

Based on the potassium-nutrient-application profile (the amount of potassium nutrient that is required for a given time period of the given crop cycle), the master controller 78 automatically determines and sets the correct synchronizations of the feed pumps 74 to provide the desired potassium-nutrient feedstock.

As mentioned elsewhere herein, the master controller 78 controls the temperature within the mixing chamber 14, preventing the temperature from straying out of (normally exceeding) the desired range, by shutting off the feed pumps 74 until that temperature drops to, and can be maintained within, the desired range.

When filter(s) are disposed within the path of the irrigation water flowing through the system of the present inven-

tion (which is standard but not universal for commercial irrigation systems), such as the sand-media filters 16 shown within the path of the irrigation water between the pre-filter main line 18 and post-filter main line 20 (except the small stream of irrigation water that is routed through the mixing chamber 14), there is normally a small but significant water-flow pressure drop across the filters, such as sand-media filters 16. A flow rate of at least 20 gallons per minute or more of untreated irrigation water 110 through the mixing chamber 14 is preferred, and the optional booster pump 98 is preferably included to provide such flow rate if the pressure drop across the sand-media filters 16 would result in a lower flow rate through the mixing chamber 14 or if a higher flow rate is required to maintain a mixing chamber temperature below 40 degrees C.

As noted elsewhere, disposed along the mixing-chamber feed line 70 are the booster pump 98, the mixing-chamber feed-line flow meter 100, the mixing-chamber feed-line flow sensor 102 and the mixing-chamber feed-line shut-off valve 104. The mixing-chamber feed-line flow meter 100 determines the actual flow rate of untreated irrigation water 110 to, and therefore through, the mixing chamber 14. The mixing-chamber feed-line flow sensor 102 determines if a flow of untreated irrigation water 110 is occurring to, and therefore through, the mixing chamber 14. The flow of materials to the mixing chamber 14 will not be permitted unless a flow of untreated irrigation water 110 is occurring through the mixing chamber 14. There of course are electrical connections (not shown) between the mixing-chamber feed-line flow meter 100 and the master controller 78, and between the mixing-chamber feed-line flow sensor 102 and the master controller 78.

The mixing-chamber feed-line shut-off valve 104 is not generally an active element in the operation of the present system, but instead it is an optional, and typically manual, expedient. The mixing-chamber feed-line shut-off valve 104 and the mixing-chamber discharge-line shut-off valve 108 (which likewise is an optional, and typically manual, expedient) can be conveniently used together to isolate the mixing chamber 14 from the flows of irrigation water for maintenance or repair purposes, if ever needed. When the mixing-chamber feed-line shut-off valve 104 and the mixing-chamber discharge-line shut-off valve 108 are open (or in embodiments when they are not present), the small stream of untreated irrigation water 110 flows through the mixing chamber 14 whenever the irrigation water is flowing to the fields (not shown), regardless of whether or not any materials are being fed to the mixing chamber 14.

Along the mixing-chamber discharge line 71, downstream of the mixing chamber 14, is the mixing-chamber discharge-line thermocouple 106 which senses the temperature of the potassium-nutrient feedstock and irrigation water mixture as it exits the mixing chamber 14, and sends that data signal (temperature reading) to the master controller 78 for its processing and control of the temperature within the mixing chamber 14 as discussed elsewhere herein. There of course are electrical connections (not shown) between the mixing-chamber discharge-line thermocouple 106 and the master controller 78.

The dispositions and functions of the post-filter main-line pressure gauge 126, pre-filter main-line pressure sensor 130 and the post-filter main-line flow sensor 128 are discussed elsewhere.

The sand-media filters 16 are typically large, for instance 300 gallons, stainless steel filters. Such type of filters is routinely used by growers to remove debris from untreated irrigation water before it enters the irrigation system in the

fields. The sand-media filters **16** of the system **10** of the present invention generally and preferably would be filters that are already in place at the given irrigation-system site. As the untreated irrigation water **110** passes through the sand of the sand-media filters **16**, the flow of the untreated irrigation water **110** is restricted and that flow restriction causes a small but significant pressure drop across the sand-media filters **16**. Such pressure drop is typically in the range of from 5 to 15 psi (but can be higher as debris builds up in the filter), and is the reason that there is a pressure differential between the pre-filter main line **18** and the post-filter main line **20**. This pressure drop facilitates a large (fast) flow of untreated irrigation water **110** through the mixing chamber **14** that is needed to temper or mitigate any temperature increase within the mixing chamber **14**. The previously-described optional booster pump **98** is available to create and/or maintain the requisite water flow through the mixing chamber **14**, and it is a highly recommended option for irrigation systems that do not have a large enough pressure drop across the filters **16** to provide the requisite cooling by the untreated irrigation water **110** when the potassium-nutrient feedstock is charged to the mixing chamber **14**. In other words, the flow of untreated irrigation water **110** water through the mixing chamber **14** is large (fast) compared to the feed rate (injection rate) of the materials into the mixing chamber **14**.

In contrast, the system shown in FIG. 4 and described below charges the potassium-nutrient feedstock directly into the irrigation main line.

Master controller **78** includes various electronic components that are designed to monitor various electrical signals from the sensing devices. Depending on what signals are input, the master controller **78** turns on the various components of the system once the irrigation system is fully operational and in a mode to insure the proper feed of all the materials in the correct proportions, under controlled conditions, to safely add the potassium-nutrient feedstock to the irrigation system. Numerous configurations of electric components could be designed to achieve this control. As shown, the master controller **78** consists of various relays, timing devices and power supplies that take the various signals from the sensing equipment and turn on and off the various control systems to safely control the chemical feed pumps **74**. (A master controller could of course send the sensing and control data, via wireless communication networks, to an operator stationed in a distant office.) If any incorrect or out-of-range signal is received by the master controller **78** and circuitry inside the master controller **78** responds and sends the appropriate feedback signal to the appropriate device or system to immediately correct the out-of-range condition, change the flow rate of the material feed pumps **74** or totally shut off the material feed pumps **74**.

The system **10** can determine and adjust the pH of the treated irrigation water **111**, particularly as illustrated in FIG. 2 and FIG. 3 in which the lower chamber **82** as shown also houses a pH monitoring system **83** (shown in phantom lines in FIG. 2) which, as shown, is comprised of a pH monitoring-system pump **84**, a pH sensor **86**, a pH feed line **88** and a pH return line **90**, and in which the upper chamber **92** includes a pH controller **80**. Also along the post-filter main line **20**, in the order of from upstream (closest to the mixing-chamber discharge line **71**) to downstream (farthest from the mixing-chamber discharge line **71**), are the terminal end **116** of the pH return line **90**, the starting end **120** of the pH feed line **88** (along which is a pH line shut-off valve **122** and a solenoid **124**). The pH control additives, for instance an acid such as sulfuric acid or phosphoric acid are

preferably stored as concentrated solutions in a storage container(s) served by a feed pump(s) and a feed line(s) as discussed above and illustrated for the materials.

When this optional feature is present, the pH controller **80**, which is in electrical connection (not shown) with the flow controller **76**, might override the flow controller **76** at times for the specific control of the feed pump(s) (such as one of the feed pumps **74** shown) along the feed line (such as one of the feed lines **40** shown) of the sulfuric acid material (or other mineral acid material or even one or more separate pH-control additives) tank (such as one of the tanks **22** shown) to given the target pH. (The construction and operation of these electrical connections are well within the skill of an ordinary person skilled in the art.)

The pH controller **80** is electrically connected (not shown) to the pH monitoring system **83**. (The construction and operation of these electrical connections are well within the skill of an ordinary person skilled in the art.) The pH controller **80** in conjunction with the pH monitoring system **83** controls the pH of the treated irrigation water **111** as it leaves the system **10**. The pH of the treated irrigation water **111** is monitored by diverting a very small stream of treated irrigation water **111** through the starting end **120** of the pH feed line **88** (see FIG. 3) to the pH sensor **86** (see FIG. 2) whereat the pH of that small stream is determined. Based on the pH of the treated irrigation water **111** and based on the feed being produced in the mixing chamber **14**, the pH controller **80** adjusts (increases or decreases) the feed of one or more pH adjustment additives to achieve a target treated irrigation water pH. (Under the present invention, a base is optionally available for increasing the pH if needed to achieve a constant target pH, although in practice a pH increase would normally not be required. Further discussion herein a pH adjustment presumes that decreasing the pH is the only adjustment required.) The target treated irrigation water pH is typically a pH of about 6.5, or between 6.5 and 7, and usually is lower than the pH of the untreated irrigation water, because untreated irrigation water is usually alkaline.

The solenoid **124** allows the small stream of the treated irrigation water **111** to be delivered to the pH monitoring system **83** via the pH feed line **88**. The master controller **78** will normally and preferably activate the solenoid **124** when it actuates the feed pumps **74** and injection valves **96**. The electrical connections between the solenoid **124** and the master controller **78** are not shown.

As mentioned above, a small stream of treated irrigation water **111** is diverted from the post-filter main line **20** to the pH monitoring system **83** through the pH feed line **88** and is returned to the post-filter main line **20** (preferably, as shown, upstream of its diversion point) through the pH return line **90**. Along the starting end **116** of the pH feed line **88** is a pH feed-line shut-off valve **122**. Along the terminal end **120** of the pH return line **90** is a pH return-line shut-off valve **123**. The pH feed-line shut-off valve **122** and the pH return-line shut-off valve **123** are not normally active elements of the system **10** but instead are optional, and typically manual, expedients which can be conventionally used together to isolate the pH monitoring system **83** from the flows of irrigation water for maintenance or repair purposes, if ever needed, without discontinuing the irrigation water flow through the remainder of the system **10**.

The small stream of treated irrigation water **111** that is diverted from the post-filter main line **20** at the starting end **120** of the pH feed line **88** feeds into the pH monitoring system **83** through pH feed line **88**. (The starting end **120** of the pH feed line **88** as seen in FIG. 3 and the pH feed line **88** as seen in FIG. 2 are opposite ends of a single flow line.)

The pH of that small stream is read by the pH sensor **86** of the pH monitoring system **83**. Electrical connections between the pH sensor **86** and the pH monitoring system **83** exist but are not shown. The pH monitoring-system pump **84** pumps the small stream through the pH monitoring system **83**, and the pH monitoring-system pump **84** is controlled by the master controller **78** (electrical connections between these elements are not shown.)

To summarize, the pH monitoring system **83** includes the pH monitoring-system pump **84** which pumps treated irrigation water **111** from the post-filter main line **20** through the pH feed line **88**, past the pH sensor **86**, and then back to the post-filter main line **20** through the pH return line **90**. The electrical connections between the pH monitoring system **83** and the pH controller **80** are not shown.

The solenoid **124** shuts off treated irrigation water **111** flow from the post-filter main line **20** through the starting end **120** of the pH feed line **88** when the water-flow pressure seen at the pre-filter main-line pressure sensor **130** and/or at the mixing-chamber feed-line flow sensor **102** drop below predetermined threshold values. The solenoid **124** is in electrical connection (not shown) with the master controller **78**.

The System of FIG. 4

Referring to FIG. 4, there is shown a segment of a system of the present invention designated by the general reference numeral **310**, which differs from the system **10** of FIG. 1 to FIG. 3 by the omission of a separate mixing chamber component such as the mixing chamber **14** of the embodiment shown in FIG. 1 to FIG. 3. In the system **310** of FIG. 4, the material feed lines **340** (only two shown for simplicity) feed directly into a main line (as shown, into the main line segment that is the post-filter main line **320**).

The system **310** includes a control unit **310** (partially shown in FIG. 4), a plurality of filters **316**, an irrigation-water line or main line (which is designated in two segments, namely a pre-filter main line **318** and a post-filter main line **320**) and filters **316** along the main line between its pre-filter segment (pre-filter main line **318**) and its post-filter segment (post-filter main line **320**). Components of system **310** that are not shown in FIG. 4 include the components within the control unit **312**, namely a lower chamber which houses a feed-line feed pump, pH monitoring-system pump, a pH sensor, a pH feed line and a pH return line, and also an upper chamber which houses a flow controller, a master controller, a pH controller and a temperature controller. Other components of system **310** that are not shown in FIG. 4 include at least one storage container (one for the potassium-nutrient feedstock, although this system **310** could just as well have more storage containers to hold other materials as discussed above for system **10** of FIG. 1 through FIG. 3). In each instance the components of system **310** that are not shown in FIG. 4, and their electrical connections, are analogous to those described above for the system **10** shown in FIG. 1 to FIG. 3, and therefore no further description is needed here. Further, the components of system **310** that are shown in FIG. 4, and their electrical connections, also are analogous to those described above for the system **10** shown in FIG. 1 to FIG. 3, except as explicitly stated otherwise herein, and therefore little or no further description is needed here.

As mentioned above, there is a raw-material feed line **340** between the raw-material tank (not shown) and the post-filter main line **320**. This raw-material feed line **340** runs through the interior of the control unit **312** and, as seen in FIG. 4, from there to the post-filter main line **320**. For each of the materials, and raw-material feed lines **340**, which for

system **310** is at least one material and one raw-material feed line **340**, there is an injection valve **396** along the raw-material feed line **340** just ahead of the point at which the feed line **340** enters, or discharges to, the post-filter main line **320**.

Irrigation water flows to and through each of the filters **316** through filter feed lines **372**, and discharges from each of the filters **316** to the post-filter main line **320**. The materials also discharge to the post-filter main line **320** (via the feed lines **340**) and along each of the material feed lines **340** upstream of the post-filter main line **320** is, as mentioned above, an injection valve **396**, each of which is equipped with a backflow preventer (not shown).

In system **310**, unlike the system **10** shown in FIG. 1 to FIG. 3, not only is there no sequence mixing chamber component, there is no mixing-chamber feed line, no optional booster pump, no mixing-chamber feed-line flow meter, no mixing-chamber feed-line flow sensor, no mixing-chamber feed-line shut-off valve, no mixing-chamber discharge line and no mixing chamber discharge-line shut-off valve. There is a component that is the functional equivalent of the mixing-chamber discharge-line thermocouple **106**, and that is a post-filter main-line thermocouple **406** that is positioned along the post-filter main line **320** downstream of the points at which the feed lines **340** discharge to the post-filter main line **320**. The post-filter main-line thermocouple **406** ("thermocouple **406**"), like the mixing-chamber discharge-line thermocouple **106** of system **10**, monitors the irrigation-water temperature in the water stream to which the feedstock is charged.

The pre-filter segment of the main line (pre-filter main line **318**) is open to each of the filters **316** through filter feed lines **372** or openings. Untreated irrigation water, that is, irrigation water that is not yet treated by the method of the present invention, which is shown by flow arrows and is designated as untreated irrigation water **410** in FIG. 4, flows through the pre-filter main line **318** and discharges to the filters **316** through the respective filter feed lines **372**. In addition, each of the filters **316** is open to, and discharges to, the post-filter main line **320** via filter discharge lines **314** or openings. The untreated irrigation water **410** thus flows through the filters **316** and thereafter receives the charge of materials from their feed lines **340**, becoming treated irrigation water that carries or has been treated with the potassium-nutrient feedstock of the present invention. Although charging the potassium-nutrient feedstock along a post-filter section of the main line (post-filter main line **320**) is preferred, charging the potassium-nutrient feedstock along a pre-filter section of the main line (pre-filter main line **318**) is not excluded from the present invention. The potassium-nutrient feedstock charge should, however, be pre-delivery (upstream of the point(s) of delivering the irrigation water to the crop). Such irrigation water is shown by flow arrows and is designated as treated irrigation water **411** in FIG. 4 and elsewhere herein.

Along the post-filter main line **320**, in the order of from upstream (where the stream of irrigation water has not flowed past the feed lines **340** and therefore the water is filtered but not yet irrigation water **409**) to downstream (farthest along the post-filter main line **320**), are a post-filter main-line pressure gauge **426** and a post-filter main-line flow sensor **428**.

Along the pre-filter main line **318**, in the order of from upstream (closest to the water source, not shown) to downstream, are a pre-filter main-line pressure sensor **430** and a pre-filter main-line pressure gauge **432**.

The temperature controller (not shown) within the control unit **312** is in electrical connection (not shown) with the thermocouple **406** along the post-filter main line **320**. (The construction and operation of these electrical connections are well within the skill of an ordinary person skilled in the art.) The materials from the various storage tanks (not shown) are routed through the respective material feed lines **340** and charged to the post-filter main line **320** as the potassium-nutrient feedstock of the present invention. The potassium-nutrient feedstock intermixes with any other material being fed and with the relatively large stream of filtered irrigation water **409** flowing out from the filter **316**. The treated irrigation water is preferably monitored by the thermocouple **406** downstream of the points at which the feed lines **340** discharge the materials to the post-filter main line **320**. If that temperature is undesirably high, for instance 40° C. or higher (higher than 39°C.), the temperature controller (not shown) sends a feedback signal to the master controller (not shown) and the master controller shuts off the feed pumps (not shown) until a safe temperature is seen at the thermocouple **406**, and this off/on sequence is repeated until a safe temperature, as seen at the thermocouple **406**, is maintained. The volume and flow of irrigation water **409** in the post-filter main line **320** are, however, far greater than that through the mixing chamber **14** of system **10** shown in FIG. **1** to FIG. **3**, and therefore the likelihood of an excessively high temperature being seen at the thermocouple **406** approaches negligible, regardless of the concentration of materials which are being fed, outside of, of course, a major water-flow problem in the irrigation system itself.

The master controller (not shown) automatically turns the system **310** on. The master controller is electrically connected (not shown) to the pre-filter main-line pressure sensor **430**. (The construction and operation of these electrical connections are well within the skill of an ordinary person skilled in the art.) When a minimum pressure (typically 15 psi) is seen at the pre-filter main-line pressure sensor **430**, the master controller actuates the feed pumps (not shown) and injection valves **396** and any other component of the system **310** which facilitate the treatment of the irrigation water that are then in an inactive state. Upon such actuation, the potassium-nutrient feedstock of the present invention starts feeding to the post-filter main line **320**. The master controller will not allow such actuation unless the minimum is met. Once the feed pumps (not shown) and injection valves **396** are actuated, the master controller, for safety reasons and preferably, will automatically shut down the feed pumps and injection valves **396** when the value seen at the pre-filter main-line pressure sensor **430** falls below its minimum, and automatically restart the feed pumps and injection valves **396** when the value seen at the pre-filter main-line pressure sensor **430** meets or exceeds its respective minimum. In other words, once the flow of untreated irrigation water **410** to the fields begins, the irrigation water starts flowing (a) through the pre-filter main line **318**, (b) to and through the filters **316**, (c) discharging to, and flowing through the post-filter main line **320**, and (d) from there to the irrigation lines in the field(s) (not shown), and when this flow starts, the master controller will actuate the feed pumps and injection valves **396** provided this irrigation water flow is at the normal, or expected, pressure, flow and flow rate. Note that generally the flow of irrigation will occur as described above regardless of whether the master controller has actuated the feed pumps and injection valves **396** or has shut down the feed pumps and injection valves **396** after

initial actuation because that water flow sequence and infrastructure are the conventional elements of the irrigation system.

The starting end **420** of the pH feed line is downstream of the point(s) at which the materials are charged to the post-filter main line **320** and therefore, as in system **10** shown in FIG. **1** to FIG. **3**, it is the pH of the treated irrigation water **411**, not the irrigation water prior to treatment, which is being monitored by diverting a very small stream of treated irrigation water **411** through the starting end **420** of the pH feed line to the pH sensor (not shown) whereby the pH controller (not shown) adjusts (increases or decreases) the feed of acid(s) and/or base(s) to achieve a constant target treated irrigation water pH. The target treated irrigation water pH is typically a pH of about 6.5. Along the post-filter main line **320**, in the order of from upstream (where the stream of irrigation water has not flowed past the feed lines **340** and therefore the water is filtered but not yet irrigation water **409**) to downstream (farthest along the post-filter main line **320**), are the terminal end **416** of the pH return line, the material feed lines **340** and the thermocouple **406** (both mentioned above), the starting end **420** of the pH feed line (along which is a pH line shut-off valve **422** and a solenoid **424**), a post-filter main-line pressure gauge **426** and a post-filter main-line flow sensor **428** (both mentioned above).

Again, the remainder of the system **310** is analogous to the system **10** shown in FIG. **1** to FIG. **3** and described in detail above. Further, as described above for system **310**, the “mixing chamber” concept is part of, or within, the irrigation main line, namely the post-filter section of the irrigation main line (post-filter main line **320**). The dilution of the potassium-nutrient feedstock in this far greater water stream is of course highly increased. Further, system **310** is simpler than system **10** because most of the controls associated with a separate mixing chamber component such as the mixing chamber **14** of system **10** are eliminated, as described above.

Demonstrative Example 1

The method of the present invention was assessed for use at a 150 acre almond ranch which will normally receive a total of four acre-feet of irrigation water over its eight-month (March 1 to October 31) growing season, delivered as follows: (a) 1.0 acre-foot during the first three months (March 1 through June 1); 2.5 acre-feet during the second three months (June 1 through September 1); and 0.5 acre-foot during the last two months (September 1 through November 1). The source of potassium is a potassium-nutrient feedstock of the present invention, which in this instance is a 75 wt. % aqueous solution of potassium formate (a nonconventional 0-0-42 NPK fertilizer), continuously added with the irrigation water in the amount of 50 lb/acre potassium (as K₂O) over the March, April and May three-month time interval period, 25 lb/acre over the June, July and August three-month time period, and 50 lb/acre over the September and October two-month time period. In addition to delivering 125 lb/acre potassium (as K₂O) during the crop cycle, this prolonged-term continuous irrigation delivers 119 lb/acre of organic formate and no yield-extraneous material.

Demonstrative Comparative Example A

In comparison to Example 1, if the source of potassium used is potassium thiosulfate (K₂S₂O₃) fed to the irrigation system as a 25 wt. percent aqueous solution (a conventional 0-0-25 NPK fertilizer), the soil receives no organic material,

the soil receives yield-extraneous material, and the weight and volume of the potassium source are multiples of the potassium-nutrient feedstock of Example 1 which seriously escalates shipping, storage and handling costs and convenience.

Demonstrative Comparative Example B

In comparison to Example 1, if the source of potassium used is potassium sulfate (K₂SO₄) fed to the irrigation system as an 8 wt. percent aqueous solution (a concentration 0-0-8 NPK fertilizer), the soil receives no organic material, the soil receives yield-extraneous material, and the weight and volume of the potassium source are multiples of the potassium-nutrient feedstock of Example 1 which seriously escalates shipping, storage and handling costs and convenience.

While the foregoing written description of the invention enables one of ordinary skill in the art to make and use the invention, and to make and use what is presently considered the best mode of the invention, those of ordinary skill in the art will understand and appreciate the existence of variations, combinations and equivalents of the specific embodiments, methods and examples provided herein. The present invention should not be limited by the above described embodiments, methods and examples.

We claim:

1. A method of prolonged-termed emitter-irrigation potassium fertigation of an agricultural field, said agricultural field being irrigated by [means of] an [active] emitter-irrigation system having a stream of flowing irrigation water upstream of said agricultural field, said method comprising [the steps of]:

(step 1) converting said irrigation water to treated irrigation water by continuously charging a potassium-nutrient feedstock to said stream of said flowing irrigation water upstream of said agricultural field whereby said irrigation water is converted to treated irrigation water, wherein said potassium-nutrient feedstock [is comprised of] comprises potassium formate and water;

(step 2) irrigating said agricultural field with said treated irrigation water; and

(step 3) repeating step 1 and step 2 each irrigation day over a prolonged term.

2. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim [1] 14, wherein said potassium-nutrient feedstock [is] comprises a 50 to 75 wt. percent aqueous solution of potassium formate.

3. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim 1, wherein said potassium-nutrient feedstock is a [65] 50 to 75 wt. percent aqueous solution of potassium formate.

4. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim 1, wherein said [emitter-irrigation] irrigation system [is a] comprises said micro-irrigation system.

5. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim 1, wherein said [emitter-irrigation] irrigation system [is] comprises an overhead sprinkler system.

6. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim 1 wherein, in step 3, said prolonged term is from 50 to 100 percent of said crop cycle.

7. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to]

claim [1] 14, wherein[, in step 3,] said [prolonged term] potassium-nutrient feedstock is [from] continuously or substantially continuously charged to said stream of irrigation water during 75 to 100 percent of said crop cycle.

8. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim [1] 7, wherein[, in step 3,] said [prolonged term] potassium-nutrient feedstock is [from] continuously or substantially continuously charged to said stream of irrigation water during 90 to 100 percent of said crop cycle.

9. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim [1] 14, wherein[, in step 3,] said [prolonged term] potassium-nutrient feedstock is continuously or substantially continuously charged to said stream of irrigation water in a three month time period during said crop cycle.

10. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim 1 wherein, in step 3, said prolonged term is a five month time period during said crop cycle.

11. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim [1] 14, wherein[, in step 1, said] continuously charging [of] said potassium-nutrient feedstock provides a concentration of from 1 to 200 ppm of potassium as [K₂O] K₂O in said treated irrigation water.

12. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim 1 wherein, in step 1, [said] continuously charging [of] said potassium-nutrient feedstock provides a concentration of from 5 to 100 ppm of potassium as [K₂O] K₂O in said treated irrigation water.

13. The method of [prolonged-termed emitter-irrigation potassium fertigation of an agricultural field according to] claim 1 wherein said [active agricultural] emitter-irrigation system includes a main line and a side-arm mixing chamber off said main line, and said stream of flowing irrigation water [is flowing] flows through said side-arm mixing chamber and [discharging] discharges to said main line, and wherein, in step 1, [said] continuously charging [of] said potassium-nutrient feedstock to said stream of said flowing irrigation water upstream of said agricultural field [is a] comprises continuously charging [of] said potassium-nutrient feedstock to side-arm mixing chamber.

14. A method of potassium fertigation of an agricultural field, said agricultural field being irrigated using an irrigation system having a stream of irrigation water upstream of said agricultural field, said method comprising:

charging a potassium-nutrient feedstock to said stream of said irrigation water upstream of said agricultural field to convert said irrigation water to treated irrigation water, wherein said potassium-nutrient feedstock includes potassium formate and water; and irrigating said agricultural field with said treated irrigation water,

wherein, during at least 50% of a growing season or crop cycle, said potassium-nutrient feedstock is continuously or substantially continuously charged to said stream of irrigation water upstream of said agricultural field, and said agricultural field is irrigated with said treated irrigation water in multiple consecutive irrigations.

15. The method of claim 11, wherein said concentration is from 5 to 100 ppm of potassium as K₂O.

16. The method of claim 14, wherein said irrigation system comprises an emitter-irrigation system, a micro-irrigation system, or an overhead sprinkler system.

17. The method of claim 14, wherein said potassium-nutrient feedstock includes 28-42% of potassium as K_2O , 5 and does not include sulfate, thiosulfate, phosphate or chloride.

* * * * *