

US00RE49369E

(19) **United States**
(12) **Reissued Patent**
Stefanov

(10) **Patent Number:** **US RE49,369 E**
(45) **Date of Reissued Patent:** **Jan. 17, 2023**

(54) **DRUG DELIVERY DEVICE WITH PNEUMATIC POWER PACK**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **SHL MEDICAL AG**, Zug (CH)

CN 1909939 A 2/2007
CN 104968381 A1 10/2015

(Continued)

(72) Inventor: **Slobodan Stefanov**, Deerfield Beach, FL (US)

OTHER PUBLICATIONS

(73) Assignee: **SHL MEDICAL AG**, Zug (CH)

International Search Report issued in International Application No. PCT/EP2017/066263 dated Oct. 20, 2017.

(21) Appl. No.: **17/088,852**

(Continued)

(22) Filed: **Nov. 4, 2020**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **10,328,205**
Issued: **Jun. 25, 2019**
Appl. No.: **15/204,187**
Filed: **Jul. 7, 2016**

Primary Examiner — Catherine S Williams

(74) *Attorney, Agent, or Firm* — McDonnell Boehnen Hulbert & Berghoff LLP

(51) **Int. Cl.**
A61M 5/20 (2006.01)
A61M 5/24 (2006.01)
(Continued)

(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC **A61M 5/2053** (2013.01); **A61M 5/24** (2013.01); **A61M 5/31511** (2013.01);
(Continued)

A drug delivery device configured to provide a dose of medicament is disclosed. The drug delivery device includes a main housing, a syringe arranged in the main housing, and a pneumatic power pack arranged in the main housing. The pneumatic power pack includes a pressurized gas source storing pressurized gas, a valve for the pressurized gas source, a sleeve having an inner wall, and a plunger. The sleeve is configured to receive pressurized gas released from the pressurized gas source. The plunger is in sliding gas-tight engagement with the inner wall of the sleeve. Upon activation of the valve, the valve releases the pressurized gas, and the released pressurized gas flows into the sleeve and propels the plunger in a distal direction with respect to the sleeve and the syringe, so as to eject medicament from the syringe.

(58) **Field of Classification Search**
CPC .. **A61M 5/2053**; **A61M 5/24**; **A61M 5/31511**; **A61M 5/31576**; **A61M 5/31583**;
(Continued)


(56) **References Cited**

U.S. PATENT DOCUMENTS

2,605,763 A 8/1952 Smoot
4,518,384 A * 5/1985 Tarello A61M 5/20
604/61

(Continued)

23 Claims, 7 Drawing Sheets



- (51) **Int. Cl.**
A61M 5/32 (2006.01)
A61M 5/315 (2006.01)
A61M 5/31 (2006.01)

(52) **U.S. Cl.**
CPC *A61M 5/31576* (2013.01); *A61M 5/31583*
(2013.01); *A61M 5/31591* (2013.01); *A61M*
5/3202 (2013.01); *A61M 2005/208* (2013.01);
A61M 2005/3128 (2013.01); *A61M 2005/3267*
(2013.01); *A61M 2205/8218* (2013.01)

(58) **Field of Classification Search**
CPC A61M 5/31591; A61M 5/3202; A61M
2005/208; A61M 2005/3128; A61M
2005/3267

See application file for complete search history.
- 7,635,356 B2 12/2009 Stamp
7,654,983 B2 2/2010 De la Sema et al.
7,776,015 B2 8/2010 Sadowski et al.
8,002,753 B2 8/2011 Krumme et al.
9,987,436 B2 6/2018 Giambattista et al.
2002/0123717 A1 * 9/2002 Landau A61M 5/30
604/70
2005/0165360 A1 * 7/2005 Stamp A61M 5/2033
604/187
2014/0018729 A1 * 1/2014 Foster A61M 5/3015
604/58
2015/0165129 A1 * 6/2015 Row A61M 5/31501
604/189

FOREIGN PATENT DOCUMENTS

EP 1476210 B1 9/2008
EP 2624887 B1 1/2015
GB 2410188 A 7/2005
WO 2014095424 A1 6/2014

- (56) **References Cited**

U.S. PATENT DOCUMENTS

5,383,851 A * 1/1995 McKinnon, Jr. A61M 5/30
604/143
5,478,316 A * 12/1995 Bitdinger A61M 5/2033
604/134
5,891,086 A * 4/1999 Weston A61M 5/30
604/143
6,830,560 B1 12/2004 Gross et al.
7,207,967 B1 * 4/2007 Bellhouse A61M 5/3015
604/68

OTHER PUBLICATIONS

Search Report issued in Chinese Patent Application No. 106122080
dated Jul. 25, 2018.
English Translation of Abstract of WO 2014/095525 dated Nov. 15,
2018.

* cited by examiner




FIG. 1




FIG. 2






FIG. 3






FIG. 6




FIG. 7





FIG. 8



DRUG DELIVERY DEVICE WITH PNEUMATIC POWER PACK

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED APPLICATIONS

This is an application for reissue of U.S. Pat. No. 10,328, 205, which issued on Jun. 25, 2019.

FIELD OF THE PRESENT PATENT APPLICATION

This present disclosure relates to drug delivery devices such as automatic injection devices.

BACKGROUND

Unless otherwise indicated herein, the materials described in this section are not prior art to the claims in this application and are not admitted to be prior art by inclusion in this section.

In some situations, it is desirable for patients to be able to administer drugs and medicament by themselves, e.g., without the need for trained medical staff to administer the drugs. There are a number of different existing delivery devices with varying degrees of automatic functions. For instance, existing automatic injection devices provide a means for automatically propelling a plunger forward to eject medicament from the automatic injection device in response to activation of the device.

In existing devices, the means for automatically propelling the plunger forward to eject the medicament are often complex and expensive to manufacture. There is, therefore, a desire to reduce the cost of manufacturing automatic injection devices while maintaining the reliability of the injection device to eject the dose of medicament.

Further, for some types of medicaments, there is a desire to eject the medicament at a substantially constant force. However, certain existing devices for ejecting the medicament at a substantially constant force are complex and expensive to manufacture. There is a desire to reduce the cost of manufacturing automatic injection devices while maintaining the reliability of the injection device to eject the medicament at a substantially constant force.

SUMMARY

A drug delivery device configured to administer a dose of medicament is provided. In an example embodiment, the drug delivery device includes a main housing, a syringe arranged in the main housing, and a pneumatic power pack arranged in the main housing. The syringe holds a medicament. The pneumatic power pack includes: (i) a pressurized gas source storing pressurized gas; (ii) a valve for the pressurized gas source; (iii) a sleeve having an inner wall, wherein the sleeve is configured to receive pressurized gas released from the pressurized gas source; and (iv) a plunger axially movable with respect to both the sleeve and the syringe. The plunger is in sliding gas-tight engagement with

the inner wall of the sleeve. Upon activation of the valve, the valve releases the pressurized gas, and the released pressurized gas flows into the sleeve and propels the plunger in a distal direction with respect to the sleeve and the syringe, so as to eject the medicament from the syringe.

In another example embodiment, the drug delivery device includes a main housing, a medicament container arranged in the main housing, a needle cover axially movable with respect to the main housing, and a pneumatic power pack arranged in the main housing. The medicament container holds a medicament. The pneumatic power pack includes: (i) a pressurized gas source having a valve and storing pressurized gas; (ii) a sleeve having an inner wall, wherein the sleeve is axially moveable with respect to the main housing; and (iii) a plunger comprising an inner chamber. The plunger is axially movable with respect to both the sleeve and the medicament container. Further, the plunger is in sliding gas-tight engagement with the inner wall of the sleeve. Still further, the sleeve and the inner chamber are configured to receive pressurized gas released from the pressurized gas source. Axial movement of the needle cover in a proximal direction causes axial movement of the sleeve in the proximal direction, and the axial movement of the sleeve in the proximal direction activates the valve to release the pressurized gas. The released pressurized gas flows into both the sleeve and the inner chamber and propels the plunger in a distal direction with respect to the sleeve and the medicament container, so as to eject the medicament from the medicament container.

In still yet another example embodiment, the drug delivery device includes a main housing, a medicament container arranged in the main housing, and a pneumatic power pack arranged in the main housing. The medicament container holds a medicament. The pneumatic power pack includes: (i) a pressurized gas source storing pressurized gas; (ii) a valve for the pressurized gas source; (iii) a sleeve having an inner wall; and (iv) a plunger comprising an inner chamber and a pressure release valve configured to release pressure from the inner chamber when the pressure in the inner chamber reaches a threshold pressure level. The plunger is axially movable with respect to both the sleeve and the medicament container. Further, the plunger is in sliding gas-tight engagement with the inner wall of the sleeve. The sleeve and the inner chamber are configured to receive pressurized gas released from the pressurized gas source. The valve for the pressurized gas source is configured to release the pressurized gas upon activation of the valve. Further, the released pressurized gas flows into both the sleeve and inner chamber and propels the plunger in a distal direction with respect to the sleeve and the medicament container at a substantially constant force, so as to eject the medicament from the medicament container.

The foregoing summary is illustrative only and is not intended to be in any way limiting. In addition to the illustrative aspects, embodiments, and features described above, further aspects, embodiments, and features will become apparent by reference to the figures and the following detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

Exemplary embodiments are described herein with reference to the drawings, in which:

FIG. 1 illustrates a perspective view of an example drug delivery device having an example pneumatic power pack, according to an example embodiment of the present disclosure.

3

FIG. 2 illustrates an exploded, perspective view of example components of the drug delivery device of FIG. 1 in an initial state prior to injection, according to an example embodiment of the present disclosure.

FIG. 3 illustrates a front view of the example drug delivery device of FIG. 1 during dose delivery, according to an example embodiment of the present disclosure.

FIG. 4 illustrates a perspective view of example components of the drug delivery device of FIG. 1 during dose delivery, according to an example embodiment of the present disclosure.

FIG. 5 illustrates a perspective view of example components of the drug delivery device of FIG. 1 at the end of dose delivery, according to an example embodiment of the present disclosure.

FIG. 6 illustrates a perspective, cross-sectional view of an example plunger of the drug delivery device of FIG. 1, according to an example embodiment of the present disclosure.

FIG. 7 illustrates a perspective view of an example drug delivery device having an example pneumatic power pack, according to an example embodiment of the present disclosure.

FIG. 8 illustrates a perspective, cross-sectional view of the pneumatic power pack of the drug delivery device of FIG. 7, according to an example embodiment of the present disclosure.

FIG. 9 illustrates a perspective view of an example valve of the pneumatic power pack of FIG. 8, according to an example embodiment of the present disclosure.

FIG. 10 illustrates a perspective, cross-sectional view of the pneumatic power pack of the drug delivery device of FIG. 7 during dose delivery, according to an example embodiment of the present disclosure.

DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented herein. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the figures, can be arranged, substituted, combined, separated, and designed in a wide variety of different configurations, all of which are explicitly contemplated herein.

The methods and systems in accordance with the present disclosure beneficially provide improved methods and systems for propelling a plunger forward so as to eject the medicament from an automatic injection device. The disclosed methods and systems provide a reliable, intuitive, and user-friendly drug delivery device that uses a pressurized gas to eject a dose of medicament. Further, the disclosed methods and systems provide a cost effective means for propelling the plunger forward so as to eject the medicament and thus help to reduce the cost of manufacturing automatic injection devices.

In accordance with an example embodiment of the present disclosure, a drug delivery device includes a main housing, a syringe arranged in the main housing, and a pneumatic power pack arranged in the main housing. The syringe holds a dose of medicament. The pneumatic power pack includes

4

a pressurized gas source storing pressurized gas, a valve for the pressurized gas source, a sleeve having an inner wall, and a plunger. The sleeve is in gas-tight engagement with the pressurized gas source and is configured to receive pressurized gas released from the pressurized gas source. The plunger is at least partly surrounded by the sleeve and is axially movable with respect to both the sleeve and the syringe. Further, the plunger is in sliding gas-tight engagement with the inner wall of the sleeve. Upon activation of the valve, the valve releases the pressurized gas. The released pressurized gas then flows into the sleeve and propels the plunger in a distal direction with respect to the sleeve and the syringe, so as to eject the medicament from the syringe.

In an example embodiment, the plunger includes an inner chamber for receiving the released pressurized gas. In this embodiment, upon activation of the valve, the released pressurized gas flows into both the sleeve and the inner chamber. This pressurized gas then propels the plunger in the distal direction with respect to the sleeve and the syringe, so as to eject the medicament from the syringe.

FIG. 1 generally illustrates an example drug delivery device that uses pressurized gas to deliver a dose of medicament. In particular, FIG. 1 illustrates a drug delivery device 100 in an initial state prior to injection. Further, FIG. 2 illustrates an exploded view of the components of the drug delivery device 100 in the initial state prior to injection.

As seen in FIGS. 1 and 2, drug delivery device 100 includes a main housing 102 and a syringe 104 arranged in the main housing 102. Main housing 102 includes a first housing portion 106 and a second housing portion 108. First and second housing portions 106, 108 include corresponding engagement features for providing an engagement between the two housing portions 106, 108. In an example embodiment, during assembly of the drug delivery device 100, the first and second housing portions are irreversibly attached to one another. Although main housing 102 is depicted as comprising first and second housing portions 106, 108, in other examples, main housing 102 may comprise more or fewer portions. For instance, in an example embodiment, the main housing 102 is of unitary construction.

With reference to FIG. 2, the syringe 104 includes a syringe body 110 holding a medicament 112, a needle 114, and a needle cover 116 covering the needle 114. A piston or stopper 118 is disposed in the syringe body 110. The drug delivery device 100 further includes a pneumatic power pack 120 for ejecting the medicament from the syringe 104. The pneumatic power pack 120 includes a pressurized gas source 122 storing pressurized gas 123, a valve 124 for the pressurized gas source 122, a sleeve 126, and a plunger 128.

The sleeve 126 is in gas-tight engagement with the pressurized gas source 122 and is configured to receive pressurized gas 123 released from the pressurized gas source 122. As used herein, “gas-tight engagement” means an engagement providing a seal that prevents or substantially prevents leakage of gas through the seal during the dose delivery process. By the term “substantially” it is meant that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide. In an example embodiment, the gas-tight engagement prevents or limits leakage of gas such that less than 0.5% of the released pressurized gas 123 received in sleeve 126 is able to leak through the gas-tight engagement during the dose delivery process. In another example embodiment, the gas-tight

5

engagement prevents or limits leakage of gas such that less than 1% of the released pressurized gas 123 received in sleeve 126 is able to leak through the gas-tight engagement during the dose delivery process. In yet another example, the gas-tight engagement prevents or limits leakage of gas such that less than 5% of the released pressurized gas 123 received in sleeve 126 is able to leak through the gas-tight engagement during the dose delivery process.

The sleeve 126 has an inner wall 130, and the plunger 128 is in sliding gas-tight engagement with the inner wall 130 of the sleeve 126. During an injection process of drug delivery device 100, the pressurized gas 123 will axially move the plunger 128 with respect to the sleeve 126 and consequently with respect to the syringe 104. In particular, upon activation of valve 124, the valve 124 releases the pressurized gas 123. The pressurized gas 123 then flows into the sleeve 126 and propels the plunger 128 in distal direction 132 with respect to the sleeve 126 and syringe 104, so as to eject the medicament from the syringe 104 through needle 114.

In general, the valve 124 may be activated by the drug delivery device 100 in any suitable manner. In the example embodiment of FIG. 1, the needle cover 116 and the sleeve 126 interact with one another in order to activate the valve 124. To initiate the injection process, the user places the drug delivery device 100 on an injection site, such as injection site 140 as shown in FIG. 3. When the drug delivery device 100 is pressed onto the injection site 140 in distal direction 132, the needle cover 116 moves in a proximal direction 136 relative to the main housing 102. This retraction of the needle cover 116 exposes the needle 114 and the needle 114 is consequently inserted into the injection site 140.

In addition to exposing needle 114, this retraction of the needle cover 116 also serves to activate the valve 124 of the pneumatic power pack 120. In particular, the axial movement of the needle cover 116 in the proximal direction 136 causes axial movement of the sleeve 126 in the proximal direction 136. This axial movement of the sleeve 126 causes the sleeve 126 to interact with and activate the valve 124. The needle shield 116 may interact with sleeve 126 in any suitable manner in order to move the sleeve 126 in order to activate the valve 124. In the example shown in FIG. 2, a coupling flange 138 is attached to the sleeve 126. Axial movement of the needle shield 116 in the proximal direction 136 causes a proximal end 144 of the needle cover 116 to engage the coupling flange 138 and move the sleeve 126 in the proximal direction 136 to activate the valve 124.

The sleeve 126 may interact with the valve 124 in any suitable manner in order to activate the valve 124. In the example of FIG. 2, valve 124 includes a push portion 142 configured to open the valve 124. In particular, the valve 124 is configured to open when the push portion 142 is moved a threshold amount in the proximal direction 136. Axial movement of the sleeve 126 in the proximal direction 136 causes the sleeve 126 to contact the push portion 142 and then move the push portion 142 the threshold amount in the proximal direction 136. This movement opens the valve 124 and releases the pressurized gas 123. In general, for such a push-activated valve, any suitable threshold amount of movement in the proximal direction 136 to activate the valve 124 is possible. In an example, the threshold amount is between 0.5 and 5 millimeters (mm). However, threshold amounts less than 0.5 mm and greater than 5 mm are possible as well.

Although the example of FIG. 2 depicts a push-activated valve 124, in other example embodiments, the valve 124 may be activated in other suitable ways. For instance, the valve 124 may include a twist portion that is configured to

6

open the valve 124 upon rotation. In such an example, the device 100 is configured such that movement of the sleeve 126 causes rotation of the twist portion to open the valve 124. Other examples are possible as well.

After activation of the valve 124, the pneumatic power pack 120 releases the pressurized gas 123 to automatically inject the dose of medicament 112. The injection process is described in detail with reference to FIGS. 2 and 4-5. As mentioned above, FIG. 2 depicts the device 100 in an initial state prior to injection. Further, FIG. 4 depicts the pneumatic power pack 120 and syringe 104 during dose delivery. Still further, FIG. 5 depicts the pneumatic power pack 120 and syringe 104 at the end of dose delivery.

In the initial state (see FIG. 2), a proximal end 146 of plunger 128 is positioned in a proximal end 148 of the sleeve 126. When the valve 124 is activated, the valve 124 releases the pressurized gas 123. The pressurized gas 123 then flows into the sleeve 126 as indicated by arrow 150 (see FIG. 4) and propels the plunger 128 in distal direction 132 with respect to the sleeve 126 and syringe 104, so as to eject the medicament from the syringe 104 through the needle 114. Since sleeve 126 is in gas-tight engagement with the pressurized gas source 122 and the plunger 128 is in sliding gas-tight engagement with the inner wall of sleeve 126, the released pressurized gas 123 flowing into the sleeve 126 creates a pressure sufficient to propel the plunger 128 in the distal direction 132 with respect to the sleeve 126.

The pressurized gas 123 propels the plunger 128 in the distal direction 132 until the stopper 118 reaches a distal end 152 of the syringe body 110 (see FIG. 5). When the stopper 118 reaches the distal end 152 of the syringe body 110, the proximal end 146 of plunger 128 is positioned in a distal end 154 of sleeve 126.

During the dose delivery, the sleeve 126, syringe 104, and gas source 122 may be axially fixed with respect to main housing 102. As a result of these components being axially fixed during dose delivery, all or substantially all of the pressure from the released pressurized gas 123 will beneficially go towards propelling the plunger 128 in the distal direction 132.

In an example embodiment, the plunger 128 includes an inner chamber configured to receive the pressurized gas 123. FIG. 6 illustrates a perspective cross-sectional view of plunger 128, which includes inner chamber 170. During dispense, the pressurized gas 123 flowing into sleeve 126 will also flow into the inner chamber 170 of the plunger 128. Beneficially, the plunger 128 including an inner chamber 170 may help to reduce the mass of the plunger 128, and this may consequently reduce the force required to propel the plunger 128 forward during dose delivery.

Although plunger 128 is depicted as having an open inner chamber 170 for receiving pressurized gas 123, in other example embodiments, the inner chamber is closed such that pressurized gas 123 does not flow into the inner chamber 170. Such a closed inner chamber 170 may help to reduce the mass of the plunger 128, and this may consequently reduce the force required to propel the plunger 128 forward during dose delivery. In yet other example embodiments, the plunger 128 does not include an inner chamber.

As mentioned above, sleeve 126 is in gas-tight engagement with pressurized gas source 122 and plunger 128 is in sliding gas-tight engagement with the inner wall 130 of sleeve 126. The gas-tight engagement between the sleeve 126 and gas source 122 may be provided in any suitable manner. For instance, the engagement between the sleeve 126 and gas source 122 may include at least one washer or O-ring to provide the gas-tight engagement. Similarly, the

sliding gas-tight engagement may be provided in any suitable manner. For instance, at least one washer or O-ring may be attached to the plunger 128 to provide the sliding gas-tight engagement with the inner wall 130. As seen in FIG. 4, plunger 128 includes a first washer 172 and a second washer 174 attached at the proximal end 146 of the plunger 128. The plunger 128 may include one or more ribs, such as ribs 178 and 180 (see FIG. 6), to hold the washers 172, 174 on the plunger 128. The washers 172, 174 placed around the plunger 128 ensure that the space between the plunger 128 and pressurized gas source 122 is substantially air-tight so that any gas leakage that would reduce the thrusting force is minimized or prevented. Other methods for providing the gas-tight engagement between the sleeve 126 and gas source 122 and for providing the slidable, gas-tight engagement with inner wall 130 are possible as well.

After injection is complete, the device 100 is removed from the injection site 140 and the needle cover 116 will extend outward and lock into place. This extension and locking may limit or prevent needle stick injuries. The needle cover 116 may extend outward and lock into place in any suitable manner. In an example embodiment, when the drug delivery device 100 is removed from the injection site 140, the needle cover 116 automatically extends outward in the distal direction 132 under a force such as a spring force. As seen in FIG. 2, drug delivery device 100 includes spring 182 positioned between syringe 104 and needle cover 116. This spring 182 provides the force to automatically extend the needle cover 116 in the distal direction 132 after the user removes the drug delivery device 100 from the injection site 140. Other ways of locking the needle cover 116 in an extended position are possible as well.

In an example embodiment, during dose delivery, the user can hear and/or feel an audible and/or tactile feedback (e.g., clicking) throughout the dose delivery. For instance, the device 100 may include a clicker than produces a clicking sound when the plunger 128 is being propelled forward in the distal direction 132. The end of injection may be indicated by the audible/tactile clicking having stopped. Additionally or alternatively, the stopper 118 and plunger 128 may be visible in the main body window 184 (see FIG. 3) when injection is complete. In such an example, the end of delivery may be indicated by the stopper 118 and plunger 128 having stopped moving. Other indications of dose delivery being complete are possible as well.

Pressurized gas source 122 may be any source of pressurized gas suitable to propel the plunger 128 forward to eject the medicament 112. In an example embodiment, the pressurized gas is CO₂, Argon, or Nitrogen. Other example pressurized gases are possible as well. Further, in an example embodiment, the pressurized gas source 122 contains a gas pressurized to a pressure of between 50-3000 PSI. However, in other examples, the pressure may be less than 600 PSI or more than 3000 PSI. For instance, in another example, the pressure is between 500-600 PSI. In yet another example, the pressure is between 3000-3500 PSI. Other example pressures are possible as well.

Additionally, even though a syringe 104 is described in this example embodiment of FIG. 1, any suitable type of medicament container may be used in the disclosed drug delivery device 100, such as a syringe, an ampoule, a cartridge, an enclosure, etc. Further, the medicament may be any suitable substance used for medical treatment. In an example embodiment, the medicament is epinephrine (commonly known as adrenaline).

In an example embodiment, the disclosed pneumatic power pack may be configured to propel the plunger with a

constant or substantially constant force. An example drug delivery device having a pneumatic power pack configured to propel the plunger with a constant or substantially constant force is described with reference to FIGS. 7-10.

FIG. 7 depicts a drug delivery device 200. The drug delivery device 200 operates in a similar fashion as drug delivery devices 100; however, rather than including power pack 120, drug delivery device 200 includes power pack 202 (see FIG. 8). Other elements of drug delivery device 200 may be the same or substantially similar to the other elements drug delivery device 100, and thus drug delivery device 200 is not described in as great of detail. It should be explicitly noted, however, that any possibilities and permutations described above with respect to drug delivery device 100 may equally apply to drug delivery device 200, and vice versa. Further, throughout the description of FIGS. 7-10, elements in drug delivery device 200 that are the same as or substantially similar to elements in drug delivery device 100 are described with like reference numerals.

FIG. 8 depicts a cross-sectional view of power pack 202 of drug delivery device 200. Power pack 202 is positioned in second housing portion 108. Further, power pack 202 includes pressurized gas source 204 storing pressurized gas 206, valve 208, sleeve 210, and plunger 212 having inner chamber 214. Sleeve 210 is in gas-tight engagement with pressurized gas source 204 and plunger 212 is in sliding gas-tight engagement with an inner wall 211 of sleeve 210. In order to propel the plunger 212 with a constant or substantially constant force, valve 208 is configured to release the pressurized gas 206 at a substantially constant rate, and plunger 212 is configured to release pressure when the pressurized gas 206 in the inner chamber 214 reaches a threshold pressure level.

With reference to FIG. 8, valve 208 includes a flow control orifice 216. Valve 208 also includes a gasket 218 configured to open and close the flow control orifice 216. Flow control orifice 216 includes an opening 220 and an exit 222 and is sized to release pressurized gas 206 at a substantially constant rate regardless of the pressure at the opening 220 and the pressure at exit 222. An example size of the flow control orifice 216 may be on the order of 5 to about 250 Microns.

The flow control orifice 216 may release the pressurized gas at any suitable substantially constant rate. As mentioned herein, by the term "substantially" it is meant that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide.

In an example embodiment, the substantially constant rate at which the flow control orifice 216 releases the pressurized gas is any substantially constant rate. Further, as used herein, a substantially constant rate of X means any rate in the range of $X \pm 0.05(X)$.

Plunger 212 includes a pressure release valve 224 that is configured to release pressure when the pressurized gas in the inner chamber 214 reaches a threshold pressure level. The pressure release valve 224 includes one or more release holes (such as release hole 226), gasket 228, and spring 230. Gasket 228 and spring 230 are disposed in a distal end of inner chamber 214. When the pressure level in the inner chamber 214 is below the threshold pressure level, the gasket 228 is positioned at a location proximal to a location of the release hole 226, so as to prevent the pressurized gas 206 from reaching the release hole 226. FIG. 8 illustrates the

gasket **228** positioned at a location proximal to a location of the release hole **226**. On the other hand, when the pressure level in the inner chamber **214** is above the threshold level, the pressurized gas **206** urges the gasket **228** against the spring **230** in a distal direction **132** until the gasket **228** moves distally beyond at least a part of the release hole **226**, so as to allow the pressurized gas **206** to exit the release hole **226**. FIG. **10** depicts the gasket **228** positioned at a location distal of the release hole **226**.

In general, the threshold pressure level may be selected based on a desired force at which the plunger **212** is to be propelled. In an example embodiment, the threshold pressure level is a pressure level between 25 PSI and 400 PSI.

In the example shown in FIG. **8**, pneumatic power pack **202** includes a container **230** for holding the pressurized gas source **204**. The container **230** includes a needle **232** that punctures the pressurized gas source **204** during assembly of the power pack **202**. In this example embodiment, the valve **208** for the pressurized gas source **204** is provided by flow control orifice **216** in container **230** and gasket **218**. However, in other embodiments, the pressurized gas source **204** may be replaced by a gas source that already has a release valve, such as valve **124**.

During operation of the drug delivery device **200**, valve **208** may be activated in any suitable manner. In the example of FIG. **8**, the valve **208** is activated by rotation of the gasket **218** to uncover the flow control orifice **216**. Similar to drug delivery device **100**, movement of the needle cover **116** may act on the sleeve **210** to activate the valve **208**. For instance, axial movement of needle cover **116** acts on sleeve **210** in order to rotate the gasket **218** in a clockwise direction **238** (see FIG. **9**) to uncover the flow control orifice **216**. In one arrangement, the sleeve **210** and an inner housing portion enclosing the gasket **218** are coupled during assembly. The needle cover **116** may act on either the sleeve **210** or the inner housing portion, depending on the designs, and the gasket **218** will be rotated by the inner housing portion to open and active the valve **208**. In others words, the needle cover **116** can act either the sleeve **210** or the inner housing portion to active the valve **208**.

When the valve **208** is activated by the rotation of gasket **218** to uncover flow control orifice **216**, the pressurized gas **206** moves through flow control orifice **216** at a substantially constant flow rate as shown by arrow **240** (see FIG. **10**). The pressurized gas **206** then moves into sleeve **210** and inner chamber **214** as shown by arrow **242**. Since the plunger **212** is in sliding gas-tight engagement with the inner wall **211** of the sleeve **210**, the flow of gas shown by arrow **242** will increase the pressure in the sleeve **210** and inner chamber **214** to propel the plunger **212** forward in distal direction **132** so as to eject medicament **112**. The pressurized gas **206** propels the plunger **212** in the distal direction **132** with the substantially constant force until the stopper **118** reaches the distal end **152** of the syringe body **110**. When the plunger **212** reaches this final point, any remaining pressurized gas **206** will be released through the pressure release valve **224** until the pressurized gas source **204** is empty or substantially empty.

During the propelling of the plunger **212** in the distal direction **132**, if the pressure in the inner chamber **214** exceeds the threshold level, the pressurized gas **206** will get released through pressure release valve **224** (as shown by arrow **244**). This pressure release through pressure release valve **224** allows for effectively keeping the pressure in the inner chamber **214** at a substantially constant value. As a result of the pressure being regulated in this manner, the pneumatic power pack **202** is able to push the plunger **212**

in the distal direction **132** with a substantially constant force produced by the pressure in the sleeve **210** and inner chamber **214**.

The pneumatic power pack **202** may propel the plunger **212** forward with any suitable substantially constant force. As mentioned herein, by the term “substantially” it is meant that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide.

In an example embodiment, the substantially constant force at which the plunger **212** is propelled is any substantially constant force falling in the range of forces between 10 N and 100 N+/-15 N. Further, as used herein, a substantially constant force of X Newtons means any force in the range of 10 N and 100 N+/-15 N.

Beneficially, the disclosed pneumatic power pack provides a cost effective means for propelling a plunger forward in an automatic injection device. Further, embodiments of the disclosed pneumatic power pack also provide a low-cost means for propelling the plunger forward at a substantially constant force. Therefore, the disclosed pneumatic power pack may help to reduce the cost of manufacturing automatic injection devices.

In the examples shown in the Figures, the drug delivery devices **100** and **200** are configured to inject a non-variable dose of medicament. However, in other embodiments, the drug delivery device could be configured to allow the user to select a variable single dose. For instance, in an example embodiment, the user is able to select two different dose values, three different dose values, four different dose values, and so forth.

In the Figures, various engagement features for are shown for providing an engagement between one or more components of the drug delivery device. The engagement features may be any suitable connecting mechanism such as a snap lock, a snap fit, form fit, a bayonet, lure lock, threads or combination of these designs. Other designs are possible as well.

It should be understood that the illustrated components are intended as an example only. In other example embodiments, fewer components, additional components, and/or alternative components are possible as well. Further, it should be understood that the above described and shown embodiments of the present disclosure are to be regarded as non-limiting examples and that they can be modified within the scope of the claims.

While various aspects and embodiments have been disclosed herein, other aspects and embodiments will be apparent to those skilled in the art. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope being indicated by the following claims, along with the full scope of equivalents to which such claims are entitled. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting.

We claim:

1. A drug delivery device comprising:

a main housing;

a syringe arranged in the main housing, wherein the syringe comprises a medicament;

a needle attached to the syringe;

a needle cover axially movable with respect to the main housing; and

11

- a pneumatic power pack arranged in the main housing, wherein the pneumatic power pack comprises:
- (i) a pressurized gas source storing pressurized gas;
 - (ii) a valve for the pressurized gas source;
 - (iii) a sleeve having an inner wall, wherein the sleeve is configured to receive pressurized gas released from the pressurized gas source; and
 - (iv) a plunger axially movable with respect to both the sleeve and the syringe, wherein the plunger is in sliding gas-tight engagement with the inner wall of the sleeve,
- wherein, upon activation of the valve, the valve releases the pressurized gas and the released pressurized gas flows into the sleeve and propels the plunger in a distal direction with respect to the sleeve and the syringe, so as to eject the medicament from the syringe, and
- wherein axial movement of the needle cover in the proximal direction causes axial movement of the sleeve in the proximal direction, and wherein the axial movement of the sleeve in the proximal direction activates the valve to release the pressurized gas.
2. The drug delivery device of claim 1, further comprising:
- a coupling flange attached to the sleeve, wherein axial movement of the needle cover in the proximal direction causes the needle cover to engage the coupling flange and move the sleeve in the proximal direction.
3. The drug delivery device of claim 1, wherein the valve comprises a push portion configured to open the valve, and wherein axial movement of the sleeve in the proximal direction causes the sleeve to contact the push portion and open the valve.
4. The drug delivery device of claim 1, wherein the syringe comprises a stopper, and wherein movement of the plunger in the distal direction with respect to the sleeve and the syringe causes the plunger to act on the stopper.
5. The drug delivery device of claim 1, wherein the plunger comprises an inner chamber configured to receive the released pressurized gas.
6. The drug delivery device of claim 1, further comprising:
- at least one washer attached to the plunger, wherein the at least one washer provides sliding gas-tight engagement with the inner wall of the sleeve.
7. The drug delivery device of claim 1, wherein the valve comprises:
- a flow control orifice; and
 - a gasket configured to open and close the flow control orifice.
8. The drug delivery device of claim 7,
- wherein axial movement of the needle cover in the proximal direction causes rotation of the gasket to open the flow control orifice.
9. The drug delivery device of claim 7, wherein the pneumatic power pack further comprises a container for holding the pressurized gas source, wherein the container comprises (i) the flow control orifice and (ii) an additional needle configured to puncture the pressurized gas source.
10. The drug delivery device of claim 1, wherein the pneumatic power pack is configured to propel the plunger in the distal direction with respect to the sleeve and the syringe at a substantially constant force.
11. The drug delivery device of claim 10, wherein the valve comprises a flow control orifice having an opening and an exit, wherein the flow control orifice is sized to release the

12

- pressurized gas at a substantially constant rate in response to a pressure at the opening and a pressure at the exit.
12. The drug delivery device of claim 10, wherein the plunger comprises:
- an inner chamber configured to receive the released pressurized gas; and
 - a pressure release valve configured to release pressure when the received released pressurized gas in the inner chamber reaches a threshold pressure level.
13. The drug delivery device of claim 12, wherein the pressure release valve comprises:
- at least one release hole; and
 - a gasket and spring disposed in a distal end of the inner chamber, wherein the gasket and spring are configured such that (i) below the threshold pressure level, the gasket is positioned at a location proximal to a location of the at least one release hole, so as to prevent the released pressurized gas from reaching the at least one release hole, and (ii) above the threshold pressure level, the released pressurized gas urges the gasket against the spring in a distal direction until the gasket moves distally beyond at least part of the at least one release hole, so as to allow the received released pressurized gas to exit the at least one release hole.
14. The drug delivery device of claim 1, wherein the drug delivery device is a single-use disposable injection device.
15. A drug delivery device comprising:
- a main housing;
 - a medicament container arranged in the main housing, wherein the medicament container comprises a medicament;
 - a needle cover axially movable with respect to the main housing; and
 - a pneumatic power pack arranged in the main housing, wherein the pneumatic power pack comprises:
 - (i) a pressurized gas source having a valve and storing pressurized gas;
 - (ii) a sleeve having an inner wall, wherein the sleeve is axially moveable with respect to the main housing; and
 - (iii) a plunger comprising an inner chamber, wherein the plunger is axially movable with respect to both the sleeve and the medicament container, wherein the plunger is in sliding gas-tight engagement with the inner wall of the sleeve, and wherein the sleeve and the inner chamber are configured to receive pressurized gas released from the pressurized gas source,
- wherein axial movement of the needle cover in a proximal direction causes axial movement of the sleeve in the proximal direction, wherein the axial movement of the sleeve in the proximal direction activates the valve to release the pressurized gas, and wherein the released pressurized gas flows into both the sleeve and the inner chamber and propels the plunger in a distal direction with respect to the sleeve and the medicament container, so as to eject the medicament from the medicament container.
16. A drug delivery device comprising:
- a main housing;
 - a medicament container arranged in the main housing, wherein the medicament container comprises a medicament; and
 - a pneumatic power pack arranged in the main housing, wherein the pneumatic power pack comprises:
 - (i) a pressurized gas source storing pressurized gas;
 - (ii) a valve for the pressurized gas source;

13

- (iii) a sleeve having an inner wall; and
 (iv) a plunger comprising an inner chamber and a pressure release valve configured to release pressure from the inner chamber when the pressure in the inner chamber reaches a threshold pressure level, 5
 wherein the *inner chamber of the* plunger is axially movable with respect to both the sleeve and the medicament container,
 wherein the *inner chamber of the* plunger is in sliding gas-tight engagement with the inner wall of the sleeve, 10
 wherein the sleeve and the inner chamber are configured to receive pressurized gas released from the pressurized gas source,
 wherein the valve is configured to release the pressurized gas upon activation of the valve, and 15
 wherein the released pressurized gas is configured to flow into both the sleeve and the inner chamber to propel the *inner chamber of the* plunger in a distal direction with respect to the sleeve and the medicament container with a substantially constant force, such that the plunger moves into the medicament container to eject the medicament from the medicament container. 20
17. The drug delivery device of claim 16, wherein the pressure release valve comprises: 25
 at least one release hole; and
 a gasket and spring disposed in a distal end of the inner chamber, wherein the gasket and spring are configured such that (i) below the threshold pressure level, the gasket is positioned at a location proximal to a location of the at least one release hole, so as to prevent the released pressurized gas from reaching the at least one release hole, and (ii) above the threshold pressure level, the released pressurized gas urges the gasket against the spring in a distal direction until the gasket moves distally beyond at least part of the at least one release hole, so as to allow the received released pressurized gas to exit the at least one release hole. 30
18. The drug delivery device of claim 17, wherein the valve comprises a flow control orifice having an opening and an exit, wherein the flow control orifice is sized to release the pressurized gas at a substantially constant rate regardless of a pressure at the opening and a pressure at the exit. 40
19. *The drug delivery device of claim 1, wherein the needle cover directly contacts and engages the sleeve when the needle cover moves proximally from a first position to a second position.* 45
20. *A drug delivery device comprising:*
a main housing having a distal end and a proximal end;

14

- a container of medicament axially fixed within the main housing and having a stopper slidably positioned within the container of medicament;*
a needle cover slidably positioned within the main housing and axially movable between a first position and a second position, where when the needle cover is in the first position a distal portion of the needle cover extends out beyond the distal end of the main housing;
a container of pressurized gas positioned at the proximal end of the main housing;
a valve operatively associated with the container of pressurized gas;
a sleeve that is operatively engaged with the container of pressurized gas such that the sleeve will be in a gas tight engagement with the container of pressurized gas source when the needle cover is in the second position; and
a plunger positioned within the sleeve and comprising a seal that forms a gas tight engagement with an inner wall of the sleeve such that pressurized gas released from the container of pressurized gas will cause the plunger to move axially in a distal direction relative to the main housing and the sleeve when the needle cover is in the second position,
wherein movement of the needle cover from the first position to the second position moves the sleeve in a proximal direction relative to the main housing, where the proximal movement of the sleeve causes the valve to open releasing the pressurized gas into the sleeve, and wherein axial movement of the plunger causes axial movement of the stopper relative to the main housing, sleeve and the container of medicament.
21. *The drug delivery device of claim 20, wherein the needle cover directly contacts and engages the sleeve when the needle cover moves from the first position to the second position.*
22. *The drug delivery device of claim 20, wherein the plunger further comprises an inner chamber, wherein pressurized gas released from the container of pressurized gas will enter both the sleeve and the inner chamber to cause the plunger to move distally relative to the sleeve and the container of medicament.*
23. *The drug delivery device of claim 20, wherein the valve further comprises a flow control orifice having an opening and an exit, wherein the flow control orifice is sized to release the pressurized gas at a substantially constant rate in response to a pressure at the opening and a pressure at the exit.*

* * * * *