

US RE49,458 E

Page 2

(51) **Int. Cl.**
F21V 8/00 (2006.01)
G02F 1/1333 (2006.01)
G02F 1/13357 (2006.01)

(58) **Field of Classification Search**
CPC H05K 7/20963; G02F 1/133308; G02F
1/133615; G02F 2001/133317; G02F
2001/133628
USPC 349/62, 65
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

7,771,104 B2 8/2010 Iwasaki
7,864,258 B2 * 1/2011 Cho G02B 6/0073
349/58
2001/0050732 A1 * 12/2001 Okamoto et al.
G02F 1/133308
349/58
2003/0218702 A1 11/2003 Kwon et al.
2006/0203140 A1 9/2006 Kim
2006/0239035 A1 10/2006 Won et al.
2006/0243948 A1 11/2006 Ishiwa et al.
2006/0285362 A1 12/2006 Cho et al.
2007/0085943 A1 * 4/2007 Kang et al. 349/65
2007/0133222 A1 6/2007 Watanabe et al.
2008/0304286 A1 12/2008 Iwasaki
2008/0304288 A1 12/2008 Iwasaki
2011/0273631 A1 * 11/2011 Hayashi G02B 6/0091
348/790

FOREIGN PATENT DOCUMENTS

CN 1912711 A 2/2007
CN 1949055 A 4/2007
CN 101017278 8/2007
CN 101017278 A 8/2007
CN 101038389 A 9/2007
CN 101149534 A 3/2008
CN 101308272 A 11/2008
EP 1835330 A1 9/2007

JP 2004117744 A 4/2004
JP 2005077979 A 3/2005
JP 2005528748 9/2005
JP 2005528748 A 9/2005
JP WO 2006080201 A1 * 3/2006
JP 2007287463 A 11/2007
JP 2008066008 3/2008
JP 2008216406 A 9/2008
JP 2008299181 12/2008
JP 2008299181 A 12/2008
JP 2008305657 A 12/2008
JP 2008305713 12/2008
JP 2008305713 A 12/2008
KR 1020060131382 A 12/2006
KR 1020070076879 A 7/2007
KR 1020070093216 A 9/2007
TW 200600915 1/2006
TW 200600915 A 1/2006
TW 200609606 3/2006
TW 200609606 A 3/2006
TW 200813564 3/2008
TW 200813564 A 3/2008
TW 200831996 8/2008
TW 200831996 A 8/2008
TW 200842452 11/2008
TW 200842452 A 11/2008
WO 03102680 12/2003
WO 03102680 A1 12/2003
WO 2006080201 A1 8/2006

OTHER PUBLICATIONS

Japanese Office Action-Japanese patent application No. 2014-145908 dated Apr. 7, 2015.
Korean Office Action-KR Application No. 10-2009-0007034 dated Dec. 15, 2014, citing KR 2007-0093216A and JP 2005-077979A.
Taiwanese Office Action-Taiwanese patent application No. 099102439 dated Mar. 24, 2015.
Machine translation of Lee, Sang Yu et al (KR 10-2006-0131382), Dec. 12, 2006.*
Machine translation of KR 10-2007-00193216, Sep. 18, 2007.*
European Search Report for application No. 10000501.6-2205 dated Jun. 2, 2010.

* cited by examiner




FIG. 2




FIG. 3




FIG. 4





FIG. 5






FIG. 7





FIG. 8



BACKLIGHT ASSEMBLY AND DISPLAY DEVICE INCLUDING THE SAME

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

This application is a reissue application of U.S. Pat. No. 9,194,571, issued on Nov. 24, 2015. This application is a continuation of U.S. patent application Ser. No. 12/696,948, filed on Jan. 29, 2010, which claims priority to Korean Patent Application No. 2009-0007034, filed on Jan. 29, 2009, and all the benefits accruing therefrom under 35 U.S.C. §119, the content of which in its entirety is herein incorporated by reference.

BACKGROUND OF THE INVENTION

(1) Field of the Invention

The present invention relates to a backlight assembly and a display device including the backlight assembly. More particularly, the present invention relates to a backlight assembly that effectively discharges heat generated from a light source therein, and a display device having the backlight assembly.

(2) Description of the Related Art

In general, liquid crystal display devices are often used due to a variety of features, such as light weight, slim shape, low power consumption, full-color implementation and high resolution, for example. Specifically, for example, liquid crystal display devices are utilized in computers, laptop computers, portable digital assistants ("PDAs"), telephones, television ("TV") sets, audio/video devices and other similar devices. In liquid crystal display devices, light transmission is controlled, based on image signals applied to control switches disposed in a matrix pattern, to display images on liquid crystal display panels of the devices.

However, a liquid crystal display device is not a self light-emitting device, and thus, requires a light source such as a backlight, for example. The backlight for the liquid crystal display device may be an edge type backlight or a direct type backlight, based on a position of the light source in the backlight.

More specifically, in the edge type backlight, for example, the light source is disposed at an end portion of the liquid crystal display panel, such that light emitted from the light source is radiated to the liquid crystal display panel through a transparent waveguide plate disposed below the liquid crystal display panel. The edge type backlight provides good light uniformity, has a substantially extended life span and can easily be included in a thin display device. In general, the edge type backlight is employed in a medium-size or small-size liquid crystal display panel.

On the other hand, in the direct type backlight, light sources are typically disposed below the liquid crystal display panel such that light emitted from the light source is radiated over an entire surface of the liquid crystal display panel. The direct type backlight provides high luminance and can generally be employed in a large-size or medium-size liquid crystal display panel.

In a conventional backlight, a cold cathode fluorescent lamp may be used as a light source. Recently, research has

been conducted into using a light emitting diode as the light source, since the light emitting diode has various properties such as long life span, lower power consumption, light weight and thin shape, for example. However, the light emitting diode generates a substantial amount of heat. Therefore, a reliability of electric circuits is degraded, due to an increase in the internal temperature of a backlight assembly caused by heat generated from the light emitting diode. In addition, deformation of parts or cases is caused due to thermal stresses caused by an internal temperature gradient.

BRIEF SUMMARY OF THE INVENTION

An aspect of the present invention relates to a display device including a light source which emits light, a light guide plate disposed adjacent to the light source and which receives the light emitted from the light source, a light source supporter including a bottom plane including a first region and a second region, and a first receiving unit including a bottom surface and a side wall. In an exemplary embodiment, the light source and the light guide plate are disposed on the first region of the bottom plane, the second region extends from a portion of the first region on which the light source is disposed, the bottom surface is disposed opposite the light guide plate, and the side wall is disposed at an end portion of the bottom surface along a direction perpendicular to a plane defined by the bottom surface.

In an exemplary embodiment, the light source may include a printed circuit board and a light emitting diode.

In an exemplary embodiment, an inner space may be formed on the second region and between the light source and the side wall of the first receiving unit.

In an exemplary embodiment, the light source supporter may further include a bent portion disposed on an end portion of the second region of the light source supporter.

In an exemplary embodiment, the backlight assembly may further include a middle frame and at least a portion of the middle frame may be disposed in the inner space.

In an exemplary embodiment, the middle frame may include a U-shaped portion, and at least a portion of the U-shaped portion of the middle frame may be disposed in the inner space.

In an exemplary embodiment, the middle frame may further include a bent portion connected to the U-shaped portion and disposed on an optical sheet disposed on the light source and the light guide plate.

In an exemplary embodiment, the light source supporter may include a metal plate.

In another exemplary embodiment, the light source supporter may include aluminum.

In an exemplary embodiment, the second region of the light source supporter may extend from the light source and provide a heat dissipation path for the backlight assembly.

In an exemplary embodiment, the light source supporter may contact the first receiving unit and dissipate heat.

In an exemplary embodiment, the bent portion of the second region may be disposed along the side wall of the first receiving unit and contact the side wall.

In an exemplary embodiment, a hole may be formed in the bottom surface of the first receiving unit, and the light source supporter may further include a protrusion disposed in the hole.

In another exemplary embodiment, a liquid crystal display includes a liquid crystal panel, a backlight assembly and a second receiving unit. The liquid displays an image. The backlight assembly includes a light source disposed adjacent to an edge portion of the liquid crystal panel, a light

3

guide plate disposed adjacent to the light source and which emits light to the liquid crystal panel, an optical sheet disposed between the light guide plate and the liquid crystal panel, a first receiving unit including a bottom surface and a side wall and which accommodates the light source, the light guide plate and the optical sheet and a light source supporter which supports the light source and the light guide plate, the light source and the light guide disposed on a first region of the light source supporter. The second receiving unit covers at least a portion of the edge portion of the liquid crystal panel and the side wall of the first receiving unit.

In an exemplary embodiment, the light source supporter may include a second region extending from the first region of the light source supporter.

In an exemplary embodiment, a gap may be formed on the second region of the light source supporter and between an end portion of the second region and the light source.

In an exemplary embodiment, the liquid crystal display may further include a third receiving unit covering at least a portion of the optical sheet and the liquid crystal panel, and at least a portion of the third receiving unit may be disposed in the gap.

In an exemplary embodiment, the third receiving unit may include a U-shaped portion disposed in the gap.

In an exemplary embodiment, the light source supporter may include metallic material.

In another exemplary embodiment, the light source supporter may include aluminum.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects and features of the present invention will become more readily apparent by describing in further detail embodiments thereof with reference to the accompanying drawings, in which:

FIG. 1 is an exploded perspective view of an exemplary embodiment of a display device according to the present invention;

FIG. 2 is a partial cross-sectional view taken along line A-A' of FIG. 1;

FIGS. 3 to 5 are partial cross-sectional views showing additional exemplary embodiments of a metal plate of the display device shown in FIG. 2;

FIG. 6 is an exploded perspective view of another exemplary embodiment of a display device according to the present invention;

FIG. 7 is a partial cross-sectional view taken along line B-B' of FIG. 6; and

FIG. 8 is a partial cross-sectional view showing another exemplary embodiment of a metal plate of the display device shown in FIG. 7;

DETAILED DESCRIPTION OF THE INVENTION

The invention now will be described more fully herein-after with reference to the accompanying drawings, in which various embodiments are shown. This invention may, however, be embodied in many different forms, and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like reference numerals refer to like elements throughout.

It will be understood that when an element is referred to as being "on" another element, it can be directly on the other element or intervening elements may be present therebe-

4

tween. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

It will be understood that, although the terms first, second, third etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present invention.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used herein, the singular forms "a," "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," or "includes" and/or "including" when used in this specification, specify the presence of stated features, regions, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, regions, integers, steps, operations, elements, components, and/or groups thereof.

Furthermore, relative terms, such as "lower" or "bottom" and "upper" or "top," may be used herein to describe one element's relationship to another element as illustrated in the Figures. It will be understood that relative terms are intended to encompass different orientations of the device in addition to the orientation depicted in the Figures. For example, if the device in one of the figures is turned over, elements described as being on the "lower" side of other elements would then be oriented on "upper" sides of the other elements. The exemplary term "lower," can therefore, encompass both an orientation of "lower" and "upper," depending on the particular orientation of the figure. Similarly, if the device in one of the figures is turned over, elements described as "below" or "beneath" other elements would then be oriented "above" the other elements. The exemplary terms "below" or "beneath" can, therefore, encompass both an orientation of above and below.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and the present disclosure, and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

One or more embodiments are described herein with reference to cross section illustrations that are schematic illustrations of idealized embodiments. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments described herein should not be construed as limited to the particular shapes of regions as illustrated herein but are to include deviations in shapes that result, for example, from manufacturing. For example, a region illustrated or described as flat may, typically, have rough and/or nonlinear features. Moreover, sharp angles that are illustrated may be rounded. Thus, the regions illustrated

5

in the figures are schematic in nature and their shapes are not intended to illustrate the precise shape of a region and are not intended to limit the scope of the present claims.

Hereinafter, one or more exemplary embodiments of the present invention will be described in further detail with reference to the accompanying drawings.

FIG. 1 is an exploded perspective view of an exemplary embodiment of a display device according to the present invention. FIG. 2 is a partial cross-sectional view taken along line A-A' of FIG. 1.

Referring to FIGS. 1 and 2, a liquid crystal display ("LCD") device includes a display assembly 1000 disposed in an upper portion of the LCD device and a backlight assembly 2000 disposed in a lower portion of the LCD device.

The display assembly 1000 includes a liquid crystal ("LC") panel 200, a driver circuit 300 including a first driver circuit 300a and a second driver circuit 300b, and a second receiving unit 100.

The LC panel 200 includes a color filter substrate 210 and a thin film transistor ("TFT") substrate 220. The color filter substrate 210 includes red, green and blue ("RGB") pixels, which are disposed using a thin film process and generate a predetermined color when light passes through the RGB pixels. A common electrode, including a transparent conductive material such as indium thin oxide ("ITO") or indium zinc oxide ("IZO"), for example, is disposed on an outer surface of the color filter substrate 210.

The TFT substrate 220 is a transparent glass substrate on which thin film transistors are disposed in a matrix pattern. A source terminal of each of the TFTs is connected to a data line, and a gate terminal of each of the TFTs is connected to a gate line. In addition, a drain terminal of each of the TFTs is connected to a pixel electrode, which is a transparent electrode including a transparent conductive material. When an electrical signal is applied to the data line and gate line, each of the TFTs is turned on or off to apply an electrical signal to drive a pixel connected to the drain terminal. Specifically, when electric power is applied to the gate terminal and source terminal of the TFT substrate 220 to turn the TFT on, an electric field is generated between the pixel electrode and the common electrode of the color filter substrate 210. Thus, liquid crystal molecules in the LC panel disposed between the TFT substrate 220 and the color filter substrate 210 changes their orientation and light transmissivity is changed according to the change of the orientation, thereby displaying a desired image.

The driver circuit 300 connected to the LC panel 200 includes a data-side printed circuit board ("PCB") 310a, which may include a control integrated circuit ("IC") and apply a predetermined data signal to the data line of the TFT substrate 220, a gate-side printed circuit board 310b which may include a control integrated circuit and apply a gate signal to the gate line of the TFT substrate 220, a data-side flexible printed circuit board ("FPCB") 330a which has an exposed ground pattern and connects the TFT substrate 220 to the data-side printed circuit board 310a, and a gate-side flexible printed circuit board 330b which has an exposed ground pattern and connects the TFT substrate 220 to the gate-side printed circuit board 310b.

The data-side and gate-side printed circuit boards 310a and 310b are connected to the data-side and gate-side flexible printed circuit boards 330a and 330b, respectively, and thereby transmit an external image signal and a gate drive signal. The data-side and gate-side printed circuit boards 310a and 310b may be disposed on a same printed circuit board. In an exemplary embodiment, the data-side

6

and gate-side printed circuit boards 310a and 310b may be alternately connected to a side of the LC panel 200 and the gate line and data line of the TFT substrate 220 may extend to one side thereof.

The data-side and gate-side flexible printed circuit boards 330a and 330b are connected to the data line and to the gate line of the TFT substrate 220, respectively, and thereby transmit a data drive signal and a gate drive signal to the TFT. In an exemplary embodiment, the flexible printed circuit board 230 include a tape automated bonding ("TAB") integrated circuit, which alternately transmits read, green, blue signals, a shift start clock ("SSC") signal, a latch pulse ("LP") signal, a gamma analog ground signal, a digital ground signal, digital electric power, an analog electric power common voltage, a stored voltage and other similar signals, for example, which are generated from the data-side and gate-side printed circuit boards 310a and 310b, to the LC panel 200. In an exemplary embodiment, the TFT substrate 220 may include an integrated circuit.

The second receiving unit 100 is in a rectangular frame shape having a plane section and a sidewall section disposed perpendicular to the plane section. The second receiving unit effectively prevents components of the display assembly 1000 from departing from the display assembly 1000 and protects LC panel 200 and backlight assembly 2000 against external impact. In an exemplary embodiment, the second receiving unit 100 may cover at least a portion of the LC panel 200 and the backlight assembly 2000.

In an exemplary embodiment, the backlight assembly 2000 includes a light source 600, a light guide plate 700 disposed adjacent to the light source 600, a reflective sheet 710 disposed below the light guide plate 700, optical sheets 500 disposed above the light guide plate 700 and a first receiving unit 900 accommodating the reflective sheet 710, the light guide plate 700 and the optical sheets 500. The backlight assembly 2000 may further include a third receiving unit 400 accommodating the reflective sheet 710, light guide plate 700 and optical sheets 500 along with the first receiving unit 900. The third receiving unit 400 may be referred to as a middle frame 400, which is disposed between the first and second receiving units 900 and 100. The third receiving unit 400 may include plastic material.

As shown in FIGS. 1 and 2, a metal plate 800 attached to the light source 600 to dissipate heat is further included in the backlight assembly. In one or more exemplary embodiments, the metal plate 800 is referred to as a light source supporter 800, and the light source supporter 800 is disposed adjacent to, e.g., is attached to, the light source 600. Hereinafter, the metal plate may be referred to as the light source supporter when the light source supporter accommodates and supports the light source.

In an exemplary embodiment, the light source 600 includes a printed circuit board 620 and a light emitting diode 610 disposed thereon. The light emitting diode 610 emits white light or one color of the red, green and blue. The backlight assembly may include more than one light emitting diode 610.

The printed circuit board 620 may discharge heat generated from the light emitting diode 610 to an outside and supply a predetermined voltage to the light emitting diode 610 disposed on the printed circuit board 620. The printed circuit board may include a metallic layer such as metal core printed circuit board ("MCPCB"), for example.

In an exemplary embodiment, a groove may be formed in a predetermined portion of the printed circuit board 620, and the light emitting diode may be disposed on the groove such that the printed circuit board 620 surrounds the light emit-

ting diode **610** and thereby provides a reflective surface to the light emitting diode **610** and maximizes light efficiency. The printed circuit board **620** may include at least one light emitting diode **610**.

In FIG. 2, light source **600** is disposed in a side of the backlight. In another embodiment, the light source **600** may be disposed in more than one side of the backlight assembly according to types of the display devices such as cellular phone, monitor, a laptop computer and television set, for example.

The light guide plate **700** is disposed in the first receiving unit **900** and disposed opposite, e.g., facing, the light sources **600** to convert light distribution of a line light source generated from light sources **600** into a light distribution of a surface light source. In an exemplary embodiment, the light guide plate **700** may include a wedge-type plate or parallel flat plate, for example. In addition, the light guide plate **700** may include polymethyl methacrylate ("PMMA"), which has good transmissivity and high strength, and thereby effectively prevents deformation or damage. The light guide plate **700** may be disposed apart from the light source at a predetermined distance or disposed adjacent to the light source **600**.

The reflective sheet **710** includes a plate with high light reflectivity such that light incident thereon through a rear surface of the light guide plate **700** is reflected again to the light guide plate **700**, thereby reducing light loss. The reflective sheet **710** may be disposed below the first receiving unit **900**. Although it has been illustrated in the figures that the reflective sheet **710** is in a flat shape, the reflective plate may be in various shapes, for example, a corrugated form having a triangular projection protruding from a reference reflective surface. Further, when a highly reflective material is disposed at a bottom surface of the first receiving unit **900**, the reflective sheet **710** may be omitted or integrated into the first receiving unit **900**.

The optical sheets **500** include a diffusion sheet **510**, a polarization sheet **520** and a luminance-improving sheet **530**, which are disposed above the light guide plate **700** to cause a luminance distribution of the light emitted from the light guide plate **700** to be uniform. The diffusion sheet **510** may direct the light incident from the lower light guide plate towards a surface of the LC panel **200** to be diffused and uniformly distributed in a wide range such that a diffused light is radiated on the LC panel **200**. The diffusion sheet **510** includes a transparent resin film including a light diffusion member disposed on at least one side of the diffusion sheet **510**. The polarization sheet **520** converts light incident thereon at an inclined angle into light emitted vertically from the polarization sheet **520** and incident perpendicular to the LC panel **200**, and the light efficiency is thereby substantially maximized. Therefore, at least one polarization sheet **520** may be disposed below the LC panel **200** such that the light is emitted from the polarization sheet **520** to be perpendicular to the LC panel **200**. In an exemplary embodiment, two polarization sheets may be used, which include a first polarization sheet which polarizes the light from the diffusion sheet in a first direction and a second polarization sheet which polarizes the light in a second direction perpendicular to a plane defined by the first polarization sheet. The luminance-improving sheet **530** transmits light parallel to a transmission axis of the luminance-improving sheet and reflects light perpendicular to the transmission axis. In an exemplary embodiment, the transmission axis of the luminance-improving sheet **530** may be in a same direction as the polarization axis of the polarization sheet **520**, and transmission efficiency is thereby substantially increased.

The first receiving unit **900** may be in a box-like shape including open top and predetermined depth to have a receiving space. The first receiving unit **900** includes bottom surface **910** and side walls **920** extended vertically from the bottom surface **910**. At an inner space of the opposing side walls **920**, disposed opposite to, e.g., facing, each other a metal plate **800** is disposed in the first receiving unit **900**. Thus, the metal plate **800** is disposed in a gap between the bottom surface **910** of the first receiving unit **900** and the light source **600**.

The metal plate **800** includes a bottom plane **810** and a lateral plane **820** extended vertically from the bottom plane **810**. (As described above, the metal plate **800** is also referred to as "light source supporter" which supports the light source.) In an exemplary embodiment, the lateral plane **820** contacts the third receiving unit **400**, i.e. middle mold structure, and the bottom plane **810** contacts the first receiving unit **900**. With the contacting structure of the metal plate **800**, heat generated from the light source **600** migrates to the metal plate **800** and thereby spread to the first and third receiving unit **900** and **400**. The heat spread to the first and third receiving unit is further dissipated to the outside of the LCD and thereby substantially lower the temperature of the LCD.

The metal plate **800** may include any material with sufficient thermal conductivity such as aluminum, stainless steel and iron, for example, to transfer heat from the metal plate **800** to outside of the LCD. The metal plate **800** may be formed using various methods such as assembling or welding the bottom plane **810** and the lateral plane **820**, for example. In an exemplary embodiment, the whole shape of the metal plate **800** may be formed using molded metal material inserted and taken out from a predesigned frame.

FIG. 3 is a partial cross-sectional view of another exemplary embodiment of the metal plate **800** of the display device of FIG. 2.

As shown in FIG. 3, the first receiving unit **900** has at least one hole **930** on the bottom surface **910** accommodating at least one protrusion **830** extended from the metal plate **800**. The protrusion **830** is exposed to the outside of LCD by passing through the hole **930** of the first receiving unit **900**. Here, convection heat transfer, made by the contact structure of the first receiving unit **900** and the metal plate **800**, is accommodated since the heat may be directly transferred to an outside atmosphere.

Referring to FIGS. 1 to 3, a route of heat dissipation will now be described. In an exemplary embodiment, heat generated from the light source **600** is transferred metal plate **800** contacting the light source **600**, and the heat transferred from the light source **600** is further transferred to lateral plane **820** contacting third receiving unit **400** and bottom plane **810** contacting the bottom surface **910** of the first receiving unit **900**. The heat transferred to the third receiving unit **400** may be transferred to the first receiving unit **900** through inter-contact structure. In an exemplary embodiment, heat, emitted along with light from the LED **610** of the light source **600**, is transferred to the printed circuit board ("PCB") **620** where the LED **610** is disposed, and the heat is dissipated to the outside through inter-contact structures of the metal plate **800**, the first receiving unit **900**, and the third receiving unit **400**.

The third receiving unit **400** covers at least a portion of the optical sheets **500** along with the first receiving unit **900**. The third receiving unit may include plastic material according to contact structure of the optical sheets and light backlight assembly. As described above, the third receiving unit is also referred to as "a middle mold frame." In another embodi-

ment, the third receiving unit **400** may be omitted corresponding to application of the LCD. For example, an exemplary embodiment of the LCD in a small sized application may not include the third receiving unit **400** for a simple structure.

FIGS. **4** and **5** are partial cross-sectional views showing additional exemplary embodiments of the metal plate **800**.

As shown in FIGS. **4** and **5**, the metal plate **800** may include a bent portion **840** connected to an elongated end of the bottom plane **810** and extending substantially perpendicular to the bottom plane **810** from an edge portion of the bottom plane **810** of the metal plate **800** along the side wall **920** of the first receiving unit **900**. The metal plate including the bent portion **840** effectively discharges the heat from the light source.

As shown in FIG. **4**, the metal plate **800** supports the light guide plate **700** with the bottom plane **810** similarly to the metal plates shown in FIGS. **1** to **3**. The metal plate **800** further supports the light source, e.g., light emitting diode **610**, which is disposed above the metal plate **800**. Hereinafter, a portion of the bottom plane **810** where the light source **600** and the light guide plate **700** are disposed on is referred to as "a first region."

The bottom plane **810** further extends to the side wall **920** of the first receiving unit **900**. A portion of the bottom plane **810** where the third receiving unit **400** is disposed is referred to as "a second region" of the bottom surface **910**. In another embodiment, the metal plate **800** may not include the bent portion **840**. When the metal plate **800** includes the bent portion **840**, a gap G1 may be formed between the bent portion **840** and the light source **600** as shown in FIG. **4**. In another embodiment, the metal plate **800** may include the lateral plane shown in FIG. **2**, and the gap G1 may be formed between the lateral plane and the bent portion **840** of the metal plate **800**. In an exemplary embodiment, an area accommodated in discharging the heat of the light source **600** to the first receiving unit **900** may be substantially increased due to the gap G1, and temperature of the back-light assembly is thereby substantially lowered.

The third receiving unit may be disposed in the gap G1 as shown in FIG. **4**. In an exemplary embodiment, the third receiving unit **400** may include a first portion, a second portion, a third portion, a fourth portion, a fifth portion, a first bending portion **410**, a second bending portion **420**, a third bending portion **430** and a fourth bending portion **440** and be bent four times and disposed in the gap G1. The first bending portion **410** connects the first portion and the second portion, the second bending portion **420** connects the second portion and the third portion, the third bending portion **430** connects the third portion and the fourth portion and the fourth bending portion **440** connects the fourth portion and the fifth portion. In an exemplary embodiment, the third receiving unit may include a U-shaped portion, e.g., the second portion, the third portion, fourth portion, the second bending portion **420** and the third bending portion **430** connected one another, and the first portion and the fifth portion are connected to the U-shaped portion. The first portion, which is a bent portion in an exemplary embodiment, is disposed between the optical sheets **500** and LC panel **200**. In an exemplary embodiment, the first portion, the second portion, the first bending portion **410** and the second bending portion **420** of the third receiving unit **400** may cover at least a portion of the optical sheets **500**, the light source **600** and the light guide plate **700** along with the first receiving unit **900** and thereby restrict movement of the optical sheets **500**, the light source **600** and the light guide plate **700**. In another embodiment, the second receiving unit

100 may cover at least a portion of the LC panel **200** along with the first portion **410** of the third receiving unit **400**.

The first bending portion **410** is connected to the second portion disposed adjacent to one of the light source **600** and the lateral plane **820** of FIG. **2** of the metal plate **800**. The third portion is disposed on the second region of the bottom surface **910** and the fourth portion is disposed opposite the side wall **920** of the first receiving unit **900**. The fifth portion connected to the fourth bending portion **440** is disposed on the bent portion **840** of the metal plate **800** and the side wall **920** of the first receiving unit **900**. In an exemplary embodiment, the third receiving unit **400** includes a U-shaped portion disposed in a space between the side wall **920** of the first receiving unit **900** and light source **600** as shown in FIG. **4**. In another embodiment, the U-shaped portion may be disposed in a space between the bent portion **840** of the metal plate **800** and lateral plane **820** of FIG. **2** of the metal plate **800**. The U-shaped portion may extend in a horizontal direction, parallel to the bottom surface **910** of the first receiving unit **900**.

The whole shape of the third receiving unit **400** may vary to be disposed in a gap between the lateral plane **820** and the side wall **920** as shown in FIG. **2** and thereby effectively prevent departing of the light source **600** and the LC panel **200** from the display device due to external impact along with the second receiving unit **100**. As described above, the third receiving unit **400** may be disposed between the lateral plane **820** and the bent portion **840** of the metal plate **800** when the metal plate further includes the lateral plane **820** disposed between the third receiving unit **400** and the light source **600**. In an exemplary embodiment, the third receiving unit may include plastic material, and be referred to as the middle mold frame.

FIG. **5** is a partial cross-sectional view of still another exemplary embodiment of the metal plate **800** of the display panel shown in FIG. **2**. The display device in FIG. **5** is substantially the same as the display device shown in FIG. **4** except that the first receiving unit **900** includes the hole **930** disposed in the bottom surface **910** and a protrusion **830** extending from the bottom plane **810** of the metal plate **800** through the hole **930**, and thereby dissipates the heat of the metal plate **800** to the outside substantially effectively. The same or like elements shown in FIG. **5** have been labeled with the same reference characters as used above to describe the embodiment of display device shown in FIG. **4**, and any repetitive detailed description thereof will hereinafter be omitted. One or more embodiments of the display device include a backlight assembly including the third receiving unit **400**. However, the third receiving unit **400** may be omitted according to the overall design of the LCD. One or more embodiments of the LCD which do not include the third receiving unit **400** are shown in FIGS. **6** to **8**. The same or like elements shown in FIGS. **6** to **8** have been labeled with the same reference characters as used above to describe the embodiments of the display device shown in FIGS. **1** to **5**, and any repetitive detailed description thereof will hereinafter be omitted or simplified.

FIG. **6** is an exploded perspective view illustrating another exemplary embodiment of a display device according to the present invention. FIG. **7** is a partial cross-sectional view taken along line B-B' of FIG. **6**. FIG. **8** is a partial cross-sectional view illustrating another exemplary embodiment of a metal plate of the display device shown in FIG. **7**.

Referring to FIGS. **6** to **8**, the embodiment of the display device includes a display assembly **1000** and a backlight assembly **2000**. The display assembly **1000** includes a LC

11

panel 200, driver circuits 300a and 300b and a second receiving unit 100. The LC panel 200 includes a color filter substrate and a TFT substrate. As shown in FIG. 6, the backlight assembly 2000 may include a light source 600, a light guide plate 700 disposed adjacent to the light source 600, a reflective sheet 710 disposed below the light guide plate 700, optical sheets 500 disposed above the light guide plate 700, a first receiving unit 900 accommodating the reflective sheet 710, the light guide plate 700 and the optical sheets 500, and a metal plate 800 which dissipates heat generated from the light source.

The light source 600 includes a printed circuit board 620 and a light emitting diode 610 disposed on the printed circuit board 620. The light emitting diode 610 emits white light or light having one color of the red, green and blue. The printed circuit board 620 may discharge heat generated from the light emitting diode 610 to outside and apply a predetermined voltage to the light emitting diode 610 disposed on the printed circuit board 620. In an exemplary embodiment, a groove may be formed in a predetermined portion of the printed circuit board 620, and the light emitting diode may be disposed in the groove such that the printed circuit board 620 surrounds at least a portion of the light emitting diode 610 and provides a reflective surface thereto, thereby maximizes light efficiency. In an exemplary embodiment, at least one light emitting diode 610 may be disposed on the printed circuit board 620.

As shown in FIGS. 6 and 7, the light source 600 may be disposed on side walls 920 of the first receiving unit 900 disposed opposite to, e.g., facing, each other. In another embodiment, the light source 600 may be disposed on one side wall 920 of the first receiving unit 900. In another embodiment, the light sources 600 may be disposed on four of the side walls 920 of the first receiving unit 900 and thereby surround the light guide plate 700. The number of light sources may vary based on a size and type of a device including the display device, for example, cellular phone, monitor, laptop computer and television set.

As shown in FIGS. 7 and 8, a lateral plane 820 of the metal plate 800 contacts the side wall 920 of the first receiving unit 900, and the bottom surface 910 of the first receiving unit 900 contacts the bottom plane 810 of the metal plate 800. By contacting side and bottom portions of the first receiving unit 900 and to side and bottom portions of the metal plate 800, the metal plate 800 transfers heat from the light source 600 to the first receiving unit 900.

The display device in FIG. 8 is substantially the same as the display device shown in FIG. 7 except that the first receiving unit 900 includes a hole 930 disposed in the bottom surface 910 and a protrusion 830 extending from the bottom plane 810 of the metal plate 800 through the hole 930, and thereby dissipates the heat of the metal plate 800 to the outside substantially effectively. The same or like elements shown in FIG. 8 have been labeled with the same reference characters as used above to describe the embodiment of display device shown in FIG. 7, and any repetitive detailed description thereof will hereinafter be omitted.

The present invention should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete and will fully convey the concept of the present invention to those skilled in the art.

While the present invention has been particularly shown and described with reference to embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein

12

without departing from the spirit or scope of the present invention as defined by the following claims.

What is claimed is:

1. A backlight assembly comprising:

a light source which emits light, *wherein the light source comprises a printed circuit board and a light emitting diode;*

a light guide plate [disposed adjacent to the light source and] which receives the light emitted from the light source;

a light source supporter comprising a [bottom plane] *first supporting portion* and a [lateral plane] *second supporting portion* which is extended vertically from the [bottom plane] *first supporting portion* and integrated with the [bottom plane] *first supporting portion*, *the first supporting portion comprising a supporting surface, the second supporting portion comprising a first surface and a second surface opposing the first surface;* and

a first receiving unit comprising a bottom [plane] *portion* and a lateral [plane] *portion* which is extended vertically from the bottom [plane] *portion* and integrated with the bottom [plane] *portion* and accommodating the light guide plate and the light source,

wherein the light source and the light guide plate are disposed on the [bottom plane] *supporting surface of the first supporting portion* of the light source supporter, [and]

wherein the [lateral plane] *second surface of the second supporting portion* of the light source supporter is in direct contact with the lateral [plane] *portion* of the first receiving unit,

wherein the first supporting portion of the light source supporter is disposed directly on the bottom portion of the first receiving unit, and

wherein a height of the second supporting portion of the light source supporter is less than or equal to a height of the lateral portion of the first receiving unit.

2. The backlight assembly of claim 1, further comprising a middle frame, which is coupled to the first receiving unit, wherein at least a portion of the middle frame is in direct contact with the light source supporter.

3. The backlight assembly of claim 2, wherein the middle frame comprises a U-shaped portion, and at least a portion of the U-shaped portion of the middle frame is disposed in the inner space.

4. The backlight assembly of claim 3, wherein the middle frame further comprises a bent portion connected to the U-shaped portion and disposed on an optical sheet disposed on the light source and the light guide plate.

5. The backlight assembly of claim 1, wherein the light source supporter includes a metal plate.

6. The backlight assembly of claim 1, wherein a hole is formed in [a] the bottom [surface] *portion* of the first receiving unit, and

the light source supporter further comprises a protrusion disposed in the hole.

7. The backlight assembly of claim 1, wherein the light source is in direct contact with the [lateral plane] *first surface* of the *second supporting portion of the* light source supporter.

8. The backlight assembly of claim 1, further comprising a reflective sheet interposed between the light guide plate and the [bottom plane] *supporting surface of the first supporting portion* of the light source supporter.

9. A backlight assembly comprising:

a light source which emits light;

13

a light guide plate [disposed adjacent to the light source and] which receives the light emitted from the light source;

a light source supporter disposed under the light source and the light guide plate; an optical sheet disposed on the light guide plate;

a first receiving unit accommodating the light guide plate and the light source, and

a middle frame which is coupled to the first receiving unit, *wherein a portion of the middle frame is disposed between the light source and a lateral portion of the first receiving unit,*

wherein the light source supporter comprises a [bottom plane] *first supporting portion* and a [lateral plane] *second supporting portion* which is extended vertically from the [bottom plane] *first supporting portion* and integrated with the [bottom plane] *first supporting portion, the first supporting portion comprising a supporting surface, the second supporting portion comprising a first surface and a second surface opposing the first surface, and*

wherein at least a portion of the middle frame is in direct contact with more than a substantial portion of [a major surface plane defining the lateral plane] *the second surface of the second supporting portion* of the light source supporter.

10. The backlight assembly of claim 9, wherein the light source is in direct contact with [both the bottom plane and the lateral plane of] *the first surface of the second supporting portion* of the light source supporter.

11. The backlight assembly of claim 9, wherein the middle frame comprises a U-shaped portion, and at least a portion of the U-shaped portion of the middle frame is disposed in the inner space.

12. The backlight assembly of claim 11, wherein the middle frame further comprises a bent portion connected to the U-shaped portion and disposed on an optical sheet disposed on the light source and the light guide plate.

13. The backlight assembly of claim 9, wherein the light source supporter includes a metal plate.

14. The backlight assembly of claim 9, wherein a hole is formed in a bottom surface of the first receiving unit, and the light source supporter further comprises a protrusion disposed in the hole.

15. A liquid crystal display, comprising:

a liquid crystal panel which displays an image; and

a backlight assembly comprising:

a light source disposed adjacent to an edge portion of the liquid crystal panel, *wherein the light source comprises a printed circuit board and a light emitting diode;*

14

a light guide plate [disposed adjacent to the light source and] which emits light to the liquid crystal panel;

an optical sheet disposed between the light guide plate and the liquid crystal panel;

a first receiving unit including a bottom [plane] *portion* and a lateral [plane] *portion* which is extended vertically from the bottom [plane] *portion* and integrated with the bottom [plane] *portion* and accommodating the light source, the light guide plate and the optical sheet; [and]

a light source supporter which supports the light source and the light guide plate, the light source supporter comprising a [bottom plane and a lateral plane] *first supporting portion and a second supporting portion* which is extended vertically from the [bottom plane] *first supporting portion* and integrated with the [bottom plane] *first supporting portion, the first supporting portion comprising a supporting surface, the second supporting portion comprising a first surface and a second surface opposing the first surface;* and

a second receiving unit covering at least a portion of the edge portion of the liquid crystal panel and the side wall of the first receiving unit,

wherein the light source and the light guide plate are disposed on the [first region of the bottom plane] *supporting surface of the first supporting portion* of the light source supporter, [and]

wherein the [lateral plane of] *second surface of the second supporting portion* of the light source supporter is in direct contact with the lateral [plane] *portion* of the first receiving unit,

wherein the first supporting portion of the light source supporter is disposed directly on the bottom portion of the first receiving unit, and

wherein a height of the second supporting portion of the light source supporter is less than or equal to a height of the lateral portion of the first receiving unit.

16. The liquid crystal display of claim 15, wherein the light source is in direct contact with the [lateral plane] *first surface of the second supporting portion* of the light source supporter.

17. The liquid crystal display of claim 15, further comprising a reflective sheet interposed between the light guide plate and the [bottom plane] *supporting surface of the first supporting portion* of the light source supporter.

18. The liquid crystal display of claim 15, further comprising a middle frame, which is coupled to the first receiving unit, wherein at least a portion of the middle frame is in direct contact with the light source supporter.

19. The liquid crystal display of claim 15, wherein the light source supporter includes metallic material.

* * * * *