



US00RE49655E

(19) **United States**
(12) **Reissued Patent**
Koo

(10) **Patent Number: US RE49,655 E**
(45) **Date of Reissued Patent: *Sep. 12, 2023**

(54) **SYSTEM AND METHOD FOR CORRECTING POSITION INFORMATION OF SURROUNDING VEHICLE**

(71) Applicant: **Hyundai Mobis Co., Ltd.**, Seoul (KR)

(72) Inventor: **Bon Wook Koo**, Yongin-si (KR)

(73) Assignee: **Hyundai Mobis Co., Ltd.**, Seoul (KR)

(*) Notice: This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/021,695**

(22) Filed: **Sep. 15, 2020**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,836,961**
Issued: **Dec. 5, 2017**
Appl. No.: **14/811,156**
Filed: **Jul. 28, 2015**

U.S. Applications:

(63) Continuation of application No. 16/540,257, filed on Aug. 14, 2019, now Pat. No. Re. 48,288, which is an application for the reissue of Pat. No. 9,836,961.

(30) **Foreign Application Priority Data**

Nov. 11, 2014 (KR) 10-2014-0156134

(51) **Int. Cl.**
G08G 1/01 (2006.01)
G08G 1/16 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G08G 1/0137** (2013.01); **G01S 13/931** (2013.01); **G06V 20/58** (2022.01);
(Continued)

(58) **Field of Classification Search**
CPC G06K 9/00805; G06K 9/3258; G06K 2209/15; G08G 1/0112; G08G 1/166;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,766,038 B1 * 7/2004 Sakuma G01P 3/806
340/933
7,982,634 B2 * 7/2011 Arrighetti G08G 1/04
340/937

(Continued)

FOREIGN PATENT DOCUMENTS

CN 101221049 A 7/2008
CN 102460535 A 5/2012

(Continued)

OTHER PUBLICATIONS

Chinese Office Action dated Aug. 31, 2017, in counterpart Chinese Patent Application No. 201510564809.1 (9 pages in Chinese, no English translation).

(Continued)


Primary Examiner — Deandra M Hughes

(74) *Attorney, Agent, or Firm* — NSIP Law

(57) **ABSTRACT**

The present invention relates to a system and a method for correcting position information of a surrounding vehicle, which provide accurate position information of a surrounding vehicle by correcting the position information of the surrounding vehicle received through vehicle-to-vehicle communication, and identifies a license-plate number of a front vehicle through a sensor mounted in a vehicle, calculates a position of the front vehicle, and compare position information, which is included in information including the identified number of the front vehicle in information received from the surrounding vehicle, with the calculated position of the front vehicle to correct the position information of the surrounding vehicle.

13 Claims, 3 Drawing Sheets




US RE49,655 E

<p>(51) Int. Cl. G08G 1/00 (2006.01) G01S 13/93 (2020.01) G08G 1/017 (2006.01) G08G 1/04 (2006.01) G06V 20/58 (2022.01) G06V 20/62 (2022.01) G01S 13/931 (2020.01) G08G 1/0967 (2006.01)</p> <p>(52) U.S. Cl. CPC G06V 20/63 (2022.01); G08G 1/0112 (2013.01); G08G 1/0175 (2013.01); G08G 1/04 (2013.01); G08G 1/09675 (2013.01); G08G 1/096716 (2013.01); G08G 1/096791 (2013.01); G08G 1/163 (2013.01); G08G 1/166 (2013.01); G08G 1/20 (2013.01); G01S 13/931 (2013.01); G06V 20/625 (2022.01)</p> <p>(58) Field of Classification Search CPC .. G08G 1/0175; G08G 1/04; G08G 1/096716; G08G 1/096575; G08G 1/096791; G08G 1/163; G08G 1/20; G08G 1/0137; G01S 13/931; G01S 2013/9325 See application file for complete search history.</p> <p>(56) References Cited</p> <p style="text-align: center;">U.S. PATENT DOCUMENTS</p> <p>8,520,695 B1 * 8/2013 Rubin G01C 21/3658 370/445 9,147,353 B1 9/2015 Slusar 9,360,328 B2 * 6/2016 You G01C 21/26 9,630,625 B2 * 4/2017 Shin G08G 1/161 9,836,961 B2 * 12/2017 Koo G08G 1/096791 9,892,567 B2 * 2/2018 Binion G06Q 40/08 10,091,855 B2 * 10/2018 Van Winkle F21V 23/04 10,518,877 B2 12/2019 Levien et al. RE48,288 E * 10/2020 Koo G08G 1/0175 10,843,685 B2 * 11/2020 Stahlin G08G 1/163 2004/0230373 A1 11/2004 Tzamaloukas 2006/0123051 A1 * 6/2006 Hofman G06K 9/6857 2007/0109111 A1 * 5/2007 Breed G01S 13/867 340/435 2007/0265777 A1 * 11/2007 Munakata G01C 21/26 701/301 2009/0237291 A1 * 9/2009 Sakuma G01S 5/0072 342/107 2010/0036578 A1 * 2/2010 Taguchi B60K 31/0008 701/93 2010/0052944 A1 * 3/2010 Luke B60W 30/02 340/903 2010/0112529 A1 * 5/2010 Miura B60T 8/3275 434/65 2010/0164789 A1 * 7/2010 Basnayake G01S 19/43 342/357.23 2010/0214085 A1 * 8/2010 Avery G08G 1/161 340/435 2011/0109475 A1 * 5/2011 Basnayake G08G 1/096783 340/902 2012/0029813 A1 2/2012 Tajima et al. 2012/0287276 A1 * 11/2012 Dwivedi G06K 9/00825 348/148 2012/0290146 A1 * 11/2012 Dedes G01C 21/3697 701/1 2012/0303176 A1 11/2012 Wong et al. 2013/0030687 A1 * 1/2013 Shida G01S 5/0072 701/301 2013/0060443 A1 * 3/2013 Shida B60K 31/0008 701/96 2013/0093618 A1 * 4/2013 Oh G01S 5/0072 342/357.44 2013/0131976 A1 5/2013 Hubbard et al.</p>	<p>2013/0188837 A1 7/2013 Takahashi 2013/0238181 A1 9/2013 James 2013/0265414 A1 * 10/2013 Yoon B60W 30/0953 348/118 2014/0032100 A1 * 1/2014 Park G01C 21/30 701/446 2014/0070980 A1 * 3/2014 Park G01S 19/42 342/118 2014/0292545 A1 * 10/2014 Nemoto G08G 1/163 340/988 2014/0300743 A1 * 10/2014 Kumon B60R 1/00 348/148 2014/0375813 A1 * 12/2014 Lee G08G 1/017 348/148 2015/0002620 A1 * 1/2015 Shin G06K 9/00805 348/36 2015/0022426 A1 1/2015 Ng-Throw-Hing et al. 2015/0073705 A1 * 3/2015 Hiwatashi G01S 19/48 701/468 2015/0081202 A1 3/2015 Levin 2015/0146605 A1 5/2015 Rubin et al. 2015/0153178 A1 * 6/2015 Koo G01C 21/165 701/472 2015/0170522 A1 6/2015 Noh 2015/0178998 A1 * 6/2015 Attard G07C 5/008 701/23 2015/0185735 A1 * 7/2015 Liang G05D 1/0234 701/523 2015/0200957 A1 * 7/2015 Zhang G08G 1/163 726/22 2015/0201120 A1 * 7/2015 Irie G06T 7/254 348/148 2017/0154531 A1 6/2017 Funabashi 2018/0151072 A1 * 5/2018 Altinger H04W 4/44 2018/0209795 A1 7/2018 Okuyama 2019/0035279 A1 1/2019 Tang et al.</p> <p style="text-align: center;">FOREIGN PATENT DOCUMENTS</p> <p>CN 102844800 A 12/2012 CN 103124994 A 5/2013 CN 103733084 A 4/2014 JP 2009-230390 A 10/2009 JP 2009-257763 A 11/2009 JP 2011-175572 A 9/2011 WO WO 2013/115470 A1 8/2013</p> <p style="text-align: center;">OTHER PUBLICATIONS</p> <p>Korean Office Action dated Sep. 23, 2020, in counterpart Korean Patent Application No. 10-2014-0156134 (5 pages in Korean, no English translation). Korean Office Action dated Sep. 23, 2020, in counterpart Korean Patent Application No. 10-2019-0091123 (5 pages in Korean, no English translation). Korean Office Action dated Sep. 23, 2020, in counterpart Korean Patent Application No. 10-2019-0091124 (5 pages in Korean, no English translation). U.S. Appl. No. 16/540,257, filed Aug. 14, 2019, Bon Wook Koo, Hyundai Mobis Co., Ltd. U.S. Appl. No. 16/716,787, filed Dec. 17, 2019, Bon Wook Koo, Hyundai Mobis Co., Ltd. U.S. Appl. No. 16/716,840, filed Sep. 15, 2020, Bon Wook Koo, Hyundai Mobis Co., Ltd. U.S. Appl. No. 17/021,271, filed Sep. 15, 2020, Bon Wook Koo, Hyundai Mobis Co., Ltd. U.S. Appl. No. 17/021,405, filed Sep. 15, 2020, Bon Wook Koo, Hyundai Mobis Co., Ltd. U.S. Appl. No. 17/021,867, filed Sep. 15, 2020, Bon Wook Koo, Hyundai Mobis Co., Ltd. U.S. Appl. No. 17/021,915, filed Sep. 15, 2020, Bon Wook Koo, Hyundai Mobis Co., Ltd.</p>
--	--


* cited by examiner

FIG. 1A



ACTUAL TRAVELLING POSITION

FIG. 1B



GPS-BASED POSITION RECEIVED THROUGH COMMUNICATION

FIG. 2





FIG. 3



**SYSTEM AND METHOD FOR CORRECTING
POSITION INFORMATION OF
SURROUNDING VEHICLE**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED
APPLICATIONS

Notice: More than one reissue application has been filed for a reissue of U.S. Pat. No. 9,836,961. The reissue applications are Reissue application Ser. No. 16/540,257 filed on Aug. 14, 2019, now U.S. Reissue Pat. No. RE48,288 issued on Oct. 27, 2020; Continuation Reissue application Ser. Nos. 16/716,787 and 16/716,840 both filed on Dec. 17, 2019; and Continuation Reissue application Ser. Nos. 17/021,271, 17/021,405, 17/021,695 (the present continuation reissue application), 17/021,867, and 17/021,915 all filed on Sep. 15, 2020. Reissue application Ser. No. 16/540,257 is for a reissue of U.S. Pat. No. 9,836,961. Continuation Reissue application Ser. Nos. 16/716,787, 16/716,840, 17/021,271, 17/021,405, 17/021,695, 17/021,867, and 17/021,915 are all continuation reissue applications of Reissue application Ser. No. 16/540,257, and are all for a reissue of U.S. Pat. No. 9,836,961.

This reissue application is a continuation reissue application of Reissue application Ser. No. 16/540,257 filed on Aug. 14, 2019, now U.S. Reissue Pat. No. RE48,288 issued on Oct. 27, 2020, which is for a reissue of U.S. Pat. No. 9,836,961 issued on Dec. 5, 2017, from application Ser. No. 14/811,156 filed on Jul. 28, 2015, and claims priority under 35 U.S.C. §119 to Korean Patent Application No. 10-2014-0156134[,] filed on Nov. 11, 2014, in the Korean Intellectual Property Office, the [disclosure] disclosures of which [is] are incorporated herein by reference in [its entirety] their entireties. This reissue application is also for a reissue of U.S. Pat. No. 9,836,961.

TECHNICAL FIELD

The present invention relates to a system and a method for providing position information of vehicles travelling around a travelling vehicle, and particularly, to a system and a method for correcting an error of position information of vehicles travelling in a surrounding area, and providing information of surrounding vehicles based on the corrected position information.

BACKGROUND

An advanced driver assistance system (ADAS) is a system assisting driving based on information obtained through a sensor or communication for safety and convenience for a driver, and an autonomous emergency braking (AEB) system, a forward collision warning (FCW) system, and the like are present as systems for preventing a collision with a vehicle travelling at a front side.

The AEB system or the FCW system may provide safe driving services according to information obtained through a sensor, or give a warning to a driver or self-control a vehicle based on information, such as deceleration or emer-

gency braking of a vehicle travelling at a front side, in information received from surrounding vehicles through vehicle-to-vehicle (V2V) communication, thereby reducing risk of an accident.

In this case, when the AEB system or the FCW system provides safe driving services based on the information received through the V2V communication, it is necessary to identify whether the received information is information of the vehicle travelling at the front side, so that the information received from the vehicle travelling at the front side is identified based on position information received from surrounding vehicles and information of a road which the vehicle travels on.

However, the position information received from the surrounding vehicles is based on a global positioning system (GPS) signal of the surrounding vehicles, and when an error is generated in the GPS signal, there is a problem in that incorrect position information of the surrounding vehicles may be received.

SUMMARY

The present invention has been made in an effort to provide a system and a method of correcting position information of a surrounding vehicle, which are capable of obtaining information of a front vehicle through a sensor, identifying the information of the front vehicle in information received from a surrounding vehicle, and comparing a position of the front vehicle obtained through the sensor and position information of the front vehicle received through vehicle-to-vehicle communication, thereby accurately correcting position information received from the surrounding vehicle.

An exemplary embodiment of the present invention provides a system for correcting position information of a surrounding vehicle, the system including: a front vehicle information obtaining unit configured to obtain a license-plate number of a front vehicle, which is travelling at a front side, measure a distance to the front vehicle, and calculate a position of the front vehicle; a surrounding vehicle information receiving unit configured to receive a number and position information of a surrounding vehicle, which is travelling in a surrounding area; a position information correcting unit configured to search for a license-plate number a surrounding vehicle corresponding to the license-plate number of the front vehicle, which is travelling at the front side, among the license-plate numbers of the surrounding vehicles received by the surrounding vehicle information receiving unit, compare position information of a surrounding vehicle, which transmits the searched number of the surrounding vehicle, with a position of the front vehicle, which is travelling at the front side, and correct the position information of the surrounding vehicle, which is travelling in the surrounding area, according to a result of the comparison; and a display unit configured to display a position of the surrounding vehicle, which is travelling in the surrounding area, according to the position information corrected by the position information correcting unit.

The position information correcting unit may calculate a correction value based on a difference between the position information of the surrounding vehicle, which transmits the searched number of the surrounding vehicle, and the position of the front vehicle, which is travelling at the front side, and correct the position information of the surrounding vehicle, which is received by the surrounding vehicle information receiving unit, according to the calculated correction value.

The position information correcting unit may generate a travel map of the surrounding vehicle, which is travelling in the surrounding area, according to the corrected position information.

When the position information of the surrounding vehicle, which transmits the searched number of the surrounding vehicle, is within a predetermined range from the position of the front vehicle, which is travelling at the front side, the position information correcting unit may generate a travel map of the surrounding vehicle, which is travelling in the surrounding area, according to the position information of the surrounding vehicle received by the surrounding vehicle information receiving unit.

The front vehicle information obtaining unit may calculate a position of the front vehicle, which is travelling at the front side, by using the measured distance to the front vehicle, information of a road, which the vehicle is travelling on, and a current position of the vehicle.

In this case, the information of the road may include total lanes and a curvature of the road which the vehicle is travelling on.

The front vehicle information obtaining unit may calculate a relative position of the front vehicle with respect to the current position of the vehicle by using the measured distance to the front vehicle, and when a road, which the vehicle is travelling on, is a curved road, the front vehicle information obtaining unit may calculate a relative position of the front vehicle with respect to the current position of the vehicle by using the measured distance to the front vehicle and a direction of the front vehicle.

The front vehicle information obtaining unit may obtain the license-plate number of the front vehicle, which is travelling at the front side, through a camera sensor, and measure a distance to the front vehicle through a radar or a laser scanner.

Another exemplary embodiment of the present invention provides a method for correcting position information of a surrounding vehicle, the method including: obtaining a license-plate number of a front travelling vehicle, and calculating a position of the front travelling vehicle; receiving a number and position information of a surrounding vehicle, which is travelling in a surrounding area; searching for a surrounding vehicle having a number corresponding to the license-plate number of the front travelling vehicle among the received numbers of surrounding vehicles; and correcting position information of the searched surrounding vehicle according to a position of the front travelling vehicle.

According to the present invention, it is possible to prevent a position of a vehicle from being inaccurately recognized due to an error of a GPS signal, and correct even position information of a vehicle, which is being travelling in an area, which is not detected by the sensor, by correcting position information of a surrounding vehicle received through the V2V communication based on information of a front vehicle obtained through the sensor.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B are diagrams illustrating an example of a case where a correction of position information is demanded by a system for correcting position information of a surrounding vehicle according to an exemplary embodiment of the present invention.

FIG. 2 is a block diagram illustrating a structure of the system for correcting position information of a surrounding vehicle according to the exemplary embodiment of the present invention.

FIG. 3 is a flowchart illustrating a process of a method of correcting position information of a surrounding vehicle according to another exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

Various advantages and features of the present invention and methods accomplishing thereof will become apparent from the following detailed description of exemplary embodiments with reference to the accompanying drawings. However, the present invention is not limited to exemplary embodiments disclosed herein, but will be implemented in various forms. The exemplary embodiments are provided so that the present invention is completely disclosed, and a person of ordinary skill in the art can fully understand the scope of the present invention, and the present invention will be defined by the scope of the appended claims.

Meanwhile, terms used in the present specification are to explain exemplary embodiments rather than limiting the present invention. Unless particularly stated otherwise in the present specification, a singular form also includes a plural form. The meaning of “comprises” and/or “comprising” used in this specification does not exclude the existence or addition of one or more other constituent elements, steps, operations, and/or devices in addition to aforementioned constituent elements, steps, operations, and/or device. Hereinafter, exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings.

FIGS. 1A and 1B are diagrams illustrating an example of a case where incorrect position information is received from a surrounding vehicle, and FIG. 1A illustrates actual travelling positions of a vehicle and a surrounding (front) vehicle, and FIG. 1B illustrates a case where a position of a surrounding vehicle is recognized based on a global positioning system (GPS) signal received from the surrounding vehicle, and an incorrect position is recognized due to an error of the GPS signal.

That is, actually, the vehicle is travelling in a state illustrated in FIG. 1A, but the vehicle recognizes a travelling situation as a travelling situation illustrated in FIG. 1B due to an error of a GPS signal received from a surrounding vehicle, and even though emergency braking information is received from the surrounding vehicle, the surrounding vehicle is not recognized as a front vehicle travelling on the same lane, so that there is a problem in that an advanced driver assistance system (ADAS) is not operated. A system for correcting position information of a surrounding vehicle according to an exemplary embodiment of the present invention is to solve the aforementioned problem, and hereinafter, a system and a method for correcting position information of a surrounding vehicle according to an exemplary embodiment of the present invention will be described with reference to FIGS. 2 and 3.

FIG. 2 illustrates a structure of a system for correcting position information of a surrounding vehicle according to an exemplary embodiment of the present invention.

A system **[100]** for correcting position information of a surrounding vehicle according to an exemplary embodiment of the present invention includes a front vehicle information obtaining unit **101**, a surrounding vehicle information receiving unit **102**, a position information correcting unit **[130] 103**, and a display unit **104**.

The front vehicle information obtaining unit **101** obtains a license-plate number of a vehicle travelling at a front side

5

of the vehicle, measures a distance to the front vehicle, and calculates a position of the front vehicle based on the measured distance.

The front vehicle information obtaining unit **101** processes an image photographed through a camera **110** mounted in the vehicle, and identifies the license-plate number of the front vehicle. That is, the front vehicle information obtaining unit **101** obtains the license-plate number of the front vehicle and uses the obtained number of the front vehicle for identifying information received from the vehicle travelling at the front side among information received from surrounding vehicles.

The front vehicle information obtaining unit **101** measures a distance to the front vehicle through a radar **120** or a laser scanner **130** mounted in the vehicle.

The front vehicle information obtaining unit **101** may calculate a position of the front vehicle by using the distance to the front vehicle measured through the radar **120** or the laser scanner **130**, a current position of the vehicle calculated based on a signal of a GPS **140**, and information of a road, which the vehicle is travelling on, obtained from a road map DB **150**. In this case, the road map DB **150** provides information, such as the total lanes **[ad]** and a curvature of the road, which the vehicle is travelling on.

Otherwise, the front vehicle information obtaining unit **101** may calculate a relative position (for example, 00 m in an X-axis and 00 m in a Y-axis) of the front vehicle with respect to the current position of the vehicle by using the distance to the front vehicle, and calculate a relative position of the front vehicle by using a distance to the front vehicle and a direction of the front vehicle while the vehicle travels a curved road.

The front vehicle information obtaining unit **101** transmits the obtained number of the front vehicle and the calculated position of the front vehicle to the position information correcting unit **103**.

The surrounding vehicle information receiving unit **102** receives travelling information of a surrounding vehicle from the surrounding vehicles, which are travelling in an area, in which the surrounding vehicles may be communicated with the vehicle through V2V communication, and the travelling information includes a license-plate number of the surrounding vehicle and position information of the surrounding vehicle.

The surrounding vehicle information receiving unit **102** transmits the received number and position information of the surrounding vehicle to the position information correcting unit **103**.

The position information correcting unit **103** compares the information of the front vehicle received from the front vehicle information obtaining unit **101** and the information of the surrounding vehicle received from the surrounding vehicle information receiving unit **102**, corrects the position information of the surrounding vehicle, and generates a travel map of the surrounding vehicle according to the corrected position information.

The position information correcting unit **103** searches for information of the surrounding vehicle including the same license-plate number as the license-plate number of the front vehicle in the information of the surrounding vehicle received from the surrounding vehicle information receiving unit **102**.

When the information of the surrounding vehicle including the same license-plate number as the license-plate number of the front vehicle is confirmed, the position information correcting unit **103** may recognize that the confirmed information of the surrounding vehicle is the information

6

transmitted by the vehicle actually travelling at the front side, so that the position information correcting unit **103** compares the position information received from the corresponding surrounding vehicle with the position of the front vehicle received from the front vehicle information obtaining unit **101**.

When the position information received from the surrounding vehicle, which is recognized as the front vehicle, is the same as the position of the front vehicle calculated by the front vehicle information obtaining unit **101** or is within a predetermined range from the position of the front vehicle, the position information received from the surrounding vehicle may be considered as accurate information having no error, so that the position information correcting unit **103** generates the travel map of the surrounding vehicle, which is travelling around the vehicle, according to the position information received from the surrounding vehicle.

When a distance between the position information received from the surrounding vehicle and the position calculated by the front vehicle information obtaining unit **101** is out of a predetermined range, the position information correcting unit **103** may recognize that the position information from the surrounding vehicle is inaccurate information due to an error of the GPS.

Accordingly, the position information correcting unit **103** calculates a correction value according to the difference between the position information received from the surrounding vehicle and the position calculated by the front vehicle information obtaining unit **101**, and corrects the position information received from the surrounding vehicle according to the calculated correction value.

In this case, the position information correcting unit **103** may correct only the position information received from the surrounding vehicle, which is recognized as the front vehicle, according to the calculated correction value, but may also correct position information of all of the surrounding vehicles received by the surrounding vehicle information receiving unit **102** according to the calculated correction value.

The position information correcting unit **103** may generate a travel map of the surrounding vehicle, which is travelling around the vehicle, based on the corrected position information, and display the generated travel map through a display unit **104**, thereby providing a driver with accurate position information of the surrounding vehicle which is travelling in a surrounding area.

The position information correcting unit **103** transmits the corrected position information of the surrounding vehicle or the generated travel map to a driving assist system **200** to enable the driving assist system **200** to use the corrected position information of the surrounding vehicle or the generated travel map for identifying the information of the front vehicle.

Accordingly, according to the present invention, the position information, which is received from the surrounding vehicle recognized as the front vehicle in the position information of the surrounding vehicles received through the V2V communication is compared with the position of the front vehicle calculated based on the information obtained through the sensor and corrected, so that even through the position information received through the V2V communication has an error, it is possible to provide a driver or the driving assist system **200** with accurate position information.

FIG. 3 is a flowchart illustrating a process of a method of correcting position information of a surrounding vehicle according to another exemplary embodiment of the present invention.

The system for correcting position information of a surrounding vehicle according to the exemplary embodiment of the present invention may compare position information of a surrounding vehicle received from the surrounding vehicle and information of a front vehicle obtained through the sensor and correct the position information of the surrounding vehicle to provide accurate position information of the surrounding vehicle.

The system for correcting position information of a surrounding vehicle recognizes a license-plate number of a vehicle, which is travelling at a front side, through a camera mounted in the vehicle (S300), and measures a distance to the front vehicle using a radar, and the like (S310). Further, the system for correcting position information of a surrounding vehicle calculates a position of the front vehicle based on a distance to the front vehicle and a current position of the vehicle and information of a road which the vehicle travels on (S320).

That is, the present invention may correct even position information of vehicles travelling in an area, which is not detected by the sensor, by determining accuracy of the position information received through the V2V communication based on the information of the front vehicle.

The system for correcting position information of a surrounding vehicle obtains the information of the front vehicle, and receives travel information including a number and position information of the surrounding vehicle from the surrounding vehicle (S330).

The system for correcting position information of a surrounding vehicle searches for information including the same license-plate number as the license-plate number of the front vehicle in the information received from the surrounding vehicle (S340).

When the information including the same license-plate number as the license-plate number of the front vehicle is identified in the information received from the surrounding vehicle, the system for correcting position information of a surrounding vehicle may recognize that the identified surrounding vehicle is the vehicle travelling at the front side, so that the system for correcting position information of a surrounding vehicle compares the position information of the identified surrounding vehicle with the obtained position of the front vehicle obtained through the sensor (S350).

When the position information of the identified surrounding vehicle is the same as the position of the front vehicle obtained through the sensor, or a difference between the position information of the identified surrounding vehicle and the position of the front vehicle obtained through the sensor is within a predetermined range (S360), the position information received from the surrounding vehicle may be determined as information having no error, so that the system for correcting position information of a surrounding vehicle provides the received position information to the driving assist system or generates a travel map of the surrounding vehicle based on the received position information (S390).

When the difference between the position information of the identified surrounding vehicle and the position of the front vehicle obtained through the sensor is out of the predetermined range (S360), the position information received from the surrounding vehicle may be considered as inaccurate information due to an error of GPS information, so that the system for correcting position information of a

surrounding vehicle calculates a correction value based on the difference between the received position information and the position of the front vehicle (S370).

The system for correcting position information of a surrounding vehicle corrects the received position information according to the calculated correction value (S380). In this case, the system for correcting position information of a surrounding vehicle may also correct position information of a surrounding vehicle, which is travelling in an area that is communication available with a vehicle, but is not detected by the sensor, by correcting all of the received position information of the surrounding vehicles according to the calculated correction value.

Accordingly, according to the present invention, it is possible to provide a driver with accurate position information of a surrounding vehicle by correcting an error of position information received from the surrounding vehicle, and provide accurate driving assist services according to a travel situation of a front vehicle by enabling the driving assist system to accurately identify information of a front vehicle received through the V2V communication.

Although an exemplary embodiment of the present invention has been described for illustrative purposes, those skilled in the art will appreciate that various modifications and changes are possible, without departing from the scope and spirit of the invention. Accordingly, the exemplary embodiments disclosed in the present invention are not intended to limit but illustrate the technical spirit of the present invention, and the scope of the technical spirit of the present invention is not limited by the exemplary embodiments. The protection scope of the present invention should be construed based on the following appended claims and it should be interpreted that all the technical spirit included within the scope identical or equivalent to the claims belongs to the scope of the present invention.

What is claimed is:

[1. An apparatus in a first vehicle to correct position information of a surrounding vehicle, the surrounding vehicle being located in a surrounding area of the first vehicle, the apparatus comprising:

- a front vehicle location unit configured to obtain a license-plate number of a second vehicle that is travelling in front of the first vehicle, measure a distance from the first vehicle to the second vehicle, and calculate a position of the second vehicle;
- a surrounding vehicle information receiving unit configured to receive license-plate numbers and position information of one or more surrounding vehicles that are travelling in the surrounding area of the first vehicle;
- a position information correcting unit configured to search for the license-plate number of the second vehicle among the license-plate numbers of the one or more surrounding vehicles received by the surrounding vehicle information receiving unit, compare the calculated position information of the second vehicle among the position information of the one or more surrounding vehicles with a received position information of the second vehicle received from the surrounding vehicle information receiving unit, correct the received position information of the second vehicle according to a result of the comparing, and transmit the corrected position information to a driving assist system to prevent a collision between the first vehicle and the second vehicle,

wherein the collision between the first vehicle and the second vehicle is prevented by an autonomous emergency braking system.]

[2. The apparatus of claim 1, wherein the position information correcting unit is further configured to calculate a correction value based on a difference between the received position information of the second vehicle and the calculated position of the second vehicle, and to correct the received position information of the second vehicle according to the calculated correction value.]

[3. The apparatus of claim 2, further comprising a display, wherein the position information correcting unit is further configured to generate a travel map of the second vehicle according to the corrected position information, and to display the generated travel map on the display.]

[4. The apparatus of claim 1, wherein, the position information correcting unit is further configured to generate a travel map of the second vehicle according to the received position information of the second vehicle when the received position information of the second vehicle is within a range from the calculated position of the second vehicle.]

[5. The apparatus of claim 1, wherein the front vehicle location unit is further configured to calculate the calculated position of the second vehicle using the measured distance to the second vehicle, information of a road on which the first vehicle is travelling, and a current position of the first vehicle.]

[6. The apparatus of claim 5, wherein the information of the road comprises total lanes and a curvature of the road on which the first vehicle is travelling.]

[7. The apparatus of claim 6, wherein the front vehicle location unit is further configured to calculate a relative position of the second vehicle with respect to the current position of the first vehicle using the measured distance to the second vehicle, and in response to the road on which the first vehicle is travelling being a curved road, to calculate a relative position of the second vehicle with respect to the current position of the first vehicle using the measured distance to the second vehicle and a direction of the second vehicle.]

[8. The apparatus of claim 1, wherein the front vehicle location unit is further configured to obtain the license-plate number of the second vehicle through a camera, and to measure the distance to the second vehicle through a radar or a laser scanner.]

[9. The apparatus of claim 1, further comprising:
a display unit configured to display a position of the second vehicle according to the position information which is corrected by the position information correcting unit.]

[10. A method to correct position information of a surrounding vehicle, the method comprising:

obtaining, by a camera, a license-plate number of a front travelling vehicle, and determining, by a measurement device, a calculated position of the front travelling vehicle;

receiving a license-plate number and position information of one or more surrounding vehicles that are travelling in a surrounding area;

searching for a surrounding vehicle comprising a license-plate number corresponding to the license-plate number of the front travelling vehicle among the received license-plate numbers of surrounding vehicles to determine a matching surrounding vehicle;

correcting received position information of the matching surrounding vehicle according to the calculated position of the front travelling vehicle; and

transmitting the corrected position information to a driving assist system to prevent a collision with the surrounding vehicle,

wherein the collision with the surrounding vehicle is prevented by an autonomous emergency braking system.]

[11. The method of claim 10, wherein the determining of the position of the front travelling vehicle comprises measuring a distance to the front travelling vehicle, and calculating the position of the front travelling vehicle using the measured distance, information of a road on which the first vehicle is travelling, and a current position of the first vehicle.]

[12. The method of claim 11, wherein the determining of the position of the front travelling vehicle comprises calculating a relative position of the front travelling vehicle with respect to the current position of the first vehicle using the measured distance to the front travelling vehicle, and when a road on which the first vehicle is travelling is a curved road, calculating a relative position of the front travelling vehicle with respect to the current position of the first vehicle using the measured distance to the front travelling vehicle and a direction of the front travelling vehicle.]

[13. The method of claim 10, wherein the correcting of the received position information of the matching surrounding vehicle according to the position of the front travelling vehicle comprises:

calculating a correction value according to a difference between the received position information of the matching surrounding vehicle and the calculated position of the front travelling vehicle; and

correcting the received position information of the matching surrounding vehicle according to the calculated correction value.]

[14. The method of claim 10, wherein the correcting of the received position information of the matching surrounding vehicle according to the calculated position of the front travelling vehicle comprises generating a travel map of the matching surrounding vehicle according to the received position information of the matching surrounding vehicle when the received position information of the matching surrounding vehicle is within a range from the calculated position of the front travelling vehicle.]

[15. The method of claim 11, wherein the measuring of the distance to the front travelling vehicle comprises measuring by either one of a radar device and a laser device.]

[16. The apparatus of claim 1, wherein the collision between the first vehicle and the second vehicle is further prevented by a forward collision warning system.]

[17. The method of claim 10, wherein the collision with the surrounding vehicle is further prevented by a forward collision warning system.]

18. *An apparatus in a first vehicle to correct position information of a surrounding vehicle, the surrounding vehicle being located in a surrounding area of the first vehicle, the apparatus comprising:*

a front vehicle location unit comprising one or more processors configured to:

obtain identifier information of a second vehicle that is visible from the first vehicle and is travelling in front of the first vehicle while the first vehicle is travelling on a curved road,

measure a distance from the first vehicle to the second vehicle, and

determine a relative position of the second vehicle with respect to a current position of the first vehicle using the measured distance from the first vehicle to the

11

second vehicle and information of the curved road on which the first vehicle is travelling;

a surrounding vehicle information receiver configured to receive identifier information and position information of one or more surrounding vehicles that are travelling in the surrounding area of the first vehicle; and

a position information correcting unit comprising one or more processors configured to:

identify the identifier information of the second vehicle among the identifier information of the one or more surrounding vehicles received by the surrounding vehicle information receiver,

compare the determined relative position of the second vehicle with received position information of the second vehicle among the position information of the one or more surrounding vehicles received by the surrounding vehicle information receiver,

correct the received position information of the second vehicle according to a result of the comparing, and generate a travel map of the second vehicle using the corrected position information of the second vehicle.

19. The apparatus of claim 18, wherein the front vehicle location unit comprising one or more processors is further configured to determine the relative position of the second vehicle with respect to the current position of the first vehicle using the measured distance to the second vehicle and a direction of the second vehicle.

20. The apparatus of claim 19, wherein the information of the curved road on which the first vehicle is travelling comprises a total number of lanes and a curvature of the curved road on which the first vehicle is travelling.

21. The apparatus of claim 18, wherein the position information correcting unit comprising one or more processors is further configured to:

determine a correction value based on a difference between the received position information of the second vehicle and the determined relative position of the second vehicle, and

correct the received position information of the one or more surrounding vehicles according to the determined correction value.

22. The apparatus of claim 18, wherein the front vehicle location unit is further configured to measure the distance from the first vehicle to the second vehicle through a radar or a laser scanner.

23. The apparatus of claim 18, wherein the position information correcting unit is further configured to transmit the travel map of the second vehicle to a driving assist system to prevent a collision between the first vehicle and the second vehicle, and

the collision between the first vehicle and the second vehicle is prevented by an autonomous emergency braking system.

24. A method performed in a first vehicle travelling on a road to correct position information of a surrounding vehicle, the method comprising:

obtaining, by a sensor, identifier information of a front travelling vehicle that is visible from the first vehicle and is travelling on the road in front of the first vehicle;

determining a position of the front travelling vehicle using a measured distance to the front travelling vehicle and information of the road;

receiving identifier information and position information of one or more surrounding vehicles that are travelling in a surrounding area of the first vehicle;

12

identifying a surrounding vehicle comprising identifier information corresponding to the identifier information of the front travelling vehicle among the received identifier information of the one or more surrounding vehicles as being a matching surrounding vehicle corresponding to the front travelling vehicle;

correcting the received position information of the matching surrounding vehicle according to the determined position of the front travelling vehicle; and

generating a travel map of the matching surrounding vehicle using the corrected position information of the matching surrounding vehicle.

25. The method of claim 24, wherein the determining a position of the front travelling vehicle using a measured distance to the front travelling vehicle and information of a road comprises:

determining a relative position of the front travelling vehicle with respect to a current position of the first vehicle using a measured distance from the first vehicle to the front travelling vehicle and a direction of the front travelling vehicle in response to the road on which the first vehicle is travelling being a curved road.

26. The method of claim 25, wherein the information of the road comprises a total number of lanes and a curvature of the road on which the first vehicle is travelling.

27. The method of claim 24, wherein the determining of the position of the front travelling vehicle comprises:

measuring a distance from the first vehicle to the front travelling vehicle through a radar or a laser scanner; and

determining the position of the front travelling vehicle using the measured distance from the first vehicle to the front travelling vehicle.

28. The method of claim 24, wherein the receiving of the identifier information and the position information comprises receiving the identifier information and the position information from the one or more surrounding vehicles including the matching surrounding vehicle via vehicle-to-vehicle (V2V) communication, and

the correcting of the received position information comprises correcting the received position information of the matching surrounding vehicle received via the vehicle-to-vehicle (V2V) communication according to the determined position of the front travelling vehicle.

29. The method of claim 24, wherein the obtaining, by the sensor, of the identifier information of the front travelling vehicle, the determining of the position of the front travelling vehicle, the receiving of the identifier information and the position information of the one or more surrounding vehicles, the identifying of the surrounding vehicle, the correcting of the received position information of the matching surrounding vehicle, and the generating of the travel map of the matching surrounding vehicle are collectively performed in sufficient time to enable a driving assist system to prevent a collision between the first vehicle and the matching surrounding vehicle based on the travel map of the matching surrounding vehicle.

30. The method of claim 24, further comprising transmitting the travel map of the matching surrounding vehicle to a driving assist system to prevent a collision with the front travelling vehicle,

wherein the collision with the front travelling vehicle is prevented by an autonomous emergency braking system.