



US00RE50074E

(19) **United States**  
(12) **Reissued Patent**  
**Kim et al.**

(10) **Patent Number:** **US RE50,074 E**  
(45) **Date of Reissued Patent:** **Aug. 6, 2024**

(54) **METHOD FOR MANAGING AND CONTROLLING EXTERNAL IOT DEVICE AND ELECTRONIC DEVICE SUPPORTING THE SAME**

(58) **Field of Classification Search**  
CPC ..... H04W 4/14; H04W 76/10; H04W 4/80;  
H04W 12/06; H04W 4/70; H04W 12/77;  
(Continued)

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)

(56) **References Cited**

(72) Inventors: **Nam Jin Kim**, Gyeonggi-do (KR); **Tae Jun Kim**, Gyeonggi-do (KR); **Hae Na Kim**, Gyeonggi-do (KR); **Yoe Chan Song**, Gyeonggi-do (KR); **Jung Hwan Song**, Gyeonggi-do (KR); **Sung Yeon Woo**, Gyeonggi-do (KR); **Joon Hwan Lee**, Seoul (KR); **Pyo Je Cho**, Gyeonggi-do (KR); **Han Jib Kim**, Gyeonggi-do (KR); **Gyu Cheol Choi**, Gyeonggi-do (KR); **Bo Kun Choi**, Seoul (KR)

U.S. PATENT DOCUMENTS

7,739,414 B2 \* 6/2010 Yi ..... H04L 69/329  
709/224  
9,380,055 B2 \* 6/2016 Hiramoto ..... H04L 63/083  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 102948112 A 2/2013  
CN 106355409 A 1/2017  
(Continued)

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

OTHER PUBLICATIONS

(21) Appl. No.: **17/587,085**

Korean Notice of Allowance dated Nov. 24, 2022 for KR Application No. 10-2021-0176983.

(22) Filed: **Jan. 28, 2022**

(Continued)

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **10,547,731**  
Issued: **Jan. 28, 2020**  
Appl. No.: **15/935,472**  
Filed: **Mar. 26, 2018**

*Primary Examiner* — C. Michelle Tarae

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye P.C.

(30) **Foreign Application Priority Data**

Mar. 29, 2017 (KR) ..... 10-2017-0039912

(57) **ABSTRACT**

A method and electronic device are disclosed herein. The electronic device includes a display, a communication unit, a processor and a memory storing instructions. The process executes the instructions to implement the method, including establishing wireless communication with one or more IoT devices, displaying a user interface for managing IoT devices, receiving a user input selecting a group of IoT devices, transmitting first information including user account data to an external server, transmitting second information to another device, the first information also indicating a selected group of IoT devices, and the second information causing the other device to communicatively connect with the first external server.

(51) **Int. Cl.**

**H04W 4/14** (2009.01)  
**H04L 9/40** (2022.01)


(Continued)

(52) **U.S. Cl.**

CPC ..... **H04W 4/14** (2013.01); **H04L 41/22** (2013.01); **H04L 63/0853** (2013.01);

(Continued)

**20 Claims, 20 Drawing Sheets**



- |      |                     |           |                  |         |                           |
|------|---------------------|-----------|------------------|---------|---------------------------|
| (51) | <b>Int. Cl.</b>     |           | 2016/0173578 A1  | 6/2016  | Sharma et al.             |
|      | <i>H04L 41/22</i>   | (2022.01) | 2016/0177937 A1  | 6/2016  | Liu et al.                |
|      | <i>H04L 67/12</i>   | (2022.01) | 2016/0197772 A1  | 7/2016  | Britt et al.              |
|      | <i>H04L 67/55</i>   | (2022.01) | 2016/0212178 A1* | 7/2016  | Zhang ..... H04L 65/1066  |
|      | <i>H04M 1/72415</i> | (2021.01) | 2016/0253083 A1  | 9/2016  | Lee et al.                |
|      | <i>H04W 4/70</i>    | (2018.01) | 2016/0337322 A1  | 11/2016 | Kang et al.               |
|      | <i>H04W 4/80</i>    | (2018.01) | 2017/0012950 A1  | 1/2017  | Kim et al.                |
|      | <i>H04W 12/06</i>   | (2021.01) | 2017/0126525 A1* | 5/2017  | Coates ..... H04L 43/0817 |
|      | <i>H04W 12/77</i>   | (2021.01) | 2017/0366966 A1* | 12/2017 | Carter ..... G06F 21/6245 |
|      | <i>H04W 76/10</i>   | (2018.01) | 2018/0019929 A1* | 1/2018  | Chen ..... H04L 41/145    |
|      |                     |           | 2018/0098366 A1* | 4/2018  | Cohn ..... H04W 76/14     |

- (52) **U.S. Cl.**  
 CPC ..... *H04L 67/12* (2013.01); *H04L 67/55* (2022.05); *H04M 1/72415* (2021.01); *H04W 4/70* (2018.02); *H04W 4/80* (2018.02); *H04W 12/06* (2013.01); *H04W 76/10* (2018.02); *H04W 12/77* (2021.01)

- (58) **Field of Classification Search**  
 CPC ..... H04L 67/12; H04L 63/0853; H04L 41/22; H04L 67/55; H04M 1/72415  
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,473,504 B2	10/2016	Sundaresan et al.
9,661,105 B2	5/2017	Sharma et al.
9,716,675 B2	7/2017	Choi et al.
9,774,497 B2	9/2017	Britt et al.
9,858,425 B2	1/2018	Guedalia et al.
10,075,420 B2	9/2018	Zhu et al.
10,230,717 B2*	3/2019	Main ..... H04W 12/37
10,248,399 B2	4/2019	Yoon
10,291,712 B2	5/2019	Koo
10,448,486 B2	10/2019	Baek et al.
10,484,347 B2	11/2019	Kim et al.
10,659,246 B2	5/2020	Guedalia et al.
10,693,959 B2*	6/2020	Peixoto Guimarães Ubirajara e Silva ..... H04L 12/2832
10,802,708 B2	10/2020	Lee et al.
2004/0146057 A1*	7/2004	Yi ..... H04L 67/56 370/465
2010/0131897 A1	5/2010	Yamao
2014/0006517 A1*	1/2014	Hsiao ..... G06Q 50/01 709/205
2014/0244834 A1	8/2014	Guedalia et al.
2015/0237071 A1*	8/2015	Maher ..... H04L 63/20 726/1
2016/0004871 A1	1/2016	Guedalia et al.
2016/0036764 A1*	2/2016	Dong ..... H04L 61/3025 370/254
2016/0072839 A1	3/2016	Mortimore, Jr.
2016/0105292 A1*	4/2016	Choi ..... H04L 12/1818 709/206
2016/0105415 A1*	4/2016	Hiramoto ..... H04L 63/0876 726/7
2016/0112429 A1	4/2016	Sundaresan et al.
2016/0112433 A1	4/2016	Chung et al.
2016/0112434 A1	4/2016	Chung et al.

FOREIGN PATENT DOCUMENTS

CN	106537849 A	3/2017
EP	2950510 A1	12/2015
JP	2007108973	4/2007
KR	10-2005-0035456 A	4/2005
KR	10-2011-0008964 A	1/2011
KR	10-2014-0081295 A	7/2014
KR	10-2015-0136981 A	12/2015
KR	20150144282	12/2015
KR	20160045505	4/2016
KR	20160046888	4/2016
WO	WO 2009096183 A1	8/2009
WO	WO 2016111916 A1	7/2016
WO	WO 2016-192537 A1	12/2016

OTHER PUBLICATIONS

Korean Notice of Allowance dated Jan. 27, 2023 for KR Application 10-2021-0137661.  
 Korean Office Action for Application No. 10-2021-0137661 issued Jan. 13, 2022 (w/English Translation).  
 Korean Office Action dated Apr. 27, 2022 for KR Application No. 10-2021-0176983.  
 CN Office Action dated Mar. 17, 2023 for CN Application No. 201810269312.0.  
 European Office Action dated Mar. 23, 2023 for EP Application No. 22165654.9.  
 Chinese Office Action dated Aug. 9, 2023 for CN Application No. 201810269312.0.  
 Korean Office Action dated Aug. 16, 2023 for KR Application No. 10-2021-0173030.  
 Chinese Notice of Allowance dated Dec. 8, 2023 for CN Application No. 201810269312.0.  
 Korean Notice of Final Rejection dated Feb. 27, 2024 for KR Application No. 10-2021-0173030.  
 Extended European Search Report dated May 16, 2024 for EP Application No. 24159316.9.  
 Tschofenig et al.; "Authentication and Authorization for Constrained Environments Using OAuth and UMA"; Internet Engineering Task Force; Mar. 9, 2015; p. 1-22; XP015105482.  
 Cirani et al.; "Effective Authorization for the Web of Things"; 2015 IEEE 2nd World Forum on Internet of Things; Dec. 14, 2015; p. 316-320; XP032854079.  
 European Search Report dated Aug. 3, 2018.

\* cited by examiner

100




FIG.1A






FIG. 1B




FIG. 2




FIG.3A




FIG. 3B




FIG. 4






FIG. 5




FIG. 6




FIG. 7





FIG. 8



901

910	920	930	940	950	960	970	980	990
Id	guest_id	inviter_id	token	oauth_client_id	group_role	create_time	update_time	state
476	NULL	326	010235*****	NULL	2	2017-01-06 11:42	2017-01-06 11:42	0



902

910	920	930	940	950	960	970	980	990
Id	guest_id	inviter_id	token	oauth_client_id	group_role	create_time	update_time	state
476	535	326	NULL	NULL	2	2017-01-06 11:42	2017-01-06 15:13	0

FIG.9




FIG. 10




FIG. 11




FIG.12






FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17




FIG. 18



**METHOD FOR MANAGING AND  
CONTROLLING EXTERNAL IOT DEVICE  
AND ELECTRONIC DEVICE SUPPORTING  
THE SAME**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.**

CROSS-REFERENCE TO RELATED  
APPLICATION(S)

This application is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2017-0039912, filed on Mar. 29, 2017, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein its entirety.

TECHNICAL FIELD

Various embodiments of the present disclosure relate to a method for managing and controlling an external Internet-of-Things (IoT) device and an electronic device supporting the same.

BACKGROUND

Internet of Things (hereinafter, referred to as IoT) technology has been developed. Various types of things may include a wireless communication module and may transmit and receive data with another device in real time through the communication module. For example, various IoT devices may be present in a house. TV, an air conditioner, an air cleaner, a vacuum cleaner, a light, or the like to which IoT technology is applied may be present in a living room, and a refrigerator, an oven, a light, or the like to which IoT technology is applied may be present in a kitchen.

The IoT devices may transmit and receive data by using wireless communication technologies, such as ZigBee®, Z-Wave®, BT/BLE®, Wi-Fi®, a cellular network (e.g., 3G or LTE), or the like. Each of the wireless communication technologies may have various characteristics in configuring a usable frequency, a data rate, a transmission distance, power consumption, and network topology.

An electronic device (e.g., a smartphone) that integrally manages the IoT devices may establish communication with IoT devices within a specified range and may store information beneficial for control. For example, the electronic device may execute an application for managing IoT devices. The application may output a UI capable of registering or removing a new IoT device.

The above information is presented as background information only to assist with an understanding of the present disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the present disclosure.

SUMMARY

In the related art, IoT devices existing in various spaces (e.g., a living room or a room in a house, an office, or the

like) may be operated through operating devices (e.g., remote controllers) in conjunction with the respective spaces.

Alternatively, the IoT devices may be operated by an electronic device (e.g., a smartphone) in which applications operating in conjunction with the IoT devices are installed. In this case, another electronic device in which an application capable of managing and controlling an IoT device is not installed has to repeatedly install applications, search for a plurality of IoT devices, and establish connections to manage and control the plurality of IoT devices.

Aspects of the present disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the present disclosure is to provide a method in which an electronic device managing a plurality of IoT devices shares setting information for managing the plurality of IoT devices with an external device, and an electronic device that supports the same.

In accordance with an aspect of the present disclosure, an electronic device includes a display, a wireless communication circuit, a processor, and a memory. The memory includes instructions executable by the processor to establish wireless communication with one or more IoT devices by using the wireless communication circuit, display a user interface for managing a plurality of including the one or more IoT devices through the display, receive a user input selecting a group of IoT devices from among the one or more IoT devices, transmit first information including user account data of the electronic device to a first external server using the wireless communication circuit, transmit second information to another electronic device using the wireless communication circuit, wherein the first information includes information indicating the selected group and the user account data of the electronic device, and wherein the second information causes the other electronic device to communicatively connect with the first external server and control one or more IoT devices included in the selected group.

In an aspect of the present disclosure, an electronic device is disclosed including a display, a wireless communication circuit, a processor and a memory, the memory stores instructions executable by the processor to: receive at least one of a push message through a first application for managing one or more Internet-of-Things (IoT) devices from a first external server and an SMS message related to the first application from a second external server, and when the first application is executed, receive, from the first external server, setting information for controlling the one or more IoT devices by another electronic device.

In an aspect of the present disclosure, an electronic device is disclosed including a display, a communication circuit, a memory and a processor. The processor establishes wireless communication with one or more Internet-of-Things (IoT) devices using the communication circuit, transmits setting information associated with the one or more IoT devices to an external server using the communication circuit, and transmits a request signal including first user account information and second user account information to the external server, wherein at least a portion of the transmitted setting information is included in the transmitted request signal and is further transmitted to another electronic device, wherein the first user account information indicates at least a first user registered to the electronic device, and wherein the second user account information indicates at least a second user registered to the other electronic device.



A device management method and an electronic device supporting the same, according to various embodiments of the present disclosure, may share setting information related to an IoT device with an external electronic device.

A device management method and an electronic device supporting the same, according to various embodiments of the present disclosure, may transmit an invitation message to an external electronic device by using a user account or a telephone number of an application that manages an IoT device.

A device management method and an electronic device supporting the same, according to various embodiments of the present disclosure, may safely share information and authority relating to control of an IoT device with an external electronic device through an authentication process.

Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the present disclosure.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1A and FIG. 1B illustrate an IoT device management system according to various embodiments;

FIG. 2 is a flowchart illustrating a device management method according to various embodiments;

FIG. 3A is a signal flow diagram illustrating a process of sharing IoT environment information using an account of a second user, according to various embodiments;

FIG. 3B is a signal flow diagram illustrating a process of sharing IoT environment information using identification information of an invitee device, according to various embodiments;

FIG. 4 illustrates a UI of an IoT management app according to various embodiments;

FIG. 5 illustrates a UI through which a host device transmits an invitation message, according to various embodiments;

FIG. 6 is a flowchart in the case where an invitee device receives an invitation message in an SMS form, according to various embodiments;

FIG. 7 illustrates a user interface of an invitee device that receives an SMS message as an invitation message, according to various embodiments;

FIG. 8 illustrates a user interface for identifying an invitation message, according to various embodiments;

FIG. 9 illustrates a DB table stored in an IoT server, according to various embodiments;

FIG. 10 is a signal flow diagram illustrating a process in which an invitee device makes a request to add a device, according to various embodiments;

FIG. 11 illustrates a sharing process using short-range communication, according to various embodiments;

FIG. 12 illustrates a PIN code input UI using an IoT server, according to various embodiments;

FIG. 13 illustrates a UI showing a process in which a host device and an invitee device share a PIN code, according to various embodiments;

FIG. 14 illustrates an invitation UI using a QR code, according to various embodiments;

FIG. 15 illustrates a join UI using a QR code, according to various embodiments;

FIG. 16 illustrates a UI for setting authority, according to various embodiments;

FIG. 17 is a block diagram of an electronic device according to various embodiments; and

FIG. 18 is a block diagram of a program module according to various embodiments.

Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

#### DETAILED DESCRIPTION

Hereinafter, various embodiments of the present disclosure will be described with reference to the accompanying drawings. Accordingly, those of ordinary skill in the art will recognize that modification, equivalent, and/or alternative on the various embodiments described herein can be variously made without departing from the present disclosure. With regard to description of drawings, similar components may be marked by similar reference numerals.

In the disclosure disclosed herein, the expressions “have”, “may have”, “include” and “comprise”, or “may include” and “may comprise” used herein indicate existence of corresponding features (for example, elements such as numeric values, functions, operations, or components) but do not exclude presence of additional features.

In the disclosure disclosed herein, the expressions “A or B”, “at least one of A or/and B”, or “one or more of A or/and B”, and the like used herein may include any and all combinations of one or more of the associated listed items. For example, the term “A or B”, “at least one of A and B”, or “at least one of A or B” may refer to all of the case (1) where at least one A is included, the case (2) where at least one B is included, or the case (3) where both of at least one A and at least one B are included.

The terms, such as “first”, “second”, and the like used herein may refer to various elements of various embodiments of the present disclosure, but do not limit the elements. For example, such terms are used only to distinguish an element from another element and do not limit the order and/or priority of the elements. For example, a first user device and a second user device may represent different user devices irrespective of sequence or importance. For example, without departing the scope of the present disclosure, a first element may be referred to as a second element, and similarly, a second element may be referred to as a first element.

It will be understood that when an element (for example, a first element) is referred to as being “(operatively or communicatively) coupled with/to” or “connected to” another element (for example, a second element), it can be directly coupled with/to or connected to the other element or an intervening element (for example, a third element) may be present. In contrast, when an element (for example, a first element) is referred to as being “directly coupled with/to” or “directly connected to” another element (for example, a second element), it should be understood that there are no intervening element (for example, a third element).

According to the situation, the expression “configured to” used herein may be used as, for example, the expression “suitable for”, “having the capacity to”, “designed to”, “adapted to”, “made to”, or “capable of”. The term “configured to (or set to)” must not mean only “specifically designed to” in hardware. Instead, the expression “a device configured to” may mean that the device is “capable of” operating together with another device or other components. CPU, for example, a “processor configured to (or set to)



perform A, B, and C” may mean a dedicated processor (for example, an embedded processor) for performing a corresponding operation or a generic-purpose processor (for example, a central processing unit (CPU) or an application processor) which may perform corresponding operations by executing one or more software programs which are stored in a memory device.

Terms used in this specification are used to describe specified embodiments of the present disclosure and are not intended to limit the scope of the present disclosure. The terms of a singular form may include plural forms unless otherwise specified. Unless otherwise defined herein, all the terms used herein, which include technical or scientific terms, may have the same meaning that is generally understood by a person skilled in the art. It will be further understood that terms, which are defined in a dictionary and commonly used, should also be interpreted as is customary in the relevant related art and not in an idealized or overly formal detect unless expressly so defined herein in various embodiments of the present disclosure. In some cases, even if terms are terms which are defined in the specification, they may not be interpreted to exclude embodiments of the present disclosure.

An electronic device according to various embodiments of the present disclosure may include at least one of smartphones, tablet personal computers (PCs), mobile phones, video telephones, electronic book readers, desktop PCs, laptop PCs, netbook computers, workstations, servers, personal digital assistants (PDAs), portable multimedia players (PMPs), MP3 players, mobile medical devices, cameras, and wearable devices. According to various embodiments of the present disclosure, the wearable devices may include accessories (for example, watches, rings, bracelets, ankle bracelets, glasses, contact lenses, or head-mounted devices (HMDs)), cloth-integrated types (for example, electronic clothes), body-attached types (for example, skin pads or tattoos), or implantable types (for example, implantable circuits).

In some embodiments of the present disclosure, the electronic device may be one of home appliances. The home appliances may include, for example, at least one of a digital video disk (DVD) player, an audio, a refrigerator, an air conditioner, a cleaner, an oven, a microwave oven, a washing machine, an air cleaner, a set-top box, a home automation control panel, a security control panel, a TV box (for example, Samsung HomeSync™, Apple TV™, or Google TV™), a game console (for example, Xbox™ or PlayStation™), an electronic dictionary, an electronic key, a camcorder, or an electronic panel.

In another embodiment of the present disclosure, the electronic device may include at least one of various medical devices (for example, various portable medical measurement devices (a blood glucose meter, a heart rate measuring device, a blood pressure measuring device, and a body temperature measuring device), a magnetic resonance angiography (MRA), a magnetic resonance imaging (MRI) device, a computed tomography (CT) device, a photographing device, and an ultrasonic device), a navigation system, a global navigation satellite system (GNSS), an event data recorder (EDR), a flight data recorder (FDR), a vehicular infotainment device, electronic devices for vessels (for example, a navigation device for vessels and a gyro compass), avionics, a security device, a vehicular head unit, an industrial or home robot, an automatic teller’s machine (ATM) of a financial company, a point of sales (POS) of a store, or an internet of things (for example, a bulb, various sensors, an electricity or gas meter, a spring cooler device,

a fire alarm device, a thermostat, an electric pole, a toaster, a sporting apparatus, a hot water tank, a heater, and a boiler).

According to some embodiments of the present disclosure, the electronic device may include at least one of a furniture or a part of a building/structure, an electronic board, an electronic signature receiving device, a projector, or various measurement devices (for example, a water service, electricity, gas, or electric wave measuring device). In various embodiments of the present disclosure, the electronic device may be one or a combination of the aforementioned devices. The electronic device according to some embodiments of the present disclosure may be a flexible electronic device. Further, the electronic device according to an embodiment of the present disclosure is not limited to the aforementioned devices, but may include new electronic devices produced due to the development of technologies.

Hereinafter, electronic devices according to an embodiment of the present disclosure will be described with reference to the accompanying drawings. The term “user” used herein may refer to a person who uses an electronic device or may refer to a device (for example, an artificial electronic device) that uses an electronic device.

FIGS. 1A and 1B illustrate an IoT device management system according to various embodiments.

Referring to FIGS. 1A and 1B, an IoT device management system **100** may include a first electronic device or host device **110**, a second electronic device **120**, and an IoT server **130**. According to various embodiments, the IoT device management system **100** may further include a message transfer server (e.g., an SMS server) **140**, an application market server **150**, and an authentication server **160**.

The first electronic device or host device **110** (hereinafter, referred to as the ‘host device’) (e.g., a smartphone or a tablet PC) may manage various IoT devices **111**. For example, the host device **110** may discover the IoT devices **111** around the host device **110** and may establish communication with each of the IoT devices **111**. The host device **110** may display, on a display thereof, the IoT devices **111** that are controllable.

The host device **110** may execute an application (hereinafter, referred to as the IoT management app) that manages IoT devices. The IoT management app may check a communication status of each IoT device **111** and may output a user interface for control of the IoT device **111**. In an embodiment, the IoT management app may be downloaded through the application market server **150** (e.g., Google Play Store or Apple App Store) and may be installed in the host device **110** or the second electronic device or the invitee device **120** (hereinafter, referred to as the ‘invitee device’) (e.g., a smartphone or a table PC).

According to various embodiments, the host device **110** may manage the various IoT devices **111** located in a plurality of places, by using the IoT management app. For example, the host device **110** may collectively manage a first group of IoT devices (e.g., TV **1**, refrigerator **1**, or air-conditioner **1**) located in a first area (e.g., a user’s home) and a second group of IoT devices (e.g., TV **2**, air-conditioner **2**, or air-cleaner **1**) located in a second area (e.g., the user’s office).

The IoT management app may manage the first group of IoT devices and the second group of IoT devices as separate things. For example, in the case where the user selects (e.g., through a touch input or a voice input) a place (e.g., a tab for managing the place) that corresponds to a first location (e.g., the user’s home), the host device **110** may display a list, status information, or controllable functions of the first



group of IoT devices (e.g., TV 1, refrigerator 1, and air-conditioner 1). In the case where the user selects a place corresponding to a second location (e.g., the user's office), the host device 110 may display a list, status information, or controllable functions of the second group of IoT devices (e.g., TV 2, air-conditioner 2, and air-cleaner 1). Alternatively, in the case where the user selects a tab corresponding to a full list, the host device 110 may display a list, status information, or functions of all the IoT devices included in the first and second groups.

The host device 110 may store setting information or control information (hereinafter, referred to as IoT environment information) about the plurality of IoT devices 111. For example, the IoT environment information may include identification information, device types, executable-function information, authority information, or control methods of the IoT devices 111.

According to various embodiments, the host device 110 (used with an account of a first user) may share the stored IoT environment information with the invitee device 120 (used with an account of a second user). For example, the host device 110 (e.g., a smartphone) of the first user (e.g., father) may provide IoT environment information about TV 1, refrigerator 1, and air-conditioner 1 located in the home to the invitee device 120 (e.g., a smartphone) of the second user (e.g., spouse or child). In the case where the IoT environment information is shared according to a specified procedure, the invitee device 120 may have control authority over TV 1, refrigerator 1, and air-conditioner 1.

According to various embodiments, the shared IoT environment information may be all or part of the IoT environment information stored in the host device 110. For example, information about all places (e.g., Home, Office, and Nearby), some places (Home), or some devices (e.g., TV or an air-conditioner registered in home) registered in the IoT environment information of the host device 110 may be shared with the invitee device 120.

According to various embodiments, the host device 110 may start a process of sharing the IoT environment information, by transmitting an invitation message (or a message for sharing) to the invitee device 120. The invitation message may include information about the host device 110, information about controllable IoT devices, information about the IoT management app, or information about places (or locations) where the IoT devices are located.

According to various embodiments, the host device 110 (registered by the first user's account) may transmit the invitation message, based on the account information or the telephone number of the second user of the invitee device 120 (registered by the second user's account). For example, in the case where an IoT management app is installed in the invitee device 120 and the invitee device 120 is logged in using the second user's account, the host device 110 may transmit the invitation message through the IoT server 130 by a push message method. In another example, in the case where an IoT management app is not installed in the invitee device 120, the host device 110 may transmit an SMS message including a URL for installation of an IoT management app as the invitation message.

According to various embodiments, the host device 110 may create an invitation message, based on IoT device information, the first user's account registered in the host device 110, and information about the invitee device 120. For example, the host device 110 or the IoT server 130 may create a hash code of the invitation message. In another example, the host device 110 may create an invitation message, based on information (name and spatial informa-

tion) of the host device 110 and a URL for downloading an IoT management app. Additional information about a method of transmitting the invitation message by the host device 110 may be provided through FIGS. 2, 3A, and 3B.

The invitee device 120 may receive an invitation message from the host device 110 or the IoT server 130. In an embodiment, the invitation message may be a message that is transmitted through a push message or a text message (e.g., SMS or MMS) of an IoT management app or short-range communication (e.g., NFC or BLE).

The invitee device 120 may receive the IoT environment information stored in the host device 110, by using the invitation message. In this case, the invitee device 120 may obtain control authority over at least one IoT device managed by the host device 110. The invitee device 120 may operate as a separate host device that is distinguished from the host device 110. Additional information about a process of receiving the IoT environment information by the invitee device 120 may be provided through FIG. 6.

The IoT server 130 may include a memory, a communication circuit, or a processor therein and may serve as an intermediary between the host device 110 and the invitee device 120 in a process of sharing the IoT environment information. The IoT server 130 may receive, from the host device 110, information (hereinafter, referred to as sharing setting information) useful for sharing the IoT environment information. The sharing setting information may include first user account information, place information (or group information of IoT devices), IoT device information, or information about the invitee device 120 (account information or a phone number of the second user).

The IoT server 130 may create a push message to be transmitted to the invitee device 120. The IoT server 130 may create a push message list, based on the sharing setting information.

In an embodiment, the IoT server 130 may transmit the push message in the case where an IoT management app is installed in the invitee device 120 and the invitee device 120 is logged in using the second user's account. In another embodiment, in the case where the invitee device 120 is not logged in to an IoT management app by using the second user's account, the IoT server 130 may transmit accumulated push messages to the invitee device 120 when the invitee device 120 logs in to the IoT management app by using the second user's account. In another embodiment, in the case where an IoT management app is not installed in the invitee device 120, the IoT server 130 may transmit, to the invitee device 120, a list of accumulated push messages based on the identification information (e.g., the telephone number) of the invitee device 120 when the invitee device 120 installs an IoT management app, creates an account of the second user, and performs SMS authentication related to the account of the second user.

According to various embodiments, the IoT server 130 may remove the information (e.g., the telephone number) of the invitee device 120 when settings for sharing the IoT environment information are completed.

The message transfer server 140 may play an intermediary role in the transfer of a message between the host device 110 and the invitee device 120. For example, the message transfer server 140 may serve as an intermediary to allow the host device 110 and the invitee device 120 to transmit and receive a message in an SMS or MMS form.

The application market server 150 may be a server capable of downloading various applications. The applica-



tion market server **150** may provide an installation file for installing an IoT management app, in response to a request of the invitee device **120**.

The authentication server **160** may perform authentication on a telephone number in response to a request of the invitee device **120**. In various embodiments, in the case where the host device **110** transmits an invitation message through the telephone number of the invitee device **120**, authentication of a subject requesting the invitation message from the IoT server **130** may be utilized to enhance security. In this case, the invitee device **120** may request the authentication server **160** to perform an authentication procedure on the telephone number of the invitee device **120**. The authentication server **160** may transmit the authentication result to the IoT server **130** and the invitee device **120**.

FIG. 2 is a flowchart illustrating a device management method according to various embodiments.

Referring to FIG. 2, in operation **211**, the host device **110** may establish wireless communication with one or more IoT devices using a communication circuit. For example, the host device **110** may establish communication channels with IoT devices around the host device **110** using short-range communication, Wi-Fi communication (e.g., communication belonging to the same AP), and/or cellular communication. The host device **110** may receive information useful for controlling the IoT devices (e.g., identification information or device types of the IoT devices, or information about controllable functions) from the IoT devices, or the IoT server **130** through the communication channels. According to various embodiments, the host device **110** may establish the communication channels with the one or more IoT devices through separate authentication processes (e.g., such as input of a password, an identification number, or input of some biometric information).

In operation **212**, the host device **110** may output, through a display, a user interface including a list of the one or more IoT devices. The host device **110** may execute an IoT management app to display a list of IoT devices that are capable of communication and/or otherwise controllable. According to various embodiments, the host device **110** may manage the one or more IoT devices by dividing the IoT devices into groups. For example, the host device **110** may group the plurality of IoT devices according to location (e.g., such as home, office, living room, room **1**, room **2**, etc.) indicating where the plurality of IoT devices are physically located within a locale, access points (APs) to which the plurality of IoT devices are connected, and/or any other criteria created or configured by a user.

In operation **213**, the host device **110** may receive, from a first user, a user input for selecting a group of IoT devices from among the one or more IoT devices. For example, as described above, the group may be classified according to the location where the IoT devices are located. The user input may therefore include an input selecting a tab corresponding to the particular group and adding another user in the IoT management app. For example, in the case where the user selects a "living-room" tab from among tabs including "living-room," "room **1**," and "room **2**" and further selects an "add member" button, processes executable to share IoT environment information may be initiated.

In operation **214**, the host device **110** may transmit first information including user account data of the first user to the IoT server **130** (the first external server) using the communication circuit. The first information may also include information about the selected group, and the account of the first user associated with the host device **110**. For example, the first information may include at least one

or more of first user account information, place information (or group information of IoT devices), IoT device information, and information about the invitee device **120** (i.e., referring to for example second user account information or a phone number associated with the invitee).

In operation **215**, the host device **110** may transmit the second information to another electronic device (e.g., referring to the invitee device **120**) using the communication circuit. The second information may be information which facilitates the other electronic device to communicatively respond to the IoT server **130** to connect to and thus control the selected group. For example, the second information may include URL information for installing an IoT management app.

According to an embodiment, the second information may be delivered to the other electronic device through the IoT server **130**, or may be transmitted to the other electronic device through the separate message transfer server **160**. According to another embodiment, the host device **110** may transmit the second information to the other electronic device (e.g., the invitee device **120**) through short-range communication (e.g., Bluetooth).

FIG. 3A is a signal flow diagram illustrating a process of sharing IoT environment information using an account of a second user, according to various embodiments.

Referring to FIG. 3A, in operation **331**, the host device **110** may create an invitation message (or a request signal) by receiving IoT environment information to be shared (e.g., a list of IoT devices or the location of the IoT devices) and the account of the second user of the invitee device **120** from a user through an IoT management app. For example, the second user's account information may be directly input by the user, or may be input through information of a contact stored in the host device **110**.

In operation **332**, the host device **110** may transmit the created invitation message to the IoT server **130**. For example, the invitation message may include first user account information, place information (or group information of IoT devices), IoT device information, or second user account information.

In operation **333**, the IoT server **130** may search a database for the second user's account that was indicated or otherwise included in the invitation message. For example, in the case where an IoT management app is installed in the invitee device **120** a log-in history of the second user exists, the second user's account may be discoverable in the database of the IoT server **130**. According to an embodiment, in the case where the second user's account is not discovered in the database of the IoT server **130**, the IoT server **130** may determine that the second user's account included in the invitation message is invalid, and may transmit an error message to the host device **110**. The host device **110**, when receiving the error message from the IoT server **130**, may display a notification (e.g., a pop-up message) to the user, or may provide a user interface of guide screen to prompt the user to reenter the second user's account.

In the case where the second user's account is discovered in the database of the IoT server **130**, the IoT server **130** may, in operation **334**, create a database table based on the received invitation message. For example, the IoT server **130** may create a database table that includes first user account information, second user account information, authority information, creation time information, or update time information.



## 11

In operation 335, the IoT server 130 may inform the invitee device 120 corresponding to the second user that the invitation message has arrived, by using a push message.

According to an embodiment, the IoT server 130 may transmit the push message in real time when the invitee device 120 is logged in to the IoT management app by using the discovered account of the second user, or when the invitee device 120 allows the receipt of a push message. According to another embodiment, in the case where the invitee device 120 is not logged in to the IoT management app by using the discovered account of the second user or does not allow the receipt of a push message, the IoT server 130 may transmit the push message after the invitee device 120 logs in to the IoT management app by using the second user's account. According to another embodiment, in the case where an IoT management app is not installed in the invitee device 120, the IoT server 130 may transmit the push message after an IoT management app is installed in the invitee device 120 and the invitee device 120 logs in to the IoT management app by using the second user's account.

In operation 336, the invitee device 120 may identify the invitation message. In the case where the invitee device 120 is logged in to the IoT management app using the second user account, the invitee device 120 may inform the second user of the reception or arrival of the invitation message in real time. In the case where the invitee device 120 is not logged in to the IoT management app by using the second user account, the invitee device 120 may inform the second user of the arrival of the invitation message after logging in to the IoT management app.

According to various embodiments, the invitee device 120 may automatically execute the IoT management app when the second user identifies the invitation message.

In operation 337, the invitee device 120 may log in to the IoT management app using the second user account, and may request the IoT environment information from the IoT server 130.

According to various embodiments, the invitee device 120 may automatically log in using the second user account according to settings of the installed IoT management app and may request the IoT server 130 to provide the IoT environment information.

In operation 338, the IoT server 130 may identify the second user's account and the invitation message in the database table.

In operation 339, the IoT server 130 may transmit the IoT environment information to the invitee device 120. When the invitee device 120 receives the IoT environment information, the invitee device 120 may control at least some of the IoT devices managed by the host device 110.

FIG. 3B is a signal flow diagram illustrating a process of sharing IoT environment information using identification information of an invitee device, according to various embodiments.

Referring to FIG. 3B, in operation 351, the host device 110 may create an invitation message by entering IoT environment information to be shared (e.g., an IoT device list or locations of IoT devices) and identification information (e.g., a telephone number) of the invitee device 120 into an IoT management app.

In operation 352, the host device 110 may transmit the created invitation message to the IoT server 130.

In operation 353, the IoT server 130 may create a database table based on the received invitation message.

In operations 354 and 354\_1, the host device 110 may transmit the created invitation message to a message transfer server (e.g., the message transfer server 140 of FIG. 1B).

## 12

The message transfer server 140 may transmit an SMS message corresponding to the invitation message to the invitee device 120. The invitation message may include identification information (e.g., a telephone number or a first user account) of the host device 110. The invitation message may include a URL for installing an IoT management app.

In operation 355, the invitee device 120 may identify the invitation message transmitted through the message transfer server 140. The invitee device 120 may determine whether an IoT management app is installed in the invitee device 120. For example, when the invitee device 120 receives, from a user, an input selecting the URL included in the invitation message, the invitee device 120 may determine whether an IoT management app is installed in the invitee device 120.

In the case where an IoT management app is not installed in the invitee device 120, the invitee device 120 may, in operations 356 and 356\_1, connect to the application market server 150 and request data for installing an IoT management app.

In operation 357, the invitee device 120 may receive, from the application market server 150, data for installing the IoT management app and may install the IoT management app using the received data.

In operation 358, the invitee device 120 may log in to the IoT management app by using an account of a second user. According to an embodiment, the IoT management app may output a UI for creating an account.

According to various embodiments, in operation 359, the invitee device 120 may request an authentication server (e.g., the authentication server 160 of FIG. 1B) to authenticate the identification information (e.g., the telephone number) of the invitee device 120. For example, in the case where the invitee device 120 logs in to the IoT management app by using the second user's account in operation 358, the invitee device 120 may perform an authentication operation through the identification information (e.g., the telephone number).

In operation 360, the authentication server 160 may perform authentication on the telephone number of the invitee device 120.

In operation 361, the authentication server 160 may transmit the authentication result to the IoT server 130 and the invitee device 120.

In the case where the authentication result is valid, the IoT server 130 may, in operation 362, search for the identification information (e.g., the telephone number) of the invitee device 120 and update the DB table. The IoT server 130 may update the account information of the second user. According to an embodiment, the IoT server 130 may update the DB table created in operation 353, based on the second user's log-in information. The second user account information may have been newly recorded in the updated DB table, and accordingly, an update time may be modified. Also, the IoT server 130 may also enhance security by removing the identification information (e.g., the telephone number) of the invitee device 120 that is stored in the DB table.

In operation 363, the IoT server 130 may transmit the IoT environment information to the invitee device 120. The invitee device 120 may share control authority over at least some of the IoT devices managed by the host device 110, based on the received IoT environment information.

FIG. 4 illustrates a UI of an IoT management app according to various embodiments. FIG. 4 is merely illustrative, and the present disclosure is not limited thereto.



Referring to FIG. 4, an IoT management app may output a user interface **401** for managing a plurality of IoT devices. The user interface **401** may include a list of the plurality of IoT devices **420**. The user interface **401** may display identification information or device type of each IoT device, or status information thereof (e.g., whether the IoT device is driven or not, a scheduled routine, or settings).

According to various embodiments, the user interface **401** may display the list of the IoT devices **420** by dividing the IoT devices into groups. FIG. 4 illustrates an example in which the IoT devices are grouped based on places where the IoT devices are located. It is understood of course that the present disclosure is not limited to this kind of grouping.

According to various embodiments, the user interface **401** may further include place tabs **410**, an IoT device list **420**, and/or a plus button **440**.

The place tabs **410** may display place information (i.e., location information) set by the host device **110** and may allow a user to select each place. IoT devices located in the same location may be simultaneously or separately controlled.

When the user selects one of the place tabs **410**, IoT devices included in the selected group may be displayed. For example, in the case where a “home” tab is selected, a user interface **401a** related to IoT devices located in the home may be displayed. The user interface **401a** may include a sub-device list **420a** and a menu **415** for collectively controlling the group. The sub-device list **420a** may correspond to at least some of the IoT devices included in the IoT device list **420**.

The plus button **440** may be used to add an IoT device, a location, a user having new control authority, or a control mode. Additional information about adding a user having new control authority are illustrated in more detail below, in FIG. 5.

According to various embodiments, setting menus may be output differently, depending on a type of a selected place tab from among the tabs **410**. For example, in the case where an “All devices” tab is selected from the place tabs **410**, a list of “Add place,” “Add function execution rule,” and “Delete device” may be included in a setting menu. In the case where the “home” tab is selected from the place tabs **410**, a list of “Add editing mode,” “Add place,” “Add member,” and “Add function execution rule” may be included in a setting menu.

According to an embodiment, a tab created based on IoT environment information received from another device may not include a device addition item. Alternatively, at least some functions may be limited in the created tab. For example, a tab (e.g., Home of the host device **110**) created based on IoT environment information received from the host device **110** by an IoT management app of the invitee device **120** may not have or be denied authority to perform more secure functions, such as editing a routine or register a routine.

According to various embodiments, the user interface **401** may further include a routine dash board (not illustrated). The routine dash board may be updated in the case where the host device **110** registers a routine. For example, the host device **110** may configure an air-conditioner to be turned on in the morning, and may configure a specific device to perform an operation, by identifying whether an event occurs.

According to various embodiments, the user interface **401** may further include a device dash board (not illustrated). The device dash board may display the name of a registered

IoT device, information about the owner of the device, and an operation performed in the device.

FIG. 5 illustrates a UI through which a host device transmits an invitation message, according to various embodiments. FIG. 5 is merely illustrative, and the present disclosure is not limited thereto.

Referring to FIG. 5, the host device **110** may display an invitation message creation screen **501** when an input is detected requesting addition of a new user occurs (e.g., when a user selects “Add member” by selecting the plus button **440** of FIG. 4).

The invitation message creation screen **501** may include a UI for selecting a method of transmitting an invitation message. For example, the invitation message creation screen **501** may include a first field **510** into which a second user’s account is entered, and a button **520** for selectable to request usage of an SMS message.

In the case where a first user desires to permit issuance of control authority to the second user using the second user’s account, the first user may enter the second user’s account into the first field **510** and select a confirmation icon or element **511**. The second user’s account may be responsively transmitted to an IoT server (e.g., the IoT server **130** of FIG. 1A).

The IoT server **130** may check validity of the second user’s account input. In the case where data matching the second user’s account is included in a database table, the IoT server **130** may transmit a push message to the invitee device **120** by using the matched data.

In the case where there is no data matching the second user’s account in the database table, the IoT server **130** may notify, through a displayed pop-up window, the first user of the fact that the requested user (having no log-in history) is not registered in an IoT management app.

In an embodiment, in the case where the first user’s account is entered into the first field **510** or the account of the second user having control authority is entered into the first field **510**, the host device **110** may display an error message.

In an embodiment, a plurality of pieces of second user account information may be entered into the first field **510** through separators (e.g., “,” or “;”). For example, in the case where a plurality of pieces of second user account information separated from one another by specified separators are entered into the first field **510** and the user selects the okay button **511**, the plurality of pieces of second user account information may be transmitted to the IoT server **130**.

The first user may use the message use button **520** in the case where the first user wants to transmit an invitation message by using an SMS message. In the case where the first user selects the message use button **520**, the host device **110** may output an address book screen **502**. The first user may select the second user’s telephone number from the address book, or may directly enter the second user’s telephone number.

The host device **110** may display a message editor screen **503**, based on the second user’s telephone number input. The message editor screen **503** may include an invitation message **550**. For example, the invitation message **550** may include the name of the host device **110**, the first user’s account, information about places where IoT devices are located, and URL information for downloading an IoT management app or a related guide. According to an embodiment, the URL information may be created by the IoT management app or the IoT server and may be encrypted information.

In the case where the user selects a send button, the invitation message **550** may be transmitted to the invitee



device **120** through a message transfer server (e.g., the message transfer server **140** of FIG. **1B**).

According to various embodiments, the host device **110** may transmit sharing setting information (e.g., the first user account information, place information (or group information of IoT devices), IoT device information, the telephone number of the invitee device **120**, or the time at which the invitation message was transmitted) to the IoT server **130** in the background. The IoT server **130** may create a database table, based on the received sharing setting information.

FIG. **6** is a flowchart in the case where an invitee device receives an invitation message in an SMS form, according to various embodiments.

Referring to FIG. **6**, in operation **610**, an invitee device (e.g., the invitee device **120** of FIG. **1B**) may receive an invitation message in an SMS form from a host device (e.g., the host device **110** of FIG. **1B**). For example, the invitation message may be transmitted through a message transfer server (e.g., the message transfer server **140** of FIG. **1B**). In an embodiment, the invitation message may be in a text or image format. The invitation message may include information associated with a first user or the host device **110** that initiated the invitation (e.g., a telephone number or the first user's account ID) or URL information for installing an IoT management app.

In operation **620**, the invitee device **120** may determine whether the IoT management app specified in the invitation message is installed in the invitee device **120**, based on an operation identifying the invitation message by a user. For example, in the case where a second user (e.g., the user of the invitee device **120**) selects the URL information for installing the IoT management app, the invitee device **120** may determine whether the IoT management app is installed. In another example, the invitee device **120**, when receiving the invitation message in an SMS form, may analyze text included in the SMS and may determine whether the IoT management app is installed.

In the case where the specified IoT management app is not installed in the invitee device **120**, the invitee device **120** may, in operation **625**, connect to the app market server **150** (e.g., Google Play Store or Apple App Store) according to an input of the second user (e.g., execution of a URL shortcut) to download and install the specified IoT management app.

In operation **630**, the invitee device **120** may determine whether the invitee device **120** is logged in to the IoT management app by using the second user's account.

In the case where the invitee device **120** is not logged in to the IoT management app, the invitee device **120** may, in operation **635**, output a user interface for log-in (e.g., a screen including a UI for entering account information or a UI for signing up for a membership).

According to an embodiment, in the case where the user identifies (or selects) the received invitation message in an SMS form in the state in which the invitee device **120** logs in to the IoT management app by using the second user's account, the invitee device **120** may automatically execute the IoT management app.

In the case where the invitee device **120** is logged in to the IoT management app, the invitee device **120** may, in operation **640**, receive an invitation message in a push message form from the IoT server **130**.

According to various embodiments, in operation **650**, the invitee device **120** may determine whether the second user has generated an input approving the invitation. In the case where the second user rejects the invitation, the invitee device **120** may not obtain authority to control IoT devices managed by the host device **110**. According to an embodi-

ment, in the case where the invitee device **120** transmits rejection information to the IoT server **130**, the IoT server **130** may remove information related to the invitation message from a database.

In the case where the second user generates an input approving the invitation, the invitee device **120** may, in operation **655**, receive IoT environment information from the IoT server **130**. The invitee device **120** may share at least a part of control authority of the host device **110** over the IoT devices. For example, the invitee device **120** may obtain control authority over at least one IoT device belonging to a group shared by the host device **110**.

FIG. **7** illustrates a user interface of an invitee device that receives an SMS message as an invitation message, according to various embodiments. FIG. **7** is merely illustrative, and the present disclosure is not limited thereto.

Referring to FIG. **7**, on a screen **701**, an invitee device (e.g., the invitee device **120** of FIG. **1B**) may receive an invitation message **710**. The invitation message **710** may include information (e.g., a telephone number or an account ID) of a first user or a host device (e.g., the host device **110** of FIG. **1B**) that initiated the invitation. Also, the invitation message **710** may include URL information **711** for downloading an IoT management app. In an embodiment, the invitation message **710** may be implemented using text or an image.

On a screen **702**, the invitee device **120** may display a page for downloading the IoT management app in the case where a user selects the information (e.g., the URL information **711**) of the invitation message **710**. The page may include display of an icon or element **720** selectable to imitate the download.

On a screen **703**, the invitee device **120** may output a user interface for log-in (e.g., a UI for signing up for a membership) in the case where the invitee device **120** is not logged in to the IoT management app after the IoT management app has completed installation.

According to various embodiments, in the case where the IoT management app is installed in the invitee device **120** in advance, the processes corresponding to the screens **702** and **703** may be omitted.

On a screen **704**, the invitee device **120** may output a user interface for receiving a user log-in. A second user may log in by entering a second user account and a password into the respective entry fields.

On a screen **705**, the invitee device **120** may create an account to perform an SMS personal identification number or "PIN" authentication process in the case where the invitee device **120** logs in to the IoT management app for the first time. Based on the SMS PIN authentication result, the IoT server **130** may match and store, in a DB table, the telephone number of the invitee device **120** and the second user account of the IoT management app. According to various embodiments, the telephone number of the invitee device **120** may be removed from the DB table later. According to an embodiment, the information (e.g., the telephone number) of the second user that is used for the SMS PIN authentication process may be input by the second user or a system (e.g., an OS). For example, in the case where the information of the second user is input by the system, the information of the second user may be automatically input.

According to various embodiments, in the case where the invitee device **120** has previously logged in using the second user account, the process corresponding to the screen **705** may be omitted.

On a screen **706**, the invitee device **120** may determine whether the second user approves the invitation. For



example, the invitee device **120** may output a screen that includes a rejection button **761** and an approval button **762** each selectable to determine whether to approve sharing of IoT environment information. According to an embodiment, in the case where the second user receives a plurality of invitation messages from the first user or receives invitation messages from a plurality of users, the invitee device **120** may output the plurality of invitation messages sequentially (e.g., in the order that the invitation messages are received or with respect to the first user).

In the case where the second user selects the approval button **762** on the screen **706**, the invitee device **120** may receive IoT environment information from the IoT server **130** and may provide a screen **707** for controlling IoT devices, based on the received information. The invitee device **120** may share at least a part of control authority of the host device **110** over the IoT devices.

In the case where the second user selects the rejection button **761** on the screen **706**, the invitee device **120** may transmit an invitation rejection message (or signal) to the IoT server **130**. The IoT server **130** may remove the invitation message from a database of the IoT server **130**, based on the invitation rejection message.

FIG. **8** illustrates a user interface for identifying an invitation message, according to various embodiments. FIG. **8** is merely illustrative, and the present disclosure is not limited thereto.

Referring to FIG. **8**, an invitation message **801** may include first user information **810**, an invitation guide **820**, an approval button **830**, and a rejection button **840**. For example, the invitation message **801** may be output on the screen **706** of FIG. **7**.

The first user information **810** may include information about a first user having transmitted the invitation message (e.g., an account ID, the name, or a profile picture of the first user) and information about the host device **110** (e.g., the telephone number).

The invitation guide **820** may include a simple introduction to a function, a greeting, or the like. The invitation guide **820** may include descriptions of a place of invitation, a device range, and the like.

The approval button **830** and the rejection button **840** may be selectable buttons for indicating whether to approve sharing of IoT environment information.

In the case where a second user selects the approval button **830**, a user interface **802** for controlling IoT devices may be output. The second user may control the IoT devices displayed on the user interface **802**.

In the case where the second user selects the rejection button **840**, an additional dialogue **803** for confirming the rejection may be output. In the case where the rejection is selected once more, the invitee device **120** may not obtain authority to control the IoT devices managed by the host device **110**. Information about the second user's selection of rejection may be transmitted to the IoT server **130**. In an embodiment, the invitee device **120** may transmit, to the host device **110**, an SMS message about the selection of rejection.

According to various embodiments, in the case where the invitee device **120** receives a plurality of invitation messages, the plurality of invitation messages may be displayed in a card form on a dashboard. For example, in the case where the invitee device **120** receives an invitation message of office and home from John and an invitation message of home from Paul, Office, Home, and Home tabs may be created on a dashboard, and the second user may approve or reject each invitation message.

The second user may create places in an IoT management app, may add various IoT devices to the created places (e.g., place tabs), and may manage the IoT devices. In various embodiments, the invitee device **120** may differently display (e.g., color, text, or icon) an IoT environment (e.g., a place tab) shared with the host device **110** and an IoT environment (e.g., a place tab) created by the invitee device **120**.

FIG. **9** illustrates a DB table stored in an IoT server, according to various embodiments.

Referring to FIG. **9**, the IoT server **130** may receive sharing setting information from the host device **110**. The sharing setting information may include first user account information, place information (or group information of IoT devices), IoT device information, or information about the invitee device **120** (second user account information or a phone number). The IoT server **130** may create a DB table **901** based on the sharing setting information.

According to various embodiments, the DB table **901** may include a DB identifier **910**, a second user account **920**, a first user account **930**, token information **940**, authentication information **950**, authority information **960**, creation time **970**, update time **980**, and status information **990**.

The DB identifier **910** may be identification information uniquely created for each invitation message.

The second user account **920** may be information that a second user of the invitee device **120** receiving the invitation message uses to log in to an IoT management app. According to an embodiment, the second user account **920** may have null information in the case where the invitation message is transmitted based on the telephone number of the invitee device **120**.

The first user account **930** may be information that a first user of the host device **110** transmitting the invitation message uses to log in to the IoT management app.

The token information **940** may be identification information (e.g., a telephone number) used to identify the invitee device **120**. For example, the token information **940** may be a field used to invite the invitee device **120** to the telephone number.

The authentication information **950** may be information related to authentication of the first user or the second user.

The authority information **960** may represent a range in which the host device **110** or the invitee device **120** is capable of managing or controlling IoT devices. For example, when the authority information **960** is set to "1", this may mean authority to control all registered IoT devices. When the authority information **960** is set to "2", this may mean authority to control IoT devices located in a specified place, among the registered IoT devices. According to an embodiment, the authority information **960** may include authority to edit (e.g., remove, add, or collectively control) an IoT device group shared by the host device **110**.

The creation time **970** may be time when the DB table **901** was stored in the IoT server **130**. The update time **980** may be time when the DB table **901** was updated last.

The status information **990** may be information representing whether the DB table **901** is available or not.

According to various embodiments, when the invitee device **120** logs in using the second user account, the IoT server **130** may update the DB table **901**, based on the log-in information of the second user. The second user account **930**, the token information **940**, or the update time **980** may be modified in an updated DB table **902**. According to an embodiment, in the case where data is stored in the second user account **930** (in the case where the second user account **930** is not Null), the IoT server **130** may remove the



telephone number of the invitee device **120** from the token information **940** later (a Null status).

FIG. **9** is merely illustrative, and the present disclosure is not limited thereto. For example, in the case where the host device **110** transmits an invitation message by using a second user ID, the second user ID received from the host device **110** may be stored in the second user account **920**. In this case, the token information **940** may have null information.

According to various embodiments, the IoT server **130** may store a separate database related to an IoT environment of the host device **110**. For example, the IoT server **130** may store a database related to information about IoT devices registered in the host device **110**, group information (e.g., place information) to which each of the IoT devices belongs, and the like.

FIG. **10** is a signal flow diagram illustrating a process in which an invitee device makes a request to add a device, according to various embodiments.

Referring to FIG. **10**, in operation **1010**, the invitee device **120** may receive a user input for adding at least one IoT device to control the IoT device. For example, the invitee device **120** may search for a nearby device through short-range communication (e.g., Bluetooth or Wi-Fi) and perform an operation registering the discovered device. According to an embodiment, the invitee device **120** may already have the IoT management app installed in the invitee device **120** and be logged in to the IoT management app using a second user account. For example, in the case where an edit button (a button for adding or removing a device) is selected in one screen (e.g., home) of the IoT management app of the invitee device **120**, the invitee device **120** may initiate an operation of adding a nearby IoT device.

In operation **1020**, the invitee device **120** may transmit a device addition request to the IoT server **130** to register the discovered device. The device addition request may include identification information of the IoT device to be added and the second user account information.

In operation **1040**, the IoT server **130** may search a database for the identification information of the IoT device. According to an embodiment, in the case where the IoT server **130** receives the request for registering the IoT device, the IoT server **130** may determine whether the IoT device is registered to a different user account. For example, the IoT server **130** may allow one user to have top-level control authority over one IoT device. Accordingly, in the case where another user requests control authority over the same registered IoT device, the user obtains approval of the higher priority user registered in advance. In operation **1045**, the IoT server **130** may register the IoT device in the second user account in the case where the IoT device is not registered in a different user account. The IoT server **130** may update information (e.g., identification information, device type, or group information (e.g., place information) about the newly added IoT device to a database related to IoT devices registered in the invitee device **120**.

In operation **1046**, the IoT server **130** may notify the invitee device **120** of the registration result. The invitee device **120** may control the corresponding IoT device using the IoT management app. According to an embodiment, a function of controlling the corresponding IoT device may be enabled in the IoT management app of the invitee device **120**, or the invitee device **120** may download controllable data from the IoT server **130**.

In operation **1050**, the IoT server **130** may transmit a join request to the host device **110** in the case where the IoT device for which the invitee device **120** has requested

registration is registered in a different user account (e.g., in a first user account of the host device **110**). The join request may allow IoT environment information registered in the host device **110** to be shared with the invitee device **120** associated with the second user account.

In operation **1060**, the host device **110** may identify the join request. For example, the host device **110** may identify, through a pop-up or a push message, a request for the host device **110** to share IoT environment information related to the corresponding IoT device with the invitee device **120** in which the second user account is registered.

In operation **1070**, the host device **110** may determine whether approval of a first user is detected.

In operation **1075**, the host device **110** may create and transmit an invitation message using the second user account in the case where there is an approval of the first user. For example, the host device **110** may create the invitation message based on the second user account and may transmit the invitation message to the IoT server **1030**. In another example, the host device **110** may transmit, to the IoT server **130**, a response message indicating that the host device **110** has approved the sharing request, and the IoT server **130** may provide authority to the invitee device **120**, based on the response message.

According to various embodiments, the IoT server **130** may update the database related to the IoT devices registered in the host device **110** or the invitee device **120**, based on the invitation message or the response message of the host device **110**.

In operation **1080**, the host device **110** may transmit a rejection message to the IoT server **130** in the case where no approval of the first user is detected.

In operation **1085**, the IoT server **130** may transmit the rejection result to the invitee device **120**.

FIG. **11** is a signal flow diagram illustrating a process of sharing IoT environment information using a security code, according to various embodiments. FIG. **12** illustrates a UI showing a process of sharing IoT environment information using a security code, according to various embodiments.

Referring to FIGS. **11** and **12**, the host device **110** may transmit an invitation message to the invitee device **120** within a close distance by which short-range communication (e.g., BLE communication, NFC communication, or the like) is possible, by using short-range communication. The host device **110**, the IoT server **130**, and the invitee device **120** may perform an invitation operation based on the same security code (e.g., PIN code). The host device **110** may receive a security code (e.g., a PIN code) from the IoT server **130** and may share IoT environment information with the invitee device **120** by using the received security code. Although the following description will be focused on a case where a security code is PIN information, the present disclosure is not limited thereto.

In operation **1110**, the host device **110** may receive a user input for adding a second user (or the invitee device **120**) (Screen **1201**).

In operation **1120**, the host device **110** may request a PIN code from the IoT server **130**.

In operation **1130**, the IoT server **130** may create a PIN code. In an embodiment, the IoT server **130** may create a PIN code having a preset number of digits (e.g., eight digits) or a PIN code valid for a specified period of time (e.g., three minutes) to enhance security.

According to various embodiments, the IoT server **130** may create a PIN code based on sharing setting information received from the host device **110**. The sharing setting



information may include first user account information, place information (or group information of IoT devices), or IoT device information.

In operation 1140, the IoT server 130 may transmit the created PIN code to the host device 110 (Screen 1202).

In operation 1150, the host device 110 may share the received PIN code with the invitee device 120 (Screen 1211). For example, the host device 110 may transmit the PIN code to the invitee device 120 through short-range communication, such as Bluetooth Low Energy or "BLE". According to an embodiment, a first user may show the PIN code to the second user and may allow the second user to directly input the PIN code.

According to various embodiments, the host device 110 may add a separate dummy code to the received PIN code and may share the PIN code having the dummy code added thereto with the invitee device 120 through short-range communication, such as BLE.

In operation 1160, the invitee device 120 may log in to an IoT management app.

In operation 1170, the invitee device 120 may request an invitation message from the IoT server 130 by using the PIN code (Screen 1212).

In operation 1180, the IoT server 130 may request the host device 110 to confirm the invitation.

In operation 1190, the host device 110 may transmit the confirmation result to the IoT server 130.

According to various embodiments, operations 1180 and 1190 may be omitted. For example, in the case where the PIN code is valid, the IoT server 130 may transmit an invitation message without a separate confirmation process.

In operation 1195, the IoT server 130 may transmit an invitation message to the invitee device 120. The invitee device 120 may share IoT environment information with the host device 110. The invitee device 120 may control various IoT devices according to the IoT environment information (Screen 1213).

FIG. 13 illustrates a UI showing a process in which a host device and an invitee device share a security code, according to various embodiments.

Referring to FIG. 13, the host device 110 may receive a user input for adding a second user (or the invitee device 120) (Screen 1301). In the case where a first user selects a code creation button 1310, a security code 1320 may be created depending on a specified algorithm (Screen 1302). According to an embodiment, the security code 1320 may be valid for a predetermined period of time (e.g., about one minute), or may be valid a predetermined number of times (e.g., once).

The invitee device 120 may receive a user input to press a button 1330 for performing a join request through a code input (Screen 1311).

The invitee device 120 may output a user interface including a code input field 1340 (Screen 1312). The second user may enter, into the code input field 1340, a security code provided by the first user.

According to an embodiment, the invitee device 120 may request the IoT server 130 to check validity of the security code entered into the code input field 1340 by the invitee device 120. In the case where the input security code is valid, the IoT server 130 may transmit, to the host device 110, a message to request an approval input of the first user. The host device 110 may display a screen for the approval request received from the IoT server 130 (Screen 1303). In the case where the approval input of the first user occurs in

the host device 110, the host device 110 may share IoT environment information with invitee device 120 through the IoT server 130.

According to an embodiment, the host device 110 may check validity of the security code entered into the code input field 1340 of the invitee device 120, by using short-range communication (Screen 1303). For example, the host device 110 may receive, through BLE communication, the security code entered into the code input field 1340 of the invitee device 120. In the case where the received security code matches a security code stored in the host device 110 and the approval input of the first user occurs, the host device 110 may share IoT environment information with invitee device 120 through the IoT server 130.

The invitee device 120 may control various IoT devices, based on the IoT environment information received through the IoT server 130 (Screen 1313).

According to various embodiments, in the case where the host device 110 starts the process of sharing the IoT environment information with the invitee device 120 in the state in which a specified place (e.g., home) is selected, IoT environment information related to the corresponding place may be shared, and IoT environment information related to a different place (e.g., office) may not be shared. For example, the IoT server 130 may transmit, to the invitee device 120, information (e.g., a place, group information, or IoT device information) to be shared, based on information (e.g., a place, a group, or IoT device information) on the basis of which the host device 110 creates the security code.

FIG. 14 illustrates an invitation UI using a quick response or "QR" code, according to various embodiments.

Referring to FIG. 14, the host device 110 may output a member addition screen 1401 in the case where the host device 110 receives a user input related to addition of a member (e.g., an input for sharing, with a second user (or the invitee device 120), authority over IoT devices being managed).

The member addition screen 1401 may include various methods for adding a member. For example, the member addition screen 1401 may include a method of adding a member by inputting a second user account or a method of adding a member by creating a QR code.

According to an embodiment, in the case where a user selects a QR code creation button 1410, the host device 110 may output a QR code 1420 related to IoT environment information (Screen 1402). The invitee device 120 may share the IoT environment information by recognizing the QR code 1420 output by the host device 110. According to an embodiment, the QR code 1420 may be created by the host device 110, based on information of the host device 110 and an IoT device group (or location) to be shared. According to another embodiment, the host device 110 may receive, from the IoT server 130, a QR code created based on the information of the host device 110 and the IoT device group (or location) to be shared, and may output the QR code. The IoT server 130 may create a QR code based on sharing setting information received from the host device 110. The sharing setting information may include first user account information, place information (or group information of IoT devices), or IoT device information.

The invitee device 120 may output a UI capable of recognizing a QR code. For example, the invitee device 120 may recognize the QR code 1420 displayed on a display of the host device 110, by using a camera.

In the case where the invitee device 120 recognizes the QR code, information about the QR code may be automatically shared with the IoT server 130, and an invitation



message related to the corresponding QR code may be transmitted to the invitee device 120.

FIG. 15 illustrates a join UI using a QR code, according to various embodiments.

Referring to FIG. 15, the invitee device 120 may output a user interface 1501 for recognizing a QR code (e.g., the QR code 1420 of FIG. 14) that is output on a display of the host device 110. The invitee device 120 may output a recognition area 1510 for recognizing a QR code by using a camera module.

According to various embodiments, the invitee device 120 may automatically output the user interface 1501 according to a specified condition. For example, in the case where the invitee device 120 and the host device 110 are located in the same space (e.g., within a distance by which short-range communication is possible), the invitee device 120 may recognize the host device 110 through short-range communication and may automatically output the user interface 1501 including the recognition area 1510. A first user and a second user may simply and conveniently share IoT environment information by using a QR code.

According to various embodiments, the invitee device 120 may output the user interface 1501 for recognizing a QR code, based on the second user's selection.

FIG. 16 illustrates a UI for setting authority, according to various embodiments.

Referring to FIG. 16, the IoT server 130 may allow one user to have top-level control authority over one IoT device. Accordingly, in the case where another user wants to have control authority over a registered IoT device, the user may have to obtain an approval of a user registered in advance.

According to an embodiment, in the case where the IoT server 130 receives, from the invitee device 120, a registration request for an IoT device in which a first user (e.g., a user of the host device 110) is already registered, the IoT server 130 may send the first user a notification message (e.g., a push message) for requesting authority. For example, as shown on a screen 1601, the IoT server 130 may inform, through a notification message 1610, the host device 110 that the invitee device 120 requests (e.g., join request) authority over the IoT device registered in the host device 110. The request may be a request for allowing setting information related to the IoT device registered in the host device 110 to be shared with the invitee device 120 associated with a second user account.

In the case where a user selects the notification message 1610, the host device 110 may output a user interface for determining whether to share IoT environment information with the invitee device 120 as seen in screen 1602.

In the case where the user generates an input for approving the sharing, the host device 110 may transmit, to the IoT server 130, a response message that the host device 110 approves the sharing request, and the IoT server 130 may provide authority to the invitee device 120, based on the response message.

In the case where the user generates an input for rejecting the sharing, the host device 110 may transmit, to the IoT server 130, a response message that the host device 110 rejects the sharing request, and the IoT server 130 may inform the invitee device 120 that authority cannot be assigned to the invitee device 120, based on the response message.

FIG. 17 is a block diagram illustrating an electronic device according to an embodiment of the present disclosure.

Referring to FIG. 17, an electronic device 1701 may include, for example, a part or the entirety of the host device

110 illustrated in FIG. 1A. The electronic device 1701 may include at least one processor (e.g., AP) 1710, a communication module 1720, a subscriber identification module (SIM) 1729, a memory 1730, a sensor module 1740, an input device 1750, a display 1760, an interface 1770, an audio module 1780, a camera module 1791, a power management module 1795, a battery 1796, an indicator 1797, and a motor 1798.

The processor 1710 may run an operating system or an application program so as to control a plurality of hardware or software elements connected to the processor 1710, and may process various data and perform operations. The processor 1710 may be implemented with, for example, a system on chip (SoC). According to an embodiment of the present disclosure, the processor 1710 may further include a graphic processing unit (GPU) and/or an image signal processor. The processor 1710 may include at least a portion (e.g., a cellular module 1721) of the elements illustrated in FIG. 17. The processor 1710 may load, on a volatile memory, an instruction or data received from at least one of other elements (e.g., a nonvolatile memory) to process the instruction or data, and may store various data in a nonvolatile memory.

The communication module 1720 may have a configuration that is the same as or similar to that of the communication interface 170 of FIG. 1. The communication module 1720 may include, for example, a cellular module 1721, a Wi-Fi module 1722, a Bluetooth (BT) module 1723, a GNSS module 1724 (e.g., a GPS module, a GLONASS module, a BeiDou module, or a Galileo module), a NFC module 1725, MST module 1726 and a radio frequency (RF) module 1727.

The cellular module 1721 may provide, for example, a voice call service, a video call service, a text message service, or an Internet service through a communication network. The cellular module 1721 may identify and authenticate the electronic device 1701 in the communication network using the subscriber identification module 1729 (e.g., a SIM card). The cellular module 1721 may perform at least a part of functions that may be provided by the processor 1710. The cellular module 1721 may include a communication processor (CP).

Each of the Wi-Fi module 1722, the Bluetooth module 1723, the GNSS module 1724 and the NFC module 1725 may include, for example, a processor for processing data transmitted/received through the modules. According to some various embodiments of the present disclosure, at least a part (e.g., two or more) of the cellular module 1721, the Wi-Fi module 1722, the Bluetooth module 1723, the GNSS module 1724, and the NFC module 1725 may be included in a single integrated chip (IC) or IC package.

The RF module 1727 may transmit/receive, for example, communication signals (e.g., RF signals). The RF module 1727 may include, for example, a transceiver, a power amp module (PAM), a frequency filter, a low noise amplifier (LNA), an antenna, or the like. According to another embodiment of the present disclosure, at least one of the cellular module 1721, the Wi-Fi module 1722, the Bluetooth module 1723, the GNSS module 1724, or the NFC module 1725 may transmit/receive RF signals through a separate RF module.

The SIM 1729 may include, for example, an embedded SIM and/or a card containing the subscriber identity module, and may include unique identification information (e.g., an integrated circuit card identifier (ICCID)) or subscriber information (e.g., international mobile subscriber identity (IMSI)).



The memory **1730** may include, for example, an internal memory **1732** or an external memory **1734**. The internal memory **1732** may include at least one of a volatile memory (e.g., a dynamic RAM (DRAM), a static RAM (SRAM), a synchronous dynamic RAM (SDRAM), or the like), a nonvolatile memory (e.g., a one-time programmable ROM (OTPROM), a programmable ROM (PROM), an erasable and programmable ROM (EPROM), an electrically erasable and programmable ROM (EEPROM), a mask ROM, a flash ROM, a flash memory (e.g., a NAND flash memory, a NOR flash memory, or the like)), a hard drive, or a solid state drive (SSD).

The external memory **1734** may include a flash drive such as a compact flash (CF), a secure digital (SD), a Micro-SD, a Mini-SD, an extreme digital (xD), a MultiMediaCard (MMC), a memory stick, or the like. The external memory **1734** may be operatively and/or physically connected to the electronic device **1701** through various interfaces.

The sensor module **1740** may, for example, measure physical quantity or detect an operation state of the electronic device **1701** so as to convert measured or detected information into an electrical signal. The sensor module **1740** may include, for example, at least one of a gesture sensor **1740A**, a gyro sensor **1740B**, a barometric pressure sensor **1740C**, a magnetic sensor **1740D**, an acceleration sensor **1740E**, a grip sensor **1740F**, a proximity sensor **1740G**, a color sensor **1740H** (e.g., a red/green/blue (RGB) sensor), a biometric sensor **1740I**, a temperature/humidity sensor **1740J**, an illumination sensor **1740K**, or an ultraviolet (UV) sensor **1740M**. Additionally or alternatively, the sensor module **1740** may include, for example, an olfactory sensor (E-nose sensor), an electromyography (EMG) sensor, an electroencephalogram (EEG) sensor, an electrocardiogram (ECG) sensor, an infrared (IR) sensor, an iris recognition sensor, and/or a fingerprint sensor. The sensor module **1740** may further include a control circuit for controlling at least one sensor included therein. In some various embodiments of the present disclosure, the electronic device **1701** may further include a processor configured to control the sensor module **1740** as a part of the processor **1710** or separately, so that the sensor module **1740** is controlled while the processor **1710** is in a sleep state.

The input device **1750** may include, for example, a touch panel **1752**, a (digital) pen sensor **1754**, a key **1756**, or an ultrasonic input device **1758**. The touch panel **1752** may employ at least one of capacitive, resistive, infrared, and ultraviolet sensing methods. The touch panel **1752** may further include a control circuit. The touch panel **1752** may further include a tactile layer so as to provide a haptic feedback to a user.

The (digital) pen sensor **1754** may include, for example, a sheet for recognition which is a part of a touch panel or is separate. The key **1756** may include, for example, a physical button, an optical button, or a keypad. The ultrasonic input device **1758** may sense ultrasonic waves generated by an input tool through a microphone **1788** so as to identify data corresponding to the ultrasonic waves sensed.

The display **1760** may include a panel **1762**, a hologram device **1764**, or a projector **1766**. The panel **1762** may be, for example, flexible, transparent, or wearable. The panel **1762** and the touch panel **1752** may be integrated into a single module. The hologram device **1764** may display a stereoscopic image in a space using a light interference phenomenon. The projector **1766** may project light onto a screen so as to display an image. The screen may be disposed in the inside or the outside of the electronic device **1701**. According to an embodiment of the present disclosure, the display

**1760** may further include a control circuit for controlling the panel **1762**, the hologram device **1764**, or the projector **1766**.

The interface **1770** may include, for example, an HDMI **1772**, a USB **1774**, an optical interface **1776**, or a D-sub-miniature (D-sub) **1778**. Additionally or alternatively, the interface **1770** may include, for example, a mobile high-definition link (MHL) interface, an SD card/multi-media card (MMC) interface, or an infrared data association (IrDA) interface.

The audio module **1780** may convert, for example, a sound into an electrical signal or vice versa. The audio module **1780** may process sound information input or output through a speaker **1782**, a receiver **1784**, an earphone **1786**, or the microphone **1788**.

The camera module **1791** is, for example, a device for shooting a still image or a video. According to an embodiment of the present disclosure, the camera module **1791** may include at least one image sensor (e.g., a front sensor or a rear sensor), a lens, an image signal processor (ISP), or a flash (e.g., an LED or a xenon lamp).

The power management module **1795** may manage power of the electronic device **1701**. According to an embodiment of the present disclosure, the power management module **1795** may include a power management integrated circuit (PMIC), a charger integrated circuit (IC), or a battery or gauge. The PMIC may employ a wired and/or wireless charging method. The wireless charging method may include, for example, a magnetic resonance method, a magnetic induction method, an electromagnetic method, or the like. An additional circuit for wireless charging, such as a coil loop, a resonant circuit, a rectifier, or the like, may be further included. The battery gauge may measure, for example, a remaining capacity of the battery **1796** and a voltage, current or temperature thereof while the battery is charged. The battery **1796** may include, for example, a rechargeable battery and/or a solar battery.

The indicator **1797** may display a specific state of the electronic device **1701** or a part thereof (e.g., the processor **1710**), such as a booting state, a message state, a charging state, or the like. The motor **1798** may convert an electrical signal into a mechanical vibration, and may generate a vibration or haptic effect. Although not illustrated, a processing device (e.g., a GPU) for supporting a mobile TV may be included in the electronic device **1701**. The processing device for supporting a mobile TV may process media data according to the standards of digital multimedia broadcasting (DMB), digital video broadcasting (DVB), Media-FLO™, or the like.

Each of the elements described herein may be configured with one or more components, and the names of the elements may be changed according to the type of an electronic device. In various embodiments of the present disclosure, an electronic device may include at least one of the elements described herein, and some elements may be omitted or other additional elements may be added. Furthermore, some of the elements of the electronic device may be combined with each other so as to form one entity, so that the functions of the elements may be performed in the same manner as before the combination.

According to various embodiments, an electronic device includes a display, a wireless communication circuit, a processor, and a memory, wherein the memory stores an application program, and the application program includes a user interface configured to manage a plurality of Internet-of-Things (IoT) devices, wherein the memory stores instructions that cause the processor to establish wireless commu-



nication with one or more IoT devices by using the wireless communication circuit, output the user interface including the one or more IoT devices through the display, receive a user input for selecting a group from the one or more IoT devices, transmit first information including user account data to a first external server by using the wireless communication circuit, and transmit second information to another electronic device by using the wireless communication circuit, wherein the first information includes information about the group and the user account related to the electronic device, and wherein the second information is information that causes the other electronic device to communicate with the first external server to connect to and control one or more IoT devices included in the group.

According to various embodiments, the instructions cause the processor to transmit the second information by using account information or a telephone number that is associated with the other electronic device.

According to various embodiments, the first information further includes account information or a telephone number that is associated with the other electronic device.

According to various embodiments, the instructions cause the processor to transmit the second information through a short message service (SMS).

According to various embodiments, the instructions cause the processor to manage the plurality of IoT devices by dividing the plurality of IoT devices into a plurality of groups. The instructions cause the processor to divide the plurality of IoT devices into the plurality of groups, based on places where the plurality of IoT devices are located.

According to various embodiments, an electronic device includes a display, a wireless communication circuit, a processor, and a memory, wherein the memory stores instructions that cause the processor to receive a push message through a first application for managing one or more Internet-of-Things (IoT) devices from a first external server, or receive an SMS message related to the first application from a second external server, and when the first application is executed, receive, from the first external server, setting information for controlling the one or more IoT devices by another electronic device.

According to various embodiments, the instructions cause the processor to receive the setting information for controlling the one or more IoT devices included in a specified place.

According to various embodiments, the instructions cause the processor to determine whether the first application is installed, and install the first application through a URL included in the SMS message when it is determined that the first application is not installed.

According to various embodiments, the instructions cause the processor to transmit a user account applied to the first application to the first external server when the SMS message is received and the first application is executed.

According to various embodiments, the instructions cause the processor to control at least some of the one or more IoT devices, based on the setting information received from the first external server.

According to various embodiments, the one or more IoT devices are configured to be controllable by the other electronic device.

According to various embodiments, the instructions cause the processor to have management authority equal to or less than authority of the other electronic device over the one or more IoT devices.

According to various embodiments, the instructions cause the processor to request authentication of identification

information of the other electronic device from a third external server through the wireless communication circuit, and receive an authentication result from the third external server.

According to various embodiments, the identification information is a telephone number of the other electronic device.

According to various embodiments, a server device includes a memory, a communication circuit, and a processor, wherein the memory stores instructions that cause the processor to receive, from a first electronic device registered by first user account information, at least one of second user account information and identification information of a second electronic device, the first user account information, and setting information for controlling a plurality of Internet-of-Things (IoT) devices, create a database based on the second user account information or the identification information, receive, from the second electronic device, the second user account information or the identification information of the second electronic device, and transmit at least a portion of the setting information to the second electronic device when the information received from the second electronic device matches the information stored in the database.

According to various embodiments, an electronic device includes a display, a wireless communication circuit, a processor, and a memory, wherein the memory stores an application program, and the application program includes a user interface configured to manage a plurality of Internet-of-Things (IoT) devices, and wherein the memory stores instructions that cause the processor to establish wireless communication with one or more IoT devices by using the wireless communication circuit, output the user interface including the one or more IoT devices through the display, receive a user input for selecting a group from the one or more IoT devices, share a security code created in the electronic device or a first external server with another electronic device, and transmit first information including user account data to the first external server by using the wireless communication circuit.

According to various embodiments, the security code is a PIN code or a QR code.

According to various embodiments, the instructions cause the processor to share the security code with the other electronic device through short-range communication.

According to various embodiments, the instructions cause the processor to when the security code is created in the first external server, add a separate dummy code to the created security code and share the security code having the dummy code added thereto with the other electronic device.

According to various embodiments, an electronic device includes a display, a communication circuit, a memory, and a processor, wherein the processor establishes wireless communication with one or more Internet-of-Things (IoT) devices by using the communication circuit, transmits setting information of the one or more IoT devices to an external server by using the communication circuit, and transmits a request signal including first user account information and second user account information to the external server, wherein the request signal is a signal for transmitting at least a portion of the setting information to another device, wherein the first user account information is information about a first user registered in the electronic device, and wherein the second user account information is information about a second user registered in the other device.

According to various embodiments, an Internet-of-Things (IoT) device management method performed in an elec-



tronic device. The method includes establishing wireless communication with one or more IoT devices by using a communication circuit, outputting a user interface including the one or more IoT devices through a display, receiving a user input for selecting a group from the one or more IoT devices, transmitting first information including user account data to a first external server by using the communication circuit, wherein the first information includes information about the group and the user account related to the electronic device, and transmitting second information to another electronic device by using the communication circuit, wherein the second information includes information that causes the other electronic device to communicate with the first external server to connect to and control one or more IoT devices included in the group.

FIG. 18 is a block diagram illustrating a program module according to an embodiment of the present disclosure.

Referring to FIG. 18, a program module 1810 may include an operating system (OS) for controlling a resource related to an electronic device (e.g., the host device 110) and/or various applications (e.g., the application program 147) running on the OS. The operating system may be, for example, Android, iOS, Windows, Symbian, Tizen, or the like.

The program module 1810 may include a kernel 1820, a middleware 1830, an API 1860, and/or an application 1870. At least a part of the program module 1810 may be pre-loaded on an electronic device or may be downloaded from an external electronic device.

The kernel 1820 may include, for example, a system resource manager 1821 or a device driver 1823. The system resource manager 1821 may perform control, allocation, or retrieval of a system resource. According to an embodiment of the present disclosure, the system resource manager 1821 may include a process management unit, a memory management unit, a file system management unit, or the like. The device driver 1823 may include, for example, a display driver, a camera driver, a Bluetooth driver, a shared memory driver, a USB driver, a keypad driver, a Wi-Fi driver, an audio driver, or an inter-process communication (IPC) driver.

The middleware 1830, for example, may provide a function that the applications 1870 utilize in common, or may provide various functions to the applications 1870 through the API 1860 so that the applications 1870 may efficiently use limited system resources in the electronic device. According to an embodiment of the present disclosure, the middleware 1830 may include at least one of a runtime library 1835, an application manager 1841, a window manager 1842, a multimedia manager 1843, a resource manager 1844, a power manager 1845, a database manager 1846, a package manager 1847, a connectivity manager 1848, a notification manager 1849, a location manager 1850, a graphic manager 1851, and a security manager 1852.

The runtime library 1835 may include, for example, a library module that a compiler uses to add a new function through a programming language while the application 1870 is running. The runtime library 1835 may perform a function for input/output management, memory management, or an arithmetic function.

The application manager 1841 may manage, for example, a life cycle of at least one of the applications 1870. The window manager 1842 may manage a GUI resource used in a screen. The multimedia manager 1843 may recognize a format utilized for playing various media files and may encode or decode a media file using a codec matched to the format. The resource manager 1844 may manage a resource

such as a source code, a memory, or a storage space of at least one of the applications 1870.

The power manager 1845, for example, may operate together with a basic input/output system (BIOS) to manage a battery or power and may provide power information utilized for operating the electronic device. The database manager 1846 may generate, search, or utilize a database to be used in at least one of the applications 1870. The package manager 1847 may manage installation or update of an application distributed in a package file format.

The connectivity manager 1848 may manage wireless connection of Wi-Fi, Bluetooth, or the like. The notification manager 1849 may display or notify an event such as message arrival, appointments, and proximity alerts in such a manner as not to disturb a user. The location manager 1850 may manage location information of the electronic device. The graphic manager 1851 may manage a graphic effect to be provided to a user or a user interface related thereto. The security manager 1852 may provide various security functions utilized for system security or user authentication. According to an embodiment of the present disclosure, in the case in which an electronic device (e.g., the host device 110) includes a phone function, the middleware 1830 may further include a telephony manager for managing a voice or video call function of the electronic device.

The middleware 1830 may include a middleware module for forming a combination of various functions of the above-mentioned elements. The middleware 1830 may provide a module specialized for each type of an operating system to provide differentiated functions. Furthermore, the middleware 1830 may delete a part of existing elements or may add new elements dynamically.

The API 1860 which is, for example, a set of API programming functions may be provided in different configurations according to an operating system. For example, in the case of Android or iOS, one API set may be provided for each platform, and, in the case of Tizen, at least two API sets may be provided for each platform.

The application 1870, for example, may include at least one application capable of performing functions such as a home 1871, a dialer 1872, an SMS/MMS 1873, an instant message (IM) 1874, a browser 1875, a camera 1876, an alarm 1877, a contact 1878, a voice dial 1879, an e-mail 1880, a calendar 1881, a media player 1882, an album 1883, a clock 1884, health care (e.g., measure an exercise amount or blood sugar), or environmental information provision (e.g., provide air pressure, humidity, or temperature information).

According to an embodiment of the present disclosure, the application 1870 may include an information exchange application for supporting information exchange between the electronic device (e.g., the host device 110) and an external electronic device. The information exchange application may include, for example, a notification relay application for relaying specific information to the external electronic device or a device management application for managing the external electronic device.

For example, the notification relay application may have a function for relaying, to an external electronic device, notification information generated in another application (e.g., an SMS/MMS application, an e-mail application, a health care application, an environmental information application, or the like) of the electronic device. Furthermore, the notification relay application may receive notification information from the external electronic device and may provide the received notification information to the user.



The device management application, for example, may manage (e.g., install, delete, or update) at least one function (e.g., turn-on/turn off of the external electronic device itself (or some elements) or the brightness (or resolution) adjustment of a display) of the external electronic device communicating with the electronic device, an application running in the external electronic device, or a service (e.g., a call service, a message service, or the like) provided from the external electronic device.

According to an embodiment of the present disclosure, the application **1870** may include a specified application (e.g., a healthcare application of a mobile medical device) according to an attribute of the external electronic device. The application **1870** may include an application received from an external electronic device. The application **1870** may include a preloaded application or a third-party application downloadable from a server. The names of the elements of the program module **1810** illustrated may vary with the type of an operating system.

According to various embodiments of the present disclosure, at least a part of the program module **1810** may be implemented with software, firmware, hardware, or a combination thereof. At least a part of the program module **1810**, for example, may be implemented (e.g., executed) by a processor (e.g., the processor **1710**). At least a part of the program module **1810** may include, for example, a module, a program, a routine, sets of instructions, or a process for performing at least one function.

A computer-readable recording medium may include a hard disk, a floppy disk, a magnetic medium (e.g., a magnetic tape), an optical medium (e.g., CD-ROM, digital versatile disc (DVD)), a magneto-optical medium (e.g., a floptical disk), or a hardware device (e.g., a ROM, a RAM, a flash memory, or the like). The program instructions may include machine language codes generated by compilers and high-level language codes that can be executed by computers using interpreters. The above-mentioned hardware device may be configured to be operated as one or more software modules for performing operations of various embodiments of the present disclosure and vice versa.

A module or a program module according to various embodiments of the present disclosure may include at least one of the above-mentioned elements, or some elements may be omitted or other additional elements may be added. Operations performed by the module, the program module or other elements according to various embodiments of the present disclosure may be performed in a sequential, parallel, iterative or heuristic way. Furthermore, some operations may be performed in another order or may be omitted, or other operations may be added.

While the present disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the present disclosure as defined by the appended claims and their equivalents.

What is claimed is:

1. **[An]** A system comprising an electronic device and a first external server, the electronic device comprising:
  - a display;
  - a wireless communication circuit;
  - [a]** at least one processor; and
  - a memory that stores an application program for managing a plurality of Internet-of-Things (IoT) devices, the application program including instructions executable by the at least one processor to:

establish wireless communication with one or more IoT devices by using the wireless communication circuit; display a user interface for managing the one or more IoT devices through the display, wherein a first user interface includes a list for a first user input selecting IoT devices from among the one or more IoT devices to form a group, and wherein a second user interface includes a field into which account information associated with a user of another electronic device is entered, and an object for sending a Short Message Service (SMS) message;

when the account information is entered into the field and confirmed on the second user interface, transmit first information including user account data of the electronic device, group information indicating the selected IoT devices forming the group and the account information or a telephone number of the another electronic device to a first external server using the wireless communication **[circuits]** circuit; wherein the first external server **[transmits]** is configured to transmit a push message to the another electronic device causing the another electronic device to be communicatively connected with the first external server and control the selected IoT devices; and

when the object for sending the SMS message is selected in the second user interface, **[and]** transmit second information including URL information for downloading the application program to the another electronic device using the SMS message by the wireless communication circuit,

wherein the second information causes the another electronic device to communicatively connect with the first external server and control the selected IoT devices.

2. The **[electronic device]** system of claim 1, wherein the second information is transmitted using at least one of account information associated with the another electronic device and the telephone number of the another electronic device.

3. The **[electronic device]** system of claim 1, wherein the plurality of IoT devices are divided into a plurality of groups.

4. The **[electronic device]** system of claim 3, wherein **[the instructions are executable by the processor to divide]** the plurality of IoT devices are divided into the plurality of groups, based on locations where the plurality of IoT devices are located.

5. The **[electronic device]** system of claim 1, wherein the instructions are executable by the at least one processor to: share at least one of a security code generated in the electronic device and the first external server with another electronic device.

6. The **[electronic device]** system of claim 5, wherein the security code is a personal identification number (PIN) code or a quick response (QR) code.

7. The **[electronic device]** system of claim 5, wherein the instructions are executable by the at least one processor to: transmit the security code to the another electronic device using short-range communication.

8. The **[electronic device]** system of claim 5, wherein **[the instructions are executable by the processor to]** the at least one processor is configured to:

when the security code is generated in the first external server, control the electronic device to add a dummy code to the generated security code; and



transmit the generated security code to which the dummy code is added to the another electronic device.

9. The [electronic device] system of claim 1, wherein the instructions are executable by the *at least one* processor to: receive a request from the another electronic device to control the one or more IoT devices; and responsive to receiving an input confirming the request, transmitting the first information.

10. The [electronic device] system of claim 1, wherein the instructions are executable by the *at least one* processor to: after sending the SMS message, transmit third information including the user account data, the group information and the telephone number of the another electronic device to the first external server using the wireless communication circuit in the background.

11. An electronic device comprising:

a display;

a wireless communication circuit;

at least one processor; and

a memory that stores an application program for managing a plurality of Internet-of-Things (IoT) devices, the application program including instructions executable by the *at least one* processor, wherein the *at least one* processor is configured to control the electronic device to:

establish wireless communication with one or more IoT devices by using the wireless communication circuit;

display a user interface for managing the one or more IoT devices via the display, wherein a first user interface includes a list for a first user input for selecting IoT devices from among the one or more IoT devices to form a group, and wherein a second user interface includes a field into which account information associated with a user of another electronic device is to be entered, and an object for sending a Short Message Service (SMS) message;

when the account information is entered into the field and confirmed on the second user interface, control to transmit first information including user account data of the electronic device, group information indicating the selected IoT devices forming the group and the account information and/or a telephone number of the another electronic device to a first external server via the wireless communication circuit so that the first external server can transmit a push message to the another electronic device for causing the another electronic device to be communicatively connected with the first external server and control the selected IoT devices; and

when the object for sending the SMS message is selected in the second user interface, control to transmit second information including URL information for downloading the application program to

the another electronic device via SMS message by the wireless communication circuit and for causing the another electronic device to communicatively connect with the first external server and control the selected IoT devices.

12. The electronic device of claim 11, wherein the *at least one* processor is configured so that the second information is to be transmitted using at least one of account information associated with the another electronic device and the telephone number of the another electronic device.

13. The electronic device of claim 11, wherein the plurality of IoT devices are divided into a plurality of groups.

14. The electronic device of claim 13, wherein the plurality of IoT devices are divided into the plurality of groups, based on locations where the plurality of IoT devices are located.

15. The electronic device of claim 11, wherein the *at least one* processor is configured to control the electronic device to:

share at least one of a security code generated in the electronic device and the first external server with another electronic device.

16. The electronic device of claim 15, wherein the security code is a personal identification number (PIN) code or a quick response (QR) code.

17. The electronic device of claim 15, wherein the *at least one* processor is configured to control the electronic device to:

transmit the security code to the another electronic device via short-range communication.

18. The electronic device of claim 15, wherein the *at least one* processor is configured to:

when the security code is generated in the first external server, control the electronic device to add a dummy code to the generated security code; and transmit the generated security code to which the dummy code is added to the another electronic device.

19. The electronic device of claim 11, wherein the *at least one* processor is configured to control the electronic device to:

receive a request from the another electronic device to control the one or more IoT devices; and responsive to receiving an input confirming the request, control to transmit the first information.

20. The electronic device of claim 11, wherein the *at least one* processor is configured to control the electronic device to:

after sending the SMS message, control to transmit third information including the user account data, the group information and the telephone number of the another electronic device to the first external server using the wireless communication circuit in the background.

\* \* \* \* \*