



US00RE50077E

(19) **United States**  
(12) **Reissued Patent**  
**Zhang et al.**

(10) **Patent Number: US RE50,077 E**  
(45) **Date of Reissued Patent: Aug. 13, 2024**

(54) **GAS SOURCE SYSTEM FOR SUPPLYING GAS TO A TURBINE ENGINE BY FRACTURING MANIFOLD EQUIPMENT**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Yantai Jereh Petroleum Equipment & Technologies Co., Ltd., Yantai (CN)**

4,280,323 A 7/1981 Jersey  
6,079,198 A 6/2000 Prowse et al.

(Continued)

(72) Inventors: **Peng Zhang, Yantai (CN); Rikui Zhang, Yantai (CN); Xiaolei Ji, Yantai (CN); Mingchao Mao, Yantai (CN); Zhuqing Mao, Yantai (CN); Jihua Wang, Yantai (CN); Jianwei Wang, Yantai (CN)**

FOREIGN PATENT DOCUMENTS

CN 1310292 A 8/2001  
CN 203626662 U 6/2014

(Continued)

(73) Assignee: **Yantai Jereh Petroleum Equipment & Technologies Co., Ltd., Yantai (CN)**

OTHER PUBLICATIONS

(21) Appl. No.: **17/318,409**

International Search Report and Written Opinion mailed Aug. 15, 2022 for International Application No. PCT/CN2022/076182.

(22) Filed: **May 12, 2021**

(Continued)

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **10,830,032**  
Issued: **Nov. 10, 2020**  
Appl. No.: **16/874,827**  
Filed: **May 15, 2020**

*Primary Examiner* — Carlos N Lopez

(74) *Attorney, Agent, or Firm* — Crowell & Moring LLP

(30) **Foreign Application Priority Data**

Jan. 7, 2020 (CN) ..... 202010013728.3

(51) **Int. Cl.**

**E21B 43/26** (2006.01)  
**B01D 46/42** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **E21B 43/2607** (2020.05); **B01D 46/42** (2013.01); **F02C 7/055** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC .... **B01D 46/42**; **B01D 46/10**; **B01D 2279/60**;  
**B01D 46/0005**; **B01D 46/62**;


(Continued)

(57)

**ABSTRACT**

Disclosed is [an air] a gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment, including [an air] a gas supply device, an [air] gas delivery manifold, a filtering device, a gas detecting system and a connecting device, the [air] gas delivery manifold, the filtering device and the gas detecting system are integrated on the fracturing manifold equipment, the [air] gas supply device is connected to the [air] gas delivery manifold through the filtering device, and the [air] gas delivery manifold supplies [air] gas to the turbine engine through the connecting device. Beneficial effects: avoiding the hidden danger of the high pressure region, saving the floor space, avoiding the wiring of on-site delivery manifold, enhancing the connection efficiency, and reducing the difficulty of wellsite installation.

**4 Claims, 1 Drawing Sheet**



Amended

- (51) **Int. Cl.**  
*F02C 7/055* (2006.01)  
*B01D 46/00* (2022.01)  
*B01D 46/10* (2006.01)  
*B01D 46/52* (2006.01)  
*B01D 46/62* (2022.01)
- (52) **U.S. Cl.**  
 CPC ..... *B01D 46/0005* (2013.01); *B01D 46/0086*  
 (2013.01); *B01D 46/10* (2013.01); *B01D*  
*46/521* (2013.01); *B01D 46/62* (2022.01);  
*B01D 2279/60* (2013.01)

- (58) **Field of Classification Search**  
 CPC ..... *B01D 46/0086*; *B01D 46/521*; *E21B*  
*43/2607*; *E21B 43/26*; *F02C 7/055*; *F05D*  
*2260/607*  
 See application file for complete search history.

(56) **References Cited**  
 U.S. PATENT DOCUMENTS

10,020,711 B2 7/2018 Oehring  
 10,830,032 B1 11/2020 Zhang  
 10,961,908 B1 3/2021 Yeung  
 11,560,845 B2\* 1/2023 Yeung ..... F02C 6/00  
 2011/0118967 A1\* 5/2011 Tsuda ..... B60W 30/10  
 701/117  
 2011/0290483 A1 12/2011 Zornes  
 2012/0085079 A1 4/2012 Kaminsky  
 2014/0042199 A1\* 2/2014 Gregory, Jr. .... B60R 7/02  
 224/401  
 2015/0204239 A1 7/2015 Minto  
 2015/0205006 A1\* 7/2015 Maerten ..... G01V 99/005  
 703/2  
 2016/0032702 A1 2/2016 Gay  
 2017/0009666 A1 1/2017 Cano Wolff et al.

2017/0052070 A1\* 2/2017 Marsh ..... G01N 25/72  
 2017/0074074 A1 3/2017 Joseph et al.  
 2017/0145918 A1 5/2017 Oehring  
 2017/0203241 A1\* 7/2017 Subedi ..... B01D 46/442  
 2017/0321608 A1 11/2017 Crowley  
 2019/0211661 A1 7/2019 Reckels et al.  
 2019/0211814 A1 7/2019 Weightman et al.  
 2019/0323428 A1 10/2019 Oehring et al.  
 2021/0079758 A1 3/2021 Yeung et al.  
 2021/0198993 A1 7/2021 Christinzio  
 2021/0223801 A1 7/2021 Lawson  
 2021/0372256 A1 12/2021 Yeung


FOREIGN PATENT DOCUMENTS

CN 105334061 A 2/2016  
 CN 106285603 A 1/2017  
 CN 206205996 U 5/2017  
 CN 207111064 U 3/2018  
 CN 207503423 U 6/2018  
 CN 109906305 A 6/2019  
 CN 110469314 A 11/2019  
 CN 210422814 U 4/2020  
 CN 111089003 A 5/2020  
 CN 112664356 A 4/2021  
 CN 112879160 A 6/2021  
 CN 113982758 A 1/2022

OTHER PUBLICATIONS

International Search Report mailed Sep. 30, 2020, corresponding PCT/CN2020/070664.  
 Written Opinion mailed Sep. 30, 2020, corresponding PCT/CN2020/070664.  
 Non-final Office Action mailed Jun. 15, 2023 for U.S. Appl. No. 17/715,562.

\* cited by examiner



Amended

**GAS SOURCE SYSTEM FOR SUPPLYING  
GAS TO A TURBINE ENGINE BY  
FRACTURING MANIFOLD EQUIPMENT**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.**

*CROSS REFERENCE TO RELATED  
APPLICATION*

*This application is a Reissue of U.S. Pat. No. 10,830,032, issued Nov. 10, 2020, which claims priority to Chinese Application No. 2020100137283, filed Jan. 7, 2020, the entire contents of which is incorporated herein by reference.*

TECHNICAL FIELD

The present invention relates to the technical field of turbine fracturing, and particularly relates to [an air] a gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment.

BACKGROUND

For recent decades, hydraulic fracturing has been used to increase the production in oil or gas wells. In this process, a fracturing pump is used to pump the fluid into a wellbore under high pressure, then the fluid is squeezed into the formation, fracturing several hydraulic fractures. Water, other liquids as well as fracturing proppants are also injected into the fractures. After fracturing, the fracturing base fluid is returned to the ground, with the fracturing proppants remaining in the fractures to prevent fracture closure, through which a large amount of oil and gas enter the wellbore to be exploited.

In the working sites of fracturing in oil and gas fields all over the world, the [air] gas source supply for turbine fracturing is as follows:

The turbine fracturing trucks are arranged side by side, [air] gas pipelines are connected between the turbine fracturing trucks, [air] gas filters are disposed at the position of accessories of the turbine fracturing trucks, and the whole [air] gas piping is arranged around the vehicle set.

The problems are as follows:

1. **Unsafty:** The [air] gas filters are disposed at the rear of the turbine fracturing trucks, which is a high pressure region, with a risk of damaging the filters; moreover, the protection of most [air] gas filters is not safe enough, once the high-pressure pipeline leaks, the [air] gas supply will be disconnected, finally affecting the efficiency of the wellsite.

2. **Unreasonable arrangement:** The [air] gas pipeline for the whole vehicle set is in an annular form, if one of turbine fracturing trucks has to drive away, the piping for the whole vehicle set would be broken, with a risk of cutting off the [air] gas, thus affecting the efficiency of the wellsite.

3. **Incompact structure, labor and time-consuming of installation:** It is necessary to temporarily install [air] gas filters, [air] gas pipelines and other materials after the wellsite arrangement has been completed, increasing the difficulty of wellsite installation and affecting the operating efficiency.

SUMMARY

To overcome the deficiencies in the prior art, an objective of the present invention is to provide [an air] a gas source

system for supplying [air] gas to a turbine engine by fracturing manifold equipment, wherein the [air] gas delivery manifold and the filtering device are integrated on the manifold equipment at the fracturing site, avoiding the on-site wiring of the [air] gas delivery manifold in the prior art, saving the installation time, reducing the difficulty of wellsite installation, and enhancing the installation efficiency; the change in the location of the filtering device also eliminates the hidden danger of the high pressure region at the rear of the turbine fracturing truck in the prior art; the connecting device enables more flexible [air] gas supply, changing from [air] gas supply in series between turbine fracturing truck sets in the prior art to [air] gas supply in parallel, so that the movement of a single turbine fracturing truck does not affect the [air] gas supply of other turbine fracturing trucks, it is only necessary to shut off the valve and disconnect the fast interface; the guard is set to isolate the fracturing manifold from the [air] gas delivery manifold, increasing the safety.

The objective of the present invention is achieved by the following technical measures: [An air] A gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment, including [an air] A gas supply device, [an air] a gas delivery manifold, a filtering device, a gas detecting system and a connecting device, the [air] gas delivery manifold, the filtering device and the gas detecting system are integrated on the fracturing manifold equipment, the [air] gas supply device is connected to the [air] gas delivery manifold through the filtering device, and the [air] gas delivery manifold supplies [air] gas to the turbine engine through the connecting device.

Further, the [air] gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment includes a guard, the guard is integrated on the fracturing manifold equipment and is used to isolate the [air] gas delivery manifold from the fracturing manifold on the fracturing manifold equipment.

Further, the guard is an isolating board.

Further, the guard is made of steel.

Further, the gas detecting system is a laser gas detecting system.

Further, the gas detecting system is a pan-and-tilt laser gas detecting system.

Further, the pan-and-tilt laser gas detecting system includes multiple scanning laser gas telemeters, and the pan-and-tilt drives the scanning laser gas telemeters to detect multi-dimensional space on site in real time.

Further, the connecting device includes a connecting pipeline, a valve and a fast interface, the valve is used for the on-off of [air] gas supply of the connecting pipeline, and the fast interface is used for the fast connection between the connecting pipeline and the turbine engine.

Compared with the prior art, the present invention has the following beneficial effects: [An air] A gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment, wherein the [air] gas delivery manifold and the filtering device are integrated on the manifold equipment at the fracturing site, avoiding the on-site wiring of the [air] gas delivery manifold in the prior art, saving the installation time, reducing the difficulty of wellsite installation, and enhancing the installation efficiency; the change in the location of the filtering device also eliminates the hidden danger of the high pressure region at the rear of the turbine fracturing truck in the prior art; the connecting device enables more flexible [air] gas supply, changing from [air] gas supply in series between turbine fracturing truck sets in the prior art to [air] gas supply in parallel, so that the

movement of a single turbine fracturing truck does not affect the [air] gas supply of other turbine fracturing trucks, it is only necessary to shut off the valve and disconnect the fast interface; the guard is set to isolate the fracturing manifold from the [air] gas delivery manifold, increasing the safety.

The present invention will be described in detail below with reference to the accompanying drawings and specific implementations.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic structural diagram of [an air] a gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment according to an embodiment of the invention.

Wherein, 1. [air] gas supply device, 2. [air] gas delivery manifold, 3. filtering device, 4. gas detecting system, 5. guard, 6. connecting device, 7. fracturing manifold equipment.

#### DESCRIPTION OF THE EMBODIMENTS

As shown in FIG. 1, [an air] a gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment, including [an air] a gas supply device 1, [an air] a gas delivery manifold 2, a filtering device 3, a gas detecting system 4 and a connecting device 6, wherein the [air] gas delivery manifold 2, the filtering device 3 and the gas detecting system 4 are integrated on the fracturing manifold equipment 7, the [air] gas supply device 1 is connected to the [air] gas delivery manifold 2 through the filtering device 3, and the [air] gas delivery manifold 2 supplies [air] gas to the turbine engine through the connecting device 6. In the actual fracturing working site, the fracturing manifold equipment 7 is located near the wellhead for delivering the fracturing fluid in the fracturing equipment into the wellhead. The engine of the fracturing equipment is powered by a plunger pump, which pumps the fracturing fluid into the wellhead. In the actual site location, the fracturing equipment is also located around the fracturing manifold equipment 7. In this technical solution, the engine of the fracturing equipment is a turbine engine. The [air] gas delivery manifold 2 and the filtering device 3 are integrated on the manifold equipment at the fracturing site, avoiding the on-site wiring of the [air] gas delivery manifold 2 in the prior art, saving the installation time, reducing the difficulty of wellsite installation, enhancing the installation efficiency, and decreasing the floor space of the [air] gas delivery manifold 2 and the filtering device 3 in the prior art; the location of the filtering device 3 is changed from the high pressure region at the rear of the turbine fracturing truck in the prior art to the fixed location on the fracturing manifold equipment 7, also eliminating the hidden danger of the filtering device 3.

The [air] gas source system for supplying [air] gas to a turbine engine by fracturing manifold equipment includes a guard 5, the guard 5 is integrated on the fracturing manifold equipment 7 and is used to isolate the [air] gas delivery manifold 2 from the fracturing manifold on the fracturing manifold equipment 7. The guard 5 is set to isolate the fracturing manifold from the [air] gas delivery manifold 2, enabling the safety protection on the natural gas and high-pressure fracturing fluid, and enhancing the safety of the wellsite. The guard 5 is an isolating board.

The guard 5 is made of steel.

The gas detecting system 4 is a laser gas detecting system.

The gas detecting system 4 is a pan-and-tilt laser gas detecting system.

The pan-and-tilt laser gas detecting system includes multiple scanning laser gas telemeters, the intelligent pan-and-tilt drives the scanning laser gas telemeter to rotate 360° horizontally and 180° vertically, enabling the detection of multi-dimensional space on site in real time. The intelligent adjustment function of the pan-and-tilt laser gas detecting system can focus on the key detection areas, and the camera captures the scene pictures synchronously, achieving the basic positioning of missing areas. Meanwhile, the real-time detection data is transmitted to the background analysis system, realizing early detection, early warning and early handling of hidden dangers, greatly improving the safety protection level of the wellsite.

The connecting device 6 includes a connecting pipeline, a valve and a fast interface, the valve is used for the on-off of [air] gas supply of the connecting pipeline, and the fast interface is used for the fast connection between the connecting pipeline and the turbine engine. The connecting device 6 enables more flexible [air] gas supply, changing from [air] gas supply in series between turbine fracturing truck sets in the prior art to [air] gas supply in parallel, so that the movement of a single turbine fracturing truck does not affect the [air] gas supply of other turbine fracturing trucks, it is only necessary to shut off the valve and disconnect the fast interface.

It will be appreciated to persons skilled in the art that the present invention is not limited to the foregoing embodiments, which together with the context described in the specification are only used to illustrate the principle of the present invention. Various changes and improvements may be made to the present invention without departing from the spirit and scope of the present invention. All these changes and improvements shall fall within the protection scope of the present invention, which is defined by the appended claims and equivalents thereof.

What is claimed is:

1. [An air] A natural gas source system for supplying [air] natural gas to a turbine engine by fracturing manifold equipment, comprising [an air] a natural gas supply device, [an air] a natural gas delivery manifold, a filtering device, a gas detecting system and a connecting device, the [air] natural gas delivery manifold, the filtering device and the gas detecting system are integrated on the fracturing manifold equipment, the [air] natural gas supply device is connected to the [air] natural gas delivery manifold through the filtering device, and the [air] natural gas delivery manifold supplies [air] natural gas to the turbine engine through the connecting device wherein the [air] natural gas source system for supplying [air] natural gas to a turbine engine by fracturing manifold equipment comprises a guard, the guard is integrated on the fracturing manifold equipment and is used to isolate the [air] natural gas delivery manifold from the fracturing manifold on the fracturing manifold equipment; wherein the gas detecting system is a pan-and-tilt laser gas detecting system comprises multiple scanning laser gas telemeters, and the pan-and-tilt drives the scanning laser gas telemeters to detect multi-dimensional space on site in real time.

2. The [air] natural gas source system for supplying [air] natural gas to a turbine engine by fracturing manifold equipment according to claim 1, wherein the guard is an isolating board.

3. The [air] *natural gas* source system for supplying [air] *natural gas* to a turbine engine by fracturing manifold equipment according to claim 2, wherein the guard is made of steel.

4. The [air] *natural gas* source system for supplying [air] *natural gas* to a turbine engine by fracturing manifold equipment according to claim 1, wherein the connecting device comprises a connecting pipeline, a valve and a fast interface, the valve is used for the on-off of [air] *natural gas* supply of the connecting pipeline, and the fast interface is used for the fast connection between the connecting pipeline and the turbine engine.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : RE50,077 E  
APPLICATION NO. : 17/318409  
DATED : August 13, 2024  
INVENTOR(S) : Peng Zhang et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

In Line 3, item (57) after “device”, delete “an [air] *gas*” and replace with --[an air] *a gas*--.

In the Claims

In Column 4, Claim 1, Line 53, between “device” and “wherein”, insert --,--.

Signed and Sealed this  
Twenty-second Day of October, 2024



Katherine Kelly Vidal  
*Director of the United States Patent and Trademark Office*