

US00RE50176E

(19) **United States**
(12) **Reissued Patent**
McDevitt et al.

(10) **Patent Number:** **US RE50,176 E**
(45) **Date of Reissued Patent:** **Oct. 22, 2024**

(54) **HAND STIMULATION DEVICE TO FACILITATE THE INVOCATION OF A MEDITATIVE STATE**

(71) Applicant: **HYPERICE IP SUBCO, LLC**, Irvine, CA (US)

(72) Inventors: **Sarah McDevitt**, Kensington, CA (US);
Brian Bolze, San Francisco, CA (US)

(73) Assignee: **HYPERICE IP SUBCO, LLC**, Irvine, CA (US)

(21) Appl. No.: **17/490,822**

(22) Filed: **Sep. 30, 2021**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **10,758,451**
Issued: **Sep. 1, 2020**
Appl. No.: **15/590,885**
Filed: **May 9, 2017**

U.S. Applications:

(60) Provisional application No. 62/333,699, filed on May 9, 2016.

(51) **Int. Cl.**
A61H 23/00 (2006.01)
A61B 5/316 (2021.01)
A61B 5/349 (2021.01)

(52) **U.S. Cl.**
CPC **A61H 23/00** (2013.01); **A61B 5/316** (2021.01); **A61B 5/349** (2021.01); **A61H 2201/5043** (2013.01); **A61H 2201/5097** (2013.01); **A61H 2205/065** (2013.01); **A61H 2230/04** (2013.01)

(58) **Field of Classification Search**
CPC **A61H 23/00**; **A61H 2201/5043**; **A61H 2201/5097**; **A61H 2205/065**; **A61H 2230/04**; **A61B 5/316**; **A61B 5/349**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,297,981 A * 3/1994 Maxim **A63H 33/005**
446/437
5,575,761 A * 11/1996 Hajianpour **A61H 23/0263**
601/48
2007/0179414 A1 * 8/2007 Imboden **A61H 19/00**
601/72
2013/0062921 A1 * 3/2013 Meyer **B60N 2/976**
297/354.1
2013/0253388 A1 * 9/2013 Juto **A61H 9/0078**
601/48
2014/0163439 A1 * 6/2014 Uryash **A61B 17/22004**
601/47


(Continued)

Primary Examiner — Catherine S Williams
(74) *Attorney, Agent, or Firm* — Goodwin Procter LLP

(57) **ABSTRACT**

An apparatus has a bottom sphere and a top sphere connected to the bottom sphere to define an interior volume with a central plane. The top sphere includes a concave surface at an angle to the central plane. A motor is positioned within the interior volume. A processor is positioned within the interior volume and is connected to the motor. A memory is positioned within the interior volume and is connected to the processor. The memory stores instructions executed by the processor. The instructions include hand stimulation sessions. Each hand stimulation session comprises a sequence of cycles, where each cycle is a sequence of vibration intensity values applied to the motor.

33 Claims, 11 Drawing Sheets



References Cited

2015/0119770	A1 *	4/2015	Driscoll	A61H 23/02 601/48
2015/0328082	A1 *	11/2015	Jiang	A61H 19/00 600/38
2015/0351999	A1 *	12/2015	Brouse	A61H 23/0263 601/74
2016/0074278	A1 *	3/2016	Muench	A61H 23/02 601/46
2016/0199249	A1 *	7/2016	Dunham	A61H 19/44 601/15
2017/0106249	A1 *	4/2017	Marton	A63B 43/004
2017/0367923	A1 *	12/2017	Bergbacka	A01K 13/00
2018/0185237	A1 *	7/2018	Baetica	G08C 17/02
2019/0261313	A1 *	8/2019	Borras	A61H 23/0218

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

1

HAND STIMULATION DEVICE TO FACILITATE THE INVOCATION OF A MEDITATIVE STATE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED APPLICATION

Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 10,758,451. The reissue applications are U.S. patent application Ser. No. 17/490,822, filed on Sep. 30, 2021 (the present application); and U.S. patent application Ser. Nos. 17/494,975, 17/494,982, 17/494,984, and 17/494,989, each of which was filed on Oct. 6, 2021 and each of which is also a continuation of U.S. patent application Ser. No. 17/490,822.

[This] *The present application, in particular, is a reissue of U.S. Pat. No. 10,758,451, which issued on Sep. 1, 2020 and which claims priority to and the benefit of U.S. Provisional Patent Application [Ser.] No. 62/333,699, filed on May 9, 2016, the contents of all of which are incorporated herein by reference in their entirety.*

FIELD OF THE INVENTION

This invention relates generally to a hardware appliance operative with a mobile device executing an application. More particularly, the hardware appliance is in the form of a hand stimulation device to facilitate invocation of a meditative state.

BACKGROUND OF THE INVENTION

The salutary effects of meditation have been known for centuries. It would be desirable to leverage advances in technology to facilitate the invocation of a meditative state. More particularly, it would be desirable to provide a hardware appliance in the form of a hand stimulation device operative with a mobile device executing an application to facilitate the invocation of a meditative state.

SUMMARY OF THE INVENTION

An apparatus has a bottom sphere and a top sphere connected to the bottom sphere to define an interior volume with a central plane. The top sphere includes a concave surface at an angle to the central plane. A motor is positioned within the interior. A processor is positioned within the interior volume and is connected to the motor. A memory is positioned within the interior volume and is connected to the processor. The memory stores instructions executed by the processor. The instructions include hand stimulation sessions. Each hand stimulation session comprises a sequence of cycles, where each cycle is a sequence of vibration intensity values applied to the motor.

BRIEF DESCRIPTION OF THE FIGURES

The invention is more fully appreciated in connection with the following detailed description taken in conjunction with the accompanying drawings, in which:

2

FIG. 1 illustrates a system configured in accordance with an embodiment of the invention.

FIG. 2 illustrates electronic components associated with a hand stimulation device configured in accordance with an embodiment of the invention.

FIG. 3 is a perspective view of a housing for a hand stimulation device configured in accordance with an embodiment of the invention.

FIG. 4 is a front view of a top sphere of a hand stimulation device configured in accordance with an embodiment of the invention.

FIG. 5 illustrates a user engaging a hand stimulation device configured in accordance with an embodiment of the invention.

FIG. 6 illustrates a breathing session executed by the hand stimulation device in accordance with an embodiment of the invention.

FIG. 7 illustrates a soothing session executed by the hand stimulation device in accordance with an embodiment of the invention.

FIG. 8 illustrates a wandering thoughts session executed by the hand stimulation device in accordance with an embodiment of the invention.

FIG. 9 illustrates an interval bell session executed by the hand stimulation device in accordance with an embodiment of the invention.

FIG. 10 illustrates an instructor session executed by the hand stimulation device in accordance with an embodiment of the invention.

FIG. 11 illustrates a biofeedback session executed by the hand stimulation device in accordance with an embodiment of the invention.

FIG. 12 illustrates a fade session executed by the hand stimulation device in accordance with an embodiment of the invention.

Like reference numerals refer to corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a system **100** configured in accordance with an embodiment of the invention. The system includes a client device **102** connected to a server **104** via a network **106**, which may be any combination of wired and/or wireless networks. A hand stimulation device (HSD) **108** is also connected to the network **106**.

The client device **106** may be a computer, a table, a mobile device, a wearable device and the like. The client device **106** includes a central processing unit **110** and input/output devices **112** connected via a bus **114**. The input/output devices **112** may include a keyboard, mouse, touch display and the like. A network interface circuit **116** is also connected to the bus **114** to provide connectivity to network **106**. A memory **120** is also connected to the bus **114**. The memory **120** stores a hand stimulation device (HSD) application **122** with instructions executed by the central processing unit **110**. The HSD application **122** is operative to interact with the HSD **108** via network **106**, such as through a WiFi or Bluetooth® connection. The HSD application **122** is also operative to communicate with server **104**.

Server **104** includes a central processing unit **130**, input/output devices **132**, a bus **134** and a network interface circuit **136**. A memory **140** is connected to bus **134**. The memory stores instructions executed by the central processing unit **130**. In one embodiment, the memory **140** stores an HSD

session database **142**. The HSD session database **142** is a repository of hand stimulation sessions, where each hand stimulation session includes a sequence of cycles, where each cycle is a sequence of vibration intensity values applied to motor of the HSD **108**. As a result, the HSD **108** vibrates. As demonstrated below, a user holds the HSD **108**. The vibration intensity values are configured to invoke in the user a meditative state. Individual sessions of the HSD session database **142** are downloaded to client **102** and/or HSD **108** via network **106**. The memory **140** also stores a sensor signal processor **144**. The sensor signal processor **144** collects sensor signals from the hand stimulation device **108**. The sensor signal processor **144** evaluates the signals and selectively provides feedback to the HSD application **122** for consumption by a user of the HSD **108**. The memory **140** also stores an analytics module **146**. The analytics module **146** includes instructions executed by the central processing unit **130** to supply HSD analytic information, such as HSD session participation history, sensor signal analytics, recommended HSD sessions and the like. In one embodiment, the HSD analytic information is conveyed over network **106** to the HSD application **122**. An output device **112** (e.g., a display) of the client device **102** displays the HSD analytic information to a user. The HSD application **122** may also incorporate analytics that are generated and displayed locally.

FIG. **2** illustrates an HSD **108** configured in accordance with an embodiment of the invention. The HSD **108** includes a processor **200** in communication with a memory **202**. The memory **202** stores a set of hand stimulation sessions **204** (e.g., hand stimulation sessions **1** through **N**). Each hand stimulation session is executed by the processor **200**, which coordinates motor **210** to apply vibration intensity values to the HSD **108**. Each hand stimulation session is configured to guide a user into a meditative state, maintain the user in the meditative state and then guide the user out of the meditative state. Each session provides gentle, subtle rhythms and cues designed to guide and aid meditation.

The memory **202** also stores a sensor processor **206** to collect and process signals from sensors **220**. By way of example, the sensors **220** may include an electrocardiogram (ECG) sensor, a moisture sensor, a temperature sensor and the like. Such signals may be evaluated to access parameters associated with a meditative state. The sensors **220** may be in the form of electrodes, as discussed below.

The memory **202** also stores a communication module **208**. The communication module **208** coordinates communications between the client device **102** and/or server **104**. The communication module **208** accesses the wireless interface circuit **214** to coordinate such communications. For example, the wireless interface circuit **214** receives hand stimulation sessions from the network **106**, which originate at HSD session database **142** of server **104**. The wireless interface circuit **214** also transmits hand stimulation session utilization data, which may be conveyed to the HSD application **122** and/or the HSD session database **142**.

The HSD **108** may also include a battery charging circuit **216** and an associated battery **218**. The battery charging circuit **216** may be a physical connector, such as a USB port, or an inductive connection. The HSD **108** may also include an output device **222**. The output device **222** may be a display or a more basic form of output, such as a sequence of light emitting diodes (LEDs).

FIG. **3** is a perspective view of an HSD **108** configured in accordance with an embodiment of the invention. The HSD **108** has a bottom sphere **300**. The bottom sphere is shaped like a ball, such as a round ball or an oblong ball. The shape

of the sphere is selected to facilitate comfortable engagement with a hand of a user. The bottom sphere **300** may have a smooth surface, a dimpled surface or a textured surface. In one embodiment, the bottom sphere **300** is formed of wood (e.g., wood with stain and a light varnish finish). The bottom sphere **300** has a bottom surface that is flat so that the bottom surface may rest on a base **301**. The base **301** may include a power charging circuit for engagement with battery charging circuit **216**. In one embodiment, the flat surface has a diameter of approximately 40 mm.

The HSD **108** also has a top sphere **302**, which is connected to the bottom sphere **300**. The point of connection defines a central plane. The top sphere **302** and bottom sphere **300** define an interior volume in which components of FIG. **2** may be housed. In one embodiment, the HSD **108** has a diameter of between 80 and 110 mm, preferably approximately 95 mm.

The top sphere **302** includes a concave surface **304** at an angle (e.g., between 30 and 60 degrees, preferably around 45 degrees) to the central plane. The concave surface **304** hosts electrodes **306**. The electrodes **306** may be formed of stainless steel and protrude from the concave surface **304** by approximately 0.5 mm to 3 mm. As shown, the electrodes **306** are arranged in two concentric semi-circles on the left and right half of the concave surface **304**. This facilitates engagement of the right and left thumbs of a user. The top sphere **302** may have a smooth surface, a dimpled surface or a textured surface. In one embodiment, the top sphere **302** is formed of plastic with a matte finish.

FIG. **4** is a more detailed view of the top sphere **302**. The figure illustrates concave surface **304** and electrodes **306**. The figure also illustrates a set of LEDs **400** in the center of the concave surface **304**. The LEDs **400** are operative as an output device **222** to convey such information as, device on, session progress, and the like. In one embodiment, there are 9 white LEDs and 1 RGB LED. The LEDs may be used to communicate information, such as session progress, bio-feedback results and diagnostic information, such as charging, low battery, Bluetooth® pairing and the like.

FIG. **5** illustrates a hand **500** of a user engaging the HSD. More particularly, the figure illustrates the thumbs of a user engaging electrodes **306** of the concave surface **304**. In one embodiment, the electrodes **306** are stainless steel with a matte finish. The electrodes may be domed and protrude 1 mm or less from the concave surface **304**. The electrodes **306** may be circular, rectangular or any other polygonal shape. The electrodes **306** are positioned to accommodate people with different hand and finger sizes. Typically, a user's thumbs rest on two or more electrodes **306** in natural reach. Other fingers may be used to engage the electrodes **306**. The HSD may be configured without electrodes. In such a case, the vibration intensity values applied to the motor vibrate the entire HSD, but the user does not have the additional tactile sensation provided by the electrodes.

One or more of the electrodes **306** may be substituted with a sensor of the type earlier described. In one embodiment, the sensors measure electrocardiogram (ECG) signals from a user via contact with hands. The ECG data is used to analyze heart health, heart rate, heart rate variability, respiration rate and nervous system activity. In particular, the P, Q, R, S and T waves of ECG activity are analyzed. These metrics are used to determine personal heart rate variability baselines, stress and calm thresholds for stressed and calm states, and indicators related to additional health goals, such as fitness and risk of over-training, risk of fatigue, smoking cessation, weight loss, stress management, anxiety, mental health and the like.

The ECG data may be processed by the sensor processor **206** of HSD **108**, the HSD application **122** on client **102** and/or the sensor signal processor **144** on server **104**. The sensor data may be used to alter vibration intensity values or information conveyed by the output device **222**. The sensor signal processor **144** may evaluate sensor signals to derive new HSD sessions, which are loaded into HSD session DB **142**. Such sessions may also be downloaded to the HSD application **122**, which may convey it to the HSD **108** via a Bluetooth® connection. The sensor signal processor **144** may also generate data for consumption by the analytics module **146**. The HSD application **122** may query the analytics module **146** for various HSD analytical activity. For example, a user may obtain data about a single session, multiple sessions over time and suggested sessions. In one embodiment, the HSD application **122** is used to play an audio guided meditation track while the HSD **108** is used. The audio track may be obtained from the HSD session database **142**.

Attention now turns to different hand stimulation sessions that may be utilized in accordance with embodiments of the invention. As previously discussed, a hand stimulation session includes a sequence of cycles. Each cycle is a sequence of vibration intensity values applied to electrodes. The vibration intensity values may be characterized as a percentage of the maximum vibration intensity of motor **210**.

Hand stimulation sessions **204** may be obtained from HSD session database **142**. For example, in one embodiment, HSD application **122** of client **102** is used to communicate with server **104** via network **106**. More particularly, the HSD application **122** views and selects HSD sessions from the HSD session database **142**. The HSD application **122**, may then convey an HSD session to the HSD utilizing the wireless interface circuit **214** of the HSD **108**. In one embodiment, the HSD application **122** allows a session to be altered for user preference, instructor control and/or biofeedback.

One type of HSD session is referred to as a breathing cycle session. The breathing cycle session mimics a human breathing rhythm at a rate and pattern that is optimal for the body's homeostatic processes, efficiency of the heart and autonomic nervous system activities, and recovery. For most people, this optimal breathing rate is between 4.5 and 7 breaths per minute (BPM), with the average at 6 BPM. Forty percent of a respiration cycle is spent in inhale and 60% in exhale. The breathing cycle session is designed accordingly, so that the vibration is a breathing guide that aids the user to achieve optimal recovery during a session. The user inhales as the vibration intensity ramps up and exhales as it ramps down.

A one minute long session made up of 10-second Breathing Cycles (for the average optimal breathing rate of 6 BPM) is shown in FIG. 6. Each cycle includes rising vibration intensity values **600** followed by falling vibration intensity values **602** for a total cycle duration of approximately 10 seconds. In general, each cycle should be between six and twelve seconds.

FIG. 7 illustrates a soothing session with a soothing rhythm to relax and release tension as vibration intensity values fall. As shown in FIG. 7, each cycle includes consistent nominal vibration intensity values **700** followed by at least one rising vibration intensity value **702** followed by falling vibration intensity values **704** for a total cycle duration of approximately 10 seconds. In general, each cycle should be between six and twelve seconds.

FIG. 8 illustrates a wandering thoughts session. This session involves subtle constant input and periodic pulses at

intervals that would commonly be used by meditation instructors to help meditators become aware if their thoughts have wandered from the meditation's point of focus. That is, the periodic pulses nudge meditators to bring their thoughts and attention back into meditation. As shown in FIG. 8, each cycle includes consistent nominal vibration intensity values **800** followed by at least one rising vibration intensity value **802** followed by falling vibration intensity values **804**. The consistent nominal vibration intensity values **800** are at least three-quarters of each cycle. In the example of FIG. 8, the consistent nominal vibration intensity values **800** are over a minute and the rising vibration intensity value **802** followed by falling vibration intensity values **804** are approximately ten seconds or less.

FIG. 9 illustrates an interval bells session. Each cycle has at least one rising vibration intensity value **900** followed by falling vibration intensity values **902**, followed by absent vibration intensity values **904**. The at least one rising vibration intensity value **900** followed by falling vibration intensity values **902** are a quarter or less of each cycle. In the example of FIG. 9 they are approximately five seconds of a sixty second cycle or one-twelfth of a cycle.

FIG. 10 illustrates an instructor session. This session may be used with a live or recorded instructor to facilitate rhythmic counting, controlled breathing exercises and physical awareness exercises. Each cycle includes rising vibration intensity values **1000** followed by falling vibration intensity values **1002** followed by consistent nominal vibration **1004** intensity values. The rising vibration intensity values **1000** followed by the falling vibration intensity values **1002** have a combined duration approximately equal to duration of the consistent nominal vibration intensity values **1004**.

FIG. 11 illustrates a biofeedback session. A user's biofeedback is used to dynamically alter the sequence of cycles for a session. Biometric thresholds are set that represent stress and calm states, and different cycles are chosen for each state. Any cycle can be used for any given biometric state. The choice of cycle for each state is made either by pre-set defaults, analyzing previous sessions and other users' data to select cycle sequences that have been most effective for the specific user (or for users like her), user choice or instructor choice. The session of FIG. 11 uses the breathing cycle when a user is above a biometric stress threshold, in order to help calm down the user. Upon achieving a calm biometric threshold, the vibration fades into the soothing cycle. If the user returns to the stressed state, the breathing cycle starts again. That is, FIG. 11 illustrates a breathing session segment, followed by a soothing session segment. In the breathing session segment each cycle includes rising vibration intensity values followed by falling vibration intensity values, as shown in FIG. 6. In the soothing session segment each cycle includes consistent nominal vibration intensity values followed by at least one rising vibration intensity value followed by falling vibration intensity values, as shown in FIG. 7. The biofeedback session includes a sequence of breathing session segments **1100** followed by a sequence of soothing session segments **1102**. The sequence of soothing session segments **1102** are at least twice as long as the sequence of breathing session segments **1100**.

FIG. 12 illustrates a fade session. For any of the sessions described here, an optional fade is applied. This means that approximately 40% through a timed meditation, or after a set number of minutes, the vibration cycles slowly fade out, as the user is deep in her meditation flow. The cycles slowly fades back in at approximately 85% through the meditation or after a set number of minutes. This allows the user to

gently become aware of her physical surroundings and sensations as she ends a meditation session—a tangible version of instructor guidance towards the end of a session to become aware of physical feelings, sounds, and physical surroundings before opening one's eyes and completing a meditation.

FIG. 12 illustrates a ramp up session segment **1200** with a first sequence of cycles where each cycle in the first sequence of cycles has rising vibration intensity values followed by falling vibration intensity values that are greater than rising vibration intensity values and falling vibration intensity values of a previous cycle. A steady state session segment **1202** has substantially identical rising vibration intensity values followed by falling vibration intensity values. A ramp down session segment **1204** has a second sequence of cycles where each cycle in the second sequence of cycles has rising vibration intensity values followed by falling vibration intensity values that are greater than rising vibration intensity values and falling vibration intensity values of a subsequent cycle. A quiescent session segment **1206** omits vibration intensity values. The ramp up session segment **1200** is less than a quarter of the fade session duration, the steady state session segment **1202** is at least one half of the fade session duration, the ramp down session segment **1204** is less than a quarter of the fade session segment, and the quiescent session segment **1206** is less than a quarter of the fade session duration.

An embodiment of the present invention relates to a computer storage product with a computer readable storage medium having computer code thereon for performing various computer-implemented operations. The media and computer code may be those specially designed and constructed for the purposes of the present invention, or they may be of the kind well known and available to those having skill in the computer software arts. Examples of computer-readable media include, but are not limited to: magnetic media such as hard disks, floppy disks, and magnetic tape; optical media such as CD-ROMs, DVDs and holographic devices; magneto-optical media; and hardware devices that are specially configured to store and execute program code, such as application-specific integrated circuits (“ASICs”), programmable logic devices (“PLDs”) and ROM and RAM devices. Examples of computer code include machine code, such as produced by a compiler, and files containing higher-level code that are executed by a computer using an interpreter. For example, an embodiment of the invention may be implemented using JAVA®, C++, or other object-oriented programming language and development tools. Another embodiment of the invention may be implemented in hard-wired circuitry in place of, or in combination with, machine-executable software instructions.

The foregoing description, for purposes of explanation, used specific nomenclature to provide a thorough understanding of the invention. However, it will be apparent to one skilled in the art that specific details are not required in order to practice the invention. Thus, the foregoing descriptions of specific embodiments of the invention are presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed; obviously, many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, they thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use

contemplated. It is intended that the following claims and their equivalents define the scope of the invention.

The invention claimed is:

1. An apparatus, comprising:
 - a bottom sphere;
 - a top sphere connected to the bottom sphere to define an interior volume with a central plane, wherein the top sphere includes a concave surface at an angle to the central plane;
 - a motor positioned within the interior volume;
 - a processor positioned within the interior volume and connected to the motor; and
 - a memory positioned within the interior volume and connected to the processor, the memory storing instructions which are configured to be executed by the processor, wherein the instructions include hand stimulation sessions, each hand stimulation session comprising a sequence of cycles, wherein each cycle is a sequence of vibration intensity values applied to the motor and wherein the hand stimulation sessions include a biofeedback session comprising:
 - a breathing session segment wherein each cycle includes rising vibration intensity values followed by falling vibration intensity values for a total cycle duration of between six and twelve seconds;
 - a soothing session segment wherein each cycle includes consistent nominal vibration intensity values followed by at least one rising vibration intensity value followed by falling vibration intensity values for a total cycle duration of between six and twelve seconds;
 wherein the biofeedback session includes a sequence of breathing session segments followed by a sequence of soothing session segments, wherein the sequence of soothing session segments are at least twice as long as the sequence of breathing session segments.
2. The apparatus of claim 1 wherein the bottom sphere is formed of wood.
3. The apparatus of claim 1 wherein the top sphere is formed of plastic.
4. The apparatus of claim 1 wherein the concave surface hosts electrodes.
5. The apparatus of claim 1 further comprising sensors positioned on the concave surface.
6. The apparatus of claim 1 further comprising a wireless communication circuit positioned within the interior volume and connected to the processor.
7. The apparatus of claim 6 wherein the wireless communication circuit is configured to receive the hand stimulation sessions.
8. The apparatus of claim 6 wherein the wireless communication circuit is configured to transmit hand stimulation session utilization data.
9. The apparatus of claim 6 in combination with a mobile device configured for executing an application that coordinates operation of the apparatus.
10. The apparatus of claim 9 in combination with a server in network communication with the mobile device.
11. An apparatus, comprising:
 - a bottom sphere;
 - a top sphere connected to the bottom sphere to define an interior volume with a central plane, wherein the top sphere includes a concave surface at an angle to the central plane;
 - a motor positioned within the interior volume;
 - a processor positioned within the interior volume and connected to the motor; and

- a memory positioned within the interior volume and connected to the processor, the memory storing instructions configured to be executed by the processor, wherein the instructions include hand stimulation sessions, each hand stimulation session comprising a sequence of cycles, wherein each cycle is a sequence of vibration intensity values applied to the motor and wherein the hand stimulation sessions include a fade session comprising;
- a ramp up session segment with a first sequence of cycles wherein each cycle in the first sequence of cycles has rising vibration intensity values followed by falling vibration intensity values that are greater than rising vibration intensity values and falling vibration intensity values of a previous cycle;
- a steady state session segment wherein each cycle has substantially identical rising vibration intensity values followed by falling vibration intensity values;
- a ramp down session segment with a second sequence of cycles wherein each cycle in the second sequence of cycles has rising vibration intensity values followed by falling vibration intensity values that are greater than rising vibration intensity values and falling vibration intensity values of a subsequent cycle; and
- a quiescent session segment without vibration intensity values;
- wherein the ramp up session segment is less than a quarter of the fade session duration, the steady state session segment is at least one half of the fade session duration, the ramp down session segment is less than a quarter of the fade session segment, and the quiescent session segment is less than a quarter of the fade session duration.
12. The apparatus of claim 11 wherein the bottom sphere is formed of wood.
13. The apparatus of claim 11 wherein the top sphere is formed of plastic.
14. The apparatus of claim 11 wherein the concave surface hosts electrodes.
15. The apparatus of claim 11 further comprising sensors positioned on the concave surface.
16. The apparatus of claim 11 further comprising a wireless communication circuit positioned within the interior volume and connected to the processor.
17. The apparatus of claim 16 wherein the wireless communication circuit is configured to receive the hand stimulation sessions.
18. The apparatus of claim 16 wherein the wireless communication circuit is configured to transmit hand stimulation session utilization data.
19. The apparatus of claim 16 in combination with a mobile device is configured for executing an application that coordinates operation of the apparatus.
20. The apparatus of claim 19 in combination with a server in network communication with the mobile device.
21. *An apparatus, comprising:*
a housing sized and shaped to be held within a hand of a user, the housing defining an interior volume;
a motor positioned within the interior volume;

- a processor positioned within the interior volume and in communication with the motor; and*
a memory positioned within the interior volume and in communication with the processor, the memory storing instructions which are configured to be executed by the processor, wherein the instructions include hand stimulation sessions, each hand stimulation session comprising a sequence of cycles, wherein each cycle is a sequence of vibration intensity values applied to the motor and wherein the hand stimulation sessions include a biofeedback session comprising:
a breathing session segment wherein each cycle includes rising vibration intensity values followed by falling vibration intensity values for a total cycle duration of between six and twelve seconds;
a soothing session segment wherein each cycle includes consistent nominal vibration intensity values followed by at least one rising vibration intensity value followed by falling vibration intensity values for a total cycle duration of between six and twelve seconds;
wherein the biofeedback session includes a sequence of breathing session segments followed by a sequence of soothing session segments, wherein the sequence of soothing session segments are at least twice as long as the sequence of breathing session segments.
22. *The apparatus of claim 21, wherein a portion of the housing comprises wood.*
23. *The apparatus of claim 21, wherein a portion of the housing comprises plastic.*
24. *The apparatus of claim 21 further comprising a plurality of sensors coupled to an exterior surface of the housing.*
25. *The apparatus of claim 24, wherein the sensors comprise electrodes.*
26. *The apparatus of claim 24, wherein the sensors are selected from the group consisting of electrocardiogram sensors, moisture sensors, and temperature sensors.*
27. *The apparatus of claim 24, wherein the sensors protrude from the exterior surface of the housing by approximately 0.5 mm to 3 mm.*
28. *The apparatus of claim 24, wherein the sensors protrude from the exterior surface of the housing by 1 mm or less.*
29. *The apparatus of claim 21 further comprising an output device, in communication with the processor, for conveying information.*
30. *The apparatus of claim 29, wherein the output device comprises a plurality of light emitting diodes.*
31. *The apparatus of claim 21 further comprising a wireless interface circuit positioned within the interior volume and in communication with the processor.*
32. *The apparatus of claim 31, wherein the wireless interface circuit is configured to receive the hand stimulation sessions.*
33. *The apparatus of claim 31, wherein the wireless interface circuit is configured to transmit hand stimulation session utilization data.*